

## YRC1000 OPTIONS CC-Link COMMUNICATIONS FUNCTION INSTRUCTIONS

FOR SST-CCS-PCIE MADE BY Molex, Inc.

---

Upon receipt of the product and prior to initial operation, read these instructions thoroughly, and retain for future reference.

---

### MOTOMAN INSTRUCTIONS

MOTOMAN-□□□ INSTRUCTIONS

YRC1000 INSTRUCTIONS

YRC1000 OPERATOR'S MANUAL (GENERAL) (SUBJECT SPECIFIC)

YRC1000 MAINTENANCE MANUAL

YRC1000 ALARM CODES (MAJOR ALARMS) (MINOR ALARMS)

The YRC1000 operator's manual above corresponds to specific usage. Be sure to use the appropriate manual.

The YRC1000 operator's manual above consists of "GENERAL" and "SUBJECT SPECIFIC".

The YRC1000 alarm codes above consists of "MAJOR ALARMS" and "MINOR ALARMS".



## DANGER

- This manual explains the SST-CCS-PCIE board (manufactured by Molex Corporation) of the YRC1000 system. Read this manual carefully and be sure to understand its contents before handling the YRC1000. Any matter, including operation, usage, measures, and an item to use, not described in this manual must be regarded as "prohibited" or "improper".
- General information related to safety are described in "Chapter 1. Safety" of the YRC1000 INSTRUCTIONS. To ensure correct and safe operation, carefully read "Chapter 1. Safety" of the YRC1000 INSTRUCTIONS.



## CAUTION

- In some drawings in this manual, protective covers or shields are removed to show details. Make sure that all the covers or shields are installed in place before operating this product.
- YASKAWA is not responsible for incidents arising from unauthorized modification of its products. Unauthorized modification voids the product warranty.

## NOTICE

- YASKAWA may modify this model without notice when necessary due to product improvements, modifications, or changes in specifications.
- If such modification is made, the manual number will also be revised.
- If your copy of the manual is damaged or lost, contact a YASKAWA representative to order a new copy. The representatives are listed on the back cover. Be sure to tell the representative the manual number listed on the front cover.

## NOTES FOR SAFE OPERATION

Read this manual carefully before installation, operation, maintenance, or inspection of the YRC1000.

In this manual, the Notes for Safe Operation are classified as “DANGER”, “WARNING”, “CAUTION”, or “NOTICE”.



### DANGER

Indicates an imminently hazardous situation which, if not avoided, will result in death or serious injury. Safety Signs identified by the signal word DANGER should be used sparingly and only for those situations presenting the most serious hazards.



### WARNING

Indicates a potentially hazardous situation which, if not avoided, will result in death or serious injury. Hazards identified by the signal word WARNING present a lesser degree of risk of injury or death than those identified by the signal word DANGER.



### CAUTION

Indicates a hazardous situation, which if not avoided, could result in minor or moderate injury. It may also be used without the safety alert symbol as an alternative to “NOTICE”.

### NOTICE

NOTICE is the preferred signal word to address practices not related to personal injury. The safety alert symbol should not be used with this signal word. As an alternative to “NOTICE”, the word “CAUTION” without the safety alert symbol may be used to indicate a message not related to personal injury.

Even items described as “CAUTION” may result in a serious accident in some situations.

At any rate, be sure to follow these important items.



To ensure safe and efficient operation at all times, be sure to follow all instructions, even if not designated as “DANGER”, “WARNING” and “CAUTION”.

## NOTICE

- Do not use or keep the board in the following environmental conditions.
  - Where exposed to direct sunshine
  - Where vibration or impact occurs
  - Where high humidity exists
  - Where a strong magnetic field exists
  - Where much dust exists
  - Where a sudden change in the temperature occurs
  - Where corrosive gases occur
  - Where condensation occurs

Improper usage of the board may damage the board.



## DANGER

- Before operating the manipulator, make sure the servo power is turned OFF by performing the following operations. When the servo power is turned OFF, the SERVO ON LED on the programming pendant is turned OFF.
  - Press the emergency stop buttons on the front door of the YRC1000, on the programming pendant, on the external control device, etc.
  - Disconnect the safety plug of the safety fence. (when in the play mode and the remote mode)

If operation of the manipulator cannot be stopped in an emergency, personal injury and/or equipment damage may result.

*Fig. : Emergency Stop Button*



- Before releasing the emergency stop, make sure to remove the obstacle or error caused the emergency stop, if any, and then turn the servo power ON.

Failure to observe this instruction may result in personal injury caused by unintended manipulator movement.

*Fig. : Release of Emergency Stop*



- Observe the following precautions when performing a teaching operation within the P-point maximum envelope of the manipulator:
  - Be sure to perform lockout by putting a lockout device on the safety fence when going into the area enclosed by the safety fence. In addition, the operator of the teaching operation must display the sign that the operation is being performed so that no other person closes the safety fence.
  - View the manipulator from the front whenever possible.
  - Always follow the predetermined operating procedure.
  - Always keep in mind emergency response measures against the manipulator's unexpected movement toward a person.
  - Ensure a safe place to retreat in case of emergency.

Failure to observe this instruction may result in personal injury caused by improper or unintended manipulator movement.

- Confirm that no person is present in the P-point maximum envelope of the manipulator and that the operator is in a safe location before:
  - Turning ON the YRC1000 power
  - Moving the manipulator by using the programming pendant
  - Running the system in the check mode
  - Performing automatic operations

Injury may result if any person should enter the P-point maximum envelope of the manipulator during operation. Immediately press an emergency stop button whenever there is a problem. The emergency stop buttons are located on the front panel of the YRC1000 and on the right of the programming pendant.

- Read and understand the Explanation of the Warning Labels in the YRC1000 Instructions before operating the manipulator.



## WARNING

- Do not touch the inside of the panel for 5 minutes after the power is turned OFF.

The remaining charged voltage in the capacitor may cause an electric shock or an injury.

- Be sure to close the door and install the protection cover while the power is turned ON.

Failure to observe this warning may result in a fire or an electric shock.

- Perform the following inspection procedures prior to conducting manipulator teaching. If problems are found, repair them immediately, and be sure that all other necessary processing has been performed.
  - Check for problems in manipulator movement.
  - Check for damage to insulation and sheathing of external wires.
- Always return the programming pendant to the hook on the cabinet of the YRC1000 after use.

If the programming pendant is left unattended on the manipulator, on a fixture, or on the floor, the Enable Switch may be activated due to surface irregularities of where it is left, and the servo power may be turned ON. In addition, in case the operation of the manipulator starts, the manipulator or the tool may hit the programming pendant left unattended, which may result in personal injury and/or equipment damage.

- The wiring and mounting must be performed by authorized and qualified personnel.

Failure to observe this caution may result in fire or electric shock.



## CAUTION

- Make sure that there is no foreign matter such as metal chips on the board.

In case of malfunction, etc. it may result in an injury or damage the board.

- Make sure that there is no damage or deflection of parts on the board.

In case of malfunction, etc. it may result in an injury or damage the board.

- Correctly connect each cable and connector.

Failure to observe this caution may result in a fire or damage the board.

- Set the switches, etc. correctly.

Malfunction, caused by an incorrect setting, may result in an injury or damage the board.

- Never touch the soldered surfaces of the board directly with fingers.

Protrusions on the soldered surface may result in an injury.

## NOTICE

- Never touch the mounting surfaces of the board parts directly with fingers.

The generated static electricity may damage the IC.

- No shock to the board.

The shock may damage the board.

---

## Definition of Terms Used Often in This Manual

The MOTOMAN is the YASKAWA industrial robot product.

The MOTOMAN usually consists of the manipulator, the controller, the programming pendant, and supply cables.

In this manual, the equipment is designated as follows.

| Equipment  | Manual Designation  |
|--|---------------------|
| YRC1000 controller                               | YRC1000             |
| YRC1000 programming pendant                      | Programming pendant |
| Cable between the manipulator and the controller | Manipulator cable   |



Descriptions of the programming pendant keys, buttons, and displays are shown as follows:

| Equipment           |                             | Manual Designation  |
|---------------------|-----------------------------|---|
| Programming Pendant | Character Keys /Symbol Keys | The keys which have characters or its symbol printed on them are denoted with [ ].<br>ex. [ENTER]                       |
|                     | Axis Keys /Numeric Keys     | [Axis Key] and [Numeric Key] are generic names for the keys for axis operation and number input.                        |
|                     | Keys pressed simultaneously | When two keys are to be pressed simultaneously, the keys are shown with a "+" sign between them,<br>ex. [SHIFT]+[COORD] |
|                     | Displays                    | The menu displayed in the programming pendant is denoted with { }.<br>ex. {JOB}   |

## Description of the Operation Procedure

In the explanation of the operation procedure, the expression "Select •••" means that the cursor is moved to the object item and [SELECT] is pressed, or that the item is directly selected by touching the screen.

## Registered Trademark

In this manual, names of companies, corporations, or products are trademarks, registered trademarks, or brand names for each company or corporation. The indications of (R) and <sup>TM</sup> are omitted.

---

## Contents

---

|       |   |      |
|-------|---|------|
| 1     | Outline.....  | 1-1  |
| 1.1   | System Configuration.....   | 1-2  |
| 2     | Hardware Specifications .....   | 2-1  |
| 2.1   | External View of the CCS-PCIE Board .....   | 2-1  |
| 2.2   | CCS-PCIE Specifications.....  | 2-2  |
| 2.3   | Communication Specifications.....   | 2-4  |
| 3     | Mounting the CCS-PCIE Board.....  | 3-1  |
| 3.1   | Opening the Front Door of the YRC1000.....  | 3-3  |
| 3.2   | Mounting the CCS-PCIE Board on the YRC1000.....                                     | 3-4  |
| 3.3   | Cable Connection .....  | 3-5  |
| 3.4   | Closing Front Door of the YRC1000 .....   | 3-6  |
| 4     | I/O Signal Allocation.....  | 4-1  |
| 4.1   | Setting of Optional Board and I/O Module .....                                      | 4-1  |
| 4.2   | External I/O Setting.....   | 4-7  |
| 4.3   | Transmitting Data.....  | 4-12 |
| 4.3.1 | YRC1000 I/O Allocation Example (For Handling).....                                  | 4-13 |
| 4.3.2 | YRC1000 I/O Allocation Example (For Except Handling).....                           | 4-15 |
| 4.3.3 | Board Status .....  | 4-17 |
| 4.4   | Relationship with the Sending / Receiving Data of the CC-Link and the I/O Data..... | 4-23 |
| 4.4.1 | Data Classification .....   | 4-23 |
| 4.4.2 | User Area and System Area .....   | 4-24 |
| 4.4.3 | Details and Control of System Area.....   | 4-26 |
| 5     | Network Specifications.....   | 5-1  |
| 5.1   | CC-Link Terminal Units.....   | 5-1  |
| 5.2   | Number of Connected Stations of Each Terminal Unit .....                            | 5-2  |
| 5.3   | Construction and Specifications of Network System .....                             | 5-4  |
| 6     | Error Indication.....   | 6-1  |

## 1 Outline

This manual describes the CC-Link I/O board SST-CCS-PCIE (hereafter CCS-PCIE) (manufactured by Molex Corporation) to be used in the YRC1000. The application of the CCS-PCIE board enables the exchange of general-purpose I/O data and register data between a CC-link device and the YRC1000. The CCS-PCIE board is designed only as a remote device station and cannot be used as a master station.

The CCS-PCIE board conforms to CC-Link Remote Net Ver 1 mode and Remote Net Ver 2 mode.


# 1 Outline

## 1.1 System Configuration

### 1.1 System Configuration

The following diagram shows an example of the configuration of a system with an CCS-PCIE board.

**NOTE** In the master station network configuration, set the CCS-PCIE board as a remote device station.



**The CCS-PCIE board does not include a CC-Link dedicated cable or an external terminator.**


**NOTE**

When the CCS-PCIE board is connected at the end of the network, connect the external terminator to the CCS-PCIE board. If the terminator is not correctly connected, communications may not be performed. The value of resistance and the connection method differ depending on the cable type and the cable connection method. For details, refer to "Cable Wiring Manual" published by the CC-Link Partner Association.

CC-Link is a registered trademark of the CLPA (CC-Link Partner Association).

2 Hardware Specifications

2.1 External View of the CCS-PCIE Board



2 Hardware Specifications  
2.2 CCS-PCIE Specifications

## 2.2 CCS-PCIE Specifications

| Items                             | Specifications  |
|-----------------------------------|---|
| Interface to external device      | CC-Link   |
| Board mounting position           | PCI Express slot in the YRC1000   |
| Error indicator                   | LED indicators  |
| Number of transmission I/O points | <p>Maximum number of I/O points: Input: 880 output: 880 (4 CC-Link stations occupied/8-time setting)</p> <p>Number of I/O points</p> <p>Remote Net Ver 1 mode<br/>Input: 16 output: 16 (1 CC-Link station occupied/extended cyclic setting unavailable (1 time))<br/>Input: 112 output: 112 (4 CC-Link stations occupied/extended cyclic setting unavailable (1 time))</p> <p>Remote Net Ver 2 mode<br/>Input: 16 output: 16 (1 CC-Link station occupied/1-time setting)<br/>Input: 16 output: 16 (1 CC-Link station occupied/2-time setting)<br/>Input: 48 output: 48 (1 CC-Link station occupied/4-time setting)<br/>Input: 112 output: 112 (1 CC-Link station occupied/8-time setting)<br/>Input: 48 output: 48 (2 CC-Link stations occupied/1-time setting)<br/>Input: 80 output: 80 (2 CC-Link stations occupied/2-time setting)<br/>Input: 176 output: 176 (2 CC-Link stations occupied/4-time setting)<br/>Input: 368 output: 368 (2 CC-Link stations occupied/8-time setting)<br/>Input: 80 output: 80 (3 CC-Link stations occupied/1-time setting)<br/>Input: 144 output: 144 (3 CC-Link stations occupied/2-time setting)<br/>Input: 304 output: 304 (3 CC-Link stations occupied/4-time setting)<br/>Input: 624 output: 624 (3 CC-Link stations occupied/8-time setting)<br/>Input: 112 output: 112 (4 CC-Link stations occupied/1-time setting)<br/>Input: 208 output: 208 (4 CC-Link stations occupied/2-time setting)<br/>Input: 432 output: 432 (4 CC-Link stations occupied/4-time setting)<br/>Input: 880 output: 880 (4 CC-Link stations occupied/8-time setting)</p> |

## 2 Hardware Specifications

### 2.2 CCS-PCIE Specifications

| Items                             | Specifications  |
|-----------------------------------|---|
| Number of transmission I/O points | Number of I/O registers   |
|                                   | Remote Net Ver 1 mode   |
|                                   | Input: 4 output: 4 (1 CC-Link station occupied/extended cyclic setting unavailable (1 time))    |
|                                   | Input: 16 output: 16 (4 CC-Link stations occupied/extended cyclic setting unavailable (1 time)) |
|                                   | Remote Net Ver 2 mode   |
|                                   | Input: 4 output: 4 (1 CC-Link station occupied/1-time setting)                                  |
|                                   | Input: 8 output: 8 (1 CC-Link station occupied/2-time setting)                                  |
|                                   | Input: 16 output: 16 (1 CC-Link station occupied/4-time setting)                                |
|                                   | Input: 32 output: 32 (1 CC-Link station occupied/8-time setting)                                |
|                                   | Input: 8 output: 8 (2 CC-Link stations occupied/1-time setting)                                 |
|                                   | Input: 16 output: 16 (2 CC-Link stations occupied/2-time setting)                               |
|                                   | Input: 32 output: 32 (2 CC-Link stations occupied/4-time setting)                               |
|                                   | Input: 64 output: 64 (2 CC-Link stations occupied/8-time setting)                               |
|                                   | Input: 12 output: 12 (3 CC-Link stations occupied/1-time setting)                               |
|                                   | Input: 24 output: 24 (3 CC-Link stations occupied/2-time setting)                               |
|                                   | Input: 48 output: 48 (3 CC-Link stations occupied/4-time setting)                               |
|                                   | Input: 96 output: 96 (3 CC-Link stations occupied/8-time setting)                               |
|                                   | Input: 16 output: 16 (4 CC-Link stations occupied/1-time setting)                               |
|                                   | Input: 32 output: 32 (4 CC-Link stations occupied/2-time setting)                               |
|                                   | Input: 64 output: 64 (4 CC-Link stations occupied/4-time setting)                               |
|                                   | Input: 128 output: 128 (4 CC-Link stations occupied/8-time setting)                             |

- 
- 2 Hardware Specifications
  - 2.3 Communication Specifications
- 

## 2.3 Communication Specifications

| Items                       | Specifications  |
|-----------------------------|---|
| Transmission speed          | 10 Mbps / 5 Mbps / 2.5 Mbps / 625 kbps / 156 kbps   |
| Communication method        | Broadcast polling method  |
| Transmission channel        | Bus type  |
| Number of nodes             | Maximally 64 Slave station: 1 to 64   |
| Station type                | Local station   |
| Operation mode              | Ver 1, Ver 2  |
| Parameter mode              | Fixed to Remote Net mode  |
| Extended cyclic             | Remote Net Ver 1: Fixed to 1 time,<br>Remote Net Ver 2: 1 time, 2 times, 4 times, 8 times |
| Number of occupied stations | Remote Net Ver 1: 1 or 4 stations,<br>Remote Net Ver 2: 1 to 4 stations                   |



### 3 Mounting the CCS-PCIE Board



#### WARNING

- Before wiring, be sure to turn OFF the power supply and put up a warning sign, such as “DO NOT TURN ON THE POWER”.

Failure to observe this warning may result in an electric shock or an injury.

- Do not touch the inside of the panel for 5 minutes after the power is turned OFF.

The remaining charged voltage in the capacitor may cause an electric shock or an injury.

- Be sure to close the door and install the protection cover while the power is turned ON.

Failure to observe this warning may result in a fire or an electric shock.

- The wiring and mounting must be performed by authorized and qualified personnel.

Failure to observe this caution may result in a fire or an electric shock.



#### CAUTION

- Make sure that there is no foreign matter such as metal chips on the board.

In case of malfunction, etc. it may result in an injury or damage the board.

- Make sure that there is no damage or deflection of parts on the board.

In case of malfunction, etc. it may result in an injury or damage the board.

- Correctly connect each cable and connector.

Failure to observe this caution may result in a fire or damage the board.

- Set the switches, etc. correctly.

Malfunction, caused by an incorrect setting, may result in an injury or damage the board.

- Never touch the soldered surfaces of the board directly with fingers.

Protrusions on the soldered surface may result in an injury.

---

### 3 Mounting the CCS-PCIE Board

---

## NOTICE

- Never touch the mounting surfaces of the board parts directly with fingers.

The generated static electricity may damage the IC.

- No shock to the board.

The shock may damage the board.

### 3 Mounting the CCS-PCIE Board

#### 3.1 Opening the Front Door of the YRC1000


### 3.1 Opening the Front Door of the YRC1000

Mount the CCS-PCIE board in the following manner.

1. Open the front door of YRC1000.


- (1) Turn the door lock on the front face of the YRC1000 clockwise for 90 ° with a coin or a flat tip screwdriver.

*Fig. 3-1: Door Unlock*



- (2) With the door locks turned clockwise for 90 °, turn the main switch handle to the "OFF" position, and slowly open the door.

*Fig. 3-2: Open the Door "OFF" Position (Horizontal)*




- 3 Mounting the CCS-PCIE Board
- 3.2 Mounting the CCS-PCIE Board on the YRC1000

### 3.2 Mounting the CCS-PCIE Board on the YRC1000

1. Remove the riser card (JANCD-ABB02-E) from the CPU rack.
2. Insert the CCS-PCIE board into the PCI Express slot of the riser card, then securely tighten the CCS-PCIE board with the metal support.
3. Mount the riser card in the CPU rack.


*Fig. 3-3: (Mounting Example) When the CCS-PCIE Board is Inserted into Option: Slot1*



### 3.3 Cable Connection

1. Connect the CC-Link dedicated cable with the CCS-PCIE board connector.

*Fig. 3-4: (Mounting Example) When the CCS-PCIE Board is Inserted into Option: Slot1*




- 3 Mounting the CCS-PCIE Board
- 3.4 Closing Front Door of the YRC1000

### 3.4 Closing Front Door of the YRC1000

1. Close the front door of YRC1000.
  - (1) Close the door gently.
  - (2) Turn the door lock on the front face of the YRC1000 counterclockwise for 90 °.

Fig. 3-5: Lock the Door



## WARNING

Make sure to close the door and close all the door locks of the YRC1000 whenever it is used, except for maintenance.

Failure to observe this instruction may cause the ingress of dust, dirt, or water, which may result in electric shock and/or mechanical failure.

## 4 I/O Signal Allocation

### 4.1 Setting of Optional Board and I/O Module

In order to use the CCS-PCIE board on the YRC1000, perform the setting of the optional board and I/O module in the following manner.


Before setting the optional board and I/O module;

- Make sure that the power supply to the YRC1000 is OFF.
- Insert the CCS-PCIE board into the PCI Express slot on the YRC1000. For the board mounting, refer to *chapter 3 “Mounting the CCS-PCIE Board”*.




Set the optional board and I/O module in the management mode.  
 In the operation mode and the editing mode, the settings are for reference only.

1. Turn ON the power supply while pressing [MAIN MENU].
  - The main menu appears.



2. Set the security mode to the “MANAGEMENT MODE”.
3. Select {SYSTEM} under the main menu
  - The sub menu appears.



## 4 I/O Signal Allocation

### 4.1 Setting of Optional Board and I/O Module


#### 4. Select {SETUP}.

- The SETUP display appears.



#### 5. Select "OPTION BOARD".

- The OPTION BOARD display appears.





## 4 I/O Signal Allocation

### 4.1 Setting of Optional Board and I/O Module

#### 6. Select "CCS-PCIE".

- The CCS-PCIE setup display appears.
- Set the items on the display.



#### Explanation of Setup Items

##### ①CCS-PCIE

Selects whether to use the CCS-PCIE board.

##### ②I/O SIZE

Displays the size of input/output to send and receive data.

The displayed value is a result of automatic calculation and cannot be changed directly here.

##### ③MODE

Sets CC-Link operation mode.

Selects the mode among REMOTE NET VER 1 and REMOTE NET VER 2.

##### ④OCCUPIED STATIONS

Sets the number of the CC-Link occupied station.

Selects the station among 1 occupied station, 2 occupied stations, 3 occupied stations, and 4 occupied stations.

##### ⑤EXTENDED CYCLIC

Sets CC-Link extended cyclic settings.

When REMOTE NET VER 1 is selected: Fixed to 1 time and no changes can be made.

When REMOTE NET VER 2 is selected: Selects the setting among 1time, 2times, 4times, and 8times.

##### ⑥STATION NUMBER

Sets the CC-Link station number. The setting varies depending on the number of occupied stations.

When 1 station is occupied: 1 to 64

When 2 stations are occupied: 1 to 63

When 3 stations are occupied: 1 to 62

When 4 stations are occupied: 1 to 61

##### ⑦COMMUNICATION SPEED

Sets the CC-Link communication speed. Selects the speed among 156 k/625 k/2.5 M/5 M/10 M/bps.

##### ⑧REMOTE REGISTER

Sets whether to allocate the CC-Link remote register to the YRC1000 M-register.

## 4 I/O Signal Allocation

### 4.1 Setting of Optional Board and I/O Module

#### ⑨ REMOTE REGISTER (RWw) ALLOC. : IN

Sets the first numbers of the YRC1000 M-register when the CC-Link remote register (RWw) is allocated to the YRC1000 M-register. From M000 to M559 can be used. Set the first number of M register numbers. (RWw) is the data sent from the master station to the remote device station.

#### ⑩ REMOTE REGISTER (RWr) ALLOC. : OUT


Sets the first numbers of the YRC1000 M-register when the CC-Link remote register (RWr) is allocated to the YRC1000 M-register. From M000 to M999 can be used. Set the first number of M register numbers. (RWr) is the data sent from the remote device station to the master station.



Before allocating the CC-Link remote register to the M-register, make sure to use the M-register No. that is not used for other applications. If the M-register is duplicated, the remote register data may not be correctly transmitted between the master station and the remote device station.

#### 7. Press [ENTER].

- The confirmation dialog box appears.



## 4 I/O Signal Allocation

### 4.1 Setting of Optional Board and I/O Module

#### 8. Select {YES}.

- The IO MODULE display appears.

The message, "Select 'Safety Board FLASH Reset'." appears, however, do not perform 'Safety Board FLASH Reset' this time, but perform the settings continuously.



#### 9. Press [ENTER].

- The rest of the I/O module display appears, and "CCS-PCIE" is displayed.
- The I/O points is displayed under "DI/DO" according to the number of the occupied station that is set on the "OPTION BOARD" display.



The DI/DO points can be found using the I/O size on the set up display in the following equation:

$$\text{DI/DO points} = (\text{I/O size} \times 8) + 8$$

" + 8 " : the I/O points for status

---

## 4 I/O Signal Allocation

### 4.1 Setting of Optional Board and I/O Module

---

10. Press [ENTER].

- The confirmation dialog box appears.




11. Select {YES}.

- Select “YES” if the display corresponds to the current mounted status of the I/O modules. The I/O module setting is updated, and the IO MODULE window changes to the EXTERNAL IO SETUP window.

## 4.2 External I/O Setting

1. The EXTERNAL IO SETUP window appears.



2. Select {AUTO} or {MANUAL} in the ALLOCATION MODE.
  - The selection menu appears after selecting {AUTO} or {MANUAL}.




If the allocation mode is changed from {MANUAL} to {AUTO}, the set allocation data is discarded. The data will be allocated by AUTO MODE again. Save the set allocation data to the external devices in advance, if needed.

## 4 I/O Signal Allocation

### 4.2 External I/O Setting


3. Select the allocation mode to set up.

- Select {AUTO} to allocate I/O signal allocation automatically.  
Select {MANUAL} to allocate I/O signal allocation manually.
- The selected allocation mode is set up.



4. Select {DETAIL} of {EXTERNAL IO ALLOCATION}.

- When select {AUTO}, the following procedures No.5 to 7 are not necessary. Operate the procedure from No.8.
- When select {MANUAL}, operate the following procedures No.5 to 7 accordant with the setting manually.



## 4 I/O Signal Allocation

### 4.2 External I/O Setting


5. Select the external I/O signal number (at the change source) to be changed. (In the setting example, select “#20060”.)

– The select menu appears.



6. Select {MODIFY}, and input the external input signal number (at the change destination) to be changed. (In the setting example, enter “#20200”.)

– The external input signal number is changed.



7. Likewise, select/modify the number of the external input signal.


– Repeat select/modify until it becomes the desired allocation to set up.

## 4 I/O Signal Allocation

### 4.2 External I/O Setting

8. Press {ENTER}.

- The allocation window of the external output signal appears.



9. Select/modify the number of the external output signal same as the external input signal.

- Repeat select/modify until it becomes the desired allocation to set up.


10. Press {ENTER}.

- Confirmation dialog appears.



11. Select {YES}.

- The settings are confirmed, and returns to the SETUP window.






## 4 I/O Signal Allocation

### 4.2 External I/O Setting

12. Change the security mode to the safety mode.


13. Select [FILE]- [INITIALIZE].

- The INITIALIZE window appears.



14. Select "Safety Board FLASH Reset".

- The confirmation dialog box appears.



15. Select {YES}.


- The setting is completed after beep sound.

4.3 Transmitting Data

The data to be transmitted from the CCS-PCIE board to inside of the YRC1000 is not only the I/O data from the external device connected to the CC-Link, but also the status of the CCS-PCIE board.

Therefore, inside the YRC1000, 8 points (1 byte) for both input and output are reserved for the status of the CCS-PCIE board beside the area for the digital data. The output area, however, cannot be used.

The transmission data from the CCS-PCIE board are allocated to the external I/O signals of concurrent I/O and the M-registers.



Where only an CCS-PCIE (4 CC-Link stations occupied/1-time) is mounted as an optional I/O board, the concurrent I/O allocation of each board is shown in the following table.

Furthermore, the following table shows the remote register allocation of word data when the remote register allocation (RWw) is set to M000 and the remote register allocation (RWr) is set to M016.

## 4 I/O Signal Allocation

### 4.3 Transmitting Data

#### 4.3.1 YRC1000 I/O Allocation Example (For Handling)

Note1) The following example is for the standard setting. When change the allocation of the external output signal or the concurrent ladder program, the allocation changes in accordance with the changes.

Note2) As for the input data/output data of JANCD-AIO01-E (standard I/O board), refer to "YRC1000 INSTRUCTIONS (RE-CTO-A221)" for more details.

Note3) JANCD-AIO01-E (standard I/O board) is displayed as ASF01(base board of AIO01) in the IO module setup display.

|                                 |            |                        |                                   |                                  |
|---------------------------------|------------|------------------------|-----------------------------------|----------------------------------|
| JANCD-AIO01-E<br>(Standard I/O) | I/O Input  | External input signal  | User input signal                 | Details                          |
|                                 |            | 20010 to 20017         | None (allocated on the system)    | Input data (1)                   |
|                                 |            | 20020 to 20027         | None (allocated on the system)    | Input data (2)                   |
|                                 |            | 20030 to 20037         | 00010 to 00017 (IN0001 to IN0008) | Input data (3)                   |
|                                 |            | 20040 to 20047         | 00020 to 00027 (IN0009 to IN0016) | Input data (4)                   |
|                                 |            | 20050 to 20057         | None (allocated on the system)    | Input data (5)                   |
|                                 | I/O Output | EXternal output signal | User output signal                | Details                          |
|                                 |            | 30010 to 30017         | None (allocated on the system)    | Output data (1)                  |
|                                 |            | 30020 to 30027         | None (allocated on the system)    | Output data (2)                  |
|                                 |            | 30030 to 30037         | 10010 to 10017 (OT0001 to OT0008) | Output data (3)                  |
|                                 |            | 30040 to 30047         | 10020 to 10027 (OT0009 to OT0016) | Output data (4)                  |
|                                 |            | 30050 to 30057         | None (allocated on the system)    | Output data (5)                  |
| CCS-PCIE<br>(CC-Link)           | I/O Input  | External input signal  | User input signal                 | Details                          |
|                                 |            | 20060 to 20067         | 00030 to 00037 (IN0017 to IN0024) | Board status <sup>1)</sup>       |
|                                 |            | 20070 to 20077         | 00040 to 00047 (IN0025 to IN0032) | Input data (1)                   |
|                                 |            | 20080 to 20087         | 00050 to 00057 (IN0033 to IN0040) | Input data (2)                   |
|                                 |            | 20090 to 20097         | 00060 to 00067 (IN0041 to IN0048) | Input data (3)                   |
|                                 |            | 20100 to 20107         | 00070 to 00077 (IN0049 to IN0056) | Input data (4)                   |
|                                 |            | 20110 to 20117         | 00080 to 00087 (IN0057 to IN0064) | Input data (5)                   |
|                                 |            | 20120 to 20127         | 00090 to 00097 (IN0065 to IN0072) | Input data (6)                   |
|                                 |            | 20130 to 20137         | 00100 to 00107 (IN0073 to IN0080) | Input data (7)                   |
|                                 |            | 20140 to 20147         | 00110 to 00117 (IN0081 to IN0088) | Input data (8)                   |
|                                 |            | 20150 to 20157         | 00120 to 00127 (IN0089 to IN0096) | Input data (9)                   |
|                                 |            | 20160 to 20167         | 00130 to 00137 (IN0097 to IN0104) | Input data (10)                  |
|                                 |            | 20170 to 20177         | 00140 to 00147 (IN0105 to IN0112) | Input data (11)                  |
|                                 |            | 20180 to 20187         | 00150 to 00157 (IN0113 to IN0120) | Input data (12)                  |
|                                 |            | 20190 to 20197         | 00160 to 00167 (IN0121 to IN0128) | Input data (13)                  |
|                                 |            | 20200 to 20207         | 00170 to 00177 (IN0129 to IN0136) | Input data (14)                  |
|                                 | I/O Output | EXternal output signal | User output signal                | Details                          |
|                                 |            | 30060 to 30067         | 10030 to 10037 (OT0017 to OT0024) | System reservation <sup>1)</sup> |
|                                 |            | 30070 to 30077         | 10040 to 10047 (OT0025 to OT0032) | Output data (1)                  |
|                                 |            | 30080 to 30087         | 10050 to 10057 (OT0033 to OT0040) | Output data (2)                  |
|                                 |            | 30090 to 30097         | 10060 to 10067 (OT0041 to OT0048) | Output data (3)                  |
|                                 |            | 30100 to 30107         | 10070 to 10077 (OT0049 to OT0056) | Output data (4)                  |
|                                 |            | 30110 to 30117         | 10080 to 10087 (OT0057 to OT0064) | Output data (5)                  |
|                                 |            | 30120 to 30127         | 10090 to 10097 (OT0065 to OT0072) | Output data (6)                  |
|                                 |            | 30130 to 30137         | 10100 to 10107 (OT0073 to OT0080) | Output data (7)                  |
|                                 |            | 30140 to 30147         | 10110 to 10117 (OT0081 to OT0088) | Output data (8)                  |
|                                 |            | 30150 to 30157         | 10120 to 10127 (OT0089 to OT0096) | Output data (9)                  |

## 4 I/O Signal Allocation

### 4.3 Transmitting Data

|  |   |                 |                                   |                  |
|--|---|-----------------|-----------------------------------|------------------|
|  |   | 30160 to 30167  | 10130 to 10137 (OT0097 to OT0104) | Output data (10) |
|  |   | 30170 to 30177  | 10140 to 10147 (OT0105 to OT0112) | Output data (11) |
|  |   | 30180 to 30187  | 10150 to 10157 (OT0113 to OT0120) | Output data (12) |
|  |   | 30190 to 30197  | 10160 to 10167 (OT0121 to OT0128) | Output data (13) |
|  |   | 30200 to 30207  | 10170 to 10177 (OT0129 to OT0136) | Output data (14) |
|  | Remote<br>register<br>(RWr)<br>allocation | Register number | Details                           |                  |
|  |   | M000            | Input word data (1)               |                  |
|  |   | M001            | Input word data (2)               |                  |
|  |   | M002            | Input word data (3)               |                  |
|  |   | M003            | Input word data (4)               |                  |
|  |   | M004            | Input word data (5)               |                  |
|  |   | M005            | Input word data (6)               |                  |
|  |   | M006            | Input word data (7)               |                  |
|  |   | M007            | Input word data (8)               |                  |
|  |   | M008            | Input word data (9)               |                  |
|  |   | M009            | Input word data (10)              |                  |
|  |   | M010            | Input word data (11)              |                  |
|  |   | M011            | Input word data (12)              |                  |
|  |   | M012            | Input word data (13)              |                  |
|  |   | M013            | Input word data (14)              |                  |
|  |   | M014            | Input word data (15)              |                  |
|  |   | M015            | Input word data (16)              |                  |
|  | Remote<br>register<br>(RWr)<br>allocation | Register number | Details                           |                  |
|  |   | M016            | Output word data (1)              |                  |
|  |   | M017            | Output word data (2)              |                  |
|  |   | M018            | Output word data (3)              |                  |
|  |   | M019            | Output word data (4)              |                  |
|  |   | M020            | Output word data (5)              |                  |
|  |   | M021            | Output word data (6)              |                  |
|  |   | M022            | Output word data (7)              |                  |
|  |   | M023            | Output word data (8)              |                  |
|  |   | M024            | Output word data (9)              |                  |
|  |   | M025            | Output word data (10)             |                  |
|  |   | M026            | Output word data (11)             |                  |
|  |   | M027            | Output word data (12)             |                  |
|  |   | M028            | Output word data (13)             |                  |
|  |   | M029            | Output word data (14)             |                  |
|  |   | M030            | Output word data (15)             |                  |
|  |   | M031            | Output word data (16)             |                  |

- 1 Board status and system reservation cannot be allocated as IO signal.  
Also, this data is not able to transmit by CC-Link.  
(Unable to communicate with the main PLC.)

## 4 I/O Signal Allocation

### 4.3 Transmitting Data

#### 4.3.2 YRC1000 I/O Allocation Example (For Except Handling)

Note1) The following example is for the standard setting. When change the allocation of the external output signal or the concurrent ladder program, the allocation changes in accordance with the changes.

Note2) As for the input data/output data of JANCD-AIO01-E (standard I/O board), refer to "YRC1000 INSTRUCTIONS (RE-CTO-A221)" for more details.

Note3) JANCD-AIO01-E (standard I/O board) is displayed as ASF01(base board of AIO01) in the IO module setup display.

|                                 |            |                        |                                   |                                  |
|---------------------------------|------------|------------------------|-----------------------------------|----------------------------------|
| JANCD-AIO01-E<br>(Standard I/O) | I/O Input  | External input signal  | User input signal                 | Details                          |
|                                 |            | 20010 to 20017         | None (allocated on the system)    | Input data (1)                   |
|                                 |            | 20020 to 20027         | None (allocated on the system)    | Input data (2)                   |
|                                 |            | 20030 to 20037         | 00010 to 00017 (IN0001 to IN0008) | Input data (3)                   |
|                                 |            | 20040 to 20047         | 00020 to 00027 (IN0009 to IN0016) | Input data (4)                   |
|                                 |            | 20050 to 20057         | 00030 to 00037 (IN0017 to IN0024) | Input data (5)                   |
|                                 | I/O Output | EXternal output signal | User output signal                | Details                          |
|                                 |            | 30010 to 30017         | None (allocated on the system)    | Output data (1)                  |
|                                 |            | 30020 to 30027         | None (allocated on the system)    | Output data (2)                  |
|                                 |            | 30030 to 30037         | 10010 to 10017 (OT0001 to OT0008) | Output data (3)                  |
|                                 |            | 30040 to 30047         | 10020 to 10027 (OT0009 to OT0016) | Output data (4)                  |
|                                 |            | 30050 to 30057         | 10030 to 10037 (OT0017 to OT0024) | Output data (5)                  |
| CCS-PCIE<br>(CC-Link)           | I/O Input  | External input signal  | User input signal                 | Details                          |
|                                 |            | 20060 to 20067         | 00040 to 00047 (IN0025 to IN0032) | Board status <sup>1)</sup>       |
|                                 |            | 20070 to 20077         | 00050 to 00057 (IN0033 to IN0040) | Input data (1)                   |
|                                 |            | 20080 to 20087         | 00060 to 00067 (IN0041 to IN0048) | Input data (2)                   |
|                                 |            | 20090 to 20097         | 00070 to 00077 (IN0049 to IN0056) | Input data (3)                   |
|                                 |            | 20100 to 20107         | 00080 to 00087 (IN0057 to IN0064) | Input data (4)                   |
|                                 |            | 20110 to 20117         | 00090 to 00097 (IN0065 to IN0072) | Input data (5)                   |
|                                 |            | 20120 to 20127         | 00100 to 00107 (IN0073 to IN0080) | Input data (6)                   |
|                                 |            | 20130 to 20137         | 00110 to 00117 (IN0081 to IN0088) | Input data (7)                   |
|                                 |            | 20140 to 20147         | 00120 to 00127 (IN0089 to IN0096) | Input data (8)                   |
|                                 |            | 20150 to 20157         | 00130 to 00137 (IN0097 to IN0104) | Input data (9)                   |
|                                 |            | 20160 to 20167         | 00140 to 00147 (IN0105 to IN0112) | Input data (10)                  |
|                                 |            | 20170 to 20177         | 00150 to 00157 (IN0113 to IN0120) | Input data (11)                  |
|                                 |            | 20180 to 20187         | 00160 to 00167 (IN0121 to IN0128) | Input data (12)                  |
|                                 |            | 20190 to 20197         | 00170 to 00177 (IN0129 to IN0136) | Input data (13)                  |
|                                 |            | 20200 to 20207         | 00180 to 00187 (IN0137 to IN0144) | Input data (14)                  |
|                                 | I/O Output | EXternal output signal | User output signal                | Details                          |
|                                 |            | 30060 to 30067         | 10040 to 10047 (OT0025 to OT0032) | System reservation <sup>1)</sup> |
|                                 |            | 30070 to 30077         | 10050 to 10057 (OT0033 to OT0040) | Output data (1)                  |
|                                 |            | 30080 to 30087         | 10060 to 10067 (OT0041 to OT0048) | Output data (2)                  |
|                                 |            | 30090 to 30097         | 10070 to 10077 (OT0049 to OT0056) | Output data (3)                  |
|                                 |            | 30100 to 30107         | 10080 to 10087 (OT0057 to OT0064) | Output data (4)                  |
|                                 |            | 30110 to 30117         | 10090 to 10097 (OT0065 to OT0072) | Output data (5)                  |
|                                 |            | 30120 to 30127         | 10100 to 10107 (OT0073 to OT0080) | Output data (6)                  |
|                                 |            | 30130 to 30137         | 10110 to 10117 (OT0081 to OT0088) | Output data (7)                  |
|                                 |            | 30140 to 30147         | 10120 to 10127 (OT0089 to OT0096) | Output data (8)                  |
|                                 |            | 30150 to 30157         | 10130 to 10137 (OT0097 to OT0104) | Output data (9)                  |

## 4 I/O Signal Allocation

### 4.3 Transmitting Data

|  |   |                 |                                   |                  |
|--|---|-----------------|-----------------------------------|------------------|
|  |   | 30160 to 30167  | 10140 to 10147 (OT0105 to OT0112) | Output data (10) |
|  |   | 30170 to 30177  | 10150 to 10157 (OT0113 to OT0120) | Output data (11) |
|  |   | 30180 to 30187  | 10160 to 10167 (OT0121 to OT0128) | Output data (12) |
|  |   | 30190 to 30197  | 10170 to 10177 (OT0129 to OT0136) | Output data (13) |
|  |   | 30200 to 30207  | 10180 to 10187 (OT0137 to OT0144) | Output data (14) |
|  | Remote<br>register<br>(RWr)<br>allocation | Register number | Details                           |                  |
|  |   | M000            | Input word data (1)               |                  |
|  |   | M001            | Input word data (2)               |                  |
|  |   | M002            | Input word data (3)               |                  |
|  |   | M003            | Input word data (4)               |                  |
|  |   | M004            | Input word data (5)               |                  |
|  |   | M005            | Input word data (6)               |                  |
|  |   | M006            | Input word data (7)               |                  |
|  |   | M007            | Input word data (8)               |                  |
|  |   | M008            | Input word data (9)               |                  |
|  |   | M009            | Input word data (10)              |                  |
|  |   | M010            | Input word data (11)              |                  |
|  |   | M011            | Input word data (12)              |                  |
|  |   | M012            | Input word data (13)              |                  |
|  |   | M013            | Input word data (14)              |                  |
|  |   | M014            | Input word data (15)              |                  |
|  |   | M015            | Input word data (16)              |                  |
|  | Remote<br>register<br>(RWr)<br>allocation | Register number | Details                           |                  |
|  |   | M016            | Output word data (1)              |                  |
|  |   | M017            | Output word data (2)              |                  |
|  |   | M018            | Output word data (3)              |                  |
|  |   | M019            | Output word data (4)              |                  |
|  |   | M020            | Output word data (5)              |                  |
|  |   | M021            | Output word data (6)              |                  |
|  |   | M022            | Output word data (7)              |                  |
|  |   | M023            | Output word data (8)              |                  |
|  |   | M024            | Output word data (9)              |                  |
|  |   | M025            | Output word data (10)             |                  |
|  |   | M026            | Output word data (11)             |                  |
|  |   | M027            | Output word data (12)             |                  |
|  |   | M028            | Output word data (13)             |                  |
|  |   | M029            | Output word data (14)             |                  |
|  |   | M030            | Output word data (15)             |                  |
|  |   | M031            | Output word data (16)             |                  |

- <sup>1</sup> Board status and system reservation cannot be allocated as IO signal.  
Also, this data is not able to transmit by CC-Link.  
(Unable to communicate with the main PLC.)

## 4 I/O Signal Allocation

### 4.3 Transmitting Data

#### 4.3.3 Board Status

[CCS-PCIE board status]

The first one byte (20060 to 20067 in the allocation example above) of the input data of the CCS-PCIE allocated to the external input signal indicates the board status of the CCS-PCIE.

| Signal         | Contents   |
|----------------|--|
| 2xxx0 to 2xxx3 | Reserved for the manufacturer. The user cannot use these signals.                  |
| 2xxx4          | CPU error status of the master station sequencer      Normal: 0      Error: 1      |
| 2xxx5          | CC-Link communication setting value      Normal: 0      Error: 1                   |
| 2xxx6          | Indicates the CC-Link communication status.      Normal: 0      Error: 1           |
| 2xxx7          | Indicates the operation status of the CCS-PCIE board.      Normal: 0      Error: 1 |



In the case below, 2xxx6 CC-Link communication status is "Normal: 0".

To check whether these settings are correct, actually send and receive the IO signal.

- When the CPU operation of the master station is set to STOP.
- When other slave stations and the occupied station number is duplicated.
- When the number of occupied stations of the master station is more than the number of occupied stations of the slave station.
- When the extended cyclic settings of the master station are more than the cyclic settings of the slave station.

[The Alarm when Communications Error Occurs Using the Board Status]

When the optional board detects the communication error, by using the CIO ladder or the user alarm allows to occur the alarm.

The examples of the method are described in below.

There are two alarms of the occurrence alarms.

- IO Board operation error
- IO Communication error

As for the user alarm registration, refer to "Chap.13.7 I/O Messages and I/O Alarms" in "YRC1000 OPTIONS INSTRUCTIONS FOR Concurrent I/O(RE-CKI-A467<0>)" for more details.

---

## 4 I/O Signal Allocation

### 4.3 Transmitting Data

---

| <b>[Alarm No.]</b><br><b>Alarm name</b> | <b>Signal No.</b><br><b>(Board status signal)</b> | <b>Description of the alarm</b>                   |
|---|---|---|
| [9065]<br>IO BOARD OPERATION<br>ERROR   | 20067<br>(Board status signal:<br>2xxx7)          | The operation status of the<br>board is abnormal. |
| [9066]<br>IO COMMUNICATION<br>ERROR     | 20066<br>(Board status signal:<br>2xxx6)          | The communication status<br>is abnormal.          |

When the optional board detects and alerts the error by the board status signal, the ladder program, which raises an alarm, is created according to the error signal.

The procedures to register the alarms above as the user alarm and the ladder program, which alert an alarm, are described below.




## 4 I/O Signal Allocation


### 4.3 Transmitting Data

#### ■ Register the User Alarm


1. Change the security mode to the "Management Mode".
2. Select the {I/O ALARM} from the {IN/OUT} in the main menu.



3. I/O alarm (user) window appears.




4. Move the cursor over the desired No. to register, and press [SELECT].
  - The window changes to the character string entry window.



## 4 I/O Signal Allocation


### 4.3 Transmitting Data

5. Enter the I/O alarm name.




6. Press [ENTER].

– The entered alarm is registered.



7. Register the other alarms.

– Repeat the same procedures to register the alarm to use.



---

## 4 I/O Signal Allocation

### 4.3 Transmitting Data

---

#### ■ IO Allocation and the Ladder Program

Create the ladder program to alert the alarm by using the following signals when the optional board detects an error.

External input

| Signal | Description  |
|--------|--|
| 20066  | Optional board status<br>(IO communication status) |
| 20067  | Optional board status<br>(Board operation status)  |

System input signal

| Signal | Description                 |
|--------|-----------------------------|
| 40012  | User part alarm requirement |
| 40220  | User part alarm code d0     |
| 40221  | User part alarm code d1     |
| 40222  | User part alarm code d2     |
| 40223  | User part alarm code d3     |
| 40224  | User part alarm code d4     |
| 40225  | User part alarm code d5     |

Assistant relay


| Signal | Description   |
|--------|---|
| 70017  | Turned ON the control power supply<br>(continuously ON) |

## 4 I/O Signal Allocation

### 4.3 Transmitting Data

The ladder program (the figure of the ladder)

Creating the following ladder allows to alert the alarm according to the status error signals of the optional board.



## 4 I/O Signal Allocation

## 4.4 Relationship with the Sending / Receiving Data of the CC-Link and the I/O Data

## 4.4 Relationship with the Sending / Receiving Data of the CC-Link and the I/O Data

## 4.4.1 Data Classification

For sending and receiving data with the CC-Link, 4 types of data exist: Remote input (RX), remote output (RY), remote register (RW<sub>r</sub>) and remote register (RW<sub>w</sub>).

- Remote input (RX), remote output (RY)  
Bit data sent and received in communication with the master station. When looking from the master station, input data is indicated as RX, and output data is indicated as RY. Exchange the data with each YRC1000 external output signal (#3xxxx) and YRC1000 external input signal (#2xxxx).
- Remote register (RW<sub>r</sub>), remote register (RW<sub>w</sub>)  
Word data sent and received in communication with the master station. When looking from the master station, input data is indicated as RW<sub>r</sub>, and output data is indicated as RW<sub>w</sub>. Exchange the data with YRC1000 M register.




Fig. 4-1: Correlation Between Sending and Receiving Data

|     |  |
|-----|--|
| 4   | I/O Signal Allocation  |
| 4.4 | Relationship with the Sending / Receiving Data of the CC-Link and the I/O Data |

#### 4.4.2 User Area and System Area

The number of I/O points indicated in *chapter 2.2 “CCS-PCIE Specifications”* of this instruction manual indicates only points of the user area which the customer can use in sending and receiving the bit data. In the actual sending and receiving of bit data, the 16 points of the system area other than the user area which is indicated in the CCS-PCIE specifications are included.

The relationship between the remote I/O points and the number of occupied stations in Remote Net Ver.1 is shown below.

As the same also applies to Remote Net Ver.2, the actual sent and received bit data include the 16 points of the system area other than the user area which the customer is available to use.


|                                 | Remote input (RX)                            | Remote output (RY)                           |
|---------------------------------|--|--|
| One CC-Link station occupied    | User area 16 points + system area 16 points  | User area 16 points + system area 16 points  |
| Two CC-Link stations occupied   | User area 48 points + system area 16 points  | User area 48 points + system area 16 points  |
| Three CC-Link stations occupied | User area 80 points + system area 16 points  | User area 80 points + system area 16 points  |
| Four CC-Link stations occupied  | User area 112 points + system area 16 points | User area 112 points + system area 16 points |

4

I/O Signal Allocation

4.4

Relationship with the Sending / Receiving Data of the CC-Link and the I/O Data



- 
- 4 I/O Signal Allocation
- 4.4 Relationship with the Sending / Receiving Data of the CC-Link and the I/O Data
- 

#### 4.4.3 Details and Control of System Area

The CC-Link system area is defined below.  
(For details, refer to CC-Link specifications published by CC-Link Partner Association.)

YRC1000 turns ON the remote Ready bit of the remote input (RX) area when start-up is complete. The system area of other remote inputs (RX) are always OFF. The system area of the remote output (RY) is not subject to monitoring from the YRC1000, so the signal of this area does not affect the operation of the YRC1000.

| Link input (RX) | Signal name                          | Link output (RY) | Signal name                             |
|-----------------|--------------------------------------|------------------|---|
| RX (n) 0        | Reserved                             | RY (n) 0         | Reserved                                |
| RX (n) 1        |                                      | RY (n) 1         |   |
| RX (n) 2        |                                      | RY (n) 2         |   |
| RX (n) 3        |                                      | RY (n) 3         |   |
| RX (n) 4        |                                      | RY (n) 4         |   |
| RX (n) 5        |                                      | RY (n) 5         |   |
| RX (n) 6        |                                      | RY (n) 6         |   |
| RX (n) 7        |                                      | RY (n) 7         |   |
| RX (n) 8        | Initial data processing request flag | RY (n) 8         | Initial data processing completion flag |
| RX (n) 9        | Initial data setting completion flag | RY (n) 9         | Initial data settings request flag      |
| RX (n) A        | Error status flag                    | RY (n) A         | Error reset request flag                |
| RX (n) B        | Remote Ready                         | RY (n) B         | Reserved                                |
| RX (n) C        | Message transmission                 | RY (n) C         | Message transmission request flag       |
| RX (n) D        | Message handshake flag               | RY (n) D         | Message handshake flag                  |
| RX (n) E        | Reserved                             | RY (n) E         | Reserved                                |
| RX (n) F        | Reserved                             | RY (n) F         | Reserved                                |

n: Last registered number of the number of occupied points



## 5 Network Specifications

### 5.1 CC-Link Terminal Units

CC-Link terminal units are assigned to the following CC-Link stations.

**Station:** A device that is connected via the CC-Link to which any of station numbers 0 to 64 can be assigned. The following station types are available.

**Master station**

A station that has the control information (parameters) and controls the entire network. One master station is required in each network.

The station number is fixed to 0.

**Slave station**

A generic station name for all stations excluding the master station.

**Local station**

A station that can perform n:n cyclic transmission and transient transmission with the master station and other local stations.

**Standby master station**

A station that replaces the master station to continue the data link in case the master station function stops. A standby master station has the same functions as the master station, and functions as a local station in a normal condition.

**Intelligent device station**

A station that can perform 1:n cyclic transmission and transient transmission with the master station.

**Remote station**

A generic station name for remote I/O stations and remote device stations.

**Remote device station**

A station that can use bit data and word data.

**Remote I/O station**

A station that can only use bit data.



The CCS-PCIE board is assigned to a remote device station.

- 5 Network Specifications  
 5.2 Number of Connected Stations of Each Terminal Unit

## 5.2 Number of Connected Stations of Each Terminal Unit

One master station can connect with 64 stations in total, including remote I/O stations, remote device stations, local stations, standby master stations and intelligent device stations, under the following conditions.

(1) In Remote Net Ver 1 mode

|             |   |  |
|-------------|---|--|
| Condition 1 | $\{ (1 \times a) + (2 \times b) + (3 \times c) + (4 \times d) \} \leq 64$ | a: Number of units occupied by 1 station<br>b: Number of units occupied by 2 stations<br>c: Number of units occupied by 3 stations<br>d: Number of units occupied by 4 stations                |
| Condition 2 | $\{ (16 \times A) + (54 \times B) + (88 \times C) \} \leq 2034$           | A: Number of remote I/O stations $\leq 64$<br>B: Number of remote device stations $\leq 42$<br>C: Number of local stations, standby master stations, and intelligent device stations $\leq 26$ |

## 5 Network Specifications

## 5.2 Number of Connected Stations of Each Terminal Unit

(2) In Remote Net Ver 2 mode, Remote Net Additional mode

|             |   |  |
|-------------|---|--|
| Condition 1 | $\{ (a + a2 + a4 + a8) + (b + b2 + b4 + b8) \times 2 + (c + c2 + c4 + c8) \times 3 + (d + d2 + d4 + d8) \times 4 \} \leq 64$  | <p>a: The total number of Ver 1-compatible slave stations (occupied by 1 station) and Ver 2-compatible slave stations (occupied by 1 station/1-time setting)</p> <p>b: The total number of Ver 1-compatible slave stations (occupied by 2 stations) and Ver 2-compatible slave stations (occupied by 1 station/1-time setting)</p> <p>c: The total number of Ver 1-compatible slave stations (occupied by 3 stations) and Ver 2-compatible slave stations (occupied by 1 station/1-time setting)</p> <p>d: The total number of Ver 1-compatible slave stations (occupied by 4 stations) and Ver 2-compatible slave stations (occupied by 1 station/1-time setting)</p>   |
| Condition 2 | $[ \{ (a \times 32) + (a2 \times 32) + (a4 \times 32) + (a8 \times 128) \} + \{ (b \times 64) + (b2 \times 96) + (b4 \times 192) + (b8 \times 384) \} + \{ (c \times 96) + (c2 \times 160) + (c4 \times 320) + (c8 \times 640) \} + \{ (d \times 128) + (d2 \times 224) + (d4 \times 448) + (d8 \times 896) \} ] \leq 8192$ | <p>a2: The number of Ver 2-compatible slave stations (occupied by 1 station/2-time setting)</p> <p>b2: The number of Ver 2-compatible slave stations (occupied by 2 stations/2-time setting)</p> <p>c2: The number of Ver 2-compatible slave stations (occupied by 3 stations/2-time setting)</p> <p>d2: The number of Ver 2-compatible slave stations (occupied by 4 stations/2-time setting)</p> <p>a4: The number of Ver 2-compatible slave stations (occupied by 1 station/4-time setting)</p> <p>b4: The number of Ver 2-compatible slave stations (occupied by 2 stations/4-time setting)</p> <p>c4: The number of Ver 2-compatible slave stations (occupied by 3 stations/4-time setting)</p> <p>d4: The number of Ver 2-compatible slave stations (occupied by 4 station/s4-time setting)</p> <p>a8: The number of Ver 2-compatible slave stations (occupied by 1 station/8-time setting)</p> <p>b8: The number of Ver 2-compatible slave stations (occupied by 2 stations/8-time setting)</p> <p>c8: The number of Ver 2-compatible slave stations (occupied by 3 stations/8-time setting)</p> <p>d8: The number of Ver 2-compatible slave stations (occupied by 4 stations/8-time setting)</p> |
| Condition 3 | $[ \{ (a \times 4) + (a2 \times 8) + (a4 \times 16) + (a8 \times 32) \} + \{ (b \times 8) + (b2 \times 16) + (b4 \times 32) + (b8 \times 64) \} + \{ (c \times 12) + (c2 \times 24) + (c4 \times 48) + (c8 \times 96) \} + \{ (d \times 16) + (d2 \times 32) + (d4 \times 64) + (d8 \times 128) \} ] \leq 2048$             | <p>a4: The number of Ver 2-compatible slave stations (occupied by 1 station/4-time setting)</p> <p>b4: The number of Ver 2-compatible slave stations (occupied by 2 stations/4-time setting)</p> <p>c4: The number of Ver 2-compatible slave stations (occupied by 3 stations/4-time setting)</p> <p>d4: The number of Ver 2-compatible slave stations (occupied by 4 station/s4-time setting)</p> <p>a8: The number of Ver 2-compatible slave stations (occupied by 1 station/8-time setting)</p> <p>b8: The number of Ver 2-compatible slave stations (occupied by 2 stations/8-time setting)</p> <p>c8: The number of Ver 2-compatible slave stations (occupied by 3 stations/8-time setting)</p> <p>d8: The number of Ver 2-compatible slave stations (occupied by 4 stations/8-time setting)</p>  |
| Condition 4 | $\{ (16 \times A) + (54 \times B) + (88 \times C) \} \leq 2304$   | <p>A: Number of remote I/O stations <math>\leq 64</math></p> <p>B: Number of remote device stations <math>\leq 42</math></p> <p>C: Number of local stations, standby master stations, and intelligent device stations <math>\leq 26</math></p>   |

---

|     |   |
|-----|---|
| 5   | Network Specifications                            |
| 5.3 | Construction and Specifications of Network System |


---

### **5.3 Construction and Specifications of Network System**

For construction and specifications of network system, refer to "Cable Wiring Manual" published by the CC-Link Partner Association.

## 6 Error Indication

On the front of the CCS-PCIE board, the four LEDs which indicate the CC-link status are mounted.



| LED type |                                | LED status      |                              | Remedy   |
|----------|--------------------------------|-----------------|------------------------------|--|
| Name     | Meaning                        | Status          | Meaning                      |  |
| RUN      | Board operation status display | Green lights up | During normal communication  | <ul style="list-style-type: none"> <li>• Check the CCS-PCIE communication settings.</li> <li>• Check the connection status for the CC-Link cable and the external terminator.</li> <li>• Check the operation status of the CC-Link master PLC.</li> <li>• Turn the YRC1000 power OFF and ON.</li> <li>• Replace the CCS-PCIE board.</li> </ul> |
|          |                                | Off             | Not connected to the network |  |
|          |                                |                 | Not during communication     |  |
|          |                                | Red lights up   | Board operation error        |  |
| ERR      | Communication error display    | Off             | During normal communication  | <ul style="list-style-type: none"> <li>• Check the CCS-PCIE communication settings.</li> <li>• Check the connection status for the CC-Link cable and the external terminator.</li> <li>• Check the operation status of the CC-Link master PLC.</li> <li>• Turn the YRC1000 power OFF and ON.</li> <li>• Replace the CCS-PCIE board.</li> </ul> |
|          |                                |                 | Not connected to the network |  |
|          |                                | Red lights up   | Receiving error data         | <ul style="list-style-type: none"> <li>• Check the CCS-PCIE communication settings.</li> <li>• Check the connection status for the CC-Link cable and the external terminator.</li> <li>• Check the operation status of the CC-Link master PLC.</li> <li>• Turn the YRC1000 power OFF and ON.</li> <li>• Replace the CCS-PCIE board.</li> </ul> |
|          |                                |                 | Board operation error        |  |
|          |                                | Red blinking    | During error mode operation  | <ul style="list-style-type: none"> <li>• Check the CCS-PCIE communication settings.</li> <li>• Turn the YRC1000 power OFF and ON.</li> <li>• Replace the CCS-PCIE board.</li> </ul>  |

## 6 Error Indication

| LED type |                          | LED status      |                             | Remedy   |
|----------|--------------------------|-----------------|-----------------------------|--|
| SD       | Sending status display   | Green lights up | During normal communication |  |
|          |                          | Off             | Not during communication    | <ul style="list-style-type: none"> <li>• Check the CCS-PCIE communication settings.</li> </ul>   |
|          |                          | Red lights up   | Board operation error       | <ul style="list-style-type: none"> <li>• Check the connection status for the CC-Link cable and the external terminator.</li> <li>• Check the operation status of the CC-Link master PLC.</li> <li>• Turn the YRC1000 power OFF and ON.</li> <li>• Replace the CCS-PCIE board.</li> </ul> |
|          |                          | Red blinking    | Board operation error       | <ul style="list-style-type: none"> <li>• Check the CCS-PCIE communication settings.</li> <li>• Turn the YRC1000 power OFF and ON.</li> <li>• Replace the CCS-PCIE board.</li> </ul>  |
| RD       | Receiving status display | Green lights up | During normal communication |  |
|          |                          | Off             | Not during communication    | <ul style="list-style-type: none"> <li>• Check the CCS-PCIE communication settings.</li> </ul>   |
|          |                          | Red lights up   | Board operation error       | <ul style="list-style-type: none"> <li>• Check the connection status for the CC-Link cable and the external terminator.</li> <li>• Check the operation status of the CC-Link master PLC.</li> <li>• Turn the YRC1000 power OFF and ON.</li> <li>• Replace the CCS-PCIE board.</li> </ul> |
|          |                          | Green blinking  | Board operation error       | <ul style="list-style-type: none"> <li>• Check the CCS-PCIE communication settings.</li> <li>• Turn the YRC1000 power OFF and ON.</li> <li>• Replace the CCS-PCIE board.</li> </ul>  |

# YRC1000 OPTIONS CC-Link COMMUNICATIONS FUNCTION INSTRUCTIONS

FOR SST-CCS-PCIE MADE BY Molex, Inc.

---

## HEAD OFFICE

2-1 Kurosakishiroishi, Yahatanishi-ku, Kitakyushu 806-0004, Japan  
Phone +81-93-645-7703 Fax +81-93-645-7802

YASKAWA America Inc. (Motoman Robotics Division)  
100 Automation Way, Miamisburg, OH 45342, U.S.A.  
Phone +1-937-847-6200 Fax +1-937-847-6277

YASKAWA Europe GmbH (Robotics Division)  
Yaskawastrasse 1, 85391 Allershausen, Germany  
Phone +49-8166-90-100 Fax +49-8166-90-103

YASKAWA Nordic AB  
Verkstadsgatan 2, Box 504, SE-385 25 Torsås, Sweden  
Phone +46-480-417-800 Fax +46-486-414-10

YASKAWA Electric (China) Co., Ltd.  
22F, One Corporate Avenue, No.222, Hubin Road, Huangpu District, Shanghai 200021, China  
Phone +86-21-5385-2200 Fax +86-21-5385-3299

YASKAWA SHOUGANG ROBOT Co. Ltd.  
No7 Yongchang North Road, Beijing E&T Development Area, China 100176  
Phone +86-10-6788-2858 Fax +86-10-6788-2878

YASKAWA India Private Ltd. (Robotics Division)  
#426, Udyog Vihar, Phase- IV, Gurgaon, Haryana, India  
Phone +91-124-475-8500 Fax +91-124-475-8542

YASKAWA Electric Korea Corporation  
35F, Three IFC, 10 Gukjegeumyung-ro, Yeongdeungpo-gu, Seoul, Korea 07326  
Phone +82-2-784-7844 Fax +82-2-784-8495

YASKAWA Electric Taiwan Corporation  
12F, No.207, Sec. 3, Beishin Rd., Shindian District, New Taipei City 23143, Taiwan  
Phone +886-2-8913-1333 Fax +886-2-8913-1513

YASKAWA Electric (Singapore) PTE Ltd.  
151 Lorong Chuan, #04-02A, New Tech Park, Singapore 556741  
Phone +65-6282-3003 Fax +65-6289-3003

YASKAWA Electric (Thailand) Co., Ltd.  
59,1st-5th Floor, Flourish Building, Soi Ratchadapisek 18,Ratchadapisek Road,  
Huaykwang, Bangkok 10310, THAILAND  
Phone +66-2-017-0099 Fax +66-2-017-0199

PT. YASKAWA Electric Indonesia  
Secure Building-Gedung B Lantai Dasar & Lantai 1 Jl. Raya Protokol Halim Perdanakusuma,  
Jakarta 13610, Indonesia  
Phone +62-21-2982-6470 Fax +62-21-2982-6741

---

Specifications are subject to change without notice  
for ongoing product modifications and improvements.

## YASKAWA

YASKAWA ELECTRIC CORPORATION

© Printed in Japan September 2016 16-09

MANUAL NO.

# HW1484040

55/55