

R Programming & Syntax

SOCI 3238 Digital Sociology · Tutorial 1

Sep 28, 2026 (Mon) 12:30–14:00 · Sino Building 408B

Xuanlong QIN (Teaching Assistant)

Agenda

1. Why R for digital sociology?
2. RStudio & R scripts: the basics and syntax
3. How to write codes? (The logistic of coding)
4. Control flow & functions
5. Hands-on: from data to a plot

Why R?

- **Open source** and free — runs everywhere
- Purpose-built for **statistics and data analysis**
 - Comparing with **Python**
- Packages for digital sociology: `dplyr`, `ggplot2`, `igraph`, `quanteda`, `httr` ...
 - Public Package ([CRAN](https://cran.r-project.org/))
- Great for **reproducible research** (scripts > clicks)

Before Coding

- I am also new to R programming
- Learn-by-doing
- Know `"Input"` and Read `"Output"` - My personal experience
- AI is a helpful tool (Encouraged) - The point is AI can help us writing code but you need to know what are they writing for you.

RStudio basics (1)

The four panes

1. Source (scripts) - Rmd file vs. R file
2. Console
3. Environment
4. Files / Plots / Help

Run the current line with `⌘ + Enter` or click `Run`

RStudio basics (2)

Tips

- Create an **R Project** per course
- Use relative paths: `read_csv("data/x.csv")`
 - the difference between **Path** and **Relative Path**
- You can use the provided **.Rmd** file to follow the tutorial.

1. Learn R basics and syntax

1. Input

2. Comment

- Comments can be used to explain R code, and to make it more readable.
- It can also be used to prevent execution when testing alternative code.
- Comments starts with a `#`. When executing code, R will ignore anything that starts with `#`.

Work with R variables and data types

1. Variable

- **Variables are containers for storing data values.**

2. Data Types

- In programming, data type is an important concept.
- **Variables can store data of different types, and different types can do different things.**
- In R, variables do not need to be declared with any particular type, and can even change type after they have been set

Work with R variables and data types

Basic Data Types

- numeric - (10.5, 55, 787) - e.g., age, grade, income
- integer - (1L, 55L, 100L, where the letter "L" declares this as an integer) - e.g., educational level
- complex - (9 + 3i, where "i" is the imaginary part) - e.g., Common in mathematics
- character (a.k.a. **string** more common) - ("k", "R is exciting", "FALSE", "11.5") - e.g., tweets..
- logical (a.k.a. **boolean** more common) - (TRUE or FALSE) - e.g., gender..

Work with R variables and data types

Type Conversion

- `as.numeric()`
- `as.integer()`
- `as.complex()`

Why we need convert types?

- In R, you can use operators to perform common mathematical operations on numbers.

Work with R variables and data types

Operators

- Addition, Subtraction, Multiplication, Division, Exponent, Modulus (Remainder from division), Integer Division - for number-related variables

Logistic variable

- In programming, you often need to know if an expression is true or false.
- When you compare two values, the expression is evaluated and R returns the logical answer

2. R Operators and Control structures (if, while, for)

R Operators

R divides the operators in the following groups:

- Arithmetic operators - numeric values (e.g., + - * /)
- Assignment operators - assign values to variables (<-)
- Comparison operators - compare two values (== , != , > , <)
- Logical operators - combine conditional statements (e.g., & , | , !)
- Miscellaneous operators - manipulate data (e.g., :)

Control Structures

The if Statement

- An "if statement" is written with the if keyword, and it is used to specify a block of code to be executed if a condition is TRUE.
- If, else if, else..
- or

Control Structures

While Loop

- With the while loop we can execute a set of statements as long as a condition is TRUE
- With the break statement, we can stop the loop even if the while condition is TRUE:

For Loop

- A for loop is used for iterating over a sequence.

3. Create and use functions in R

A function is a block of code which only runs when it is called.

- Why we need a function?

You can pass data, known as parameters, into a function.

- To create a function, use the **function()** keyword

A function can return data as a result.

- return something

4. Work with data structures

Why we need structures?

R provides many built-in data structures. Each is used to handle data in different ways:

- Vectors ; Same type
- Lists; No
- Matrices (2D); Same type
- Arrays (Multiple dimensions); Same type
- Data Frames; No

5. Make plots and visualize data (line, scatter, pie, bar)

plot() function can solve most visualization issue.

- ggplot2() - another package

You can use AI to help enhance your images. - Generally, it is better than human.

6. Perform basic statistics (mean, median, mode)

Statistics is the science of analyzing, reviewing and conclude data.

The R language was developed by two statisticians.

- It has many built-in functionalities (Variance, Standard Deviation, Probability distributions, etc.)
- In addition to libraries for the exact purpose of statistical analysis. (Regression models, advanced techniques.. we will use them in following tutorials.)

Hands-on

Data → table → plot (5 -10 mins)

Hands-on: from data to a plot

1. Task:

- Visualize the relationship between vehicle weight and fuel consumption in the `mtcars` dataset;

2. The code is at the end of `Tutorial_1.Rmd` file (Hands-on: from data to a plot part)

Do: the hands-on exercise end-to-end on your own machine

Thanks!

Slides & materials: course content on Blackboard or Download from Github.

Questions → email (xuanlong@link.cuhk.edu.hk)