

- 3 A wire has length L and cross-sectional area A . The wire is made from a metal that has Young modulus E and resistivity ρ .

(a) Define the Young modulus of a material.

.....
 [1]

- (b) (i) State an expression, in terms of some or all of L , A , E and ρ , for the resistance R_0 of the wire.

$R_0 =$ [1]

- (ii) Show that the spring constant k_0 of the wire is given by

$$k_0 = \frac{EA}{L}.$$

[2]

- (c) The wire is stretched, within the limit of proportionality, by a tensile force F . Assume that any changes in the cross-sectional area of the wire are negligible.

- (i) On Fig. 3.1, sketch the variation with F of the resistance R of the wire.



Fig. 3.1

[1]



(ii) On Fig. 3.2, sketch the variation with F of the spring constant k of the wire.



Fig. 3.2

[1]

(d) Copper has a resistivity of $1.8 \times 10^{-8} \Omega \text{ m}$ and a Young modulus of $1.3 \times 10^{11} \text{ Pa}$.

A copper wire of diameter 1.6 mm has a resistance of 0.034Ω .

(i) Show that the length of the wire is 3.8 m.

[1]

(ii) Use the equation in (b)(ii) to determine the spring constant of the wire.

spring constant = N m^{-1} [2]

[Total: 9]

