

RLChina Reinforcement Learning Summer School



RLChina 2022

实践课三：经典强化学习算法 实践

Prof. 田政

上海科技大学


ShanghaiTech University

August 17, 2022

目录

- MDP
- Dynamic Programming
 - Policy Iteration
 - Value Iteration
- Value-based:
 - Model free:
 - SARSA
 - n-step SARSA
 - Q-learning
 - Model-based:
 - Dyna-Q
 - Deep model free:
 - DQN
- Policy gradients:
 - REINFORCE

Markov Decision Process(MDP)



A MDP can be defined as a tuple $(\mathcal{S}, \mathcal{A}, \mathcal{P}, \gamma, \mathcal{R})$, which consists of:

- \mathcal{S} : a set of states called the state space;
- \mathcal{A} : a set of actions called the action space ;
- $P(s'|s, a)$: states transition function, describing the probability that action a and state s at time step t will lead to state s' at time step $t+1$;
- $\mathcal{R}(s, a)$: reward function, describing the immediate reward received after taking action a at state s .
- $\gamma \in [0, 1]$: discount factor, which will discount the future rewards.

¹ <https://blog.paperspace.com/reinforcement-learning-for-machine-learning-folks/>

Goal: Maximizing Cumulated Return

- $$G_t = R_t + \gamma R_{t+1} + \gamma^2 R_{t+2} + \cdots = \sum_{k=0}^{\infty} \gamma^k R_{t+k}$$

Tools:

- Policy: $\pi(a | s) = P(A_t = a | S_t = s)$, describing the probability of taking action a at state s . Policy can be stochastic or deterministic. Policy depending on current state is sufficient to be optimal in MDP.
- State-value function: $V^\pi(s) = \mathbb{E}_\pi[G_t | S_t = s]$
- Action-value function: $Q^\pi(s, a) = \mathbb{E}_\pi[G_t | S_t = s, A_t = a]$
- Bellman expectation function:

$$\begin{aligned} V^\pi(s) &= \mathbb{E}_\pi[R_t + \gamma V^\pi(S_{t+1}) | S_t = s] \\ &= \sum_{a \in \mathcal{A}} \pi(a|s) \left(r(s, a) + \gamma \sum_{s' \in \mathcal{S}} p(s'|s, a) V^\pi(s') \right) \end{aligned}$$

$$\begin{aligned} Q^\pi(s, a) &= \mathbb{E}_\pi[R_t + \gamma Q^\pi(S_{t+1}, A_{t+1}) | S_t = s, A_t = a] \\ &= r(s, a) + \gamma \sum_{s' \in \mathcal{S}} p(s'|s, a) \sum_{a' \in \mathcal{A}} \pi(a'|s') Q^\pi(s', a') \end{aligned}$$

- Bellman optimal function:

$$V^*(s) = \max_{a \in \mathcal{A}} \{ r(s, a) + \gamma \sum_{s' \in \mathcal{S}} p(s'|s, a) V^*(s') \}$$

$$Q^*(s, a) = r(s, a) + \gamma \sum_{s' \in \mathcal{S}} p(s'|s, a) \max_{a' \in \mathcal{A}} Q^*(s', a')$$

Main Resources


人民邮电出版社
POSTS & TELECOM PRESS

异步社区
www.epubit.com

上海交通大学ACM班创始人

俞勇教授团队 编写

图灵奖得主 **John Hopcroft** 推荐的
——强化学习入门书——




张伟楠 沈键 俞勇 著

李沐 | John Hopcroft
俞扬 | 张志华
汪军 | 李航
等多位业内领军人士推荐

- 理论与实践相结合，既讲解了算法，又展示了代码实现，是一本不可多得的强化学习教科书！
- 配有视频课程、在线代码运行环境、课后习题和在线答疑！
- 代码实现基于Python 3和PyTorch框架！

当当扫码购买 京东扫码购买

<https://hrl.boyuai.com/>



<http://incompleteideas.net/book/the-book-2nd.html>



上海数字大脑研究院
Digital Brain Laboratory

◆ 招聘 ◆

上海数字大脑研究院面向中国和全球数字化业务需求，聚焦决策智能大模型、多智能体强化学习、机器学习驱动的运筹优化算法、人在环路算法、数字孪生等新一代人工智能关键技术研究与应用。

HR邮箱: jing.liu@digitalbrain.cn

联系电话: 13024157621 (微信)

联系人: 刘小姐

社招职位


机器学习系统开发leader
机器学习平台开发工程师
强化学习研究员 (博士/博士后)
后端开发工程师
后端开发工程师 (GPU方向)
算法工程师 (大模型预训练方向-文本)
算法工程师 (大模型预训练方向-多模态)
算法工程师 (工业智能能源方向)
算法工程师 (3D数字人方向)



社招官网

实习生职位

Unity3D开发
后端开发
项目管理
产品助理
算法
大模型平台
游戏AI
工业智能
智能交互
商务助理



实习生招聘官网