Ordering number:ENN4630

N-Channel Silicon MOSFET

2SK2046

Ultrahigh-Speed Switching Applications

Features

- Low ON resistance.
- Ultrahigh-speed switching.
- Low-voltage drive.

Package Dimensions

unit:mm

2083B



unit:mm

2092B



SANYO Electric Co.,Ltd. Semiconductor Company

TOKYO OFFICE Tokyo Bldg., 1-10, 1 Chome, Ueno, Taito-ku, TOKYO, 110-8534 JAPAN

Specifications

Absolute Maximum Ratings at Ta = 25˚C

Parameter	Symbol	Conditions	Ratings	Unit
Drain-to-Source Voltage	V_{DSS}		30	V
Gate-to-Source Voltage	V_{GSS}		±15	V
Drain Current (DC)	I_D		12	A
Drain Current (pulse)	I_{DP}	PW≤10μs, duty cycle≤1%	48	A
Allowable Power Dissipation	P_D	Tc=25°C	30	W
Channel Temperature	Tch		150	˚C
Storage Temperature	Tstg		–55 to +150	˚C

Electrical Characteristics at Ta = 25˚C

Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	
Drain-to-Source Breakdown Voltage	$V_{(BR)DSS}$	I_D=1mA, V_{GS}=0	30			V
Gate-to-Source Breakdown Voltage	$V_{(BR)GSS}$	I_G=±100μA, V_{DS}=0	±15			V
Zero-Gate Votlage Drain Current	I_{DSS}	V_{DS}=30V, V_{GS}=0			100	μA
Gate-to-Source Leakage Current	I_{GSS}	V_{GS}=±12V, V_{DS}=0			±10	μA
Cutoff Voltage	$V_{GS(off)}$	V_{DS}=10V, I_D=1mA	1.0		2.0	V
Forward Transfer Admittance	| yfs |	V_{DS}=10V, I_D=4A	5	8		S
Static Drain-to-Source On-State Resistance	$R_{DS(on)}1$	I_D=4A, V_{GS}=10V	24	35	50	mΩ
	$R_{DS(on)}2$	I_D=4A, V_{GS}=4V		50	70	mΩ
Input Capacitance	Ciss	V_{DS}=10V, f=1MHz		1000		pF
Output Capacitance	Coss	V_{DS}=10V, f=1MHz		550		pF
Reverse Transfer Capacitance	Crss	V_{DS}=10V, f=1MHz		180		pF
Turn-ON Delay Time	$t_{d(on)}$	See specified Test Circuit		13		ns
Rise Time	t_r	See specified Test Circuit		40		ns
Turn-OFF Delay Time	$t_{d(off)}$	See specified Test Circuit		130		ns
Fall Time	t_f	See specified Test Circuit		120		ns
Diode Forward Voltage	V_{SD}	I_S=8A, V_{GS}=0		1.0	1.5	V
Drain Current	I_{DSX}	V_{DS}=5V, V_{GS}=0.1V			0.5	μA

Switching Time Test Circuit



I_D – V_{DS}



I_D – V_{GS}



$|y_{fs}|$ – I_D



$R_{DS(on)}$ – V_{GS}



$R_{DS(on)}$ – Tc



Ciss, Coss, Crss – V_{DS}



SW Time – I_D



A S O