TOSHIBA TRANSISTOR SILICON NPN EPITAXIAL TYPE (PCT PROCESS)

2SC3074

HIGH CURRENT SWITCHING APPLICATIONS

- Low Collector Saturation Voltage
  : $V_{CE\ (sat)}$ = 0.4 V (Max.) (at I_C = 3 A)
- High Speed Switching Time : t_{stg} = 1.0 μs (Typ.)
- Complementary to 2SA1244

MAXIMUM RATINGS (Tc = 25°C)

CHARACTERISTIC		SYMBOL	RATING	UNIT
Collector-Base Voltage		V_{CBO}	60	V
Collector-Emitter Voltage		V_{CEO}	50	V
Emitter-Base Voltage		V_{EBO}	5	V
Collector Current		I_C	5	A
Base Current		I_B	1	A
Collector Power Dissipation	Ta = 25°C	P_C	1.0	W
	Tc = 25°C		20	
Junction Temperature		T_j	150	°C
Storage Temperature Range		T_{stg}	−55~150	°C

Unit in mm



JEDEC	—
JEITA	—
TOSHIBA	(A) 2-7B1A (B) 2-7B2A

Weight : 0.36 g (Typ.)

ELECTRICAL CHARACTERISTICS (Tc = 25°C)

CHARACTERISTIC		SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Collector Cut-off Current		I_{CBO}	V_{CB} = 50 V, I_E = 0	—	—	1	μA
Emitter Cut-off Current		I_{EBO}	V_{EB} = 5 V, I_C = 0	—	—	1	μA
Collector-Emitter Breakdown Voltage		$V_{(BR)CEO}$	I_C = 10 mA, I_B = 0	50	—	—	V
DC Current Gain		$h_{FE(1)}$ (Note)	V_{CE} = 1V, I_C = 1 A	70	—	240	
		$h_{FE(2)}$	V_{CE} = 1 V, I_C = 3 A	30	—	—	
Saturation Voltage	Collector-Emitter	$V_{CE(sat)}$	I_C = 3 A, I_B = 0.15 A	—	0.2	0.4	V
	Base-Emitter	$V_{BE(sat)}$	I_C = 3 A, I_B = 0.15 A	—	0.9	1.2	
Transition Frequency		f_T	V_{CE} = 4 V, I_C = 1 A	—	120	—	MHz
Collector Output Capacitance		C_{ob}	V_{CB} = 10 V, I_E = 0, f = 1 MHz	—	80	—	pF
Switching Time	Turn-on Time	t_{on}		—	0.1	—	μs
	Storage Time	t_{stg}		—	1.0	—	
	Fall Time	t_f	$I_{B1} = -I_{B2}$ = 0.15 A, DUTY CYCLE ≦ 1%	—	0.1	—	

(Note) : $h_{FE(1)}$ Classification O : 70~140, Y : 120~240

I_C – V_{CE}



V_{CE} – I_C



V_{CE} – I_C



V_{CE} – I_C



h_{FE} – I_C



$V_{CE\,(sat)}$ – I_C



$V_{BE\,(sat)}$ – I_C



I_C – V_{BE}



SAFE OPERATING AREA



P_C – Ta



RESTRICTIONS ON PRODUCT USE

000707EAA

- TOSHIBA is continually working to improve the quality and reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to comply with the standards of safety in making a safe design for the entire system, and to avoid situations in which a malfunction or failure of such TOSHIBA products could cause loss of human life, bodily injury or damage to property.
  In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent TOSHIBA products specifications. Also, please keep in mind the precautions and conditions set forth in the "Handling Guide for Semiconductor Devices," or "TOSHIBA Semiconductor Reliability Handbook" etc..
- The TOSHIBA products listed in this document are intended for usage in general electronics applications (computer, personal equipment, office equipment, measuring equipment, industrial robotics, domestic appliances, etc.). These TOSHIBA products are neither intended nor warranted for usage in equipment that requires extraordinarily high quality and/or reliability or a malfunction or failure of which may cause loss of human life or bodily injury ("Unintended Usage"). Unintended Usage include atomic energy control instruments, airplane or spaceship instruments, transportation instruments, traffic signal instruments, combustion control instruments, medical instruments, all types of safety devices, etc.. Unintended Usage of TOSHIBA products listed in this document shall be made at the customer's own risk.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.