TOSHIBA TRANSISTOR SILICON PNP EPITAXIAL TYPE (PCT PROCESS)

2SA817A

DRIVER STAGE AMPLIFIER APPLICATIONS
VOLTAGE AMPLIFIER APPLICATIONS

- Complementary to 2SC1627A.
- Driver Stage Application of 30 to 35 Watts Amplifiers.

Unit in mm



JEDEC	TO-92MOD
JEITA	—
TOSHIBA	2-5J1A

Weight : 0.36g (Typ.)

MAXIMUM RATINGS (Ta = 25°C)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Collector-Base Voltage	V_{CBO}	−80	V
Collector-Emitter Voltage	V_{CEO}	−80	V
Emitter-Base Voltage	V_{EBO}	−5	V
Collector Current	I_C	−400	mA
Emitter Current	I_E	400	mA
Collector Power Dissipation	P_C	800	mW
Junction Temperature	T_j	150	°C
Storage Temperature Range	T_{stg}	−55~150	°C

ELECTRICAL CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Collector Cut-off Current	I_{CBO}	V_{CB} = −50V, I_E = 0	—	—	−100	nA
Emitter Cut-off Current	I_{EBO}	V_{EB} = −5V, I_C = 0	—	—	−100	nA
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	I_C = −5mA, I_B = 0	−80	—	—	V
DC Current Gain	$h_{FE(1)}$ (Note)	V_{CE} = −2V, I_C = −50mA	70	—	240	
	$h_{FE(2)}$	V_{CE} = −2V, I_C = −200mA	40	—	—	
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	I_C = −200mA, I_B = −20mA	—	—	−0.4	V
Base-Emitter Voltage	V_{BE}	V_{CE} = −2V, I_C = −5mA	−0.55	—	−0.8	V
Transition Frequency	f_T	V_{CE} = −10V, I_C = −10mA	—	100	—	MHz
Collector Output Capacitance	C_{ob}	V_{CB} = −10V, I_E = 0, f = 1MHz	—	14	—	pF

(Note) : $h_{FE(1)}$ Classification O : 70~140, Y : 120~240

$I_C - V_{CE}$



$h_{FE} - I_C$



$V_{CE(sat)} - I_C$



$I_C - V_{BE}$



$P_C - Ta$



SAFE OPERATING AREA



RESTRICTIONS ON PRODUCT USE

000707EAA

- TOSHIBA is continually working to improve the quality and reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to comply with the standards of safety in making a safe design for the entire system, and to avoid situations in which a malfunction or failure of such TOSHIBA products could cause loss of human life, bodily injury or damage to property.
  In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent TOSHIBA products specifications. Also, please keep in mind the precautions and conditions set forth in the "Handling Guide for Semiconductor Devices," or "TOSHIBA Semiconductor Reliability Handbook" etc..
- The TOSHIBA products listed in this document are intended for usage in general electronics applications (computer, personal equipment, office equipment, measuring equipment, industrial robotics, domestic appliances, etc.). These TOSHIBA products are neither intended nor warranted for usage in equipment that requires extraordinarily high quality and/or reliability or a malfunction or failure of which may cause loss of human life or bodily injury ("Unintended Usage"). Unintended Usage include atomic energy control instruments, airplane or spaceship instruments, transportation instruments, traffic signal instruments, combustion control instruments, medical instruments, all types of safety devices, etc.. Unintended Usage of TOSHIBA products listed in this document shall be made at the customer's own risk.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.