


2SA1600

(TP12T4)

-12A PNP

OUTLINE DIMENSIONS



RATINGS

● Absolute Maximum Ratings


Item	Symbol	Conditions	Ratings	Unit
Storage Temperature	T _{stg}		-55~150	°C
Junction Temperature	T _j		150	°C
Collector to Base Voltage	V _{CBO}		-60	V
Collector to Emitter Voltage	V _{CEO}		-40	V
Emitter to Base Voltage	V _{EBO}		-7	V
Collector Current DC	I _C		-12	A
Collector Current Peak	I _{CP}		-24	A
Base Current DC	I _B		-2	A
Base Current Peak	I _{BP}		-3	A
Total Transistor Dissipation	P _T	T _c = 25°C	30	W
Dielectric Strength	V _{dis}	Terminal to case, AC 1 minute	2	kV
Mounting Torque	TOR	(Recommended torque : 0.3N·m)	0.5	N·m

● Electrical Characteristics (T_c=25°C)


Item	Symbol	Conditions	Ratings	Unit
Collector to Emitter Sustaining Voltage	V _{CEO(sus)}	I _C = -0.1A	Min -40	V
Collector Cutoff Current	I _{CBO}	At rated Voltage	Max -0.1	mA
			Max -0.1	
Emitter Cutoff Current	I _{EBO}	At rated Voltage	Max -0.1	mA
DC Current Gain	h _{FE}	V _{CE} = -2V, I _C = -6A	Min 70	
Collector to Emitter Saturation Voltage	V _{CE(sat)}	I _C = -6A	Max -0.3	V
Base to Emitter Saturation Voltage	V _{BE(sat)}	I _B = -0.3A	Max -1.2	V
Thermal Resistance	θ _{jc}	Junction to case	Max 4.16	°C/W
Transition Frequency	f _T	V _{CE} = -10V, I _C = -1.2A	TYP 50	MHz
Turn on Time	ton	I _C = -6A I _{B1} = -0.6A, I _{B2} = -0.6A R _L = 5Ω, V _{BB2} = -4V	Max 0.3	μs
Storage Time	ts		Max 1.5	
Fall Time	tf		Max 0.5	

2SA1600

$h_{FE} - I_C$




2SA1600 Saturation Voltage




2SA1600

Switching Time - I_C




2SA1600


Switching Time - Tc



2SA1600 Transient Thermal Impedance



2SA1600 Forward Bias SOA



2SA1600

Collector Current Derating

