ALPHA & OMEGA SEMICONDUCTOR

AO3401
P-Channel Enhancement Mode Field Effect Transistor

General Description

The AO3401 uses advanced trench technology to provide excellent $R_{DS(ON)}$, low gate charge and operation with gate voltages as low as 2.5V. This device is suitable for use as a load switch or in PWM applications. *Standard product AO3401 is Pb-free (meets ROHS & Sony 259 specifications).*

Features

V_{DS} (V) = -30V
I_D = -4.2 A (V_{GS} = -10V)
$R_{DS(ON)}$ < 50mΩ (V_{GS} = -10V)
$R_{DS(ON)}$ < 65mΩ (V_{GS} = -4.5V)
$R_{DS(ON)}$ < 120mΩ (V_{GS} = -2.5V)

TO-236
(SOT-23)
Top View





Absolute Maximum Ratings T_A=25°C unless otherwise noted

Parameter		Symbol	Maximum	Units
Drain-Source Voltage		V_{DS}	-30	V
Gate-Source Voltage		V_{GS}	±12	V
Continuous Drain Current [A]	T_A=25°C	I_D	-4.2	A
	T_A=70°C		-3.5	
Pulsed Drain Current [B]		I_{DM}	-30	
Power Dissipation [A]	T_A=25°C	P_D	1.4	W
	T_A=70°C		1	
Junction and Storage Temperature Range		T_J, T_{STG}	-55 to 150	°C

Thermal Characteristics

Parameter		Symbol	Typ	Max	Units
Maximum Junction-to-Ambient [A]	t ≤ 10s	$R_{\theta JA}$	65	90	°C/W
Maximum Junction-to-Ambient [A]	Steady-State		85	125	°C/W
Maximum Junction-to-Lead [C]	Steady-State	$R_{\theta JL}$	43	60	°C/W

Electrical Characteristics (T_J=25°C unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
STATIC PARAMETERS						
BV_{DSS}	Drain-Source Breakdown Voltage	I_D=-250µA, V_{GS}=0V	-30			V
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS}=-24V, V_{GS}=0V			-1	µA
		T_J=55°C			-5	
I_{GSS}	Gate-Body leakage current	V_{DS}=0V, V_{GS}=±12V			±100	nA
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS}=V_{GS} I_D=-250µA	-0.7	-1	-1.3	V
$I_{D(ON)}$	On state drain current	V_{GS}=-4.5V, V_{DS}=-5V	-25			A
$R_{DS(ON)}$	Static Drain-Source On-Resistance	V_{GS}=-10V, I_D=-4.2A		42	50	mΩ
		T_J=125°C			75	
		V_{GS}=-4.5V, I_D=-4A		53	65	mΩ
		V_{GS}=-2.5V, I_D=-1A		80	120	mΩ
g_{FS}	Forward Transconductance	V_{DS}=-5V, I_D=-5A	7	11		S
V_{SD}	Diode Forward Voltage	I_S=-1A,V_{GS}=0V		-0.75	-1	V
I_S	Maximum Body-Diode Continuous Current				-2.2	A
I_{SM}	Pulsed Body-Diode Current[B]				-30	A
DYNAMIC PARAMETERS						
C_{iss}	Input Capacitance	V_{GS}=0V, V_{DS}=-15V, f=1MHz		954		pF
C_{oss}	Output Capacitance			115		pF
C_{rss}	Reverse Transfer Capacitance			77		pF
R_g	Gate resistance	V_{GS}=0V, V_{DS}=0V, f=1MHz		6		Ω
SWITCHING PARAMETERS						
Q_g	Total Gate Charge	V_{GS}=-4.5V, V_{DS}=-15V, I_D=-4A		9.4		nC
Q_{gs}	Gate Source Charge			2		nC
Q_{gd}	Gate Drain Charge			3		nC
$t_{D(on)}$	Turn-On DelayTime	V_{GS}=-10V, V_{DS}=-15V, R_L=3.6Ω, R_{GEN}=6Ω		6.3		ns
t_r	Turn-On Rise Time			3.2		ns
$t_{D(off)}$	Turn-Off DelayTime			38.2		ns
t_f	Turn-Off Fall Time			12		ns
t_{rr}	Body Diode Reverse Recovery Time	I_F=-4A, dI/dt=100A/µs		20.2		ns
Q_{rr}	Body Diode Reverse Recovery Charge	I_F=-4A, dI/dt=100A/µs		11.2		nC

A: The value of $R_{\theta JA}$ is measured with the device mounted on 1in^2 FR-4 board with 2oz. Copper, in a still air environment with T_A=25°C. The value in any a given application depends on the user's specific board design. The current rating is based on the t≤ 10s thermal resistance rating.

B: Repetitive rating, pulse width limited by junction temperature.

C. The $R_{\theta JA}$ is the sum of the thermal impedence from junction to lead $R_{\theta JL}$ and lead to ambient.

D. The static characteristics in Figures 1 to 6,12,14 are obtained using <300µs pulses, duty cycle 0.5% max.

E. These tests are performed with the device mounted on 1 in^2 FR-4 board with 2oz. Copper, in a still air environment with T_A=25°C. The SOA curve provides a single pulse rating.

Rev5: Dec.2006

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS



Fig 1: On-Region Characteristics



Figure 2: Transfer Characteristics



Figure 3: On-Resistance vs. Drain Current and Gate Voltage



Figure 4: On-Resistance vs. Junction Temperature



Figure 5: On-Resistance vs. Gate-Source Voltage



Figure 6: Body-Diode Characteristics

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS



Figure 7: Gate-Charge Characteristics



Figure 8: Capacitance Characteristics



Figure 9: Maximum Forward Biased Safe Operating Area (Note E)



Figure 10: Single Pulse Power Rating Junction-to-Ambient (Note E)



Figure 11: Normalized Maximum Transient Thermal Impedance