2SC4126

Silicon NPN Epitaxial

HITACHI

Application

VHF and UHF wide band amplifier

Outline

MPAK-4



1. Collector
2. Emitter
3. Base
4. Emitter

Hitachi semiconductor

Absolute Maximum Ratings (Ta = 25°C)

Item	Symbol	Ratings	Unit
Collector to base voltage	V_{CBO}	15	V
Collector to emitter voltage	V_{CEO}	11	V
Emitter to base voltage	V_{EBO}	2	V
Collector current	I_C	50	mA
Collector power dissipation	P_C	150	mW
Junction temperature	Tj	150	°C
Storage temperature	Tstg	–55 to +150	°C

Electrical Characteristics (Ta = 25°C)

Item	Symbol	Min	Typ	Max	Unit	Test conditions
Collector to base breakdown voltage	$V_{(BR)CBO}$	15	—	—	V	I_C = 10 µA, I_E = 0
Collector cutoff current	I_{CBO}	—	—	1	µA	V_{CB} = 12 V, I_E = 0
	I_{CEO}	—	—	1	µA	V_{CE} = 10 V, R_{BE} = ∞
Emitter cutoff current	I_{EBO}	—	—	1	µA	V_{EB} = 1 V, I_C = 0
DC current transfer ratio	h_{FE}	50	—	250		V_{CE} = 5 V, I_C = 20 mA
Collector output capacitance	Cob	—	1.0	1.5	pF	V_{CB} = 5 V, I_E = 0, f = 1 MHz
Gain bandwidth product	f_T	4.5	6.0	—	GHz	V_{CE} = 5 V, I_C = 20 mA
Power gain	PG	9.0	11.0	—	dB	V_{CE} = 5 V, I_C = 20 mA, f = 900 MHz
Noise figure	NF	—	1.5	3.0	dB	V_{CE} = 5 V, I_C = 5 mA, f = 900 MHz

Note: Marking is “MI–”.

Maximum Collector Dissipation Curve



Typical Output Characteristics



DC Current Transfer Ratio vs. Collector Current



Gain Bandwidth Product vs. Collector Current



Collector Output Capacitance vs. Collector to Base Voltage



Power Gain vs. Collector Current



Noise Figure vs. Collector Current



S Parameters (Emitter Common)

Test condition V_{CE} = 5 V, Z_O = 50 Ω, Freq. = 100 to 1000 MHz (100 MHz Step)



S Parameters (Emitter Common)

Test condition V_{CE} = 5 V, I_C = 5 mA, Z_O = 50 Ω

Freq. (MHz)	$\|S_{11}\|$	$\angle S_{11}$ (DEG.)	$\|S_{21}\|$	$\angle S_{21}$ (DEG.)	$\|S_{12}\|$	$\angle S_{12}$ (DEG.)	$\|S_{22}\|$	$\angle S_{22}$ (DEG.)	Gmax*[1] (dB)
100	0.798	–37.3	13.345	152.3	0.033	69.6	0.898	–20.1	34.03
200	0.659	–69.4	10.696	131.4	0.054	56.0	0.730	–33.1	26.37
300	0.550	–93.7	8.434	117.0	0.067	49.2	0.592	–39.3	21.96
400	0.480	–113.6	6.815	107.3	0.074	47.3	0.502	–42.3	19.07
500	0.438	–129.8	5.684	100.0	0.081	47.0	0.442	–43.7	16.96
600	0.414	–143.6	4.847	94.2	0.087	47.3	0.399	–44.4	15.28
700	0.410	–154.4	4.229	89.4	0.092	48.6	0.366	–45.3	13.95
800	0.406	–164.7	3.750	85.0	0.098	49.5	0.340	–46.3	12.80
900	0.412	–174.9	3.352	81.0	0.104	50.6	0.317	–47.4	11.78
1000	0.424	–178.1	3.071	77.4	0.110	51.6	0.299	–48.3	11.01

Test condition V_{CE} = 5 V, I_C = 20 mA, Z_O = 50 Ω

Freq. (MHz)	$\|S_{11}\|$	$\angle S_{11}$ (DEG.)	$\|S_{21}\|$	$\angle S_{21}$ (DEG.)	$\|S_{12}\|$	$\angle S_{12}$ (DEG.)	$\|S_{22}\|$	$\angle S_{22}$ (DEG.)	Gmax*[1] (dB)
100	0.501	–75.1	26.789	131.8	0.024	62.2	0.683	–36.5	32.54
200	0.402	–117.1	16.600	111.1	0.035	58.5	0.446	–45.4	26.13
300	0.368	–141.0	11.543	100.7	0.044	61.3	0.337	–45.6	22.40
400	0.347	–157.6	8.823	94.7	0.054	63.3	0.282	–44.2	19.83
500	0.354	–169.0	7.131	89.5	0.063	65.0	0.250	–42.8	17.92
600	0.358	–178.7	5.979	85.8	0.074	66.6	0.228	–42.1	16.36
700	0.370	174.9	5.158	82.3	0.084	66.9	0.208	–42.1	15.08
800	0.380	167.1	4.536	79.2	0.094	67.3	0.192	–42.7	13.98
900	0.400	161.5	4.042	76.5	0.104	67.6	0.178	–43.2	13.03
1000	0.411	157.0	3.677	73.5	0.114	67.4	0.165	–43.3	12.24

Note: 1. $\text{Gmax} = \dfrac{1}{\left|1-|S_{11}|^2\right|} \cdot |S_{21}|^2 \cdot \dfrac{1}{\left|1-|S_{22}|^2\right|}$

Unit: mm



Hitachi Code	MPAK-4
JEDEC	—
EIAJ	Conforms
Weight (reference value)	0.013 g

Cautions

1. Hitachi neither warrants nor grants licenses of any rights of Hitachi's or any third party's patent, copyright, trademark, or other intellectual property rights for information contained in this document. Hitachi bears no responsibility for problems that may arise with third party's rights, including intellectual property rights, in connection with use of the information contained in this document.
2. Products and product specifications may be subject to change without notice. Confirm that you have received the latest product standards or specifications before final design, purchase or use.
3. Hitachi makes every attempt to ensure that its products are of high quality and reliability. However, contact Hitachi's sales office before using the product in an application that demands especially high quality and reliability or where its failure or malfunction may directly threaten human life or cause risk of bodily injury, such as aerospace, aeronautics, nuclear power, combustion control, transportation, traffic, safety equipment or medical equipment for life support.
4. Design your application so that the product is used within the ranges guaranteed by Hitachi particularly for maximum rating, operating supply voltage range, heat radiation characteristics, installation conditions and other characteristics. Hitachi bears no responsibility for failure or damage when used beyond the guaranteed ranges. Even within the guaranteed ranges, consider normally foreseeable failure rates or failure modes in semiconductor devices and employ systemic measures such as fail-safes, so that the equipment incorporating Hitachi product does not cause bodily injury, fire or other consequential damage due to operation of the Hitachi product.
5. This product is not designed to be radiation resistant.
6. No one is permitted to reproduce or duplicate, in any form, the whole or part of this document without written approval from Hitachi.
7. Contact Hitachi's sales office for any questions regarding this document or Hitachi semiconductor products.

HITACHI

Hitachi, Ltd.
Semiconductor & Integrated Circuits.
Nippon Bldg., 2-6-2, Ohte-machi, Chiyoda-ku, Tokyo 100-0004, Japan
Tel: Tokyo (03) 3270-2111 Fax: (03) 3270-5109

URL
NorthAmerica : http:semiconductor.hitachi.com/
Europe : http://www.hitachi-eu.com/hel/ecg
Asia (Singapore) : http://www.has.hitachi.com.sg/grp3/sicd/index.htm
Asia (Taiwan) : http://www.hitachi.com.tw/E/Product/SICD_Frame.htm
Asia (HongKong) : http://www.hitachi.com.hk/eng/bo/grp3/index.htm
Japan : http://www.hitachi.co.jp/Sicd/indx.htm

For further information write to:

Hitachi Semiconductor
(America) Inc.
179 East Tasman Drive,
San Jose,CA 95134
Tel: <1> (408) 433-1990
Fax: <1>(408) 433-0223

Hitachi Europe GmbH
Electronic components Group
Dornacher Straße 3
D-85622 Feldkirchen, Munich
Germany
Tel: <49> (89) 9 9180-0
Fax: <49> (89) 9 29 30 00

Hitachi Europe Ltd.
Electronic Components Group.
Whitebrook Park
Lower Cookham Road
Maidenhead
Berkshire SL6 8YA, United Kingdom
Tel: <44> (1628) 585000
Fax: <44> (1628) 778322

Hitachi Asia Pte. Ltd.
16 Collyer Quay #20-00
Hitachi Tower
Singapore 049318
Tel: 535-2100
Fax: 535-1533

Hitachi Asia Ltd.
Taipei Branch Office
3F, Hung Kuo Building. No.167,
Tun-Hwa North Road, Taipei (105)
Tel: <886> (2) 2718-3666
Fax: <886> (2) 2718-8180

Hitachi Asia (Hong Kong) Ltd.
Group III (Electronic Components)
7/F., North Tower, World Finance Centre,
Harbour City, Canton Road, Tsim Sha Tsui,
Kowloon, Hong Kong
Tel: <852> (2) 735 9218
Fax: <852> (2) 730 0281
Telex: 40815 HITEC HX