TOSHIBA TRANSISTOR SILICON NPN EPITAXIAL PLANAR TYPE

2SC5319

VHF~UHF BAND LOW NOISE AMPLIFIER APPLICATIONS

- Low Noise Figure : NF = 1.3 dB (f = 2 GHz)
- High Gain : Ga = 11.5 dB (f = 2 GHz)

Unit in mm



1, 3. EMITTER
2. BASE
4. COLLECTOR

USQ	
JEDEC	—
EIAJ	—
TOSHIBA	2-2K1A

Weight : 0.006 g

MAXIMUM RATINGS (Ta = 25°C)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Collector-Base Voltage	V_{CBO}	8	V
Collector-Emitter Voltage	V_{CEO}	5	V
Emitter-Base Voltage	V_{EBO}	1.5	V
Collector Current	I_C	20	mA
Base Current	I_B	10	mA
Collector Power Dissipation	P_C	100	mW
Junction Temperature	T_j	125	°C
Storage Temperature Range	T_{stg}	−55~125	°C

MARKING



MICROWAVE CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Transition Frequency	f_T	V_{CE} = 3 V, I_C = 15 mA	13	16	—	GHz
Insertion Gain	$\|S_{21e}\|^2$ (1)	V_{CE} = 3 V, I_C = 15 mA, f = 1 GHz	14.5	17	—	dB
	$\|S_{21e}\|^2$ (2)	V_{CE} = 3 V, I_C = 15 mA, f = 2 GHz	8.5	11.5	—	
Noise Figure	NF (1)	V_{CE} = 3 V, I_C = 5 mA, f = 1 GHz	—	0.9	1.8	dB
	NF (2)	V_{CE} = 3 V, I_C = 5 mA, f = 2 GHz	—	1.3	2.2	

ELECTRICAL CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Collector Cut-off Current	I_{CBO}	V_{CB} = 8 V, I_E = 0	—	—	1	μA
Emitter Cut-off Current	I_{EBO}	V_{EB} = 1 V, I_C = 0	—	—	1	μA
DC Current Gain	h_{FE}	V_{CE} = 3 V, I_C = 15 mA	50	—	250	V
Output Capacitance	C_{ob}	V_{CB} = 2.5 V, I_E = 0, f = 1 MHz (Note)	—	0.6	—	pF
Reverse Transfer Capacitance	C_{re}		—	0.4	0.85	pF

(Note) : C_{re} is measured by 3 terminal method with Capacitance Bridge.

CAUTION

This device electrostatic sensitivity. Please handle with caution.

f_T – I_C



$|S_{21e}|^2$ – I_C



NF, Ga – I_C



NF, Ga – V_{CE}



$|S_{21e}|^2$ – f



C_{re}, C_{ob} – V_{CB}



S-PARAMETER Z_O = 50 Ω, Ta = 25°C
V_{CE} = 3 V, I_C = 1 mA

f	S11		S21		S12		S22	
(MHz)	Mag.	Ang.	Mag.	Ang.	Mag.	Ang.	Mag.	Ang.
800	0.838	−52.3	3.011	134.2	0.146	56.2	0.880	−38.1
900	0.813	−57.7	2.956	130.8	0.161	53.4	0.854	−40.8
1000	0.793	−62.3	2.839	125.4	0.174	49.5	0.842	−44.8
1100	0.780	−67.0	2.758	122.9	0.183	46.4	0.811	−47.9
1200	0.736	−72.6	2.584	116.6	0.194	42.6	0.798	−51.6
1300	0.733	−77.0	2.597	115.6	0.198	39.5	0.778	−54.5
1400	0.709	−82.4	2.500	109.2	0.202	38.0	0.760	−57.6
1500	0.688	−87.2	2.414	105.8	0.206	36.1	0.739	−60.7
1600	0.686	−89.8	2.331	102.2	0.213	35.7	0.728	−63.5
1700	0.668	−93.8	2.229	100.1	0.228	34.4	0.713	−66.2
1800	0.643	−97.7	2.201	95.4	0.236	30.4	0.707	−69.3
1900	0.619	−102.6	2.094	90.4	0.236	27.4	0.698	−71.5
2000	0.589	−107.3	2.003	90.5	0.239	24.9	0.686	−74.7
2100	0.593	−107.8	1.941	84.9	0.236	23.0	0.678	−76.7
2200	0.560	−112.4	1.864	86.0	0.240	22.5	0.666	−79.6
2300	0.564	−116.6	1.942	79.1	0.247	19.6	0.668	−81.8
2400	0.590	−119.3	1.753	81.6	0.239	16.5	0.656	−84.0

V_{CE} = 3 V, I_C = 3 mA

f	S11		S21		S12		S22	
(MHz)	Mag.	Ang.	Mag.	Ang.	Mag.	Ang.	Mag.	Ang.
800	0.634	−83.6	6.442	118.6	0.113	48.4	0.682	−56.4
900	0.606	−91.1	6.105	114.7	0.121	45.7	0.644	−59.7
1000	0.587	−96.3	5.681	110.0	0.126	42.8	0.613	−64.2
1100	0.562	−101.2	5.375	107.1	0.131	40.8	0.582	−66.9
1200	0.528	−108.0	4.899	102.1	0.133	38.6	0.555	−70.9
1300	0.524	−113.7	4.756	100.3	0.135	37.7	0.532	−74.0
1400	0.504	−118.2	4.473	96.2	0.137	37.6	0.507	−77.1
1500	0.470	−124.2	4.223	93.0	0.140	37.0	0.489	−79.7
1600	0.480	−127.2	4.049	90.2	0.144	37.3	0.477	−82.4
1700	0.459	−128.9	3.813	88.8	0.150	35.8	0.459	−85.3
1800	0.445	−134.4	3.662	84.7	0.153	33.9	0.457	−87.7
1900	0.428	−140.0	3.441	81.0	0.153	33.3	0.442	−89.9
2000	0.424	−143.1	3.329	81.0	0.152	32.5	0.436	−92.4
2100	0.404	−145.6	3.149	77.3	0.153	33.0	0.432	−94.1
2200	0.385	−149.3	3.041	77.5	0.157	33.0	0.420	−97.2
2300	0.407	−156.7	2.999	71.6	0.159	31.6	0.421	−98.4
2400	0.437	−155.7	2.808	74.0	0.157	31.8	0.413	−100.6

V_{CE} = 3 V, I_C = 5 mA

f	S11		S21		S12		S22	
(MHz)	Mag.	Ang.	Mag.	Ang.	Mag.	Ang.	Mag.	Ang.
800	0.539	−101.6	7.906	110.6	0.093	47.0	0.557	−66.6
900	0.512	−109.5	7.361	106.9	0.098	45.0	0.516	−70.0
1000	0.498	−114.8	6.733	102.6	0.102	43.5	0.486	−74.0
1100	0.472	−122.2	6.308	100.0	0.105	42.9	0.455	−76.7
1200	0.461	−126.3	5.709	95.8	0.108	41.9	0.431	−80.0
1300	0.450	−131.8	5.487	94.0	0.109	41.9	0.411	−82.8
1400	0.439	−136.7	5.146	90.4	0.112	42.6	0.392	−86.0
1500	0.413	−143.8	4.796	87.9	0.116	42.8	0.377	−88.3
1600	0.435	−146.5	4.593	85.4	0.121	43.3	0.368	−90.9
1700	0.411	−146.6	4.305	83.9	0.126	42.5	0.355	−93.4
1800	0.402	−153.7	4.099	80.0	0.128	41.5	0.354	−95.7
1900	0.386	−159.0	3.870	77.6	0.129	41.5	0.343	−97.9
2000	0.386	−161.9	3.729	77.2	0.131	41.4	0.340	−99.9
2100	0.369	−164.5	3.519	74.1	0.133	42.4	0.337	−101.7
2200	0.368	−168.2	3.407	74.2	0.138	42.6	0.332	−104.1
2300	0.378	−172.1	3.339	69.1	0.140	41.8	0.334	−105.2
2400	0.398	−170.2	3.153	71.0	0.140	42.4	0.328	−107.2

RESTRICTIONS ON PRODUCT USE

000707EAA

- TOSHIBA is continually working to improve the quality and reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to comply with the standards of safety in making a safe design for the entire system, and to avoid situations in which a malfunction or failure of such TOSHIBA products could cause loss of human life, bodily injury or damage to property.
  In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent TOSHIBA products specifications. Also, please keep in mind the precautions and conditions set forth in the "Handling Guide for Semiconductor Devices," or "TOSHIBA Semiconductor Reliability Handbook" etc..
- The TOSHIBA products listed in this document are intended for usage in general electronics applications (computer, personal equipment, office equipment, measuring equipment, industrial robotics, domestic appliances, etc.). These TOSHIBA products are neither intended nor warranted for usage in equipment that requires extraordinarily high quality and/or reliability or a malfunction or failure of which may cause loss of human life or bodily injury ("Unintended Usage"). Unintended Usage include atomic energy control instruments, airplane or spaceship instruments, transportation instruments, traffic signal instruments, combustion control instruments, medical instruments, all types of safety devices, etc.. Unintended Usage of TOSHIBA products listed in this document shall be made at the customer's own risk.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.