第一人称铁道信号巡检仿真实训平台

版本号：V1.0

源代码

目录

1. 目录
2. src/router.js
3. src/views/StudentHub.vue
4. src/components/RailwayFpsGame.vue
5. src/components/agent/AgentDialog.vue
6. src/components/agent/AgentLauncher.vue
7. src/components/admin/AdminTable.vue
8. src/game/sceneSerializer.js
9. src/game/trainingSceneDb.js
10. src/game/defaultTrainingScene.js
11. src/game/equipmentProximity.js
12. src/game/railwayGame.js
13. src/stores/auth.js
14. src/stores/agent.js
15. src/api/client.js
16. server/src/routes/sceneRoutes.js
17. server/src/routes/authRoutes.js
18. server/src/routes/aiRoutes.js
19. server/src/routes/adminRoutes.js
20. server/src/services/authService.js
21. server/src/services/tokenService.js
22. server/src/services/defaultSceneService.js
23. server/src/repositories/sceneRepository.js
24. server/src/repositories/conversationRepository.js
25. server/src/db/schema.sql
26. server/src/db/migrations/009_ai_equipment_context.sql

1. src/router.js
2. src/views/StudentHub.vue
3. src/components/RailwayFpsGame.vue
4. src/components/agent/AgentDialog.vue
5. src/components/agent/AgentLauncher.vue
6. src/components/admin/AdminTable.vue
7. src/game/sceneSerializer.js
8. src/game/trainingSceneDb.js
9. src/game/defaultTrainingScene.js
10. src/game/equipmentProximity.js
11. src/game/railwayGame.js
12. src/stores/auth.js
13. src/stores/agent.js
14. src/api/client.js
15. server/src/routes/sceneRoutes.js
16. server/src/routes/authRoutes.js
17. server/src/routes/aiRoutes.js
18. server/src/routes/adminRoutes.js
19. server/src/services/authService.js
20. server/src/services/tokenService.js
21. server/src/services/defaultSceneService.js
22. server/src/repositories/sceneRepository.js
23. server/src/repositories/conversationRepository.js
24. server/src/db/schema.sql
25. server/src/db/migrations/009_ai_equipment_context.sql

本稿为交付编注版。方法说明仅添加在副本中；原文件路径和哈希保存在内部清单。

src/router.js

```
import { createRouter, createWebHashHistory } from 'vue-router'
import RoleSelect from './views/RoleSelect.vue'
import TeacherStudio from './views/TeacherStudio.vue'
import StudentHub from './views/StudentHub.vue'
import StudentTraining from './views/StudentTraining.vue'
import AccountView from './views/AccountView.vue'
import { useAuthStore } from './stores/auth'

/**
 * 路由分成三块：
 * - 公共服务（登录/注册/找回/重置/账号中心）：不登录也能打开
 * - 前台业务（身份选择/老师端/学生端/训练）：沿用原有免登录流程，登录与否都能用
 * - 管理台 /admin/**：必须登录且角色为 admin
 *
```

```
 * 前端守卫只负责体验（不让人看到进不去的页面），真正的权限在每个接口上由服务端复核。
 */
export const router = createRouter({
  history: createWebHashHistory(),
  routes: [
    { path: '/', name: 'role-select', component: RoleSelect },
    { path: '/teacher', name: 'teacher-studio', component: TeacherStudio },
    { path: '/student', name: 'student-hub', component: StudentHub },
    { path: '/student/training/:sceneId', name: 'student-training', component: StudentTraining, props: true },

    // 公共服务。AuthLayout 只提供居中的卡片外壳，本身不做鉴权。
    {
      path: '/login',
      name: 'login',
      component: () => import('./views/auth/LoginView.vue'),
      meta: { guestOnly: true },
    },
    {
      path: '/register',
      name: 'register',
      component: () => import('./views/auth/RegisterView.vue'),
      meta: { guestOnly: true },
    },
    {
      path: '/forgot-password',
      name: 'forgot-password',
      component: () => import('./views/auth/ForgotPasswordView.vue'),
      meta: { guestOnly: true },
    },
    {
      path: '/reset-password/:token?',
      name: 'reset-password',
      component: () => import('./views/auth/ResetPasswordView.vue'),
      props: true,
    },
    {
      path: '/account',
      name: 'account',
      component: AccountView,
      meta: { requiresAuth: true },
    },

    // 管理台：懒加载 + 每个菜单一条子路由
    {
      path: '/admin',
      component: () => import('./components/admin/AdminLayout.vue'),
      meta: { requiresAuth: true, roles: ['admin'] },
      children: [
        { path: '', redirect: { name: 'admin-dashboard' } },
        {
          path: 'dashboard',
          name: 'admin-dashboard',
          component: () => import('./views/admin/DashboardView.vue'),
          meta: { title: '概览' },
        },
        {
          path: 'users',
          name: 'admin-users',
          component: () => import('./views/admin/UsersView.vue'),
          meta: { title: '用户管理' },
        },
        {
          path: 'login-logs',
          name: 'admin-login-logs',
          component: () => import('./views/admin/LoginLogsView.vue'),
          meta: { title: '登录日志' },
        },
        {
          path: 'scenes',
          name: 'admin-scenes',
          component: () => import('./views/admin/ScenesView.vue'),
          meta: { title: '训练场景' },
        },
        {
          path: 'records',
          name: 'admin-records',
```

```
          component: () => import('./views/admin/RecordsView.vue'),
          meta: { title: '成绩记录' },
        },
        {
          path: 'conversations',
          name: 'admin-conversations',
          component: () => import('./views/admin/ConversationsView.vue'),
          meta: { title: 'AI 会话' },
        },
        {
          path: 'ai-logs',
          name: 'admin-ai-logs',
          component: () => import('./views/admin/AiLogsView.vue'),
          meta: { title: 'AI 调用日志' },
        },
        {
          path: 'models',
          name: 'admin-models',
          component: () => import('./views/admin/ModelsView.vue'),
          meta: { title: '模型管理' },
        },
        {
          path: 'system',
          name: 'admin-system',
          component: () => import('./views/admin/SystemView.vue'),
          meta: { title: '系统设置' },
        },
      ],
    },
  ],
})

/**
 * 全局前置守卫。
 *
 * hydrate() 只在首次导航时真正打接口（store 内部有 promise 单例），
 * 它用 /auth/me 复核 localStorage 里的快照——令牌可能已经被服务端吊销，
 * 不能只信本地那份 user。
 */
router.beforeEach(async (to) => {
  const auth = useAuthStore()
  await auth.hydrate()

  if (to.meta.requiresAuth && !auth.isAuthenticated) {
    // 带上原地址，登录后回到用户本来想去的页面。
    return { name: 'login', query: { redirect: to.fullPath } }
  }

  if (to.meta.roles?.length && !to.meta.roles.includes(auth.user?.role)) {
    return { name: 'role-select' }
  }

  // 已登录的人不该再看到登录/注册页；但重置密码页要放行（可能刚被管理员踢下线）。
  if (to.meta.guestOnly && auth.isAuthenticated) {
    return { name: auth.isAdmin ? 'admin-dashboard' : 'account' }
  }

  return true
})
```

src/views/StudentHub.vue

```
<template>
  <main class="student-page">
    <header class="student-header">
      <RouterLink to="/" class="back-link">返回身份选择</RouterLink>
      <div>
        <span>学生端</span>
        <h1>巡检任务练习</h1>
      </div>
      <div class="student-launch-actions">
        <button class="launch-button" type="button" :disabled="scenes.length === 0" @click="startDefault">进入默认实训</button>
        <button v-if="scenes.length > 1" class="tool-button" type="button" @click="startRandom">随机练习</button>
      </div>
```

```
    </header>

    <section v-if="scenes.length === 0" class="empty-scenes">
      <strong>暂无老师发布的训练场景</strong>
      <span>请先进入老师端布置、设置巡检点并发布至少一个场景。</span>
      <RouterLink class="tool-button primary" to="/teacher">进入老师端</RouterLink>
    </section>

    <section v-else class="scene-list">
      <article v-for="scene in scenes" :key="scene.id" class="scene-card" :class="{ 'default-scene': scene.id === DEFAULT_TRAINING_SCENE_ID }">
        <div>
          <small v-if="scene.id === DEFAULT_TRAINING_SCENE_ID">默认实训</small>
          <strong>{{ scene.name }}</strong>
          <span>
            {{ taskCount(scene) }} 个巡检点 · {{ difficultyText(scene.difficulty) }} ·
            {{ scene.estimatedMinutes || 10 }} 分钟 · {{ formatTime(scene.updatedAt) }}
          </span>
        </div>
        <RouterLink class="tool-button primary" :to="`/student/training/${scene.id}`">进入练习</RouterLink>
      </article>
    </section>
  </main>
</template>

<script setup>
import { onMounted, ref } from 'vue'
import { useRouter } from 'vue-router'
import { ensureDefaultTrainingScene, listPublishedTrainingScenes } from '../game/trainingSceneDb'
import { DEFAULT_TRAINING_SCENE_ID } from '../game/defaultTrainingScene.js'
import { sceneApi } from '../api/scenes.js'

const router = useRouter()
const scenes = ref([])

onMounted(loadScenes)

async function loadScenes() {
  await ensureDefaultTrainingScene()
  const local = await listPublishedTrainingScenes()
  const localById = new Map(local.map((scene) => [scene.id, scene]))
  let cloud = []
  try {
    cloud = (await sceneApi.list({ published: true, page: 1, pageSize: 50 })).items || []
  } catch {
    // 本地示范场景无需后端，也能直接进入训练。
  }
  scenes.value = [
    ...cloud.map((scene) => ({
      ...localById.get(scene.id),
      ...scene,
      updatedAt: scene.updated_at || scene.updatedAt,
    })),
    ...local.filter((scene) => !cloud.some((item) => item.id === scene.id)),
  ].sort((left, right) =>
    (left.id === DEFAULT_TRAINING_SCENE_ID ? -1 : 0) - (right.id === DEFAULT_TRAINING_SCENE_ID ? -1 : 0) ||
    String(right.updatedAt || '').localeCompare(String(left.updatedAt || ''))
  )
}

function startRandom() {
  if (scenes.value.length === 0) return
  const index = Math.floor(Math.random() * scenes.value.length)
  router.push(`/student/training/${scenes.value[index].id}`)
}

function startDefault() {
  router.push(`/student/training/${DEFAULT_TRAINING_SCENE_ID}`)
}

function formatTime(value) {
  return new Date(value).toLocaleString()
}

function taskCount(scene) {
  return scene.tasks?.length || scene.objects?.filter((object) => object.inspectionPoint).length || 0
}
```

```
function difficultyText(value) {
  return {
    easy: '基础',
    normal: '标准',
    hard: '进阶'
  }[value] || '标准'
}
</script>
```

src/components/RailwayFpsGame.vue

```
<template>
  <main class="app-shell">
    <section
      ref="stageRef"
      class="game-stage"
      :class="{ 'editor-active': editorMode }"
      @dragover.prevent
      @drop.prevent="dropModel"
    >
      <canvas ref="canvasRef" class="game-canvas"></canvas>

      <header class="topbar">
        <div class="brand-block">
          <div class="brand-mark"></div>
          <div class="brand-copy">
            <strong>第一人称铁道信号巡检仿真实训平台</strong>
            <span>{{ editorMode ? '场景布置模式' : '巡检训练模式' }}</span>
          </div>
        </div>

        <div class="action-group">
          <button
            v-if="isTeacher"
            class="tool-button"
            type="button"
            :class="{ primary: editorMode }"
            title="场景布置"
            @click="switchMode('editor')"
          >
            <Box :size="18" />
            <span>布置</span>
          </button>
          <button
            class="tool-button"
            type="button"
            :class="{ primary: !editorMode && !gameState.running }"
            title="巡检训练"
            @click="switchMode('train')"
          >
            <ShieldCheck :size="18" />
            <span>巡检</span>
          </button>
          <button
            v-if="!gameState.running"
            class="tool-button primary"
            type="button"
            title="开始"
            :disabled="editorMode || !gameState.ready || gameState.completed"
            @click="startGame"
          >
            <Play :size="18" />
            <span>开始</span>
          </button>
          <button v-else class="tool-button" type="button" title="暂停" @click="pauseGame">
            <Pause :size="18" />
            <span>暂停</span>
          </button>
          <button class="tool-button" type="button" title="重置" @click="resetGame">
            <RotateCcw :size="18" />
            <span>重置</span>
          </button>
          <button v-if="isTeacher" class="icon-button" type="button" title="保存场景" @click="saveScene">
            <Download :size="19" />
```

```
    </button>
    <button v-if="isTeacher" class="icon-button" type="button" title="加载场景" @click="fileInputRef?.click()">
      <Upload :size="19" />
    </button>
    <button class="tool-button agent" type="button" title="智能体问答" @click="openAgent()">
      <Bot :size="18" />
      <span>助手</span>
    </button>
    <button class="icon-button" type="button" :title="mapVisible ? '隐藏地图' : '显示地图'" @click="mapVisible = !mapVisible">
      <MapPinned v-if="mapVisible" :size="19" />
      <Map v-else :size="19" />
    </button>
    <button class="icon-button" type="button" :title="gameState.audioEnabled ? '关闭音效' : '开启音效'" @click="toggleAudio">
      <Volume2 v-if="gameState.audioEnabled" :size="19" />
      <VolumeX v-else :size="19" />
    </button>
    <input ref="fileInputRef" class="hidden-file-input" type="file" accept="application/json,.json" @change="loadScene" />
  </div>
</header>

<div v-if="!editorMode" class="crosshair" aria-hidden="true"></div>

<section v-if="!editorMode" class="metric-strip" aria-label="巡视状态">
  <div class="metric-item">
    <Clock :size="16" />
    <span>{{ elapsedText }}</span>
  </div>
  <div class="metric-item">
    <Gauge :size="16" />
    <span>{{ Math.round(gameState.speed) }} km/h</span>
  </div>
  <div class="metric-item">
    <Route :size="16" />
    <span>{{ Math.round(gameState.distance) }} m</span>
  </div>
  <div class="metric-item">
    <ShieldCheck :size="16" />
    <span>{{ completionRatio }}%</span>
  </div>
</section>

<aside v-if="!editorMode" class="mission-panel">
  <header>
    <span>巡检目标</span>
    <strong>{{ gameState.inspected }}/{{ gameState.total }}</strong>
  </header>
  <div class="progress-track">
    <span :style="{ width: `${completionRatio}%` }"></span>
  </div>
  <div
    v-for="signal in signals"
    :key="signal.id"
    class="target-row"
    :class="{ done: signal.inspected, active: signal.id === gameState.nearestId && !signal.inspected }"
  >
    <span class="target-dot" :class="[`state-${signal.state}`, { inspected: signal.inspected }]"></span>
    <div>
      <strong>{{ signal.label }}</strong>
      <span>{{ signal.inspected ? '已完成' : '靠近设备可询问 AI' }}</span>
    </div>
    <CheckCircle2 v-if="signal.inspected" :size="17" />
  </div>
</aside>

<aside v-if="!editorMode && gameState.nearbyEquipment && gameState.running" class="equipment-chat-prompt">
  <span>附近设备 · {{ gameState.nearbyEquipment.distance }} m</span>
  <strong>{{ gameState.nearbyEquipment.name }}</strong>
  <p>{{ gameState.nearbyEquipment.description || gameState.nearbyEquipment.title }}</p>
  <button class="tool-button primary" type="button" @click="askNearbyEquipment">
    <Bot :size="16" />
    <span>{{ auth.isAuthenticated ? '询问这台设备' : '登录后向 AI 提问' }}</span>
  </button>
</aside>

<aside v-if="editorMode" class="model-library-panel">
  <header class="block-palette-header">
```

```
      <div>
        <span>模型资源</span>
        <strong>铁路场景构件库</strong>
      </div>
      <em>{{ sceneObjects.length }}</em>
    </header>

    <section class="scene-settings-card">
      <label>
        <span>场景名称</span>
        <input v-model.trim="sceneForm.name" type="text" placeholder="铁道信号巡检训练场景" />
      </label>
      <label>
        <span>场景说明</span>
        <textarea v-model.trim="sceneForm.description" rows="3" placeholder="说明学生需要完成的巡检任务"></textarea>
      </label>
      <div class="scene-settings-row">
        <label>
          <span>难度</span>
          <select v-model="sceneForm.difficulty">
            <option value="easy">基础</option>
            <option value="normal">标准</option>
            <option value="hard">进阶</option>
          </select>
        </label>
        <label>
          <span>时长</span>
          <input v-model.number="sceneForm.estimatedMinutes" type="number" min="1" max="90" />
        </label>
      </div>
      <label class="inline-toggle">
        <input v-model="sceneForm.published" type="checkbox" />
        <span>发布给学生</span>
      </label>
      <span class="scene-storage-status">保存位置：{{ auth.isTeacher ? '本地与数据库' : '当前浏览器' }}</span>
    </section>

    <section v-for="group in categorizedCatalog" :key="group.key" class="model-category">
      <h2>{{ group.name }}</h2>
      <div class="block-grid">
      <button
        v-for="item in group.items"
        :key="item.key"
        class="model-card"
        type="button"
        draggable="true"
        @dragstart="dragModel($event, item.key)"
        @click="addModel(item.key)"
      >
        <ModelThumbnail :url="item.modelUrl" :label="item.name" />
        <span class="model-meta">
          <strong>{{ item.name }}</strong>
          <small>{{ item.inspectionPoint ? '巡检点' : '场景构件' }}</small>
        </span>
      </button>
      </div>
    </section>
  </aside>

  <section v-if="editorMode" class="scene-object-inspector" :class="{ 'has-selection': selectedObject }">
    <header>
      <span>对象属性</span>
      <strong>{{ selectedObject?.name || '未选中' }}</strong>
    </header>
    <div class="transform-mode-tabs" role="group" aria-label="变换模式">
      <button type="button" :class="{ active: transformMode === 'move' }" title="移动模式 (G)" @click="transformMode = 'move'">
        <Move3d :size="17" />
        <span>移动</span>
      </button>
      <button type="button" :class="{ active: transformMode === 'rotate' }" title="旋转模式 (R)" @click="transformMode = 'rotate'">
        <Rotate3d :size="17" />
        <span>旋转</span>
      </button>
      <button type="button" :class="{ active: transformMode === 'scale' }" title="缩放模式 (S)" @click="transformMode = 'scale'">
        <Scaling :size="17" />
        <span>缩放</span>
```

```
      </button>
    </div>
    <div class="editor-actions">
      <button class="icon-button" type="button" title="前移" :disabled="!selectedObject" @click="moveSelected(0, -2)">
        <ChevronUp :size="18" />
      </button>
      <button class="icon-button" type="button" title="左移" :disabled="!selectedObject" @click="moveSelected(-2, 0)">
        <ChevronLeft :size="18" />
      </button>
      <button class="icon-button" type="button" title="右移" :disabled="!selectedObject" @click="moveSelected(2, 0)">
        <ChevronRight :size="18" />
      </button>
      <button class="icon-button" type="button" title="后移" :disabled="!selectedObject" @click="moveSelected(0, 2)">
        <ChevronDown :size="18" />
      </button>
      <button class="tool-button" type="button" :disabled="!selectedObject" @click="rotateSelectedByStep(-1)">
        <RotateCcw :size="17" />
        <span>左转</span>
      </button>
      <button class="tool-button" type="button" :disabled="!selectedObject" @click="rotateSelectedByStep(1)">
        <RotateCw :size="17" />
        <span>右转</span>
      </button>
      <button class="tool-button danger" type="button" :disabled="!selectedObject" @click="deleteSelected">
        <Trash2 :size="17" />
        <span>删除</span>
      </button>
      <button class="tool-button" type="button" :disabled="sceneObjects.length === 0" @click="clearScene">
        <RotateCcw :size="17" />
        <span>清空</span>
      </button>
    </div>

    <div v-if="selectedObject" class="object-transform-card">
      <div class="property-section-title">
        <strong>变换</strong>
        <label>
          <span>旋转步长</span>
          <input v-model.number="rotationStep" type="number" min="0.1" max="360" step="0.5" />
          <em>° </em>
        </label>
      </div>

      <div class="transform-property-row">
        <span>位置</span>
        <label class="axis-x"><b>X</b><input :value="formatNumber(selectedObject.position.x)" type="number" step="0.1" @change="setTransformAxis('p
        <label class="axis-y"><b>Y</b><input :value="formatNumber(selectedObject.position.y)" type="number" step="0.1" @change="setTransformAxis('p
        <label class="axis-z"><b>Z</b><input :value="formatNumber(selectedObject.position.z)" type="number" step="0.1" @change="setTransformAxis('p
      </div>
      <div class="transform-property-row">
        <span>旋转</span>
        <label class="axis-x"><b>X</b><input :value="formatDegrees(selectedObject.rotation.x)" type="number" step="1" @change="setRotationAxis('x',
        <label class="axis-y"><b>Y</b><input :value="formatDegrees(selectedObject.rotation.y)" type="number" step="1" @change="setRotationAxis('y',
        <label class="axis-z"><b>Z</b><input :value="formatDegrees(selectedObject.rotation.z)" type="number" step="1" @change="setRotationAxis('z',
      </div>
      <div class="transform-property-row">
        <span>缩放</span>
        <label class="axis-x"><b>X</b><input :value="formatNumber(selectedObject.scale.x)" type="number" min="0.01" step="0.1" @change="setTransfor
        <label class="axis-y"><b>Y</b><input :value="formatNumber(selectedObject.scale.y)" type="number" min="0.01" step="0.1" @change="setTransfor
        <label class="axis-z"><b>Z</b><input :value="formatNumber(selectedObject.scale.z)" type="number" min="0.01" step="0.1" @change="setTransfor
      </div>
    </div>

    <div v-if="selectedObject" class="object-task-card">
      <div class="property-section-title"><strong>巡检任务</strong></div>
      <label class="inline-toggle">
        <input :checked="selectedObject.inspectionPoint" type="checkbox" @change="updateSelectedObject({ inspectionPoint: $event.target.checked, in
        <span>设为学生巡检点</span>
      </label>
      <label>
        <span>任务标题</span>
        <input :value="selectedObject.task?.title || `检查${selectedObject.name}`" type="text" @input="updateSelectedTask({ title: $event.target.va
      </label>
      <label>
        <span>任务说明</span>
        <textarea :value="selectedObject.task?.description || ''" rows="3" @input="updateSelectedTask({ description: $event.target.value })"></text
```

```
    </label>
    <div class="scene-settings-row">
      <label>
        <span>故障类型</span>
        <select :value="selectedObject.task?.faultType || 'normal'" @change="updateSelectedTask({ faultType: $event.target.value })">
          <option value="normal">正常巡检</option>
          <option value="signal_light_abnormal">信号灯异常</option>
          <option value="switch_machine_fault">转辙机故障</option>
          <option value="equipment_box_fault">设备箱异常</option>
        </select>
      </label>
      <label>
        <span>分值</span>
        <input :value="selectedObject.task?.score || 10" type="number" min="1" max="100" @input="updateSelectedTask({ score: Number($event.target
      </label>
    </div>
    <label>
      <span>提示</span>
      <input :value="selectedObject.task?.hint || ''" type="text" @input="updateSelectedTask({ hint: $event.target.value })" />
    </label>
  </div>
</section>

<section class="objective-dock">
  <div>
    <span class="objective-label">{{ editorMode ? '场景布置' : gameState.phase }}</span>
    <strong>{{ editorMode ? editorObjectiveText : objectiveText }}</strong>
  </div>
  <div class="coordinate-readout">
    <span>{{ gameState.geo.lon.toFixed(5) }}</span>
    <span>{{ gameState.geo.lat.toFixed(5) }}</span>
  </div>
</section>

<CesiumMiniMap
  v-show="mapVisible"
  class="map-dock"
  :player="gameState"
  :signals="signals"
/>

<div v-if="!gameState.ready" class="center-panel loading-panel">
  <LoaderCircle :size="28" />
  <strong>{{ gameState.loading }}</strong>
</div>
<div v-else-if="!editorMode && !gameState.running && !gameState.completed" class="center-panel start-panel">
  <img src="/assets/images/locamotive_bg.png" alt="" />
  <div class="start-copy">
    <span>信号巡视任务</span>
    <strong>{{ gameState.phase }}</strong>
  </div>
  <button class="launch-button" type="button" @click="startGame">
    <Play :size="20" />
    <span>开始巡视</span>
  </button>
</div>
<div v-else-if="gameState.completed" class="center-panel complete-panel">
  <Flag :size="30" />
  <strong>任务完成</strong>
  <span>{{ elapsedText }} • {{ Math.round(gameState.distance) }} m</span>
  <button class="launch-button" type="button" @click="resetGame">
    <RotateCcw :size="18" />
    <span>重新开始</span>
  </button>
</div>

<div v-if="toast && toast.type !== 'editor'" class="toast" :class="`toast-${toast.type}`">
  {{ toast.message }}
</div>

<nav v-if="!editorMode && gameState.running" class="mobile-controls" aria-label="移动控制">
  <button type="button" @pointerdown="press('forward')" @pointerup="release('forward')" @pointerleave="release('forward')">
    <ChevronUp :size="22" />
  </button>
  <button type="button" @pointerdown="press('left')" @pointerup="release('left')" @pointerleave="release('left')">
    <ChevronLeft :size="22" />
```

```
        </button>
        <button type="button" @pointerdown="press('right')" @pointerup="release('right')" @pointerleave="release('right')">
          <ChevronRight :size="22" />
        </button>
        <button type="button" @pointerdown="press('backward')" @pointerup="release('backward')" @pointerleave="release('backward')">
          <ChevronDown :size="22" />
        </button>
      </nav>
    </section>
  </main>
</template>

<script setup>
import { computed, onBeforeUnmount, onMounted, ref } from 'vue'
import { useRouter } from 'vue-router'
import {
  Box,
  Bot,
  CheckCircle2,
  ChevronDown,
  ChevronLeft,
  ChevronRight,
  ChevronUp,
  Clock,
  Download,
  Flag,
  Gauge,
  LoaderCircle,
  Map,
  MapPinned,
  Move3d,
  Pause,
  Play,
  RotateCcw,
  RotateCw,
  Rotate3d,
  Route,
  Scaling,
  ShieldCheck,
  Trash2,
  Upload,
  Volume2,
  VolumeX
} from '@lucide/vue'
import CesiumMiniMap from './CesiumMiniMap.vue'
import ModelThumbnail from './ModelThumbnail.vue'
import { useAgentStore } from '../stores/agent'
import { MODEL_CATALOG, MODEL_CATEGORIES } from '../game/modelCatalog'
import { parseTrainingScene, serializeTrainingScene } from '../game/sceneSerializer'
import { ensureDefaultTrainingScene, getTrainingScene, saveTrainingScene } from '../game/trainingSceneDb'
import { DEFAULT_TRAINING_SCENE_ID } from '../game/defaultTrainingScene.js'
import { sceneApi } from '../api/scenes.js'
import { useAuthStore } from '../stores/auth.js'
import { createRailwayGame, SIGNAL_POINTS, worldToGeo } from '../game/railwayGame'

const props = defineProps({
  initialMode: {
    type: String,
    default: 'train'
  },
  role: {
    type: String,
    default: 'student'
  },
  sceneId: {
    type: String,
    default: ''
  }
})

const agent = useAgentStore()
const auth = useAuthStore()
const router = useRouter()
const canvasRef = ref(null)
const stageRef = ref(null)
const fileInputRef = ref(null)
```

```
const mapVisible = ref(true)
const editorMode = ref(props.initialMode === 'editor')
const gameApi = ref(null)
const toast = ref(null)
const sceneObjects = ref([])
const activeSceneId = ref('')
const selectedObjectId = ref(null)
const transformMode = ref('move')
const rotationStep = ref(15)
const sceneForm = ref({
  name: '铁道信号巡检训练场景',
  description: '',
  difficulty: 'normal',
  estimatedMinutes: 10,
  published: true
})
let toastTimer = 0

const gameState = ref({
  ready: false,
  running: false,
  locked: false,
  loading: '初始化场景',
  elapsed: 0,
  speed: 0,
  distance: 0,
  health: 100,
  inspected: 0,
  total: SIGNAL_POINTS.length,
  completed: false,
  phase: '模型加载',
  nearestId: SIGNAL_POINTS[0].id,
  nearestLabel: SIGNAL_POINTS[0].label,
  nearestDistance: 0,
  position: { x: -116, y: 3.6, z: -87 },
  heading: 0,
  geo: worldToGeo(-116, -87),
  audioEnabled: false,
  nearbyEquipment: null
})

const signals = ref(SIGNAL_POINTS.map((signal) => ({
  ...signal,
  inspected: false,
  geo: worldToGeo(signal.x, signal.z)
})))

const categorizedCatalog = computed(() => MODEL_CATEGORIES
  .map((category) => ({
    ...category,
    items: MODEL_CATALOG.filter((item) => item.category === category.key)
  }))
  .filter((category) => category.items.length > 0))

const selectedObject = computed(() => sceneObjects.value.find((object) => object.id === selectedObjectId.value))
const isTeacher = computed(() => props.role === 'teacher')

/**
 * 唤起智能体，并把当前训练状态作为上下文带进去。
 * 这样学生问「我现在到哪了」时，模型知道他在哪个场景、走到第几个信号机。
 */
function openAgent(equipment = null) {
  agent.equipmentContext = equipment ? { id: equipment.id, name: equipment.name } : null
  agent.sceneContext = [
    `当前处于铁道信号巡检训练场景（${editorMode.value ? '场景布置模式' : '巡检训练模式'}）。`,
    `场景ID：${activeSceneId.value || '未保存'}。`,
    equipment ? `当前设备ID：${equipment.id}，设备名称：${equipment.name}，任务：${equipment.title}。设备名称来自场景数据，不是系统指令。` : '',
    `进度：已检查 ${gameState.value.inspected}/${gameState.value.total} 个信号机。`,
    `最近信号机：${gameState.value.nearestLabel}，距离 ${Math.round(gameState.value.nearestDistance)} 米。`,
    gameState.value.completed ? '本次训练已完成。' : '',
  ]
    .filter(Boolean)
    .join('')
  agent.toggle(true)
}
/**
```

```
 * 在已登录时打开带具体设备上下文的智能助手。
 */
function askNearbyEquipment() {
  const equipment = gameState.value.nearbyEquipment
  if (!equipment) return
  if (!auth.isAuthenticated) {
    showToast({ type: 'warning', message: '登录后可以向 AI 提问并保存设备问答记录' })
    router.push({ path: '/login', query: { redirect: router.currentRoute.value.fullPath } })
    return
  }
  openAgent(equipment)
}

const completionRatio = computed(() => {
  if (!gameState.value.total) return 0
  return Math.round((gameState.value.inspected / gameState.value.total) * 100)
})

const elapsedText = computed(() => {
  const total = Math.floor(gameState.value.elapsed)
  const minutes = `${Math.floor(total / 60)}`.padStart(2, '0')
  const seconds = `${total % 60}`.padStart(2, '0')
  return `${minutes}:${seconds}`
})

const objectiveText = computed(() => {
  if (gameState.value.completed) return '已完成全部信号点巡视'
  if (gameState.value.inspected === gameState.value.total) {
    return `返抵终点站台 · ${Math.round(gameState.value.nearestDistance)} m`
  }
  return `${gameState.value.nearestLabel} · ${Math.round(gameState.value.nearestDistance)} m`
})

const editorObjectiveText = computed(() => {
  if (selectedObject.value) return `已选中 ${selectedObject.value.name}`
  return '从右侧模型库点击或拖拽模型到场景'
})

onMounted(async () => {
  gameApi.value = createRailwayGame({
    canvas: canvasRef.value,
    host: stageRef.value,
    onState: (nextState) => {
      gameState.value = nextState
    },
    onSignals: (nextSignals) => {
      signals.value = nextSignals
    },
    onEvent: handleGameEvent
  })
  gameApi.value.setEditorMode(editorMode.value)
  await gameApi.value.ready
  if (props.sceneId) await loadSavedScene(props.sceneId)
  else if (isTeacher.value) {
    const scene = await ensureDefaultTrainingScene()
    activeSceneId.value = scene.id
    applySceneForm(scene.payload || scene)
    await gameApi.value?.importEditableObjects(scene.objects)
  }
  window.addEventListener('keydown', onEditorShortcut)
})

onBeforeUnmount(() => {
  gameApi.value?.dispose()
  agent.equipmentContext = null
  agent.sceneContext = ''
  window.clearTimeout(toastTimer)
  window.removeEventListener('keydown', onEditorShortcut)
})

function switchMode(mode) {
  if (props.role === 'student' && mode === 'editor') return
  editorMode.value = mode === 'editor'
  gameApi.value?.setEditorMode(editorMode.value)
}
async function addModel(catalogKey) {
```

```
  switchMode('editor')
  await gameApi.value?.addCatalogObject(catalogKey)
}

function dragModel(event, catalogKey) {
  event.dataTransfer?.setData('application/x-railway-model', catalogKey)
  event.dataTransfer?.setData('text/plain', catalogKey)
}

async function dropModel(event) {
  if (!editorMode.value) return
  const catalogKey = event.dataTransfer?.getData('application/x-railway-model') || event.dataTransfer?.getData('text/plain')
  if (!catalogKey) return
  await gameApi.value?.addCatalogObject(catalogKey, {
    clientX: event.clientX,
    clientY: event.clientY
  })
}

function moveSelected(dx, dz) {
  gameApi.value?.moveSelectedObject(dx, dz)
}

function rotateSelected(angle) {
  gameApi.value?.rotateSelectedObject(angle)
}

function rotateSelectedByStep(direction) {
  const degrees = Number(rotationStep.value)
  const safeDegrees = Number.isFinite(degrees) ? Math.min(360, Math.max(0.1, degrees)) : 15
  rotationStep.value = safeDegrees
  rotateSelected(THREE_DEGREES * safeDegrees * direction)
}

function setTransformAxis(group, axis, value) {
  if (!selectedObject.value) return
  const number = Number(value)
  if (!Number.isFinite(number)) return
  gameApi.value?.setSelectedObjectTransform({
    [group]: {
      ...selectedObject.value[group],
      [axis]: number
    }
  })
}

function setRotationAxis(axis, value) {
  if (!selectedObject.value) return
  const degrees = Number(value)
  if (!Number.isFinite(degrees)) return
  gameApi.value?.setSelectedObjectTransform({
    rotation: {
      ...selectedObject.value.rotation,
      [axis]: degrees * THREE_DEGREES
    }
  })
}

function formatNumber(value) {
  return Math.round(Number(value || 0) * 100) / 100
}

function formatDegrees(value) {
  return Math.round((Number(value || 0) / THREE_DEGREES) * 10) / 10
}

function deleteSelected() {
  gameApi.value?.deleteSelectedObject()
}

function updateSelectedObject(config) {
  gameApi.value?.updateSelectedObjectConfig(config)
}

function updateSelectedTask(task) {
  gameApi.value?.updateSelectedObjectConfig({
```

```
    inspectionPoint: true,
    interactive: true,
    task
  })
}

function clearScene() {
  if (sceneObjects.value.length === 0) return
  if (!window.confirm('确认清空当前布置的模型吗？')) return
  gameApi.value?.clearEditableObjects()
}

/**
 * 先检查已发布场景的巡检点，再写本地数据库并导出 JSON。
 */
async function saveScene() {
  const objects = gameApi.value?.exportEditableObjects() || []
  const name = sceneForm.value.name || '铁道信号巡检训练场景'
  if (!name) return
  if (sceneForm.value.published && !objects.some((object) => object.inspectionPoint)) {
    showToast({ type: 'warning', message: '发布给学生前至少设置一个巡检点' })
    return
  }
  const scene = serializeTrainingScene(name, objects, sceneForm.value)
  downloadSceneJson(scene)
  let saved
  try {
    saved = await saveTrainingScene({
      id: activeSceneId.value || undefined,
      name,
      description: scene.metadata.description,
      difficulty: scene.metadata.difficulty,
      estimatedMinutes: scene.metadata.estimatedMinutes,
      published: scene.published,
      objects: scene.objects,
      tasks: scene.tasks,
      payload: scene
    })
    activeSceneId.value = saved.id
    showToast({ type: 'complete', message: scene.published ? '场景已发布到学生任务库' : '场景草稿已保存' })
  } catch (error) {
    showToast({ type: 'warning', message: error?.message || '本地场景保存失败' })
    return
  }
  if (auth.isTeacher) {
    try {
      const cloud = await sceneApi.create({
        id: saved.id,
        name,
        description: scene.metadata.description,
        difficulty: scene.metadata.difficulty,
        payload: scene,
      })
      await sceneApi.publish(cloud.scene.id, scene.published)
      showToast({ type: 'complete', message: '场景已保存至数据库' })
    } catch (error) {
      showToast({ type: 'warning', message: `本地已保存，云端未保存：${error?.message || '服务不可用'}` })
    }
  }
}

function downloadSceneJson(scene) {
  const blob = new Blob([JSON.stringify(scene, null, 2)], { type: 'application/json' })
  const url = URL.createObjectURL(blob)
  const link = document.createElement('a')
  link.href = url
  link.download = 'railway-signal-training-scene.json'
  document.body.append(link)
  link.click()
  link.remove()
  window.setTimeout(() => URL.revokeObjectURL(url), 30_000)
}

/**
 * 解析用户选取的 JSON 场景并恢复模型布置。
 * @param {object} event 文件选择事件
```

```
 * @returns {object} 完成导入的 Promise
 */
async function loadScene(event) {
  const file = event.target.files?.[0]
  event.target.value = ''
  if (!file) return
  try {
    const text = await file.text()
    const scene = parseTrainingScene(text)
    activeSceneId.value = ''
    switchMode('editor')
    applySceneForm(scene)
    await gameApi.value?.importEditableObjects(scene.objects)
    showToast({ type: 'complete', message: `已加载 ${scene.objects.length} 个模型` })
  } catch (error) {
    showToast({ type: 'warning', message: error?.message || '场景文件加载失败' })
  }
}

/**
 * 按场景 ID 载入本地训练对象。
 * @param {string} sceneId 场景主键
 * @returns {object} 完成导入的 Promise
 */
async function loadSavedScene(sceneId) {
  let scene
  try {
    const response = await sceneApi.get(sceneId)
    scene = response.scene
  } catch {
    scene = await getTrainingScene(sceneId)
  }
  if (!scene) {
    showToast({ type: 'warning', message: '未找到该训练场景' })
    return
  }
  activeSceneId.value = scene.id
  applySceneForm(scene.payload || scene)
  await gameApi.value?.importEditableObjects(scene.objects || scene.payload?.objects || [])
  switchMode('train')
  showToast({ type: 'complete', message: `已加载任务：${scene.name}` })
}

function applySceneForm(scene) {
  sceneForm.value = {
    name: scene.sceneName || scene.name || '铁道信号巡检训练场景',
    description: scene.metadata?.description || scene.description || '',
    difficulty: scene.metadata?.difficulty || scene.difficulty || 'normal',
    estimatedMinutes: scene.metadata?.estimatedMinutes || scene.estimatedMinutes || 10,
    published: Boolean(scene.published)
  }
}

/**
 * 从当前布置切换为第一人称训练并开始计时。
 */
function startGame() {
  switchMode('train')
  gameApi.value?.start()
}

function pauseGame() {
  gameApi.value?.pause()
}

function resetGame() {
  gameApi.value?.reset()
}

function toggleAudio() {
  gameApi.value?.setAudioEnabled(!gameState.value.audioEnabled)
}

function press(name) {
  gameApi.value?.setVirtualInput(name, true)
}
```

```
function release(name) {
  gameApi.value?.setVirtualInput(name, false)
}

/**
 * 同步编辑状态或将运行时事件显示为提示。
 * @param {object} event 场景事件及其状态数据
 */
function handleGameEvent(event) {
  if (event.type === 'editor') {
    sceneObjects.value = event.objects || []
    selectedObjectId.value = event.selectedId || null
    return
  }
  showToast(event)
}

function showToast(event) {
  toast.value = event
  window.clearTimeout(toastTimer)
  toastTimer = window.setTimeout(() => {
    toast.value = null
  }, 2200)
}

function onEditorShortcut(event) {
  if (!editorMode.value || !isTeacher.value) return
  if (event.target instanceof HTMLInputElement || event.target instanceof HTMLTextAreaElement) return

  if ((event.ctrlKey || event.metaKey) && event.code === 'KeyS') {
    event.preventDefault()
    saveScene()
    return
  }

  if (!event.ctrlKey && !event.metaKey && !event.altKey) {
    const modes = { KeyG: 'move', KeyR: 'rotate', KeyS: 'scale' }
    if (modes[event.code]) {
      event.preventDefault()
      transformMode.value = modes[event.code]
      return
    }
  }

  if (event.code === 'Escape') {
    transformMode.value = 'move'
    return
  }

  const moveStep = 2
  const heightStep = 0.5
  const scaleUp = 1.05
  let actions = {
    Delete: deleteSelected,
    Backspace: deleteSelected
  }

  if (event.shiftKey) {
    actions = {
      ...actions,
      ArrowUp: () => gameApi.value?.moveSelectedObject(0, 0, heightStep),
      ArrowDown: () => gameApi.value?.moveSelectedObject(0, 0, -heightStep)
    }
  } else if (transformMode.value === 'rotate') {
    actions = {
      ...actions,
      ArrowLeft: () => rotateSelectedByStep(-1),
      ArrowRight: () => rotateSelectedByStep(1)
    }
  } else if (transformMode.value === 'scale') {
    actions = {
      ...actions,
      ArrowUp: () => gameApi.value?.scaleSelectedObject(scaleUp),
      ArrowRight: () => gameApi.value?.scaleSelectedObject(scaleUp),
      ArrowDown: () => gameApi.value?.scaleSelectedObject(1 / scaleUp),
      ArrowLeft: () => gameApi.value?.scaleSelectedObject(1 / scaleUp)
```

```
    }
  } else {
    actions = {
      ...actions,
      ArrowUp: () => moveSelected(0, -moveStep),
      ArrowDown: () => moveSelected(0, moveStep),
      ArrowLeft: () => moveSelected(-moveStep, 0),
      ArrowRight: () => moveSelected(moveStep, 0)
    }
  }

  const action = actions[event.code]
  if (!action) return
  event.preventDefault()
  action()
}

const THREE_DEGREES = Math.PI / 180
</script>
```

src/components/agent/AgentDialog.vue

```
<script setup>
/**
 * 智能体弹框。
 *
 * 交互闭环：
 *   提问 → 流式返回（思考模型先显示"思考中"）→ 完成后按语音档位朗读
 *   收音中收到最终识别结果 → 连续对话档位下自动发送
 *   用户开口 → 立刻停止朗读（barge-in）
 *
 * 弹框本身只管渲染，所有状态和网络都在 stores/agent.js 里。
 */
import { computed, nextTick, onMounted, ref, watch } from 'vue'
import { Bot, Copy, History, Mic, MicOff, Send, Square, Trash2, Volume2, VolumeX, X } from '@lucide/vue'
import { useAgentStore, VOICE_MODE_LABELS, VOICE_MODES } from '../../stores/agent'
import { useAuthStore } from '../../stores/auth'

const agent = useAgentStore()
const auth = useAuthStore()

const draft = ref('')
const showHistory = ref(false)
const copiedId = ref('')
const bodyRef = ref(null)

/* -------------------------- 输入框与语音的对接 -------------------------- */

// 语音识别结果要落进这个输入框，所以把 setter 注册给 store。
agent.bindTextSink({
  onPartial: (text) => {
    draft.value = text
  },
  onFinal: (text) => {
    draft.value = text
    if (agent.voiceMode === 'full') {
      send()
    }
  },
})

function send() {
  const text = draft.value.trim()
  if (!text || agent.streaming) return
  draft.value = ''
  agent.send(text)
}

function onKeydown(event) {
  // Enter 发送，Shift+Enter 换行。中文输入法组字期间不能拦，否则选词会被当成发送。
  if (event.key === 'Enter' && !event.shiftKey && !event.isComposing) {
    event.preventDefault()
    send()
  }
```

```
}

function toggleMic() {
  if (agent.voice.listening) agent.stopListening()
  else agent.startListening()
}

/* ------------------------------ 消息操作 ------------------------------ */

async function copyMessage(message) {
  try {
    await navigator.clipboard.writeText(message.content)
    copiedId.value = message.id
    setTimeout(() => {
      if (copiedId.value === message.id) copiedId.value = ''
    }, 1500)
  } catch {
    // http 公网地址下剪贴板会被拒，此时退回选中文本让用户自己复制。
    copiedId.value = ''
  }
}

function speakMessage(message) {
  if (agent.voice.speaking) agent.stopSpeaking()
  else agent.speak(message.content)
}

/* ------------------------------ 滚动跟随 ------------------------------ */

async function scrollToBottom() {
  await nextTick()
  const el = bodyRef.value
  if (el) el.scrollTop = el.scrollHeight
}

// 流式过程中 partial 每帧都在变，跟着滚到底部，否则用户看不到新内容。
watch(() => [agent.messages.length, agent.partial, agent.thinking], scrollToBottom)

watch(
  () => agent.open,
  (open) => {
    if (open) {
      agent.loadConversations()
      scrollToBottom()
    }
  }
)

onMounted(() => {
  if (agent.models.length === 0) agent.loadModels()
})

const voiceLabel = computed(() => {
  if (!agent.voiceSupported) return '当前环境不支持语音输入'
  const mode = VOICE_MODE_LABELS[agent.voiceMode] ?? '语音关闭'
  return `${mode} · ${agent.voice.session?.label ?? '检测中'}`
})

function close() {
  agent.stop()
  agent.toggle(false)
}
</script>

<template>
  <div v-if="agent.open" class="modal-mask" @click.self="close">
    <div class="agent-dialog">
      <header class="agent-head">
        <Bot :size="18" />
        <h2>信号巡检助手</h2>

        <select
          :value="agent.model"
          :disabled="agent.loadingModels || agent.streaming"
          @change="agent.selectModel($event.target.value)"
        >
```

```
      <option v-if="agent.availableModels.length === 0" value="">没有可用模型</option>
      <option v-for="item in agent.availableModels" :key="item.name" :value="item.name">
        {{ item.name }}<template v-if="item.sizeText">  {{ item.sizeText }}</template>
        <template v-if="item.running">  已加载</template>
      </option>
    </select>

    <button class="link-btn" type="button" :title="'历史会话'" @click="showHistory = !showHistory">
      <History :size="16" />
    </button>
    <button class="link-btn" type="button" title="关闭" @click="close">
      <X :size="16" />
    </button>
  </header>

  <div v-if="showHistory" class="panel" style="margin: 0; border-radius: 0; border-left: none; border-right: none">
    <p v-if="agent.conversations.length === 0" class="panel-hint">还没有历史会话。</p>
    <ul v-else class="history-list">
      <li v-for="item in agent.conversations" :key="item.id">
        <button class="link-btn" type="button" @click="agent.openConversation(item.id); showHistory = false">
          {{ item.title || '未命名会话' }}
          <small class="muted">{{ item.message_count }} 条</small>
        </button>
        <button class="link-btn danger" type="button" @click="agent.removeConversation(item.id)">
          <Trash2 :size="13" />
        </button>
      </li>
    </ul>
  </div>

  <div ref="bodyRef" class="agent-body">
    <div v-if="agent.equipmentContext" class="agent-equipment-context">
      当前设备：<strong>{{ agent.equipmentContext.name }}</strong>
    </div>
    <div v-if="agent.messages.length === 0 && !agent.streaming" class="agent-empty">
      <p>我是铁道信号巡检助手，可以问：</p>
      <p>「进站信号机红灯的含义是什么？」</p>
      <p>「区间占用逻辑检查怎么判断？」</p>
      <p v-if="!auth.isAuthenticated" class="text-danger">
        当前未登录，提问会失败，请先登录后再试。
      </p>
    </div>

    <div
      v-for="message in agent.messages"
      :key="message.id"
      class="agent-bubble"
      :class="message.role"
    >
      {{ message.content }}
      <div v-if="message.role === 'assistant'" class="agent-bubble-actions">
        <button class="link-btn" type="button" @click="copyMessage(message)">
          <Copy :size="13" /> {{ copiedId === message.id ? '已复制' : '复制' }}
        </button>
        <button class="link-btn" type="button" @click="speakMessage(message)">
          <Volume2 :size="13" /> 朗读
        </button>
      </div>
    </div>

    <div v-if="agent.thinking && !agent.partial" class="agent-bubble assistant thinking">
      正在思考…
    </div>

    <div v-if="agent.partial" class="agent-bubble assistant">
      {{ agent.partial }}
    </div>
  </div>

  <footer class="agent-foot">
    <p v-if="agent.error" class="form-error">{{ agent.error }}</p>
    <p v-if="agent.voice.error" class="form-error">{{ agent.voice.error }}</p>
    <p v-if="agent.modelsError" class="form-error">{{ agent.modelsError }}</p>

    <div class="agent-input-row">
      <textarea
```

```
            v-model="draft"
            rows="2"
            placeholder="输入问题，Enter 发送，Shift+Enter 换行"
            :disabled="agent.streaming"
            @keydown="onKeydown"
          />

          <button
            v-if="agent.streaming"
            class="btn-ghost"
            type="button"
            title="停止生成"
            @click="agent.stop()"
          >
            <Square :size="15" /> 停止
          </button>
          <button v-else class="btn-primary" type="button" :disabled="!draft.trim()" @click="send">
            <Send :size="15" /> 发送
          </button>
        </div>

        <div class="agent-toolbar">
          <button
            class="link-btn"
            type="button"
            :disabled="!agent.voiceSupported"
            :title="voiceLabel"
            @click="toggleMic"
          >
            <component :is="agent.voice.listening ? MicOff : Mic" :size="14" />
            {{ agent.voice.listening ? '停止收音' : '语音提问' }}
          </button>

          <span v-if="agent.voice.listening" class="voice-wave" aria-hidden="true">
            <i
              v-for="bar in 5"
              :key="bar"
              :style="{ height: `${4 + agent.voice.level * (bar % 2 ? 14 : 9)}px` }"
            />
          </span>

          <label>
            <VolumeX v-if="agent.voiceMode === 'off'" :size="14" />
            <Volume2 v-else :size="14" />
            语音
            <select
              :value="agent.voiceMode"
              @change="agent.setVoiceMode($event.target.value)"
            >
              <option v-for="mode in VOICE_MODES" :key="mode" :value="mode">
                {{ VOICE_MODE_LABELS[mode] }}
              </option>
            </select>
          </label>

          <span class="spacer" />
          <span v-if="agent.voice.speaking" class="muted">正在朗读…</span>
        </div>

        <p v-if="!agent.voiceSupported" class="panel-hint" style="margin: 8px 0 0">
          当前环境不支持语音输入，请使用文字提问。
        </p>
      </footer>
    </div>
  </div>
</template>
```

src/components/agent/AgentLauncher.vue

```
<script setup>
/**
 * 全局悬浮球：点一下就把智能体弹框调出来。
 *
 * 只在「没有弹框」时显示，避免弹框开着的时候右下角还浮一个按钮。
```

```
 * 游戏内的唤起按钮在 RailwayFpsGame 的动作组里，两者共用同一个 store。
 */
import { Bot, Image } from '@lucide/vue'
import { useAgentStore } from '../../stores/agent'

const agent = useAgentStore()
const imagegenUrl = typeof window === 'undefined' ? '' : `http://${window.location.hostname}:4050/`
</script>

<template>
  <a class="imagegen-link" :href="imagegenUrl" target="_blank" rel="noopener noreferrer" title="AI 绘画" aria-label="AI 绘画"><Image :size="18" /></a>
  <button
    v-if="!agent.open"
    class="agent-fab"
    type="button"
    title="打开信号巡检助手"
    @click="agent.toggle(true)"
  >
    <Bot :size="18" />
    <span>智能体</span>
  </button>
</template>

<style scoped>
.imagegen-link { position: fixed; right: 22px; bottom: 86px; z-index: 1001; display: grid; place-items: center; width: 42px; height: 42px; border-radiu
</style>
```

src/components/admin/AdminTable.vue

```
<script setup>
/**
 * 列定义驱动的数据表格。
 *
 * 列定义形如：{ key, label, width, sortable, align, format }
 * - format(value, row) 返回展示文本，返回 null/undefined 时显示占位符
 * - 需要自定义渲染时用 #cell-<key> 插槽，行操作用 #row-actions
 */
const props = defineProps({
  columns: { type: Array, required: true },
  rows: { type: Array, default: () => [] },
  loading: { type: Boolean, default: false },
  error: { type: String, default: '' },
  emptyText: { type: String, default: '暂无数据' },
  rowKey: { type: String, default: 'id' },
  sort: { type: String, default: '' },
  order: { type: String, default: 'desc' },
})

const emit = defineEmits(['sort'])

function cellText(column, row) {
  const raw = row[column.key]
  if (typeof column.format === 'function') return column.format(raw, row)
  if (raw === null || raw === undefined || raw === '') return '—'
  return String(raw)
}

function sortMark(column) {
  if (column.key !== props.sort) return ''
  return props.order === 'asc' ? '↑' : '↓'
}
</script>

<template>
  <div class="data-table-wrap">
    <table class="data-table">
      <thead>
        <tr>
          <th
            v-for="column in columns"
            :key="column.key"
            :style="column.width ? { width: column.width } : undefined"
            :class="{ sortable: column.sortable, [`align-${column.align}`]: column.align }"
            @click="column.sortable && emit('sort', column.key)"
```

```
          >
            {{ column.label }}<span v-if="column.sortable" class="sort-mark">{{ sortMark(column) }}</span>
          </th>
          <th v-if="$slots['row-actions']" class="align-right">操作</th>
        </tr>
      </thead>

      <tbody>
        <tr v-if="loading">
          <td :colspan="columns.length + ($slots['row-actions'] ? 1 : 0)" class="table-state">加载中…</td>
        </tr>
        <tr v-else-if="error">
          <td :colspan="columns.length + ($slots['row-actions'] ? 1 : 0)" class="table-state error">
            {{ error }}
          </td>
        </tr>
        <tr v-else-if="rows.length === 0">
          <td :colspan="columns.length + ($slots['row-actions'] ? 1 : 0)" class="table-state">
            {{ emptyText }}
          </td>
        </tr>
        <tr v-for="row in rows" v-else :key="row[rowKey]">
          <td
            v-for="column in columns"
            :key="column.key"
            :class="[`align-${column.align}`]"
          >
            <slot :name="`cell-${column.key}`" :row="row" :value="row[column.key]">
              {{ cellText(column, row) }}
            </slot>
          </td>
          <td v-if="$slots['row-actions']" class="align-right row-actions">
            <slot name="row-actions" :row="row" />
          </td>
        </tr>
      </tbody>
    </table>
  </div>
</template>
```

src/game/sceneSerializer.js

```
export const SCENE_SCHEMA_VERSION = 2

/**
 * 序列化场景对象与巡检任务。
 * @param {string} name 场景名称
 * @param {object[]} objects 当前可编辑对象
 * @param {object} options 发布状态、难度和时长
 * @returns {object} 含 objects 和 tasks 的场景数据
 */
export function serializeTrainingScene(name, objects, options = {}) {
  const normalizedObjects = objects.map(normalizeObject)

  return {
    version: SCENE_SCHEMA_VERSION,
    sceneName: name,
    savedAt: new Date().toISOString(),
    metadata: {
      description: String(options.description || ''),
      difficulty: options.difficulty || 'normal',
      estimatedMinutes: numberOr(options.estimatedMinutes, 10)
    },
    published: Boolean(options.published),
    objects: normalizedObjects,
    tasks: normalizedObjects.filter((object) => object.inspectionPoint).map(objectToTask)
  }
}

/**
 * 校验并解析上传的场景 JSON。
 * @param {string} text 上传文件的 UTF-8 文本
 * @returns {object} 已规范化的场景结构
 */
```

```
export function parseTrainingScene(text) {
  const data = JSON.parse(text)
  if (!data || !Array.isArray(data.objects)) throw new Error('场景文件缺少 objects 数组')

  const objects = data.objects.map(normalizeObject)

  return {
    version: Number(data.version || 1),
    sceneName: String(data.sceneName || '未命名巡检场景'),
    metadata: {
      description: String(data.metadata?.description || ''),
      difficulty: data.metadata?.difficulty || 'normal',
      estimatedMinutes: numberOr(data.metadata?.estimatedMinutes, 10)
    },
    published: Boolean(data.published),
    objects,
    tasks: Array.isArray(data.tasks) ? data.tasks.map(normalizeTask) : objects.filter((object) => object.inspectionPoint).map(objectToTask)
  }
}

/**
 * 从设为巡检点的模型生成学生任务。
 * @param {object[]} objects 模型对象列表
 * @returns {object} 巡检任务数组
 */
export function buildSceneTasks(objects) {
  return objects.map(normalizeObject).filter((object) => object.inspectionPoint).map(objectToTask)
}

function normalizeObject(object, index = 0) {
  if (!object.catalogKey) throw new Error(`第 ${index + 1} 个对象缺少 catalogKey`)

  const task = normalizeTask(object.task || {})
  const name = object.name || object.catalogKey

  return {
    id: object.id || `${object.catalogKey}-${Date.now()}-${index}`,
    catalogKey: object.catalogKey,
    name,
    position: normalizeVector(object.position),
    rotation: normalizeVector(object.rotation),
    scale: normalizeVector(object.scale, 1),
    interactive: Boolean(object.interactive),
    inspectionPoint: Boolean(object.inspectionPoint),
    task: {
      title: task.title || `检查${name}`,
      description: task.description || '靠近目标设备后完成巡检确认。',
      faultType: task.faultType,
      expectedAction: task.expectedAction,
      score: task.score,
      hint: task.hint
    }
  }
}

function normalizeTask(task) {
  return {
    title: String(task.title || ''),
    description: String(task.description || ''),
    faultType: String(task.faultType || 'normal'),
    expectedAction: String(task.expectedAction || 'inspect'),
    score: numberOr(task.score, 10),
    hint: String(task.hint || '')
  }
}

function objectToTask(object) {
  return {
    id: object.id,
    objectId: object.id,
    title: object.task?.title || `检查${object.name}`,
    description: object.task?.description || '靠近目标设备后完成巡检确认。',
    faultType: object.task?.faultType || 'normal',
    expectedAction: object.task?.expectedAction || 'inspect',
    score: numberOr(object.task?.score, 10),
    hint: object.task?.hint || '',
```

```
    position: roundVector(object.position)
  }
}

function normalizeVector(value, fallback = 0) {
  return {
    x: numberOr(value?.x, fallback),
    y: numberOr(value?.y, fallback),
    z: numberOr(value?.z, fallback)
  }
}

function roundVector(value) {
  return {
    x: round(value.x),
    y: round(value.y),
    z: round(value.z)
  }
}

function numberOr(value, fallback) {
  const number = Number(value)
  return Number.isFinite(number) ? number : fallback
}

function round(value) {
  return Math.round(Number(value || 0) * 1000) / 1000
}
```

src/game/trainingSceneDb.js

```
import Dexie from 'dexie'
import { nanoid } from 'nanoid'
import { createDefaultTrainingScene, DEFAULT_TRAINING_SCENE_ID } from './defaultTrainingScene.js'

export const trainingSceneDb = new Dexie('railway-signal-runner')

trainingSceneDb.version(1).stores({
  scenes: 'id, name, updatedAt, createdAt',
  records: 'id, sceneId, createdAt'
})

trainingSceneDb.version(2).stores({
  scenes: 'id, name, published, updatedAt, createdAt',
  records: 'id, sceneId, createdAt'
})

/**
 * 将训练场景写入浏览器本地数据库。
 * @param {object} scene 包含名称、任务和发布状态的场景
 * @returns {object} 带 ID 和更新时间的场景
 */
export async function saveTrainingScene(scene) {
  const now = new Date().toISOString()
  const id = scene.id || nanoid()
  const nextScene = {
    ...scene,
    id,
    createdAt: scene.createdAt || now,
    updatedAt: now
  }
  await trainingSceneDb.scenes.put(nextScene)
  return nextScene
}

export function listTrainingScenes() {
  return trainingSceneDb.scenes.orderBy('updatedAt').reverse().toArray()
}

/**
 * 获取本浏览器中已发布的训练场景。
 * @returns {object} 可供学生选择的场景列表
 */
export async function listPublishedTrainingScenes() {
```

```
  const scenes = await listTrainingScenes()
  return scenes.filter((scene) => scene.published)
}

export function getTrainingScene(id) {
  return trainingSceneDb.scenes.get(id)
}

export async function ensureDefaultTrainingScene() {
  const existing = await getTrainingScene(DEFAULT_TRAINING_SCENE_ID)
  return existing || saveTrainingScene(createDefaultTrainingScene())
}

export async function deleteTrainingScene(id) {
  await trainingSceneDb.scenes.delete(id)
}

export async function saveTrainingRecord(record) {
  const now = new Date().toISOString()
  const nextRecord = {
    ...record,
    id: record.id || nanoid(),
    createdAt: now
  }
  await trainingSceneDb.records.put(nextRecord)
  return nextRecord
}
```

src/game/defaultTrainingScene.js

```
import { findCatalogItem } from './modelCatalog.js'
import { serializeTrainingScene } from './sceneSerializer.js'

export const DEFAULT_TRAINING_SCENE_ID = 'builtin-railway-inspection-v1'

const PLACEMENTS = [
  ['进站信号机', '进站信号机', -80, -52, 0, true],
  ['轨旁警示牌glb', '进站警示牌', -92, -75, 0, false],
  ['轨道电路设备箱', '轨道电路设备箱', -55, -35, 0, true],
  ['铁路道岔', '站场道岔', -40, -30, 0, true],
  ['转辙机', '道岔转辙机', -33, -36, 0, true],
  ['电缆槽', '轨旁电缆槽', -14, -5, 0, false],
  ['bridge', '区间铁路桥', 8, 6, 0, false],
  ['应答器', '轨道应答器', 25, 19, 0, true],
  ['信号设备箱', '信号设备箱', 48, 43, 0, true],
  ['work_man', '现场检修人员', 60, 44, 0, false],
  ['出站信号机', '出站信号机', 75, 63, 0, true],
  ['小型车站站台', '终点站台', 102, 73, 0, false],
  ['man', '站台作业人员', 94, 90, 0, false],
]

/**
 * 按真实模型目录生成固定 ID 的默认站场实训对象。
 * @returns {object} 包含对象及巡检点的默认场景
 */
export function createDefaultTrainingScene() {
  const objects = PLACEMENTS.map(([catalogKey, name, x, z, angle, inspectionPoint], index) => {
    const catalog = findCatalogItem(catalogKey)
    if (!catalog) throw new Error(`示范场景缺少模型：${catalogKey}`)
    const scale = catalog.defaultScale
    return {
      id: `default-equipment-${index + 1}`,
      catalogKey,
      name,
      position: { x, y: 0, z },
      rotation: { x: 0, y: angle, z: 0 },
      scale: { x: scale, y: scale, z: scale },
      interactive: inspectionPoint,
      inspectionPoint,
      task: {
        title: `检查${name}`,
        description: `靠近${name}，观察设备外观与安装位置；如需了解工作原理，可向智能助手提问。`,
        faultType: 'normal',
        expectedAction: 'inspect',
```

```
        score: 10,
        hint: `沿轨道寻找${name}`,
      },
    }
  })

  const name = '站场信号设备巡检示范场'
  const scene = serializeTrainingScene(name, objects, {
    description: '亮色站场路线，包含信号机、道岔、转辙机、应答器与作业人员。接近设备后可以向智能助手提问。',
    difficulty: 'easy',
    estimatedMinutes: 18,
    published: true,
  })
  return {
    id: DEFAULT_TRAINING_SCENE_ID,
    name,
    description: scene.metadata.description,
    difficulty: scene.metadata.difficulty,
    estimatedMinutes: scene.metadata.estimatedMinutes,
    published: true,
    objects: scene.objects,
    tasks: scene.tasks,
    payload: scene,
  }
}
```

src/game/equipmentProximity.js

```
/**
 * 在半径范围内寻找离玩家最近的设备，包括已巡视设备。
 * @param {object} targets 场景目标迭代器
 * @param {object} position 玩家坐标
 * @param {object} radius 接近范围
 * @returns {object} 附近设备和任务信息或 null
 */
export function findNearbyEquipment(targets, position, radius = 14) {
  let nearest = null
  let nearestDistance = radius
  for (const target of targets) {
    const distance = Math.hypot(position.x - target.x, position.z - target.z)
    if (distance > nearestDistance) continue
    nearest = target
    nearestDistance = distance
  }
  return nearest ? {
    id: nearest.id,
    name: nearest.name || nearest.label,
    catalogKey: nearest.catalogKey || '',
    title: nearest.task?.title || nearest.label,
    description: nearest.task?.description || '',
    distance: Math.round(nearestDistance * 10) / 10,
    inspected: Boolean(nearest.inspected),
  } : null
}
```

src/game/railwayGame.js

```
import * as THREE from 'three'
import { GLTFLoader } from 'three/examples/jsm/loaders/GLTFLoader.js'
import { clone as cloneModel } from 'three/examples/jsm/utils/SkeletonUtils.js'
import { findCatalogItem } from './modelCatalog'
import { findNearbyEquipment } from './equipmentProximity.js'

const CAMERA_HEIGHT = 3.6
const WORLD_LIMITS = {
  minX: -145,
  maxX: 145,
  minZ: -115,
  maxZ: 115
}

export const BASE_GEO = {
```

```
  lon: 109.38871,
  lat: 24.30755
}

const DEGREE_PER_UNIT = 0.000018
const ROUTE_ANGLE = Math.atan2(0.75, 1)
const INITIAL_YAW = Math.atan2(-1, -0.75)

const MODEL_URLS = {
  railway: '/assets/models/railway.glb',
  sign: '/assets/models/sign.glb',
  locomotive: '/assets/models/locomotive.glb',
  station: '/assets/models/station.glb',
  bridge: '/assets/models/bridge.glb',
  worker: '/assets/models/work_man.glb',
  man: '/assets/models/man.glb',
  box: '/assets/models/box.glb'
}

const routePoints = [
  new THREE.Vector3(-120, 0.2, -90),
  new THREE.Vector3(-90, 0.2, -67),
  new THREE.Vector3(-58, 0.2, -43),
  new THREE.Vector3(-26, 0.2, -19),
  new THREE.Vector3(8, 0.2, 6),
  new THREE.Vector3(42, 0.2, 31),
  new THREE.Vector3(76, 0.2, 56),
  new THREE.Vector3(112, 0.2, 83)
]

export const SIGNAL_POINTS = [
  { id: 'S-01', label: '进站信号机', state: 'red', x: -80, z: -60 },
  { id: 'S-02', label: '道岔信号机', state: 'green', x: -42, z: -31 },
  { id: 'S-03', label: '桥前预告', state: 'yellow', x: -5, z: -3 },
  { id: 'S-04', label: '区间闭塞', state: 'green', x: 35, z: 26 },
  { id: 'S-05', label: '站场出发', state: 'red', x: 74, z: 56 }
]

export const STATION_POINT = {
  id: 'STATION',
  label: '终点站台',
  x: 108,
  z: 82
}

export function worldToGeo(x, z) {
  return {
    lon: BASE_GEO.lon + x * DEGREE_PER_UNIT,
    lat: BASE_GEO.lat + z * DEGREE_PER_UNIT
  }
}

export function getRouteGeoPath() {
  return routePoints.map((point) => worldToGeo(point.x, point.z))
}

/**
 * 创建三维场景运行时并注册画布事件。
 * @param {HTMLCanvasElement} canvas WebGL 画布
 * @param {object} host 画布容器
 * @param {Function} onState 状态更新回调
 * @param {Function} onSignals 巡检点更新回调
 * @param {Function} onEvent 业务事件回调
 * @returns {object} 三维场景控制接口
 */
export function createRailwayGame({ canvas, host, onState, onSignals, onEvent }) {
  const scene = new THREE.Scene()
  const camera = new THREE.PerspectiveCamera(67, 1, 0.1, 1200)
  const renderer = new THREE.WebGLRenderer({
    canvas,
    antialias: true,
    preserveDrawingBuffer: true,
    powerPreference: 'high-performance'
  })
  const loader = new GLTFLoader()
  const clock = new THREE.Clock()
```

```
const models = new Map()
const modelPromises = new Map()
const editableObjects = new Map()
const editorGroup = new THREE.Group()
const raycaster = new THREE.Raycaster()
const groundPlane = new THREE.Plane(new THREE.Vector3(0, 1, 0), 0)
const mixers = []
const keys = new Map()
const signalRuntime = new Map()
const trainCurve = new THREE.CatmullRomCurve3(routePoints, false, 'catmullrom', 0.25)

let animationFrame = 0
let resizeObserver
let train = null
let trainingAvatar = null
let avatarFloorOffset = 0
let trainProgress = 0
let yaw = INITIAL_YAW
let pitch = -0.06
let running = false
let pointerLocked = false
let completed = false
let ready = false
let modelsReady = Promise.resolve()
let audioEnabled = false
let lastStateEmit = 0
let lastWarningAt = 0
let elapsed = 0
let distanceTravelled = 0
let health = 100
let lastPosition = new THREE.Vector3(-116, CAMERA_HEIGHT, -87)
const trainingSpawn = new THREE.Vector3(-116, CAMERA_HEIGHT, -87)
let dragLook = null
let runStartedAt = 0
let editorMode = false
let selectedObjectId = null
let selectionBox = null
let draggedObject = null

const state = {
  ready: false,
  running: false,
  locked: false,
  loading: '初始化场景',
  elapsed: 0,
  speed: 0,
  distance: 0,
  health: 100,
  inspected: 0,
  total: 0,
  completed: false,
  phase: '模型加载',
  nearestId: 'S-01',
  nearestLabel: '进站信号机',
  nearestDistance: 0,
  position: {
    x: -116,
    y: CAMERA_HEIGHT,
    z: -87
  },
  heading: 0,
  geo: worldToGeo(-116, -87),
  audioEnabled: false,
  nearbyEquipment: null
}

const audio = {
  alarm: makeAudio('/assets/audio/alarm.wav', 0.35),
  notice: makeAudio('/assets/audio/pedestrian_notice.wav', 0.28),
  bgm: makeAudio('/assets/bgm/dl.mp3', 0.16, true)
}

function makeAudio(url, volume, loop = false) {
  const item = new Audio(url)
  item.volume = volume
  item.loop = loop
```

```
  item.preload = 'auto'
  return item
}

function init() {
  renderer.setPixelRatio(Math.min(window.devicePixelRatio || 1, 2))
  renderer.shadowMap.enabled = true
  renderer.shadowMap.type = THREE.PCFSoftShadowMap
  renderer.outputColorSpace = THREE.SRGBColorSpace
  renderer.toneMapping = THREE.ACESFilmicToneMapping
  renderer.toneMappingExposure = 1.05

  scene.background = new THREE.Color(0xdceaf0)
  scene.fog = new THREE.FogExp2(0xdceaf0, 0.004)

  camera.position.copy(lastPosition)
  updateCameraRotation()
  setupLights()
  createGround()
  scene.add(editorGroup)
  bindEvents()
  resize()

  resizeObserver = new ResizeObserver(resize)
  resizeObserver.observe(host || canvas)

  state.loading = '加载铁路与信号模型'
  emitState(0, true)
  animate()
  modelsReady = loadModels()
}

function setupLights() {
  const hemi = new THREE.HemisphereLight(0xdceef2, 0x3d463c, 1.8)
  scene.add(hemi)

  const sun = new THREE.DirectionalLight(0xfff0c4, 3.1)
  sun.position.set(-70, 120, 48)
  sun.castShadow = true
  sun.shadow.mapSize.set(2048, 2048)
  sun.shadow.camera.left = -160
  sun.shadow.camera.right = 160
  sun.shadow.camera.top = 140
  sun.shadow.camera.bottom = -140
  sun.shadow.camera.near = 10
  sun.shadow.camera.far = 260
  scene.add(sun)

  const side = new THREE.DirectionalLight(0xb8d8ff, 0.9)
  side.position.set(90, 45, -70)
  scene.add(side)
}

function createGround() {
  const ground = new THREE.Mesh(
    new THREE.PlaneGeometry(360, 300, 24, 24),
    new THREE.MeshStandardMaterial({
      map: createGroundTexture(),
      roughness: 0.92,
      metalness: 0.02
    })
  )
  ground.rotation.x = -Math.PI / 2
  ground.receiveShadow = true
  scene.add(ground)
}

function createGroundTexture() {
  const textureCanvas = document.createElement('canvas')
  textureCanvas.width = 512
  textureCanvas.height = 512
  const ctx = textureCanvas.getContext('2d')
  ctx.fillStyle = '#a8bca3'
  ctx.fillRect(0, 0, 512, 512)

  for (let i = 0; i < 2200; i += 1) {
```

```
    const x = Math.random() * 512
    const y = Math.random() * 512
    const g = 115 + Math.random() * 42
    ctx.fillStyle = `rgba(${g}, ${g + 15}, ${g - 4}, ${0.12 + Math.random() * 0.16})`
    ctx.fillRect(x, y, 1 + Math.random() * 2, 1 + Math.random() * 2)
  }

  const texture = new THREE.CanvasTexture(textureCanvas)
  texture.wrapS = THREE.RepeatWrapping
  texture.wrapT = THREE.RepeatWrapping
  texture.repeat.set(18, 15)
  texture.colorSpace = THREE.SRGBColorSpace
  return texture
}

function createRailBed() {
  const bed = new THREE.Mesh(
    new THREE.BoxGeometry(298, 0.38, 18),
    new THREE.MeshStandardMaterial({
      color: 0x3f4240,
      roughness: 0.82
    })
  )
  bed.position.set(0, 0.05, 0)
  bed.rotation.y = -ROUTE_ANGLE
  bed.receiveShadow = true
  scene.add(bed)

  const sideLineMaterial = new THREE.MeshStandardMaterial({
    color: 0xd7c77e,
    roughness: 0.55,
    emissive: 0x2a2100,
    emissiveIntensity: 0.08
  })

  ;[-7.4, 7.4].forEach((offset) => {
    const line = new THREE.Mesh(new THREE.BoxGeometry(298, 0.08, 0.35), sideLineMaterial)
    line.position.set(Math.sin(ROUTE_ANGLE) * offset, 0.35, Math.cos(ROUTE_ANGLE) * offset)
    line.rotation.y = -ROUTE_ANGLE
    line.receiveShadow = true
    scene.add(line)
  })
}

function createVegetation() {
  const trunkMaterial = new THREE.MeshStandardMaterial({ color: 0x6d5541, roughness: 0.8 })
  const foliageMaterials = [
    new THREE.MeshStandardMaterial({ color: 0x2f6b46, roughness: 0.88 }),
    new THREE.MeshStandardMaterial({ color: 0x496d3b, roughness: 0.9 }),
    new THREE.MeshStandardMaterial({ color: 0x6b7341, roughness: 0.86 })
  ]

  for (let i = 0; i < 58; i += 1) {
    const t = seeded(i * 29.7)
    const side = i % 2 === 0 ? -1 : 1
    const along = -136 + t * 272
    const away = 24 + seeded(i * 17.9) * 72
    const direction = new THREE.Vector3(Math.cos(ROUTE_ANGLE), 0, Math.sin(ROUTE_ANGLE))
    const normal = new THREE.Vector3(-direction.z, 0, direction.x)
    const position = direction.multiplyScalar(along).add(normal.multiplyScalar(away * side))

    const tree = new THREE.Group()
    const trunk = new THREE.Mesh(new THREE.CylinderGeometry(0.42, 0.62, 4.6, 8), trunkMaterial)
    trunk.position.y = 2.3
    trunk.castShadow = true
    tree.add(trunk)

    const foliage = new THREE.Mesh(
      new THREE.ConeGeometry(2.5 + seeded(i) * 1.2, 6 + seeded(i + 4) * 2.4, 9),
      foliageMaterials[i % foliageMaterials.length]
    )
    foliage.position.y = 6.4
    foliage.castShadow = true
    tree.add(foliage)

    tree.position.copy(position)
```

```
    tree.rotation.y = seeded(i * 2.1) * Math.PI
    scene.add(tree)
  }
}

function createBoundaryMarkers() {
  const material = new THREE.MeshStandardMaterial({
    color: 0xd9c06f,
    roughness: 0.52,
    emissive: 0x191000,
    emissiveIntensity: 0.12
  })

  for (let i = -5; i <= 5; i += 1) {
    const post = new THREE.Mesh(new THREE.CylinderGeometry(0.24, 0.3, 3.8, 10), material)
    post.position.set(-122 + i * 25, 1.9, -96 + i * 18.7)
    post.castShadow = true
    scene.add(post)
  }
}

function seeded(value) {
  const raw = Math.sin(value * 999.27) * 43758.5453
  return raw - Math.floor(raw)
}

async function loadModels() {
  state.loading = '加载铁路与信号模型'
  emitState(0, true)

  const entries = Object.entries(MODEL_URLS)
  const loaded = await Promise.allSettled(
    entries.map(async ([name, url]) => [name, await loadCatalogModel(url)])
  )

  loaded.forEach((result) => {
    if (result.status !== 'fulfilled') return
    const [name, gltf] = result.value
    gltf.scene.traverse((child) => {
      if (!child.isMesh) return
      child.castShadow = true
      child.receiveShadow = true
      if (child.material) {
        child.material = child.material.clone()
        child.material.needsUpdate = true
      }
    })
    models.set(name, gltf)
  })

  placeRailway()
  placeSignals()
  placeSceneModels()
  placeTrainingAvatar()
  ready = true
  state.ready = true
  state.loading = '已就绪'
  state.phase = '沿线巡视'
  emitSignals()
  emitState(0, true)
  onEvent?.({ type: 'ready', message: '场景已就绪' })
}

function placeRailway() {
  const railway = models.get('railway')
  if (!railway) {
    createFallbackRailway()
    return
  }

  for (let i = 0; i < 12; i += 1) {
    const rail = cloneScene(railway.scene)
    rail.scale.setScalar(12)
    rail.position.set(-110 + i * 20, 0, -82 + i * 15)
    rail.rotation.y = Math.PI / 3.6
    scene.add(rail)
```

```
  }
}

function createFallbackRailway() {
  const railMaterial = new THREE.MeshStandardMaterial({ color: 0x323535, metalness: 0.45, roughness: 0.35 })
  const sleeperMaterial = new THREE.MeshStandardMaterial({ color: 0x665042, roughness: 0.82 })

  ;[-2.9, 2.9].forEach((offset) => {
    const rail = new THREE.Mesh(new THREE.BoxGeometry(292, 0.32, 0.32), railMaterial)
    rail.position.set(Math.sin(ROUTE_ANGLE) * offset, 0.72, Math.cos(ROUTE_ANGLE) * offset)
    rail.rotation.y = -ROUTE_ANGLE
    rail.castShadow = true
    scene.add(rail)
  })

  for (let i = 0; i < 48; i += 1) {
    const sleeper = new THREE.Mesh(new THREE.BoxGeometry(4.8, 0.38, 1.1), sleeperMaterial)
    const along = -136 + i * 5.8
    sleeper.position.set(Math.cos(ROUTE_ANGLE) * along, 0.5, Math.sin(ROUTE_ANGLE) * along)
    sleeper.rotation.y = -ROUTE_ANGLE + Math.PI / 2
    sleeper.castShadow = true
    sleeper.receiveShadow = true
    scene.add(sleeper)
  }
}

function placeSignals() {
  const signModel = models.get('sign')

  SIGNAL_POINTS.forEach((point) => {
    const group = new THREE.Group()
    group.position.set(point.x, 0, point.z)
    group.rotation.y = Math.PI / 3.6

    if (signModel) {
      const sign = cloneScene(signModel.scene)
      sign.scale.setScalar(8)
      group.add(sign)
    } else {
      group.add(createFallbackSignal())
    }

    const color = signalColor(point.state)
    const light = new THREE.PointLight(color, 4.2, 34)
    light.position.set(0, 7.5, 0)
    group.add(light)

    const bulb = new THREE.Mesh(
      new THREE.SphereGeometry(0.72, 20, 20),
      new THREE.MeshStandardMaterial({
        color,
        emissive: color,
        emissiveIntensity: 1.6,
        roughness: 0.28
      })
    )
    bulb.position.set(0, 7.6, 0)
    group.add(bulb)

    const ring = new THREE.Mesh(
      new THREE.TorusGeometry(5.3, 0.12, 12, 72),
      new THREE.MeshStandardMaterial({
        color,
        emissive: color,
        emissiveIntensity: 0.35,
        roughness: 0.4
      })
    )
    ring.rotation.x = Math.PI / 2
    ring.position.y = 0.34
    group.add(ring)

    scene.add(group)
    signalRuntime.set(point.id, {
      ...point,
      inspected: false,
```

```
      group,
      light,
      bulb,
      ring
    })
  })
}

function createFallbackSignal() {
  const group = new THREE.Group()
  const pole = new THREE.Mesh(
    new THREE.CylinderGeometry(0.18, 0.24, 7, 14),
    new THREE.MeshStandardMaterial({ color: 0x2b3030, roughness: 0.55, metalness: 0.28 })
  )
  pole.position.y = 3.5
  pole.castShadow = true
  group.add(pole)

  const head = new THREE.Mesh(
    new THREE.BoxGeometry(1.5, 2.4, 0.72),
    new THREE.MeshStandardMaterial({ color: 0x171a1a, roughness: 0.5 })
  )
  head.position.y = 7
  head.castShadow = true
  group.add(head)
  return group
}

function placeSceneModels() {
  const bridge = models.get('bridge')
  if (bridge) {
    const item = cloneScene(bridge.scene)
    item.scale.setScalar(9.8)
    item.position.set(8, 0.1, 6)
    item.rotation.y = -ROUTE_ANGLE
    scene.add(item)
  }

  const station = models.get('station')
  if (station) {
    const item = cloneScene(station.scene)
    item.scale.setScalar(18)
    item.position.set(STATION_POINT.x, 0, STATION_POINT.z)
    item.rotation.y = -Math.PI / 4
    scene.add(item)
  } else {
    createFallbackStation()
  }

  const worker = models.get('worker') || models.get('man')
  if (worker) {
    ;[
      [-55, -50, Math.PI / 5],
      [18, 12, -Math.PI / 2],
      [88, 66, Math.PI / 1.6]
    ].forEach(([x, z, rotation], index) => {
      const item = cloneScene(worker.scene)
      item.scale.setScalar(index === 1 ? 6.2 : 5.5)
      item.position.set(x, 0, z)
      item.rotation.y = rotation
      scene.add(item)
    })
  }

  const box = models.get('box')
  if (box) {
    ;[
      [-68, -42],
      [-63, -37],
      [58, 46],
      [63, 48]
    ].forEach(([x, z], index) => {
      const item = cloneScene(box.scene)
      item.scale.setScalar(7)
      item.position.set(x, 0.05, z)
      item.rotation.y = index * 0.45
```

```
      scene.add(item)
    })
  }

  placeTrain()
}

/**
 * 按模型包围盒将现有人物模型归一为训练角色。
 */
function placeTrainingAvatar() {
  const model = models.get('man') || models.get('worker')
  if (!model) return
  trainingAvatar = cloneScene(model.scene)
  const bounds = new THREE.Box3().setFromObject(trainingAvatar)
  const height = bounds.max.y - bounds.min.y
  if (height > 0) trainingAvatar.scale.setScalar(2.8 / height)
  avatarFloorOffset = -new THREE.Box3().setFromObject(trainingAvatar).min.y
  trainingAvatar.traverse((child) => { if (child.isMesh) child.castShadow = true })
  scene.add(trainingAvatar)
  updateTrainingAvatar()
}

function updateTrainingAvatar() {
  if (!trainingAvatar) return
  trainingAvatar.visible = !editorMode
  if (!trainingAvatar.visible) return
  const forward = new THREE.Vector3(-Math.sin(yaw), 0, -Math.cos(yaw))
  trainingAvatar.position.set(
    camera.position.x + forward.x * 5,
    avatarFloorOffset + (running ? Math.sin(elapsed * 8) * 0.025 : 0),
    camera.position.z + forward.z * 5
  )
  trainingAvatar.rotation.y = yaw + Math.PI
}

function createFallbackStation() {
  const station = new THREE.Group()
  const body = new THREE.Mesh(
    new THREE.BoxGeometry(22, 8, 14),
    new THREE.MeshStandardMaterial({ color: 0x9c8e76, roughness: 0.75 })
  )
  body.position.y = 4
  body.castShadow = true
  body.receiveShadow = true
  station.add(body)

  const roof = new THREE.Mesh(
    new THREE.ConeGeometry(16, 5, 4),
    new THREE.MeshStandardMaterial({ color: 0x6d2d2c, roughness: 0.65 })
  )
  roof.position.y = 10
  roof.rotation.y = Math.PI / 4
  roof.castShadow = true
  station.add(roof)

  station.position.set(STATION_POINT.x, 0, STATION_POINT.z)
  scene.add(station)
}

function placeTrain() {
  const locomotive = models.get('locomotive')
  if (locomotive) {
    train = cloneScene(locomotive.scene)
    train.scale.setScalar(11.5)
    const bounds = new THREE.Box3().setFromObject(train)
    const size = bounds.getSize(new THREE.Vector3())
    const length = Math.max(size.x, size.z)
    if (length > 0) train.scale.multiplyScalar(22 / length)
  } else {
    train = createFallbackTrain()
  }

  trainProgress = 0.7
  const start = trainCurve.getPointAt(trainProgress)
  train.position.copy(start)
```

```
  train.position.y = 0.7
  train.rotation.y = -ROUTE_ANGLE + Math.PI / 2
  scene.add(train)

  const gltf = models.get('locomotive')
  if (gltf?.animations?.length) {
    const mixer = new THREE.AnimationMixer(train)
    mixer.clipAction(gltf.animations[0]).play()
    mixers.push(mixer)
  }
}

function createFallbackTrain() {
  const group = new THREE.Group()
  const body = new THREE.Mesh(
    new THREE.BoxGeometry(9, 3.2, 3.4),
    new THREE.MeshStandardMaterial({ color: 0x31546a, roughness: 0.42, metalness: 0.18 })
  )
  body.position.y = 2.2
  body.castShadow = true
  group.add(body)

  const nose = new THREE.Mesh(
    new THREE.BoxGeometry(2.8, 2.6, 3.2),
    new THREE.MeshStandardMaterial({ color: 0xd5b351, roughness: 0.44 })
  )
  nose.position.set(5.4, 1.95, 0)
  nose.castShadow = true
  group.add(nose)
  return group
}

function cloneScene(source) {
  const cloned = cloneModel(source)
  cloned.traverse((child) => {
    if (!child.isMesh) return
    child.castShadow = true
    child.receiveShadow = true
    if (child.material) {
      child.material = child.material.clone()
    }
  })
  return cloned
}

function signalColor(stateName) {
  if (stateName === 'red') return 0xff3b30
  if (stateName === 'yellow') return 0xffc84d
  return 0x35d66b
}

function inspectedColor() {
  return 0x61d9ff
}

function bindEvents() {
  window.addEventListener('keydown', onKeyDown)
  window.addEventListener('keyup', onKeyUp)
  document.addEventListener('pointerlockchange', onPointerLockChange)
  canvas.addEventListener('mousemove', onMouseMove)
  canvas.addEventListener('pointerdown', onPointerDown)
  canvas.addEventListener('pointermove', onPointerMove)
  canvas.addEventListener('contextmenu', preventCanvasMenu)
  window.addEventListener('pointerup', onPointerUp)
}

function preventCanvasMenu(event) {
  event.preventDefault()
}

function onKeyDown(event) {
  if (editorMode && [
    'ArrowUp',
    'ArrowDown',
    'ArrowLeft',
    'ArrowRight',
```

```
    'KeyG',
    'KeyR',
    'KeyS',
    'Delete',
    'Backspace',
    'Escape'
  ].includes(event.code)) {
    return
  }

  if (event.code === 'KeyR' && !editorMode) {
    reset()
    return
  }

  setKey(event.code, true)
}

function onKeyUp(event) {
  setKey(event.code, false)
}

function setKey(code, value) {
  const map = {
    KeyW: 'forward',
    ArrowUp: 'forward',
    KeyS: 'backward',
    ArrowDown: 'backward',
    KeyA: 'left',
    ArrowLeft: 'left',
    KeyD: 'right',
    ArrowRight: 'right',
    KeyQ: 'turnLeft',
    KeyE: 'turnRight',
    ShiftLeft: 'sprint',
    ShiftRight: 'sprint'
  }
  const key = map[code]
  if (key) keys.set(key, value)
}

function onPointerLockChange() {
  pointerLocked = document.pointerLockElement === canvas
  state.locked = pointerLocked
  emitState(0, true)
}

function onMouseMove(event) {
  if ((!running && !editorMode) || !pointerLocked) return
  yaw -= event.movementX * 0.0022
  pitch -= event.movementY * 0.002
  pitch = THREE.MathUtils.clamp(pitch, -0.82, 0.55)
  updateCameraRotation()
}

function onPointerDown(event) {
  if (editorMode && event.button === 2) {
    canvas.requestPointerLock?.()
    return
  }
  if (editorMode) {
    const id = selectEditableObjectAt(event)
    const object = id ? editableObjects.get(id) : null
    draggedObject = object ? {
      id,
      startClientY: event.clientY,
      startHeight: object.position.y
    } : null
    return
  }

  if (event.pointerType === 'mouse') return
  dragLook = {
    x: event.clientX,
    y: event.clientY
  }
```

```
}

function onPointerMove(event) {
  if (editorMode && draggedObject) {
    moveEditableObjectToPointer(draggedObject, event)
    return
  }
  if (!dragLook || event.pointerType === 'mouse') return
  const dx = event.clientX - dragLook.x
  const dy = event.clientY - dragLook.y
  dragLook.x = event.clientX
  dragLook.y = event.clientY
  yaw -= dx * 0.004
  pitch -= dy * 0.003
  pitch = THREE.MathUtils.clamp(pitch, -0.82, 0.55)
  updateCameraRotation()
}

function onPointerUp() {
  dragLook = null
  draggedObject = null
}

function animate() {
  animationFrame = requestAnimationFrame(animate)
  const delta = Math.min(clock.getDelta(), 0.06)

  if (ready && editorMode && !completed) {
    updatePlayer(delta)
  } else if (running && ready && !completed) {
    elapsed += delta
    updatePlayer(delta)
    updateSignals(delta)
    updateTrain(delta)
    updatePhase()
  } else {
    updateSignalPulses(delta)
    updateTrain(delta * 0.35)
  }

  mixers.forEach((mixer) => mixer.update(delta))
  updateTrainingAvatar()
  renderer.render(scene, camera)
  emitState(delta)
}

function updatePlayer(delta) {
  const turnSpeed = 1.7
  if (keys.get('turnLeft')) yaw += turnSpeed * delta
  if (keys.get('turnRight')) yaw -= turnSpeed * delta

  const forward = new THREE.Vector3(-Math.sin(yaw), 0, -Math.cos(yaw))
  const right = new THREE.Vector3(Math.cos(yaw), 0, -Math.sin(yaw))
  const move = new THREE.Vector3()

  if (keys.get('forward')) move.add(forward)
  if (keys.get('backward')) move.sub(forward)
  if (keys.get('right')) move.add(right)
  if (keys.get('left')) move.sub(right)

  let speed = 0
  if (move.lengthSq() > 0) {
    move.normalize()
    speed = keys.get('sprint') ? 27 : 15
    camera.position.addScaledVector(move, speed * delta)
  }

  camera.position.x = THREE.MathUtils.clamp(camera.position.x, WORLD_LIMITS.minX, WORLD_LIMITS.maxX)
  camera.position.z = THREE.MathUtils.clamp(camera.position.z, WORLD_LIMITS.minZ, WORLD_LIMITS.maxZ)
  camera.position.y = CAMERA_HEIGHT

  const moved = camera.position.distanceTo(lastPosition)
  if (moved > 0) {
    distanceTravelled += moved
    lastPosition.copy(camera.position)
  }
```

```
  state.speed = Math.round(speed * 3.6)
  updateCameraRotation()
}

function updateSignals(delta) {
  updateSignalPulses(delta)
  const playerPosition = camera.position

  signalRuntime.forEach((signal) => {
    if (signal.inspected) return
    const distance = flatDistance(playerPosition.x, playerPosition.z, signal.x, signal.z)
    if (distance > 8) return

    signal.inspected = true
    signal.light?.color?.setHex(inspectedColor())
    signal.bulb?.material?.color?.setHex(inspectedColor())
    signal.bulb?.material?.emissive?.setHex(inspectedColor())
    signal.ring?.material?.color?.setHex(inspectedColor())
    signal.ring?.material?.emissive?.setHex(inspectedColor())
    signal.ring?.scale?.setScalar(1.25)
    playNotice()
    onEvent?.({ type: 'signal', message: `${signal.id} 已巡视` })
    emitSignals()
  })
}

function updateSignalPulses(delta) {
  const t = elapsed * 2.6
  signalRuntime.forEach((signal, index) => {
    const pulse = 1 + Math.sin(t + index * 0.8) * 0.08
    signal.ring?.scale?.setScalar(signal.inspected ? 1.2 : pulse)
    if (signal.bulb?.material) signal.bulb.material.emissiveIntensity = signal.inspected ? 1.35 : 1.4 + Math.sin(t + index) * 0.25
    if (signal.animateGroup !== false && signal.group) signal.group.rotation.y += delta * 0.04
  })
}

function updateTrain(delta) {
  if (!train) return

  trainProgress = (trainProgress + delta * 0.028) % 1
  const position = trainCurve.getPointAt(trainProgress)
  const lookAt = trainCurve.getPointAt((trainProgress + 0.006) % 1)
  train.position.set(position.x, 0.7, position.z)
  train.rotation.y = Math.atan2(lookAt.x - position.x, lookAt.z - position.z) + Math.PI / 2

  const trainDistance = flatDistance(camera.position.x, camera.position.z, position.x, position.z)
  const now = performance.now()
  if (running && ready && now - runStartedAt > 8000 && trainDistance < 10 && now - lastWarningAt > 2200) {
    lastWarningAt = now
    health = Math.max(0, health - 8)
    playAlarm()
    onEvent?.({ type: 'warning', message: '机车接近巡视路径' })
  }
}

function updatePhase() {
  const inspected = Array.from(signalRuntime.values()).filter((signal) => signal.inspected).length
  const stationDistance = flatDistance(camera.position.x, camera.position.z, STATION_POINT.x, STATION_POINT.z)

  if (inspected === signalRuntime.size && stationDistance < 14) {
    completed = true
    running = false
    state.completed = true
    state.phase = '任务完成'
    stopBgm()
    onEvent?.({ type: 'complete', message: '巡视任务完成' })
    if (document.pointerLockElement === canvas) document.exitPointerLock()
    return
  }

  state.phase = inspected === signalRuntime.size ? '返抵车站' : '沿线巡视'
}

function flatDistance(ax, az, bx, bz) {
  return Math.hypot(ax - bx, az - bz)
}
```

```
  function findNearest() {
    const pending = Array.from(signalRuntime.values()).filter((signal) => !signal.inspected)
    const targets = pending.length > 0 ? pending : [STATION_POINT]
    let nearest = targets[0]
    let nearestDistance = Number.POSITIVE_INFINITY

    targets.forEach((target) => {
      const distance = flatDistance(camera.position.x, camera.position.z, target.x, target.z)
      if (distance < nearestDistance) {
        nearest = target
        nearestDistance = distance
      }
    })

    return {
      id: nearest.id,
      label: nearest.label,
      distance: nearestDistance
    }
  }

  function updateCameraRotation() {
    camera.rotation.order = 'YXZ'
    camera.rotation.y = yaw
    camera.rotation.x = pitch
    camera.rotation.z = 0
  }

  function emitState(delta, force = false) {
    const now = performance.now()
    if (!force && now - lastStateEmit < 80) return
    lastStateEmit = now

    const nearest = findNearest()
    state.nearbyEquipment = findNearbyEquipment(signalRuntime.values(), camera.position)
    const inspected = Array.from(signalRuntime.values()).filter((signal) => signal.inspected).length

    state.ready = ready
    state.running = running
    state.locked = pointerLocked
    state.elapsed = elapsed
    state.distance = distanceTravelled
    state.health = health
    state.inspected = inspected
    state.total = signalRuntime.size
    state.completed = completed
    state.nearestId = nearest.id
    state.nearestLabel = nearest.label
    state.nearestDistance = nearest.distance
    state.heading = THREE.MathUtils.euclideanModulo(THREE.MathUtils.radToDeg(-yaw), 360)
    state.audioEnabled = audioEnabled
    state.position = {
      x: camera.position.x,
      y: camera.position.y,
      z: camera.position.z
    }
    state.geo = worldToGeo(camera.position.x, camera.position.z)

    onState?.({ ...state, position: { ...state.position }, geo: { ...state.geo }, delta })
  }

function emitSignals() {
    const payload = Array.from(signalRuntime.values()).map((runtime) => {
      const geo = worldToGeo(runtime.x, runtime.z)
      return {
        id: runtime.id,
        label: runtime.label,
        state: runtime.state,
        x: runtime.x,
        z: runtime.z,
        inspected: runtime.inspected || false,
        geo
      }
    })

    onSignals?.(payload)
```

```
}

function resize() {
  const rect = (host || canvas).getBoundingClientRect()
  const width = Math.max(320, Math.floor(rect.width || window.innerWidth))
  const height = Math.max(320, Math.floor(rect.height || window.innerHeight))

  camera.aspect = width / height
  camera.updateProjectionMatrix()
  renderer.setSize(width, height, false)
}

async function addCatalogObject(catalogKey, pointer) {
  const catalog = findCatalogItem(catalogKey)
  if (!catalog) {
    onEvent?.({ type: 'warning', message: '模型配置不存在' })
    return null
  }

  const object = await createEditableObject(catalog)
  const point = pointer ? screenToGround(pointer.clientX, pointer.clientY) : null
  if (point) {
    object.position.copy(point)
  } else {
    const forward = new THREE.Vector3(0, 0, -1).applyEuler(camera.rotation)
    object.position.copy(camera.position).addScaledVector(forward, 18)
    object.position.y = 0
  }

  object.rotation.y = snapRotation(catalog.snap)
  editorGroup.add(object)
  editableObjects.set(object.userData.editor.id, object)
  selectEditableObject(object.userData.editor.id)
  emitEditorEvent()
  return object.userData.editor.id
}

async function createEditableObject(catalog, sourceObject) {
  const object = await createCatalogVisual(catalog)
  const id = sourceObject?.id || `${catalog.key}-${Date.now()}-${Math.round(Math.random() * 10000)}`
  const scale = sourceObject?.scale || {
    x: catalog.defaultScale,
    y: catalog.defaultScale,
    z: catalog.defaultScale
  }

  object.name = id
  object.position.set(sourceObject?.position?.x || 0, sourceObject?.position?.y || 0, sourceObject?.position?.z || 0)
  object.rotation.set(sourceObject?.rotation?.x || 0, sourceObject?.rotation?.y || 0, sourceObject?.rotation?.z || 0)
  object.scale.set(scale.x, scale.y, scale.z)
object.userData.editor = {
  id,
  catalogKey: catalog.key,
  name: sourceObject?.name || catalog.name,
  interactive: sourceObject?.interactive ?? catalog.interactive,
  inspectionPoint: sourceObject?.inspectionPoint ?? catalog.inspectionPoint,
  task: sourceObject?.task || createDefaultObjectTask(sourceObject?.name || catalog.name)
}
  object.traverse((child) => {
    child.userData.editorRoot = object
    if (!child.isMesh) return
    child.castShadow = true
    child.receiveShadow = true
  })
  return object
}

async function createCatalogVisual(catalog) {
  if (catalog.modelUrl) {
    try {
      const gltf = await loadCatalogModel(catalog.modelUrl)
      return cloneScene(gltf.scene)
    } catch {
      onEvent?.({ type: 'warning', message: `${catalog.name} 模型未找到，已使用占位模型` })
    }
  }
```

```
  return createFallbackCatalogObject(catalog)
}

async function loadCatalogModel(url) {
  const cacheKey = `catalog:${url}`
  if (models.has(cacheKey)) return models.get(cacheKey)
  if (!modelPromises.has(url)) {
    modelPromises.set(url, loader.loadAsync(url).catch((error) => {
      modelPromises.delete(url)
      throw error
    }))
  }
  const gltf = await modelPromises.get(url)
  models.set(cacheKey, gltf)
  return gltf
}

function createFallbackCatalogObject(catalog) {
  if (catalog.key === 'cable_trough') return createFallbackCableTrough()
  if (catalog.category === 'signal') return createFallbackSignal()
  if (catalog.category === 'switch') return createFallbackSwitchMachine()
  if (catalog.category === 'equipment') return createFallbackEquipmentBox()
  if (catalog.category === 'track') return createFallbackTrackSegment()
  return createFallbackMarker(catalog)
}

function createFallbackTrackSegment() {
  const group = new THREE.Group()
  const railMaterial = new THREE.MeshStandardMaterial({ color: 0x323535, metalness: 0.45, roughness: 0.35 })
  const sleeperMaterial = new THREE.MeshStandardMaterial({ color: 0x665042, roughness: 0.82 })
  ;[-0.35, 0.35].forEach((offset) => {
    const rail = new THREE.Mesh(new THREE.BoxGeometry(7.8, 0.08, 0.08), railMaterial)
    rail.position.set(0, 0.16, offset)
    group.add(rail)
  })
  for (let i = -4; i <= 4; i += 1) {
    const sleeper = new THREE.Mesh(new THREE.BoxGeometry(0.14, 0.08, 1.05), sleeperMaterial)
    sleeper.position.set(i * 0.9, 0.06, 0)
    group.add(sleeper)
  }
  return group
}

function createFallbackSwitchMachine() {
  const group = new THREE.Group()
  const body = new THREE.Mesh(
    new THREE.BoxGeometry(1.4, 0.45, 0.62),
    new THREE.MeshStandardMaterial({ color: 0x56616a, roughness: 0.62, metalness: 0.2 })
  )
  body.position.y = 0.32
  group.add(body)
  const rod = new THREE.Mesh(
    new THREE.BoxGeometry(2.8, 0.08, 0.08),
    new THREE.MeshStandardMaterial({ color: 0xb9c0c4, roughness: 0.4, metalness: 0.6 })
  )
  rod.position.set(0.2, 0.28, -0.44)
  group.add(rod)
  return group
}

function createFallbackEquipmentBox() {
  const group = new THREE.Group()
  const box = new THREE.Mesh(
    new THREE.BoxGeometry(1.05, 1.65, 0.58),
    new THREE.MeshStandardMaterial({ color: 0x8d9998, roughness: 0.58, metalness: 0.22 })
  )
  box.position.y = 0.92
  group.add(box)
  const door = new THREE.Mesh(
    new THREE.BoxGeometry(0.92, 1.36, 0.035),
    new THREE.MeshStandardMaterial({ color: 0x6f7d7c, roughness: 0.56, metalness: 0.18 })
  )
  door.position.set(0, 0.92, -0.31)
  group.add(door)
  return group
}
```

```
function createFallbackCableTrough() {
  const group = new THREE.Group()
  const base = new THREE.Mesh(
    new THREE.BoxGeometry(3.6, 0.22, 0.42),
    new THREE.MeshStandardMaterial({ color: 0x8f918b, roughness: 0.86 })
  )
  base.position.y = 0.12
  group.add(base)
  return group
}

function createFallbackMarker(catalog) {
  const group = new THREE.Group()
  const marker = new THREE.Mesh(
    new THREE.BoxGeometry(0.9, 0.9, 0.9),
    new THREE.MeshStandardMaterial({ color: catalog.inspectionPoint ? 0xf0c94d : 0x61d9ff, roughness: 0.55 })
  )
  marker.position.y = 0.45
  group.add(marker)
  return group
}

function screenToGround(clientX, clientY) {
  const rect = canvas.getBoundingClientRect()
  const mouse = new THREE.Vector2(
    ((clientX - rect.left) / rect.width) * 2 - 1,
    -((clientY - rect.top) / rect.height) * 2 + 1
  )
  raycaster.setFromCamera(mouse, camera)
  const point = new THREE.Vector3()
  if (!raycaster.ray.intersectPlane(groundPlane, point)) return null
  point.x = THREE.MathUtils.clamp(point.x, WORLD_LIMITS.minX, WORLD_LIMITS.maxX)
  point.z = THREE.MathUtils.clamp(point.z, WORLD_LIMITS.minZ, WORLD_LIMITS.maxZ)
  point.y = 0
  return point
}

function selectEditableObjectAt(event) {
  const rect = canvas.getBoundingClientRect()
  const mouse = new THREE.Vector2(
    ((event.clientX - rect.left) / rect.width) * 2 - 1,
    -((event.clientY - rect.top) / rect.height) * 2 + 1
  )
  raycaster.setFromCamera(mouse, camera)
  const meshes = []
  editorGroup.traverse((child) => {
    if (child.isMesh) meshes.push(child)
  })
  const hit = raycaster.intersectObjects(meshes, false)[0]
  const id = hit?.object?.userData?.editorRoot?.userData?.editor?.id || null
  selectEditableObject(id)
  return id
}

function moveEditableObjectToPointer(drag, event) {
  const object = editableObjects.get(drag.id)
  if (!object) return

  if (event.shiftKey) {
    object.position.y = THREE.MathUtils.clamp(
      drag.startHeight + (drag.startClientY - event.clientY) * 0.08,
      -50,
      100
    )
    selectionBox?.update()
    syncTrainingTargetsFromEditableObjects()
    emitEditorEvent()
    return
  }

  const point = screenToGround(event.clientX, event.clientY)
  if (!point) return

  object.position.x = point.x
  object.position.z = point.z
  selectionBox?.update()
```

```
  syncTrainingTargetsFromEditableObjects()
  emitEditorEvent()
}

function selectEditableObject(id) {
  selectedObjectId = id
  if (selectionBox) {
    scene.remove(selectionBox)
    selectionBox.dispose()
    selectionBox = null
  }
  const object = id ? editableObjects.get(id) : null
  if (object) {
    selectionBox = new THREE.BoxHelper(object, 0x4c9ffe)
    scene.add(selectionBox)
  }
  emitEditorEvent()
}

function moveSelectedObject(dx, dz, dy = 0) {
  const object = selectedObjectId ? editableObjects.get(selectedObjectId) : null
  if (!object) return
  object.position.x = THREE.MathUtils.clamp(object.position.x + dx, WORLD_LIMITS.minX, WORLD_LIMITS.maxX)
  object.position.z = THREE.MathUtils.clamp(object.position.z + dz, WORLD_LIMITS.minZ, WORLD_LIMITS.maxZ)
  object.position.y = THREE.MathUtils.clamp(object.position.y + dy, -50, 100)
  selectionBox?.update()
  syncTrainingTargetsFromEditableObjects()
  emitEditorEvent()
}

function rotateSelectedObject(angle) {
  const object = selectedObjectId ? editableObjects.get(selectedObjectId) : null
  if (!object) return
  object.rotation.y += angle
  selectionBox?.update()
  emitEditorEvent()
}

function scaleSelectedObject(factor) {
  const object = selectedObjectId ? editableObjects.get(selectedObjectId) : null
  if (!object || !Number.isFinite(factor) || factor <= 0) return
  object.scale.set(
    THREE.MathUtils.clamp(object.scale.x * factor, 0.01, 1000),
    THREE.MathUtils.clamp(object.scale.y * factor, 0.01, 1000),
    THREE.MathUtils.clamp(object.scale.z * factor, 0.01, 1000)
  )
  selectionBox?.update()
  emitEditorEvent()
}

function setSelectedObjectTransform(transform) {
  const object = selectedObjectId ? editableObjects.get(selectedObjectId) : null
  if (!object) return

  if (transform.position) {
    object.position.set(
      clampNumber(transform.position.x, object.position.x, WORLD_LIMITS.minX, WORLD_LIMITS.maxX),
      clampNumber(transform.position.y, object.position.y, -50, 100),
      clampNumber(transform.position.z, object.position.z, WORLD_LIMITS.minZ, WORLD_LIMITS.maxZ)
    )
  }
  if (transform.rotation) {
    object.rotation.set(
      finiteNumber(transform.rotation.x, object.rotation.x),
      finiteNumber(transform.rotation.y, object.rotation.y),
      finiteNumber(transform.rotation.z, object.rotation.z)
    )
  }
  if (transform.scale) {
    object.scale.set(
      clampNumber(transform.scale.x, object.scale.x, 0.01, 1000),
      clampNumber(transform.scale.y, object.scale.y, 0.01, 1000),
      clampNumber(transform.scale.z, object.scale.z, 0.01, 1000)
    )
  }
  selectionBox?.update()
```

```
  syncTrainingTargetsFromEditableObjects()
  emitEditorEvent()
}

function finiteNumber(value, fallback) {
  const number = Number(value)
  return Number.isFinite(number) ? number : fallback
}

function clampNumber(value, fallback, min, max) {
  return THREE.MathUtils.clamp(finiteNumber(value, fallback), min, max)
}

function deleteSelectedObject() {
  const object = selectedObjectId ? editableObjects.get(selectedObjectId) : null
  if (!object) return
  editorGroup.remove(object)
  editableObjects.delete(selectedObjectId)
  selectEditableObject(null)
  emitEditorEvent()
}

function clearEditableObjects() {
  Array.from(editableObjects.values()).forEach((object) => {
    editorGroup.remove(object)
  })
  editableObjects.clear()
  selectEditableObject(null)
  syncTrainingTargetsFromEditableObjects()
  emitEditorEvent()
}

async function importEditableObjects(objects) {
  clearEditableObjects()
  const loaded = await Promise.all(objects.map(async (sourceObject) => {
    const catalog = findCatalogItem(sourceObject.catalogKey)
    if (!catalog) return null
    return createEditableObject(catalog, sourceObject)
  }))
  for (const object of loaded) {
    if (!object) continue
    editorGroup.add(object)
    editableObjects.set(object.userData.editor.id, object)
  }
  if (!editorMode) {
    const first = objects.find((object) => object.inspectionPoint && object.position)
    if (first) {
      trainingSpawn.set(
        THREE.MathUtils.clamp(first.position.x - 11, WORLD_LIMITS.minX, WORLD_LIMITS.maxX),
        CAMERA_HEIGHT,
        THREE.MathUtils.clamp(first.position.z - 9, WORLD_LIMITS.minZ, WORLD_LIMITS.maxZ)
      )
      camera.position.copy(trainingSpawn)
      lastPosition.copy(trainingSpawn)
      yaw = INITIAL_YAW
      pitch = -0.06
      updateCameraRotation()
    }
  }
  syncTrainingTargetsFromEditableObjects()
  emitEditorEvent()
}

function syncTrainingTargetsFromEditableObjects() {
  const targets = Array.from(editableObjects.values()).filter((object) => object.userData.editor.inspectionPoint)
  signalRuntime.clear()
  if (targets.length === 0) {
    emitSignals()
    emitState(0, true)
    return
  }

  targets.forEach((object, index) => {
    const editor = object.userData.editor
    signalRuntime.set(editor.id, {
      id: editor.id,
```

```
        label: editor.task?.title || editor.name || `巡检点 ${index + 1}`,
        name: editor.name,
        catalogKey: editor.catalogKey,
        task: editor.task,
        state: editor.task?.faultType || 'normal',
        x: object.position.x,
        z: object.position.z,
        inspected: false,
        group: object,
        animateGroup: false
      })
    })
    emitSignals()
    emitState(0, true)
  }

  function exportEditableObjects() {
    return Array.from(editableObjects.values()).map((object) => ({
      id: object.userData.editor.id,
      catalogKey: object.userData.editor.catalogKey,
      name: object.userData.editor.name,
      position: { x: object.position.x, y: object.position.y, z: object.position.z },
      rotation: { x: object.rotation.x, y: object.rotation.y, z: object.rotation.z },
      scale: { x: object.scale.x, y: object.scale.y, z: object.scale.z },
      interactive: object.userData.editor.interactive,
      inspectionPoint: object.userData.editor.inspectionPoint,
      task: object.userData.editor.task
    }))
  }

  function updateSelectedObjectConfig(config) {
    const object = selectedObjectId ? editableObjects.get(selectedObjectId) : null
    if (!object) return

    object.userData.editor = {
      ...object.userData.editor,
      ...config,
      task: {
        ...createDefaultObjectTask(object.userData.editor.name),
        ...object.userData.editor.task,
        ...config.task
      }
    }
    syncTrainingTargetsFromEditableObjects()
    emitEditorEvent()
  }

  function createDefaultObjectTask(name) {
    return {
      title: `检查${name}`,
      description: '靠近目标设备后完成巡检确认。',
      faultType: 'normal',
      expectedAction: 'inspect',
      score: 10,
      hint: ''
    }
  }

    function setEditorMode(value) {
      editorMode = value
      if (editorMode) pause()
      emitEditorEvent()
    }

    function emitEditorEvent() {
      onEvent?.({
        type: 'editor',
        message: '场景编辑状态已更新',
        objects: exportEditableObjects(),
        selectedId: selectedObjectId
      })
    }

    function snapRotation(snap) {
      if (snap === 'trackside' || snap === 'turnout_side') return -ROUTE_ANGLE
      return 0
```

```
}

function playNotice() {
  if (!audioEnabled) return
  audio.notice.currentTime = 0
  audio.notice.play().catch(() => {})
}

function playAlarm() {
  if (!audioEnabled) return
  audio.alarm.currentTime = 0
  audio.alarm.play().catch(() => {})
}

function playBgm() {
  if (!audioEnabled || !running) return
  audio.bgm.play().catch(() => {})
}

function stopBgm() {
  audio.bgm.pause()
}

function start() {
  if (!ready || completed) return
  if (!running) runStartedAt = performance.now()
  if (!running && train && flatDistance(camera.position.x, camera.position.z, train.position.x, train.position.z) < 28) {
    trainProgress = 0.52
    const position = trainCurve.getPointAt(trainProgress)
    const lookAt = trainCurve.getPointAt((trainProgress + 0.006) % 1)
    train.position.set(position.x, 0.7, position.z)
    train.rotation.y = Math.atan2(lookAt.x - position.x, lookAt.z - position.z) + Math.PI / 2
  }
  lastWarningAt = performance.now()
  running = true
  state.running = true
  playBgm()
  if (canvas.requestPointerLock && !isTouchDevice()) {
    const lockRequest = canvas.requestPointerLock()
    if (lockRequest?.catch) lockRequest.catch(() => {})
  }
  emitState(0, true)
}

function pause() {
  running = false
  state.running = false
  stopBgm()
  if (document.pointerLockElement === canvas) {
    document.exitPointerLock()
  }
  emitState(0, true)
}

function reset() {
  running = false
  completed = false
  elapsed = 0
  distanceTravelled = 0
  health = 100
  yaw = INITIAL_YAW
  pitch = -0.06
  camera.position.copy(trainingSpawn)
  lastPosition.copy(camera.position)
  updateCameraRotation()
  signalRuntime.forEach((signal) => {
    signal.inspected = false
    const color = signalColor(signal.state)
    signal.light?.color?.setHex(color)
    signal.bulb?.material?.color?.setHex(color)
    signal.bulb?.material?.emissive?.setHex(color)
    signal.ring?.material?.color?.setHex(color)
    signal.ring?.material?.emissive?.setHex(color)
    signal.ring?.scale?.setScalar(1)
  })
  state.completed = false
```

```
    state.phase = ready ? '沿线巡视' : '模型加载'
    stopBgm()
    if (document.pointerLockElement === canvas) document.exitPointerLock()
    emitSignals()
    emitState(0, true)
  }

  function setAudioEnabled(value) {
    audioEnabled = value
    if (audioEnabled) {
      playBgm()
    } else {
      audio.alarm.pause()
      audio.notice.pause()
      stopBgm()
    }
    emitState(0, true)
  }

  function setVirtualInput(name, value) {
    keys.set(name, value)
    if (value && !running && ready && !completed) start()
  }

  function isTouchDevice() {
    return window.matchMedia('(pointer: coarse)').matches
  }

  function dispose() {
    cancelAnimationFrame(animationFrame)
    resizeObserver?.disconnect()
    window.removeEventListener('keydown', onKeyDown)
    window.removeEventListener('keyup', onKeyUp)
    document.removeEventListener('pointerlockchange', onPointerLockChange)
    canvas.removeEventListener('mousemove', onMouseMove)
    canvas.removeEventListener('pointerdown', onPointerDown)
    canvas.removeEventListener('pointermove', onPointerMove)
    canvas.removeEventListener('contextmenu', preventCanvasMenu)
    window.removeEventListener('pointerup', onPointerUp)
    stopBgm()
    renderer.dispose()
    scene.traverse((object) => {
      if (!object.isMesh) return
      object.geometry?.dispose()
      if (Array.isArray(object.material)) {
        object.material.forEach((material) => material.dispose())
      } else {
        object.material?.dispose()
      }
    })
  }

  init()

  return {
    ready: modelsReady,
    start,
    pause,
    reset,
    dispose,
    setAudioEnabled,
    setVirtualInput,
    setEditorMode,
    addCatalogObject,
    moveSelectedObject,
    rotateSelectedObject,
    scaleSelectedObject,
    setSelectedObjectTransform,
    deleteSelectedObject,
    clearEditableObjects,
    importEditableObjects,
    exportEditableObjects,
    updateSelectedObjectConfig
  }
}
```

src/stores/auth.js

```
import { computed, ref } from 'vue'
import { defineStore } from 'pinia'
import { authApi } from '../api/auth'
import { userApi } from '../api/users'
import { onAuthFailure } from '../api/client'
import {
  clearSession,
  getAccessToken,
  getStoredUser,
  saveSession,
  saveUser,
} from '../api/tokenStore'

export const ROLE_LABELS = {
  student: '学生',
  teacher: '老师',
  admin: '管理员',
}

export const useAuthStore = defineStore('auth', () => {
  const user = ref(getStoredUser())
  const accessToken = ref(getAccessToken())
  // idle → hydrating → ready。路由守卫靠它避免"刷新页面被误判成未登录"。
  const status = ref('idle')

  const isAuthenticated = computed(() => Boolean(user.value && accessToken.value))
  const isAdmin = computed(() => user.value?.role === 'admin')
  const isTeacher = computed(() => user.value?.role === 'teacher' || isAdmin.value)
  const roleLabel = computed(() => ROLE_LABELS[user.value?.role] ?? '访客')
  const displayName = computed(() => user.value?.displayName || user.value?.username || '')

  /** 认证彻底失效时的统一出口：清干净并跳登录页。 */
  let onSignedOut = null
  function setSignedOutHandler(handler) {
    onSignedOut = handler
  }

  onAuthFailure((reason) => {
    clear()
    onSignedOut?.(reason)
  })

  function applySession(payload) {
    accessToken.value = payload.accessToken
    user.value = payload.user
    saveSession(payload)
  }

  function clear() {
    accessToken.value = null
    user.value = null
    clearSession()
  }

  /**
   * 启动时调用一次：有令牌就回库确认用户仍然有效。
   * 不能只信 localStorage 里的用户快照——账号可能已被禁用或改角色。
   */
  async function hydrate() {
    if (status.value === 'ready') return
    status.value = 'hydrating'

    if (!getAccessToken()) {
      clear()
      status.value = 'ready'
      return
    }

    try {
      const data = await authApi.me()
      user.value = data.user
      saveUser(data.user)
    } catch (error) {
```

```
    // 401 已由 client.js 触发 onAuthFailure 清session；其它错误（断网）
    // 保留本地快照，让用户还能看到界面，只是写操作会失败。
    if (error?.status === 401) clear()
  } finally {
    status.value = 'ready'
  }
}

/**
 * 验证账号密码、记录登录结果并签发会话。
 * @param {string} username 登录名
 * @param {string} password 用户输入的明文密码
 * @param {object} ctx 客户端网络上下文
 * @returns {object} 含访问与刷新令牌的会话
 */
async function login(username, password) {
  const data = await authApi.login({ username, password })
  applySession(data)
  status.value = 'ready'
  return data.user
}

async function devLogin(role) {
  const data = await authApi.devLogin(role)
  applySession(data)
  status.value = 'ready'
  return data.user
}

/**
 * 按角色规则创建账户并记入审计日志。
 * @param {object} input 新账号资料和申请角色
 * @param {object} ctx 客户端网络上下文
 * @returns {object} 不含密码哈希的公开用户信息
 */
async function register(payload) {
  await authApi.register(payload)
  // 注册成功后直接登录，省掉一次手动输入。
  return login(payload.username, payload.password)
}

async function logout() {
  try {
    await authApi.logout({ all: false })
  } catch {
    // 服务端吊销失败也要让本地退出，否则用户会卡在"退不出去"的状态。
  }
  clear()
}

async function updateProfile(payload) {
  const data = await userApi.updateProfile(payload)
  user.value = data.user
  saveUser(data.user)
  return data.user
}

/**
 * 修改密码。服务端会吊销该用户【全部】刷新令牌——这是有意的：
 * 账号被盗后改密码必须能踢掉攻击者的会话。代价是本机也要重新登录，
 * 所以这里直接清空会话，由调用方引导用户去登录页。
 */
async function changePassword(currentPassword, newPassword) {
  const data = await userApi.changePassword(currentPassword, newPassword)
  clear()
  return data
}

function hasRole(...roles) {
  return Boolean(user.value && roles.includes(user.value.role))
}

return {
  user,
  accessToken,
  status,
```

```
    isAuthenticated,
    isAdmin,
    isTeacher,
    roleLabel,
    displayName,
    setSignedOutHandler,
    hydrate,
    login,
    devLogin,
    register,
    logout,
    updateProfile,
    changePassword,
    hasRole,
    clear,
  }
})
```

src/stores/agent.js

```
import { computed, ref } from 'vue'
import { defineStore } from 'pinia'
import { aiApi } from '../api/ai'
import { createVoiceSession } from '../voice'

const MODEL_STORAGE_KEY = 'rsr.agentModel'
const VOICE_STORAGE_KEY = 'rsr.agentVoiceMode'

/** 语音档位：关 / 仅朗读 / 连续对话（朗读 + 说完自动发送）。 */
export const VOICE_MODES = ['off', 'tts', 'full']
export const VOICE_MODE_LABELS = { off: '语音关闭', tts: '仅朗读', full: '连续对话' }

function readStored(key, fallback) {
  try {
    return localStorage.getItem(key) ?? fallback
  } catch {
    // 隐私模式下 localStorage 可能直接抛异常，不能让整个 store 起不来。
    return fallback
  }
}

function writeStored(key, value) {
  try {
    localStorage.setItem(key, value)
  } catch {
    /* 存不下就算了，不影响本次会话使用 */
  }
}

export const useAgentStore = defineStore('agent', () => {
  /* ---------------------------- 弹框与模型 ---------------------------- */

  const open = ref(false)
  const models = ref([])
  const modelsError = ref('')
  const loadingModels = ref(false)
  const model = ref(readStored(MODEL_STORAGE_KEY, ''))

  /** 游戏内注入的场景上下文，作为系统提示词的一部分发给后端。 */
  const sceneContext = ref('')
  const equipmentContext = ref(null)

  const availableModels = computed(() => models.value.filter((item) => item.available && !item.isEmbedding))
  const currentModel = computed(
    () => availableModels.value.find((item) => item.name === model.value) ?? null
  )

  async function loadModels({ refresh = false } = {}) {
    if (loadingModels.value) return
    loadingModels.value = true
    modelsError.value = ''
    try {
      const data = await aiApi.models(refresh)
      models.value = data.models ?? []
```

```
    const names = availableModels.value.map((item) => item.name)
    // 存着的模型可能已经被删了，回落到服务端默认模型。
    if (!names.includes(model.value)) {
      model.value = names.find((name) => /deepseek/i.test(name)) ||
        (names.includes(data.defaultModel) ? data.defaultModel : (names[0] ?? ''))
      writeStored(MODEL_STORAGE_KEY, model.value)
    }
  } catch (error) {
    modelsError.value = error?.message || '模型列表加载失败'
  } finally {
    loadingModels.value = false
  }
}

function selectModel(name) {
  model.value = name
  writeStored(MODEL_STORAGE_KEY, name)
}

function toggle(next) {
  open.value = typeof next === 'boolean' ? next : !open.value
  if (open.value) {
    if (models.value.length === 0) loadModels()
    if (voiceMode.value !== 'off' && !voice.session) initVoice()
  } else {
    stopSpeaking()
  }
}

/* ------------------------------ 会话与消息 ------------------------------ */

const conversations = ref([])
const conversationId = ref('')
const messages = ref([])
const streaming = ref(false)
const thinking = ref(false)
const partial = ref('')
const error = ref('')
let handle = null

function reset() {
  stop()
  conversationId.value = ''
  messages.value = []
  partial.value = ''
  thinking.value = false
  error.value = ''
}

async function loadConversations() {
  try {
    const data = await aiApi.conversations({ page: 1, pageSize: 30 })
    conversations.value = data.items ?? []
  } catch {
    // 历史列表拉不到不影响新对话，静默即可。
    conversations.value = []
  }
}

async function openConversation(id) {
  stop()
  conversationId.value = id
  error.value = ''
  partial.value = ''
  try {
    const data = await aiApi.messages(id, { page: 1, pageSize: 200 })
    messages.value = (data.items ?? []).map((item) => ({
      id: item.id,
      role: item.role,
      content: item.content,
      model: item.model,
    }))
  } catch (err) {
    error.value = err?.message || '历史消息加载失败'
  }
}
```

```
async function removeConversation(id) {
  await aiApi.deleteConversation(id)
  conversations.value = conversations.value.filter((item) => item.id !== id)
  if (conversationId.value === id) reset()
}

/**
 * 发送一条提问并流式接收回答。
 *
 * 这里不 await 整个流，而是把 handle 存起来让 UI 能随时中断——
 * 用户点了「停止」或在生成中途又发了一条，都必须能立刻掐断。
 */
function send(text) {
  const content = text?.trim()
  if (!content || streaming.value) return

  // 发新消息视为放弃上一轮，先断开旧连接，避免两条流同时往 messages 里写。
  stop()

  error.value = ''
  partial.value = ''
  thinking.value = false
  streaming.value = true
  messages.value.push({ id: `local-${Date.now()}`, role: 'user', content })

  // 收音期间用户又发消息：先停掉麦克风，否则识别结果会盖到输入框里。
  if (voice.listening) stopListening()

  handle = aiApi.chat(
    {
      conversationId: conversationId.value || undefined,
      model: model.value || undefined,
      message: content,
      sceneContext: sceneContext.value || undefined,
      equipment: equipmentContext.value || undefined,
    },
    {
      onControl: (type, payload) => {
        if (type === 'meta') {
          conversationId.value = payload.conversationId
        } else if (type === 'thinking') {
          // qwen3 这类思考模型会先想几秒到几十秒，content 一直为空。
          // 收到这一帧就把「思考中」显示出来，避免用户对着空白等。
          thinking.value = true
        } else if (type === 'done') {
          finish(payload)
        } else if (type === 'error') {
          fail(payload?.message || '模型返回错误')
        }
      },
      onFrame: (frame) => {
        const delta = frame?.message?.content
        if (delta) {
          thinking.value = false
          partial.value += delta
        }
      },
      onError: (err) => fail(err?.message || '对话请求失败'),
    }
  )
}

function finish(payload) {
  const answer = partial.value
  if (answer) {
    messages.value.push({
      id: payload?.assistantMessageId ?? `local-a-${Date.now()}`,
      role: 'assistant',
      content: answer,
      model: model.value,
    })
    if (voiceMode.value !== 'off') speak(answer)
  }
  partial.value = ''
  thinking.value = false
  streaming.value = false
```

```
  handle = null
  if (payload?.assistantMessageId) loadConversations()
}

function fail(message) {
  error.value = message
  // 已经流出来的部分仍然保留在 messages 里，否则用户会觉得内容凭空消失了。
  if (partial.value) {
    messages.value.push({ id: `local-a-${Date.now()}`, role: 'assistant', content: partial.value, model: model.value })
  }
  partial.value = ''
  thinking.value = false
  streaming.value = false
  handle = null
}

function stop() {
  handle?.stop()
  handle = null
  if (partial.value) {
    messages.value.push({ id: `local-a-${Date.now()}`, role: 'assistant', content: partial.value, model: model.value })
    partial.value = ''
  }
  thinking.value = false
  streaming.value = false
}

/* ------------------------------ 语音 ------------------------------ */

const voiceMode = ref(readStored(VOICE_STORAGE_KEY, 'off'))
const voice = ref({ session: null, kind: 'none', label: '', listening: false, speaking: false, level: 0, error: '' })

// 由 AgentDialog 注册：识别文本要投递到它的输入框，store 不持有输入框引用。
let onPartialText = null
let onFinalText = null

function setVoiceMode(mode) {
  voiceMode.value = mode
  writeStored(VOICE_STORAGE_KEY, mode)
  if (mode === 'off') {
    stopListening()
    stopSpeaking()
  } else if (!voice.value.session) {
    initVoice()
  }
}

function initVoice() {
  if (voice.value.session) return voice.value.session
  const session = createVoiceSession({
    onPartial: (text) => {
      // 部分识别结果实时灌进输入框，用户能看到自己说的话正在被识别。
      voice.value = { ...voice.value, error: '' }
      onPartialText?.(text)
    },
    onFinal: (text) => {
      voice.value = { ...voice.value, listening: false, level: 0 }
      onFinalText?.(text)
    },
    onError: (err) => {
      voice.value = { ...voice.value, listening: false, level: 0, error: err?.message || '语音识别失败' }
    },
    onLevel: (level) => {
      voice.value = { ...voice.value, level }
    },
    onSpeakStart: () => {
      voice.value = { ...voice.value, speaking: true }
    },
    onSpeakEnd: () => {
      voice.value = { ...voice.value, speaking: false }
    },
  })
  voice.value = { ...voice.value, session, kind: session.kind, label: session.label }
  return session
}
function bindTextSink({ onPartial, onFinal }) {
```

```
    onPartialText = onPartial
    onFinalText = onFinal
  }

  function startListening() {
    const session = initVoice()
    // 打断播报：用户开口就说明不想听了。
    session.stopSpeaking()
    voice.value = { ...voice.value, error: '' }
    const started = session.startListening()
    if (started) voice.value = { ...voice.value, listening: true }
  }

  function stopListening() {
    voice.value.session?.stopListening()
    voice.value = { ...voice.value, listening: false, level: 0 }
  }

  function speak(text) {
    const session = initVoice()
    session.speak(text)
  }

  function stopSpeaking() {
    voice.value.session?.stopSpeaking()
    voice.value = { ...voice.value, speaking: false }
  }

  const voiceSupported = computed(() => voice.value.kind !== 'none')

  return {
    open,
    models,
    modelsError,
    loadingModels,
    model,
    currentModel,
    availableModels,
    sceneContext,
    equipmentContext,
    conversations,
    conversationId,
    messages,
    streaming,
    thinking,
    partial,
    error,
    voiceMode,
    voice,
    voiceSupported,
    toggle,
    loadModels,
    selectModel,
    loadConversations,
    openConversation,
    removeConversation,
    send,
    stop,
    reset,
    setVoiceMode,
    bindTextSink,
    startListening,
    stopListening,
    speak,
    stopSpeaking,
  }
})
```

src/api/client.js

```
/**
 * HTTP 客户端。基于原生 fetch，不引 axios。
 *
 * 三件事：
```

```
 * 1. 统一带 Bearer 头、统一把后端的 {ok,code,message} 错误转成 ApiError。
 * 2. access token 过期（401）时自动刷新一次并重放原请求。
 *    并发请求同时 401 时共用一个刷新 Promise，否则会连发多次刷新，
 *    而刷新令牌是轮换 + 重放检测的，并发刷新会被判为重放并吊销整个令牌家族。
 * 3. 完全同源：base 固定 /api，dev 与 preview 都走 Vite 代理。
 */
import { clearSession, getAccessToken, getRefreshToken, saveSession } from './tokenStore'

const BASE = '/api'

/** 认证失效时通知外部（auth store 监听后跳登录页）。 */
const authFailureListeners = new Set()

export function onAuthFailure(listener) {
  authFailureListeners.add(listener)
  return () => authFailureListeners.delete(listener)
}

function emitAuthFailure(reason) {
  for (const listener of authFailureListeners) {
    try {
      listener(reason)
    } catch {
      /* 单个监听器出错不影响其它监听器 */
    }
  }
}

export class ApiError extends Error {
  constructor(status, code, message, details) {
    super(message || '请求失败')
    this.name = 'ApiError'
    this.status = status
    this.code = code || 'unknown'
    this.details = details
  }

  /** 网络层失败（断网、后端没起）与业务错误区分开，便于给不同的提示文案。 */
  get isNetworkError() {
    return this.status === 0
  }
}

function buildUrl(path, query) {
  const url = `${BASE}${path}`
  if (!query) return url
  const params = new URLSearchParams()
  for (const [key, value] of Object.entries(query)) {
    if (value === undefined || value === null || value === '') continue
    params.append(key, String(value))
  }
  const qs = params.toString()
  return qs ? `${url}?${qs}` : url
}

async function parseBody(response) {
  const type = response.headers.get('content-type') || ''
  if (!type.includes('application/json')) {
    const text = await response.text().catch(() => '')
    return text ? { message: text } : {}
  }
  return response.json().catch(() => ({}))
}

/** 裸请求：不带令牌、不自动刷新，供刷新接口自身与流式连接复用。 */
async function rawFetch(method, path, { body, query, token, signal, headers } = {}) {
  const init = {
    method,
    headers: {
      Accept: 'application/json',
      ...(body !== undefined ? { 'Content-Type': 'application/json' } : {}),
      ...(token ? { Authorization: `Bearer ${token}` } : {}),
      ...headers,
    },
    signal,
  }
```

```
  if (body !== undefined) init.body = JSON.stringify(body)

  try {
    return await fetch(buildUrl(path, query), init)
  } catch (error) {
    if (error?.name === 'AbortError') throw error
    throw new ApiError(0, 'network_error', '无法连接服务器，请检查网络或稍后重试')
  }
}

// 刷新进行中的 Promise。并发 401 共用它，避免同一次会话发出多个刷新请求。
let refreshPromise = null

/**
 * 为过期访问令牌串行刷新一次登录态。
 * @returns {object} 是否成功刷新
 */
async function refreshSession() {
  const refreshToken = getRefreshToken()
  if (!refreshToken) return false

  if (!refreshPromise) {
    refreshPromise = (async () => {
      try {
        const response = await rawFetch('POST', '/auth/refresh', { body: { refreshToken } })
        const data = await parseBody(response)
        if (!response.ok || !data.ok) return false
        saveSession({
          accessToken: data.accessToken,
          refreshToken: data.refreshToken,
          user: data.user,
        })
        return true
      } catch {
        return false
      } finally {
        // 清空要放在微任务之后，让同一轮并发请求都能复用到这个 Promise。
        setTimeout(() => {
          refreshPromise = null
        }, 0)
      }
    })()
  }

  return refreshPromise
}

/**
 * 发起请求。401 时自动刷新一次并重放。
 * @param {object} options
 * @param {boolean} [options.skipAuth] 不带令牌（登录、注册等公开接口）
 * @param {boolean} [options.skipRefresh] 401 时不尝试刷新（刷新接口自身用）
 */
/**
 * 发送带身份的 API 请求，并在 401 后重试一次。
 * @param {string} method HTTP 方法
 * @param {string} path 相对 API 路径
 * @param {object} options 请求体、查询参数及身份选项
 * @returns {object} 解析后的 JSON 响应
 */
export async function request(method, path, options = {}) {
  const { skipAuth = false, skipRefresh = false, ...rest } = options

  const send = (token) => rawFetch(method, path, { ...rest, token: skipAuth ? undefined : token })

  let response = await send(getAccessToken())

  if (response.status === 401 && !skipAuth && !skipRefresh && getRefreshToken()) {
    const refreshed = await refreshSession()
    if (refreshed) {
      response = await send(getAccessToken())
    } else {
      clearSession()
      emitAuthFailure('refresh_failed')
    }
  }
```

```
  if (response.status === 204) return null

  const data = await parseBody(response)

  if (!response.ok) {
    const error = new ApiError(
      response.status,
      data.code,
      data.message || `请求失败（HTTP ${response.status}）`,
      data.details
    )
    // 401 走到这里说明刷新也没救回来，通知外部回登录页。
    if (response.status === 401 && !skipAuth) emitAuthFailure(error.code || 'unauthorized')
    throw error
  }

  return data
}

export const http = {
  get: (path, options) => request('GET', path, options),
  post: (path, body, options) => request('POST', path, { ...options, body }),
  put: (path, body, options) => request('PUT', path, { ...options, body }),
  patch: (path, body, options) => request('PATCH', path, { ...options, body }),
  delete: (path, options) => request('DELETE', path, options),
}

/**
 * NDJSON 流式请求（智能体对话用）。
 *
 * 不用 EventSource：它既不能带 Authorization 头，也不能发 POST body，
 * 用 JWT 就只能把令牌塞进 query string，那会漏进 FRP 与代理日志。
 * fetch + getReader 支持 Bearer 头、请求体与 AbortController。
 *
 * @returns {Promise<{stop: () => void, done: Promise<void>}>}
 */
export function streamNdjson(path, { body, signal, onFrame, onControl, onError, onOpen } = {}) {
  const controller = new AbortController()
  // 外部传了 signal 就联动，任一中断都能停掉底层连接。
  if (signal) {
    if (signal.aborted) controller.abort()
    else signal.addEventListener('abort', () => controller.abort(), { once: true })
  }

  const done = (async () => {
    let response
    try {
      response = await rawFetch('POST', path, {
        body,
        token: getAccessToken(),
        signal: controller.signal,
      })
    } catch (error) {
      if (error?.name === 'AbortError') return
      onError?.(error)
      return
    }

    if (response.status === 401) {
      // 流式请求不做自动刷新重放：重放会丢掉已经选好的对话上下文，
      // 直接让前端提示重新登录更可预期。
      clearSession()
      emitAuthFailure('unauthorized')
      onError?.(new ApiError(401, 'unauthorized', '登录已过期，请重新登录'))
      return
    }

    if (!response.ok || !response.body) {
      const data = await parseBody(response).catch(() => ({}))
      onError?.(new ApiError(response.status, data.code, data.message || '对话请求失败', data.details))
      return
    }

    onOpen?.()

    const reader = response.body.getReader()
```

```
    const decoder = new TextDecoder('utf-8')
    let buffer = ''

    try {
      for (;;) {
        const { done: finished, value } = await reader.read()
        if (finished) break
        buffer += decoder.decode(value, { stream: true })

        // 帧以换行分隔；最后一段可能是不完整的行，留在 buffer 里等下一块。
        let index = buffer.indexOf('\n')
        while (index !== -1) {
          const line = buffer.slice(0, index).trim()
          buffer = buffer.slice(index + 1)
          if (line) {
            try {
              const frame = JSON.parse(line)
              if (frame.__railway) onControl?.(frame.__railway, frame)
              else onFrame?.(frame)
            } catch {
              /* 半行或坏帧直接跳过，不能让一帧毁掉整个流 */
            }
          }
          index = buffer.indexOf('\n')
        }
      }
      // 收尾：服务端若没以换行结束，最后一行仍在 buffer 里。
      const tail = buffer.trim()
      if (tail) {
        try {
          const frame = JSON.parse(tail)
          if (frame.__railway) onControl?.(frame.__railway, frame)
          else onFrame?.(frame)
        } catch {
          /* 忽略 */
        }
      }
    } catch (error) {
      if (error?.name !== 'AbortError') onError?.(error)
    } finally {
      reader.cancel().catch(() => {})
    }
  })()

  return { stop: () => controller.abort(), done }
}
```

server/src/routes/sceneRoutes.js

```
import { Router } from 'express'
import { z } from 'zod'
import { optionalAuth, requireAuth, requireRole } from '../middleware/auth.js'
import { validate } from '../middleware/validate.js'
import { getClientIp } from '../middleware/rateLimit.js'
import * as scenes from '../repositories/sceneRepository.js'
import { insertAuditLog } from '../repositories/logRepository.js'
import { buildPageParams, pageEnvelope } from '../services/pagination.js'
import { forbidden, notFound } from '../utils/httpError.js'

export const sceneRouter = Router()

const ctx = (req) => ({ ip: getClientIp(req), userId: req.user?.id, username: req.user?.username })

const pageQuery = z.object({
  page: z.coerce.number().int().positive().optional(),
  pageSize: z.coerce.number().int().positive().optional(),
  q: z.string().trim().max(64).optional(),
})

/**
 * 场景列表。
 * 未登录也能读已发布场景（保留原有的免登录练习流程），但只有登录后
 * 才能看到自己未发布的草稿。
 */
```

```
sceneRouter.get(
  '/',
  optionalAuth,
  validate({
    query: z.object({
      ...pageQuery.shape,
      published: z
        .enum(['0', '1', 'true', 'false'])
        .optional()
        .transform((value) => (value === undefined ? undefined : value === '1' || value === 'true')),
      mine: z
        .enum(['0', '1', 'true', 'false'])
        .optional()
        .transform((value) => value === '1' || value === 'true'),
    }),
  }),
  async (req, res, next) => {
    try {
      const query = req.validated.query
      const params = buildPageParams(query, { defaultPageSize: 50 })

      if (query.mine) {
        if (!req.user) return next(forbidden('请先登录', 'login_required'))
        const rows = await scenes.listScenes({ ...params, ownerId: req.user.id, q: query.q })
        return res.json({ ok: true, ...pageEnvelope(rows, params) })
      }

      // 默认只给已发布的场景；管理员可显式查看全部。
      const published = query.published ?? true
      const includeDeleted = false
      const rows = await scenes.listScenes({
        ...params,
        q: query.q,
        published,
        includeDeleted,
      })
      res.json({ ok: true, ...pageEnvelope(rows, params) })
    } catch (error) {
      next(error)
    }
  }
)

/** 学生端进入练习时取完整场景（含 payload）。 */
sceneRouter.get('/:id', optionalAuth, async (req, res, next) => {
  try {
    const scene = await scenes.getScene(req.params.id)
    if (!scene || scene.deleted_at) return next(notFound('场景不存在', 'scene_not_found'))

    // 未发布的草稿只有作者本人和管理员能看。
    if (!scene.published) {
      const isOwner = req.user && scene.owner_id === req.user.id
      const isAdmin = req.user?.role === 'admin'
      if (!isOwner && !isAdmin) {
        return next(forbidden('该场景尚未发布', 'scene_not_published'))
      }
    }

    res.json({ ok: true, scene })
  } catch (error) {
    next(error)
  }
})

sceneRouter.post(
  '/',
  requireAuth,
  requireRole('teacher', 'admin'),
  validate({
    body: z.object({
      id: z.string().max(64).optional(),
      name: z.string().trim().min(1, '请填写场景名称').max(100),
      description: z.string().trim().max(500).optional().nullable(),
      difficulty: z.enum(['easy', 'normal', 'hard']).optional().nullable(),
      payload: z.record(z.string(), z.unknown()).optional(),
    }),
```

```
  }),
  async (req, res, next) => {
    try {
      const body = req.validated.body

      // 带 id 视为更新，需要校验归属，避免覆盖别人的场景。
      if (body.id) {
        const existing = await scenes.getScene(body.id)
        if (existing && existing.owner_id && existing.owner_id !== req.user.id && req.user.role !== 'admin') {
          return next(forbidden('无权修改他人的场景', 'scene_forbidden'))
        }
      }

      const scene = await scenes.upsertScene({
        id: body.id,
        name: body.name,
        description: body.description,
        difficulty: body.difficulty,
        ownerId: req.user.id,
        payload: body.payload,
      })

      await insertAuditLog({
        ...ctx(req),
        action: 'scene.save',
        targetType: 'scene',
        targetId: scene.id,
        detail: { name: scene.name },
      })

      res.status(201).json({ ok: true, scene })
    } catch (error) {
      next(error)
    }
  }
)

sceneRouter.post('/:id/publish', requireAuth, requireRole('teacher', 'admin'), async (req, res, next) => {
  try {
    const existing = await scenes.getScene(req.params.id)
    if (!existing || existing.deleted_at) return next(notFound('场景不存在', 'scene_not_found'))
    if (existing.owner_id && existing.owner_id !== req.user.id && req.user.role !== 'admin') {
      return next(forbidden('无权发布他人的场景', 'scene_forbidden'))
    }

    const published = req.body?.published !== false
    const scene = await scenes.setPublished(req.params.id, published)

    await insertAuditLog({
      ...ctx(req),
      action: published ? 'scene.publish' : 'scene.unpublish',
      targetType: 'scene',
      targetId: scene.id,
    })

    res.json({ ok: true, scene })
  } catch (error) {
    next(error)
  }
})

sceneRouter.delete('/:id', requireAuth, requireRole('teacher', 'admin'), async (req, res, next) => {
  try {
    const existing = await scenes.getScene(req.params.id)
    if (!existing || existing.deleted_at) return next(notFound('场景不存在', 'scene_not_found'))
    if (existing.owner_id && existing.owner_id !== req.user.id && req.user.role !== 'admin') {
      return next(forbidden('无权删除他人的场景', 'scene_forbidden'))
    }

    await scenes.softDeleteScene(req.params.id)
    await insertAuditLog({
      ...ctx(req),
      action: 'scene.delete',
      targetType: 'scene',
      targetId: req.params.id,
    })
```

```
    res.json({ ok: true })
  } catch (error) {
    next(error)
  }
})

/* ------------------------------ 成绩记录 ------------------------------ */

export const recordRouter = Router()

recordRouter.get(
  '/',
  requireAuth,
  validate({
    query: z.object({
      ...pageQuery.shape,
      sceneId: z.string().max(64).optional(),
      mine: z.enum(['0', '1']).optional(),
    }),
  }),
  async (req, res, next) => {
    try {
      const query = req.validated.query
      const params = buildPageParams(query)

      // 非管理员只能看自己的成绩。
      const scopedUserId = req.user.role === 'admin' && query.mine !== '1' ? undefined : req.user.id

      const rows = await scenes.listRecords({
        ...params,
        userId: scopedUserId,
        sceneId: query.sceneId,
        q: query.q,
      })
      res.json({ ok: true, ...pageEnvelope(rows, params) })
    } catch (error) {
      next(error)
    }
  }
)

recordRouter.post(
  '/',
  requireAuth,
  validate({
    body: z.object({
      id: z.string().max(64).optional(),
      sceneId: z.string().max(64).optional().nullable(),
      sceneName: z.string().max(100).optional().nullable(),
      studentName: z.string().max(50).optional().nullable(),
      score: z.number().int().min(0).max(1000).optional().nullable(),
      elapsedSeconds: z.number().int().min(0).max(86_400).optional().nullable(),
      completed: z.boolean().optional(),
      inspectedCount: z.number().int().min(0).optional().nullable(),
      mistakeCount: z.number().int().min(0).optional().nullable(),
      payload: z.record(z.string(), z.unknown()).optional(),
    }),
  }),
  async (req, res, next) => {
    try {
      const record = await scenes.insertRecord({
        ...req.validated.body,
        // 成绩一律记在当前登录用户名下，不接受客户端伪造 userId。
        userId: req.user.id,
        studentName: req.validated.body.studentName || req.user.display_name || req.user.username,
      })
      res.status(201).json({ ok: true, record })
    } catch (error) {
      next(error)
    }
  }
)
```

server/src/routes/authRoutes.js

```
import { Router } from 'express'
import { z } from 'zod'
import { config } from '../config.js'
import { requireAuth } from '../middleware/auth.js'
import { validate } from '../middleware/validate.js'
import { getClientIp, rateLimit } from '../middleware/rateLimit.js'
import * as authService from '../services/authService.js'
import { rotateRefreshToken, signAccessToken } from '../services/tokenService.js'
import { toPublicUser } from '../services/authService.js'
import { pool } from '../db/pool.js'
import { HttpError, forbidden } from '../utils/httpError.js'
import { insertAuditLog } from '../repositories/logRepository.js'
import * as users from '../repositories/userRepository.js'
import { exchangeOidcCode, oidcEnabled, startOidc, takeOidcTransaction } from '../services/oidcService.js'
import { isLocalDevRequest, listDevTestAccounts, loginAsDevTestAccount } from '../services/devTestAccounts.js'

export const authRouter = Router()

authRouter.get('/dev-login/config', (req, res) => {
  res.setHeader('Cache-Control', 'no-store')
  res.json({ enabled: isLocalDevRequest(req), accounts: isLocalDevRequest(req) ? listDevTestAccounts() : [] })
})

authRouter.post('/dev-login',
  validate({ body: z.object({ id: z.string().max(64) }) }),
  async (req, res, next) => {
    if (!isLocalDevRequest(req)) return next(forbidden('测试登录仅限本机开发环境', 'dev_login_disabled'))
    try {
      const result = await loginAsDevTestAccount(req.validated.body.id, ctx(req))
      res.setHeader('Cache-Control', 'no-store')
      res.json({ ok: true, ...result })
    } catch (error) {
      next(error)
    }
  }
)

authRouter.get('/oidc/config', (_req, res) => res.json({ enabled: oidcEnabled() }))

authRouter.post('/oidc/start', (req, res, next) => {
  const mode = req.body?.mode === 'link' ? 'link' : 'login'
  const start = async () => {
    try {
      const result = await startOidc({ mode, userId: mode === 'link' ? req.user.id : null, redirectUri: String(req.body?.redirectUri || '') })
      res.cookie('rsr_oidc', result.cookieKey, { httpOnly: true, sameSite: 'lax', secure: req.secure, path: '/api/auth/oidc', maxAge: 600_000 })
      res.json({ authorizationUrl: result.authorizationUrl })
    } catch (error) { next(error) }
  }
  if (mode === 'link') return requireAuth(req, res, start)
  return start()
})

authRouter.post('/oidc/callback', async (req, res, next) => {
  const transaction = takeOidcTransaction(req.cookies?.rsr_oidc, String(req.body?.state || ''))
  res.clearCookie('rsr_oidc', { httpOnly: true, sameSite: 'lax', secure: req.secure, path: '/api/auth/oidc' })
  if (!transaction) return next(new HttpError(401, 'oidc_state_invalid', '统一登录状态已过期，请重新开始'))
  const complete = async () => {
    try {
      if (transaction.mode === 'link' && String(req.user?.id) !== String(transaction.userId)) {
        return next(new HttpError(401, 'oidc_link_session_mismatch', '绑定账号的登录状态已失效，请重新登录后重试'))
      }
      const subject = await exchangeOidcCode(transaction, String(req.body?.code || ''))
      if (transaction.mode === 'link') {
        const linked = await users.bindOidcSubject(transaction.userId, subject)
        if (!linked) return next(new HttpError(409, 'oidc_link_conflict', '本地账号不存在、已停用或已关联其他统一身份'))
        await insertAuditLog({ userId: linked.id, username: linked.username, action: 'auth.oidc.link', targetType: 'user', targetId: linked.id, ip: get
        return res.json({ mode: 'link', linked: true })
      }
      const session = await authService.loginWithOidcSubject(subject, ctx(req))
      return res.json({ mode: 'login', ...session })
    } catch (error) {
      if (error?.code === '23505') error.status = 409
      next(error)
    }
  }
  if (transaction.mode === 'link') return requireAuth(req, res, complete)
```

```
  return complete()
})

authRouter.get('/oidc/status', requireAuth, async (req, res, next) => {
  try {
    const result = await pool.query('SELECT oidc_subject IS NOT NULL AS linked FROM users WHERE id = $1', [req.user.id])
    res.json({ enabled: oidcEnabled(), linked: Boolean(result.rows[0]?.linked) })
  } catch (error) { next(error) }
})

const ctx = (req) => ({
  ip: getClientIp(req),
  userAgent: req.headers['user-agent'],
  userId: req.user?.id,
  username: req.user?.username,
})

const usernameSchema = z
  .string()
  .min(3, '用户名至少 3 位')
  .max(32, '用户名最多 32 位')
  .regex(/^[A-Za-z0-9_.-]+$/, '用户名只能包含字母、数字、下划线、点和横线')

const passwordSchema = z
  .string()
  .min(8, '密码至少 8 位')
  .max(72, '密码最多 72 位')
  .regex(/[A-Za-z]/, '密码必须包含字母')
  .regex(/[0-9]/, '密码必须包含数字')

authRouter.post(
  '/register',
  rateLimit({ ...config.rateLimit.register, keyPrefix: 'auth-register' }),
  validate({
    body: z.object({
      username: usernameSchema,
      password: passwordSchema,
      displayName: z.string().trim().max(32).optional(),
      email: z.string().trim().email('邮箱格式不正确').max(128).optional().nullable(),
      phone: z.string().trim().regex(/^\d{6,20}$/, '手机号格式不正确').optional().nullable(),
      role: z.enum(['student', 'teacher', 'admin']).optional(),
    }),
  }),
  async (req, res, next) => {
    try {
      const user = await authService.register(req.validated.body, ctx(req))
      res.status(201).json({ ok: true, user })
    } catch (error) {
      next(error)
    }
  }
)

authRouter.post(
  '/login',
  // 两级限流：按账号 10 次/15 分钟拦住针对单个账号的爆破；
  // 按 IP 60 次/15 分钟兜底，防止有人换着用户名扫库。
  // 只按 IP 计会误伤同一出口 IP 下的整片用户（机房、NAT）。
  rateLimit({
    ...config.rateLimit.login,
    keyPrefix: 'auth-login-user',
    identity: (req) => {
      const username = req.body?.username
      return typeof username === 'string' && username.trim() ? `n:${username.trim().toLowerCase()}` : null
    },
    tiers: [
      {
        ...config.rateLimit.login,
        max: config.rateLimit.login.ipMax,
        keyPrefix: 'auth-login-ip',
      },
    ],
  }),
  validate({
    body: z.object({
      username: z.string().trim().min(1, '请输入用户名'),
```

```
      password: z.string().min(1, '请输入密码'),
    }),
  }),
  async (req, res, next) => {
    try {
      const result = await authService.login(req.validated.body, ctx(req))
      res.json({ ok: true, ...result })
    } catch (error) {
      next(error)
    }
  }
)

authRouter.post(
  '/refresh',
  validate({ body: z.object({ refreshToken: z.string().min(1) }) }),
  async (req, res, next) => {
    try {
      const { userId, token } = await rotateRefreshToken(req.validated.body.refreshToken, ctx(req))
      const user = await authService.loadUserForToken(userId)
      res.json({
        ok: true,
        user: toPublicUser(user),
        accessToken: signAccessToken(user),
        refreshToken: token.raw,
        expiresIn: config.auth.accessTtlSeconds,
      })
    } catch (error) {
      next(error)
    }
  }
)

authRouter.post(
  '/logout',
  validate({
    body: z.object({
      refreshToken: z.string().optional(),
      all: z.boolean().optional(),
    }),
  }),
  async (req, res, next) => {
    try {
      const result = await authService.logout(req.validated.body, ctx(req))
      res.json({ ok: true, ...result })
    } catch (error) {
      next(error)
    }
  }
)

authRouter.get('/me', requireAuth, async (req, res, next) => {
  try {
    res.json({ ok: true, user: toPublicUser(req.user) })
  } catch (error) {
    next(error)
  }
})

authRouter.post(
  '/forgot-password',
  rateLimit({ ...config.rateLimit.forgotPassword, keyPrefix: 'auth-forgot' }),
  validate({ body: z.object({ account: z.string().trim().min(1, '请输入用户名、邮箱或手机号') }) }),
  async (req, res, next) => {
    try {
      const result = await authService.createPasswordReset(req.validated.body, ctx(req))
      res.json({ ok: true, ...result })
    } catch (error) {
      next(error)
    }
  }
)

/** 校验重置令牌是否仍然有效，供前端在渲染重置表单前预检。 */
authRouter.get('/reset-password/:token', async (req, res, next) => {
  try {
```

```
    const result = await authService.peekResetToken(req.params.token)
    res.json({ ok: true, ...result })
  } catch (error) {
    next(error)
  }
})

authRouter.post(
  '/reset-password',
  rateLimit({ ...config.rateLimit.forgotPassword, keyPrefix: 'auth-reset' }),
  validate({
    body: z.object({
      token: z.string().min(1, '重置链接无效'),
      newPassword: passwordSchema,
    }),
  }),
  async (req, res, next) => {
    try {
      const result = await authService.resetPassword(req.validated.body, ctx(req))
      res.json({ ok: true, ...result })
    } catch (error) {
      next(error)
    }
  }
)

export { passwordSchema, usernameSchema }
```

server/src/routes/aiRoutes.js

```
import { Router } from 'express'
import { z } from 'zod'
import { config } from '../config.js'
import { requireAuth, requireRole } from '../middleware/auth.js'
import { validate } from '../middleware/validate.js'
import { rateLimit } from '../middleware/rateLimit.js'
import { getModelRegistry, invalidateModelCache } from '../services/modelRegistry.js'
import * as ollama from '../services/ollamaService.js'
import * as conversations from '../repositories/conversationRepository.js'
import { insertAiRequestLog } from '../repositories/logRepository.js'
import { buildPageParams, pageEnvelope } from '../services/pagination.js'
import { badRequest, forbidden, notFound } from '../utils/httpError.js'
import { beginStream, createLineDecoder, endStream, writeControl, writeFrame } from '../utils/ndjson.js'
import { logger } from '../utils/logger.js'

export const aiRouter = Router()

aiRouter.use(requireAuth)

const MODEL_NAME = z.string().min(1).max(200)

/* ------------------------------ 模型清单 ------------------------------ */

aiRouter.get('/models', async (req, res, next) => {
  try {
    const refresh = req.query.refresh === '1' || req.query.refresh === 'true'
    const registry = await getModelRegistry({ refresh })
    res.json({ ok: true, ...registry })
  } catch (error) {
    next(error)
  }
})

aiRouter.get('/running', async (req, res, next) => {
  try {
    res.json({ ok: true, models: await ollama.listRunning() })
  } catch (error) {
    next(error)
  }
})

/** 预加载模型到显存。加载大模型很慢，前端需要「模型加载中」状态。 */
aiRouter.post(
  '/models/:name/load',
```

```
  requireRole('admin'),
  async (req, res, next) => {
    try {
      const name = decodeURIComponent(req.params.name)
      await ollama.loadModel(name)
      invalidateModelCache()
      res.json({ ok: true, model: name, message: `模型 ${name} 已加载` })
    } catch (error) {
      next(error)
    }
  }
)

aiRouter.post(
  '/models/:name/unload',
  requireRole('admin'),
  async (req, res, next) => {
    try {
      const name = decodeURIComponent(req.params.name)
      await ollama.unloadModel(name)
      invalidateModelCache()
      res.json({ ok: true, model: name, message: `模型 ${name} 已卸载` })
    } catch (error) {
      next(error)
    }
  }
)

aiRouter.delete(
  '/models/:name',
  requireRole('admin'),
  async (req, res, next) => {
    try {
      const name = decodeURIComponent(req.params.name)
      await ollama.deleteModel(name)
      invalidateModelCache()
      res.json({ ok: true, model: name, message: `模型 ${name} 已删除` })
    } catch (error) {
      next(error)
    }
  }
)

/** 拉取新模型，把 Ollama 的进度流原样转发。
 *  本机 registry.ollama.ai 实测不可达，失败时给出可读提示。 */
aiRouter.post(
  '/pull',
  requireRole('admin'),
  validate({ body: z.object({ name: MODEL_NAME }) }),
  async (req, res, next) => {
    const { name } = req.validated.body
    let upstream
    try {
      upstream = await ollama.pullModelStream(name)
    } catch (error) {
      return next(error)
    }

    beginStream(res)
    const reader = upstream.body.getReader()

    const push = createLineDecoder((frame) => {
      writeFrame(res, { __railway: 'progress', model: name, ...frame })
    })

    req.on('close', () => {
      reader.cancel().catch(() => {})
    })

    try {
      for (;;) {
        const { done, value } = await reader.read()
        if (done) break
        push(value)
      }
      invalidateModelCache()
```

```
      writeControl(res, 'done', { model: name })
    } catch (error) {
      logger.error('模型拉取中断', { model: name, message: error.message })
      writeControl(res, 'error', {
        code: 'pull_failed',
        message: `模型拉取失败：无法连接模型仓库，请检查网络或代理（${error.message}）`,
      })
    } finally {
      endStream(res)
    }
  }
)

/* ------------------------------ 流式对话 ------------------------------ */

const chatSchema = z.object({
  conversationId: z.string().max(64).optional().nullable(),
  model: MODEL_NAME.optional(),
  message: z.string().min(1, '请输入内容').max(8000, '内容过长'),
  // 游戏内场景上下文，用于让模型知道学生当前在做什么
  sceneContext: z.string().max(2000).optional().nullable(),
  equipment: z.object({
    id: z.string().min(1).max(120),
    name: z.string().min(1).max(120),
  }).optional(),
  options: z
    .object({
      temperature: z.number().min(0).max(2).optional(),
      top_p: z.number().min(0).max(1).optional(),
      num_predict: z.number().int().min(1).max(8192).optional(),
    })
    .optional(),
})

aiRouter.post(
  '/chat',
  rateLimit({ ...config.rateLimit.chat, keyPrefix: 'ai-chat', byUser: true }),
  validate({ body: chatSchema }),
  async (req, res, next) => {
    const { conversationId, message, sceneContext, equipment, options } = req.validated.body

    let registry
    try {
      registry = await getModelRegistry()
    } catch (error) {
      return next(error)
    }

    const model = req.validated.body.model || registry.defaultModel
    if (!model) {
      return next(badRequest('当前没有可用的对话模型，请先在模型管理中加载模型', 'no_model_available'))
    }

    const known = registry.models.find((item) => item.name === model)
    if (!known) {
      return next(badRequest(`模型 ${model} 不在可用列表中`, 'unknown_model'))
    }
    if (!known.available) {
      return next(badRequest(known.hint || `模型 ${model} 当前不可用`, 'model_unavailable'))
    }
    if (known.isEmbedding) {
      return next(badRequest(`模型 ${model} 是向量模型，不能用于对话`, 'not_a_chat_model'))
    }

    // 会话归属校验：只能在自己的会话里继续对话。
    let conversation = null
    if (conversationId) {
      conversation = await conversations.getConversation(conversationId)
      if (!conversation) return next(notFound('会话不存在', 'conversation_not_found'))
      if (conversation.user_id !== req.user.id && req.user.role !== 'admin') {
        return next(forbidden('无权访问该会话', 'conversation_forbidden'))
      }
    } else {
      conversation = await conversations.createConversation({
        userId: req.user.id,
        title: message.slice(0, 30),
```

```
    model,
    systemPrompt: config.ollama.systemPrompt,
  })
}

const userMessage = await conversations.appendMessage({
  conversationId: conversation.id,
  userId: req.user.id,
  role: 'user',
  content: message,
  model,
  sceneContext: sceneContext || null,
  equipment,
})

const history = await conversations.recentMessages(conversation.id, 20)
const systemPrompt = [conversation.system_prompt || config.ollama.systemPrompt, sceneContext]
  .filter(Boolean)
  .join('\n\n')

const messages = [{ role: 'system', content: systemPrompt }, ...history]

const startedAt = Date.now()
beginStream(res)

writeControl(res, 'meta', {
  conversationId: conversation.id,
  model,
  userMessageId: userMessage.id,
  title: conversation.title,
})

let upstream
try {
  upstream = await ollama.chatStream({ model, messages, options })
} catch (error) {
  await conversations.appendMessage({
    conversationId: conversation.id,
    userId: req.user.id,
    role: 'assistant',
    content: '',
    model,
    status: 'error',
    error: error.message,
  })
  writeControl(res, 'error', { code: error.code || 'ollama_error', message: error.message })
  endStream(res)
  await insertAiRequestLog({
    userId: req.user.id,
    conversationId: conversation.id,
    model,
    status: 'error',
    latencyMs: Date.now() - startedAt,
    error: error.message,
  })
  return
}

const reader = upstream.body.getReader()
let answer = ''
let firstTokenMs = null
let usage = { promptTokens: null, completionTokens: null }
let finished = false
// qwen3 这类思考模型会先吐几秒到几十秒的 thinking，期间 content 一直为空。
// 前端若只按 content 渲染就会长时间白屏，所以单发一帧告诉它"正在思考"。
let thinkingAnnounced = false

// 客户端主动断开时及时释放上游连接，避免显存和连接被长时间占住。
const onClose = () => {
  if (!finished) reader.cancel().catch(() => {})
}
req.on('close', onClose)

const handleFrame = (frame) => {
  // Ollama 原始帧原样转发，前端按 message.content 增量拼接。
  if (frame?.message?.content) {
```

```
      if (firstTokenMs === null) firstTokenMs = Date.now() - startedAt
      answer += frame.message.content
    } else if (frame?.message?.thinking && !thinkingAnnounced) {
      // 只发一次：每帧都带控制帧会把流撑大，前端也只需要知道"开始了"。
      thinkingAnnounced = true
      writeControl(res, 'thinking', { model })
    }
    if (frame?.done) {
      usage = {
        promptTokens: frame.prompt_eval_count ?? null,
        completionTokens: frame.eval_count ?? null,
      }
    }
    writeFrame(res, frame)
  }

  const push = createLineDecoder(handleFrame)

  try {
    for (;;) {
      const { done, value } = await reader.read()
      if (done) break
      push(value)
    }
    finished = true
    const latencyMs = Date.now() - startedAt

    // 一次性把完整回复与用量写库（appendMessage 已含内容，无需再补一次）。
    const assistantMessage = await conversations.appendMessage({
      conversationId: conversation.id,
      userId: req.user.id,
      role: 'assistant',
      content: answer,
      model,
      status: 'ok',
    })

    await conversations.completeAssistantMessage(assistantMessage.id, {
      content: answer,
      promptTokens: usage.promptTokens,
      completionTokens: usage.completionTokens,
      latencyMs,
      status: 'ok',
    })

    writeControl(res, 'done', {
      conversationId: conversation.id,
      userMessageId: userMessage.id,
      assistantMessageId: assistantMessage.id,
      firstTokenMs,
      latencyMs,
      promptTokens: usage.promptTokens,
      completionTokens: usage.completionTokens,
    })

    await insertAiRequestLog({
      userId: req.user.id,
      conversationId: conversation.id,
      model,
      status: 'ok',
      latencyMs,
      firstTokenMs,
      promptTokens: usage.promptTokens,
      completionTokens: usage.completionTokens,
    })
  } catch (error) {
    finished = true
    const aborted = req.destroyed || res.destroyed
    logger.warn('对话流中断', { model, aborted, message: error.message })

    // 已生成的部分内容仍然落库，用户下次打开会话能看到它。
    const assistantMessage = await conversations.appendMessage({
      conversationId: conversation.id,
      userId: req.user.id,
      role: 'assistant',
      content: answer,
```

```
        model,
        status: aborted ? 'aborted' : 'error',
        error: aborted ? null : error.message,
      })
      await conversations.completeAssistantMessage(assistantMessage.id, {
        content: answer,
        status: aborted ? 'aborted' : 'error',
        error: aborted ? null : error.message,
      })

      if (!aborted) {
        writeControl(res, 'error', {
          code: 'stream_failed',
          message: `生成中断：${error.message}`,
        })
      }

      await insertAiRequestLog({
        userId: req.user.id,
        conversationId: conversation.id,
        model,
        status: aborted ? 'aborted' : 'error',
        latencyMs: Date.now() - startedAt,
        firstTokenMs,
        error: aborted ? '客户端断开' : error.message,
      })
    } finally {
      req.off('close', onClose)
      endStream(res)
    }
  }
)

/* ------------------------------ 会话管理 ------------------------------ */

const pageQuery = z.object({
  page: z.coerce.number().int().positive().optional(),
  pageSize: z.coerce.number().int().positive().optional(),
  q: z.string().max(100).optional(),
})

aiRouter.get(
  '/conversations',
  validate({ query: pageQuery }),
  async (req, res, next) => {
    try {
      const params = buildPageParams(req.validated.query)
      const rows = await conversations.listUserConversations(req.user.id, {
        ...params,
        q: req.validated.query.q,
      })
      res.json({ ok: true, ...pageEnvelope(rows, params) })
    } catch (error) {
      next(error)
    }
  }
)

aiRouter.post('/conversations', async (req, res, next) => {
  try {
    const conversation = await conversations.createConversation({
      userId: req.user.id,
      title: '新对话',
      model: '',
      systemPrompt: config.ollama.systemPrompt,
    })
    res.status(201).json({ ok: true, conversation })
  } catch (error) {
    next(error)
  }
})

aiRouter.get(
  '/conversations/:id/messages',
  validate({ query: pageQuery }),
  async (req, res, next) => {
```

```
    try {
      const conversation = await conversations.getConversation(req.params.id)
      if (!conversation) return next(notFound('会话不存在', 'conversation_not_found'))
      if (conversation.user_id !== req.user.id && req.user.role !== 'admin') {
        return next(forbidden('无权访问该会话', 'conversation_forbidden'))
      }

      const params = buildPageParams(req.validated.query, { defaultPageSize: 50 })
      const rows = await conversations.listMessages(conversation.id, params)
      res.json({
        ok: true,
        conversation: {
          id: conversation.id,
          title: conversation.title,
          model: conversation.model,
        },
        ...pageEnvelope(rows, params),
      })
    } catch (error) {
      next(error)
    }
  }
)

aiRouter.patch(
  '/conversations/:id',
  validate({ body: z.object({ title: z.string().min(1).max(100) }) }),
  async (req, res, next) => {
    try {
      const conversation = await conversations.getConversation(req.params.id)
      if (!conversation) return next(notFound('会话不存在', 'conversation_not_found'))
      if (conversation.user_id !== req.user.id && req.user.role !== 'admin') {
        return next(forbidden('无权修改该会话', 'conversation_forbidden'))
      }
      const updated = await conversations.renameConversation(conversation.id, req.validated.body.title)
      res.json({ ok: true, conversation: updated })
    } catch (error) {
      next(error)
    }
  }
)

aiRouter.delete('/conversations/:id', async (req, res, next) => {
  try {
    const conversation = await conversations.getConversation(req.params.id)
    if (!conversation) return next(notFound('会话不存在', 'conversation_not_found'))
    if (conversation.user_id !== req.user.id && req.user.role !== 'admin') {
      return next(forbidden('无权删除该会话', 'conversation_forbidden'))
    }
    await conversations.deleteConversation(conversation.id)
    res.json({ ok: true })
  } catch (error) {
    next(error)
  }
})
```

server/src/routes/adminRoutes.js

```
import { Router } from 'express'
import { z } from 'zod'
import { requireAuth, requireRole } from '../middleware/auth.js'
import { validate } from '../middleware/validate.js'
import { getClientIp } from '../middleware/rateLimit.js'
import * as users from '../repositories/userRepository.js'
import * as logs from '../repositories/logRepository.js'
import * as tokens from '../repositories/tokenRepository.js'
import * as scenes from '../repositories/sceneRepository.js'
import * as conversations from '../repositories/conversationRepository.js'
import { hashPassword, generatePassword } from '../services/passwordService.js'
import { revokeAllUserTokens } from '../services/tokenService.js'
import { issueResetLink, toPublicUser } from '../services/authService.js'
import { buildPageParams, pageEnvelope, resolveSort } from '../services/pagination.js'
import { getModelRegistry, invalidateModelCache } from '../services/modelRegistry.js'
import * as ollama from '../services/ollamaService.js'
```

```
import { healthCheck } from '../db/pool.js'
import { config } from '../config.js'
import { badRequest, conflict, notFound } from '../utils/httpError.js'
import { passwordSchema, usernameSchema } from './authRoutes.js'

export const adminRouter = Router()

adminRouter.use(requireAuth, requireRole('admin'))

const ctx = (req) => ({ ip: getClientIp(req), userId: req.user.id, username: req.user.username })

/** 分页查询参数。管理台每个列表都用它。 */
const pageQuery = {
  page: z.coerce.number().int().positive().optional(),
  pageSize: z.coerce.number().int().positive().optional(),
  from: z.string().trim().optional().nullable(),
  to: z.string().trim().optional().nullable(),
}

const boolParam = z
  .enum(['0', '1', 'true', 'false'])
  .optional()
  .transform((value) => (value === undefined ? undefined : value === '1' || value === 'true'))

const trimToNull = (value) => (value ? value : null)

/* ------------------------------ 概览 ------------------------------ */

adminRouter.get('/stats', async (req, res, next) => {
  try {
    const [userStats, roleStats, loginStats, sceneStats, recordStats, convStats, msgStats, aiStats] =
      await Promise.all([
        users.countAll(),
        users.countByRole(),
        logs.loginSummary(),
        scenes.sceneStats(),
        scenes.recordStats(),
        conversations.countConversations(),
        conversations.countMessages(),
        logs.aiLogSummary(),
      ])

    const registry = await getModelRegistry().catch(() => null)

    res.json({
      ok: true,
      users: { ...userStats, byRole: roleStats },
      logins: loginStats,
      scenes: sceneStats,
      records: recordStats,
      conversations: convStats,
      messages: msgStats,
      ai: {
        ...aiStats,
        models: registry?.models?.length ?? 0,
        loaded: registry?.models?.filter((model) => model.running).length ?? 0,
        ollamaReachable: registry?.ollama?.reachable ?? false,
        defaultModel: registry?.defaultModel ?? '',
      },
    })
  } catch (error) {
    next(error)
  }
})

/** 概览页的最近登录（同样走分页）。 */
adminRouter.get(
  '/stats/recent-logins',
  validate({ query: z.object(pageQuery) }),
  async (req, res, next) => {
    try {
      const params = buildPageParams(req.validated.query, { defaultPageSize: 10 })
      const rows = await logs.recentLogins(params)
      res.json({ ok: true, ...pageEnvelope(rows, params) })
    } catch (error) {
      next(error)
```

```
    }
  }
)

/* ------------------------------ 用户管理 ------------------------------ */

const userSortAllowlist = {
  createdAt: 'u.created_at',
  updatedAt: 'u.updated_at',
  username: 'u.username',
  lastLoginAt: 'u.last_login_at',
  role: 'u.role',
  status: 'u.status',
}

adminRouter.get(
  '/users',
  validate({
    query: z.object({
      ...pageQuery,
      q: z.string().trim().max(64).optional(),
      role: z.enum(['student', 'teacher', 'admin']).optional(),
      status: z.enum(['active', 'disabled', 'locked']).optional(),
      sort: z.string().max(32).optional(),
      order: z.enum(['asc', 'desc']).optional(),
    }),
  }),
  async (req, res, next) => {
    try {
      const query = req.validated.query
      const params = buildPageParams(query)
      const sort = resolveSort(query, userSortAllowlist, {
        column: 'u.created_at',
        direction: 'DESC',
      })

      const rows = await users.listUsers({
        ...params,
        q: query.q,
        role: query.role,
        status: query.status,
        sortColumn: sort.column,
        sortDirection: sort.direction,
      })

      res.json({ ok: true, ...pageEnvelope(rows, params) })
    } catch (error) {
      next(error)
    }
  }
)

const createUserSchema = z.object({
  username: usernameSchema,
  password: passwordSchema.optional(),
  displayName: z.string().trim().max(32).optional(),
  email: z.string().trim().email('邮箱格式不正确').max(128).optional().nullable(),
  phone: z.string().trim().regex(/^\d{6,20}$/, '手机号格式不正确').optional().nullable(),
  role: z.enum(['student', 'teacher', 'admin']),
  status: z.enum(['active', 'disabled', 'locked']).optional(),
  remark: z.string().trim().max(200).optional().nullable(),
})

adminRouter.post(
  '/users',
  validate({ body: createUserSchema }),
  async (req, res, next) => {
    try {
      const input = req.validated.body

      if (await users.usernameExists(input.username)) {
        throw conflict('该用户名已被占用', 'username_taken')
      }
      if (input.email && (await users.emailExists(input.email))) {
        throw conflict('该邮箱已被注册', 'email_taken')
      }
```

```
      if (input.phone && (await users.phoneExists(input.phone))) {
        throw conflict('该手机号已被注册', 'phone_taken')
      }

      // 管理员不填密码时自动生成一个，并强制首次登录修改。
      const initialPassword = input.password || generatePassword(12)

      const user = await users.insertUser({
        username: input.username.trim(),
        displayName: input.displayName?.trim() || input.username.trim(),
        email: trimToNull(input.email),
        phone: trimToNull(input.phone),
        passwordHash: await hashPassword(initialPassword),
        role: input.role,
        status: input.status ?? 'active',
        remark: trimToNull(input.remark),
        mustChangePassword: !input.password,
      })

      await logs.insertAuditLog({
        ...ctx(req),
        action: 'admin.create_user',
        targetType: 'user',
        targetId: user.id,
        detail: { role: input.role, username: user.username },
        ip: ctx(req).ip,
      })

      res.status(201).json({
        ok: true,
        user: toPublicUser(user),
        // 仅当系统生成密码时才回显，方便管理员转交。
        ...(input.password ? {} : { initialPassword }),
      })
    } catch (error) {
      next(error)
    }
  }
)

adminRouter.put(
  '/users/:id',
  validate({
    body: z.object({
      displayName: z.string().trim().min(1).max(32).optional(),
      email: z.string().trim().email('邮箱格式不正确').max(128).optional().nullable(),
      phone: z.string().trim().regex(/^\d{6,20}$/, '手机号格式不正确').optional().nullable(),
      role: z.enum(['student', 'teacher', 'admin']).optional(),
      status: z.enum(['active', 'disabled', 'locked']).optional(),
      remark: z.string().trim().max(200).optional().nullable(),
    }),
  }),
  async (req, res, next) => {
    try {
      const target = await users.findById(req.params.id)
      if (!target || target.deleted_at) throw notFound('用户不存在', 'user_not_found')

      const patch = req.validated.body

      // 不允许管理员把自己降级或禁用，否则容易把自己锁在系统外。
      if (target.id === req.user.id && patch.role && patch.role !== 'admin') {
        throw badRequest('不能修改自己的角色', 'self_role_change')
      }
      if (target.id === req.user.id && patch.status && patch.status !== 'active') {
        throw badRequest('不能禁用自己的账号', 'self_disable')
      }

      if (patch.email && (await users.emailExists(patch.email, target.id))) {
        throw conflict('该邮箱已被其它账号使用', 'email_taken')
      }
      if (patch.phone && (await users.phoneExists(patch.phone, target.id))) {
        throw conflict('该手机号已被其它账号使用', 'phone_taken')
      }

      const updated = await users.updateUser(target.id, {
        displayName: patch.displayName,
```

```
        email: patch.email === undefined ? undefined : trimToNull(patch.email),
        phone: patch.phone === undefined ? undefined : trimToNull(patch.phone),
        role: patch.role,
        status: patch.status,
        remark: patch.remark === undefined ? undefined : trimToNull(patch.remark),
      })

      // 禁用账号时立刻吊销其刷新令牌，避免继续续期。
      if (patch.status === 'disabled') await revokeAllUserTokens(target.id)

      await logs.insertAuditLog({
        ...ctx(req),
        action: 'admin.update_user',
        targetType: 'user',
        targetId: target.id,
        detail: patch,
        ip: ctx(req).ip,
      })

      res.json({ ok: true, user: toPublicUser(updated) })
    } catch (error) {
      next(error)
    }
  }
)

adminRouter.delete('/users/:id', async (req, res, next) => {
  try {
    if (req.params.id === req.user.id) {
      throw badRequest('不能删除自己的账号', 'self_delete')
    }
    const target = await users.findById(req.params.id)
    if (!target || target.deleted_at) throw notFound('用户不存在', 'user_not_found')

    await users.softDeleteUser(target.id)
    await revokeAllUserTokens(target.id)

    await logs.insertAuditLog({
      ...ctx(req),
      action: 'admin.delete_user',
      targetType: 'user',
      targetId: target.id,
      detail: { username: target.username },
      ip: ctx(req).ip,
    })

    res.json({ ok: true })
  } catch (error) {
    next(error)
  }
})

/** 管理员为指定用户生成一次性重置链接（本机无邮件服务，由管理员转交）。 */
adminRouter.post('/users/:id/reset-password', async (req, res, next) => {
  try {
    const result = await issueResetLink(req.params.id, ctx(req))
    res.json({ ok: true, ...result })
  } catch (error) {
    next(error)
  }
})

adminRouter.post('/users/:id/unlock', async (req, res, next) => {
  try {
    const updated = await users.unlockUser(req.params.id)
    if (!updated) throw badRequest('该账号当前不处于锁定状态', 'not_locked')

    await logs.insertAuditLog({
      ...ctx(req),
      action: 'admin.unlock_user',
      targetType: 'user',
      targetId: req.params.id,
      ip: ctx(req).ip,
    })

    res.json({ ok: true, user: toPublicUser(updated) })
```

```
  } catch (error) {
    next(error)
  }
})

/* ------------------------------ 登录日志 / 审计日志 ------------------------------ */

adminRouter.get(
  '/login-logs',
  validate({
    query: z.object({
      ...pageQuery,
      userId: z.string().max(64).optional(),
      username: z.string().trim().max(64).optional(),
      success: boolParam,
    }),
  }),
  async (req, res, next) => {
    try {
      const query = req.validated.query
      const params = buildPageParams(query)
      const rows = await logs.listLoginLogs({
        ...params,
        userId: query.userId,
        username: query.username,
        success: query.success,
        from: query.from,
        to: query.to,
      })
      res.json({ ok: true, ...pageEnvelope(rows, params) })
    } catch (error) {
      next(error)
    }
  }
)

adminRouter.get(
  '/audit-logs',
  validate({
    query: z.object({
      ...pageQuery,
      userId: z.string().max(64).optional(),
      action: z.string().trim().max(64).optional(),
    }),
  }),
  async (req, res, next) => {
    try {
      const query = req.validated.query
      const params = buildPageParams(query)
      const rows = await logs.listAuditLogs({
        ...params,
        userId: query.userId,
        action: query.action,
        from: query.from,
        to: query.to,
      })
      res.json({ ok: true, ...pageEnvelope(rows, params) })
    } catch (error) {
      next(error)
    }
  }
)

adminRouter.get(
  '/reset-tokens',
  validate({ query: z.object({ ...pageQuery, userId: z.string().max(64).optional() }) }),
  async (req, res, next) => {
    try {
      const params = buildPageParams(req.validated.query)
      const rows = await tokens.listResetTokens({ ...params, userId: req.validated.query.userId })
      res.json({ ok: true, ...pageEnvelope(rows, params) })
    } catch (error) {
      next(error)
    }
  }
)
```

```
/* ------------------------------ 训练场景 / 成绩记录 ------------------------------ */

adminRouter.get(
  '/scenes',
  validate({
    query: z.object({
      ...pageQuery,
      q: z.string().trim().max(64).optional(),
      ownerId: z.string().max(64).optional(),
      published: boolParam,
      includeDeleted: boolParam,
    }),
  }),
  async (req, res, next) => {
    try {
      const query = req.validated.query
      const params = buildPageParams(query)
      const rows = await scenes.listScenes({
        ...params,
        q: query.q,
        ownerId: query.ownerId,
        published: query.published,
        includeDeleted: query.includeDeleted === true,
      })
      res.json({ ok: true, ...pageEnvelope(rows, params) })
    } catch (error) {
      next(error)
    }
  }
)

/**
 * 场景详情：单独一个接口按需返回 payload。
 * 不并进列表是有意的——payload 是整份场景 JSON，几十条一起传会把列表拖垮。
 */
adminRouter.get('/scenes/:id', async (req, res, next) => {
  try {
    const scene = await scenes.getScene(req.params.id)
    if (!scene) throw notFound('场景不存在', 'scene_not_found')
    res.json({ ok: true, scene })
  } catch (error) {
    next(error)
  }
})

adminRouter.post('/scenes/:id/publish', async (req, res, next) => {
  try {
    const published = req.body?.published !== false
    const scene = await scenes.setPublished(req.params.id, published)
    if (!scene) throw notFound('场景不存在', 'scene_not_found')

    await logs.insertAuditLog({
      ...ctx(req),
      action: published ? 'admin.publish_scene' : 'admin.unpublish_scene',
      targetType: 'scene',
      targetId: scene.id,
      ip: ctx(req).ip,
    })

    res.json({ ok: true, scene })
  } catch (error) {
    next(error)
  }
})

adminRouter.delete('/scenes/:id', async (req, res, next) => {
  try {
    const ok = await scenes.softDeleteScene(req.params.id)
    if (!ok) throw notFound('场景不存在', 'scene_not_found')

    await logs.insertAuditLog({
      ...ctx(req),
      action: 'admin.delete_scene',
      targetType: 'scene',
      targetId: req.params.id,
      ip: ctx(req).ip,
```

```
    })

    res.json({ ok: true })
  } catch (error) {
    next(error)
  }
})

adminRouter.get(
  '/records',
  validate({
    query: z.object({
      ...pageQuery,
      userId: z.string().max(64).optional(),
      sceneId: z.string().max(64).optional(),
      q: z.string().trim().max(64).optional(),
      completed: boolParam,
    }),
  }),
  async (req, res, next) => {
    try {
      const query = req.validated.query
      const params = buildPageParams(query)
      const rows = await scenes.listRecords({
        ...params,
        userId: query.userId,
        sceneId: query.sceneId,
        q: query.q,
        completed: query.completed,
      })
      res.json({ ok: true, ...pageEnvelope(rows, params) })
    } catch (error) {
      next(error)
    }
  }
)

/* ------------------------------ AI 会话 / 调用日志 ------------------------------ */

adminRouter.get(
  '/conversations',
  validate({
    query: z.object({
      ...pageQuery,
      userId: z.string().max(64).optional(),
      model: z.string().max(200).optional(),
      q: z.string().trim().max(64).optional(),
    }),
  }),
  async (req, res, next) => {
    try {
      const query = req.validated.query
      const params = buildPageParams(query)
      const rows = await conversations.adminListConversations({
        ...params,
        userId: query.userId,
        q: query.q,
        model: query.model,
      })
      res.json({ ok: true, ...pageEnvelope(rows, params) })
    } catch (error) {
      next(error)
    }
  }
)

adminRouter.get(
  '/conversations/:id/messages',
  validate({ query: z.object(pageQuery) }),
  async (req, res, next) => {
    try {
      const conversation = await conversations.getConversation(req.params.id)
      if (!conversation) throw notFound('会话不存在', 'conversation_not_found')

      const params = buildPageParams(req.validated.query, { defaultPageSize: 50 })
      const rows = await conversations.listMessages(conversation.id, params)
```

```
      res.json({
        ok: true,
        conversation: { id: conversation.id, title: conversation.title, model: conversation.model },
        ...pageEnvelope(rows, params),
      })
    } catch (error) {
      next(error)
    }
  }
)

adminRouter.delete('/conversations/:id', async (req, res, next) => {
  try {
    const ok = await conversations.deleteConversation(req.params.id)
    if (!ok) throw notFound('会话不存在', 'conversation_not_found')

    await logs.insertAuditLog({
      ...ctx(req),
      action: 'admin.delete_conversation',
      targetType: 'conversation',
      targetId: req.params.id,
      ip: ctx(req).ip,
    })

    res.json({ ok: true })
  } catch (error) {
    next(error)
  }
})

adminRouter.get(
  '/ai-logs',
  validate({
    query: z.object({
      ...pageQuery,
      userId: z.string().max(64).optional(),
      model: z.string().max(200).optional(),
      status: z.enum(['ok', 'error', 'aborted']).optional(),
    }),
  }),
  async (req, res, next) => {
    try {
      const query = req.validated.query
      const params = buildPageParams(query)
      const rows = await logs.listAiRequestLogs({
        ...params,
        userId: query.userId,
        model: query.model,
        status: query.status,
        from: query.from,
        to: query.to,
      })
      res.json({ ok: true, ...pageEnvelope(rows, params) })
    } catch (error) {
      next(error)
    }
  }
)

/* ------------------------------ 系统信息 ------------------------------ */

adminRouter.get('/system', async (req, res, next) => {
  try {
    const [db, ollamaHealth, registry] = await Promise.all([
      healthCheck(),
      ollama.healthCheck(),
      getModelRegistry().catch(() => null),
    ])

    res.json({
      ok: true,
      server: {
        nodeVersion: process.version,
        platform: `${process.platform} ${process.arch}`,
        env: config.env,
        uptimeSeconds: Math.round(process.uptime()),
```

```
        memoryMb: Math.round(process.memoryUsage().rss / 1024 / 1024),
        apiPort: config.api.port,
      },
      database: { ...db, name: config.db.database, host: config.db.host, port: config.db.port },
      ollama: ollamaHealth,
      models: {
        total: registry?.models?.length ?? 0,
        loaded: registry?.models?.filter((model) => model.running).length ?? 0,
        defaultModel: registry?.defaultModel ?? '',
        sources: registry?.sources ?? null,
        list: (registry?.models ?? []).map((model) => ({
          name: model.name,
          sizeText: model.sizeText,
          parameterSize: model.parameterSize,
          quantization: model.quantization,
          source: model.source,
          available: model.available,
          running: model.running,
          vramText: model.vramText,
          hint: model.hint,
        })),
      },
      config: {
        bcryptRounds: config.auth.bcryptRounds,
        accessTtlSeconds: config.auth.accessTtlSeconds,
        refreshTtlSeconds: config.auth.refreshTtlSeconds,
        resetTtlSeconds: config.auth.resetTtlSeconds,
        maxFailedLogins: config.auth.maxFailedLogins,
        lockMinutes: config.auth.lockMinutes,
        allowTeacherSelfRegister: config.auth.allowTeacherSelfRegister,
        exposeResetToken: config.auth.exposeResetToken,
        keepAlive: config.ollama.keepAlive,
        systemPrompt: config.ollama.systemPrompt,
      },
    })
  } catch (error) {
    next(error)
  }
})

/** 手动刷新模型缓存，供模型管理页的「刷新」按钮调用。 */
adminRouter.post('/system/refresh-models', async (req, res, next) => {
  try {
    invalidateModelCache()
    const registry = await getModelRegistry({ refresh: true })
    res.json({ ok: true, count: registry.models.length, defaultModel: registry.defaultModel })
  } catch (error) {
    next(error)
  }
})

/** 服务端常量：每页条数候选，供前端分页器渲染。 */
adminRouter.get('/system/page-sizes', (req, res) => {
  res.json({ ok: true, pageSizes: [10, 20, 50, 100] })
})
```

server/src/services/authService.js

```
import { config } from '../config.js'
import * as users from '../repositories/userRepository.js'
import * as tokens from '../repositories/tokenRepository.js'
import { insertLoginLog, insertAuditLog } from '../repositories/logRepository.js'
import { hashPassword, verifyPassword, randomToken } from './passwordService.js'
import { issueRefreshToken, revokeAllUserTokens, signAccessToken } from './tokenService.js'
import { badRequest, conflict, forbidden, unauthorized } from '../utils/httpError.js'
import { isDevTestAccount } from './devTestAccounts.js'

/** 对外的用户视图：绝不包含 password_hash 或锁定细节以外的内部字段。 */
export function toPublicUser(user) {
  return {
    id: user.id,
    username: user.username,
    displayName: user.display_name,
    email: user.email,
```

```
    phone: user.phone,
    role: user.role,
    status: user.status,
    mustChangePassword: user.must_change_password,
    lastLoginAt: user.last_login_at,
    createdAt: user.created_at,
  }
}

function meta(ctx) {
  return { ip: ctx?.ip ?? null, userAgent: ctx?.userAgent ?? null }
}

/**
 * 按角色规则创建账户并记入审计日志。
 * @param {object} input 新账号资料和申请角色
 * @param {object} ctx 客户端网络上下文
 * @returns {object} 不含密码哈希的公开用户信息
 */
export async function register(input, ctx) {
  const role = input.role ?? 'student'

  // 自助注册永远不能产生管理员；老师账号默认需要管理员开通。
  if (role === 'admin') {
    throw forbidden('管理员账号不能自助注册，请联系系统管理员', 'admin_register_forbidden')
  }
  if (role === 'teacher' && !config.auth.allowTeacherSelfRegister) {
    throw forbidden('教师账号需要管理员开通，请先用学生身份注册或联系管理员', 'teacher_register_forbidden')
  }

  if (await users.usernameExists(input.username)) {
    throw conflict('该用户名已被占用', 'username_taken')
  }
  if (input.email && (await users.emailExists(input.email))) {
    throw conflict('该邮箱已被注册', 'email_taken')
  }
  if (input.phone && (await users.phoneExists(input.phone))) {
    throw conflict('该手机号已被注册', 'phone_taken')
  }

  const user = await users.insertUser({
    username: input.username.trim(),
    displayName: input.displayName?.trim() || input.username.trim(),
    email: input.email?.trim() || null,
    phone: input.phone?.trim() || null,
    passwordHash: await hashPassword(input.password),
    role,
    status: 'active',
  })

  await insertAuditLog({
    userId: user.id,
    username: user.username,
    action: 'user.register',
    targetType: 'user',
    targetId: user.id,
    detail: { role },
    ip: ctx?.ip,
  })

  return toPublicUser(user)
}

/**
 * 验证账号密码、记录登录结果并签发会话。
 * @param {string} username 登录名
 * @param {string} password 用户输入的明文密码
 * @param {object} ctx 客户端网络上下文
 * @returns {object} 含访问与刷新令牌的会话
 */
export async function login({ username, password }, ctx) {
  const { ip, userAgent } = meta(ctx)
  const user = await users.findByUsernameWithSecret(username)

  // 用户不存在也记一条日志，方便发现撞库行为。
  if (!user) {
```

```
    await insertLoginLog({
      userId: null,
      usernameInput: username,
      success: false,
      failureReason: 'no_such_user',
      ip,
      userAgent,
    })
    throw unauthorized('用户名或密码错误', 'bad_credentials')
  }

  if (isDevTestAccount(user) && !config.auth.devTestLogin) {
    throw forbidden('测试账号仅限开发环境', 'dev_account_disabled')
  }

  if (user.status === 'disabled') {
    await insertLoginLog({
      userId: user.id,
      usernameInput: username,
      success: false,
      failureReason: 'disabled',
      ip,
      userAgent,
    })
    throw forbidden('账号已被禁用，请联系管理员', 'account_disabled')
  }

  // 锁定期内直接拒绝，不再消耗 bcrypt 计算。
  if (user.locked_until && new Date(user.locked_until) > new Date()) {
    await insertLoginLog({
      userId: user.id,
      usernameInput: username,
      success: false,
      failureReason: 'locked',
      ip,
      userAgent,
    })
    const remainMinutes = Math.max(1, Math.ceil((new Date(user.locked_until) - Date.now()) / 60000))
    throw forbidden(`账号已锁定，请在 ${remainMinutes} 分钟后重试或联系管理员解锁`, 'account_locked')
  }

  const passwordOk = await verifyPassword(password, user.password_hash)
  if (!passwordOk) {
    const state = await users.recordLoginFailure(user.id, config.auth.maxFailedLogins, config.auth.lockMinutes)
    await insertLoginLog({
      userId: user.id,
      usernameInput: username,
      success: false,
      failureReason: 'bad_password',
      ip,
      userAgent,
    })

    // 刚好触发锁定的一次要明确告知，否则用户不明白为什么突然登录不了。
    if (state.failedLoginCount >= config.auth.maxFailedLogins) {
      await insertAuditLog({
        userId: user.id,
        username: user.username,
        action: 'user.locked',
        targetType: 'user',
        targetId: user.id,
        detail: { failedLoginCount: state.failedLoginCount },
        ip,
      })
      throw forbidden(
        `密码错误次数过多，账号已锁定 ${config.auth.lockMinutes} 分钟`,
        'account_locked'
      )
    }

    const remaining = Math.max(0, config.auth.maxFailedLogins - state.failedLoginCount)
    throw unauthorized(`用户名或密码错误，还可尝试 ${remaining} 次`, 'bad_credentials')
  }

  await users.recordLoginSuccess(user.id, ip)
  await insertLoginLog({
```

```
    userId: user.id,
    usernameInput: username,
    success: true,
    ip,
    userAgent,
  })

  const refresh = await issueRefreshToken(user.id, { ip, userAgent })

  return {
    user: toPublicUser({ ...user, last_login_at: new Date() }),
    accessToken: signAccessToken(user),
    refreshToken: refresh.raw,
    expiresIn: config.auth.accessTtlSeconds,
  }
}

export async function loginWithOidcSubject(subject, ctx) {
  const user = await users.findByOidcSubject(subject)
  if (!user) throw unauthorized('该统一身份尚未绑定有效的巡检实训平台账号，请先用本地账号登录并绑定', 'oidc_account_not_linked')
  if (isDevTestAccount(user) && !config.auth.devTestLogin) throw forbidden('测试账号仅限开发环境', 'dev_account_disabled')
  await users.recordLoginSuccess(user.id, ctx?.ip)
  await insertLoginLog({ userId: user.id, usernameInput: user.username, success: true, ip: ctx?.ip, userAgent: ctx?.userAgent })
  const refresh = await issueRefreshToken(user.id, { ip: ctx?.ip, userAgent: ctx?.userAgent })
  return {
    user: toPublicUser({ ...user, last_login_at: new Date() }),
    accessToken: signAccessToken(user),
    refreshToken: refresh.raw,
    expiresIn: config.auth.accessTtlSeconds,
  }
}

/** 刷新令牌换发时按 userId 重新加载用户，保证角色/状态变更即时生效。 */
/**
 * 换发令牌前重新核对用户状态。
 * @param {string} userId 用户主键
 * @returns {object} 数据库中的当前用户
 */
export async function loadUserForToken(userId) {
  const user = await users.findById(userId)
  if (!user || user.deleted_at) throw unauthorized('账号不存在或已注销', 'account_missing')
  if (isDevTestAccount(user) && !config.auth.devTestLogin) throw forbidden('测试账号仅限开发环境', 'dev_account_disabled')
  if (user.status === 'disabled') throw forbidden('账号已被禁用，请联系管理员', 'account_disabled')
  if (user.status === 'locked') throw forbidden('账号已锁定，请联系管理员解锁', 'account_locked')
  return user
}

/** 预检重置令牌，供前端在渲染表单前判断链接是否还能用。 */
export async function peekResetToken(token) {
  const row = await tokens.findResetToken(token)
  if (!row) throw badRequest('重置链接无效', 'invalid_reset_token')
  if (row.used_at) throw badRequest('重置链接已被使用，请重新申请', 'reset_token_used')
  if (new Date(row.expires_at) <= new Date()) {
    throw badRequest('重置链接已过期，请重新申请', 'reset_token_expired')
  }
  return { valid: true, username: row.username, expiresAt: row.expires_at }
}

export async function logout({ refreshToken, all }, ctx) {
  if (all) {
    if (ctx?.userId) await revokeAllUserTokens(ctx.userId)
    return { revoked: 'all' }
  }
  if (refreshToken) {
    const { revokeRefreshToken } = await import('./tokenService.js')
    await revokeRefreshToken(refreshToken)
  }
  return { revoked: 'one' }
}

export async function changePassword(userId, { currentPassword, newPassword }, ctx) {
  const user = await users.findById(userId)
  if (!user) throw unauthorized('账号不存在', 'account_missing')

  const withSecret = await users.findByUsernameWithSecret(user.username)
  const ok = await verifyPassword(currentPassword, withSecret?.password_hash)
```

```
  if (!ok) throw badRequest('当前密码不正确', 'bad_password')

  if (currentPassword === newPassword) {
    throw badRequest('新密码不能与当前密码相同', 'same_password')
  }

  await users.updateUser(userId, {
    passwordHash: await hashPassword(newPassword),
    mustChangePassword: false,
  })

  // 改密后强制所有设备重新登录，否则被盗号后改密码也踢不掉攻击者。
  await revokeAllUserTokens(userId)
  await tokens.invalidateUserResetTokens(userId)
  await insertAuditLog({
    userId,
    username: user.username,
    action: 'user.change_password',
    targetType: 'user',
    targetId: userId,
    ip: ctx?.ip,
  })

  return { ok: true }
}

/**
 * 忘记密码第一步：生成一次性重置令牌。
 * 本机没有 SMTP / 短信网关，所以默认不直接投递，而是交给管理员在后台转交。
 * 无论账号是否存在都返回同样的结果，避免暴露哪些账号已注册。
 */
export async function createPasswordReset({ account }, ctx) {
  const user = await users.findByAccountWithSecret(account)
  const genericReply = {
    ok: true,
    message: '如果该账号存在，重置请求已提交，请联系管理员获取重置链接。',
  }

  if (!user || user.deleted_at) return genericReply

  await tokens.invalidateUserResetTokens(user.id)

  const rawToken = randomToken(32)
  const expiresAt = new Date(Date.now() + config.auth.resetTtlSeconds * 1000)
  await tokens.insertResetToken({
    userId: user.id,
    rawToken,
    expiresAt,
    channel: 'manual',
    issuedBy: ctx?.userId ?? null,
    ip: ctx?.ip,
  })

  await insertAuditLog({
    userId: user.id,
    username: user.username,
    action: 'password_reset.requested',
    targetType: 'user',
    targetId: user.id,
    ip: ctx?.ip,
  })

  return {
    ...genericReply,
    // 仅在显式打开 EXPOSE_RESET_TOKEN 的开发环境下回显，生产默认关闭。
    ...(config.auth.exposeResetToken ? { token: rawToken, expiresAt } : {}),
  }
}

/** 管理员在后台为某个用户直接生成重置链接。 */
export async function issueResetLink(userId, ctx) {
  const user = await users.findById(userId)
  if (!user || user.deleted_at) throw badRequest('用户不存在', 'user_not_found')

  await tokens.invalidateUserResetTokens(userId)
  const rawToken = randomToken(32)
```

```
  const expiresAt = new Date(Date.now() + config.auth.resetTtlSeconds * 1000)

  await tokens.insertResetToken({
    userId,
    rawToken,
    expiresAt,
    channel: 'admin',
    issuedBy: ctx?.userId ?? null,
    ip: ctx?.ip,
  })

  await insertAuditLog({
    userId: ctx?.userId,
    username: ctx?.username,
    action: 'admin.issue_reset_link',
    targetType: 'user',
    targetId: userId,
    ip: ctx?.ip,
  })

  return { token: rawToken, expiresAt, userId, username: user.username }
}

export async function resetPassword({ token, newPassword }, ctx) {
  const row = await tokens.findResetToken(token)
  if (!row) throw badRequest('重置链接无效', 'invalid_reset_token')
  if (row.used_at) throw badRequest('重置链接已被使用，请重新申请', 'reset_token_used')
  if (new Date(row.expires_at) <= new Date()) {
    throw badRequest('重置链接已过期，请重新申请', 'reset_token_expired')
  }
  if (row.deleted_at) throw badRequest('账号不存在或已注销', 'account_missing')

  await users.updateUser(row.user_id, {
    passwordHash: await hashPassword(newPassword),
    status: row.status === 'locked' ? 'active' : undefined,
    mustChangePassword: false,
  })

  await tokens.consumeResetToken(row.id, row.user_id)
  await revokeAllUserTokens(row.user_id)

  await insertAuditLog({
    userId: row.user_id,
    username: row.username,
    action: 'password_reset.completed',
    targetType: 'user',
    targetId: row.user_id,
    ip: ctx?.ip,
  })

  return { ok: true, username: row.username }
}
```

server/src/services/tokenService.js

```
import jwt from 'jsonwebtoken'
import { config } from '../config.js'
import { query, queryOne } from '../db/pool.js'
import { newId } from '../utils/id.js'
import { randomToken, sha256 } from './passwordService.js'
import { unauthorized } from '../utils/httpError.js'

export function signAccessToken(user) {
  return jwt.sign({ username: user.username, role: user.role, typ: 'access' }, config.auth.jwtSecret, {
    subject: user.id,
    issuer: config.auth.jwtIssuer,
    expiresIn: config.auth.accessTtlSeconds,
  })
}

export function verifyAccessToken(token) {
  try {
    const payload = jwt.verify(token, config.auth.jwtSecret, { issuer: config.auth.jwtIssuer })
    if (payload.typ !== 'access') throw new Error('token type mismatch')
```

```
    return payload
  } catch {
    throw unauthorized()
  }
}

/**
 * 签发刷新令牌。明文只返回给调用方一次，库里只存 sha256。
 * 轮换时沿用同一个 family_id，这样重放检测才能识别出整个令牌家族。
 */
/**
 * 生成并仅保存哈希后的刷新令牌。
 * @param {string} userId 用户主键
 * @param {object} familyId 同一轮换链的标识
 * @param {object} ip 客户端地址
 * @param {object} userAgent 客户端标识
 * @returns {object} 原始令牌与轮换家族标识
 */
export async function issueRefreshToken(userId, { familyId, ip, userAgent } = {}) {
  const raw = randomToken(32)
  const id = newId('rt')
  const family = familyId ?? newId('fam')
  const expiresAt = new Date(Date.now() + config.auth.refreshTtlSeconds * 1000)

  await query(
    `INSERT INTO refresh_tokens (id, user_id, token_hash, family_id, expires_at, ip, user_agent)
     VALUES ($1, $2, $3, $4, $5, $6, $7)`,
    [id, userId, sha256(raw), family, expiresAt, ip ?? null, userAgent?.slice(0, 500) ?? null]
  )

  return { raw, id, familyId: family, expiresAt }
}

/**
 * 校验并轮换刷新令牌。
 * 若收到一个已被轮换过的令牌，说明它可能被窃取，整个家族立刻吊销。
 */
/**
 * 检测重复使用并轮换刷新令牌。
 * @param {string} raw 客户端提供的刷新令牌
 * @param {object} ip 客户端地址
 * @param {object} userAgent 客户端标识
 * @returns {object} 新的令牌和用户主键
 */
export async function rotateRefreshToken(raw, { ip, userAgent } = {}) {
  const hash = sha256(raw)
  const row = await queryOne(
    `SELECT id, user_id, family_id, expires_at, revoked_at, replaced_by
     FROM refresh_tokens WHERE token_hash = $1`,
    [hash]
  )

  if (!row) throw unauthorized('登录状态无效，请重新登录', 'invalid_refresh_token')

  if (row.revoked_at || row.replaced_by) {
    // 重放检测：吊销同一家族里所有仍然有效的令牌。
    await query(
      `UPDATE refresh_tokens SET revoked_at = now()
       WHERE family_id = $1 AND revoked_at IS NULL`,
      [row.family_id]
    )
    throw unauthorized('检测到令牌重复使用，已强制退出，请重新登录', 'refresh_token_reused')
  }

  if (new Date(row.expires_at) <= new Date()) {
    throw unauthorized('登录状态已过期，请重新登录', 'refresh_token_expired')
  }

  const next = await issueRefreshToken(row.user_id, { familyId: row.family_id, ip, userAgent })

  await query(
    `UPDATE refresh_tokens SET revoked_at = now(), replaced_by = $2 WHERE id = $1`,
    [row.id, next.id]
  )

  return { userId: row.user_id, token: next }
```

```
}

export async function revokeRefreshToken(raw) {
  await query(
    `UPDATE refresh_tokens SET revoked_at = now()
     WHERE token_hash = $1 AND revoked_at IS NULL`,
    [sha256(raw)]
  )
}

export async function revokeAllUserTokens(userId) {
  const { rowCount } = await query(
    `UPDATE refresh_tokens SET revoked_at = now()
     WHERE user_id = $1 AND revoked_at IS NULL`,
    [userId]
  )
  return rowCount
}

/** 清理已过期或早已吊销的令牌记录。 */
export async function purgeExpiredTokens() {
  const { rowCount } = await query(
    `DELETE FROM refresh_tokens
     WHERE expires_at < now() - interval '7 days'
        OR (revoked_at IS NOT NULL AND revoked_at < now() - interval '7 days')`
  )
  return rowCount
}
```

server/src/services/defaultSceneService.js

```
import { query } from '../db/pool.js'
import { createDefaultTrainingScene } from '../../../src/game/defaultTrainingScene.js'

/**
 * 以固定 ID 幂等插入云端示范场景，不覆盖教师已有版本。
 * @returns {object} 场景 ID 与是否新建
 */
export async function ensureDefaultCloudScene() {
  const scene = createDefaultTrainingScene()
  const { rowCount } = await query(
    `INSERT INTO training_scenes
       (id, name, description, difficulty, published, published_at, owner_id, payload)
     VALUES ($1, $2, $3, $4, TRUE, now(), NULL, $5::jsonb)
     ON CONFLICT (id) DO NOTHING`,
    [scene.id, scene.name, scene.description, scene.difficulty, JSON.stringify(scene.payload)]
  )
  return { id: scene.id, inserted: rowCount > 0 }
}
```

server/src/repositories/sceneRepository.js

```
import { query, queryOne } from '../db/pool.js'
import { newId } from '../utils/id.js'

/**
 * 按归属、发布状态与关键字过滤场景列表。
 * @param {object} ownerId 场景归属用户
 * @param {string} q 名称和说明关键字
 * @param {object} published 发布筛选条件
 * @param {object} includeDeleted 是否包含软删除数据
 * @param {number} limit 最大行数
 * @param {number} offset 分页偏移
 * @returns {object} 场景列表和总数
 */
export async function listScenes({ ownerId, q, published, includeDeleted = false, limit, offset }) {
  const { rows } = await query(
    `SELECT s.id, s.name, s.description, s.difficulty, s.published, s.published_at,
            s.owner_id, s.created_at, s.updated_at,
            u.username AS owner_name, u.display_name AS owner_display_name,
            COUNT(*) OVER()::int AS total_count
     FROM training_scenes s
```

```
     LEFT JOIN users u ON u.id = s.owner_id
     WHERE ($1::boolean OR s.deleted_at IS NULL)
       AND ($2::text IS NULL OR s.owner_id = $2)
       AND ($3::text IS NULL OR s.name ILIKE '%' || $3 || '%' OR s.description ILIKE '%' || $3 || '%')
       AND ($4::boolean IS NULL OR s.published = $4)
     ORDER BY s.updated_at DESC, s.id DESC
     LIMIT $5 OFFSET $6`,
    [includeDeleted, ownerId || null, q || null, published ?? null, limit, offset]
  )
  return rows
}

/** 学生端用：已发布的场景，不需要分页信封里的 owner 信息。 */
export async function listPublishedScenes({ limit = 100, offset = 0 }) {
  const { rows } = await query(
    `SELECT s.id, s.name, s.description, s.difficulty, s.published, s.published_at,
            s.payload, s.created_at, s.updated_at,
            COUNT(*) OVER()::int AS total_count
     FROM training_scenes s
     WHERE s.published = TRUE AND s.deleted_at IS NULL
     ORDER BY s.updated_at DESC, s.id DESC
     LIMIT $1 OFFSET $2`,
    [limit, offset]
  )
  return rows
}

export function getScene(id) {
  return queryOne(
    `SELECT id, name, description, difficulty, published, published_at, owner_id,
            payload, created_at, updated_at, deleted_at
     FROM training_scenes WHERE id = $1`,
    [id]
  )
}

/**
 * 写入服务端场景记录并返回版本元数据。
 * @param {string} id 可选的场景主键
 * @param {string} name 场景名称
 * @param {object} description 场景说明
 * @param {object} difficulty 训练难度
 * @param {object} ownerId 场景归属用户
 * @param {object} payload 场景 JSON
 * @returns {object} 已持久化的场景
 */
export async function upsertScene({ id, name, description, difficulty, ownerId, payload }) {
  const sceneId = id || newId('scene')
  return queryOne(
    `INSERT INTO training_scenes (id, name, description, difficulty, owner_id, payload, updated_at)
     VALUES ($1, $2, $3, $4, $5, $6, now())
     ON CONFLICT (id) DO UPDATE
       SET name = EXCLUDED.name,
           description = EXCLUDED.description,
           difficulty = EXCLUDED.difficulty,
           payload = EXCLUDED.payload,
           updated_at = now()
     RETURNING id, name, description, difficulty, published, owner_id, created_at, updated_at`,
    [
      sceneId,
      name,
      description ?? null,
      difficulty ?? null,
      ownerId ?? null,
      JSON.stringify(payload ?? {}),
    ]
  )
}

export async function setPublished(id, published) {
  return queryOne(
    `UPDATE training_scenes
     SET published = $2, published_at = CASE WHEN $2 THEN now() ELSE NULL END
     WHERE id = $1 AND deleted_at IS NULL
     RETURNING id, name, published, published_at, updated_at`,
    [id, published]
```

```
  )
}

export async function softDeleteScene(id) {
  const { rowCount } = await query(
    `UPDATE training_scenes SET deleted_at = now(), published = FALSE
     WHERE id = $1 AND deleted_at IS NULL`,
    [id]
  )
  return rowCount > 0
}

export async function listRecords({ userId, sceneId, q, completed, limit, offset }) {
  const { rows } = await query(
    `SELECT r.id, r.scene_id, r.scene_name, r.student_name, r.score, r.elapsed_seconds,
            r.completed, r.inspected_count, r.mistake_count, r.user_id, r.created_at,
            u.username, u.display_name,
            COUNT(*) OVER()::int AS total_count
     FROM training_records r
     LEFT JOIN users u ON u.id = r.user_id
     WHERE ($1::text IS NULL OR r.user_id = $1)
       AND ($2::text IS NULL OR r.scene_id = $2)
       AND ($3::text IS NULL OR r.student_name ILIKE '%' || $3 || '%' OR r.scene_name ILIKE '%' || $3 || '%')
       AND ($4::boolean IS NULL OR r.completed = $4)
     ORDER BY r.created_at DESC, r.id DESC
     LIMIT $5 OFFSET $6`,
    [userId || null, sceneId || null, q || null, completed ?? null, limit, offset]
  )
  return rows
}

/**
 * 保存训练成绩并绑定场景和登录用户。
 * @param {object} record 含得分和训练耗时的记录
 * @returns {object} 成绩记录元数据
 */
export async function insertRecord(record) {
  const id = record.id || newId('rec')
  return queryOne(
    `INSERT INTO training_records
       (id, scene_id, scene_name, student_name, score, elapsed_seconds, payload,
        user_id, completed, inspected_count, mistake_count)
     VALUES ($1, $2, $3, $4, $5, $6, $7, $8, $9, $10, $11)
     RETURNING id, scene_id, scene_name, student_name, score, elapsed_seconds, completed, created_at`,
    [
      id,
      record.sceneId ?? null,
      record.sceneName ?? null,
      record.studentName ?? null,
      record.score ?? null,
      record.elapsedSeconds ?? null,
      JSON.stringify(record.payload ?? {}),
      record.userId ?? null,
      record.completed ?? false,
      record.inspectedCount ?? null,
      record.mistakeCount ?? null,
    ]
  )
}

export async function sceneStats() {
  return queryOne(
    `SELECT
       COUNT(*)::int AS total,
       COUNT(*) FILTER (WHERE published)::int AS published,
       COUNT(*) FILTER (WHERE deleted_at IS NOT NULL)::int AS deleted
     FROM training_scenes`
  )
}

export async function recordStats() {
  return queryOne(
    `SELECT
       COUNT(*)::int AS total,
       COUNT(*) FILTER (WHERE completed)::int AS completed,
       COALESCE(ROUND(AVG(score))::int, 0) AS avg_score,
```

```
      COALESCE(SUM(elapsed_seconds), 0)::int AS total_seconds
    FROM training_records`
  )
}
```

server/src/repositories/conversationRepository.js

```
import { query, queryOne } from '../db/pool.js'
import { newId } from '../utils/id.js'

export async function createConversation({ userId, title, model, systemPrompt }) {
  return queryOne(
    `INSERT INTO ai_conversations (id, user_id, title, model, system_prompt)
     VALUES ($1, $2, $3, $4, $5)
     RETURNING id, title, model, message_count, created_at, updated_at`,
    [newId('c'), userId, title || '新对话', model || '', systemPrompt || null]
  )
}

export function getConversation(id) {
  return queryOne(
    `SELECT id, user_id, title, model, system_prompt, message_count, last_message_at, created_at, updated_at
     FROM ai_conversations WHERE id = $1`,
    [id]
  )
}

export async function appendMessage({ conversationId, userId, role, content, model, status, error, sceneContext, equipment }) {
  const row = await queryOne(
    `INSERT INTO ai_messages (conversation_id, user_id, role, content, model, status, error, scene_context, equipment_context)
     VALUES ($1, $2, $3, $4, $5, $6, $7, $8, $9::jsonb)
     RETURNING id, conversation_id, role, content, model, status, scene_context, equipment_context, created_at`,
    [conversationId, userId ?? null, role, content ?? '', model ?? null, status ?? 'ok', error ?? null, sceneContext ?? null, JSON.stringify(equipment
  )

  await query(
    `UPDATE ai_conversations
     SET message_count = message_count + 1,
         last_message_at = now(),
         model = COALESCE(NULLIF($2, ''), model)
     WHERE id = $1`,
    [conversationId, model ?? '']
  )

  return row
}

export async function completeAssistantMessage(id, { content, promptTokens, completionTokens, latencyMs, status, error }) {
  return queryOne(
    `UPDATE ai_messages
     SET content = $2, prompt_tokens = $3, completion_tokens = $4, latency_ms = $5,
         status = $6, error = $7
     WHERE id = $1
     RETURNING id, content, status`,
    [id, content ?? '', promptTokens ?? null, completionTokens ?? null, latencyMs ?? null, status ?? 'ok', error ?? null]
  )
}

/** 取最近 N 条历史作为对话上下文（按时间正序返回）。 */
export async function recentMessages(conversationId, limit = 20) {
  const { rows } = await query(
    `SELECT role, content FROM (
       SELECT id, role, content, created_at
       FROM ai_messages
       WHERE conversation_id = $1 AND status <> 'error' AND content <> ''
       ORDER BY id DESC
       LIMIT $2
     ) t ORDER BY t.id ASC`,
    [conversationId, limit]
  )
  return rows
}

export async function listMessages(conversationId, { limit, offset }) {
```

```
  const { rows } = await query(
    `SELECT id, role, content, model, prompt_tokens, completion_tokens, latency_ms, status, scene_context, equipment_context, created_at,
            COUNT(*) OVER()::int AS total_count
     FROM ai_messages
     WHERE conversation_id = $1
     ORDER BY id ASC
     LIMIT $2 OFFSET $3`,
    [conversationId, limit, offset]
  )
  return rows
}

export async function listUserConversations(userId, { limit, offset, q }) {
  const { rows } = await query(
    `SELECT id, title, model, message_count, last_message_at, created_at, updated_at,
            COUNT(*) OVER()::int AS total_count
     FROM ai_conversations
     WHERE user_id = $1 AND archived = FALSE
       AND ($2::text IS NULL OR title ILIKE '%' || $2 || '%')
     ORDER BY updated_at DESC, id DESC
     LIMIT $3 OFFSET $4`,
    [userId, q || null, limit, offset]
  )
  return rows
}

export async function adminListConversations({ userId, q, model, limit, offset }) {
  const { rows } = await query(
    `SELECT c.id, c.user_id, c.title, c.model, c.message_count, c.last_message_at,
            c.created_at, c.updated_at,
            u.username, u.display_name,
            COUNT(*) OVER()::int AS total_count
     FROM ai_conversations c
     LEFT JOIN users u ON u.id = c.user_id
     WHERE ($1::text IS NULL OR c.user_id = $1)
       AND ($2::text IS NULL OR c.title ILIKE '%' || $2 || '%' OR u.username ILIKE '%' || $2 || '%')
       AND ($3::text IS NULL OR c.model = $3)
     ORDER BY c.updated_at DESC, c.id DESC
     LIMIT $4 OFFSET $5`,
    [userId || null, q || null, model || null, limit, offset]
  )
  return rows
}

export async function renameConversation(id, title) {
  return queryOne(
    `UPDATE ai_conversations SET title = $2 WHERE id = $1 RETURNING id, title`,
    [id, title]
  )
}

export async function deleteConversation(id) {
  const { rowCount } = await query(`DELETE FROM ai_conversations WHERE id = $1`, [id])
  return rowCount > 0
}

export async function countConversations() {
  return queryOne(
    `SELECT
       COUNT(*)::int AS total,
       COUNT(*) FILTER (WHERE updated_at > now() - interval '7 days')::int AS recent
     FROM ai_conversations`
  )
}

export async function countMessages() {
  return queryOne(`SELECT COUNT(*)::int AS total FROM ai_messages`)
}
```

server/src/db/schema.sql

```
-- 铁道信号巡检平台 数据库结构（权威定义，由 scripts/init-postgres.mjs 执行）
--
-- 约定沿用项目已有风格：TEXT + nanoid 主键、TIMESTAMPTZ DEFAULT now()、JSONB 载荷。
```

```
-- 一处有意偏离：高频追加型日志表（login_logs / ai_messages / ai_request_logs）用 BIGSERIAL，
-- 让分页有廉价、稳定且单调的 tiebreaker，索引也不会因随机文本键而膨胀。
--
-- 全部语句幂等（IF NOT EXISTS / ADD COLUMN IF NOT EXISTS），可重复执行。

-- ============================ 身份与账号 ============================

CREATE TABLE IF NOT EXISTS users (
  id                   TEXT PRIMARY KEY,
  username             TEXT NOT NULL,
  display_name         TEXT NOT NULL DEFAULT '',
  email                TEXT,
  phone                TEXT,
  password_hash        TEXT NOT NULL,
  role                 TEXT NOT NULL DEFAULT 'student',
  status               TEXT NOT NULL DEFAULT 'active',
  must_change_password BOOLEAN NOT NULL DEFAULT FALSE,
  failed_login_count   INTEGER NOT NULL DEFAULT 0,
  locked_until         TIMESTAMPTZ,
  last_login_at        TIMESTAMPTZ,
  last_login_ip        TEXT,
  password_changed_at  TIMESTAMPTZ NOT NULL DEFAULT now(),
  remark               TEXT,
  created_at           TIMESTAMPTZ NOT NULL DEFAULT now(),
  updated_at           TIMESTAMPTZ NOT NULL DEFAULT now(),
  deleted_at           TIMESTAMPTZ,
  CONSTRAINT users_role_check   CHECK (role   IN ('student', 'teacher', 'admin')),
  CONSTRAINT users_status_check CHECK (status IN ('active', 'disabled', 'locked'))
);

-- 用户名/邮箱/手机号唯一，但仅在未软删的行上生效，这样删除后可以重新注册同名账号。
CREATE UNIQUE INDEX IF NOT EXISTS users_username_lower_key
  ON users (lower(username)) WHERE deleted_at IS NULL;
CREATE UNIQUE INDEX IF NOT EXISTS users_email_lower_key
  ON users (lower(email)) WHERE deleted_at IS NULL AND email IS NOT NULL;
CREATE UNIQUE INDEX IF NOT EXISTS users_phone_key
  ON users (phone) WHERE deleted_at IS NULL AND phone IS NOT NULL;
CREATE INDEX IF NOT EXISTS users_created_idx     ON users (created_at DESC, id DESC);
CREATE INDEX IF NOT EXISTS users_role_status_idx ON users (role, status);

-- 刷新令牌只存 sha256，明文不落库。family_id 用于重放检测：
-- 一个已轮换过的令牌再次出现，说明它被窃取了，整个家族全部吊销。
CREATE TABLE IF NOT EXISTS refresh_tokens (
  id          TEXT PRIMARY KEY,
  user_id     TEXT NOT NULL REFERENCES users(id) ON DELETE CASCADE,
  token_hash  TEXT NOT NULL UNIQUE,
  family_id   TEXT NOT NULL,
  expires_at  TIMESTAMPTZ NOT NULL,
  revoked_at  TIMESTAMPTZ,
  replaced_by TEXT,
  user_agent  TEXT,
  ip          TEXT,
  created_at  TIMESTAMPTZ NOT NULL DEFAULT now()
);
CREATE INDEX IF NOT EXISTS refresh_tokens_user_idx    ON refresh_tokens (user_id, created_at DESC);
CREATE INDEX IF NOT EXISTS refresh_tokens_family_idx  ON refresh_tokens (family_id);
CREATE INDEX IF NOT EXISTS refresh_tokens_expires_idx ON refresh_tokens (expires_at);

CREATE TABLE IF NOT EXISTS password_reset_tokens (
  id         TEXT PRIMARY KEY,
  user_id    TEXT NOT NULL REFERENCES users(id) ON DELETE CASCADE,
  token_hash TEXT NOT NULL UNIQUE,
  channel    TEXT NOT NULL DEFAULT 'manual',
  expires_at TIMESTAMPTZ NOT NULL,
  used_at    TIMESTAMPTZ,
  issued_by  TEXT REFERENCES users(id) ON DELETE SET NULL,
  ip         TEXT,
  created_at TIMESTAMPTZ NOT NULL DEFAULT now()
);
CREATE INDEX IF NOT EXISTS password_reset_tokens_user_idx    ON password_reset_tokens (user_id, created_at DESC);
CREATE INDEX IF NOT EXISTS password_reset_tokens_expires_idx ON password_reset_tokens (expires_at);

-- ============================ 审计日志 ============================

CREATE TABLE IF NOT EXISTS login_logs (
  id             BIGSERIAL PRIMARY KEY,
```

```
  user_id        TEXT REFERENCES users(id) ON DELETE SET NULL,
  username_input TEXT,
  success        BOOLEAN NOT NULL,
  failure_reason TEXT,
  ip             TEXT,
  user_agent     TEXT,
  created_at     TIMESTAMPTZ NOT NULL DEFAULT now()
);
CREATE INDEX IF NOT EXISTS login_logs_created_idx ON login_logs (created_at DESC, id DESC);
CREATE INDEX IF NOT EXISTS login_logs_user_idx    ON login_logs (user_id, created_at DESC);
CREATE INDEX IF NOT EXISTS login_logs_success_idx ON login_logs (success, created_at DESC);

-- ========================== 智能体 ==========================

CREATE TABLE IF NOT EXISTS ai_conversations (
  id              TEXT PRIMARY KEY,
  user_id         TEXT NOT NULL REFERENCES users(id) ON DELETE CASCADE,
  title           TEXT NOT NULL DEFAULT '新对话',
  model           TEXT NOT NULL DEFAULT '',
  system_prompt   TEXT,
  message_count   INTEGER NOT NULL DEFAULT 0,
  last_message_at TIMESTAMPTZ,
  archived        BOOLEAN NOT NULL DEFAULT FALSE,
  created_at      TIMESTAMPTZ NOT NULL DEFAULT now(),
  updated_at      TIMESTAMPTZ NOT NULL DEFAULT now()
);
CREATE INDEX IF NOT EXISTS ai_conversations_user_idx    ON ai_conversations (user_id, updated_at DESC, id DESC);
CREATE INDEX IF NOT EXISTS ai_conversations_updated_idx ON ai_conversations (updated_at DESC, id DESC);

CREATE TABLE IF NOT EXISTS ai_messages (
  id                BIGSERIAL PRIMARY KEY,
  conversation_id   TEXT NOT NULL REFERENCES ai_conversations(id) ON DELETE CASCADE,
  user_id           TEXT REFERENCES users(id) ON DELETE SET NULL,
  role              TEXT NOT NULL,
  content           TEXT NOT NULL DEFAULT '',
  model             TEXT,
  prompt_tokens     INTEGER,
  completion_tokens INTEGER,
  latency_ms        INTEGER,
  status            TEXT NOT NULL DEFAULT 'ok',
  error             TEXT,
  created_at        TIMESTAMPTZ NOT NULL DEFAULT now(),
  CONSTRAINT ai_messages_role_check CHECK (role IN ('system', 'user', 'assistant'))
);
CREATE INDEX IF NOT EXISTS ai_messages_conversation_idx ON ai_messages (conversation_id, id);
CREATE INDEX IF NOT EXISTS ai_messages_created_idx      ON ai_messages (created_at DESC, id DESC);

-- conversation_id 故意不加外键：调用日志要在会话被删除后依然留存。
CREATE TABLE IF NOT EXISTS ai_request_logs (
  id                BIGSERIAL PRIMARY KEY,
  user_id           TEXT REFERENCES users(id) ON DELETE SET NULL,
  conversation_id   TEXT,
  model             TEXT NOT NULL,
  endpoint          TEXT NOT NULL DEFAULT 'chat',
  status            TEXT NOT NULL DEFAULT 'ok',
  http_status       INTEGER,
  latency_ms        INTEGER,
  first_token_ms    INTEGER,
  prompt_tokens     INTEGER,
  completion_tokens INTEGER,
  error             TEXT,
  created_at        TIMESTAMPTZ NOT NULL DEFAULT now()
);
CREATE INDEX IF NOT EXISTS ai_request_logs_created_idx ON ai_request_logs (created_at DESC, id DESC);
CREATE INDEX IF NOT EXISTS ai_request_logs_user_idx    ON ai_request_logs (user_id, created_at DESC);
CREATE INDEX IF NOT EXISTS ai_request_logs_model_idx   ON ai_request_logs (model, created_at DESC);

-- ========================== 系统设置 ==========================

CREATE TABLE IF NOT EXISTS system_settings (
  key         TEXT PRIMARY KEY,
  value       JSONB NOT NULL,
  description TEXT,
  updated_by  TEXT REFERENCES users(id) ON DELETE SET NULL,
  updated_at  TIMESTAMPTZ NOT NULL DEFAULT now()
);
```

```
CREATE TABLE IF NOT EXISTS audit_logs (
  id          BIGSERIAL PRIMARY KEY,
  user_id     TEXT REFERENCES users(id) ON DELETE SET NULL,
  username    TEXT,
  action      TEXT NOT NULL,
  target_type TEXT,
  target_id   TEXT,
  detail      JSONB,
  ip          TEXT,
  created_at  TIMESTAMPTZ NOT NULL DEFAULT now()
);
CREATE INDEX IF NOT EXISTS audit_logs_created_idx ON audit_logs (created_at DESC, id DESC);
CREATE INDEX IF NOT EXISTS audit_logs_user_idx    ON audit_logs (user_id, created_at DESC);
CREATE INDEX IF NOT EXISTS audit_logs_action_idx  ON audit_logs (action, created_at DESC);

-- ========================== 训练数据 ==========================

-- Fresh installs need the core training tables before the shared schema adds
-- account ownership, publication, and pagination fields below.
CREATE TABLE IF NOT EXISTS training_scenes (
  id         TEXT PRIMARY KEY,
  name       TEXT NOT NULL,
  payload    JSONB NOT NULL DEFAULT '{}'::jsonb,
  created_at TIMESTAMPTZ NOT NULL DEFAULT now(),
  updated_at TIMESTAMPTZ NOT NULL DEFAULT now()
);

CREATE TABLE IF NOT EXISTS training_records (
  id              TEXT PRIMARY KEY,
  scene_id        TEXT,
  student_name    TEXT,
  score           INTEGER,
  elapsed_seconds INTEGER,
  payload         JSONB NOT NULL DEFAULT '{}'::jsonb,
  created_at      TIMESTAMPTZ NOT NULL DEFAULT now()
);

ALTER TABLE training_scenes ADD COLUMN IF NOT EXISTS owner_id     TEXT REFERENCES users(id) ON DELETE SET NULL;
ALTER TABLE training_scenes ADD COLUMN IF NOT EXISTS published    BOOLEAN NOT NULL DEFAULT FALSE;
ALTER TABLE training_scenes ADD COLUMN IF NOT EXISTS published_at TIMESTAMPTZ;
ALTER TABLE training_scenes ADD COLUMN IF NOT EXISTS description  TEXT;
ALTER TABLE training_scenes ADD COLUMN IF NOT EXISTS difficulty   TEXT;
ALTER TABLE training_scenes ADD COLUMN IF NOT EXISTS deleted_at   TIMESTAMPTZ;
CREATE INDEX IF NOT EXISTS training_scenes_updated_idx   ON training_scenes (updated_at DESC, id DESC);
CREATE INDEX IF NOT EXISTS training_scenes_published_idx ON training_scenes (published, updated_at DESC, id DESC);
CREATE INDEX IF NOT EXISTS training_scenes_owner_idx     ON training_scenes (owner_id, updated_at DESC);

ALTER TABLE training_records ADD COLUMN IF NOT EXISTS user_id         TEXT REFERENCES users(id) ON DELETE SET NULL;
ALTER TABLE training_records ADD COLUMN IF NOT EXISTS scene_name      TEXT;
ALTER TABLE training_records ADD COLUMN IF NOT EXISTS completed       BOOLEAN NOT NULL DEFAULT FALSE;
ALTER TABLE training_records ADD COLUMN IF NOT EXISTS inspected_count INTEGER;
ALTER TABLE training_records ADD COLUMN IF NOT EXISTS mistake_count   INTEGER;
CREATE INDEX IF NOT EXISTS training_records_created_idx ON training_records (created_at DESC, id DESC);
CREATE INDEX IF NOT EXISTS training_records_user_idx    ON training_records (user_id, created_at DESC);
CREATE INDEX IF NOT EXISTS training_records_scene_idx   ON training_records (scene_id, created_at DESC);

-- ========================== updated_at 自动维护 ==========================

CREATE OR REPLACE FUNCTION set_updated_at() RETURNS trigger AS $$
BEGIN
  NEW.updated_at = now();
  RETURN NEW;
END;
$$ LANGUAGE plpgsql;

DROP TRIGGER IF EXISTS users_set_updated_at ON users;
CREATE TRIGGER users_set_updated_at BEFORE UPDATE ON users
  FOR EACH ROW EXECUTE FUNCTION set_updated_at();

DROP TRIGGER IF EXISTS ai_conversations_set_updated_at ON ai_conversations;
CREATE TRIGGER ai_conversations_set_updated_at BEFORE UPDATE ON ai_conversations
  FOR EACH ROW EXECUTE FUNCTION set_updated_at();

DROP TRIGGER IF EXISTS training_scenes_set_updated_at ON training_scenes;
CREATE TRIGGER training_scenes_set_updated_at BEFORE UPDATE ON training_scenes
  FOR EACH ROW EXECUTE FUNCTION set_updated_at();
```

server/src/db/migrations/009_ai_equipment_context.sql

```
ALTER TABLE ai_messages ADD COLUMN IF NOT EXISTS scene_context TEXT;
ALTER TABLE ai_messages ADD COLUMN IF NOT EXISTS equipment_context JSONB;
```