

马来西亚留学生汉语练习平台源代码

软件名称：马来西亚留学生汉语练习平台

版本号：V1.0

源代码属性结构说明

本源码由后台 admin、前台 fronter 和数据库脚本三部分组成。后台使用 Node.js、Express、mysql2 和 MySQL 连接池提供认证、学习练习、管理统计、日志记录和数据库初始化能力；前台使用 Vue 3、Vue Router 和 Vite 提供学生端练习页面、管理端看板页面、国际化界面和 API 调用封装；数据库脚本负责创建用户、等级、分类、题库、试卷、答题记录、错题本和国际化消息等业务表。

选入源码稿的范围包括 admin/src、admin/sql、fronter/src 以及两个 package.json 中与系统运行直接相关的配置。已排除 node_modules、dist、package-lock、日志文件和第三方依赖源码。源码中涉及密码、令牌、邮箱、主机地址和数据库连接敏感值均已脱敏。

三级目录结构

- admin/src：后台应用入口、路由、中间件、配置和工具模块
- admin/sql：数据库建表和演示题库初始化脚本
- fronter/src：前台入口、路由、状态、国际化、页面组件和样式
- package.json：前后台运行脚本和依赖配置

文件：admin/src/server.js

文件职责：提供系统运行所需的入口、配置或支撑逻辑。

所属模块：后台服务模块

```
import app from './app.js';
import { logger } from './utils/logger.js';
const port = Number(process.env.PORT || 3000);
app.listen(port, () => {
  logger.info(`Chinese practice API running at http://localhost:${port}`);
});
```

文件：admin/src/app.js

文件职责：提供系统运行所需的入口、配置或支撑逻辑。

所属模块：后台服务模块

```
import express from 'express';
import cors from 'cors';
import dotenv from 'dotenv';
import authRoutes from './routes/auth.js';
import learningRoutes from './routes/learning.js';
import adminRoutes from './routes/admin.js';
import { requestLogger } from './middleware/requestLogger.js';
import { logger } from './utils/logger.js';
dotenv.config();
const app = express();
app.use(cors());
app.use(express.json());
app.use(requestLogger);
app.get('/api/health', (_req, res) => res.json({ code: 200, message: 'success', data: { status: 'ok' } }));
app.use('/api/auth', authRoutes);
app.use('/api/learning', learningRoutes);
app.use('/api/admin', adminRoutes);
app.use((req, res) => res.status(404).json({ code: 404, message: `Not found: ${req.path}` }));
app.use((err, req, res, _next) => {
  const status = err.status || 500;
```

```

logger.error('HTTP request failed', {
  method: req.method,
  path: req.originalUrl,
  status,
  message: err.message,
  stack: process.env.NODE_ENV === 'production' ? undefined : err.stack
});
res.status(status).json({ code: status, message: err.message || 'Internal server error' });
});
export default app;

```

文件：admin/src/config/db.js

文件职责：配置 MySQL 连接池和事务封装。

所属模块：后台服务模块

```

import mysql from 'mysql2/promise';
import dotenv from 'dotenv';
dotenv.config();
export const pool = mysql.createPool({
  host: process.env.DB_HOST || 'localhost',
  port: Number(process.env.DB_PORT || 3306),
  user: process.env.DB_USER || 'root',
  password: process.env.DB_PASSWORD || '***',
  database: process.env.DB_NAME || 'school_chinese_exam_practice',
  waitForConnections: true,
  connectionLimit: 10,
  namedPlaceholders: true
});
export async function tx(work) {
  const conn = await pool.getConnection();
  try {
    await conn.beginTransaction();
    const result = await work(conn);
    await conn.commit();
    return result;
  } catch (error) {
    await conn.rollback();
    throw error;
  } finally {
    conn.release();
  }
}

```

文件：admin/src/middleware/auth.js

文件职责：解析 JWT 并完成接口登录态校验。

所属模块：后台服务模块

```

import jwt from 'jsonwebtoken';
import { HttpError } from '../utils/errors.js';
export function auth(required = true) {
  return (req, _res, next) => {
    const header = req.headers.authorization || '';
    const token = header.startsWith('Bearer ') ? header.slice(7) : '';
    if (!token) {
      if (!required) return next();
      return next(new HttpError(401, 'Unauthorized'));
    }
  }
}

```

```

try {
  req.user = jwt.verify(token, process.env.JWT_SECRET || '***');
  return next();
} catch {
  return next(new HttpError(401, 'Invalid token'));
}
};
}

```

文件：admin/src/middleware/role.js

文件职责：按用户角色限制管理员接口访问。

所属模块：后台服务模块

```

import { HttpError } from '../utils/errors.js';
export function allow(...roles) {
  return (req, _res, next) => {
    if (!req.user || !roles.includes(req.user.role)) {
      return next(new HttpError(403, 'Forbidden'));
    }
    return next();
  };
}

```

文件：admin/src/middleware/requestLogger.js

文件职责：记录 HTTP 请求状态、路径、耗时和用户标识。

所属模块：后台服务模块

```

import { logger } from '../utils/logger.js';
export function requestLogger(req, res, next) {
  const startedAt = Date.now();
  res.on('finish', () => {
    const durationMs = Date.now() - startedAt;
    logger.info('HTTP request completed', {
      method: req.method,
      path: req.originalUrl,
      status: res.statusCode,
      durationMs,
      userId: req.user?.id || null
    });
  });
  next();
}

```

文件：admin/src/routes/auth.js

文件职责：提供注册、登录、个人资料查询和个人资料更新接口。

所属模块：后台服务模块

```

import { Router } from 'express';
import bcrypt from 'bcryptjs';
import jwt from 'jsonwebtoken';
import { pool } from '../config/db.js';
import { auth } from '../middleware/auth.js';
import { asyncHandler, ok } from '../utils/response.js';
import { HttpError } from '../utils/errors.js';
const router = Router();
const publicUserFields = 'id, username, name, email, phone, role, student_no, nationality, language, status, created_at';

```

```

router.post('/register', asyncHandler(async (req, res) => {
  const { username, password, name, email, phone, student_no, nationality, language = 'zh-CN' } = req.body;
  if (!username || !password) throw new HttpError(400, 'Username and password are required');
  const hash = await bcrypt.hash(password, 10);
  await pool.execute(
    `INSERT INTO users (username, password, name, email, phone, role, student_no, nationality, language, status)
    VALUES (?, ?, ?, ?, ?, 'student', ?, ?, ?, 'active')`,
    [username, hash, name || username, email || null, phone || null, student_no || null, nationality || 'Malaysia', language]
  );
  ok(res, null, 'registered');
}));
router.post('/login', asyncHandler(async (req, res) => {
  const { username, password } = req.body;
  const [rows] = await pool.execute(`SELECT * FROM users WHERE username = ? AND status = 'active'`, [username]);
  const user = rows[0];
  if (!user || !(await bcrypt.compare(password || '', user.password))) {
    throw new HttpError(401, 'Invalid username or password');
  }
  const token = jwt.sign({ id: user.id, username: user.username, role: user.role }, process.env.JWT_SECRET || '***', { expiresIn: '7d' });
  delete user.password;
  ok(res, { token, user });
}));
router.get('/profile', auth(), asyncHandler(async (req, res) => {
  const [rows] = await pool.execute(`SELECT ${publicUserFields} FROM users WHERE id = ?`, [req.user.id]);
  ok(res, rows[0]);
}));
router.put('/profile', auth(), asyncHandler(async (req, res) => {
  const { name, email, phone, nationality, language } = req.body;
  await pool.execute(
    'UPDATE users SET name=?, email=?, phone=?, nationality=?, language=? WHERE id=?',
    [name, email, phone, nationality, language, req.user.id]
  );
  ok(res);
}));
export default router;

```

文件：admin/src/routes/learning.js

文件职责：提供等级、分类、练习列表、试卷详情、答题提交、成绩记录和错题本接口。

所属模块：后台服务模块

```

import { Router } from 'express';
import { pool, tx } from '../config/db.js';
import { auth } from '../middleware/auth.js';
import { asyncHandler, ok } from '../utils/response.js';
import { HttpError } from '../utils/errors.js';
const router = Router();
function lang(req) {
  return req.query.lang || req.body.language || 'zh-CN';
}
async function getQuestionsByPaper(paperId, language) {
  const [rows] = await pool.execute(

```

```

` SELECT q.id, q.question_type, q.difficulty, pq.score, qt.title, qt.content, qt.analysis,
      l.code level_code, lt.name level_name, c.code category_code, ct.name category_name
FROM paper_questions pq
JOIN questions q ON q.id = pq.question_id
JOIN question_translations qt ON qt.question_id = q.id AND qt.language_code = ?
JOIN levels l ON l.id = q.level_id
JOIN level_translations lt ON lt.level_id = l.id AND lt.language_code = ?
JOIN question_categories c ON c.id = q.category_id
JOIN question_category_translations ct ON ct.category_id = c.id AND ct.language_code = ?
WHERE pq.paper_id = ? AND q.status = 'published'
ORDER BY pq.sort_order ASC`,
[language, language, language, paperId]
);
if (!rows.length) return [];
const ids = rows.map((row) => row.id);
const [options] = await pool.query(
  ` SELECT o.id, o.question_id, o.option_key, ot.content
  FROM question_options o
  JOIN question_option_translations ot ON ot.option_id = o.id AND ot.language_code = ?
  WHERE o.question_id IN (?)
  ORDER BY o.question_id, o.sort_order`,
  [language, ids]
);
return rows.map((question) => ({
  ...question,
  options: options.filter((option) => option.question_id === question.id).map(({ question_id, ...option })
=> option)
}));
}
router.get('/levels', asyncHandler(async (req, res) => {
  const language = lang(req);
  const [rows] = await pool.execute(
    ` SELECT l.id, l.code, lt.name, lt.description
    FROM levels l
    JOIN level_translations lt ON lt.level_id = l.id AND lt.language_code = ?
    WHERE l.status = 'active'
    ORDER BY l.sort_order`,
    [language]
  );
  ok(res, rows);
}));
router.get('/categories', asyncHandler(async (req, res) => {
  const language = lang(req);
  const [rows] = await pool.execute(
    ` SELECT c.id, c.code, ct.name, ct.description
    FROM question_categories c
    JOIN question_category_translations ct ON ct.category_id = c.id AND ct.language_code = ?
    WHERE c.status = 'active'
    ORDER BY c.sort_order`,
    [language]
  );
  ok(res, rows);
}));
router.get('/papers', asyncHandler(async (req, res) => {
  const language = lang(req);
  const [rows] = await pool.execute(
    ` SELECT p.id, p.paper_type, p.total_score, p.duration_minutes, pt.title, pt.description, lt.name level_
name,

```

```

    COUNT(pq.id) question_count
  FROM papers p
  JOIN paper_translations pt ON pt.paper_id = p.id AND pt.language_code = ?
  LEFT JOIN level_translations lt ON lt.level_id = p.level_id AND lt.language_code = ?
  LEFT JOIN paper_questions pq ON pq.paper_id = p.id
  WHERE p.status = 'published'
  GROUP BY p.id, p.paper_type, p.total_score, p.duration_minutes, pt.title, pt.description, lt.name
  ORDER BY p.id DESC`,
  [language, language]
);
ok(res, rows);
});
router.get('/papers/:id', auth(), asyncHandler(async (req, res) => {
  const language = lang(req);
  const paperId = Number(req.params.id);
  const [[paper]] = await pool.execute(
    `SELECT p.id, p.paper_type, p.total_score, p.duration_minutes, pt.title, pt.description
    FROM papers p
    JOIN paper_translations pt ON pt.paper_id = p.id AND pt.language_code = ?
    WHERE p.id = ? AND p.status = 'published'`,
    [language, paperId]
  );
  if (!paper) throw new HttpError(404, 'Paper not found');
  paper.questions = await getQuestionsByPaper(paperId, language);
  ok(res, paper);
});
router.post('/papers/:id/submit', auth(), asyncHandler(async (req, res) => {
  const paperId = Number(req.params.id);
  const answers = Array.isArray(req.body.answers) ? req.body.answers : [];
  const durationSeconds = Number(req.body.duration_seconds || 0);
  const result = await tx(async (conn) => {
    const [questions] = await conn.execute(
      `SELECT pq.question_id, pq.score, GROUP_CONCAT(o.id ORDER BY o.id) correct_option_ids
      FROM paper_questions pq
      JOIN question_options o ON o.question_id = pq.question_id AND o.is_correct = 1
      WHERE pq.paper_id = ?
      GROUP BY pq.question_id, pq.score`,
      [paperId]
    );
    if (!questions.length) throw new HttpError(404, 'Paper not found');
    const byQuestion = new Map(questions.map((q) => [Number(q.question_id), q]));
    let correctCount = 0;
    let totalScore = 0;
    const answerResults = [];
    for (const item of answers) {
      const questionId = Number(item.question_id);
      const question = byQuestion.get(questionId);
      if (!question) continue;
      const selectedIds = (item.selected_option_ids || []).map(Number).sort((a, b) => a - b);
      const correctIds = String(question.correct_option_ids).split(',').map(Number).sort((a, b) => a - b);
      const isCorrect = JSON.stringify(selectedIds) === JSON.stringify(correctIds);
      const score = isCorrect ? Number(question.score) : 0;
      if (isCorrect) correctCount += 1;
      totalScore += score;
      answerResults.push({ question_id: questionId, selected_option_ids: selectedIds, correct_option_ids:
correctIds, is_correct: isCorrect, score });
    }
    const wrongCount = questions.length - correctCount;

```

```

const [record] = await conn.execute(
  `INSERT INTO study_records (user_id, paper_id, total_questions, correct_count, wrong_count, total_score, duration_seconds, started_at, submitted_at)
  VALUES (?, ?, ?, ?, ?, ?, ?, DATE_SUB(NOW(), INTERVAL ? SECOND), NOW())`,
  [req.user.id, paperId, questions.length, correctCount, wrongCount, totalScore, durationSeconds, durationSeconds]
);
for (const item of answerResults) {
  await conn.execute(
    `INSERT INTO user_answers (user_id, question_id, paper_id, study_record_id, selected_option_ids, is_correct, score)
    VALUES (?, ?, ?, ?, ?, ?, ?)`,
    [req.user.id, item.question_id, paperId, record.insertId, item.selected_option_ids.join(','), item.is_correct ? 1 : 0, item.score]
  );
  if (!item.is_correct) {
    await conn.execute(
      `INSERT INTO wrong_questions (user_id, question_id, wrong_count, resolved, last_wrong_at)
      VALUES (?, ?, 1, 0, NOW())
      ON DUPLICATE KEY UPDATE wrong_count = wrong_count + 1, resolved = 0, last_wrong_at = NOW()`,
      [req.user.id, item.question_id]
    );
  } else {
    await conn.execute('UPDATE wrong_questions SET resolved = 1 WHERE user_id = ? AND question_id = ?', [req.user.id, item.question_id]);
  }
}
return {
  record_id: record.insertId,
  total_questions: questions.length,
  correct_count: correctCount,
  wrong_count: wrongCount,
  total_score: totalScore,
  answers: answerResults
};
});
ok(res, result);
});
router.get('/records', auth(), asyncHandler(async (req, res) => {
  const language = lang(req);
  const [rows] = await pool.execute(
    `SELECT r.*, pt.title paper_title
    FROM study_records r
    LEFT JOIN paper_translations pt ON pt.paper_id = r.paper_id AND pt.language_code = ?
    WHERE r.user_id = ?
    ORDER BY r.submitted_at DESC`,
    [language, req.user.id]
  );
  ok(res, rows);
});
router.get('/wrong-questions', auth(), asyncHandler(async (req, res) => {
  const language = lang(req);
  const [rows] = await pool.execute(
    `SELECT w.id, w.wrong_count, w.resolved, w.last_wrong_at, q.id question_id, qt.title, qt.analysis, ct.name category_name
    FROM wrong_questions w
    JOIN questions q ON q.id = w.question_id`
  );

```



```

    JOIN question_translations qt ON qt.question_id = q.id AND qt.language_code = ?
    JOIN question_category_translations ct ON ct.category_id = q.category_id AND ct.language_code = ?
    WHERE w.user_id = ?
    ORDER BY w.resolved ASC, w.last_wrong_at DESC`,
    [language, language, req.user.id]
  );
  ok(res, rows);
});
export default router;

```

文件：admin/src/routes/admin.js

文件职责：提供管理平台统计、学生列表、题库列表、试卷列表和成绩记录列表接口。

所属模块：后台服务模块

```

import { Router } from 'express';
import { pool } from '../config/db.js';
import { auth } from '../middleware/auth.js';
import { allow } from '../middleware/role.js';
import { asyncHandler, ok } from '../utils/response.js';
const router = Router();
router.use(auth(), allow('admin'));
router.get('/stats', asyncHandler(async (_req, res) => {
  const [[users]] = await pool.execute(` SELECT COUNT(*) count FROM users WHERE role='student'`);
  const [[questions]] = await pool.execute(` SELECT COUNT(*) count FROM questions`);
  const [[papers]] = await pool.execute(` SELECT COUNT(*) count FROM papers`);
  const [[records]] = await pool.execute(` SELECT COUNT(*) count, COALESCE(AVG(total_score),0) avg_score FROM study_records`);
  ok(res, {
    students: users.count,
    questions: questions.count,
    papers: papers.count,
    records: records.count,
    avgScore: Number(records.avg_score).toFixed(1)
  });
}));
router.get('/users', asyncHandler(async (_req, res) => {
  const [rows] = await pool.execute(
    ` SELECT id, username, name, email, phone, role, student_no, nationality, language, status, created_at
    FROM users ORDER BY id DESC`
  );
  ok(res, rows);
}));
router.get('/questions', asyncHandler(async (req, res) => {
  const language = req.query.lang || 'zh-CN';
  const [rows] = await pool.execute(
    ` SELECT q.id, qt.title, q.question_type, q.difficulty, q.score, q.status, lt.name level_name, ct.name category_name
    FROM questions q
    JOIN question_translations qt ON qt.question_id = q.id AND qt.language_code = ?
    JOIN level_translations lt ON lt.level_id = q.level_id AND lt.language_code = ?
    JOIN question_category_translations ct ON ct.category_id = q.category_id AND ct.language_code = ?
    ORDER BY q.id DESC`,
    [language, language, language]
  );
  ok(res, rows);
}));

```



```

router.get('/papers', asyncHandler(async (req, res) => {
  const language = req.query.lang || 'zh-CN';
  const [rows] = await pool.execute(
    `SELECT p.id, pt.title, p.paper_type, p.total_score, p.duration_minutes, p.status, COUNT(pq.id) questi
on_count
    FROM papers p
    JOIN paper_translations pt ON pt.paper_id = p.id AND pt.language_code = ?
    LEFT JOIN paper_questions pq ON pq.paper_id = p.id
    GROUP BY p.id, pt.title, p.paper_type, p.total_score, p.duration_minutes, p.status
    ORDER BY p.id DESC`,
    [language]
  );
  ok(res, rows);
}));
router.get('/records', asyncHandler(async (req, res) => {
  const language = req.query.lang || 'zh-CN';
  const [rows] = await pool.execute(
    `SELECT r.id, u.username, u.name, pt.title paper_title, r.total_questions, r.correct_count, r.wrong_cou
nt, r.total_score, r.submitted_at
    FROM study_records r
    JOIN users u ON u.id = r.user_id
    LEFT JOIN paper_translations pt ON pt.paper_id = r.paper_id AND pt.language_code = ?
    ORDER BY r.submitted_at DESC`,
    [language]
  );
  ok(res, rows);
}));
export default router;

```

文件：admin/src/utils/errors.js

文件职责：提供系统运行所需的入口、配置或支撑逻辑。

所属模块：后台服务模块

```

export class HttpError extends Error {
  constructor(status, message) {
    super(message);
    this.status = status;
  }
}

```

文件：admin/src/utils/response.js

文件职责：提供系统运行所需的入口、配置或支撑逻辑。

所属模块：后台服务模块

```

export function ok(res, data = null, message = 'success') {
  return res.json({ code: 200, message, data });
}
export function asyncHandler(fn) {
  return (req, res, next) => Promise.resolve(fn(req, res, next)).catch(next);
}

```

文件：admin/src/utils/logger.js

文件职责：提供控制台和文件双写的日志工具，并脱敏敏感字段。

所属模块：后台服务模块

```

import fs from 'node:fs';
import path from 'node:path';

```

```

import { fileURLToPath } from 'node:url';
const __dirname = path.dirname(fileURLToPath(import.meta.url));
const root = path.resolve(__dirname, '../');
const logDir = process.env.LOG_DIR || path.join(root, 'logs');
const logFile = path.join(logDir, 'app.log');
function ensureLogDir() {
  fs.mkdirSync(logDir, { recursive: true });
}
function mask(value) {
  if (value == null) return value;
  const text = typeof value === 'string' ? value : JSON.stringify(value);
  return text
    .replace(/(authorization["']?\s*[:=]\s*["']?Bearer\s+)[^"\s]+/gi, '$1***')
    .replace(/(password["']?\s*[:=]\s*["']?)[^"\s]+/gi, '$1***')
    .replace(/(token["']?\s*[:=]\s*["']?)[^"\s]+/gi, '$1***');
}
function write(level, message, meta) {
  const timestamp = new Date().toISOString();
  const extra = meta === undefined ? '' : `${mask(meta)} `;
  const line = `[${timestamp}] [${level}] ${message}${extra}`;
  ensureLogDir();
  fs.appendFileSync(logFile, `${line}\n`, 'utf8');
  if (level === 'ERROR') {
    console.error(line);
  } else {
    console.log(line);
  }
}
export const logger = {
  info(message, meta) {
    write('INFO', message, meta);
  },
  warn(message, meta) {
    write('WARN', message, meta);
  },
  error(message, meta) {
    write('ERROR', message, meta);
  }
};
export { logFile };

```

文件：admin/src/utils/initDb.js

文件职责：提供系统运行所需的入口、配置或支撑逻辑。

所属模块：后台服务模块

```

import fs from 'node:fs/promises';
import path from 'node:path';
import { fileURLToPath } from 'node:url';
import mysql from 'mysql2/promise';
import dotenv from 'dotenv';
import { logger } from './logger.js';
dotenv.config();
const __dirname = path.dirname(fileURLToPath(import.meta.url));
const root = path.resolve(__dirname, '../');
const connection = await mysql.createConnection({
  host: process.env.DB_HOST || 'localhost',
  port: Number(process.env.DB_PORT || 3306),

```

```

user: process.env.DB_USER || 'root',
password: process.env.DB_PASSWORD || '***',
multipleStatements: true
});
for (const file of ['schema.sql', 'seed.sql']) {
  const sql = await fs.readFile(path.join(root, 'sql', file), 'utf8');
  await connection.query(sql);
  logger.info(`Executed ${file}`);
}
await connection.end();
logger.info('Database initialized.');
```

文件：admin/src/utis/seedUsers.js

文件职责：提供系统运行所需的入口、配置或支撑逻辑。

所属模块：后台服务模块

```

import bcrypt from 'bcryptjs';
import { pool } from '../config/db.js';
import { logger } from './logger.js';
const users = [
  ['admin', '***', '系统管理员', 'admin', '***@***', 'Malaysia'],
  ['student', '***', 'Amin', 'student', '***@***', 'Malaysia']
];
for (const [username, password, name, role, email, nationality] of users) {
  const hash = await bcrypt.hash(password, 10);
  await pool.execute(
    `INSERT INTO users (username, password, name, email, role, nationality, language, status)
    VALUES (?, ?, ?, ?, ?, 'zh-CN', 'active')
    ON DUPLICATE KEY UPDATE password=VALUES(password), name=VALUES(name), role=VALUES(role),
    email=VALUES(email), nationality=VALUES(nationality), status='active'`,
    [username, hash, name, email, role, nationality]
  );
}
logger.info('Seed users ready for admin and student accounts');
await pool.end();
```

文件：admin/sql/schema.sql

文件职责：创建系统所需数据库、业务表、唯一约束和外键。

所属模块：数据库脚本模块

```

CREATE DATABASE IF NOT EXISTS school_chinese_exam_practice DEFAULT CHARACTER SET utf8mb4 CO
LLATE utf8mb4_unicode_ci;
USE school_chinese_exam_practice;
CREATE TABLE IF NOT EXISTS users (
  id BIGINT PRIMARY KEY AUTO_INCREMENT,
  username VARCHAR(50) NOT NULL UNIQUE,
  password VARCHAR(255) NOT NULL,
  name VARCHAR(100),
  email VARCHAR(120),
  phone VARCHAR(30),
  role ENUM('student','admin') NOT NULL DEFAULT 'student',
  student_no VARCHAR(50),
  nationality VARCHAR(80),
  language VARCHAR(20) DEFAULT 'zh-CN',
  status ENUM('active','disabled') NOT NULL DEFAULT 'active',
  created_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP,
  updated_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP ON UPDATE CURRENT_TIMESTAMP
```

```

);
CREATE TABLE IF NOT EXISTS levels (
  id BIGINT PRIMARY KEY AUTO_INCREMENT,
  code VARCHAR(40) NOT NULL UNIQUE,
  sort_order INT NOT NULL DEFAULT 0,
  status ENUM('active','disabled') NOT NULL DEFAULT 'active',
  created_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP
);
CREATE TABLE IF NOT EXISTS level_translations (
  id BIGINT PRIMARY KEY AUTO_INCREMENT,
  level_id BIGINT NOT NULL,
  language_code VARCHAR(20) NOT NULL,
  name VARCHAR(120) NOT NULL,
  description VARCHAR(500),
  UNIQUE KEY uk_level_lang (level_id, language_code),
  CONSTRAINT fk_level_translations_level FOREIGN KEY (level_id) REFERENCES levels(id) ON DELETE CASCADE
);
CREATE TABLE IF NOT EXISTS question_categories (
  id BIGINT PRIMARY KEY AUTO_INCREMENT,
  parent_id BIGINT,
  code VARCHAR(60) NOT NULL UNIQUE,
  sort_order INT NOT NULL DEFAULT 0,
  status ENUM('active','disabled') NOT NULL DEFAULT 'active',
  CONSTRAINT fk_categories_parent FOREIGN KEY (parent_id) REFERENCES question_categories(id) ON DELETE SET NULL
);
CREATE TABLE IF NOT EXISTS question_category_translations (
  id BIGINT PRIMARY KEY AUTO_INCREMENT,
  category_id BIGINT NOT NULL,
  language_code VARCHAR(20) NOT NULL,
  name VARCHAR(120) NOT NULL,
  description VARCHAR(500),
  UNIQUE KEY uk_category_lang (category_id, language_code),
  CONSTRAINT fk_category_translations_category FOREIGN KEY (category_id) REFERENCES question_categories(id) ON DELETE CASCADE
);
CREATE TABLE IF NOT EXISTS questions (
  id BIGINT PRIMARY KEY AUTO_INCREMENT,
  level_id BIGINT NOT NULL,
  category_id BIGINT NOT NULL,
  question_type ENUM('single_choice','multiple_choice','true_false','fill_blank') NOT NULL DEFAULT 'single_choice',
  difficulty ENUM('easy','normal','hard') NOT NULL DEFAULT 'easy',
  score DECIMAL(5,2) NOT NULL DEFAULT 1.00,
  audio_url VARCHAR(500),
  image_url VARCHAR(500),
  status ENUM('published','draft','disabled') NOT NULL DEFAULT 'published',
  created_by BIGINT,
  created_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP,
  updated_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP ON UPDATE CURRENT_TIMESTAMP,
  CONSTRAINT fk_questions_level FOREIGN KEY (level_id) REFERENCES levels(id),
  CONSTRAINT fk_questions_category FOREIGN KEY (category_id) REFERENCES question_categories(id),
  CONSTRAINT fk_questions_creator FOREIGN KEY (created_by) REFERENCES users(id) ON DELETE SET NULL
);
CREATE TABLE IF NOT EXISTS question_translations (
  id BIGINT PRIMARY KEY AUTO_INCREMENT,

```

```

question_id BIGINT NOT NULL,
language_code VARCHAR(20) NOT NULL,
title VARCHAR(500) NOT NULL,
content TEXT,
analysis TEXT,
UNIQUE KEY uk_question_lang (question_id, language_code),
CONSTRAINT fk_question_translations_question FOREIGN KEY (question_id) REFERENCES questions(id) ON DELETE CASCADE
);
CREATE TABLE IF NOT EXISTS question_options (
id BIGINT PRIMARY KEY AUTO_INCREMENT,
question_id BIGINT NOT NULL,
option_key VARCHAR(10) NOT NULL,
is_correct TINYINT(1) NOT NULL DEFAULT 0,
sort_order INT NOT NULL DEFAULT 0,
UNIQUE KEY uk_question_option_key (question_id, option_key),
CONSTRAINT fk_options_question FOREIGN KEY (question_id) REFERENCES questions(id) ON DELETE CASCADE
);
CREATE TABLE IF NOT EXISTS question_option_translations (
id BIGINT PRIMARY KEY AUTO_INCREMENT,
option_id BIGINT NOT NULL,
language_code VARCHAR(20) NOT NULL,
content VARCHAR(500) NOT NULL,
UNIQUE KEY uk_option_lang (option_id, language_code),
CONSTRAINT fk_option_translations_option FOREIGN KEY (option_id) REFERENCES question_options(id) ON DELETE CASCADE
);
CREATE TABLE IF NOT EXISTS papers (
id BIGINT PRIMARY KEY AUTO_INCREMENT,
paper_type ENUM('practice','exam','daily') NOT NULL DEFAULT 'practice',
level_id BIGINT,
total_score DECIMAL(8,2) NOT NULL DEFAULT 0,
duration_minutes INT NOT NULL DEFAULT 0,
status ENUM('published','draft','disabled') NOT NULL DEFAULT 'published',
created_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP,
updated_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP ON UPDATE CURRENT_TIMESTAMP,
CONSTRAINT fk_papers_level FOREIGN KEY (level_id) REFERENCES levels(id) ON DELETE SET NULL
);
CREATE TABLE IF NOT EXISTS paper_translations (
id BIGINT PRIMARY KEY AUTO_INCREMENT,
paper_id BIGINT NOT NULL,
language_code VARCHAR(20) NOT NULL,
title VARCHAR(200) NOT NULL,
description VARCHAR(500),
UNIQUE KEY uk_paper_lang (paper_id, language_code),
CONSTRAINT fk_paper_translations_paper FOREIGN KEY (paper_id) REFERENCES papers(id) ON DELETE CASCADE
);
CREATE TABLE IF NOT EXISTS paper_questions (
id BIGINT PRIMARY KEY AUTO_INCREMENT,
paper_id BIGINT NOT NULL,
question_id BIGINT NOT NULL,
sort_order INT NOT NULL DEFAULT 0,
score DECIMAL(5,2) NOT NULL DEFAULT 1.00,
UNIQUE KEY uk_paper_question (paper_id, question_id),
CONSTRAINT fk_paper_questions_paper FOREIGN KEY (paper_id) REFERENCES papers(id) ON DELETE CASCADE,

```

```

CONSTRAINT fk_paper_questions_question FOREIGN KEY (question_id) REFERENCES questions(id) ON
DELETE CASCADE
);
CREATE TABLE IF NOT EXISTS study_records (
  id BIGINT PRIMARY KEY AUTO_INCREMENT,
  user_id BIGINT NOT NULL,
  paper_id BIGINT,
  total_questions INT NOT NULL DEFAULT 0,
  correct_count INT NOT NULL DEFAULT 0,
  wrong_count INT NOT NULL DEFAULT 0,
  total_score DECIMAL(8,2) NOT NULL DEFAULT 0,
  duration_seconds INT NOT NULL DEFAULT 0,
  started_at DATETIME,
  submitted_at DATETIME NOT NULL DEFAULT CURRENT_TIMESTAMP,
  CONSTRAINT fk_study_records_user FOREIGN KEY (user_id) REFERENCES users(id) ON DELETE CASCA
DE,
  CONSTRAINT fk_study_records_paper FOREIGN KEY (paper_id) REFERENCES papers(id) ON DELETE SE
T NULL
);
CREATE TABLE IF NOT EXISTS user_answers (
  id BIGINT PRIMARY KEY AUTO_INCREMENT,
  user_id BIGINT NOT NULL,
  question_id BIGINT NOT NULL,
  paper_id BIGINT,
  study_record_id BIGINT,
  selected_option_ids VARCHAR(255),
  answer_text TEXT,
  is_correct TINYINT(1) NOT NULL DEFAULT 0,
  score DECIMAL(5,2) NOT NULL DEFAULT 0,
  answered_at DATETIME NOT NULL DEFAULT CURRENT_TIMESTAMP,
  CONSTRAINT fk_answers_user FOREIGN KEY (user_id) REFERENCES users(id) ON DELETE CASCADE,
  CONSTRAINT fk_answers_question FOREIGN KEY (question_id) REFERENCES questions(id) ON DELETE
CASCADE,
  CONSTRAINT fk_answers_paper FOREIGN KEY (paper_id) REFERENCES papers(id) ON DELETE SET NUL
L,
  CONSTRAINT fk_answers_record FOREIGN KEY (study_record_id) REFERENCES study_records(id) ON D
ELETE SET NULL
);
CREATE TABLE IF NOT EXISTS wrong_questions (
  id BIGINT PRIMARY KEY AUTO_INCREMENT,
  user_id BIGINT NOT NULL,
  question_id BIGINT NOT NULL,
  wrong_count INT NOT NULL DEFAULT 1,
  resolved TINYINT(1) NOT NULL DEFAULT 0,
  last_wrong_at DATETIME NOT NULL DEFAULT CURRENT_TIMESTAMP,
  UNIQUE KEY uk_wrong_user_question (user_id, question_id),
  CONSTRAINT fk_wrong_user FOREIGN KEY (user_id) REFERENCES users(id) ON DELETE CASCADE,
  CONSTRAINT fk_wrong_question FOREIGN KEY (question_id) REFERENCES questions(id) ON DELETE C
ASCADE
);
CREATE TABLE IF NOT EXISTS favorite_questions (
  id BIGINT PRIMARY KEY AUTO_INCREMENT,
  user_id BIGINT NOT NULL,
  question_id BIGINT NOT NULL,
  created_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP,
  UNIQUE KEY uk_favorite_user_question (user_id, question_id),
  CONSTRAINT fk_favorite_user FOREIGN KEY (user_id) REFERENCES users(id) ON DELETE CASCADE,
  CONSTRAINT fk_favorite_question FOREIGN KEY (question_id) REFERENCES questions(id) ON DELETE

```



```

CASCADE
);
CREATE TABLE IF NOT EXISTS i18n_messages (
  id BIGINT PRIMARY KEY AUTO_INCREMENT,
  module VARCHAR(80) NOT NULL,
  message_key VARCHAR(120) NOT NULL,
  language_code VARCHAR(20) NOT NULL,
  message_value VARCHAR(1000) NOT NULL,
  UNIQUE KEY uk_i18n_message (module, message_key, language_code)
);

```

文件：admin/sql/seed.sql

文件职责：写入等级、分类、试卷、题目、选项和多语言演示题库。

所属模块：数据库脚本模块

```

USE school_chinese_exam_practice;
INSERT INTO levels (code, sort_order, status) VALUES
('HSK1', 1, 'active'),
('HSK2', 2, 'active'),
('CAMPUS', 3, 'active')
ON DUPLICATE KEY UPDATE sort_order=VALUES(sort_order), status=VALUES(status);
INSERT INTO level_translations (level_id, language_code, name, description)
SELECT l.id, v.language_code, v.name, v.description
FROM levels l
JOIN (
  SELECT 'HSK1' code, 'zh-CN' language_code, 'HSK 1 入门' name, '适合零基础和初级学习者' description
UNION ALL
  SELECT 'HSK1', 'en-US', 'HSK 1 Beginner', 'For new and beginner learners' UNION ALL
  SELECT 'HSK1', 'ms-MY', 'HSK 1 Permulaan', 'Untuk pelajar baharu dan tahap asas' UNION ALL
  SELECT 'HSK2', 'zh-CN', 'HSK 2 基础', '掌握常用词汇和基础句型' UNION ALL
  SELECT 'HSK2', 'en-US', 'HSK 2 Elementary', 'Common vocabulary and basic sentence patterns' UNION
ALL
  SELECT 'HSK2', 'ms-MY', 'HSK 2 Asas', 'Kosa kata biasa dan pola ayat asas' UNION ALL
  SELECT 'CAMPUS', 'zh-CN', '校园生活汉语', '面向马来西亚留学生的校园场景练习' UNION ALL
  SELECT 'CAMPUS', 'en-US', 'Campus Chinese', 'Campus scenarios for Malaysian international students'
UNION ALL
  SELECT 'CAMPUS', 'ms-MY', 'Bahasa Cina Kampus', 'Latihan situasi kampus untuk pelajar Malaysia'
) v ON v.code = l.code
ON DUPLICATE KEY UPDATE name=VALUES(name), description=VALUES(description);
INSERT INTO question_categories (code, sort_order, status) VALUES
('pinyin', 1, 'active'),
('vocabulary', 2, 'active'),
('grammar', 3, 'active'),
('reading', 4, 'active')
ON DUPLICATE KEY UPDATE sort_order=VALUES(sort_order), status=VALUES(status);
INSERT INTO question_category_translations (category_id, language_code, name, description)
SELECT c.id, v.language_code, v.name, v.description
FROM question_categories c
JOIN (
  SELECT 'pinyin' code, 'zh-CN' language_code, '拼音' name, '声母、韵母和声调练习' description UNION A
LL
  SELECT 'pinyin', 'en-US', 'Pinyin', 'Initials, finals and tones' UNION ALL
  SELECT 'pinyin', 'ms-MY', 'Pinyin', 'Awalan, akhiran dan nada' UNION ALL
  SELECT 'vocabulary', 'zh-CN', '词汇', '常用汉语词汇' UNION ALL
  SELECT 'vocabulary', 'en-US', 'Vocabulary', 'Common Chinese words' UNION ALL
  SELECT 'vocabulary', 'ms-MY', 'Kosa Kata', 'Perkataan Cina biasa' UNION ALL
  SELECT 'grammar', 'zh-CN', '语法', '基础句型和语序' UNION ALL

```



```

SELECT 'grammar', 'en-US', 'Grammar', 'Basic patterns and word order' UNION ALL
SELECT 'grammar', 'ms-MY', 'Tatabahasa', 'Pola asas dan susunan kata' UNION ALL
SELECT 'reading', 'zh-CN', '阅读', '短文理解练习' UNION ALL
SELECT 'reading', 'en-US', 'Reading', 'Short passage comprehension' UNION ALL
SELECT 'reading', 'ms-MY', 'Bacaan', 'Pemahaman petikan pendek'
) v ON v.code = c.code
ON DUPLICATE KEY UPDATE name=VALUES(name), description=VALUES(description);
INSERT INTO papers (id, paper_type, level_id, total_score, duration_minutes, status)
SELECT 1, 'practice', id, 5, 15, 'published' FROM levels WHERE code='HSK1'
ON DUPLICATE KEY UPDATE total_score=VALUES(total_score), duration_minutes=VALUES(duration_min
utes), status=VALUES(status);
INSERT INTO paper_translations (paper_id, language_code, title, description) VALUES
(1, 'zh-CN', 'HSK1 每日练习', '5 道入门汉语练习题'),
(1, 'en-US', 'HSK1 Daily Practice', 'Five beginner Chinese practice questions'),
(1, 'ms-MY', 'Latihan Harian HSK1', 'Lima soalan latihan Bahasa Cina tahap permulaan')
ON DUPLICATE KEY UPDATE title=VALUES(title), description=VALUES(description);
INSERT INTO questions (id, level_id, category_id, question_type, difficulty, score, status)
SELECT 1, l.id, c.id, 'single_choice', 'easy', 1, 'published' FROM levels l JOIN question_categories c ON c.c
ode='pinyin' WHERE l.code='HSK1'
ON DUPLICATE KEY UPDATE level_id=VALUES(level_id), category_id=VALUES(category_id), status='publi
shed';
INSERT INTO questions (id, level_id, category_id, question_type, difficulty, score, status)
SELECT 2, l.id, c.id, 'single_choice', 'easy', 1, 'published' FROM levels l JOIN question_categories c ON c.c
ode='vocabulary' WHERE l.code='HSK1'
ON DUPLICATE KEY UPDATE level_id=VALUES(level_id), category_id=VALUES(category_id), status='publi
shed';
INSERT INTO questions (id, level_id, category_id, question_type, difficulty, score, status)
SELECT 3, l.id, c.id, 'single_choice', 'easy', 1, 'published' FROM levels l JOIN question_categories c ON c.c
ode='grammar' WHERE l.code='HSK1'
ON DUPLICATE KEY UPDATE level_id=VALUES(level_id), category_id=VALUES(category_id), status='publi
shed';
INSERT INTO questions (id, level_id, category_id, question_type, difficulty, score, status)
SELECT 4, l.id, c.id, 'single_choice', 'normal', 1, 'published' FROM levels l JOIN question_categories c ON
c.code='vocabulary' WHERE l.code='HSK1'
ON DUPLICATE KEY UPDATE level_id=VALUES(level_id), category_id=VALUES(category_id), status='publi
shed';
INSERT INTO questions (id, level_id, category_id, question_type, difficulty, score, status)
SELECT 5, l.id, c.id, 'single_choice', 'normal', 1, 'published' FROM levels l JOIN question_categories c ON
c.code='reading' WHERE l.code='HSK1'
ON DUPLICATE KEY UPDATE level_id=VALUES(level_id), category_id=VALUES(category_id), status='publi
shed';
INSERT INTO question_translations (question_id, language_code, title, content, analysis) VALUES
(1, 'zh-CN', '"你"的拼音是什么?', '请选择正确答案。', '"你"的拼音是 ni，第三声。'),
(1, 'en-US', 'What is the pinyin for "你"?', 'Choose the correct answer.', 'The pinyin for 你 is ni with the thir
d tone. '),
(1, 'ms-MY', 'Apakah pinyin bagi "你"?', 'Pilih jawapan yang betul.', 'Pinyin untuk 你 ialah ni dengan nada
ketiga. '),
(2, 'zh-CN', '"谢谢"是什么意思?', '请选择最合适的英文意思。', '"谢谢"表示感谢。'),
(2, 'en-US', 'What does "谢谢" mean?', 'Choose the best English meaning.', '谢谢 means thank you. '),
(2, 'ms-MY', 'Apakah maksud "谢谢"?', 'Pilih maksud Bahasa Inggeris yang paling sesuai.', '谢谢 bermaksu
d terima kasih. '),
(3, 'zh-CN', '选择正确的句子。', '哪一句的语序正确?', '汉语常用语序是主语 + 谓语 + 宾语。'),
(3, 'en-US', 'Choose the correct sentence.', 'Which sentence has the correct word order?', 'Basic Chinese
word order is subject + verb + object. '),
(3, 'ms-MY', 'Pilih ayat yang betul.', 'Ayat manakah mempunyai susunan kata yang betul?', 'Susunan kata
asas Bahasa Cina ialah subjek + kata kerja + objek. '),
(4, 'zh-CN', '"学校"的意思是?', '请选择正确答案。', '学校是学习的地方。'),
(4, 'en-US', 'What does "学校" mean?', 'Choose the correct answer.', '学校 means school. '),

```

```

(4, 'ms-MY', 'Apakah maksud “学校”?', 'Pilih jawapan yang betul.', '学校 bermaksud sekolah.'),
(5, 'zh-CN', '阅读：我叫阿明。我是马来西亚学生。我学习汉语。阿明来自哪里？', '请选择正确答案。', '短文说“我是马来西亚学生”。'),
(5, 'en-US', 'Reading: My name is Amin. I am a Malaysian student. I study Chinese. Where is Amin from?', 'Choose the correct answer.', 'The passage says he is a Malaysian student.'),
(5, 'ms-MY', 'Bacaan: Nama saya Amin. Saya pelajar Malaysia. Saya belajar Bahasa Cina. Amin berasal dari mana?', 'Pilih jawapan yang betul.', 'Petikan menyatakan dia pelajar Malaysia.'),
ON DUPLICATE KEY UPDATE title=VALUES(title), content=VALUES(content), analysis=VALUES(analysis);
INSERT INTO question_options (id, question_id, option_key, is_correct, sort_order) VALUES
(1, 1, 'A', 1, 1), (2, 1, 'B', 0, 2), (3, 1, 'C', 0, 3), (4, 1, 'D', 0, 4),
(5, 2, 'A', 0, 1), (6, 2, 'B', 1, 2), (7, 2, 'C', 0, 3), (8, 2, 'D', 0, 4),
(9, 3, 'A', 1, 1), (10, 3, 'B', 0, 2), (11, 3, 'C', 0, 3), (12, 3, 'D', 0, 4),
(13, 4, 'A', 0, 1), (14, 4, 'B', 1, 2), (15, 4, 'C', 0, 3), (16, 4, 'D', 0, 4),
(17, 5, 'A', 0, 1), (18, 5, 'B', 1, 2), (19, 5, 'C', 0, 3), (20, 5, 'D', 0, 4)
ON DUPLICATE KEY UPDATE is_correct=VALUES(is_correct), sort_order=VALUES(sort_order);
INSERT INTO question_option_translations (option_id, language_code, content) VALUES
(1, 'zh-CN', 'nǐ'), (1, 'en-US', 'nǐ'), (1, 'ms-MY', 'nǐ'),
(2, 'zh-CN', 'wǒ'), (2, 'en-US', 'wǒ'), (2, 'ms-MY', 'wǒ'),
(3, 'zh-CN', 'tā'), (3, 'en-US', 'tā'), (3, 'ms-MY', 'tā'),
(4, 'zh-CN', 'hǎo'), (4, 'en-US', 'hǎo'), (4, 'ms-MY', 'hǎo'),
(5, 'zh-CN', 'Hello'), (5, 'en-US', 'Hello'), (5, 'ms-MY', 'Hello'),
(6, 'zh-CN', 'Thank you'), (6, 'en-US', 'Thank you'), (6, 'ms-MY', 'Thank you'),
(7, 'zh-CN', 'Goodbye'), (7, 'en-US', 'Goodbye'), (7, 'ms-MY', 'Goodbye'),
(8, 'zh-CN', 'Teacher'), (8, 'en-US', 'Teacher'), (8, 'ms-MY', 'Teacher'),
(9, 'zh-CN', '我学习汉语。'), (9, 'en-US', '我学习汉语。'), (9, 'ms-MY', '我学习汉语。'),
(10, 'zh-CN', '学习我汉语。'), (10, 'en-US', '学习我汉语。'), (10, 'ms-MY', '学习我汉语。'),
(11, 'zh-CN', '汉语我学习。'), (11, 'en-US', '汉语我学习。'), (11, 'ms-MY', '汉语我学习。'),
(12, 'zh-CN', '我汉语学习。'), (12, 'en-US', '我汉语学习。'), (12, 'ms-MY', '我汉语学习。'),
(13, 'zh-CN', 'Hospital'), (13, 'en-US', 'Hospital'), (13, 'ms-MY', 'Hospital'),
(14, 'zh-CN', 'School'), (14, 'en-US', 'School'), (14, 'ms-MY', 'School'),
(15, 'zh-CN', 'Library'), (15, 'en-US', 'Library'), (15, 'ms-MY', 'Library'),
(16, 'zh-CN', 'Restaurant'), (16, 'en-US', 'Restaurant'), (16, 'ms-MY', 'Restaurant'),
(17, 'zh-CN', '中国'), (17, 'en-US', 'China'), (17, 'ms-MY', 'China'),
(18, 'zh-CN', '马来西亚'), (18, 'en-US', 'Malaysia'), (18, 'ms-MY', 'Malaysia'),
(19, 'zh-CN', '日本'), (19, 'en-US', 'Japan'), (19, 'ms-MY', 'Jepun'),
(20, 'zh-CN', '英国'), (20, 'en-US', 'United Kingdom'), (20, 'ms-MY', 'United Kingdom')
ON DUPLICATE KEY UPDATE content=VALUES(content);
INSERT INTO paper_questions (paper_id, question_id, sort_order, score) VALUES
(1, 1, 1, 1), (1, 2, 2, 1), (1, 3, 3, 1), (1, 4, 4, 1), (1, 5, 5, 1)
ON DUPLICATE KEY UPDATE sort_order=VALUES(sort_order), score=VALUES(score);

```

文件：fronter/src/main.js

文件职责：提供系统运行所需的入口、配置或支撑逻辑。

所属模块：前台页面模块

```

import { createApp } from 'vue';
import App from './App.vue';
import router from './router/index.js';
import './assets/style.css';
createApp(App).use(router).mount('#app');

```

文件：fronter/src/App.vue

文件职责：实现前台或管理端页面组件。

所属模块：前台页面模块

```

<template>
  <div class="app-shell">

```

```

<header class="topbar">
  <router-link class="brand" to="/">{{ t('app') }}</router-link>
  <nav class="toolbar">
    <router-link to="/">{{ t('home') }}</router-link>
    <router-link v-if="auth.user" to="/practice">{{ t('practice') }}</router-link>
    <router-link v-if="auth.user" to="/records">{{ t('records') }}</router-link>
    <router-link v-if="auth.user" to="/wrong-book">{{ t('wrongBook') }}</router-link>
    <router-link v-if="auth.user" to="/profile">{{ t('profile') }}</router-link>
    <router-link v-if="auth.user?.role === 'admin'" to="/admin">{{ t('dashboard') }}</router-link>
    <router-link v-if="!auth.user" to="/login">{{ t('login') }}</router-link>
    <button v-if="auth.user" @click="logout">{{ t('logout') }}</button>
    <select :value="state.lang" @change="setLang($event.target.value)">
      <option value="zh-CN">中文</option>
      <option value="en-US">English</option>
      <option value="ms-MY">Bahasa Melayu</option>
    </select>
  </nav>
</header>
<main class="content">
  <router-view />
</main>
</div>
</template>
<script setup>
import { useRouter } from 'vue-router';
import { authStore as auth } from './stores/auth.js';
import { state, t, setLang } from './i18n/index.js';
const router = useRouter();
function logout() {
  auth.logout();
  router.push('/login');
}
</script>

```

文件：fronter/src/router/index.js

文件职责：定义前台页面路由和登录、管理员访问守卫。

所属模块：前台页面模块

```

import { createRouter, createWebHistory } from 'vue-router';
import { authStore } from './stores/auth.js';
import Login from './views/Login.vue';
import Register from './views/Register.vue';
import Home from './views/Home.vue';
import PracticeList from './views/PracticeList.vue';
import PracticeDetail from './views/PracticeDetail.vue';
import Records from './views/Records.vue';
import WrongBook from './views/WrongBook.vue';
import Profile from './views/Profile.vue';
import Dashboard from './views/Dashboard.vue';
import AdminTable from './views/AdminTable.vue';
const routes = [
  { path: '/', component: Home },
  { path: '/login', component: Login },
  { path: '/register', component: Register },
  { path: '/practice', component: PracticeList, meta: { auth: true } },
  { path: '/practice/:id', component: PracticeDetail, meta: { auth: true } },
  { path: '/records', component: Records, meta: { auth: true } },

```

```

{ path: '/wrong-book', component: WrongBook, meta: { auth: true } },
{ path: '/profile', component: Profile, meta: { auth: true } },
{ path: '/admin', component: Dashboard, meta: { auth: true, admin: true } },
{ path: '/admin/users', component: AdminTable, props: { type: 'users' }, meta: { auth: true, admin: true } },
{ path: '/admin/questions', component: AdminTable, props: { type: 'questions' }, meta: { auth: true, admin: true } },
{ path: '/admin/papers', component: AdminTable, props: { type: 'papers' }, meta: { auth: true, admin: true } },
{ path: '/admin/records', component: AdminTable, props: { type: 'records' }, meta: { auth: true, admin: true } },
];
const router = createRouter({ history: createWebHistory(), routes });
router.beforeEach((to) => {
  if (to.meta.auth && !authStore.isAuthenticated) return '/login';
  if (to.meta.admin && authStore.user?.role !== 'admin') return '/';
  return true;
});
export default router;

```

文件：fronter/src/api/client.js

文件职责：封装前台 HTTP JSON 请求和令牌请求头。

所属模块：前台页面模块

```

const API_BASE = import.meta.env.VITE_API_BASE || 'http://***/api';
export function token() {
  return localStorage.getItem('token') || '';
}
export async function request(path, options = {}) {
  const headers = { 'Content-Type': 'application/json', ...(options.headers || {}) };
  if (token()) headers.Authorization = `Bearer ${token()}`;
  const response = await fetch(`${API_BASE}${path}`, {
    ...options,
    headers,
    body: options.body ? JSON.stringify(options.body) : undefined
  });
  const payload = await response.json().catch(() => ({ message: 'Network error' }));
  if (!response.ok || payload.code >= 400) throw new Error(payload.message || 'Request failed');
  return payload.data;
}

```

文件：fronter/src/stores/auth.js

文件职责：提供系统运行所需的入口、配置或支撑逻辑。

所属模块：前台页面模块

```

import { reactive } from 'vue';
import { request } from '../api/client.js';
export const authStore = reactive({
  user: JSON.parse(localStorage.getItem('user') || 'null'),
  get isAuthenticated() {
    return Boolean(localStorage.getItem('token'));
  },
  async login(form) {
    const data = await request('/auth/login', { method: 'POST', body: form });
    localStorage.setItem('token', data.token);
    localStorage.setItem('user', JSON.stringify(data.user));
    this.user = data.user;
  }
});

```

```
},  
logout() {  
  localStorage.removeItem('token');  
  localStorage.removeItem('user');  
  this.user = null;  
}  
});
```

文件：fronter/src/i18n/index.js

文件职责：维护中文、英文、马来语界面文案和语言切换状态。

所属模块：前台页面模块

```
import { reactive } from 'vue';  
export const state = reactive({  
  lang: localStorage.getItem('lang') || 'zh-CN'  
});  
const messages = {  
  'zh-CN': {  
    app: '马来西亚留学生汉语练习平台',  
    login: '登录',  
    register: '注册',  
    logout: '退出',  
    home: '首页',  
    practice: '练习',  
    records: '成绩',  
    wrongBook: '错题本',  
    profile: '个人中心',  
    dashboard: '管理台',  
    users: '学生管理',  
    questions: '题库',  
    papers: '练习/试卷',  
    adminRecords: '成绩记录',  
    username: '用户名',  
    password: '密码',  
    name: '姓名',  
    email: '邮箱',  
    phone: '电话',  
    studentNo: '学号',  
    nationality: '国籍',  
    language: '语言',  
    start: '开始练习',  
    submit: '提交',  
    next: '下一题',  
    result: '练习结果',  
    correct: '正确',  
    wrong: '错误',  
    score: '得分',  
    questionCount: '题数',  
    duration: '时长',  
    level: '等级',  
    category: '分类',  
    difficulty: '难度',  
    status: '状态',  
    role: '角色',  
    title: '标题',  
    createdAt: '创建时间',  
    submittedAt: '提交时间',
```

```
empty: '暂无数据',
chooseAnswer: '请选择答案',
analysis: '解析',
totalStudents: '学生数',
totalQuestions: '题目数',
totalPapers: '练习数',
totalRecords: '答题记录',
avgScore: '平均分'
},
'en-US': {
  app: 'Chinese Practice Platform for Malaysian Students',
  login: 'Login',
  register: 'Register',
  logout: 'Logout',
  home: 'Home',
  practice: 'Practice',
  records: 'Scores',
  wrongBook: 'Wrong Book',
  profile: 'Profile',
  dashboard: 'Admin',
  users: 'Students',
  questions: 'Question Bank',
  papers: 'Practices',
  adminRecords: 'Score Records',
  username: 'Username',
  password: 'Password',
  name: 'Name',
  email: 'Email',
  phone: 'Phone',
  studentNo: 'Student No.',
  nationality: 'Nationality',
  language: 'Language',
  start: 'Start',
  submit: 'Submit',
  next: 'Next',
  result: 'Result',
  correct: 'Correct',
  wrong: 'Wrong',
  score: 'Score',
  questionCount: 'Questions',
  duration: 'Duration',
  level: 'Level',
  category: 'Category',
  difficulty: 'Difficulty',
  status: 'Status',
  role: 'Role',
  title: 'Title',
  createdAt: 'Created',
  submittedAt: 'Submitted',
  empty: 'No data',
  chooseAnswer: 'Please choose an answer',
  analysis: 'Analysis',
  totalStudents: 'Students',
  totalQuestions: 'Questions',
  totalPapers: 'Practices',
  totalRecords: 'Records',
  avgScore: 'Avg Score'
},
```



```

'ms-MY': {
  app: 'Platform Latihan Bahasa Cina untuk Pelajar Malaysia',
  login: 'Log Masuk',
  register: 'Daftar',
  logout: 'Log Keluar',
  home: 'Laman Utama',
  practice: 'Latihan',
  records: 'Markah',
  wrongBook: 'Buku Salah',
  profile: 'Profil',
  dashboard: 'Admin',
  users: 'Pelajar',
  questions: 'Bank Soalan',
  papers: 'Latihan',
  adminRecords: 'Rekod Markah',
  username: 'Nama Pengguna',
  password: 'Kata Laluan',
  name: 'Nama',
  email: 'E-mel',
  phone: 'Telefon',
  studentNo: 'No. Pelajar',
  nationality: 'Kewarganegaraan',
  language: 'Bahasa',
  start: 'Mula',
  submit: 'Hantar',
  next: 'Seterusnya',
  result: 'Keputusan',
  correct: 'Betul',
  wrong: 'Salah',
  score: 'Markah',
  questionCount: 'Soalan',
  duration: 'Tempoh',
  level: 'Tahap',
  category: 'Kategori',
  difficulty: 'Kesukaran',
  status: 'Status',
  role: 'Peranan',
  title: 'Tajuk',
  createdAt: 'Dicipta',
  submittedAt: 'Dihantar',
  empty: 'Tiada data',
  chooseAnswer: 'Sila pilih jawapan',
  analysis: 'Analisis',
  totalStudents: 'Pelajar',
  totalQuestions: 'Soalan',
  totalPapers: 'Latihan',
  totalRecords: 'Rekod',
  avgScore: 'Purata'
}
};
export function t(key) {
  return messages[state.lang]?.[key] || key;
}
export function setLang(lang) {
  state.lang = lang;
  localStorage.setItem('lang', lang);
}

```


文件：fronter/src/views/Home.vue

文件职责：实现前台或管理端页面组件。

所属模块：前台页面模块

```
<template>
  <section class="hero">
    <div>
      <h1>{{ t('app') }}</h1>
      <p class="muted">HSK, campus Chinese, trilingual question bank and practice records.</p>
    </div>
    <div class="grid">
      <router-link class="card" to="/practice">
        <h3>{{ t('practice') }}</h3>
        <p class="muted">HSK1 / HSK2 / Campus Chinese</p>
      </router-link>
      <router-link class="card" to="/wrong-book">
        <h3>{{ t('wrongBook') }}</h3>
        <p class="muted">Review mistakes and explanations</p>
      </router-link>
      <router-link class="card" to="/records">
        <h3>{{ t('records') }}</h3>
        <p class="muted">Track practice scores</p>
      </router-link>
      <router-link v-if="auth.user?.role === 'admin'" class="card" to="/admin">
        <h3>{{ t('dashboard') }}</h3>
        <p class="muted">Question bank and student records</p>
      </router-link>
    </div>
  </section>
</template>
<script setup>
import { t } from './i18n/index.js';
import { authStore as auth } from './stores/auth.js';
</script>
```

文件：fronter/src/views/Login.vue

文件职责：实现前台或管理端页面组件。

所属模块：前台页面模块

```
<template>
  <section>
    <h1>{{ t('login') }}</h1>
    <form class="form" @submit.prevent="submit">
      <input v-model="form.username" :placeholder="t('username')" required />
      <input v-model="form.password" :placeholder="t('password')" type="password" required />
      <button class="btn">{{ t('login') }}</button>
      <router-link to="/register">{{ t('register') }}</router-link>
      <p class="muted">{{ message }}</p>
    </form>
  </section>
</template>
<script setup>
import { reactive, ref } from 'vue';
import { useRouter } from 'vue-router';
import { authStore } from './stores/auth.js';
import { t } from './i18n/index.js';
const router = useRouter();
```

```

const message = ref('');
const form = reactive({ username: 'student', password: '***' });
async function submit() {
  try {
    await authStore.login(form);
    router.push('/');
  } catch (e) {
    message.value = e.message;
  }
}
</script>

```

文件：fronter/src/views/Register.vue

文件职责：实现前台或管理端页面组件。

所属模块：前台页面模块

```

<template>
  <section>
    <h1>{{ t('register') }}</h1>
    <form class="form" @submit.prevent="submit">
      <input v-model="form.username" :placeholder="t('username')" required />
      <input v-model="form.password" :placeholder="t('password')" type="password" required />
      <input v-model="form.name" :placeholder="t('name')" />
      <input v-model="form.email" :placeholder="t('email')" />
      <input v-model="form.phone" :placeholder="t('phone')" />
      <input v-model="form.student_no" :placeholder="t('studentNo')" />
      <input v-model="form.nationality" :placeholder="t('nationality')" />
      <button class="btn">{{ t('register') }}</button>
      <p class="muted">{{ message }}</p>
    </form>
  </section>
</template>
<script setup>
import { reactive, ref } from 'vue';
import { request } from '../api/client.js';
import { t, state } from '../i18n/index.js';
const message = ref('');
const form = reactive({ username: '', password: '', name: '', email: '', phone: '', student_no: '', nationality: '
Malaysia', language: state.lang });
async function submit() {
  try {
    await request('/auth/register', { method: 'POST', body: form });
    message.value = 'registered';
  } catch (e) {
    message.value = e.message;
  }
}
</script>

```

文件：fronter/src/views/PracticeList.vue

文件职责：实现前台或管理端页面组件。

所属模块：前台页面模块

```

<template>
  <section>
    <h1>{{ t('practice') }}</h1>
    <div class="grid">

```

```

<router-link v-for="paper in papers" :key="paper.id" class="card" :to="/"`/practice/${paper.id}`">
  <h3>{{ paper.title }}</h3>
  <p class="muted">{{ paper.description }}</p>
  <div class="row">
    <span class="pill">{{ paper.level_name }}</span>
    <span class="pill">{{ t('questionCount') }}: {{ paper.question_count }}</span>
    <span class="pill">{{ t('score') }}: {{ paper.total_score }}</span>
  </div>
</router-link>
</div>
<p v-if="!papers.length" class="muted">{{ t('empty') }}</p>
</section>
</template>
<script setup>
import { onMounted, ref, watch } from 'vue';
import { request } from '../api/client.js';
import { state, t } from '../i18n/index.js';
const papers = ref([]);
async function load() {
  papers.value = await request(`/learning/papers?lang=${state.lang}`);
}
onMounted(load);
watch(() => state.lang, load);
</script>

```

文件：fronter/src/views/PracticeDetail.vue

文件职责：实现前台或管理端页面组件。

所属模块：前台页面模块

```

<template>
<section v-if="paper">
  <div class="row">
    <h1>{{ paper.title }}</h1>
    <span class="pill">{{ index + 1 }} / {{ paper.questions.length }}</span>
  </div>
  <div v-if="!result" class="split">
    <div class="card">
      <p class="muted">{{ current.category_name }} · {{ current.difficulty }}</p>
      <h3>{{ current.title }}</h3>
      <p>{{ current.content }}</p>
      <button
        v-for="option in current.options"
        :key="option.id"
        class="option"
        :class="{ active: selectedIds.includes(option.id) }"
        @click="select(option.id)"
      >
        {{ option.option_key }}. {{ option.content }}
      </button>
    <div class="row">
      <button class="btn ghost" :disabled="index === 0" @click="index -= 1"><<</button>
      <button v-if="index < paper.questions.length - 1" class="btn" @click="index += 1">{{ t('next') }}</bu
    </div>
      <button v-else class="btn" @click="submit">{{ t('submit') }}</button>
    </div>
    <p class="muted">{{ message }}</p>
  </div>

```

```

<aside class="card">
  <h4>{{ t('questionCount') }}</h4>
  <div class="row">
    <button v-for="(q, i) in paper.questions" :key="q.id" class="btn ghost" @click="index = i">
      {{ i + 1 }}
    </button>
  </div>
</aside>
</div>
<div v-else class="card">
  <h2>{{ t('result') }}</h2>
  <div class="grid">
    <div><strong>{{ result.correct_count }}</strong><p>{{ t('correct') }}</p></div>
    <div><strong>{{ result.wrong_count }}</strong><p>{{ t('wrong') }}</p></div>
    <div><strong>{{ result.total_score }}</strong><p>{{ t('score') }}</p></div>
  </div>
  <div v-for="question in paper.questions" :key="question.id" class="card">
    <h4>{{ question.title }}</h4>
    <p class="muted">{{ question.analysis }}</p>
  </div>
</div>
</section>
</template>
<script setup>
import { computed, onMounted, reactive, ref, watch } from 'vue';
import { useRoute } from 'vue-router';
import { request } from '../api/client.js';
import { state, t } from '../i18n/index.js';
const route = useRoute();
const paper = ref(null);
const index = ref(0);
const result = ref(null);
const message = ref('');
const answers = reactive({});
const startedAt = Date.now();
const current = computed(() => paper.value?.questions[index.value] || {});
const selectedIds = computed(() => answers[current.value.id] || []);
async function load() {
  paper.value = await request(`/learning/papers/${route.params.id}?lang=${state.lang}`);
  index.value = 0;
  result.value = null;
}
function select(optionId) {
  answers[current.value.id] = [optionId];
  message.value = '';
}
async function submit() {
  const payload = paper.value.questions.map((question) => ({ question_id: question.id, selected_option_ids: answers[question.id] || [] }));
  if (payload.some((item) => item.selected_option_ids.length === 0)) {
    message.value = t('chooseAnswer');
    return;
  }
  result.value = await request(`/learning/papers/${paper.value.id}/submit`, {
    method: 'POST',
    body: { answers: payload, duration_seconds: Math.round((Date.now() - startedAt) / 1000), language: state.lang }
  });
}

```

```

}
onMounted(load);
watch(() => state.lang, load);
</script>

```

文件：fronter/src/views/Records.vue

文件职责：实现前台或管理端页面组件。

所属模块：前台页面模块

```

<template>
  <section>
    <h1>{{ t('records') }}</h1>
    <div class="card" style="overflow:auto">
      <table>
        <thead>
          <tr>
            <th>{{ t('title') }}</th>
            <th>{{ t('questionCount') }}</th>
            <th>{{ t('correct') }}</th>
            <th>{{ t('wrong') }}</th>
            <th>{{ t('score') }}</th>
            <th>{{ t('submittedAt') }}</th>
          </tr>
        </thead>
        <tbody>
          <tr v-for="row in rows" :key="row.id">
            <td>{{ row.paper_title }}</td>
            <td>{{ row.total_questions }}</td>
            <td>{{ row.correct_count }}</td>
            <td>{{ row.wrong_count }}</td>
            <td>{{ row.total_score }}</td>
            <td>{{ row.submitted_at }}</td>
          </tr>
        </tbody>
      </table>
      <p v-if="!rows.length" class="muted">{{ t('empty') }}</p>
    </div>
  </section>
</template>
<script setup>
import { onMounted, ref, watch } from 'vue';
import { request } from '../api/client.js';
import { state, t } from '../i18n/index.js';
const rows = ref([]);
async function load() {
  rows.value = await request(`/learning/records?lang=${state.lang}`);
}
onMounted(load);
watch(() => state.lang, load);
</script>

```

文件：fronter/src/views/WrongBook.vue

文件职责：实现前台或管理端页面组件。

所属模块：前台页面模块

```

<template>
  <section>

```

```

<h1>{{ t('wrongBook') }}</h1>
<div class="grid">
  <article v-for="row in rows" :key="row.id" class="card">
    <div class="row">
      <span class="pill">{{ row.category_name }}</span>
      <span class="pill">{{ t('wrong') }}: {{ row.wrong_count }}</span>
    </div>
    <h3>{{ row.title }}</h3>
    <p class="muted">{{ t('analysis') }}: {{ row.analysis }}</p>
  </article>
</div>
<p v-if="!rows.length" class="muted">{{ t('empty') }}</p>
</section>
</template>
<script setup>
import { onMounted, ref, watch } from 'vue';
import { request } from '../api/client.js';
import { state, t } from '../i18n/index.js';
const rows = ref([]);
async function load() {
  rows.value = await request(`/learning/wrong-questions?lang=${state.lang}`);
}
onMounted(load);
watch(() => state.lang, load);
</script>

```

文件：fronter/src/views/Profile.vue

文件职责：实现前台或管理端页面组件。

所属模块：前台页面模块

```

<template>
<section>
  <h1>{{ t('profile') }}</h1>
  <form class="form" @submit.prevent="save">
    <input v-model="form.name" :placeholder="t('name')" />
    <input v-model="form.email" :placeholder="t('email')" />
    <input v-model="form.phone" :placeholder="t('phone')" />
    <input v-model="form.nationality" :placeholder="t('nationality')" />
    <select v-model="form.language">
      <option value="zh-CN">中文</option>
      <option value="en-US">English</option>
      <option value="ms-MY">Bahasa Melayu</option>
    </select>
    <button class="btn">{{ t('submit') }}</button>
    <p class="muted">{{ message }}</p>
  </form>
</section>
</template>
<script setup>
import { onMounted, reactive, ref } from 'vue';
import { request } from '../api/client.js';
import { setLang, t } from '../i18n/index.js';
const message = ref("");
const form = reactive({ name: "", email: "", phone: "", nationality: "", language: 'zh-CN' });
onMounted(async () => {
  Object.assign(form, await request('/auth/profile'));
});

```

```

async function save() {
  await request('/auth/profile', { method: 'PUT', body: form });
  setLang(form.language);
  message.value = 'saved';
}
</script>

```

文件：fronter/src/views/Dashboard.vue

文件职责：实现前台或管理端页面组件。

所属模块：前台页面模块

```

<template>
  <section>
    <h1>{{ t('dashboard') }}</h1>
    <div class="grid">
      <div class="card"><h3>{{ stats.students }}</h3><p>{{ t('totalStudents') }}</p></div>
      <div class="card"><h3>{{ stats.questions }}</h3><p>{{ t('totalQuestions') }}</p></div>
      <div class="card"><h3>{{ stats.papers }}</h3><p>{{ t('totalPapers') }}</p></div>
      <div class="card"><h3>{{ stats.avgScore }}</h3><p>{{ t('avgScore') }}</p></div>
    </div>
    <div class="grid" style="margin-top:12px">
      <router-link class="card" to="/admin/users">{{ t('users') }}</router-link>
      <router-link class="card" to="/admin/questions">{{ t('questions') }}</router-link>
      <router-link class="card" to="/admin/papers">{{ t('papers') }}</router-link>
      <router-link class="card" to="/admin/records">{{ t('adminRecords') }}</router-link>
    </div>
  </section>
</template>
<script setup>
import { onMounted, reactive } from 'vue';
import { request } from '../api/client.js';
import { t } from '../i18n/index.js';
const stats = reactive({ students: 0, questions: 0, papers: 0, records: 0, avgScore: 0 });
onMounted(async () => Object.assign(stats, await request('/admin/stats')));
</script>

```

文件：fronter/src/views/AdminTable.vue

文件职责：实现前台或管理端页面组件。

所属模块：前台页面模块

```

<template>
  <section>
    <h1>{{ title }}</h1>
    <div class="card" style="overflow:auto">
      <table>
        <thead>
          <tr>
            <th v-for="header in headers" :key="header">{{ label(header) }}</th>
          </tr>
        </thead>
        <tbody>
          <tr v-for="row in rows" :key="row.id">
            <td v-for="header in headers" :key="header">{{ format(row[header]) }}</td>
          </tr>
        </tbody>
      </table>
      <p v-if="!rows.length" class="muted">{{ t('empty') }}</p>
    </div>
  </section>
</template>

```



```

</div>
</section>
</template>
<script setup>
import { computed, onMounted, ref, watch } from 'vue';
import { request } from '../api/client.js';
import { state, t } from '../i18n/index.js';
const props = defineProps({ type: { type: String, required: true } });
const rows = ref([]);
const title = computed(() => t(props.type === 'records' ? 'adminRecords' : props.type));
const headerMap = {
  users: ['id', 'username', 'name', 'role', 'student_no', 'nationality', 'language', 'status'],
  questions: ['id', 'title', 'level_name', 'category_name', 'question_type', 'difficulty', 'score', 'status'],
  papers: ['id', 'title', 'paper_type', 'question_count', 'total_score', 'duration_minutes', 'status'],
  records: ['id', 'username', 'name', 'paper_title', 'total_questions', 'correct_count', 'wrong_count', 'total_score', 'submitted_at']
};
const labelMap = {
  id: 'ID',
  username: t('username'),
  name: t('name'),
  role: t('role'),
  student_no: t('studentNo'),
  nationality: t('nationality'),
  language: t('language'),
  status: t('status'),
  title: t('title'),
  level_name: t('level'),
  category_name: t('category'),
  question_type: 'Type',
  difficulty: t('difficulty'),
  score: t('score'),
  paper_type: 'Type',
  question_count: t('questionCount'),
  total_score: t('score'),
  duration_minutes: t('duration'),
  paper_title: t('title'),
  total_questions: t('questionCount'),
  correct_count: t('correct'),
  wrong_count: t('wrong'),
  submitted_at: t('submittedAt')
};
const headers = computed(() => headerMap[props.type] || ['id']);
function label(key) {
  return labelMap[key] || key;
}
function format(value) {
  if (value == null) return '';
  if (typeof value === 'string' && value.length > 80) return `${value.slice(0, 80)}...`;
  return value;
}
async function load() {
  rows.value = await request(`/admin/${props.type}?lang=${state.lang}`);
}
onMounted(load);
watch(() => [props.type, state.lang], load);
</script>

```

文件：fronter/src/assets/style.css

文件职责：提供系统运行所需的入口、配置或支撑逻辑。

所属模块：前台页面模块

```
* { box-sizing: border-box; }
body { margin: 0; font-family: Arial, "Microsoft YaHei", sans-serif; background: #f4f6f8; color: #172033; }
a { color: inherit; text-decoration: none; }
button, input, select, textarea { font: inherit; }
.app-shell { max-width: 1080px; min-height: 100vh; margin: 0 auto; background: #fff; }
.topbar { position: sticky; top: 0; z-index: 5; display: flex; gap: 12px; align-items: center; justify-content: space-between; padding: 12px 14px; background: #14304d; color: #fff; }
.brand { font-weight: 700; line-height: 1.3; }
.toolbar { display: flex; gap: 8px; align-items: center; flex-wrap: wrap; }
.toolbar a, .toolbar button, .toolbar select { border: 0; border-radius: 6px; padding: 8px 10px; background: rgba(255,255,255,.12); color: #fff; cursor: pointer; }
.toolbar select option { color: #172033; }
.content { padding: 16px; }
.hero { display: grid; gap: 14px; padding: 20px 0; }
.grid { display: grid; gap: 12px; grid-template-columns: repeat(auto-fit, minmax(220px, 1fr)); }
.card { border: 1px solid #e4e8ef; border-radius: 8px; padding: 14px; background: #fff; box-shadow: 0 1px 2px rgba(0,0,0,.04); }
.card h3, .card h4 { margin-top: 0; }
.row { display: flex; gap: 10px; align-items: center; flex-wrap: wrap; }
.split { display: grid; gap: 16px; grid-template-columns: minmax(0, 1fr) 280px; }
.form { display: grid; gap: 12px; max-width: 480px; }
.form input, .form select, .form textarea { width: 100%; border: 1px solid #ccd4df; border-radius: 6px; padding: 10px; }
.btn { border: 0; border-radius: 6px; padding: 10px 12px; background: #0d6efd; color: #fff; cursor: pointer; }
.btn.secondary { background: #5c667a; }
.btn.ghost { background: #eef3f8; color: #14304d; }
.muted { color: #687386; }
.pill { display: inline-block; border-radius: 999px; padding: 3px 8px; font-size: 12px; background: #e9edf3; color: #40506a; }
.option { display: block; width: 100%; margin: 8px 0; border: 1px solid #d8dee8; border-radius: 8px; padding: 12px; background: #fff; text-align: left; color: #172033; }
.option.active { border-color: #0d6efd; background: #eef5ff; }
.option.correct { border-color: #249653; background: #e7f7ee; }
.option.wrong { border-color: #c0392b; background: #fdecec; }
table { width: 100%; border-collapse: collapse; font-size: 14px; }
th, td { border-bottom: 1px solid #e7ebf0; padding: 10px; text-align: left; vertical-align: top; }
@media (max-width: 760px) {
  .topbar { align-items: flex-start; flex-direction: column; }
  .toolbar a, .toolbar button, .toolbar select { padding: 7px 8px; font-size: 13px; }
  .split { grid-template-columns: 1fr; }
  th, td { padding: 8px 6px; font-size: 12px; }
}
```

文件：admin/package.json

文件职责：提供系统运行所需的入口、配置或支撑逻辑。

所属模块：后台服务模块

```
{
  "name": "school-chinese-exam-practice-admin",
  "version": "1.0.0",
  "type": "module",
  "scripts": {
```

```

"dev": "nodemon src/server.js",
"start": "node src/server.js",
"db:init": "node src/utils/initDb.js",
"seed:users": "node src/utils/seedUsers.js"
},
"dependencies": {
  "bcryptjs": "^2.4.3",
  "cors": "^2.8.5",
  "dotenv": "^16.4.7",
  "express": "^4.21.2",
  "jsonwebtoken": "^9.0.2",
  "mysql2": "^3.11.5"
},
"devDependencies": {
  "nodemon": "^3.1.9"
}
}

```

文件：fronter/package.json

文件职责：提供系统运行所需的入口、配置或支撑逻辑。

所属模块：前台页面模块

```

{
  "name": "school-chinese-exam-practice-fronter",
  "version": "1.0.0",
  "type": "module",
  "scripts": {
    "dev": "vite --host 0.0.0.0",
    "build": "vite build",
    "preview": "vite preview --host 0.0.0.0"
  },
  "dependencies": {
    "@vitejs/plugin-vue": "^5.2.1",
    "vite": "^6.0.3",
    "vue": "^3.5.13",
    "vue-router": "^4.5.0"
  },
  "devDependencies": {}
}

```