

DSP Homework 07

Xu, Minhuan

October 14, 2022

Contents

1	Videos	1
1.1	Image Processing in Mice	1
1.1.1	IAS	1
1.1.2	Interpolation	2
1.2	Starch-Based Diets make us healthy	2
1.3	Our Planet	2
1.4	Further Thoughts	2
2	Pros and Cons of Shannon/Nyquist sampling method	2
2.1	Positive	2
2.2	Negative	3
3	Conclusion	3

Abstract

1 Videos

1.1 Image Processing in Mice

There are a lot of parts which cooperate with each other, but in this video we mainly know about things about image processing unit which is called Image Acquisition System (IAS) and interpolation.

1.1.1 IAS

The IAS contains a infrared LED, a pair of lenses, and the image pixel array.

About the LED, we can't see the infrared ray with our eyes, but many years ago we do see some light came out from the bottom of our mice.

And the pair of lenses, one is to refract the ray in order to let the ray hits the surface in a very small angle, the other is to receive the reflected ray. About the reflected ray, since it is shot on the rough surface in a small angle, so the high part of the surface will block the light which would hit the lower place if the surface was flat. So we can simply consider the higher place will be bright, and the lower place will be rather dim.

The last part is the image pixel array. This can be called a image sensor by itself. It can translate the light and the shade into a black and white picture. This picture won't be stored in the mouse, but be compared with the picture transmitted into the image sensor. So, how do the mouse know the displacement in x and y ?

It turns out that in the mouse there's a DSP chip which keep calculating the cross correlation of previous and present picture shot by the image sensor. If found the cross correlation is not large enough, which means the mouse has made a move, the processor will move the image in $x - y$ plane and calculate the cross correlation again. The processor will keep do that until there's a maximum of the value of cross correlation, then, only the corresponding displacement of the maximum is what the processor cares. The IAS usually takes 17,000 pictures of the surface every second, and this means that the processor will compares the present picture to the previous picture every 59 μs . But the chip in mice will only reports to the computer every 1 μs .

1.1.2 Interpolation

In the level of hardware, some mice have image sensors with 40×40 pixels. So, the raw data from that sensor will be 1,600 digits which range in $0 \sim 4095$ and represent the intensity of light. But we can still use interpolation to get more useful digits. That means apart from real points *see* by the sensor, the chips in the mice will *imagine* more points. The value of those *imagined* points are determined by the real points around.

1.2 Starch-Based Diets make us healthy

The lecturer is a doctor who has been searching for the way of making people healthy for over 40 years. He want to convince us that it is good for human to have starch-based diets in three aspects as below:

1. Throughout human history, bulk of people have had the starch-based diets.
2. People who from the areas in which people have the habit of living on starch have less sickness even though they has moved to meat-eating areas.
3. Children, military, workers, and many other people in the USA are getting overweight and sick.

1.3 Our Planet

This episode of Our Planet is about the creatures in the polar regions.

In Antarctica, krill is eaten by Gentoo Penguins and humpback whales, Gentoo Penguins are eaten by killer whales. However, with warming temperatures and disappearing sea ice, krill which depend on the sea ice algae have been getting less and less.

In island of South Georgia, the camera tells us that how difficult it is for the king penguins to reach the nursery of their from the sea. There are leopard seals who want to eat them, elephant seals who will flatten them and others' chicks who are mixed with their own chicks.

In Arctic, polar bears and seals suffer from the loss of ice. Moreover, the walrus who once live on the ice, will occupy every square centimeters just to lie down on a tiny island. Some of the even climb onto a hill and drop from that place.

For thousands of years, there's been a balance in the advance and retreat of the sea ice, but that is no longer the case. All we can know from these scenes, many are starting to lose the place where they rest, breed, hunting.

1.4 Further Thoughts

Since the mice judge the displacement through the image, so I wonder if I move a mouse so fast that a picture transmitted into the chips is total different from the previous one, it will be lost and make mistake. So I want to calculate how fast can the mouse be lost. But since I cannot make my mouse move so fast, I don't want to implement this experiment.

First, from the video I know that every μs the sensor will take a picture of the surface and report it every $59 \mu s$, so I think the during time here will be $59 \mu s$.

Second, the length of my mouse's lens is about $1 \sim 4$ mm, so the speed of my mouse must beyond:

$$v = \frac{x}{t} = \frac{1 \times 10^{-3}}{6 \times 10^{-5}} \approx 16.6 \text{ m/s}$$

to let my mouse to be lost.

Finally, I referred the data on the official website and found that the official value of the maximum of speed is about 10.2 m/s , and that's close.

2 Pros and Cons of Shannon/Nyquist sampling method

2.1 Positive

Ideal and easy to understand

In Shannon/Nyquist sampling method, we only consider things that are ideal. Like $\delta(t)$, and the ideal LPF. It is mathematically simple and friendly to beginners.

Easy to calculate

Using Fourier series and Fourier transform, we can easily find the distribution of energy on the frequency domain since the δ function has nice special properties.

No Error

Through calculation, we know that if we make f_s and f_c have proper values, a perfectly the same frequency spectrum can be reconstructed. This is good because we don't need to worry about making mistake through communication.

Easy to Reconstruct

Assuming that we have a sampled signal, all we should do is to find the bandwidth, and to let the sampled signal pass a LPF. Then, a perfectly reconstructed signal is complete.

2.2 Negative

Non-existent signal

Though the sampling progress is theoretically easy to carry out, the δ function is not so easy to generate. Mathematically, it has infinite energy in *one* period. According to the law of conservation of energy, we can't make a signal like the $\delta(t)$, see (1).

$$E = \sum_{n=-\infty}^{\infty} T \rightarrow \infty \quad (1)$$

Waste of bandwidth

In practical usage, engineers cannot find a ideal LPF, especially which has infinite differential (has a sharp drop). All we can find is those which have smooth differential, and LPF like these will occupy more bandwidth of channels. Then, because

$$f_c < f_s - W$$

Therefore, the sampling frequency f_s need to be larger which is not good.

3 Conclusion