

Package ‘FIREVAT’

March 26, 2019

Type Package

Title FIREVAT, FInding REliable Variants without ArTifacts

Description FIREVAT is a variant filtering tool for cancer sequencing data, which uses mutational signatures to identify sequencing artifacts and low-quality variants.

Version 0.3.3

Authors Andy Jinseok Lee, Hyunbin Kim

Maintainer Andy Jinseok Lee <jinseok.lee@ncc.re.kr>, Hyunbin Kim <khb7840@ncc.re.kr>

Imports data.table,
stringi,
bedr,
GA,
jsonlite,
yaml,
MutationalPatterns,
deconstructSigs,
lsa,
BSgenome.Hsapiens.UCSC.hg19,
BSgenome.Hsapiens.UCSC.hg38,
ggpubr,
caTools,
ggrepel,
gridExtra,
ggplot2,
rmarkdown,
gtable,
dplyr,
foreach,
doParallel,
IRanges

URL <https://github.com/cgab-ncc/FIREVAT>

License GPL-2

Encoding UTF-8

LazyData true

RoxygenNote 6.1.1

Suggests knitr

VignetteBuilder knitr

R topics documented:

AnnotateVCFObj	4
CheckIfVariantRefinementIsNecessary	4
Chromosome.Names	5
ComputeZScore	6
ComputeZScoreEquiValue	6
DecimalCeiling	7
Default.Obj.Fn	7
DefaultFilterToBinary	8
EnumerateTriNucCounts	8
Euc.Exp.Weighted.Obj.Fn	9
Euc.Exp.Weighted.Seq.Art.Only.Obj.Fn.1	9
Euc.Exp.Weighted.Seq.Art.Only.Obj.Fn.2	10
Euc.Obj.Fn	10
Exp.Weighted.Obj.Fn.1	11
Exp.Weighted.Obj.Fn.2	11
Exp.Weighted.Refined.Seq.Art.Only.Obj.Fn	12
FilterByStrandBiasAnalysis	12
FilterVCF	13
GenerateConfigObj	14
GetCOSMICMutSigs	14
GetCOSMICMutSigsEtiologiesColors	15
GetCOSMICMutSigsNames	15
GetGASuggestedSolutions	15
GetOptimizedSignatures	16
GetParameterLowerUpperVector	17
GetPCAWGMutSigs	18
GetPCAWGMutSigsEtiologiesColors	18
GetPCAWGMutSigsNames	18
InitializeVCF	19
MakeFilter	19
MutaliskParseVCFObj	20
MutPatParseRefMutSigs	20
MutPatParseVCFObj	21
ParameterToBits	21
ParseConfigFile	22
PCAWG.All.Sequencing.Artifact.Signatures	23
PCAWG.Known.Sequencing.Artifact.Signatures	23
PCAWG.Likely.Sequencing.Artifact.Signatures	23
PCAWG.Possible.Sequencing.Artifact.Signatures	24
PCAWG.Target.Mutational.Signatures	24

PerformStrandBiasAnalysis	24
PlotMutaliskResults	25
PlotMutationTypes	26
PlotOptimizationIterations	27
PlotSignaturesContProbs	28
PlotTable	29
PlotTriNucSpectrum	29
PlotVCFStatsBoxPlots	30
PlotVCFStatsHistograms	31
PrepareAnnotationDB	32
PrepareArtifactAnnotationTable	33
PrepareArtifactStrandBiasTable	33
PrepareArtifactualMutsOptimizationIterationsPlot	34
PrepareFilterCutoffsTable	34
PrepareGeneticAlgorithmParametersTable	35
PrepareIdentifiedSignaturesPlot	35
PrepareMLEReconstructedSpectrumsPlot	36
PrepareNucleotideSubstitutionTypesPlot	36
PrepareObservedSpectrumsPlot	37
PrepareOptimizationResultsTable	37
PrepareOptimizedVCFStatisticsPlot	38
PrepareRefinedAnnotationTable	38
PrepareRefinedMutsOptimizationIterationsPlot	39
PrepareRefinedStrandBiasTable	39
PrepareResidualSpectrumsPlot	40
PrepareTrinucleotideSpectrumsTable	40
QueryAnnotatedVCF	41
ReadOptimizationIterationReport	41
ReadVCF	42
ReportFIREVATResults	42
RunFIREVAT	43
RunMutalisk	46
RunMutaliskHelper	47
RunMutPat	48
TriNuc.Mutation.Type.Hex.Colors	49
UpdateFilter	49
WriteFIREVATResultsToTSV	50
WriteVCF	50

AnnotateVCFObj	<i>AnnotateVCFObj</i>
----------------	-----------------------

Description

Annotates a vcf.obj using df.variants.of.interest (from [PrepareAnnotationDB](#))

Usage

```
AnnotateVCFObj(vcf.obj, df.annotation.db, columns.to.include,
               include.all.columns = FALSE)
```

Arguments

- vcf.obj [ReadVCF](#)
- df.annotation.db
 A data.frame from [PrepareAnnotationDB](#). This data.frame must have the columns 'CHROM', 'POS', 'REF', 'ALT'
- columns.to.include
 A character vector of columns to include. Note that existing columns in vcf.obj will not be affected.
- include.all.columns
 A boolean value. If TRUE, then annotates vcf.obj with all columns present in df.variants.of.interest. If FALSE, columns.to.include must be supplied.

Value

An annotated vcf.obj

CheckIfVariantRefinementIsNecessary	<i>CheckIfVariantRefinementIsNecessary</i>
-------------------------------------	--

Description

Checks if variant refinement is necessary by identifying mutational signatures related to sequencing artifact in the vcf.obj (set of original unrefined point mutations).

Usage

```
CheckIfVariantRefinementIsNecessary(vcf.obj, bsg, df.mut.pat.ref.sigs,
                                     target.mut.sigs, sequencing.artifact.mut.sigs,
                                     init.artifact.stop = 0.05, verbose = TRUE)
```

Arguments

vcf.obj	A list from ReadVCF
bsg	BSgenome.Hsapiens.UCSC object
df.mut.pat.ref.sigs	A data.frame from MutPatParseRefMutSigs
target.mut.sigs	A character vector of target mutational signatures from reference mutational signatures.
sequencing.artifact.mut.sigs	A character vector of sequencing artifact mutational signatures from reference mutational signatures.
init.artifact.stop	Numeric value less than 1. If the sum of sequencing artifact weights in vcf.obj is less than or equal to this value then this function returns judgment = FALSE, otherwise returns judgment = TRUE.
verbose	If TRUE, provides process detail. Default value is TRUE.

Value

- A list with the following elements
- judgmentA boolean value
 - seq.art.sigs.weights.sumA numeric value. Sum of sequencing artifact weights.

Chromosome.Names	Constant
------------------	----------

Description

Chromosome names for FIREVAT. Chromosome names should be given in the format of "chr" + chromosome number.

Usage

Chromosome.Names

Format

An object of class character of length 25.

ComputeZScore	<i>ComputeZScore</i>
---------------	----------------------

Description

Returns a z-score of x given a distribution of values

Usage

ComputeZScore(values, x)

Arguments

- values a numeric vector
- x a numeric value

Value

a numeric value corresponding to the z-score of x

ComputeZScoreEquiValue	<i>ComputeZScoreEquiValue</i>
------------------------	-------------------------------

Description

Returns a numeric value that is equivalent to the specified z.score in the distribution of 'values'

Usage

ComputeZScoreEquiValue(z.score, values)

Arguments

- z.score numeric value
- values numeric vector

Value

a numeric value corresponding to the specified z.score in the 'values' distribution

DecimalCeiling	<i>DecimalCeiling</i>
----------------	-----------------------

Description

Returns the ceiling of a decimal value e.g. value = 0.15, decimal = 0.1 returns 0.2

Usage

DecimalCeiling(value, decimal)

Arguments

value	numeric value (decimal)
decimal	numeric value (e.g. 0.1, 0.001)

Value

a numeric value

Default.Obj.Fn	<i>Default.Obj.Fn</i>
----------------	-----------------------

Description

Calculates the default objective value for FIREVAT GA optimization.

Usage

Default.Obj.Fn(C.refined, A.refined, C.artifactual, A.artifactual)

Arguments

C.refined	A numeric value between 0 and 1.
A.refined	A numeric value between 0 and 1.
C.artifactual	A numeric value between 0 and 1.
A.artifactual	A numeric value between 0 and 1.

Value

A numeric value between 0 and 1.

DefaultFilterToBinary *Transform default filtering parameters to a binary vector*

Description

This function transforms default filtering parameter to binary vector which can be used as a suggested solution in GA algorithm.

Usage

```
DefaultFilterToBinary(vcf.filter, params.bit.len)
```

Arguments

`vcf.filter` A list generated in [MakeFilter](#)
`params.bit.len` A list with bit lengths of filtering parameters which is generated from [ParameterToBits](#)

Value

A binary vector

EnumerateTriNucCounts *EnumerateTriNucCounts*

Description

Returns C>A, C>G, C>T, T>A, T>C, T>G counts

Usage

```
EnumerateTriNucCounts(spectrum)
```

Arguments

`spectrum` a numeric vector with 96 numeric values

Details

Please note that this function assumes that 'spectrum' is sorted (i.e. 1:16 → C>A; 17:32 → C>G; 33:48 → C>T; 49:64 → T>A; 65:80 → T>C; 81:96 → T>G)

Value

a numeric vector of length 6 corresponding to the counts of each trinucleotide change (C>A, C>G, C>T, T>A, T>C, T>G)

Euc.Exp.Weighted.Obj.Fn

Euc.Exp.Weighted.Obj.Fn

Description

Calculates the Euclidean-distance of logarithmically weighted objective value for FIREVAT GA optimization.

Usage

Euc.Exp.Weighted.Obj.Fn(C.refined, A.refined, C.artifactual, A.artifactual)

Arguments

C.refined	A numeric value between 0 and 1.
A.refined	A numeric value between 0 and 1.
C.artifactual	A numeric value between 0 and 1.
A.artifactual	A numeric value between 0 and 1.

Value

A numeric value between 0 and 1.

Euc.Exp.Weighted.Seq.Art.Only.Obj.Fn.1

Euc.Exp.Weighted.Seq.Art.Only.Obj.Fn.1

Description

Calculates the Euclidean-distance of logarithmically weighted objective value for FIREVAT GA optimization.

Usage

Euc.Exp.Weighted.Seq.Art.Only.Obj.Fn.1(C.refined, A.refined, C.artifactual, A.artifactual)

Arguments

C.refined	A numeric value between 0 and 1.
A.refined	A numeric value between 0 and 1.
C.artifactual	A numeric value between 0 and 1.
A.artifactual	A numeric value between 0 and 1.

Value

A numeric value between 0 and 1.

<code>Euc.Exp.Weighted.Seq.Art.Only.Obj.Fn.2</code>
<i>Euc.Exp.Weighted.Seq.Art.Only.Obj.Fn.2</i>

Description

Calculates the Euclidean-distance of logarithmically weighted objective value for FIREVAT GA optimization.

Usage

`Euc.Exp.Weighted.Seq.Art.Only.Obj.Fn.2(C.refined, A.refined, C.artifactual, A.artifactual)`

Arguments

- | | |
|----------------------------|----------------------------------|
| <code>C.refined</code> | A numeric value between 0 and 1. |
| <code>A.refined</code> | A numeric value between 0 and 1. |
| <code>C.artifactual</code> | A numeric value between 0 and 1. |
| <code>A.artifactual</code> | A numeric value between 0 and 1. |

Value

A numeric value between 0 and 1.

<code>Euc.Obj.Fn</code>	<i>Euc.Obj.Fn</i>
-------------------------	-------------------

Description

Calculates the Euclidean-distance based objective value for FIREVAT GA optimization.

Usage

`Euc.Obj.Fn(C.refined, A.refined, C.artifactual, A.artifactual)`

Arguments

- | | |
|----------------------------|----------------------------------|
| <code>C.refined</code> | A numeric value between 0 and 1. |
| <code>A.refined</code> | A numeric value between 0 and 1. |
| <code>C.artifactual</code> | A numeric value between 0 and 1. |
| <code>A.artifactual</code> | A numeric value between 0 and 1. |

Value

A numeric value between 0 and 1.

Exp.Weighted.Obj.Fn.1	<i>Exp.Weighted.Obj.Fn.1</i>
-----------------------	------------------------------

Description

Calculates the exponentially weighted objective value for FIREVAT GA optimization.

Usage

Exp.Weighted.Obj.Fn.1(C.refined, A.refined, C.artifactual, A.artifactual)

Arguments

- | | |
|---------------|----------------------------------|
| C.refined | A numeric value between 0 and 1. |
| A.refined | A numeric value between 0 and 1. |
| C.artifactual | A numeric value between 0 and 1. |
| A.artifactual | A numeric value between 0 and 1. |

Value

A numeric value between 0 and 1.

Exp.Weighted.Obj.Fn.2	<i>Exp.Weighted.Obj.Fn.2</i>
-----------------------	------------------------------

Description

Calculates the exponentially weighted objective value for FIREVAT GA optimization.

Usage

Exp.Weighted.Obj.Fn.2(C.refined, A.refined, C.artifactual, A.artifactual)

Arguments

- | | |
|---------------|----------------------------------|
| C.refined | A numeric value between 0 and 1. |
| A.refined | A numeric value between 0 and 1. |
| C.artifactual | A numeric value between 0 and 1. |
| A.artifactual | A numeric value between 0 and 1. |

Value

A numeric value between 0 and 1.

Exp.Weighted.Refined.Seq.Art.Only.Obj.Fn
Exp.Weighted.Refined.Seq.Art.Only.Obj.Fn

Description

Calculates the Euclidean-distance of logarithmically weighted objective value for FIREVAT GA optimization.

Usage

Exp.Weighted.Refined.Seq.Art.Only.Obj.Fn(C.refined, A.refined,
 C.artifactual, A.artifactual)

Arguments

C.refined	A numeric value between 0 and 1.
A.refined	A numeric value between 0 and 1.
C.artifactual	A numeric value between 0 and 1.
A.artifactual	A numeric value between 0 and 1.

Value

A numeric value between 0 and 1.

FilterByStrandBiasAnalysis
FilterByStrandBiasAnalysis

Description

Filters refined.vcf.obj by strand bias analysis and moves these filtered variants to artifactual.vcf.obj

Usage

FilterByStrandBiasAnalysis(refined.vcf.obj, artifactual.vcf.obj,
 perform.fdr.correction, filter.by.strand.bias.analysis.cutoff)

Arguments

refined.vcf.obj	
artifactual.vcf.obj	A list of vcf data
perform.fdr.correction	A list of vcf data
filter.by.strand.bias.analysis.cutoff	A boolean value.
	A numeric value.

Value

A list with filtering parameter values

- refined.vcf.obj updated refined.vcf.obj
- artifactual.vcf.obj updated artifactual.vcf.obj

FilterVCF	<i>FilterVCF</i>
-----------	------------------

Description

Filter vcf based on the filter Filtering parameters are saved in config.obj Split vcf.obj into vcf.obj.filtered & vcf.obj.artifact based on vcf.filter

Usage

```
FilterVCF(vcf.obj, vcf.filter, config.obj, include.array = NULL,
          force.include = FALSE, verbose = TRUE)
```

Arguments

- | | |
|---------------|---|
| vcf.obj | A list from ReadVCF |
| vcf.filter | A list from MakeMuTect2Filter |
| config.obj | A list from ParseConfigFile |
| include.array | A boolean vector |
| force.include | A boolean value. If TRUE, then uses 'include.array' |
| verbose | If true, provides process detail |

Value

A list with the following elements

- 1) Mutations which passed filteringvcf.obj.filtered = vcf.obj (list with data, header, genome)
- 2) Mutations which did not pass filteringvcf.obj.artifact = vcf.obj (list with data, header, genome)

GenerateConfigObj

Generate config.obj by checking vcf header

Description

This function generate config.obj by checking vcf header. Users should fill in the information needed in console. In current version, only Integers & Float values can be used in config.obj for running FIREVAT.

Usage

```
GenerateConfigObj(vcf.obj, save.config = TRUE,  
  config.path = "../temp/FIREVAT_configure.json")
```

Arguments

vcf.obj	A list from ReadVCF
save.config	If true, save config.obj to config.path
config.path	File path to write config.obj (json or yaml)

Value

config.obj

GetCOSMICMutSigs*GetCOSMICMutSigs*

Description

Returns a data.frame of the COSMIC mutational signature reference file from the data directory

Usage

```
GetCOSMICMutSigs()
```

Value

a data.frame of the COSMIC reference mutational signatures

GetCOSMICMutSigsEtiologiesColors
<i>GetCOSMICMutSigsNames</i>

Description

Returns all COSMIC mutational signature etiologies and colors

Usage

GetCOSMICMutSigsEtiologiesColors()

Value

data.frame with following columns: signature, group and color.

GetCOSMICMutSigsNames	<i>GetCOSMICMutSigsNames</i>
-----------------------	------------------------------

Description

Returns all COSMIC mutational signature names

Usage

GetCOSMICMutSigsNames()

Value

a character vector

GetGASuggestedSolutions
<i>GetGASuggestedSolutions</i>

Description

Computes suggested solutions

Usage

GetGASuggestedSolutions(vcf.obj, bsg, config.obj, lower.upper.list,
df.mut.pat.ref.sigs, target.mut.sigs, sequencing.artifact.mut.sigs,
objective.fn, original.muts.seq.art.weights.sum, verbose = TRUE)

Arguments

<code>vcf.obj</code>	A list from ReadVCF
<code>bsg</code>	BSgenome.Hsapiens.UCSC object
<code>config.obj</code>	A list from ParseConfigFile
<code>lower.upper.list</code>	A list from GetParameterLowerUpperVector
<code>df.mut.pat.ref.sigs</code>	A data.frame from MutPatParseRefMutSigs
<code>target.mut.sigs</code>	A character vector of the target mutational signatures from reference mutational signatures.
<code>sequencing.artifact.mut.sigs</code>	A character vector of the sequencing artifact mutational signatures from reference mutational signatures.
<code>objective.fn</code>	Objective value derivation function.
<code>original.muts.seq.art.weights.sum</code>	A numeric value. 'seq.art.sigs.weights.sum' from CheckIfVariantRefinementIsNecessary
<code>verbose</code>	If TRUE, provides process detail. Default value is TRUE.

Value

A list with the following elements

- `judgment` A boolean value
- `seq.art.sigs.weights` A numeric value. Sum of sequencing artifact weights.

GetOptimizedSignatures

GetOptimizedSignatures

Description

This function fetches the last row from the optimization iteration log and returns the target and artifactual mutational signatures for the type of mutations ('refined' or 'artifactual')

Usage

```
GetOptimizedSignatures(data, mutations.type = "refined",
  signatures = "all")
```

Arguments

<code>data</code>	A list of main data from RunFIREVAT
<code>mutations.type</code>	A string for type of mutations ('refined' or 'artifact')
<code>signatures</code>	A string ('all', 'target', 'artifact')

Value

A data.frame with the columns 'signature' and 'weight'

GetParameterLowerUpperVector
GetParameterLowerUpperVector

Description

Return a lower/upper vector needed to conduct FIREVAT GA real-valued optimization.

Usage

```
GetParameterLowerUpperVector(vcf.obj, config.obj, vcf.filter,  
  multiplier = 100)
```

Arguments

vcf.obj	A list from ReadVCF
config.obj	A list from ParseConfigFile
vcf.filter	A list from MakeMuTect2Filter
multiplier	A multiplier for convert fraction to integer (default = 100)

Details

vcf.obj\$data: if $\max(\text{vcf.obj\$data}[[\text{param}]]) < 1$, then multiply multiplier to the vector

Value

A list with the elements

- lower.vector A numeric vector. Each element is the minimum value of each parameter
- upper.vector A numeric vector. Each element is the maximum value of each parameter
- vcf.obj vcf.obj with updated data

GetPCAWGMutSigs	<i>GetPCAWGMutSigs</i>
-----------------	------------------------

Description

Returns the PCAWG mutational signatures data

Usage

GetPCAWGMutSigs()

Value

a data.frame of the PCAWG mutatioanl signatures

GetPCAWGMutSigsEtiologiesColors	<i>GetPCAWGMutSigsEtiologiesColors</i>
---------------------------------	--

Description

Returns the PCAWG mutational signatures etiologies and colors

Usage

GetPCAWGMutSigsEtiologiesColors()

Value

a data.frame with the columns 'signature', 'group', 'color'

GetPCAWGMutSigsNames	<i>GetPCAWGMutSigsNames</i>
----------------------	-----------------------------

Description

Returns the PCAWG mutational signatures names

Usage

GetPCAWGMutSigsNames()

Value

a character vector of the PCAWG mutational signatures names

InitializeVCF	<i>InitializeVCF</i>
---------------	----------------------

Description

Initialize VCF with FIREVAT config file This functions selects point mutations and appends filter values to vcf.obj\$data

Usage

InitializeVCF(vcf.obj, config.obj, verbose = TRUE)

Arguments

- | | |
|------------|----------------------------------|
| vcf.obj | A list from ReadVCF |
| config.obj | A list from ParseConfigFile |
| verbose | If true, provides process detail |

Value

- A list with the following elements
- vcf.obj.filteredvcf.obj (high-quality vcf)
 - vcf.obj.artifactvcf.obj (low-quality vcf)

MakeFilter	<i>MakeFilter</i>
------------	-------------------

Description

Creates a vcf filter from config.obj

Usage

MakeFilter(config.obj)

Arguments

- | | |
|------------|---|
| config.obj | A list from ParseConfigFile (any filter with "use_in_filter" value declared as FALSE is not considered) |
|------------|---|

Value

A list with the filter parameters

MutaliskParseVCFObj	<i>MutaliskParseVCFObj</i>
---------------------	----------------------------

Description

Parses a vcf.obj and prepares it to run Mutalisk.

Usage

```
MutaliskParseVCFObj(vcf.obj)
```

Arguments

vcf.obj	A list from ReadVCF
---------	---------------------

Value

A data.frame

MutPatParseRefMutSigs	<i>MutPatParseRefMutSigs</i>
-----------------------	------------------------------

Description

Parses a df.ref.mut.sigs and prepares it to run Mutational Patterns.

Usage

```
MutPatParseRefMutSigs(df.ref.mut.sigs, target.mut.sigs,
  signature.start.column.index = 4,
  mutation.type.header = "SomaticMutationType")
```

Arguments

df.ref.mut.sigs	A data.frame of reference mutational signatures
target.mut.sigs	A character vector of target mutational signatures names
signature.start.column.index	= An integer value (e.g. column index corresponding to 'SBS1')
mutation.type.header	= A string value (name of header corresponding to column containing 'A[C>A]A' data))

Value

A data.frame of the format deconstructSigs::signatures.cosmic

MutPatParseVCFObj	<i>MutPatParseVCFObj</i>
-------------------	--------------------------

Description

Parses a vcf.obj and prepares it to run Mutational Patterns.

Usage

```
MutPatParseVCFObj(vcf.obj, bsg, sample.id = "sample")
```

Arguments

vcf.obj	A list from ReadVCF
bsg	BSgenome.Hsapiens.UCSC.hg19::BSgenome.Hsapiens.UCSC.hg19 or BSgenome.Hsapiens.UCSC.hg38
sample.id	A string value

Value

A data.frame with the column sample.id and row names corresponding to 96 substitution types

ParameterToBits	<i>ParameterToBits</i>
-----------------	------------------------

Description

Calculate the number of bits needed to conduct FIREVAT GA binary optimization.

Usage

```
ParameterToBits(vcf.obj, config.obj, vcf.filter, multiplier = 100)
```

Arguments

vcf.obj	A list from ReadVCF
config.obj	A list from ParseConfigFile
vcf.filter	A list from MakeMuTect2Filter
multiplier	A multiplier for convert fraction to integer (default = 100)

Details

vcf.obj\$data: if $\max(\text{vcf.obj\$data}[[\text{param}]]) < 1$, then multiply multiplier to the vector

Value

A list with the elements

- params.bit.lenA numeric vector. Each element is the bit length of each parameter value
- vcf.objA vcf.obj ([ReadVCF](#)) with updated data

ParseConfigFile

ParseConfigFile

Description

This function returns config.obj from JSON or YAML config file. - Check if the config file is in JSON format or YAML format - Return config.obj

Usage

```
ParseConfigFile(config.path, verbose = TRUE)
```

Arguments

config.path	A string for config file path
verbose	If true, provides process detail

Value

config.obj: list of parameters

Examples

```
## Not run:  
ParseConfigFile("example.variant.caller.json")  
ParseConfigFile("example.variant.caller.json", verbose=False)  
  
## End(Not run)
```

PCAWG.All.Sequencing.Artifact.Signatures
Constant

Description

PCAWG mutational signatures reported to be associated with sequencing artifacts

Usage

PCAWG.All.Sequencing.Artifact.Signatures

Format

An object of class character of length 17.

PCAWG.Known.Sequencing.Artifact.Signatures
Constant

Description

PCAWG mutational signatures reported to be associated with sequencing artifacts

Usage

PCAWG.Known.Sequencing.Artifact.Signatures

Format

An object of class character of length 1.

PCAWG.Likely.Sequencing.Artifact.Signatures
Constant

Description

PCAWG mutational signatures reported to be associated with sequencing artifacts

Usage

PCAWG.Likely.Sequencing.Artifact.Signatures

Format

An object of class character of length 5.

PCAWG.Possible.Sequencing.Artifact.Signatures
Constant

Description

PCAWG mutational signatures reported to be associated with sequencing artifacts

Usage

PCAWG.Possible.Sequencing.Artifact.Signatures

Format

An object of class character of length 11.

PCAWG.Target.Mutational.Signatures
Constant

Description

PCAWG target mutational signatures reported to be unrelated to sequencing artifacts

Usage

PCAWG.Target.Mutational.Signatures

Format

An object of class character of length 49.

PerformStrandBiasAnalysis
PerformStrandBiasAnalysis

Description

Performs strand bias analysis

Usage

```
PerformStrandBiasAnalysis(vcf.obj, ref.forward.strand.var,  
  ref.reverse.strand.var, alt.forward.strand.var, alt.reverse.strand.var,  
  perform.fdr.correction = TRUE, fdr.correction.method = "BH")
```


Arguments

vcf.obj [ReadVCF](#)
 ref.forward.strand.var A string value.
 ref.reverse.strand.var A string value.
 alt.forward.strand.var A string value.
 alt.reverse.strand.var A string value.
 perform.fdr.correction If TRUE, then performs false discovery rate correction
 fdr.correction.method A string value. FDR correction method (Refer to p.adjust() function)

Value

An updated vcf.obj

PlotMutaliskResults	<i>PlotMutaliskResults</i>
---------------------	----------------------------

Description

Plots Mutalisk results

Usage

```
PlotMutaliskResults(mutalisk.results, signatures, trinuc.max.y,
  trinuc.min.y, mut.type.max.y, title)
```

Arguments

mutalisk.results A list obtained from [RunMutalisk](#)
 signatures A character vector of mutational signatures names
 trinuc.max.y A numeric value (maximum y-axis value)
 trinuc.min.y A numeric value (minimum y-axis value)
 mut.type.max.y A numeric value
 title A string value

Value

A ggplot object

Examples

```
## Not run:
df.ref.mut.sigs <- GetPCAWGMutSigs()
target.mut.sigs <- GetPCAWGMutSigsNames()
vcf.obj <- ReadVCF(vcf.file = "../data/sample/P-233-CT.final.vcf")
mutalisk.results <- RunMusalisk(vcf.obj = vcf.obj,
                               df.ref.mut.sigs = df.ref.mut.sigs,
                               target.mut.sigs = target.mut.sigs)
p <- PlotMusaliskResults(musalisk.results = mutalisk.results)
print(p)

## End(Not run)
```

PlotMutationTypes	<i>PlotMutationTypes</i>
-------------------	--------------------------

Description

Plots a horizontal barplot of mutation types

Usage

```
PlotMutationTypes(mutation.types = c("C>A", "C>G", "C>T", "T>A", "T>C",
  "T>G"), mutation.types.values, mutation.types.colors, max.y.val, title,
  convert.to.percentage = T, show.legend = T, font.size.small = 8,
  font.size.med = 14, plot.margin = unit(c(0.5, 0.5, 0.5, 0.5), "cm"))
```

Arguments

<code>mutation.types</code>	Mutation types; Default = c("C>A", "C>G", "C>T", "T>A", "T>C", "T>G")
<code>mutation.types.values</code>	Mutation count for each mutation type
<code>mutation.types.colors</code>	A color vector for indicating mutation types
<code>max.y.val</code>	y axis maximum value
<code>title</code>	Plot title
<code>convert.to.percentage</code>	if True convert y values to percentage (x 100); Default = T
<code>show.legend</code>	If True, show legend; Default = T
<code>font.size.small</code>	Small font size; Default = 8
<code>font.size.med</code>	Medium font size; Default = 14
<code>plot.margin</code>	Margin vector for drawing plot; Default = unit(c(0.5, 0.5, 0.5, 0.5), "cm"))

Value

A ggplot object

Examples

```
## Not run:
p <- PlotMutationTypes(mutation.types = c("C>A", "C>G", "C>T", "T>A", "T>C", "T>G"),
  mutation.types.values = c(0.3, 0.3, 0.1, 0.1, 0.1, 0.1),
  mutation.types.colors = TriNuc.Mutation.Type.Hex.Colors,
  max.y.val = 0.5,
  convert.to.percentage = T,
  show.legend = T,
  font.size.small = 8,
  font.size.med = 14,
  plot.margin = unit(c(0.5, 0.5, 0.5, 0.5), "cm"))

print(p)

## End(Not run)
```

PlotOptimizationIterations

PlotOptimizationIterations

Description

Plots multiple scatter plots into one figure

Usage

```
PlotOptimizationIterations(df, columns.to.plot, x.axis.var, x.axis.title,
  x.max, save.file, title, y.axis.title = "", y.max = 1,
  point.size = 1, connect.dots = T, plot.legend = T,
  legend.ncol = 1, font.size.med = 14, font.size.large = 16,
  plot.margin = unit(c(0.5, 0.5, 0.5, 0.5), "cm"))
```

Arguments

df	A data.frame (from reading "FIREVAT_Optimization_Logs.tsv")
columns.to.plot	A character vector (of column names to plot)
x.axis.var	x axis variable
x.axis.title	x axis title
x.max	x axis maximum value
save.file	Filename (including full path) to which the plot will be saved
title	Plot title
y.axis.title	y axis title; Default = ""

y.max	y axis maximum value; Default = 1
point.size	Point size; Default = 1
connect.dots	If True draws dots for each iteration; Default = True
plot.legend	If True write legend of plot; Default = T
legend.ncol	legend.n Default = 1
font.size.med	Medium font size; Default = 14
font.size.large	Large font size; Default = 16
plot.margin	Margin vector for plot; Default = unit(c(0.5, 0.5, 0.5, 0.5), "cm"))

Value

A ggplot object

PlotSignaturesContProbs

PlotSignaturesContProbs

Description

Plots a horizontal barplot of identified mutational signatures

Usage

```
PlotSignaturesContProbs(df.identified.mut.sigs, df.ref.sigs.groups.colors,
  title, convert.to.percentage = T, font.size.small = 8,
  font.size.med = 14, plot.margin = unit(c(0.5, 0.5, 0.5, 0.5), "cm"))
```

Arguments

df.identified.mut.sigs	A data.frame of identified mutational signatures
df.ref.sigs.groups.colors	A data.frame with 'signature', 'group', and 'color' columns
title	Plot title
convert.to.percentage	If true, convert y values to percentage (x 100); Default = T,
font.size.small	Small font size; Default = 8,
font.size.med	Medium font size; Default = 14,
plot.margin	Margin vector for drawing plot; Default = unit(c(0.5, 0.5, 0.5, 0.5), "cm"))

Value

A ggplot object

Examples

```
## Not run:
g <- PlotSignaturesContProbs(sigs = c(mutalisk.results$identified.mut.sigs),
  sigs.probs = c(mutalisk.results$identified.mut.sigs.probs),
  df.ref.sigs.groups.colors = GetPCAWGMutSigsEtiologiesColors())
print(g)

## End(Not run)
```

PlotTable	<i>PlotTable</i>
-----------	------------------

Description

Plots basic statistics table

Usage

```
PlotTable(df, padding = 20, font.size = 14)
```

Arguments

- df = A data.frame where the first column is header and the second column is data value
- padding Padding size; Default = 20
- font.size Font size; Default = 14

Value

A plot

PlotTriNucSpectrum	<i>PlotTriNucSpectrum</i>
--------------------	---------------------------

Description

Plots the spectrum of 96 trinucleotide distribution (C>A, C>G, C>T, T>A, T>C, T>G) Please note that this function assumes that both sub.types and spectrum are sorted in the following order: C>A, C>G, C>T, T>A, T>C, T>G

Usage

```
PlotTriNucSpectrum(sub.types, spectrum, max.y.val, min.y.val, y.axis.title,
  draw.top.strip = T, draw.x.axis.labels = T, draw.y.axis.labels = T,
  draw.y.axis.title = T, font.size.small = 8, font.size.med = 14,
  plot.margin.top = 0.5, plot.margin.bottom = 0.5,
  plot.margin.left = 0.5, plot.margin.right = 0.5, title)
```

Arguments

sub.types	A character vector (types of 96 trinucleotide substitutions)
spectrum	A numeric vector (96 elements)
max.y.val	y axis maximum value
min.y.val	y axis minimum value
y.axis.title	y axis title
draw.top.strip	If True then draws top strip; Default = T
draw.x.axis.labels	If True then draws x axis labels; Default = T
draw.y.axis.labels	If True then draws y axis labels; Default = T
draw.y.axis.title	If True then draws y axis title; Default = T
font.size.small	Small font size; Default = 8
font.size.med	Medium font size; Default = 14
plot.margin.top	Top margin; Default = 0.5
plot.margin.bottom	Bottom margin; Default = 0.5
plot.margin.left	Left margin; Default = 0.5
plot.margin.right	Right margin; Default = 0.5
title	Plot title

Value

A ggplot object

PlotVCFStatsBoxPlots *PlotVCFStatsBoxPlots*

Description

Plots multiple (original, refined, artifact vcf) boxplots for single filter parameter

Usage

```
PlotVCFStatsBoxPlots(original.vcf.stat.values, refined.vcf.stat.values,
  artifact.vcf.stat.values, xlab, axis.font.size = 10,
  label.font.size = 10, title.font.size = 12)
```

Arguments

<code>original.vcf.stat.values</code>	A numeric vector corresponding to the original vcf.obj values of single filter parameter
<code>refined.vcf.stat.values</code>	A numeric vector corresponding to the refined vcf.obj values of single filter parameter
<code>artifact.vcf.stat.values</code>	A numeric vector corresponding to the artifact vcf.obj values of single filter parameter
<code>xlab</code>	A string value (x-axis label)
<code>axis.font.size</code>	An integer value (axis font size)
<code>label.font.size</code>	An integer value (label font size)
<code>title.font.size</code>	An integer value (title font size)

Value

A ggboxplot

PlotVCFStatsHistograms

PlotVCFStatsHistograms

Description

Plots multiple VCF stats histograms into one figure

Usage

```
PlotVCFStatsHistograms(plot.values, x.axis.labels, stat.y.max.vals,
  stat.x.max.vals, sample.id, save.file, title, cutoff.values,
  plot.boxplot = F, plot.cutoff.line.color = "#D4012E",
  plot.cutoff.value.lines = F, bin.width = 1, ncol = 4, nrow = 3,
  font.size.med = 10, font.size.large = 12, plot.margin = unit(c(0.5,
  0.5, 0.5, 0.5), "cm"))
```

Arguments

<code>plot.values</code>	A list of multiple numeric vectors
<code>x.axis.labels</code>	A character vector of x axis labels
<code>stat.y.max.vals</code>	A numeric vector of max y-axis values

<code>stat.x.max.vals</code>	A numeric vector of max x-axis values
<code>sample.id</code>	A string value of sample ID
<code>save.file</code>	A string value of file to which the resulting plot will be saved
<code>title</code>	A string value of plot title
<code>cutoff.values</code>	A numeric vector of cutoff values
<code>plot.boxplot</code>	A boolean value (default = False)
<code>plot.cutoff.line.color</code>	A hex string value (default = "#D4012E")
<code>plot.cutoff.value.lines</code>	A boolean value (default = False)
<code>bin.width</code>	An integer value (default = 1; histogram bin width)
<code>ncol</code>	An integer value (default = 4; ggarrange ncol)
<code>nrow</code>	An integer value (default = 3; ggarrange nrow)
<code>font.size.med</code>	An integer value (default = 10)
<code>font.size.large</code>	An integer value (default = 12)
<code>plot.margin</code>	A list (default = <code>unit(c(0.5, 0.5, 0.5, 0.5), "cm")</code>)

Value

A list with the following elements

- `f` = A ggarrange object
- `graphs` = A list of length 3; each element is a ggplot histogram

PrepareAnnotationDB	<i>PrepareAnnotationDB</i>
---------------------	----------------------------

Description

Prepares `df.genes.of.interest` from a `vcf.obj` ([ReadVCF](#)) of COSMIC or ClinVar `vcf` for [AnnotateVCFObj](#)

Usage

```
PrepareAnnotationDB(annotation.vcf.obj)
```

Arguments

`annotation.vcf.obj`
vcf.obj of COSMIC or ClinVar vcf file

Value

A data.frame of `annotation.vcf.obj`

PrepareArtifactAnnotationTable
<i>PrepareArtifactAnnotationTable</i>

Description

Prepares artifactual mutations annotation (filtered, queried) table

Usage

PrepareArtifactAnnotationTable(data)

Arguments

data A list of elements returned from [RunFIREVAT](#)

Value

A data.frame

PrepareArtifactStrandBiasTable
<i>PrepareArtifactStrandBiasTable</i>

Description

Prepares artifactual mutations strand biased variants table

Usage

PrepareArtifactStrandBiasTable(data)

Arguments

data A list of elements returned from [RunFIREVAT](#)

Value

A data.frame

`PrepareArtifactualMutsOptimizationIterationsPlot`*PrepareArtifactualMutsOptimizationIterationsPlot*

Description

Prepares artifactual mutations optimization iterations plot

Usage

```
PrepareArtifactualMutsOptimizationIterationsPlot(data)
```

Arguments

`data` A list of elements returned from [RunFIREVAT](#)

Value

A ggplot object

`PrepareFilterCutoffsTable`*PrepareFilterCutoffsTable*

Description

Prepares filter cutoffs table for reporting

Usage

```
PrepareFilterCutoffsTable(data)
```

Arguments

`data` A list of elements returned from [RunFIREVAT](#)

Value

A data.frame

PrepareGeneticAlgorithmParametersTable
<i>PrepareGeneticAlgorithmParametersTable</i>

Description

Prepares Genetic Algorithm parameters table

Usage

PrepareGeneticAlgorithmParametersTable(data)

Arguments

data A list of elements returned from [RunFIREVAT](#)

Value

A data.frame

PrepareIdentifiedSignaturesPlot
<i>PrepareIdentifiedSignaturesPlot</i>

Description

Prepares identified signatures plot for reporting

Usage

PrepareIdentifiedSignaturesPlot(data)

Arguments

data A list of elements returned from [RunFIREVAT](#)

Value

A ggarrange object

`PrepareMLEReconstructedSpectrumsPlot`*PrepareMLEReconstructedSpectrumsPlot*

Description

Prepares MLE reconstructed spectrums plot

Usage

```
PrepareMLEReconstructedSpectrumsPlot(data)
```

Arguments

data A list of elements returned from [RunFIREVAT](#)

Value

A ggarrange object

`PrepareNucleotideSubstitutionTypesPlot`*PrepareNucleotideSubstitutionTypesPlot*

Description

Prepares nucleotide substitution types plot

Usage

```
PrepareNucleotideSubstitutionTypesPlot(data)
```

Arguments

data A list of elements returned from [RunFIREVAT](#)

Value

A ggarrange object

PrepareObservedSpectrumsPlot
<i>PrepareObservedSpectrumsPlot</i>

Description

Prepares observed spectrums plot

Usage

PrepareObservedSpectrumsPlot(data)

Arguments

data A list of elements returned from [RunFIREVAT](#)

Value

A ggarrange object

PrepareOptimizationResultsTable
<i>PrepareOptimizationResultsTable</i>

Description

Prepares optimization results table

Usage

PrepareOptimizationResultsTable(data)

Arguments

data A list of elements returned from [RunFIREVAT](#)

Value

A data.frame

PrepareOptimizedVCFStatisticsPlot
<i>PrepareOptimizedVCFStatisticsPlot</i>

Description

Prepares optimized VCF statistics plot

Usage

PrepareOptimizedVCFStatisticsPlot(data)

Arguments

data A list of elements returned from [RunFIREVAT](#)

Value

A ggarrange object

PrepareRefinedAnnotationTable
<i>PrepareRefinedAnnotationTable</i>

Description

Prepares refined mutations annotation (filtered, queried) table

Usage

PrepareRefinedAnnotationTable(data)

Arguments

data A list of elements returned from [RunFIREVAT](#)

Value

A data.frame

PrepareRefinedMutsOptimizationIterationsPlot
PrepareRefinedMutsOptimizationIterationsPlot

Description

Prepares refined mutations optimization iterations plot

Usage

```
PrepareRefinedMutsOptimizationIterationsPlot(data)
```

Arguments

data A list of elements returned from [RunFIREVAT](#)

Value

A ggplot object

PrepareRefinedStrandBiasTable
PrepareRefinedStrandBiasTable

Description

Prepares refined mutations strand biased variants table

Usage

```
PrepareRefinedStrandBiasTable(data)
```

Arguments

data A list of elements returned from [RunFIREVAT](#)

Value

A data.frame

PrepareResidualSpectrumsPlot
<i>PrepareResidualSpectrumsPlot</i>

Description

Prepares residual spectrums plot

Usage

PrepareResidualSpectrumsPlot(data)

Arguments

data A list of elements returned from [RunFIREVAT](#)

Value

A ggarrange object

PrepareTrinucleotideSpectrumsTable
<i>PrepareTrinucleotideSpectrumsTable</i>

Description

Prepares trinucleotide spectrums table

Usage

PrepareTrinucleotideSpectrumsTable(data)

Arguments

data A list of elements returned from [RunFIREVAT](#)

Value

A data.frame

QueryAnnotatedVCF	<i>FilterAnnotatedVCF</i>
-------------------	---------------------------

Description

Annotates a vcf.obj using df.variants.of.interest (from ([PrepareAnnotationDB](#)))

Usage

```
QueryAnnotatedVCF(vcf.obj.annotated, filter.key.value.pairs,
  filter.condition = "AND")
```

Arguments

vcf.obj.annotated
 [AnnotateVCFObj](#)
filter.key.value.pairs
 A list with the key as the column name and value as the filtering values. E.g.
 list("CLNSIG" = c("Pathogenic", "Pathogenic/Likely_pathogenic"))
filter.condition
 'AND' or 'OR'.

Value

A vcf.obj

ReadOptimizationIterationReport	<i>ReadOptimizationIterationReport</i>
---------------------------------	--

Description

Read optimization iteration report

Usage

```
ReadOptimizationIterationReport(data)
```

Arguments

data A list of elements returned from [RunFIREVAT](#)

Value

A data.frame of FIREVAT optimization logs

ReadVCF

ReadVCF

Description

Reads a .vcf file

Usage

```
ReadVCF(vcf.file, genome = "hg19", split.info = FALSE,
        check.chromosome.name = TRUE)
```

Arguments

`vcf.file` (full path of a .vcf file)

`genome` ('hg19' or 'hg38')

`split.info` A boolean value. If TRUE, then makes the INFO column in the vcf as a separate column. Default value is FALSE.

`check.chromosome.name` A boolean value. If TRUE, then check whether converts 'MT' to 'M' and adds 'chr' to the CHROM column. Default value is TRUE.

Value

A list with elements 'data', 'header', 'genome'

ReportFIREVATResults *ReportFIREVATResults*

Description

Reports FIREVAT results in html format (generated from Rmd)

Usage

```
ReportFIREVATResults(data)
```

Arguments

`data` A list of main data from [RunFIREVAT](#)

Value

An updated data list

<i>RunFIREVAT</i>	<i>RunFIREVAT</i>
-------------------	-------------------

Description

Runs FIREVAT using configuration data. Filters point mutations in the user-specified vcf file based on mutational signature identification and outputs the refined and artifact vcf files as well as meta-data related to the refinement process.

Usage

```
RunFIREVAT(vcf.file, vcf.file.genome, config.file, df.ref.mut.sigs,
  target.mut.sigs, sequencing.artifact.mut.sigs, num.cores, output.dir,
  mode = "ga", init.artifact.stop = 0.05,
  objective.fn = Default.Obj.Fn, use.suggested.soln = TRUE,
  ga.type = "real-valued", ga.pop.size = 200, ga.max.iter = 200,
  ga.run = 50, ga.pmutation = 0.25, mutalisk = TRUE,
  mutalisk.method = "all", mutalisk.random.sampling.count = 20,
  mutalisk.random.sampling.max.iter = 10,
  perform.strand.bias.analysis = TRUE,
  filter.by.strand.bias.analysis = TRUE,
  filter.by.strand.bias.analysis.cutoff = 0.25,
  strand.bias.perform.fdr.correction = TRUE,
  strand.bias.fdr.correction.method = "BH",
  ref.forward.strand.var = NULL, ref.reverse.strand.var = NULL,
  alt.forward.strand.var = NULL, alt.reverse.strand.var = NULL,
  annotate = TRUE, df.annotation.db = NULL,
  annotated.columns.to.display = NULL,
  annotation.filter.key.value.pairs = NULL,
  annotation.filter.condition = "AND", write.vcf = TRUE,
  report = TRUE, save.rdata = TRUE, save.tsv = TRUE,
  report.format = "html", verbose = TRUE)
```

Arguments

<code>vcf.file</code>	String value corresponding to input .vcf file. Please provide the full path.
<code>vcf.file.genome</code>	Genome assembly of the input .vcf file. The value should be either 'hg19' or 'hg38'.
<code>config.file</code>	String value corresponding to input configuration file. For more details please refer to ...
<code>df.ref.mut.sigs</code>	A data.frame of the reference mutational signatures
<code>target.mut.sigs</code>	A character vector of the target mutational signatures from reference mutational signatures.

<code>sequencing.artifact.mut.sigs</code>	A character vector of the sequencing artifact mutational signatures from reference mutational signatures.
<code>num.cores</code>	Number of cores to allocate
<code>output.dir</code>	String value of the desired output directory
<code>mode</code>	String value. The value should be either 'ga' or 'manual'.
<code>init.artifact.stop</code>	Numeric value less than 1. If the sum of sequencing artifact weights in the user-specified original VCF file (i.e. <code>vcf.file</code>) is less than or equal to this value then FIREVAT does not perform variant refinement. Default value is 0.05. Note that this option does not apply if 'mode' is 'manual'.
<code>objective.fn</code>	Objective value derivation function. Default: <code>Default.Obj.Fn</code> .
<code>use.suggested.soln</code>	Boolean value. If TRUE, then FIREVAT passes the default values of filter variables declared as 'use_in_filter' in the config file to the 'suggestions' parameter of the Genetic Algorithm package. If FALSE, then FIREVAT supplies NULL to the GA package 'suggestions' parameter. FIREVAT also computes baseline performance of each filter variable and uses fittest population from each variable as a suggested solution.
<code>ga.type</code>	String value. The value should be either 'binray' or 'real-valued'.
<code>ga.pop.size</code>	Integer value of the Genetic Algorithm 'population size' parameter. Default: 200. This value should be set based on the number of filter parameters. Recommendation: 40 per filter parameter.
<code>ga.max.iter</code>	Integer value of the Genetic Algorithm 'maximum iterations' parameter. Default: 200. This value should be set based on the number of filter parameters. Recommendation: same as 'ga.pop.size'.
<code>ga.run</code>	Integer value of the Genetic Algorithm 'run' parameter. Default: 50. This value should be set based on the 'ga.max.iter' parameter. Recommendation: 25 percent of 'ga.max.iter'.
<code>ga.pmutation</code>	Float value of the Genetic Algorithm 'mutation probability' parameter. Default: 0.25.
<code>mutalisk</code>	If TRUE, confirm mutational signature analysis with Mutalisk. Default: TRUE.
<code>mutalisk.method</code>	Mutalisk signature identification method. Default: 'random.sampling'. The value can be either 'all' or 'random.sampling'. 'all' uses all <code>target.mut.sigs</code> to identify mutational signatures. 'random.sampling' randomly samples from <code>target.mut.sigs</code> to identify mutational signatures.
<code>mutalisk.random.sampling.count</code>	Mutalisk random sampling count. Default: 20. The number of signatures to sample from <code>target.mut.sigs</code>
<code>mutalisk.random.sampling.max.iter</code>	Mutalisk random sampling maximum iteration. Default: 10. The number of times Mutalisk randomly samples from <code>target.mut.sigs</code> before determining the candidate signatures.

<code>perform.strand.bias.analysis</code>	If TRUE, then performs strand bias analysis.
<code>filter.by.strand.bias.analysis</code>	If TRUE, then filters out variants in refined vcf based on strand bias analysis results
<code>filter.by.strand.bias.analysis.cutoff</code>	The p.value or q value cutoff for filtering out variants.
<code>strand.bias.perform.fdr.correction</code>	If TRUE, then performs false discovery rate correction for strand bias analysis.
<code>strand.bias.fdr.correction.method</code>	A string value. Default value is 'BH'. Refer to 'p.adjust()' function method.
<code>ref.forward.strand.var</code>	A string value.
<code>ref.reverse.strand.var</code>	A string value,
<code>alt.forward.strand.var</code>	A string value,
<code>alt.reverse.strand.var</code>	A string value,
<code>annotate</code>	A boolean value. Default value is TRUE.
<code>df.annotation.db</code>	A data.frame. Please refer to PrepareAnnotationDB
<code>annotated.columns.to.display</code>	A character vector.
<code>annotation.filter.key.value.pairs</code>	A list.
<code>annotation.filter.condition</code>	'AND' or 'OR'.
<code>write.vcf</code>	If TRUE, write original/refined/artifact vcfs. Default: TRUE.
<code>report</code>	If TRUE, generate report. Default: TRUE.
<code>save.rdata</code>	If TRUE, save rdata. Default: TRUE.
<code>save.tsv</code>	If TRUE, save tsv. Default: TRUE.
<code>report.format</code>	The format of FIREVAT report. We currently only support 'html'.
<code>verbose</code>	If TRUE, provides process detail. Default: TRUE.

Value

A list with the following elements

- `f` = A ggarrange object
- `graphs` = A list of length 3; each element is a ggplot histogram

RunMutalisk

RunMutalisk

Description

Identifies mutational signatures using Mutalisk

Usage

```
RunMutalisk(vcf.obj, df.ref.mut.sigs, target.mut.sigs,
  random.sampling.candidate.mut.sigs = c(), method = "random.sampling",
  n.sample = 20, n.iter = 10, verbose = TRUE)
```

Arguments

<code>vcf.obj</code>	A list (from <code>firevat_vcf::ReadVCF</code>)
<code>df.ref.mut.sigs</code>	A data.frame of reference mutational signatures
<code>target.mut.sigs</code>	A character vector of target mutational signatures names to identify from
<code>random.sampling.candidate.mut.sigs</code>	A character vector of mutational signatures names that gets appended to the list of candidate mutational signatures so that these are always considered.
<code>method</code>	A string value (must be either 'random.sampling' or 'all'). The method 'random.sampling' samples (without replacement) 'n.sample' number of signatures 'n.iter' number of times and runs the candidate signatures one last time. The method 'all' uses all target.mut.sigs
<code>n.sample</code>	An integer value ('random.sampling' method parameter) Number of signatures to choose for each iteration of random sampling).
<code>n.iter</code>	An integer value ('random.sampling' method parameter). Number of iterations to perform random sampling.
<code>verbose</code>	If true, provides process details

Value

A list with the following elements

- `num.point.mutations` An integer value - count of total point mutations
- `sub.types` A character vector of length 96
- `sub.types.spectrum` A numeric vector of length 96
- `num.mut.sigs` An integer value (count of unique mutational signatures identified)
- `identified.mut.sigs` A character vector where each element is a mutational signature identified
- `identified.mut.sigs.probs` A numeric vector where each element is the weight of mutational signature identified. The ordering follows `identified.mut.sigs`

- identified.mut.sigs.spectrumA numeric vector of length 96
- residualsA numeric vector of length 96
- rssA numeric value (residual sum of squares)
- cos.sim.scoreA numeric value (cosine similarity score between observed mutational spectrum and reconstructed mutational signatures)
- all.models.sigsA list where each element is a model; a model is a list of signatures identified)
- all.models.sigs.probsA list where each element is a model; a model is a list of contribution probabilities
- all.models.cos.sim.scoresA list where each element is a model; a model is a list of cosine similarity scores

RunMutaliskHelper

RunMutaliskHelper

Description

Helper function for RunMutalisk

Usage

```
RunMutaliskHelper(vcf.trinucleotide.data, df.ref.mut.sigs, target.mut.sigs)
```

Arguments

vcf.trinucleotide.data

A data.frame (from firevat_mutalisk::MutaliskParseVCFObj)

df.ref.mut.sigs

A data.frame of reference mutational signatures

target.mut.sigs

A character vector of target mutational signatures names

Value

A list with the following elements

- num.point.mutationsAn integer value - count of total point mutations
- sub.typesA character vector of length 96
- sub.types.spectrumA numeric vector of length 96
- num.mut.sigsAn integer value (count of unique mutational signatures identified)
- identified.mut.sigsA character vector where each element is a mutational signature identified
- identified.mut.sigs.probsA numeric vector where each element is the weight of mutational signature identified. The ordering follows identified.mut.sigs
- identified.mut.sigs.spectrumA numeric vector of length 96

- residualsA numeric vector of length 96
- rssA numeric value (residual sum of squares)
- cos.sim.scoreA numeric value (cosine similarity score between observed mutational spectrum and reconstructed mutational signatures)
- all.models.sigsA list where each element is a model; a model is a list of signatures identified
- all.models.sigs.probsA list where each element is a model; a model is a list of contribution probabilities
- all.models.cos.sim.scoresA list where each element is a model; a model is a list of cosine similarity scores

RunMutPat

RunMutPat

Description

Identifies mutational signatures using Mutational Patterns

Usage

```
RunMutPat(mut.pat.input, df.mut.pat.ref.sigs, target.mut.sigs,
          verbose = TRUE)
```

Arguments

mut.pat.input A list from [MutPatParseVCFObj](#)

df.mut.pat.ref.sigs A data.frame returned by [MutPatParseRefMutSigs](#)

target.mut.sigs A character vector of target mutational signatures names

verbose If true, provides process details

Value

A list with the following elements

- tumor.mutation.types.spectrumA numeric vector of length 96 - 'observed' spectrum
- identified.mutation.types.spectrumA numeric vector of length 96 - 'identified' spectrum
- residualsA numeric vector of length 96 - residuals
- mutation.typesA character vector of length 96
- identified.mut.sigsA character vector where each element is a mutational signature identified
- identified.mut.sigs.contribution.weightsA numeric vector where each element is the weight of mutational signature identified. The ordering follows identified.mut.sigs
- cosine.similarity.scoreA numeric value

Examples

```
## Not run:
vcf.obj <- ReadVCF(vcf.file = "../data/sample/HNT-082-BT.final.call.vcf", genome = "hg19")
df.ref.mut.sigs <- GetPCAWGMutSigs()
target.mut.sigs <- GetPCAWGMutSigsNames()
RunMutPat(vcf.obj = vcf.obj,
df.ref.mut.sigs = df.ref.mut.sigs,
target.mut.sigs = target.mut.sigs)

## End(Not run)
```

TriNuc.Mutation.Type.Hex.Colors
<i>Constant</i>

Description

Hex codes for the mutation types (for plotting purposes)

Usage

```
TriNuc.Mutation.Type.Hex.Colors
```

Format

An object of class character of length 6.

UpdateFilter	<i>UpdateFilter</i>
--------------	---------------------

Description

Update filter based on optim parameter values

Usage

```
UpdateFilter(vcf.filter, param.values)
```

Arguments

- vcf.filter A list from MakeFilterFromConfig
- param.values A numeric vector contains filtering value (same length with length(vcf.config.filter))

Value

Updated vcf.filter (list)

WriteFIREVATResultsToTSV
<i>WriteFIREVATResultsToTSV</i>

Description

Writes FIREVAT results to a csv file

Usage

WriteFIREVATResultsToTSV(firevat.results)

Arguments

firevat.results
List returned from RunFIREVAT

WriteVCF	<i>WriteVCF</i>
----------	-----------------

Description

Writes a vcf.obj to a .vcf file

Usage

WriteVCF(vcf.obj, save.file)

Arguments

vcf.obj (from the function ReadVCF)
save.file (full path including filename)

Index

*Topic **datasets**

- Chromosome.Names, [5](#)
- PCAWG.All.Sequencing.Artifact.Signatures, [23](#)
- PCAWG.Known.Sequencing.Artifact.Signatures, [23](#)
- PCAWG.Likely.Sequencing.Artifact.Signatures, [23](#)
- PCAWG.Possible.Sequencing.Artifact.Signatures, [24](#)
- PCAWG.Target.Mutational.Signatures, [24](#)
- TriNuc.Mutation.Type.Hex.Colors, [49](#)
- AnnotateVCFObj, [4](#), [32](#), [41](#)
- CheckIfVariantRefinementIsNecessary, [4](#)
- Chromosome.Names, [5](#)
- ComputeZScore, [6](#)
- ComputeZScoreEquiValue, [6](#)
- DecimalCeiling, [7](#)
- Default.Obj.Fn, [7](#)
- DefaultFilterToBinary, [8](#)
- EnumerateTriNucCounts, [8](#)
- Euc.Exp.Weighted.Obj.Fn, [9](#)
- Euc.Exp.Weighted.Seq.Art.Only.Obj.Fn.1, [9](#)
- Euc.Exp.Weighted.Seq.Art.Only.Obj.Fn.2, [10](#)
- Euc.Obj.Fn, [10](#)
- Exp.Weighted.Obj.Fn.1, [11](#)
- Exp.Weighted.Obj.Fn.2, [11](#)
- Exp.Weighted.Refined.Seq.Art.Only.Obj.Fn, [12](#)
- FilterByStrandBiasAnalysis, [12](#)
- FilterVCF, [13](#)
- GenerateConfigObj, [14](#)
- GetCOSMICMutSigs, [14](#)
- GetCOSMICMutSigsEtiologiesColors, [15](#)
- GetCOSMICMutSigsNames, [15](#)
- GetGASuggestedSolutions, [15](#)
- GetOptimizedSignatures, [16](#)
- GetParameterLowerUpperVector, [17](#)
- GetPCAWGMutSigs, [18](#)
- GetPCAWGMutSigsEtiologiesColors, [18](#)
- GetPCAWGMutSigsNames, [18](#)
- InitializeVCF, [19](#)
- MakeFilter, [8](#), [19](#)
- MutaliskParseVCFObj, [20](#)
- MutPatParseRefMutSigs, [20](#), [48](#)
- MutPatParseVCFObj, [21](#), [48](#)
- ParameterToBits, [8](#), [21](#)
- ParseConfigFile, [22](#)
- PCAWG.All.Sequencing.Artifact.Signatures, [23](#)
- PCAWG.Known.Sequencing.Artifact.Signatures, [23](#)
- PCAWG.Likely.Sequencing.Artifact.Signatures, [23](#)
- PCAWG.Possible.Sequencing.Artifact.Signatures, [24](#)
- PCAWG.Target.Mutational.Signatures, [24](#)
- PerformStrandBiasAnalysis, [24](#)
- PlotMutaliskResults, [25](#)
- PlotMutationTypes, [26](#)
- PlotOptimizationIterations, [27](#)
- PlotSignaturesContProbs, [28](#)
- PlotTable, [29](#)
- PlotTriNucSpectrum, [29](#)
- PlotVCFStatsBoxPlots, [30](#)
- PlotVCFStatsHistograms, [31](#)
- PrepareAnnotationDB, [4](#), [32](#), [41](#), [45](#)
- PrepareArtifactAnnotationTable, [33](#)

PrepareArtifactStrandBiasTable, [33](#)
PrepareArtifactualMutsOptimizationIterationsPlot,
 [34](#)
PrepareFilterCutoffsTable, [34](#)
PrepareGeneticAlgorithmParametersTable,
 [35](#)
PrepareIdentifiedSignaturesPlot, [35](#)
PrepareMLEReconstructedSpectrumsPlot,
 [36](#)
PrepareNucleotideSubstitutionTypesPlot,
 [36](#)
PrepareObservedSpectrumsPlot, [37](#)
PrepareOptimizationResultsTable, [37](#)
PrepareOptimizedVCFStatisticsPlot, [38](#)
PrepareRefinedAnnotationTable, [38](#)
PrepareRefinedMutsOptimizationIterationsPlot,
 [39](#)
PrepareRefinedStrandBiasTable, [39](#)
PrepareResidualSpectrumsPlot, [40](#)
PrepareTrinucleotideSpectrumsTable, [40](#)

QueryAnnotatedVCF, [41](#)

ReadOptimizationIterationReport, [41](#)
ReadVCF, [4](#), [14](#), [22](#), [25](#), [32](#), [42](#)
ReportFIREVATResults, [42](#)
RunFIREVAT, [16](#), [33–42](#), [43](#)
RunMutalisk, [25](#), [46](#)
RunMutaliskHelper, [47](#)
RunMutPat, [48](#)

TriNuc.Mutation.Type.Hex.Colors, [49](#)

UpdateFilter, [49](#)

WriteFIREVATResultsToTSV, [50](#)
WriteVCF, [50](#)