


Scale Invariant Feature Transform

261458 & 261753 Computer Vision

#10


SIFT [Scale Invariant Feature Transform]

David Lowe, 1999



• SIFT Keypoint Extraction

- Difference of Gaussian (DoG)
- Scale space



• SIFT Descriptors

- Histogram of gradient orientation


Adapted from David Lowe and Dan Huttenlocher

261458 & 261753 Computer Vision

#10

DoG [Difference of Gaussian]

3




Gaussian filter kernel $G(x, y, \sigma) = \frac{1}{\sqrt{2\pi\sigma^2}} e^{-\frac{(x^2+y^2)}{2\sigma^2}}$

261458 & 261753 Computer Vision

#10

Scale Space

4




261458 & 261753 Computer Vision

#10

Scale Space

5




261458 & 261753 Computer Vision

#10

SIFT Keypoints

6




261458 & 261753 Computer Vision

#10

Orientation Assignment

7



261458 & 261753 Computer Vision

#10


SIFT Descriptors

8

- Histogram of gradient
 - Weighted by magnitude
 - and Gaussian from center

For example:

- Use 16x16 neighbor pixels
 - Divide into 4 x 4 cells (size of 4 x 4)
 - Compute 8-bin histogram for each cell
 - Concatenate histogram from all cells
 - Descriptor length = $16 \times 8 = 128$
- cells bins



Visual Object Recognition, Kristen Grauman and Bastian Leibe

261458 & 261753 Computer Vision

#10

Properties of SIFT

9

- Extraordinarily robust matching technique

- Can handle changes in viewpoint \Rightarrow Up to about 60 degree out of plane rotation
- Can handle significant changes in illumination \Rightarrow Sometimes even day vs. night (below)
- Fast and efficient—can run in real time
- Lots of code available



261458 & 261753 Computer Vision

#10

Speed Up Robust Features


261458 & 261753 Computer Vision

#10

SURF [Speed Up Robust Features]


11

Herbert Bay et al., 2008



- SURF Keypoint Extraction

- Fast Hessian Detector
- Integral Image
- Scale space (Gaussian derivatives)



- SURF Descriptors


- Haar wavelet responses

261458 & 261753 Computer Vision

#10

Hessian Detector

12




261458 & 261753 Computer Vision

#10


Hessian Matrix

13




Hessian Matrix

14



Fast Hessian Detector

15



Integral Image

16

1	2	3	4	3	0	6	7	9
4	5	6	2	1	5	4	5	2
1	4	8	6	3	2	9	0	0
2	1	4	5	7	0	2	0	2
1	1	1	0	1	4	4	2	5
1	2	4	0	0	0	2	5	1
9	8	2	5	7	8	9	1	0
1	2	7	5	0	2	1	0	0

1	3	6	10	13	13	19	26	35
5	12	21	27	31	36	46	58	69
6	17	34	46	53	60	79	91	102
8	20	41	58	72	79	100	112	125
9	22	44	61	76	87	112	126	144
10	25	51	68	83	94	121	140	159
19	42	70	92	114	133	169	189	208
20	45	80	107	129	150	187	207	226

Original Image


Integral Image

 = 140 - 91 - 51 + 34 = 32

Can be compute using 3 operators

Scale Space


17



Instead of iteratively reducing the image size (left), the use of integral images allows the up-scaling of the filter at constant cost (right).

Scale Space


18



Approximated determinant of Hessian matrix from various scale

Scale Space

19



Time Comparison

20

detector	threshold	nb of points	comp. time (ms)
FH-15	60000	1813	160
FH-9	50000	1411	70
Hessian-Laplace*	1000	1979	700
Harris-Laplace	2500	1664	2100
DoG	default	1520	400

FH-15 = Fast Hessian detector with filter kernel of size 15×15

FH-9 = Fast Hessian detector with filter kernel of size 9×9

Hessian-Laplace = Hessian corner detector + Laplacian-of-Gaussian (LoG) scale space


Harris-Laplace = Harris corner detector + Laplacian-of-Gaussian (LoG) scale space

DoG= Difference of Gaussian detector used in SIFT

* K. Mikolajczyk and C. Schmid. Scale & affine invariant interest point detectors. IJCV, 60(1):63-86, 2004.

Orientation Assignment

21




261458 & 261753 Computer Vision

#10

Orientation Assignment

22




261458 & 261753 Computer Vision

#10

SURF Descriptors

23



- Construct a square region centred around the keypoint and oriented along the orientation (size = $20 \times \text{scale}$).
- Split up the regions into smaller 4×4 square sub-regions.

- For each sub-region, compute Haar wavelet response.

$$dx, dy$$

- Apply Gaussian weight to wavelet response.
- Compute 4 features for each sub-region.

$$\sum dx, \sum |dx|, \sum dy, \sum |dy|$$


- Concatenate features from all 4×4 sub-regions = descriptor vector of length 64. (do normalization after concatenating)

261458 & 261753 Computer Vision

#10

SURF Descriptors

24




261458 & 261753 Computer Vision

#10

SURF Descriptors

25



261458 & 261753 Computer Vision

#10

Oriented FAST and Rotated BRIEF


261458 & 261753 Computer Vision

#10

ORB [Oriented FAST and Rotated BRIEF]

27

E Rublee et al., 2011




• FAST Keypoint Extraction

- Segment-test detector
- Decision Tree
- Scale Pyramid

• BRIEF Descriptors

- Bit string description
- Intensity comparison of pixel pair
- Low complexity and memory usage




261458 & 261753 Computer Vision

#10

FAST [Features from Accelerated Segment Test]

28

Edward Rosten et al., 2006




Classifies p as a corner if there exists a set of n contiguous pixels in the circle which all brighter than p (+threshold) or all darker than p (-threshold)

261458 & 261753 Computer Vision

#10

FAST [Features from Accelerated Segment Test]

Edward Rosten et al., 2006




261458 & 261753 Computer Vision

#10

FAST [Features from Accelerated Segment Test]

Edward Rosten et al., 2006

Decision Tree



261458 & 261753 Computer Vision

#10

FAST [Features from Accelerated Segment Test]

Edward Rosten et al., 2006

- FAST does not produce a measure of cornerness, and it has large responses along edges.
- Harris corner measure may be used to verify the FAST keypoints.
- To obtain ORB keypoints, FAST keypoints are ordered according to the Harris measure, then the top N points are selected as ORB keypoints.
- FAST does not produce multi-scale features. A scale pyramid of the image is used, FAST features (filtered by Harris) are produced at each level in the pyramid.


261458 & 261753 Computer Vision

#10

Orientation Assignment

Intensity centroid :

The intensity centroid assumes that a corner's intensity is offset from its center, and this vector may be used to impute an orientation.



Centroid

Orientation

Keypoint

$$C = \left(\frac{m_{10}}{m_{00}}, \frac{m_{01}}{m_{00}} \right)$$

$$\theta = \tan^{-1} \left(\frac{m_{01}}{m_{10}} \right)$$

$$m_{pq} = \sum_{x,y} x^p y^q I(x,y)$$

261458 & 261753 Computer Vision

#10

BRIEF

33

[Binary Robust Independent Elementary Features]

M. Calonder et al., 2010

BRIEF descriptor = a bit string description of an image patch constructed from a set of binary intensity tests.

A binary intensity tests τ

$$\tau(I, \mathbf{p}, \mathbf{q}) = \begin{cases} 1; & I(\mathbf{p}) < I(\mathbf{q}) \\ 0; & I(\mathbf{p}) \geq I(\mathbf{q}) \end{cases}$$

I = Image patch
 \mathbf{p}, \mathbf{q} = Coordinate (x, y)

261458 & 261753 Computer Vision

#10

BRIEF

34

[Binary Robust Independent Elementary Features]

M. Calonder et al., 2010

BRIEF descriptor

0 1 0 0 1 0 ... 1 1

$$f_n(I) = \sum_{1 \leq i \leq n} 2^{i-1} \tau(I, \mathbf{p}_i, \mathbf{q}_i) \Rightarrow \text{Convert to bit string}$$

- There are many different types of distributions of test points
 - ORB chooses a Gaussian distribution around the center of the patch and vector length $n = 256$.
 - The image should be smoothed before performing the tests.
 - Hamming Distance can be used to match the descriptor
- To obtain rotation invariance descriptor, ORB steer BRIEF according to the orientation of keypoints.

261458 & 261753 Computer Vision


#10

BRIEF

35

[Binary Robust Independent Elementary Features]

M. Calonder et al., 2010



261458 & 261753 Computer Vision

#10


BRIEF

36


[Binary Robust Independent Elementary Features]

M. Calonder et al., 2010

Spatial Arrangement of the Test Location



G I: Uniform Distribution
G II: Gaussian Distribution, \mathbf{p} and \mathbf{q} are centered on origin
G III: Gaussian, \mathbf{p} is centered on origin, \mathbf{q} is centered on \mathbf{p}
G IV: Random \mathbf{p} and \mathbf{q} on Coarse polar grid
G V: Random only \mathbf{q} on coarse polar grid, \mathbf{p} is set at origin



261458 & 261753 Computer Vision

#10