

Shipped defaults & first boot

YaPcore ships **jar-embedded** plugin YAML plus a tracked `config/defaults/` pack that `./scripts/seed-defaults.sh` (and `start.sh`) copy into place **only when missing**.

Game path: product defaults use **YaP-Folia** (`game-authority=folia` , `folia-jar-source=build`). Build with `./scripts/build-yap-folia.sh` .

What works without editing

Layer	OOTB
Chat, Tab (sidebar), Guard, LagGuard, Packs, PluginCompat, PlaceholderAPI	Yes
YaP-Folia + first-party plugin jars	Yes (after <code>installAllProductDefaults</code> / release zip + <code>lib/yap-folia-*.jar</code>)
YaP Link + link plugins	Yes once <code>link.properties</code> seeded
Resource pack prompt	Yes when <code>server.properties</code> comes from defaults/example
YaPPerms starter ranks	Yes (<code>apply-starter-pack-on-first-boot</code> + <code>yap-ranks-auto-apply</code>)
Economy / claims / moderation / SQL plugins	Needs MariaDB
Discord webhooks	Needs your webhook URLs

Passwords & secrets: every credential is operator-owned. See [SECRETS.md](#) for MariaDB, dashboard token, forwarding secret, Discord inbound, and auth. | Floodgate key identity | Optional `key.pem` (UUID heuristic works without it) |

Fresh install (recommended)

```
./scripts/build-yap-folia.sh      # once – lib/yap-folia-26.2.jar
./scripts/seed-defaults.sh       # or just ./start.sh (seeds automatically)
./configure-db.sh --server-id lobby # starts Docker MariaDB + writes JDBC
./start.sh --fg
```

`configure-db.sh` / `ensure-db.sh` patch `plugins/YaPDB/config.yml` (and `PlayerData`) to match `deploy/mariadb/.env` — including port **3316** if host `:3306` was busy.

Defaults pack layout

```

config/defaults/
  README.md
  server.properties          → config/server.properties
  link.properties            → link-data/link.properties
  plugins/YaPDB/config.yml
  plugins/YaPPlayerData/...  # auth.enabled=false for LAN
  plugins/YaPDiscord/...     # inbound off
  plugins/YaPPerms|Chat|Tab|Essentials|Guard|LagGuard|Packs/...

```

Operator files are never overwritten. To reset a plugin to ship defaults, delete its `plugins/<Name>/config.yml` and re-run `seed-defaults.sh` (or delete the whole folder and let YaP-Folia re-extract from the jar after seed).

LAN vs public

Setting	Shipped default	Public tip
<code>online-mode</code>	<code>false</code>	<code>true</code> (or Link online-mode + forwarding)
<code>auth.enabled</code> (PlayerData)	<code>false</code>	<code>true</code> on offline-mode public servers
<code>internet-exposed</code>	<code>false</code>	<code>true</code> + nginx/Cloudflare
<code>folia-jar-source</code>	<code>build</code>	keep <code>build</code> (YaP-Folia)
Discord inbound	<code>false</code>	enable + strong <code>secret</code>

Release note

`assembleRelease` copies `config/` (including `defaults/` and `*.example`). Plugin **jars** only go under `plugins/` — configs are created on first boot via seed + jar. Ship or build `lib/yap-folia-*.jar` for the product game path.