

Grim Anticheat (optional third-party)

Grim AC is the recommended **heavy** anti-cheat for PvP / competitive networks. YaPcore ships **YaPGuard** as a lightweight native default (always on). **Grim is downloaded automatically on first setup** but **not loaded** until you enable it.

First install (automatic)

`./scripts/seed-defaults.sh` (also run from `start.sh`) downloads the latest Folia-capable Grim build from Modrinth as:

```
plugins/grim.jar.disabled
```

Folia ignores `*.jar.disabled` — Grim does **not** run until you enable it.

Skip the download (offline / CI): `YAP_SKIP_OPTIONAL_FETCH=1 ./scripts/seed-defaults.sh`

Enable Grim (operator action)

```
./scripts/grim-ac.sh enable    # → grim.jar + turns off YaPGuard movement checks
# restart Folia
```

Disable again:

```
./scripts/grim-ac.sh disable  # → grim.jar.disabled
# restart Folia
```

Status:

```
./scripts/grim-ac.sh status
```

Manual fetch (same as setup, still disabled):

```
./scripts/fetch-grim.sh --disabled
# or active jar for dev: ./scripts/fetch-grim.sh
# or: gradle fetchGrim
```

Notices: `third-party/grim/`. License: **GPLv3** (same family as YaPcore).

Place	Install?
Every Folia backend that needs AC	Yes — enable Grim per backend
Hub only	Common for lobby + PvP backends separately
YaP Link / proxy	No — Grim runs on the game server

Restart Folia after enable/disable. Config appears under `plugins/GrimAC/`.

YaPGuard vs Grim

	YaPGuard (native)	Grim (optional)
Jars	<code>yap-guard.jar</code> (product default, on)	<code>grim.jar.disabled</code> → <code>grim.jar</code> after enable
Depth	Fly/speed/reach/scaffold heuristics	Full movement simulation
Best for	Casual SMP, low cheat pressure	PvP, minigames, competitive

Do not run both at full sensitivity. Typical setups:

- **Grim only** — `./scripts/grim-ac.sh enable` (disables YaPGuard movement checks)
- **YaPGuard only** — leave Grim disabled (default after setup)
- **Grim + YaPGuard alerts** — Grim punishes; YaPGuard checks off, alerts optional

See [ANTICHEAT.md](#) for the locked product split (regions ≠ AC).

YaP stack notes

Topic	Guidance
Bedrock / Geyser-class	Grim exempts Bedrock players; keep <code>yap-floodgate</code> on the backend (not only Link) so UUID/linking matches
Via-class protocol	First-party edge on YaPcore chassis — no Via jars on backend; Grim sees normalized Paper movement
Folia	Use Modrinth builds with <code>folia</code> loader tag (<code>fetch-grim.sh</code> filters this)
Moderation	Grim alerts → wire Discord webhook in Grim config or mirror to <code>yap-moderation</code> via console
Staff	Grant Grim bypass + <code>yapguard.bypass</code> if YaPGuard stays loaded

Release zips

Release trees ship `grim.jar.disabled` when a Grim jar was present at build time (or after `seed-defaults.sh` on the installed copy). Operators still run `grim-ac.sh enable` before Grim

loads.

Related

- [ANTICHEAT.md](#) — YaPGuard vs regions vs third-party AC
- [TEBEX.md](#) — same optional-jar fetch pattern
- [LICENSING.md](#) — GPLv3 third-party redistribution