

# Internet & domain pointing

---

YaPcore separates **listen** addresses from **public** addresses so you can bind locally while advertising a domain or NAT/nginx-mapped ports to players.

Production domain for this repo: `yapcoremc.yaplabs.us`.

For Cloudflare + nginx edge setup, prefer [CLOUDFLARE\\_AND\\_NGINX.md](#).

## Quick setup (domain + nginx)

---

1. Point DNS **A/AAAA** at your origin IP (**DNS only** / **grey cloud** for Minecraft TCP+UDP).
2. Edit `config/server.properties` (see also `config/server.properties.example`):

```
internet-exposed=true
bind-host=0.0.0.0
allow-localhost=true
server-domain=yapcoremc.yaplabs.us
public-host=yapcoremc.yaplabs.us
nginx-domain=yapcoremc.yaplabs.us
# Advertised = nginx stream front (not the local bind port)
public-port=25565
public-bedrock-port=25565
# Packs via Cloudflare HTTPS → nginx :80 → YaPcore :8081
public-pack-port=443
nginx-public-port=25565
nginx-pack-port=80
resource-pack-public-host=yapcoremc.yaplabs.us
resource-pack-http-port=8081
port=25566
srv-enabled=true
```

3. Install nginx edge:

```
./scripts/nginx-setup.sh --dry-run
sudo ./scripts/nginx-setup.sh --install-pkg # first time
sudo ./scripts/nginx-setup.sh
```

4. Forward on the router/firewall to the **origin**: - **TCP+UDP** 25565 → nginx stream → YaPcore :25566 - **TCP** 80 (packs) → nginx → YaPcore :8081
5. Restart: `./scripts/gui.sh` or `./scripts/start.sh` — boot banner prints join URLs.

## What the boot banner means

---

| Line                                                      | Meaning                                               |
|-----------------------------------------------------------|-------------------------------------------------------|
| Same-PC → 127.0.0.1:25566                                 | Local bind port (always use this on the same machine) |
| Java / Bedrock → yapcoremc.yaplabs.us:25565               | Public / nginx / SRV port                             |
| Resource packs →<br>https://yapcoremc.yaplabs.us/pack/... | Public pack URL ( public-pack-port=443 )              |
| nginx edge → stream :25565 → local :25566                 | How traffic is remapped                               |

If `public-port` is 0 but `nginx-domain` / `server-domain` is set, YaPcore still advertises `nginx-public-port` (default 25565) for join/SRV.

## Player join strings

| Client                 | Address                                          |
|------------------------|--------------------------------------------------|
| Same PC                | 127.0.0.1:25566                                  |
| Internet (with SRV)    | yapcoremc.yaplabs.us                             |
| Internet (explicit)    | yapcoremc.yaplabs.us:25565                       |
| Packs (public)         | https://yapcoremc.yaplabs.us/pack/<file>         |
| Packs (same-PC client) | http://127.0.0.1:8081/pack/<file> (auto-offered) |

Console / GUI Network tab:

```
expose on
domain yapcoremc.yaplabs.us
public
```

## Optional Java DNS SRV

```
_minecraft._tcp.yapcoremc.yaplabs.us. 3600 IN SRV 0 5 25565 yapcoremc.yaplabs.us.
```

( `public` / Connect tab prints the exact line for your config.)

## Config keys

| Key              | Meaning                                   |
|------------------|-------------------------------------------|
| internet-exposed | Prefer 0.0.0.0 bind + print public banner |

| Key                                                                                       | Meaning                                                                                          |
|-------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|
| <code>server-domain</code> / <code>public-host</code>                                     | Domain players use                                                                               |
| <code>public-port</code>                                                                  | Advertised Java port after NAT/nginx ( <code>0</code> → nginx port or listen <code>port</code> ) |
| <code>public-bedrock-port</code>                                                          | Advertised Bedrock UDP port                                                                      |
| <code>public-pack-port</code>                                                             | Advertised pack port ( <code>443</code> → <code>https://</code> without <code>:443</code> )      |
| <code>nginx-domain</code> / <code>nginx-public-port</code> / <code>nginx-pack-port</code> | Edge proxy settings                                                                              |
| <code>resource-pack-public-host</code>                                                    | Override pack URL host                                                                           |

Code: `com.yapcore.network.publicity.PublicEndpoint`.

## Related

---

- [CLOUDFLARE\\_AND\\_NGINX.md](#)
- [NGINX\\_AND\\_LOCALHOST.md](#)
- [CLIENTS\\_AND\\_PACKS.md](#)