

Permissions & ranks

YaP first-party plugins gate commands with **Bukkit permission nodes**. **Native ranks** ship in `yap-perms.jar` (YaPPerms) — LuckPerms-class groups, inheritance, tracks, temp/world nodes, Vault Permission, prefix/suffix, per-rank chat colors, MariaDB, PlaceholderAPI `%yapperms_*`. `/lp` is an alias.

Quick start (native — default on product installs)

```
gradle installProductDefaults
./scripts/db/ensure-db.sh --server-id lobby
./scripts/start.sh --fg
# console or dashboard:
ranks apply
/yapperm user Steve parent set vip
/promote Steve
```

Starter pack (`default` → `vip` → `staff` → `admin` → `owner` + track `yap`) applies automatically on first boot, or via `ranks apply` / `/yapperm applypack`.

Optional auto-apply on boot (default **on** for new installs):

```
yap-ranks-auto-apply=true
```

Set `false` to disable. Requires `yap-perms.jar`; waits ~8s after start.

Surface	How
Console / stdin	<code>ranks status</code> · <code>ranks apply</code> · <code>ranks apply force</code>
In-game	<code>/yapperm applypack</code> · <code>/promote</code> · <code>/demote</code>
Web dashboard	Access & ranks (permission editor) · Rank pack → Apply pack
Config	<code>plugins/YaPPerms/config.yml</code>

OP still receives every node with `default: op` without YaPPerms attachments.

YaPPerms admin commands

Command	Permission
<code>/yapperm user <player> info</code>	<code>yapperm.user</code> / <code>admin</code>
<code>/yapperm user <player> parent set\ add\ remove <group></code>	<code>yapperm.admin</code>
<code>/yapperm user <player> permission set <node> true\ false [1d] [world=x]</code>	<code>yapperm.admin</code>
<code>/yapperm user <player> permission unset <node> [world=x]</code>	<code>yapperm.admin</code>

Command	Permission
<code>/yapperm user <player> meta set <prefix> [suffix]</code>	yapperm.admin
<code>/yapperm group create\ delete\ list\ info\ setprefix\ setsuffix\ setnamecolor\ setchatcolor\ parent ...</code>	yapperm.admin
<code>/yapperm track list\ info\ create\ append\ remove\ delete</code>	yapperm.admin
<code>/yapperm check <player> <node> [world]</code>	yapperm.user / admin
<code>/yapperm export [file.yml] · import <file.yml></code>	yapperm.admin
<code>/yapperm dump</code>	yapperm.admin — write editor- snapshot.yml for the web editor
<code>/yapperm editor-apply</code>	yapperm.admin — apply editor- apply.yml / editor-nodes from the dashboard
<code>/yapperm applypack</code>	yapperm.admin
<code>/promote <player> [track]</code>	yapperm.promote
<code>/demote <player> [track]</code>	yapperm.demote

Rank ladder (starter pack)

Rank	Weight	Prefix	Name / chat	Inherits	Role
default	0	gray name	&7 / &f	—	All players
vip	10	[VIP]	&a / &f	default	Donors / trusted
staff	50	[Staff]	&b / &f	vip	Helpers / junior-senior staff
admin	100	[Admin]	&c / &f	staff	Server admins — includes yap.bypass + MMO admin nodes
owner	200	[Owner]	&6 / &f	admin	Full access (* + yap.bypass) — network owners

Bypass rules: OP, yap.bypass, and creative/spectator skip land protection and MMO restrictions. Creative always gets vanilla-like build/combat (no skill gates, stamina, custom combat, or ability-bar locks). Admins get yap.bypass / yap.bypass.mmo in the starter pack — run /yapperm applypack after upgrading.

Legacy group **mod** still exists (same general staff tools, not on the promote track). Prefer **staff**.

Track name: **yap**. Promote with `/promote Steve` or `/yapperm user Steve parent set staff`.

```
/yapperm user Steve parent set staff
/yapperm user Steve parent set admin
/yapperm user Steve parent set owner
```

Chat colors per rank

Each group has a **prefix** (tag), **name-color** (player name), and **chat-color** (message). Chat format: `{prefix}{namecolor}{player}{suffix}&7: {chatcolor}{message}`.

```
/yapperm group setnamecolor vip &a
/yapperm group setchatcolor vip &f
/yapperm group info vip
```

Dashboard **Access & ranks** has the same fields. Codes are `&a` green, `&b` aqua, `&c` red, `&6` gold, `&f` white. YAML keys are `name-color` / `chat-color` under `groups.<rank>`. Empty database colors are filled from YAML on plugin start; `/yapperm applypack` also writes them.

Web store (Tebex): run those commands on the **Hub** backend console — [TEBEX.md](#).

YaPChat nodes

Node	Default	Feature
yapchat.use	true	Public chat
yapchat.msg	true	<code>/msg</code> <code>/reply</code>
yapchat.staff	op	<code>/staffchat</code> staff channel
yapchat.socialspy	op	See private messages
yapchat.admin	op	<code>/clearchat</code> <code>/yapchat reload</code>
yapchat.bypass.filter	op	Skip word filter
yapchat.bypass.slow	op	Skip slow mode

YaPModeration nodes

Node	Default	Feature
yapmod.ban	op	<code>/ban</code> <code>/tempban</code> <code>/unban</code>
yapmod.ipban	op	<code>/ipban</code> <code>/unbanip</code>
yapmod.mute	op	<code>/mute</code> <code>/tempmute</code> <code>/unmute</code>
yapmod.warn	op	<code>/warn</code>

Node	Default	Feature
yapmod.kick	op	/kick
yapmod.history	op	/modhistory /modcheck /banlist
yapmod.admin	op	/yapmod reload

YaPEssentials nodes

Node	Default	Command / feature
yapessentials.spawn	true	/spawn
yapessentials.setspawn	op	/setspawn
yapessentials.back	true	/back
yapessentials.tpa	true	/tpa /tpahere /tpaccept /tpdeny
yapessentials.teleport	op	/tp /tphere
yapessentials.gamemode	op	/gm /gms /gmc /gma /gmsh
yapessentials.item	op	/i /item
yapessentials.fly / .god / .speed / .heal / .feed	op	QoL toggles
yapessentials.repair / .clear / .vanish	op	Item / vanish tools
yapessentials.invsee / .echest / .nick	op	Staff QoL
yapessentials.nick.others	op	/nick for others
yapessentials.afk / .list / .rules / .motd / .suicide	true	Player info
yapessentials.ptime / .pweather / .broadcast / .hat	op	Client / broadcast
yapessentials.staff.socialspy	op	/socialspy
yapessentials.staff.freeze	op	/freeze
yapessentials.staff.check	op	/check
yapessentials.admin	op	/yapess reload

Toggle domains in `plugins/YaPEssentials/config.yml` under `features.*` (including `features.staff`).

YaPAdmin nodes

Node	Default	Command / feature
yapadmin.menu	op	/yapadmin /staff open hub
yapadmin.give	op	Give presets / materials / kits
yapadmin.server	op	Broadcast presets, /yapadmin reload
yapadmin.economy	op	Money grants (/yapmmo givemoney)

Grant `yapadmin.menu` (+ give/server) on `staff` / `admin` / `owner` ranks. Individual actions still need the underlying plugin nodes (`yapessentials.*`, `yapmod.*`, ...). See [ADMIN_MENU.md](#).

YaPProtect / YaPWorld

Node	Default	Command / feature
<code>yapprotect.admin</code>	op	<code>/yapprotect status reload prune</code>
<code>yapprotect.lookup</code>	op	<code>/yapprotect lookup user\ block ...</code>
<code>yapprotect.rollback</code>	op	<code>/yapprotect rollback <id>...</code>
<code>yapworld.admin</code>	op	<code>/yapworld status reload</code>
<code>yapworld.load</code> / <code>.unload</code>	op	<code>/yapworld load\ unload <world></code>
<code>yapworld.teleport</code>	op	<code>/yapworld tp <world> [player]</code>
<code>yapworld.selection</code>	op	<code>/yapworld wand , pos1/pos2</code>
<code>yapworld.schematic</code>	op	<code>/yapworld schem save\ paste\ import</code>
<code>yapworld.brush</code>	op	<code>/yapworld brush , undo/redo</code>
<code>yapworld.pregen</code>	op	<code>/yapworld pregen ...</code>

YaPRegions / YaPGuard / YaPMap / YaPNpcs

Node	Default	Feature
<code>yapregions.admin</code>	op	<code>/region define , flag, list</code>
<code>yapguard.admin</code>	op	<code>/yapguard reload , status</code>
<code>yapguard.bypass</code>	op	Skip anti-cheat checks
<code>yapguard.alerts</code>	op	Staff violation alerts
<code>yapmap.admin</code>	op	Map render config / reload
<code>yapnpcs.admin</code>	op	<code>/npc create\ remove</code>
<code>yapnpcs.quest</code>	true	<code>/quests list\ progress</code>

See [REGIONS.md](#) for claim flag commands (`/claim flag set`).

Dashboard: `POST /api/protect` , `POST /api/world` .

Playerdata command nodes

Node	Default	Command / feature
<code>yapdata.menu</code>	true	<code>/menu</code>
<code>yapdata.bag</code>	true	<code>/bag</code> extra storage

Node	Default	Command / feature
yapdata.bag.pages.5	false	At least 5 bag pages (VIP starter grant)
yapdata.bag.pages.7	false	At least 7 bag pages (staff starter grant)
yapdata.bag.pages.*	op	All configured bag pages
yapdata.bag.see	op	/bag see <player>
yapdata.balance	true	/bal (self)
yapdata.balance.others	op	/bal <other>
yapdata.pay	true	/pay
yapdata.eco	op	/eco give\ take\ set\ reset
yapdata.home	true	/home /sethome /delhome /homes
yapdata.warp	true	/warp /warps
yapdata.warp.admin	op	/setwarp /delwarp
yapdata.kit	true	/kit /kits GUI
yapdata.kit.starter	true	Starter kit
yapdata.kit.adventurer	false	Adventurer kit (quest / store unlock)
yapdata.kit.vip	false	VIP kit (VIP rank also has yapdata.kit.*)
yapdata.kit.*	op	All kits
yapdata.kit.give	op	/kit give /kit grant (console / Tebex)
yapdata.kit.create	op	/createkit /delkit kit signs
yapdata.kit.reset	op	/kitreset <player> [kit\ all]
yapdata.mail	true	/mail
yapdata.shop	true	/shop + chest shop buy
yapdata.jobs	true	/jobs GUI
yapdata.ah	true	/ah
yapdata.claim	true	/claim
yapdata.claims.admin	op	Bypass claims
yapdata.admin	op	/yapdata , override shops/AH/claims

Auth (/register /login ...) stays ungated so offline login always works.

YaPSkills (yap-skills.jar , gameplay opt-in)

Node	Default	Grants
yapskills.use	true	/skills , gain skill XP

Node	Default	Grants
yapskills.others	op	/skills <player>
yapskills.admin	op	/skill addxp, /skill set, /yskills reload

Placeholders (PlaceholderAPI): %yapskill_<skill>_level%, %yapskill_<skill>_xp%, %yapskill_total_level%, %yapskill_combat_level%.

Public leaderboard: /skill top <skill> [page] (no extra permission).

Bedrock MMO UI (yap-mmo-bedrock.jar , gameplay opt-in):

Node	Default	Grants
yapmmo.bedrock.use	true	/mmoui, Bedrock /skills form redirect

YaPFactions (yap-factions.jar)

Node	Default	Grants
yapfactions.use	true	/f commands
yapfactions.create	true	/f create
yapfactions.officer	true	Officer actions (invite, claim, bank withdraw)
yapfactions.leader	true	Leader actions (disband, transfer, join mode)
yapfactions.admin	op	/yapfactions admin commands

Dashboard: GET /api/factions (read-only snapshot).

YaPGuilds (yap-guilds.jar , gameplay opt-in)

Node	Default	Grants
yapguilds.use	true	/g commands
yapguilds.create	true	/g create
yapguilds.admin	op	/yapguilds admin commands

Dashboard: GET /api/guilds (read-only snapshot).

YaPCombat (yap-combat.jar , gameplay opt-in)

Node	Default	Grants
yapcombat.use	true	/combat stats
yapcombat.cast	true	/cast <spell>
yapcombat.prayer	true	/prayer on/off/list

Node	Default	Grants
yapcombat.admin	op	/combat reload , /yapcombat admin sethp

See [MMO_RS_SKILLS.md](#) for spell book, prayer drain, and ranged accuracy.

YaPCrafting (yap-crafting.jar , gameplay opt-in)

Node	Default	Grants
yapcraft.use	true	Station crafting, /recipe list
yapcraft.sell	true	/sell when economy enabled
yapcraft.admin	op	/ycraft reload

YaPGames (yap-games.jar , gameplay opt-in)

Node	Default	Grants
yapgames.use	true	/queue , /duel , /game
yapgames.admin	op	/ygames reload , list , forcestart , info , snapshot json

Requires yap-combat.jar for custom PvP in arenas (global pvp: false is overridden in active matches).

YaPMmoContent (yap-mmo-content.jar , gameplay opt-in)

Node	Default	Grants
yapmmo.hiscores	true	/hiscores <skill>
yapmmo.admin	op	/yapmmo reload , /yapmmo snapshot , quest reward hooks

Content packs: plugins/yap-mmo-content/quests/starter_chain.yml

YaPAbilities (yap-abilities.jar , gameplay opt-in)

Node	Default	Grants
yapabilities.use	true	/ability list , /ability cast , /ability bar , /ability book , /abilities , hotbar cast keys 4-9
yapabilities.bar	true	/ability bind , /ability clear , drag-bind in ability book
yapabilities.admin	op	/yapabilities reload

233 combat abilities ship in YAML packs; /cast delegates when yap-abilities is loaded.

Web rank editor

Dashboard **Access & ranks** edits what each rank may do (YaP commands, vanilla `/gamemode` / `/give` , Paper `/plugins` , deny vs inherit).

Create a rank with a **permission pack** (player / staff / admin) or **copy perms from another rank**. Add any node — including wildcards and nodes discovered from installed `plugin.yml` files — via the custom / bulk fields.

- Saves `starter-grants` (allows) and `editor-nodes` (allow + deny) in `plugins/YaPPerms/config.yml`
- Applies to MariaDB with `/yapperm editor-apply` (dashboard does this after Save)
- Live extras (custom nodes) refresh via `/yapperm dump` → `editor-snapshot.yml`
- Re- `applypack` reapplies starter grants **and** editor-nodes, so dashboard denies survive

See also

- [COMMANDS.md](#) · [WEB_DASHBOARD.md](#) · [PLUGIN_COMPAT.md](#)