

Built-in PlaceholderAPI (YaP)

YaPcore ships a **clean-room, clip-compatible** PlaceholderAPI so plugins that soft/hard-depend on HelpChat’s PlaceholderAPI work **without** installing PlaceholderAPI.jar from SpigotMC / Modrinth.

Item	Value
Product jar	plugins/yap-placeholderapi.jar
Plugin name (for getPlugin / depends)	PlaceholderAPI
Package	me.clip.placeholderapi.* (binary-compatible surface)
Built-in expansions	player, server (full upstream-style placeholder sets)
Extra expansions	Drop jars into plugins/PlaceholderAPI/expansions/
Admin	/papi full local command tree

Product rule

Do **not** also install HelpChat / clip PlaceholderAPI. Two jars both named PlaceholderAPI will conflict. YaP’s jar is the supported path.

```
gradle :placeholderapi-plugin:installIntoPlugins
# or: gradle shadowJar / assembleRelease
```

Commands

Command	Purpose
/papi help	Command list
/papi parse <me\ --null\ player> <text...>	Parse placeholders
/papi bcparse <target> <text...>	Broadcast parsed text
/papi cmdparse <target> <text...>	Dispatch parsed text as a command
/papi parserel <p1> <p2> <text...>	Relational placeholders
/papi dump	Local dump file + optional paste.helpch.at upload
/papi list / info [id] / reload	Expansion admin
/papi register <jar> / unregister <id>	Expansion folder admin

Command	Purpose
<code>/papi version</code>	Engine version
<code>/papi ecloud</code>	Explains YaP does not mirror eCloud (drop jars instead)

What works for other plugins

- `softdepend: [PlaceholderAPI] / depend: [PlaceholderAPI]`
- `Bukkit.getPluginManager().getPlugin("PlaceholderAPI") != null`
- `PlaceholderAPI.setPlaceholders(player, text)` (+ bracket / relational)
- `new MyExpansion().register()` extending `PlaceholderExpansion`
- Expansion register / unregister events
- `PlaceholderAPIPlugin.getAdventure()` (BukkitAudiences)
- `Msg`, `booleanTrue/False`, `getDateFormat()`, `getServerVersion()`
- Configurable / Cacheable / Cleanable / Taskable / Relational / VersionSpecific

Built-in placeholders

Player — name, displayname, uuid, health, *food*, *level/exp*, gamemode, world, *coords*, *yaw/pitch*, *biome*, direction, *ping/colored_ping*, *armor_*, *item_in_hand*, *permissions* (*has_permission_**), *potion effects*, *locale*, flight/sneak/sprint/dead flags, bed/compass, first/last join, and more.

Server — name, online / `online_<world>`, max_players, unique_joins, version/build, tps / colored tps, uptime, ram_, *whitelist*, *total_* entity/chunk counts, `time_*` patterns, countdown/countup helpers.

External expansions

```
plugins/PlaceholderAPI/expansions/
```

YaP does **not** download from HelpChat eCloud. Copy jars manually.

Ops extras

- **bStats** charts (YaP service id, not HelpChat's)
- **Update checker** — `check-updates` + optional `update-check-url`
- **Adventure** — `getAdventure()` for expansions that send components

First-party expansions

YaP Stacker registers `%yapstacker_*` when both jars are installed — see [STACKER.md](#).

Honesty bar

Clean-room compatibility engine — not a GPL port. eCloud download UX is intentionally absent; everything else above is in-tree.

See also [PLUGIN_COMPAT.md](#) · [PLUGINS.md](#).