

YaP PlayerData — cross-server sync, offline auth, claims, taxes, NPC traders, GUIs

First-party `yap-playerdata.jar` (`YaPPlayerData`) — shared MariaDB across **YaP Link** (or Velocity) backends running **YaP-Folia**.

Database setup (required)

See [MARIADB.md](#) and [YAPDB.md](#) — Docker MariaDB + shared `yap-db.jar` pool:

```
# Linux (preferred one-shot)
./scripts/db/ensure-db.sh --server-id lobby

# Windows PowerShell
.\scripts\windows\Start-MariaDB.ps1
.\scripts\windows\Configure-Db.ps1 -ServerId lobby
```

`YaPPlayerData` prefers the shared `YaPDB` pool (`use-shared-yapdb: true`). Multi-backend: same JDBC, unique `server-id`.

Session lock (double-login)

Always on. Prevents the same UUID being online on two backends at once:

- Acquire `lock_server` / `lock_until` on join; refresh on autosave; release on quit
- Contested lock → kick with holder server name
- Async pre-login rejects early when another server holds a live lock
- Stuck lock: `/yapdata unlock <player>`
- **Save path:** snapshot profile on main (or quit), `repository.saveProfile` on Bukkit async — I/O off main, apply stays sync

`lock-ttl-seconds` (default 120) auto-expires crashed holds.

Offline password auth (`/login`)

`AuthMe`-class for cracked / offline-mode servers (BCrypt hashes in `auth_accounts`):

Command	Who	What
<code>/register <pass> <pass></code>	player	create account
<code>/login <pass></code>	player	authenticate

Command	Who	What
/changepassword <old> <new>	logged-in	change hash
/logout	logged-in	clear session (must login again)
/unregister <player>	admin	delete auth row

Until logged in: frozen (no move/interact), no chat, no commands except auth. Inventory apply waits until success. Login timeout / max attempts kick.

Config (auth:)

```
auth:
  enabled: true
  force: false      # true = require /login even on online-mode
  trust-velocity: false # true = skip auth on Velocity modern-forwarding backends
  min-password-length: 4
  timeout-seconds: 60
  max-attempts: 5
```

- **Cracked offline server:** enabled: true, force: false, trust-velocity: false
- **Online-mode / Mojang:** auth auto-skips unless force: true
- **Velocity + modern forwarding:** set trust-velocity: true to skip passwords, or leave false / force: true if you still want /login

Session lock and password auth are independent: lock always runs; auth is optional via config.

Features (v0.6) — modular

Always on: session lock · inv/XP/vitals sync · /menu hub · /yapdata admin.

Area	Default	Config
Auth /login	on	auth.enabled
Economy /bal /pay /eco + native PlayerDataService	on	economy.enabled
Homes / warps / kits / mail	on	features.homes ...
Claims	on	features.claims (+ claims.*)
Shops / auctions (AH)	on	features.shops / auctions

Area	Default	Config
Jobs	off (keep off with YaPSkills)	<code>features.jobs</code>
NPC traders	off	<code>features.traders</code>
Backpack <code>/bag</code>	on	<code>features.backpack</code>

Money features require `economy.enabled: true`. When economy is off, shops/jobs/AH/traders and claim tax stay off even if their feature flags are true.

Native economy (no Vault required): first-party plugins use Bukkit `ServicesManager` → `PlayerDataService` (`balance` / `deposit` / `withdraw` / `setBalance`). `/sell`, minigame rewards, Tab `{balance}`, and `/yapmmo givemoney` all go through that API. Vault remains an **optional** bridge (`YaPEconomy`) only if you drop `Vault.jar` for third-party plugins.

```
# Default product features (economy on):
economy:
  enabled: true
features:
  homes: true
  warps: true
  kits: true
  mail: true
  shops: true
  jobs: false
  auctions: true
  claims: true
  traders: false
  backpack: true
backpack:
  default-pages: 3
  max-pages: 9
```

Freeze lifted: Essentials-class QoL lives in `yap-essentials.jar`. Playerdata stays the data/sync layer.

Area	What
Auth	<code>/register</code> <code>/login</code> · freeze until auth · BCrypt
Session lock	Cross-server dual-login kick · <code>/yapdata unlock</code>
Sync	Inv / XP / vitals · economy when enabled
Fancy GUIs	<code>/menu</code> hub (icons match enabled modules)
Claims	Shovel · subdivides · taxes (tax needs economy)

Area	What
NPC traders	<code>/trader</code> (opt-in; needs economy)
Homes/warps/kits/mail	Cross-server
Shops / AH	Chest shops (<code>/shop</code>) + auction house (<code>/ah</code>)
Backpack	<code>/bag</code> paged extra storage (45 slots/page). Vanilla E inventory stays 36. Optional Fabric <code>yap-bag</code> adds a keybind and inventory tabs.

Backpack (extra bag space)

The vanilla **E** inventory cannot grow from the server. `/bag` (aliases `/backpack` `/bp`) opens a double-chest GUI with **pages**. Bottom row is Prev / page tabs / Next. Contents live in MariaDB `player_backpack_pages` under the same `inventory-profile` as `inv/enderchest`, so they follow the player across backends.

Who	Pages
Everyone with <code>yapdata.bag</code>	<code>backpack.default-pages</code> (3)
VIP <code>yapdata.bag.pages.5</code>	5
Staff <code>yapdata.bag.pages.7</code>	7
Admin <code>yapdata.bag.pages.*</code>	<code>backpack.max-pages</code> (9)
Staff <code>yapdata.bag.see</code>	<code>/bag see <player> [page]</code>

Vanilla Java and Bedrock use the command `/ hub` icon. The optional **yap-bag** Fabric client (Minecraft 26.2) binds **B** and adds a Bag button on the inventory screen plus page tabs on the bag chest. Same items — the mod is not required.

Existing ranks: `ranks apply force` (or dashboard) so starter-grants pick up the new bag nodes.

Kits (EssentialsX-class)

Kits live in **YaPPlayerData**. `/createkit` captures inventory, armor, and offhand with full item data (enchants, names, components).

What	Where
Definitions	<code>plugins/YaPPlayerData/kits.yml</code> — same file on Hub + every survival backend
Cooldowns / uses	MariaDB <code>kit_cooldowns</code> (network-wide)
Store grants	MariaDB <code>kit_grants</code> via <code>kit grant <player> <kit></code>

What	Where
Access	<code>yapdata.kit.<id></code> / VIP <code>yapdata.kit.*</code> (YaPPerms)
First join	<code>first-join: true</code> on a kit (starter ships on)
Cost	<code>cost:</code> + economy balance
Signs	<code>[Kit]</code> line 1, kit id line 2

Player: `/kit` `/kits` `/showkit` · Admin: `/createkit` `/delkit` `/kitreset` · Console/store: `kit give` · `kit grant`.

Dashboard: **Gameplay → Kits** builds the same `kits.yml` (items, armor slot, cooldown, cost, first-join, commands).

Tebex on Hub: [TEBEX.md](#) · [examples/tebex/](#).

Plugin jar: `gradle :playerdata-plugin:installIntoPlugins` (also in `assembleRelease`).