

Regions & claim flags (Phase 11)

YaPcore ships **WorldGuard-class flags** on player claims (`yap-playerdata`) plus **staff admin regions** (`yap-regions.jar`).

Player claims — flags

Per-claim overrides persist in `yap_claim_flags` (MariaDB via YaPDB).

Flag	Default	Behavior
<code>pvp</code>	deny	Player vs player damage
<code>mob-damage</code>	allow	Mob damage to players
<code>build</code>	trust	Block place/break (explicit deny blocks all)
<code>interact</code>	trust	Doors, buttons, levers
<code>entry</code>	allow	Deny entry with move cancel
<code>chest-access</code>	trust	Container open
<code>fire-spread</code>	deny	Cancels fire spread into/from claim
<code>mob-spawning</code>	allow	Blocks natural mob spawns (spawners/eggs exempt)

```
/claim flag set pvp deny
/claim flag set entry allow
```

Defaults: `plugins/YaPPlayerdata/config.yml` → `claims.default-flags` .

Trust levels (`access` , `build` , `manage`) still apply when a flag is not explicitly set.

Admin regions — YaPRegions

Staff cuboids using YaPWorld selection (`/yapworld wand` , `pos1/pos2`):

```
/region define spawn
/region flag set spawn pvp deny
/region list
```

Tables: `yap_admin_regions` , `yap_admin_region_flags` .

API: `com.yapcore.regions.RegionService` on `ServicesManager` — lookup via `RegionServices.find()` .

Related

- [PLAYERDATA.md](#) — claims, trust, tax
- [PERMISSIONS.md](#) — `yapdata.claims.*`, `yapregions.admin`