

Velocity / YaP Link proxy support

YaPcore (Folia/Paper) is a **game backend**. The public edge is a **proxy**:

- **YaP Link** — YapLabs' **native Velocity-class proxy** ([YAP_LINK_NATIVE.md](#), phased)
- Stock Velocity — same forwarding contract (optional stand-in)

Quick setup (YaP Link)

```
./scripts/setup-velocity-forwarding.sh --enable
# sets game-authority=folia, velocity-enabled=true, velocity-online-mode=false
./scripts/start.sh
./scripts/start-yap-link.sh
# players → Link :25565 → Folia loopback
```

Smoke:

When Folia `proxies.velocity.enabled` is **false** (local default in some trees), Link still completes login without `velocity:player_info`. Enable forwarding for production multi-proxy as above. Game jar remains **YaP-Folia** (`folia-jar-source=build`) unless you explicitly switch to stock Fill (`fetch`).

Full Link docs: [YAP_LINK.md](#).

Quick setup (stock Velocity stand-in)

```
# From YaPcore root – creates forwarding.secret, wires config (does not enable yet)
./scripts/setup-velocity-forwarding.sh

# When Velocity is actually in front:
./scripts/setup-velocity-forwarding.sh --enable
# then restart YaPcore; players join Velocity only
```

1. YaPcore (`config/server.properties`)

```
velocity-enabled=true
# Prefer a file (same contents as Velocity's forwarding.secret):
velocity-secret-file=forwarding.secret
# Or inline (avoid committing secrets):
# velocity-secret=your-long-random-secret
```

```
# Must match Velocity's online-mode
velocity-online-mode=true

# Bind Paper to loopback so only the proxy on this host can reach the game port
velocity-bind-localhost=true

# Paper must not Mojang-auth when Velocity does (forced automatically when velocity-
enabled=true)
online-mode=false
```

On boot, YaPcore writes (Folia or Paper kernel dir):

File	Change
folia-kernel/ or paper-kernel/server.properties	online-mode=false, prevent-proxy-connections=false, optional server-ip=127.0.0.1
.../config/paper-global.yml	proxies.velocity.enabled=true + matching secret + online-mode
.../spigot.yml	settings.bungeecord=false (required — Bungee + Velocity modern conflict)

2. Velocity (velocity.toml)

```
[servers]
# Point at YaPcore's Paper JE port (default YaPcore port=25566)
lobby = "127.0.0.1:25566"

try = ["lobby"]

player-info-forwarding-mode = "modern"
# forwarding.secret file next to velocity.toml — same value as YaPcore
```

Put the same secret in Velocity's forwarding.secret and in YaPcore's velocity-secret / velocity-secret-file .

Example snippet: [examples/velocity/](#).

3. Restart both

1. Start YaPcore (./scripts/start.sh)
 2. Start Velocity
 3. Players join **Velocity's** public port — not YaPcore directly (when velocity-bind-localhost=true)
-

Config keys

Key	Default	Meaning
<code>velocity-enabled</code>	<code>false</code>	Sync Paper for Velocity modern forwarding
<code>velocity-secret</code>	<i>(empty)</i>	Inline secret
<code>velocity-secret-file</code>	<i>(empty)</i>	Path to secret file (preferred); overrides inline when set
<code>velocity-online-mode</code>	<code>true</code>	Must match Velocity <code>online-mode</code>
<code>velocity-bind-localhost</code>	<code>true</code>	Paper JE listens on <code>127.0.0.1</code> only

Missing secret with `velocity-enabled=true` **fails boot** (fail-closed).

Bedrock / Geyser

For networks, put **Geyser (+ Floodgate) on Velocity**, not as the public YaPcore Bedrock listener.

YaPcore does **not** need the Floodgate jar on the backend. Ship `yap-floodgate.jar` instead:

1. On Velocity: Geyser + Floodgate, `send-floodgate-data: true`, shared `key.pem`
2. Copy `key.pem` → `plugins/YaPFloodgate/key.pem` on YaPcore
3. Enable modern forwarding (same as above)

`yap-floodgate` decrypts the hostname Floodgate blob and/or recognizes `UUID(0, xuid)` players, exposing Bedrock XUID / link without the Floodgate plugin.

Typical behind-Velocity JE network:

```
bedrock-enabled=false
crossplay-enabled=false
velocity-enabled=true
```

If you still want YaPcore's built-in Bedrock on the same host, bind it separately and don't expose it as the main public join path while Velocity owns Java.

Native Bedrock UDP (no Velocity) already uses first-party `FloodgateAuth` with the same `UUID(0, xuid)` scheme.

ViaVersion / ViaBackwards / ViaRewind / Geyser

Do not use. Phase 4 DoD is **full** Via* + Geyser feature parity in YaPcore code ([CROSSPLAY.md](#)). Dropping those jars into `plugins/` is not the supported path.

Proxy networks that still run Via on Velocity for *other* backends are outside YaPcore's product surface; the YaPcore backend itself expects built-in remap.

Checklist

- [] Same forwarding secret on Velocity and YaPcore
 - [] `player-info-forwarding-mode = "modern"`
 - [] `velocity-online-mode` matches Velocity `online-mode`
 - [] `spigot.yml bungeecord: false` (YaPcore sets this when enabled)
 - [] Players connect to Velocity, not the backend port
 - [] Firewall: backend port not public when using localhost bind
-

Related

- [PLAYERDATA.md](#) — cross-server inventory / money sync (`yap-playerdata`)
- [NETWORKING.md](#) — domains / public ports
- [CROSSPLAY.md](#) — JE + BE
- [CLIENTS_AND_PACKS.md](#) — Paper authority path
- PaperMC: [Player information forwarding](#)