

Passwords & secrets (server owner guide)

Every credential in YaPcore is **operator-owned**. Shipped defaults use placeholders (`change-me` , empty webhooks). **Never commit** live `.env` , `forwarding.secret` , `key.pem` , or generated dashboard tokens.

Quick setup:

```
cp deploy/mariadb/.env.example deploy/mariadb/.env    # edit passwords first
./scripts/db/ensure-db.sh --server-id lobby            # writes JDBC from .env
./scripts/start.sh --fg                               # auto-generates dashboard token if empty
```

Where to set each secret

Secret	Set here	Dashboard?	Notes
MariaDB app password	deploy/mariadb/.env → <code>YAP_DB_PASSWORD</code>	No	<code>./configure-db.sh</code> copies into <code>plugins/YaPDB/config.yml</code>
MariaDB root password	deploy/mariadb/.env → <code>YAP_DB_ROOT_PASSWORD</code>	No	Docker only; change before exposing DB
JDBC password (fallback)	plugins/YaPPlayerData/config.yml → <code>jdbc.password</code>	No	Used only if YaPDB missing
Web dashboard token	<code>config/server.properties</code> → <code>web-dashboard-token</code>	Yes — Admin → rotate token	Auto-generated on first boot if empty
Minecraft OPs	<code>config/server.properties</code> → <code>ops</code>	Yes — Access & ranks	Comma-separated names
Velocity forwarding secret	<code>forwarding.secret</code> (repo root or link dir)	Partial — Network setup	<code>./scripts/setup-velocity-forwarding.sh</code>
YaP Link forwarding	<code>link-data/link.properties</code> → <code>forwarding-secret-file</code>	Yes — YaP Link tab	Points at <code>forwarding.secret</code>
Floodgate / Bedrock key	<code>floodgate-key.pem</code> or <code>key.pem</code>	No	Optional; offline UUID works without

Secret	Set here	Dashboard?	Notes
Discord webhooks	plugins/YaPDiscord/config.yml → webhooks.*	Yes — Discord tab	Paste webhook URLs
Discord inbound secret	plugins/YaPDiscord/config.yml → inbound.secret	Yes — Discord tab	Required when inbound enabled
Player auth passwords	plugins/YaPPlayerData/config.yml → auth.*	Partial — Player data tab	AuthMe-class; off by default on LAN
Folia RCON	folia-kernel/server.properties → rcon.password	No	Keep enable-rcon=false unless needed
Folia management API	folia-kernel/server.properties → management-server-secret	No	Leave empty; Folia generates locally

Recommended production order

1. Copy and edit `deploy/mariadb/.env` — **change both passwords** from `change-me` / `yaproot`.
 2. Run `./scripts/db/ensure-db.sh --server-id lobby`.
 3. Set `online-mode=true` (or Link + forwarding) in `config/server.properties` before going public.
 4. Enable PlayerData auth if using offline-mode public: `auth.enabled: true`.
 5. Start server once; copy the generated **dashboard token** from the log (or rotate in Admin tab).
 6. Set Discord webhooks before enabling relay; set a strong `inbound.secret` if enabling inbound HTTP.
 7. Run `./scripts/setup-velocity-forwarding.sh` when using YaP Link or Velocity in front of Folia.
-

What stays out of git

Enforced by `.gitignore`:

- `deploy/mariadb/.env` (not `.env.example`)
- `config/server.properties` (live operator copy)
- `link-data/link.properties`
- `forwarding.secret`, `*.pem`, `*.key`

- `plugins/**` live configs (seed from `config/defaults/` or jar defaults)
- Generated dashboard tokens in local trees

Tracked templates use placeholders only: `config/defaults/`, `*.example`, `deploy/mariadb/.env.example`.

Rotating credentials

Credential	How to rotate
Dashboard token	Web dashboard → Admin → rotate token (persists to <code>config/server.properties</code>)
DB password	Update <code>.env</code> , <code>ALTER USER</code> in MariaDB, re-run <code>./configure-db.sh</code>
Forwarding secret	Re-run <code>./scripts/setup-velocity-forwarding.sh</code> ; restart Link + backends
Discord inbound	Change <code>inbound.secret</code> in dashboard or YAML; update your Discord bot/webhook caller

Related

Doc	Topic
DEFAULTS.md	First-boot seed layout
MARIADB.md	Docker MariaDB setup
WEB_DASHBOARD.md	Token login, Admin tab
DISCORD_RELAY.md	Webhook + inbound setup
EDGE_HARDEN.md	Public exposure checklist