

MariaDB for YaP (shared YaPDB + PlayerData)

YaPcore does **not** embed a database engine. Owners run one MariaDB instance (packaged via Docker). `yap-db.jar` (**YaPDB**) owns the shared Hikari pool on each **YaP-Folia** backend; **YaPPlayerData** and other SQL plugins borrow it.

Works the same on **Linux** and **Windows**.

Recommended: Docker package

OS	Start	Configure	Stop
Linux / macOS	<code>./scripts/db/start-mariadb.sh</code>	<code>./scripts/db/ensure-db.sh</code> (or <code>configure-db.sh</code>)	<code>./scripts/db/stop-mariadb.sh</code>
Windows	<code>.\scripts\windows\Start-MariaDB.ps1</code>	<code>Configure-Db.ps1</code> / <code>Configure-PlayerData.ps1</code>	<code>Stop-MariaDB.ps1</code>
Release zip	<code>./start-mariadb.sh</code> / <code>.cmd</code>	<code>./configure-db.sh</code> / <code>configure-playerdata</code>	<code>./stop-mariadb.sh</code>

Requires [Docker](#) (Desktop on Windows).

Compose lives in `deploy/mariadb/`. First start copies `.env.example` → `.env`. If host **:3306** is already taken, `start-mariadb.sh` remaps to **3316** automatically.

One-shot (preferred)

```
./scripts/db/ensure-db.sh --server-id lobby
./scripts/start.sh --fg
```

`ensure-db.sh` starts MariaDB (if needed), writes JDBC into `plugins/YaPDB` + `plugins/YaPPlayerData`, and probes login before you boot.

For a custom home / smoke workdir:

```
./scripts/db/ensure-db.sh --root /path/to/yap-home --server-id lobby
```

Single server (same machine)

```
./scripts/db/start-mariadb.sh --configure --server-id lobby
# or: ./scripts/db/ensure-db.sh --server-id lobby
./scripts/start.sh --fg
```

JDBC points at `127.0.0.1` (port from `.env`). Shared config: `plugins/YaPDB/config.yml` .

Multi-backend / Velocity / YaP Link

1. Run MariaDB **once**.
2. On **each** game backend:

```
./scripts/db/configure-db.sh --host 192.168.1.10 --server-id lobby
./scripts/db/configure-db.sh --host 192.168.1.10 --server-id survival
```

Rules:

- **Same** JDBC URL / user / password on every backend (YaPDB + playerdata fallback)
- **Unique** `server-id` per backend (playerdata)
- Open firewall for `YAP_DB_PORT` only to backend IPs

Shared pool vs embedded

Jar	Role
<code>yap-db.jar</code>	Shared Hikari pool — install this for any SQL plugin
<code>yap-playerdata.jar</code>	Prefers YaPDB; embedded fallback if YaPDB missing

See [YAPDB.md](#) for the plugin API.

Without Docker

Install MariaDB/MySQL, create database/user matching `deploy/mariadb/.env.example` , then `configure-db.sh --host ...` .

Troubleshooting

Symptom	Fix
YaPDB disables on boot	<code>./scripts/db/ensure-db.sh --server-id <id></code> then restart; <code>./scripts/db/status-mariadb.sh</code>
Access denied for <code>yap@localhost</code>	Jar default is :3306 ; YaP Docker may be on 3316 . Re-run ensure/configure into the same home that boots (<code>--root</code>)
PlayerData uses embedded pool	Install <code>yap-db.jar</code> ; check <code>/yapdb status</code>
Multi-backend can't connect	Use LAN IP not <code>127.0.0.1</code>

Symptom	Fix
Port 3306 busy	Auto-bumped to 3316 on start; or set <code>YAP_DB_PORT</code> in <code>.env</code> and reconfigure

See also [YAPDB.md](#) · [PLAYERDATA.md](#) · [deploy/mariadb/README.md](#).