

Localhost joins + nginx

Same-machine Minecraft clients

On the PC running YaPcore, Direct Connect to:

```
127.0.0.1:25566
```

(or `localhost:25566`)

Do **not** use your public WAN IP or `yapcoremc.yaplabs.us` from the same machine — hairpin NAT often fails. LAN devices should use your LAN IP (Connect tab).

`allow-localhost=true` (default) keeps `bind-host=0.0.0.0` so loopback works. Sockets also set `SO_REUSEADDR`.

Server list vs join (log noise)

Handshake intent	Meaning	Log
1	STATUS (server-list ping)	Normal; connection closes after pong — not a join failure
2	LOGIN (actual join)	Real join path

Older builds logged STATUS closes as `JE JOIN FAILED`. Current builds only warn for real join aborts before PLAY.

Domain + Cloudflare

Production domain: `yapcoremc.yaplabs.us`.

Full checklist: [CLOUDFLARE_AND_NGINX.md](#)

DNS template: [deploy/cloudflare/dns-records.example](#)

Publicity overview: [NETWORKING.md](#)

nginx (public front)

Linux

```
./scripts/nginx-setup.sh --dry-run
sudo ./scripts/nginx-setup.sh
sudo ./scripts/nginx-setup.sh --install-pkg # also install nginx package
sudo ./scripts/nginx-setup.sh --uninstall
```

Windows

Same templates (`deploy/nginx/`). See [WINDOWS.md](#).

```
.\scripts\Nginx-Setup.ps1 -DryRun
$env:NGINX_HOME = "C:\nginx" # nginx.exe with stream module
.\scripts\Nginx-Setup.ps1
.\scripts\Nginx-Setup.ps1 -Uninstall
```

Templates: `deploy/nginx/` . Generated: `deploy/nginx/generated/` .

Path	Role
stream	Public TCP+UDP :25565 → 127.0.0.1:25566
http	Packs /pack/ → YaPcore :8081 (+ Cloudflare CF-Connecting-IP)

GUI **nginx** tab: save domain/ports, dry-run, or install with `sudo/ pkexec` .

Config keys

```
allow-localhost=true
nginx-public-port=25565
nginx-pack-port=80
nginx-domain=yapcoremc.yaplabs.us
server-domain=yapcoremc.yaplabs.us
public-host=yapcoremc.yaplabs.us
public-port=25565
public-bedrock-port=25565
public-pack-port=443
```

`nginx-setup.sh` falls back to `server-domain` / `public-host` when `nginx-domain` is empty.

After changing ports/domain

Restart the server so the boot banner and pack offers pick up new `public-*` / nginx values. Same-PC clients keep getting `http://127.0.0.1:8081/pack/...` automatically.