

Folia / Paper plugin compatibility

Default product path: Folia is the game (`game-authority=folia` , `folia-embed=true`). Drop **all** plugin jars into `plugins/` — one folder.

Kind	Loader
Folia-aware (<code>plugin.yml</code> / Folia APIs)	Real Folia (via <code>folia-kernel/plugins</code> → <code>../plugins</code>)
Paper / Spigot (<code>plugin.yml</code> / <code>paper-plugin.yml</code>)	Real Paper on legacy <code>game-authority=paper</code>
YaP next-gen (<code>yap.yml</code>)	YaP Compatibility Bridge
YaP modules (<code>module.yml</code>)	<code>modules/</code> (separate)

`folia-kernel/plugins` (and legacy `paper-kernel/plugins`) is a **symlink** to `plugins/` so the game and YaP share the same directory. On first start, jars left under an old real kernel `plugins/` are migrated automatically.

Curated matrix (Phase 16): [PLUGIN_COMPAT_MATRIX.md](#) — 50+ plugins with native replacements and dashboard badges.

Quick answer

Question	Answer
Will Folia-aware plugins work?	Yes — product path is Folia (same expectations as stock Folia)
Will LuckPerms / WorldEdit / Vault / most Paper plugins work?	Often no on Folia (same as stock Folia). Use Folia builds, or legacy <code>game-authority=paper</code> for Paper benches
Is Folia API coverage on product path?	Yes — real Folia owns the API
Is Paper API complete on Paper path?	Yes — legacy Paper authority (PAPER_API_COVERAGE.md)
Can 1.20-1.21 plugins run on 26.2?	Often on Paper path — Tier A+B rewrite (PLUGIN_BACKCOMPAT.md); Folia still needs Folia-aware jars
Can I use Folia-only plugins?	Yes on the Folia product path
Do I need two plugin folders?	No — only <code>plugins/</code>
Is every NMS/reflection plugin guaranteed?	No — same caveats as stock Folia/Paper

Where jars go

Jar type	Directory	Loader
Folia-aware	<code>plugins/</code>	Real Folia (default)
Paper / Spigot / Purpur-style	<code>plugins/</code>	Real Paper (legacy authority)
YaP next-gen (<code>yap.yml</code>)	<code>plugins/</code>	YaP facade
YaP modules (<code>module.yml</code>)	<code>modules/</code>	Module runtime
Phase 3 bridge (Paper benches only)	<code>yap-spatial-tick.jar</code> — not Folia product	Paper Phase 3
First-party Folia plugins	<code>YapSched</code> + <code>folia-supported: true</code>	Folia

```
gradle installProductDefaults # includes yap-perms.jar
./scripts/start.sh --fg
# Confirm enable in folia-kernel/logs/ or logs/server.log
```

YaP command access is permission-node based. Apply ranks:

```
ranks apply # after server start → yapperm applypack
/yapperm user Steve parent set vip
```

See [PERMISSIONS.md](#) · [examples/yapperms/](#) .

Layout: keep all jars in `plugins/` (Folia kernel symlinks to the same folder).

```
cp MyPlugin.jar plugins/
./scripts/start.sh --fg
```

What “within reason” means

Will work (in `plugins/` on Folia product path)

- Folia-aware plugins that work on **stock Folia 26.2**
- Vault / services / **built-in PlaceholderAPI** (`yap-placeholderapi.jar` , plugin name `PlaceholderAPI`) when Folia-compatible
- Normal schedulers / events that respect Folia’s region model
- YaP first-party jars shipped for the product path

Will work on legacy Paper path

- Standard Bukkit/Spigot/Paper plugins that work on **stock Paper 26.2**
- Most popular survival / minigame / chat / permission plugins

Maybe (same as Folia / Paper)

- Plugins pinned to an exact CraftBukkit / NMS mapping
- Plugins that reflect deep into Folia/Paper internals
- On **legacy Paper + Phase 3**: plugins sensitive to entity tick threading (rare; report if broken)

Will not

- Classic Paper-only plugins that assume a single main tick thread **on the Folia product path** (same breakage as stock Folia)
- Plugins that require a different Minecraft version than the pinned Folia/Paper

Dual loaders, one folder

Under Folia authority, **Folia** loads compatible `plugin.yml` jars; **YaP** loads only `yap.yml` jars from the same `plugins/` folder (no double-enable).

Under legacy Paper authority, **Paper** loads `plugin.yml` jars the same way.

When `game-authority` is neither Folia nor Paper, YaP's Compatibility Bridge may also load lightweight `plugin.yml` jars (soft-fail) — that path is not full Folia/Paper parity.

Facade feature (<code>yap.yml</code> / non-game authority)	Status
Soft-fail enable (one bad jar $\neq$ crash server)	Yes
Parent-first classloader isolation	Yes (limited)
Real world / entity / NMS depth	Use Folia (product) or Paper (legacy) + <code>plugins/</code>
Folia region schedulers	Supported on Folia product path

Details: [PLUGINS.md](#) · Brigadier/NMS notes: [BRIGADIER_NMS_EVENTS.md](#).

Phase 3 note (legacy Paper only)

With `game-authority=paper`, `paper-phase3-nms-tick=true`, and the YaP Paperclip, interior non-player entities tick on YapEngine cores 3–6. **Product defaults keep Phase 3 off.** Folia path does **not** run Phase 3 spatial tick. Almost all plugins on the Paper path keep using Bukkit/Paper APIs on the main thread as usual. If a plugin assumes **all** entity mutations

happen only on the single Paper main thread in ways that break under leased interior tick, treat it as a Phase 3 bug report — not “Paper incompatible.”

Verify

Put jars in `plugins/` and boot with `./scripts/start.sh --fg`.

Retired: Paperclip / Phase 3 vendor scripts were removed. Use `./scripts/fetch-folia.sh` and `./scripts/build-yap-folia.sh` on the Folia product path.

Also: [PLUGINS.md](#) · [YAPCORE_WHITEPAPER.md](#).