

Quick Start

Get a YaPcore server running in **under 10 minutes**. No nginx, no public domain, no plugin hunting — everything you need ships in the box.

Game jar: product default is **YaP-Folia** (`lib/yap-folia-*.jar` , `folia-jar-source=build`) — our Folia 26.2 fork, not stock Fill Folia. Build with `./scripts/build-yap-folia.sh` .

Requirements

Requirement	Notes
Java 25+	YaP-Folia 26.2 needs JDK 25 at runtime
8 GB RAM recommended	Default heap is 2 GB; raise <code>ram-mb</code> for production
Docker (optional)	Easiest path for MariaDB — MARIADB.md
Git (source path only)	Or download a release zip — RELEASES.md

License: YaPcore is [GPLv3](#) — [LICENSING.md](#).

Path A — Download a release (recommended)

Pre-built jars, plugins, packs, and launch scripts — no Gradle required.

If the release includes `lib/yap-folia-*.jar` , you’re on the product path. If missing:

```
./scripts/build-yap-folia.sh    # JDK 25+, Git, network (source tree)
# config/server.properties:
folia-jar-source=build
```

Stock Folia fallback (benches only): `folia-jar-source=fetch` + `./scripts/fetch-folia.sh` .

1. Download `yapcore-release-linux.zip` or `yapcore-release-windows.zip` built locally with `gradle publishReleasesFolder` (gitignored under `releases/`) or `gradle assembleRelease` → `build/dist/yapcore-release/` .
2. Extract and enter the folder:

```
unzip yapcore-release-linux.zip
cd yapcore-release/linux
```

3. Accept the Minecraft EULA (first run only):

```
echo "eula=true" > eula.txt
```

4. Seed shippable defaults (optional — `start.sh` also does this):

```
./scripts/seed-defaults.sh
```

5. Start MariaDB and wire JDBC (one command):

```
./configure-db.sh --server-id lobby
```

6. Start the server:

```
./start.sh --fg  
# or GUI: ./gui.sh
```

7. Open the web dashboard: **`http://127.0.0.1:8080/`** — paste the token printed in the console on first boot.

8. In console or dashboard, grant yourself OP and apply ranks:

```
op YourName  
ranks apply  
/yapperm user YourName parent set admin
```

9. Join from Minecraft:

Edition	Address
Java	<code>127.0.0.1:25566</code> (or port shown in boot banner)
Bedrock	same IP, same port (dual-stack UDP+TCP)

Path B — Build from source (developers)

```
git clone https://github.com/Xydroc-I0/YaPcore.git  
cd YaPcore  
chmod +x scripts/*.sh  
  
./scripts/build-yap-folia.sh      # YaP-Folia → lib/yap-folia-26.2.jar  
gradle installProductDefaults    # first-party plugins → plugins/
```

```
gradle shadowJar # yapcore.jar

./scripts/db/ensure-db.sh --server-id lobby
./scripts/start.sh --fg
```

Release tree (for distribution):

```
gradle assembleRelease
cd build/dist/yapcore-release/linux && ./start.sh --fg
```

Add gameplay plugins (vehicles, stacker, MMO):

```
gradle assembleRelease -PyapGameplay=true
```

What works out of the box

After `installProductDefaults` / a release zip, you get:

Jar	What it replaces
yap-perms.jar	LuckPerms — groups, tracks, prefixes
yap-chat.jar	Chat plugins — channels, PM, filter, staff chat
yap-moderation.jar	LiteBans / BanManager — ban, mute, warn, history
yap-essentials.jar	Essentials — spawn, tpa, fly, vanish, ...
yap-playerdata.jar	Cross-server data, offline <code>/login</code> , claims
yap-db.jar	Shared MariaDB pool for all SQL plugins
yap-packs.jar	Multi-active resource packs
yap-floodgate.jar	Bedrock identity without Floodgate jar
yap-placeholderapi.jar	PlaceholderAPI (built-in)
yap-lagguard.jar	Per-chunk lag-machine governor

Default rank ladder: `default` → `vip` → `mod` → `admin` (track `yap`). See [PERMISSIONS.md](#).

Default resource pack: **Faithful 64x** (+ vehicles overlay when gameplay tier enabled).

First-run checklist

Step	Command / setting
YaP-Folia jar	<code>lib/yap-folia-*.jar</code> present; <code>folia-jar-source=build</code>
Database	<code>./scripts/db/ensure-db.sh --server-id lobby</code>
Ranks	<code>ranks apply</code> (or set <code>yap-ranks-auto-apply=true</code>)
Your OP	<code>ops=YourName</code> in <code>config/server.properties</code> or <code>op YourName</code>
Dashboard token	Copy from console log → <code>http://127.0.0.1:8080/</code>
Production auth	Set <code>online-mode=true</code> before going public

Configuration profiles

Copy `config/server.properties.example` → `config/server.properties` and pick a profile.

Local / LAN (default)

```
internet-exposed=false
online-mode=false
allow-localhost=true
web-dashboard-localhost-only=true
game-authority=folia
folia-jar-source=build
```

Public production

```
internet-exposed=true
online-mode=true
public-host=play.example.com
public-port=25565
server-domain=play.example.com
web-dashboard-localhost-only=true
folia-jar-source=build
```

See [NETWORKING.md](#) · [CLOUDFLARE_AND_NGINX.md](#) · [EDGE_HARDEN.md](#).

Docker (MariaDB only)

YaPcore runs on the host JVM; Docker is provided for the **database**:

```
./scripts/db/start-mariadb.sh
./scripts/db/ensure-db.sh --server-id lobby
```

Compose: [deploy/mariadb/docker-compose.yml](#) .

Troubleshooting

Problem	Fix
"Java 25 required"	Install JDK 25+; <code>java -version</code>
YaP-Folia won't start	Run <code>./scripts/build-yap-folia.sh</code> ; check <code>lib/yap-folia-*.jar</code> and <code>folia-kernel/</code>
Stock Folia only	You set <code>folia-jar-source=fetch</code> — switch to <code>build</code> for product path
No DB connection	Run <code>ensure-db.sh</code> ; check Docker is running
Can't join Java	Check port in boot banner; firewall; <code>online-mode</code> vs client auth
Can't join Bedrock	<code>bedrock-enabled=true</code> ; same port as Java when <code>shared-listen-port=true</code>
Dashboard 401	Paste token from console log into login screen
No commands in-game	You need OP: <code>op YourName</code> or <code>ops=YourName</code> in config

More: [WIKI.md](#) · [PLUGIN_COMPAT.md](#) · [QUICK_START.md](#).

Next steps

Topic	Doc
YaP-Folia fork	QUICK_START.md
All commands	COMMANDS.md
Permissions & ranks	PERMISSIONS.md
Web dashboard	WEB_DASHBOARD.md
Multi-server proxy	YAP_LINK.md
Full doc index	WIKI.md