

Tebex / web store → YaPcore

Tebex's **plugin** is third-party (**GPLv3**). We can legally ship/redistribute it as a separate jar; we do **not** vendor it in git. Fetch the Folia build:

```
./scripts/fetch-tebex.sh          # → plugins/tebex.jar
# or: gradle fetchTebex
```

Notices: `third-party/tebex/`.

Dashboard setup (recommended)

Web admin → **Tebex store** (`GET/POST /api/tebex`):

1. Confirm `tebex.jar` is installed (fetch script above if missing).
2. Open creator.tebex.io → add a **Minecraft (Java / Folia) game server**.
3. Paste the **secret key** into the dashboard → **Save secret** (runs `tebex secret <key>` + writes `plugins/Tebex/config.yml`).
4. Optional: toggle `/buy` command name, proxy mode, verbose → **Save settings**.
5. Copy package console commands from the tab into Tebex packages (`{username}` placeholder).
6. Use **Store info** / **Force check** to verify delivery.

Also available under **Plugin editors** → Tebex (raw YAML).

Console setup (same result)

```
tebex secret <key>
tebex info
tebex forcecheck
```

Where to install

Place	Do this?
Hub / lobby Folia backend	Yes — <code>plugins/tebex.jar</code>
Survival / other backends	Optional
YaP Link / Velocity proxy	No for Bukkit console cmds (use Folia Hub)

Prefer **tebex-folia** ≥ 2.3.3 (Folia duplicate-command fix). `fetch-tebex.sh` pulls latest.

Rank packages (VIP)

YaPPerms uses shared MariaDB — one console command updates the whole network:

```
yapperm user {username} parent set vip
```

Package	Console command
Set VIP (primary)	yapperm user {username} parent set vip
Add VIP (keep other groups)	yapperm user {username} parent add vip
Remove VIP	yapperm user {username} parent remove vip

VIP starter pack already grants `yapdata.kit.*` (all kits). Run `yapperm applypack` once on first boot.

Kit packages (playerdata — not Essentials)

Kits live in `yap-playerdata` (`plugins/YaPPlayerData/kits.yml`). Copy the **same** `kits.yml` to Hub **and** every survival backend.

Goal	Console command
Unlock kit permanently	yapperm user {username} permission set yapdata.kit.adventurer true
Unlock VIP kit node	yapperm user {username} permission set yapdata.kit.vip true
Queue kit items (offline OK)	kit grant {username} vip
Give now (player online on Hub)	kit give {username} vip

`kit grant` writes to shared MariaDB; the next backend the player joins that has that kit in `kits.yml` delivers the items.

Example Tebex package: “VIP Rank”

Commands (Execute as console):

```
yapperm user {username} parent set vip  
kit grant {username} vip
```

Example package: “Adventurer Kit Unlock”

```
yapperm user {username} permission set yapdata.kit.adventurer true  
kit grant {username} adventurer
```

Checklist

1. Hub has CORE+NETWORK jars + `tebex.jar` (`./scripts/fetch-tebex.sh`).
2. Shared MariaDB (`use-shared-yapdb: true`).
3. Identical `plugins/YaPPlayerData/kits.yml` on Hub + survival.
4. Secret set via dashboard **Tebex store** or `tebex secret <key>` on Hub.
5. Packages use `{username}` — [examples/tebex/](#).

Related

[WEB_DASHBOARD.md](#) · [PERMISSIONS.md](#) · [COMMANDS.md](#) · [LICENSING.md](#) · [PLAYERDATA.md](#) · [YAP_LINK.md](#)