

Introduction to Networking

CAN201 – Week 4

Dr. Wenjun Fan & Dr. Fei Cheng

Lecture 4 – Transport Layer (1)

- **Roadmap**
  1. Overview: Transport-layer services
  2. Multiplexing and demultiplexing
  3. Connectionless transport: UDP
  4. Principles of reliable data transfer

Transport services and protocols

- Provide logical communication between app processes running on different hosts
- Transport protocols run in end systems
  - Send side: breaks app msg into segments, passes to network layer
  - Rcv side: reassembles segments into messages, passes to app layer
- Transport-layer protocols for Internet:
  - TCP and UDP



Transport vs. Network layer

- **Network layer: logical communication between hosts**
- **Transport layer: logical communication between processes**
  - Relies on, enhances, network layer services

Household analogy:

10 kids in Ann's house sending letters to 10 kids in Bill's house:

- Hosts = houses
- Processes = kids
- App messages = letters in envelopes
- Transport protocol = Ann and Bill who demux to in-house siblings
- Network-layer protocol = postal service

Internet transport-layer protocols

- **Unreliable, unordered delivery: UDP**
  - No-frills extension of "best-effort" network layer (internet protocol)
- **Reliable, in-order delivery: TCP**
  - Congestion control
  - Flow control
  - Connection setup
- **Services not available:**
  - Delay guarantees
  - Bandwidth guarantees



Feature	UDP	UDP-Lite	TCP	Multipath TCP	SCTP	DCCP	RUDP[a]
Packet header size	8 bytes	8 bytes	20–60 bytes	50–90 bytes	12 bytes[b]	12 or 16 bytes	14+ bytes
Typical data-packet overhead	8 bytes	8 bytes	20 bytes	?? bytes	44–48+ bytes[c]	12 or 16 bytes	14 bytes
Transport-layer packet entity	Datagram	Datagram	Segment	Segment	Datagram	Datagram	Datagram
Connection-oriented	No	No	Yes	Yes	Yes	Yes	Yes
Reliable transport	No	No	Yes	Yes	Yes	No	Yes
Unreliable transport	Yes	Yes	No	No	Yes	Yes	Yes
Preserve message boundary	Yes	Yes	No	No	Yes	Yes	Yes
Delivery	Unordered	Unordered	Ordered	Ordered	Ordered / Unordered	Unordered	Unordered
Data checksum	Optional	Yes	Yes	Yes	Yes	Yes	Optional
Checksum size	16 bits	16 bits	16 bits	16 bits	32 bits	16 bits	16 bits
Partial checksum	No	Yes	No	No	No	Yes	No
Path MTU	No	No	Yes	Yes	Yes	Yes	?
Flow control	No	No	Yes	Yes	Yes	No	Yes
Congestion control	No	No	Yes	Yes	Yes	Yes	?
Explicit Congestion Notification	No	No	Yes	Yes	Yes	Yes	?
Multiple streams	No	No	No	No	Yes	No	No
Multi-homing	No	No	No	Yes	Yes	No	No
Bundling / Nagle	No	No	Yes	Yes	Yes	No	?

More transport layer protocols

Lecture 4 – Transport Layer (1)

- **Roadmap**
  1. Overview: Transport-layer services
  2. Multiplexing and demultiplexing
  3. Connectionless transport: UDP
  4. Principles of reliable data transfer

多路复用

Multiplexing/demultiplexing

multiplexing at sender:

handle data from multiple sockets, add transport header (later used for demultiplexing)

解决(多路复用)

demultiplexing at receiver:

use header info to deliver received segments to correct socket



How demultiplexing works

- **Host receives IP datagrams**
  - Each datagram has source IP address, destination IP address
  - Each datagram carries one transport-layer segment
  - Each segment has source, destination port number
- **Host uses IP addresses & port numbers to direct segment to suitable socket**



TCP/UDP segment format

Connectionless demultiplexing (UDP)

- **Created socket has host-local port number:**

```
Socket = socket(AF_INET, SOCK_DGRAM)
Socket.bind(('', 12345))
```

- **When creating datagram to send into UDP socket, must specify:**
  - **Destination IP address**
  - **Destination port number**

```
clientSocket.sendto(msg,(server_name, server_port))
```

- **When host receives UDP segment:**
  - Checks destination port # in segment
  - Directs UDP segment to socket with that port #

IP datagrams with same dest. port #, but different source IP addresses and/or source port numbers will be directed to same socket at dest

Connectionless demux: example



Connection-oriented demux

- **TCP socket identified by 4-tuple:**
  - source IP address
  - source port number
  - dest IP address
  - dest port number
- **Demux: receiver uses all four values to direct segment to appropriate socket**

- **Server host may support many simultaneous TCP sockets:**
  - each socket identified by its own 4-tuple
- **Web servers have different sockets for each connecting client**
  - non-persistent HTTP will have different socket for each request

Connection-oriented demux: example



three segments, all destined to IP address: B,
dest port: 80 are demultiplexed to *different* sockets

Connection-oriented demux: example

Port 80相同不同于UDP到一个socket 进到不同的



three segments, all destined to IP address: B,
dest port: 80 are demultiplexed to *different* sockets

Lecture 4 – Transport Layer (1)

- **Roadmap**
  1. Overview: Transport-layer services
  2. Multiplexing and demultiplexing
  3. Connectionless transport: UDP
  4. Principles of reliable data transfer

UDP: User Datagram Protocol [RFC 768]

Feature:

- **Simple and straightforward**
- **Best effort**
- **Lost**
- **Connectionless**
  - No handshaking
  - Each UDP segment handled independently of others
    - Out-of-order to APP

乱序

- **UDP use:**
  - Streaming multimedia apps
  - DNS
  - …
- **Reliable transfer over UDP:**
  - Add reliability at application layer
  - Application-specific error recovery!

Fast but not comfortable and safe

Two Harleys with one big sofa & TV ….

Why not a car ?!

UDP: segment header



UDP segment format

length, in bytes of UDP segment, including header

校验值

why is there a UDP?

- No connection establishment (which can add delay)
- Simple: no connection state at sender, receiver
- Small header size
- No congestion control: UDP can blast away as fast as desired

Real UDP datagram



UDP: segment header



UDP segment format

4个不同内容

UDP checksum

- Goal: detect “errors” in transmitted segment

Sender:

- Treat segment contents, including header fields, as sequence of 16-bit integers
- Checksum: addition (one’s complement sum) of **pseudo header**, **UDP header** and **UDP data**
- Sender puts checksum value into UDP checksum field

Receiver

- Compute checksum of received segment
- Check if computed checksum equals checksum field value:
  - NO - error detected
  - YES - no error detected. But maybe errors nonetheless?



Pseudo-header



UDP Header + Data

Internet checksum: example

Example: add two 16-bit integers

```
   1  1  1  0  0  1  1  0  0  1  1  0  0  1  1  0
+  1  1  0  1  0  1  0  1  0  1  0  1  0  1  0  1
---------------------------------------------------
```

Internet checksum: example

Example: add two 16-bit integers

```
   1  1  1  0  0  1  1  0  0  1  1  0  0  1  1  0
+  1  1  0  1  0  1  0  1  0  1  0  1  0  1  0  1
-------------------------------------------------
                                                1
```

Internet checksum: example

Example: add two 16-bit integers

```
   1  1  1  0  0  1  1  0  0  1  1  0  0  1  1  0
+  1  1  0  1  0  1  0  1  0  1  0  1  0  1  0  1
-------------------------------------------------
                                          1  1
```

Internet checksum: example

Example: add two 16-bit integers

```
   1  1  1  0  0  1  1  0  0  1  1  0  0  1  1  0
+  1  1  0  1  0  1  0  1  0  1  0  1  0  1  0  1
-------------------------------------------------
                                    0  1  1
```

Internet checksum: example

Example: add two 16-bit integers

```
   1  1  1  0  0  1  1  0  0  1  1  0  0  1  1  0
+  1  1  0  1  0  1  0  1  0  1  0  1  0  1  0  1
-------------------------------------------------
                                   1  0  1  1
```

Internet checksum: example

Example: add two 16-bit integers

```
   1  1  1  0  0  1  1  0  0  1  1  0  0  1  1  0
+  1  1  0  1  0  1  0  1  0  1  0  1  0  1  0  1
-------------------------------------------------
                                1  1  0  1  1
```

Internet checksum: example

Example: add two 16-bit integers

```
   1  1  1  0  0  1  1  0  0  1  1  0  0  1  1  0
+  1  1  0  1  0  1  0  1  0  1  0  1  0  1  0  1
-------------------------------------------------
                                1  1  1  0  1  1
```

Internet checksum: example

Example: add two 16-bit integers

```
   1  1  1  0  0  1  1  0  0  1  1  0  0  1  1  0
+  1  1  0  1  0  1  0  1  0  1  0  1  0  1  0  1
-------------------------------------------------
                                0  1  1  1  0  1  1
```

Internet checksum: example

Example: add two 16-bit integers

```
   1  1  1  0  0  1  1  0  0  1  1  0  0  1  1  0
+  1  1  0  1  0  1  0  1  0  1  0  1  0  1  0  1
-------------------------------------------------
                                                  
   1  0  1  1  1  0  1  1
```

Internet checksum: example

Example: add two 16-bit integers

```
   1  1  1  0  0  1  1  0  0  1  1  0  0  1  1  0
+  1  1  0  1  0  1  0  1  0  1  0  1  0  1  0  1
-------------------------------------------------
1  1  0  1  1  1  0  1  1  1  0  1  1  1  0  1  1
```

Internet checksum: example

Example: add two 16-bit integers

	1	1	1	0	0	1	1	0	0	1	1	0	0	1	1	0
+	1	1	0	1	0	1	0	1	0	1	0	1	0	1	0	1
wraparound	1	1	0	1	1	1	0	1	1	1	0	1	1	1	0	1	1

Note: when adding numbers, a carryout from the most significant bit needs to be added to the result

Internet checksum: example

Example: add two 16-bit integers



Note: when adding numbers, a carryout from the most significant bit needs to be added to the result

Internet checksum: example

Example: add two 16-bit integers

		1	1	1	0	0	1	1	0	0	1	1	0	0	1	1	0
	+	1	1	0	1	0	1	0	1	0	1	0	1	0	1	0	1
wraparound		1	1	0	1	1	1	0	1	1	1	0	1	1	1	0	1	1
sum			1	0	1	1	1	0	1	1	1	0	1	1	1	1	0	0
checksum			0	1	0	0	0	1	0	0	0	1	0	0	0	0	1	1

(one's complement)

Note: when adding numbers, a carryout from the most significant bit needs to be added to the result




```
data = 'c0a80012' \
       '31072f31' \
       '00110020' \
       'f6fa01bb' \
       '0020' \
       '1c4353cdac605890fb00222b44524e7e408ecff72ac00fe7'

checksum = 0

while data != '':
    checksum += int(data[:4], 16)
    if checksum > 65565:
        checksum &= 0xFFFF
        checksum += 1
    data = data[4:]
    if len(data) == 2:
        data += '00'

checksum = 65535 - checksum

print('%x' % checksum)
```



Pseudo-header



UDP Header + Data

Lecture 4 – Transport Layer (1)

- **Roadmap**
  1. Overview: Transport-layer services
  2. Multiplexing and demultiplexing
  3. Connectionless transport: UDP
  4. Principles of reliable data transfer

Principles of reliable data transfer

- **Important in application, transport, link layers**
  - Top-10 list of important networking topics!



(a) provided service

Principles of reliable data transfer

- **Important in application, transport, link layers**
  - Top-10 list of important networking topics!



Principles of reliable data transfer

- **Important in application, transport, link layers**
  - Top-10 list of important networking topics!



- characteristics of unreliable channel will determine complexity of reliable

Reliable data transfer: getting started

- Incrementally develop sender, receiver sides of reliable data transfer protocol (rdt)
- Consider only unidirectional data transfer 仅考虑单向流动
  - But control info will flow on both directions!
- Use finite state machines (FSM) to specify 描述 sender, receiver



rdt1.0: reliable transfer over a reliable channel

- Underlying channel perfectly reliable
  - No bit errors
  - No loss of packets
- Separate FSMs for sender, receiver:
  - Sender sends data into underlying channel
  - Receiver reads data from underlying channel



sender



receiver

rdt2.0: channel with bit errors

- Underlying channel may flip bits in packet
  - Checksum to detect bit errors
- Question : how to recover from errors:

How do humans recover from "errors" during conversation?

rdt2.0: channel with bit errors

- **Underlying channel may flip bits in packet**
  - Checksum to detect bit errors
- **Question : how to recover from errors:**
  - *Acknowledgements (ACKs):* receiver tells sender that pkt received OK
  - *Negative acknowledgements (NAKs):* receiver tells sender that pkt had errors
  - sender retransmits pkt on receipt of NAK
- **New mechanisms in `rdt2.0` (beyond `rdt1.0`):**
  - Error detection
  - Receiver feedback: control msgs (ACK,NAK) rcvr->sender

rdt2.0: FSM specification





rdt2.0: operation with no errors



rdt2.0: Error scenario



rdt2.0 has a fatal flaw!

What happens if ACK/NAK corrupted?

- Sender doesn't know what happened at receiver!
- Can‘t just retransmit -> possible duplicate

Handling duplicates:

- Sender retransmits current pkt if ACK/NAK corrupted
- Sender adds ***sequence number*** to each pkt
- Receiver discards (doesn't deliver up) duplicate pkt

rdt2.1: sender, handles garbled ACK/NAKs



rdt2.1: receiver, handles garbled ACK/NAKs

rdt_rcv(rcvpkt) && (

sndpkt = make_pkt
udt_send(sndpkt)

rdt_rcv(rcvpkt) &&
not corrupt(rcvpk
has_seq1(rcvpkt)

sndpkt = make_pk
udt_send(sndpkt)

t_rcv(rcvpkt) && (corrupt(rcvpkt)

ndpkt = make_pkt(NAK, chksum)
dt_send(sndpkt)

dt_rcv(rcvpkt) &&
not corrupt(rcvpkt) &&
has_seq0(rcvpkt)

ndpkt = make_pkt(ACK, chksum)
dt_send(sndpkt)

udt_send(sndpkt)

rdt2.1: sender vs receiver: no error





rdt2.1: sender vs receiver: no error





rdt2.1: sender vs receiver: no error





rdt2.1: sender vs receiver: no error





rdt2.1: sender vs receiver: no error





rdt2.1: sender vs receiver: no error





rdt2.1: sender vs receiver: no error





rdt2.1: sender vs receiver: no error





rdt2.1: sender vs receiver: no error





rdt2.1: sender vs receiver: ACK corrupt





rdt2.1: sender vs receiver: ACK corrupt





rdt2.1: sender vs receiver: ACK corrupt





rdt2.1: sender vs receiver: ACK corrupt





rdt2.1: sender vs receiver: ACK corrupt





rdt2.1: sender vs receiver: ACK corrupt





rdt2.1: Discussion

Sender:

- seq # added to pkt
- Two seq. #'s (0,1) will suffice. Why?
- Must check if received ACK/NAK corrupted
- Twice as many states
  - State must "remember" whether "expected" pkt should have seq # of 0 or 1

Receiver:

- Must check if received packet is duplicate
  - state indicates whether 0 or 1 is expected pkt seq #
- Note: receiver can not know if its last ACK/NAK received OK at sender

rdt2.2: a NAK-free protocol

- Same functionality as rdt2.1, using ACKs only
  - instead of NAK, receiver sends ACK for last pkt received OK
    - receiver must explicitly include seq # of pkt being ACKed
- Duplicate ACK at sender results in same action as NAK: retransmit current pkt

rdt2.2: Sender, receiver fragments



rdt3.0: Channels with errors *and* loss

New assumption:

- **Underlying channel can also lose packets (data, ACKs)**
  - Checksum, seq. #, ACKs, retransmissions will be of help … but not enough

Approach

Sender waits "reasonable" amount of time for ACK

- **Retransmits if no ACK received in this time**
- **If pkt (or ACK) just delayed (not lost):**
  - Retransmission will be duplicate, but seq. #'s already handles this
  - Receiver must specify seq # of pkt being ACKed
- **Requires countdown timer**

rdt3.0 sender



rdt3.0 in action



(a) no loss



(b) packet loss

rdt3.0 in action



(c) ACK loss



(d) premature timeout/ delayed ACK

Performance of rdt3.0

- rdt3.0 is correct, but performance stinks 性能很差
- e.g.: 1 Gbps link, 15 ms prop. delay, 8000 bit packet:

$$D_{trans} = \frac{L}{R} = \frac{8000 \text{ bits}}{10^9 \text{ bits/sec}} = 8 \text{ microsecs}$$

1000B 或 1KB.

  - U_{sender}: utilization – fraction of time sender busy sending

$$U_{sender} = \frac{L/R}{RTT + L/R} = \frac{.008}{30.008} = 0.00027$$

1kB / 30ms

  - if RTT=30ms, 1KB pkt every 30 msec: 33kB/sec throughput over 1 Gbps link

1000 kB / 30 ≈ 33.33 kB/s.

- Network protocol limits use of physical resources!

rdt3.0: stop-and-wait operation



$$U_{sender} = \frac{L / R}{RTT + L / R} = \frac{.008}{30.008} = 0.00027$$

Question

- How to increase utilization?