



Xi'an Jiaotong-Liverpool University

西交利物浦大學

# INT305 Machine Learning

## Lecture 1

Sichen Liu


Department Intelligence Science

[Sichen.Liu@xjtlu.edu.cn](mailto:Sichen.Liu@xjtlu.edu.cn)

# Greetings!

---

- Welcome to INT305 Machine Learning!
- Graduated from Institute of Acoustics, Chinese Academy of Sciences
- Worked as an audio algorithm researcher at Tencent Video (Beijing)
- Research focus: Machine Listening



## Course Goals and Prerequisites

---

- We're going to learn:
  - Theory of Machine Learning
    - Machine Learning Problem
    - Optimization Problem
  - Machine Learning Algorithms
    - Learning Algorithms
    - Optimization Algorithms
  - Practical Machine Learning
    - Learning from Artificial and Real-World Data
- Assume solid foundation in programming and math
  - Python Programming, Linear Algebra, Probability, Vector Calculus

## Where to get Information ?

---

- Lectures and Labs
- Learning Mall Online
  - Announcements, Lecture and Labs materials, Readings and Links
  - **General Q&A Forum**
  - Coursework
  - Coursework with Lab practice
- Office hours
  - Siyue Yu: Friday 2-4pm @ SD553
  - Sichen Liu: Monday 1-3pm @ SD557.
  - **E-mail me before coming**

## Teaching Team and Schedule

---

- Teaching Assistants:
  - Xiaolei Wang
  - Shuo Jin
  - Poyang Zhang
  - Ruosen Liao
  - Yuexin Wang
- On-site
  - Lecture : Tuesday 9-11 am @ MA 104 / 6-8 pm @ MA 216
  - Lab: **Week 10**, Wednesday 6-8 pm / Friday 9-11 am @ IR112
- Textbooks
  - Bishop: Pattern Recognition and Machine Learning, by Chris Bishop.
  - Hastie, Tibshirani, and Friedman: The Elements of Statistical Learning

## Assessment

---

1. Coursework 1 : 15%
  - The coursework requires no lab practice.
  - Release: Week 4, Tuesday, 2025/10/07
  - Deadline: Week 5, Thursday, 2025/10/16
2. Coursework 2 : 15%
  - This coursework requires lab practice.
  - Release: Week 10, Tuesday, 2025/11/18
  - Deadline: Week 13, Thursday, 2025/12/11
3. Final Exam : 70%
  - Final Exam is the most important part for assessment. It will be an open book exam.

## This Course

---

- Supervised Learning
  - Nearest Neighbors
  - Decision Trees
  - Ensembles
  - Linear Regression
  - Logistic Regression
  - Neural Networks
  - SVMs
- Unsupervised Learning
  - K-means
  - Mixture models
- Basics of Reinforcement Learning

# Learning?

---

## What is learning?

*'The activity or process of gaining knowledge or skill by studying, practicing, being taught, or experiencing something.'*

Merriam Webster dictionary

*'A computer program is said to learn from experience  $E$  with respect to some class of tasks  $T$  and performance measure  $P$ , if its performance at tasks in  $T$ , as measured by  $P$ , improves with experience  $E$ .'*

Tom Mitchell



## What is machine learning?

---

- For many problems, it's difficult to program the correct behavior by hand.
  - Recognizing people and objects
  - Understanding human speech
- Machine learning approach: program an algorithm to automatically learn from data, or from experience.
- Why might you want to use a learning algorithm?

## What is machine learning?

---

- For many problems, it's difficult to program the correct behavior by hand.
  - Recognizing people and objects
  - Understanding human speech
- Machine learning approach: program an algorithm to automatically learn from data, or from experience.
- Why might you want to use a learning algorithm?
  - Hard to code up a solution by hand (e.g. vision, speech)
  - System needs to adapt to a changing environment (e.g. spam detection)
  - Want the system to perform **better** than the human programmers
  - Privacy/Fairness (e.g. ranking search results)

# What is machine learning?

---

Stats: statistics

ML: machine learning

- It's similar to statistics...
  - Both fields try to uncover patterns in data
  - Both fields draw heavily on calculus, probability, and linear algebra, and share many of the same core algorithms
- But it's not statistics!
  - Stats is more concerned with helping scientists and policymakers draw good conclusions; ML is more concerned with building autonomous agents.
  - Stats puts more emphasis on interpretability and mathematical rigor; ML puts more emphasis on predictive performance, scalability, and autonomy

## Relations to AI

---

- Nowadays, “machine learning” is often brought up with “artificial intelligence” (AI).
- AI does not always imply a learning based system.
  - Symbolic reasoning
  - Rule based system
  - Tree search
  - etc.
- Learning based system → learned based on the data → more flexibility, good at solving pattern recognition problems.

## Relations to Human Learning

---

- Human learning is:
  - Very data efficient
  - An entire multitasking system (vision, language, motor control, etc.)
  - Takes at least a few years 😊
- For serving specific purposes, machine learning doesn't have to look like human learning in the end.
- It may borrow ideas from biological systems, e.g., neural networks.
- It may perform better or worse than humans.

# What is machine learning?

---

- Types of machine learning
  - **Supervised learning:** **have** labeled examples of the correct behavior
  - **Reinforcement learning:** learning system (agent) interacts with the world and learns to maximize a scalar reward signal
  - **Unsupervised learning:** **no** labeled examples – instead, looking for “interesting” patterns in the data

## History of machine learning?

---

- 1957 – Perceptron algorithm (implemented as a circuit!)
- 1959 – Arthur Samuel wrote a learning-based checkers program that could defeat him
- 1969 – Minsky and Papert's book *Perceptrons* (Limitations of linear models)
- 1980s – Some foundational ideas
  - Connectionist psychologists explored neural models of cognition
  - 1984 – Leslie Valiant formalized the problem of learning as PAC learning
  - 1988 – Backpropagation (re-)discovered by Geoffrey Hinton and colleagues
  - 1988 – Judea Pearl's book *Probabilistic Reasoning in Intelligent Systems* introduced Bayesian networks

## History of machine learning?

---

- 1990s – the “AI Winter”, a time of pessimism and low funding
- But looking back, the '90s were also sort of a golden age for ML research
  - Markov chain Monte Carlo
  - Variational inference
  - Kernels and support vector machines
  - Boosting
  - Convolutional networks
  - Reinforcement learning
- 2000s – applied AI fields (vision, NLP, etc.) adopted ML
- 2010s – deep learning
  - 2010-2012 – neural nets smashed previous records in speech-to-text and object recognition
  - Increasing adoption by the tech industry
  - 2016 – AlphaGo defeated the human Go champion
  - 2018-now – generating photorealistic images and videos
  - 2020 – GPT3 language model
- Now – increasing attention to ethical and societal implications



# Machine learning in computer vision

Computer vision: Object detection, semantic segmentation, pose estimation, and almost every other task is done with ML.




Figure 4. More results of Mask R-CNN on COCO test images, using ResNet-101-FPN and running at 5 fps, with 35.7 mask AP (Table 1).



DAQUAR 1553  
What is there in front of the sofa?  
Ground truth: table  
IMG+BOW: table (0.74)  
2-VIS+BLSTM: table (0.88)  
LSTM: chair (0.47)



COCOQA 5078  
How many leftover donuts is the red bicycle holding?  
Ground truth: three  
IMG+BOW: two (0.51)  
2-VIS+BLSTM: three (0.27)  
BOW: one (0.29)

Instance segmentation

## Machine learning in speech processing

---

Speech: Speech to text, personal assistants, speaker identification...



## Machine learning in NLP

---

NLP: Machine translation, sentiment analysis, topic modeling, spam filtering.

### Real world example:


*The New York Times*

LDA analysis of 1.8M New York Times articles:

music band songs rock album jazz pop song singer night	book life novel story books man stories love children family	art museum show exhibition artist artists paintings painting century works	game knicks nets points team season play games night coach	show film television movie series says life man character know
theater play production show stage street broadway director musical directed	clinton bush campaign gore political republican dole presidential senator house	stock market percent fund investors funds companies stocks investment trading	restaurant sauce menu food dishes street dining dinner chicken served	budget tax governor county mayor billion taxes plan legislature fiscal

## Machine learning in Game play

---













# Machine learning in E-commerce

---

Inspired by your shopping trends




Related to items you've viewed [See more](#)



## Why this class?

---

2017 Kaggle survey of data science and ML practitioners: what data science methods do you use at work?



## ML workflow

---


### ML workflow sketch:

1. Should I use ML on this problem?
  - Is there a pattern to detect?
  - Can I solve it analytically?
  - Do I have data?
2. Gather and organize data.
  - Preprocessing, cleaning, visualizing.
3. Establishing a baseline.
4. Choosing a model, loss, regularization, ...
5. Optimization (could be simple, could be a Phd...).
6. Hyperparameter search.
7. Analyze performance & mistakes and iterate back to step 4 (or 2).

## Implementing machine learning systems

---

- You will often need to derive an algorithm (with pencil and paper), and then translate the math into code.
- Array processing (NumPy)
  - **vectorize** computations (express them in terms of matrix/vector operations) to exploit hardware efficiency.
  - This also makes your code cleaner and more readable!



A photograph of a piece of lined paper with the equation  $z = Wx + b$  handwritten in blue ink.

```
z = np.zeros(m)
for i in range(m):
    for j in range(n):
        z[i] += W[i, j] * x[j]
    z[i] += b[i]
```

$$z = W @ x + b$$



# Implementing machine learning systems

---

- Neural net frameworks: PyTorch, TensorFlow, JAX, etc.
  - automatic differentiation
  - compiling computation graphs
  - libraries of algorithms and network primitives
  - support for graphics processing units (GPUs)
- Why take this class if these frameworks do so much for you?
  - So you know what to do if something goes wrong!
  - Debugging learning algorithms requires sophisticated detective work, which requires understanding what goes on beneath the hood.
  - That's why we derive things by hand in this class!

## Nearest Neighbor

---

Preliminaries and Nearest Neighbor Methods

# Introduction

---


- Today (and for much of this course) we focus on **supervised learning**.
- This means we are given a **training set** consisting of **inputs** and corresponding **labels**, e.g.

Task	Inputs	Labels
object recognition	image	object category
image captioning	image	caption
document classification	text	document category
speech-to-text	audio waveform	text
⋮	⋮	⋮

# Input Vectors

---

What an image looks like to the computer:



## Input Vectors


---

- Machine learning algorithms need to handle lots of types of data: images, text, audio waveforms, credit card transactions, etc.
- Common strategy: represent the input as an **input vector** in  $\mathbb{R}^d$ 
  - **Representation** = mapping to another space that's easy to manipulate
  - Vectors are a great representation since we can do linear algebra!

## Input Vectors

---

Can use raw pixels:



Can do much better if you compute a vector of meaningful features.

## Input Vectors

---

- Mathematically, our training set consists of a collection of pairs of an input vector  $x \in \mathbb{R}^d$  and its corresponding **target**, or **label**,  $t$ 
  - **Regression**:  $t$  is a real number (e.g., stock price)
  - **Classification**:  $t$  is an element of a discrete set  $\{1, \dots, C\}$
  - These days,  $t$  is often a highly structured object (e.g. image)
- Denote the training set  $\{(x^{(1)}, t^{(1)}), \dots, (x^{(N)}, t^{(N)})\}$ 
  - Note: these superscripts have nothing to do with exponentiation!

## Nearest Neighbors

---

- Suppose we're given a novel input vector  $x$  we'd like to classify.
- The idea: find the nearest input vector to  $x$  in the training set and copy its label.
- Can formalize “nearest” in terms of Euclidean distance

$$\|x^{(a)} - x^{(b)}\|_2 = \sqrt{\sum_{j=1}^d (x_j^{(a)} - x_j^{(b)})^2}$$

### Algorithm:

1. Find example  $(\mathbf{x}^*, t^*)$  (from the stored training set) closest to  $\mathbf{x}$ . That is:

$$\mathbf{x}^* = \underset{\mathbf{x}^{(i)} \in \text{train. set}}{\operatorname{argmin}} \quad \text{distance}(\mathbf{x}^{(i)}, \mathbf{x})$$

2. Output  $y = t^*$


- Note: we don't need to compute the square root. Why?



## Nearest Neighbors: Decision Boundaries

---


We can visualize the behavior in the classification setting using a **Voronoi diagram**.



## Nearest Neighbors: Decision Boundaries


---

**Decision boundary:** the boundary between regions of input space assigned to different categories.



## Nearest Neighbors: Decision Boundaries


---



Example: 2D decision boundary

# Nearest Neighbors

---




[Pic by Olga Veksler]

- Nearest neighbors **sensitive to noise or mis-labeled data** (“class noise”).  
Solution?


## k-Nearest Neighbors

---



- Nearest neighbors **sensitive to noise or mis-labeled data** (“class noise”).  
Solution?
- Smooth by having k nearest neighbors vote.

# k-Nearest Neighbors



- Nearest neighbors **sensitive to noise or mis-labeled data** (“class noise”). Solution?
- Smooth by having  $k$  nearest neighbors vote.

Algorithm (kNN):

1. Find  $k$  examples  $\{x^{(i)}, t^{(i)}\}$  closest to the test instance  $x$
2. Classification output is majority class


$$y = \arg \max_{t^{(z)}} \sum_{i=1}^k \mathbb{I}(t^{(z)} = t^{(i)})$$

$\mathbb{I}\{statement\}$  is the identity function and is equal to one whenever the statement is true. We could also write this as  $\delta(t^{(z)}, t^{(i)})$ , with  $\delta(a, b) = 1$  if  $a = b$ , 0 otherwise.

## K-Nearest neighbors

---


$K = 1$



## K-Nearest neighbors

---

$K = 15$





## k-Nearest Neighbors

---


### Tradeoffs in choosing $k$ ?

- Small  $k$ 
  - Good at capturing fine-grained patterns.
  - May **overfit**, i.e. be sensitive to random idiosyncrasies in the training data.
- Large  $k$ 
  - Makes stable predictions by averaging over lots of examples.
  - May **underfit**, i.e. fail to capture important regularities.
- Balancing  $k$ 
  - Optimal choice of  $k$  depends on number of data points  $n$ .
  - Nice theoretical properties if  $k \rightarrow \infty$  and  $\frac{k}{n} \rightarrow 0$ .
  - Rule of thumb: choose  $k < \sqrt{n}$ .
  - We can choose  $k$  using validation set (next slides).

## k-Nearest Neighbors

---


- We would like our algorithm to **generalize** to data it hasn't seen before.
- We can measure the **generalization error** (error rate on new examples) using a **test set**.



## k-Nearest Neighbors

---

- $k$  is an example of a **hyperparameter**, something we can't fit as part of the learning algorithms itself.
- We can tune hyperparameters using a **validation set**:




- The test set is used only at the very end, to measure the generalization performance of the final configuration.

## Example: Digit Classification

---

- KNN can perform a lot better with a good similarity measure.
- Example: shape contexts for object recognition. In order to achieve invariance to image transformations, they tried to warp one image to match the other image.
  - Distance measure: average distance between corresponding points on *warped* images
- Achieved 0.63% error on MNIST, compared with 3% for Euclidean KNN.
- Competitive with conv nets at the time, but required careful engineering.



[Belongie, Malik, and Puzicha, 2002. Shape matching and object recognition using shape contexts.]

## Conclusions

---

- Simple algorithm that does all it work at test time – in a sense, no learning!
- Can control the complexity by varying  $k$ .
- Suffers from the Curse of Dimensionality.
- Next time: parametric models, which learn a compact summary of the data rather than referring back to it at test time.