



Source [5]
→ FROM
→ ROW
→ SHOW

Processing [6]
→ DISSECT
→ DROP
→ ENRICH
→ EVAL
→ GROK
→ KEEP
→ LIMIT
→ MV_EXPAND
→ RENAME
→ SORT
→ STATS ... BY
→ WHERE

Operators [7]
equality: ==
inequality: !=
less than: <
less than or equal: <=
larger than: >
larger than or equal: >=
→ IS NULL
→ IS NOT NULL
→ CIDR_MATCH
→ ENDS_WITH
→ IN
→ IS_FINITE
→ IS_INFINITE
→ IS_NAN
→ LIKE
→ RLIKE
→ STARTS_WITH

Functions		
Mathematical	String	Type conversion
→ ABS	→ CONCAT	→ TO_BOOLEAN
→ ACOS	→ LEFT	→ TO_DATETIME
→ ASIN	→ LENGTH	→ TO_DEGREES
→ ATAN	→ LTRIM	→ TO_DOUBLE
→ ATAN2	→ REPLACE	→ TO_INTEGER
→ CEIL	→ RIGHT	→ TO_IP
→ COS	→ RTRIM	→ TO_LONG
→ COSH	→ SPLIT	→ TO_RADIANS
→ E	→ SUBSTRING	→ TO_STRING
→ FLOOR	→ TRIM	→ TO_UNSIGNED_LONG
→ LOG10		→ TO_VERSION
→ PI	Date-time	Multivalue
→ POW	→ AUTO_BUCKET	→ MV_AVG
→ ROUND	→ DATE_EXTRACT	→ MV_CONCAT
→ SIN	→ DATE_FORMAT	→ MV_COUNT
→ SINH	→ DATE_PARSE	→ MV_DEDUPE
→ SQRT	→ DATE_TRUNC	→ MV_MAX
→ TAN	→ NOW	→ MV_MEDIAN
→ TANH		→ MV_MIN
→ TAU		→ MV_SUM
Aggregate	Conditional	
→ AVG	→ CASE	
→ COUNT	→ COALESCE	
→ COUNT_DISTINCT	→ GREATEST	
→ MAX	→ LEAST	
→ MEDIAN		
→ MEDIAN_ABSOLUTE_DEVIATION		
→ MIN		
→ PERCENTILE		
→ SUM		

Syntax Basics
source-command
processing-command1
processing-command2
FROM hosts
WHERE CIDR_MATCH(ip, "127.0.0.2/32")
FROM employees
KEEP first_name, last_name, height
EVAL fullname = CONCAT(first_name, " ", last_name)
FROM employees
WHERE first_name LIKE "?b?"
KEEP first_name, last_name
SORT first_name
FROM employees
KEEP first_name, last_name, hire_date
EVAL hired = DATE_FORMAT(hire_date, "YYYY-MM-dd")
ROW words = "foo:bar:baz:qux:quux:corge"
EVAL word = SPLIT(word, ";")

Supported field types		
◆ alias	◆ long	◆ double (float, half_float, scaled_float are represented as double)
◆ Boolean	◆ null	◆ keyword family including keyword, constant_keyword, and wildcard
◆ date	◆ text	◆ int (short and byte are represented as int)
◆ ip	◆ unsigned_long	◆ version

ES|QL Quick Reference Guide

Example

ROW a=[3, 5, 1, 6] EVAL avg_a = MV_AVG(a)															
a:integer				avg_a:double											
[3, 5, 1, 6]				3.75											
ROW a=[1,2,3], b="b", j=["a","b"] MV_EXPAND a															
a:integer		b:keyword		j:keyword											
1		b		["a", "b"]											
2		b		["a", "b"]											
3		b		["a", "b"]											
ROW language_code = "1" ENRICH languages_policy															
language_code:keyword				language_name:keyword											
1				English											
ROW a = "1953-01-23T12:15:00Z - some text - 127.0.0.1;" DISSECT a "%{Y}~%{M}~%{D}T%{h}:%{m}:%{s}Z - %{msg} - %{ip};" KEEP Y, M, D, h, m, s, msg, ip															
Y:keyword		M:keyword		D:keyword		h:keyword		m:keyword		s:keyword		msg:keyword		ip:keyword	
1953		01		23		12		15		00		some text		127.0.0.1	
FROM employees STATS count = COUNT(emp_no) BY languages SORT languages															
count:long								languages:integer							
15								1							
19								2							
17								3							
18								4							
21								5							
10								null							