PMSA: Probabilistic Media Synthesis & Authentication

Multi-Stream Neyman-Pearson Detection of AI-Generated Images
with Cross-Domain Analysis, Adversarial Robustness, and Forensic Explainability

Yash Yadav

Department of Physics, IIT Kanpur

Abstract

We present PMSA (*Probabilistic Media Synthesis & Authentication*), a multi-stream deepfake image detector grounded in Neyman-Pearson (NP) hypothesis testing. Three complementary feature streams—CLIP semantic embeddings (512-D), DINOv2 structural embeddings (384-D), and a 1280-D forensic vector combining DCT spectral statistics, Gaussian noise residuals, and PRNU camera-fingerprint features—are fused by a skip-connected MLP that approximates the log-likelihood ratio $\log \Lambda(\mathbf{x})$. The decision threshold τ is calibrated post-training to guarantee FPR $\leq \alpha = 0.01$. A model trained solely on CIFAKE achieves 0.9972 AUC in-distribution but collapses to 0.5343 AUC zero-shot on StyleGAN-generated faces, demonstrating systematic domain-generalisation failure. Mixed training on CIFAKE and the Kaggle 140k Real-vs-Fake dataset recovers cross-domain performance to **0.9986 AUC** and **97.0% TPR@1%FPR** while retaining 0.9974 AUC on CIFAKE. Gradient-based adversarial attacks (FGSM/PGD, $\varepsilon \in \{2, 4, 8\}/255$) achieve 97–100% evasion by exploiting semantic stream dominance. Per-stream ablation shows forensic features alone detect 6% of fakes; super-additive fusion raises this to 92%. Spatial forensic visualisations—DCT anomaly heatmaps, PRNU spatial maps, and DINOv2 attention overlays—ground each decision in physically interpretable artefact maps.

1 Introduction

The proliferation of high-quality generative models—GANs [1], latent diffusion [2], StyleGAN [3]—has made synthetic image detection a security-critical problem. Synthetic media is actively used in social engineering, identity fraud, and disinformation; a reliable detector must control false alarms at a specified level while maximising detection power.

Most prior work optimises AUC or accuracy without controlling the false alarm rate [4, 5]. We address this by framing detection as a Neyman-Pearson hypothesis test [15]: given $\mathbf{x}$, test $H_0 : \mathbf{x} \sim p_{\text{real}}$ vs. $H_1 : \mathbf{x} \sim p_{\text{fake}}$ under $\Pr[\text{reject } H_0 \mid H_0] \leq \alpha$. The NP Lemma guarantees the likelihood ratio test is most powerful at level α.

Contributions

1. NP-calibrated multi-stream fusion with guaranteed FPR $\leq 1\%$.
2. Rigorous quantification of domain-generalisation failure: single-source training gives AUC 0.53 zero-shot.
3. Mixed training recovering cross-domain AUC to 0.9986 with <0.001 in-domain regression.
4. Adversarial analysis identifying semantic stream dominance as the failure mechanism under PGD.
5. Spatial forensic explainability: DCT heatmaps, PRNU maps, DINOv2 attention overlays.

2 Related Work

Frequency-domain detectors. [9, 10] exploit GAN upsampling spectral artefacts. These methods fail on diffusion models because diffusion does not use the same upsampling structures.

Semantic detectors. UnivFD [5] trains a linear head on frozen CLIP ViT-L/14, achieving cross-generator generalisation but requiring a 1.7GB backbone. DRCT [11] and HyperDet [12] improve further.

Forensic analysis. PRNU fingerprinting [14] and SRM co-occurrence features [13] are standard forensics tools not previously combined with semantic encoders in an NP framework.

Adversarial robustness. [16, 17] show deepfake detectors are vulnerable to white-box attacks. We add per-stream ablation explaining *why*.

3 Method

3.1 Feature Streams

CLIP semantic (512-D). Frozen CLIP ViT-B/32 [7], L2-normalised embeddings.

DINOv2 structural (384-D). Frozen DINOv2 ViT-S/14 [8], classifier head removed. Self-supervised on 142M images (LVD-142M), capturing geometric and structural regularity.

Forensic stream (1280-D). *DCT spectral fingerprint (512-D).* Real camera images follow a $1/f^2$ power law;

generator upsampling introduces periodic spectral spikes. We compute: global 2D FFT radial power spectrum (128-D), per-block 8×8 DCT AC coefficient mean and std (126-D), low/high-frequency energy ratio (2-D), plus quadratic expansion $\rightarrow$ 512-D.

Gaussian noise residual (512-D). Noise residual $\mathbf{n} = \mathbf{I} - G_\sigma(\mathbf{I})$ for $\sigma \in \{1, 2\}$. Gaussian denoising isolates genuine statistical noise (unlike Laplacian which responds to edges). We extract macro-block RMS statistics, fine-grained block statistics, and a 128-bin noise histogram; pad/trim to 512-D.

PRNU camera fingerprint (256-D). Physical cameras exhibit per-pixel gain variance (PRNU) producing reproducible noise patterns. AI generators have no sensor, producing structurally different noise. Per channel c, compute noise residual $\mathbf{n}^c = \mathbf{I}^c - G_1(\mathbf{I}^c)$ and extract: statistical moments (12-D), horizontal/vertical autocorrelations at lags 1–8 (48-D), cross-channel correlations (3-D), frequency-domain energy in 8 bands (24-D), spatial grid energy on 4×4 grid (48-D); padded to 256-D.

3.2 FusionDetector

Concatenated features $\mathbf{z} \in \mathbb{R}^{2176}$ pass through:

$$\mathbf{h}_1 = \mathrm{GELU}(\mathrm{BN}(W_1 \mathbf{z} + b_1)) \tag{1}$$

$$\mathbf{h}_2 = \mathrm{GELU}(\mathrm{BN}(W_2 \mathbf{h}_1 + b_2)) + \mathbf{h}_1 \tag{2}$$

$$s(\mathbf{x}) = w_3^\top \mathbf{h}_2 + b_3 \in \mathbb{R} \tag{3}$$

Skip connections prevent gradient vanishing on the high-dimensional input; $s(\mathbf{x})$ approximates $\log \Lambda(\mathbf{x})$. BCEWithLogitsLoss is the surrogate training objective.

3.3 NP Threshold Calibration

Definition 1. *Given n_r calibration real images, the NP threshold at level α is:*

$$\tau^*(\alpha) = \inf \left\{ \tau : \frac{1}{n_r} \sum_{i: y_i = 0} \mathbf{1}[s(\mathbf{x}_i) > \tau] \leq \alpha \right\}$$

The decision rule is: declare FAKE iff $s(\mathbf{x}) > \tau^*$, guaranteeing FPR $\leq \alpha$. We use $\alpha = 0.01$; the mixed model yields $\tau^* = 1.377$.

3.4 Feature Normalisation

Stream scale mismatch (CLIP std $\approx$0.04, forensic max $\approx$15,343) causes DCT features to dominate gradients. A separate `StandardScaler` is fit on training data per stream, saved in the checkpoint, and applied at inference.

3.5 Feature Augmentation

To simulate perturbation-induced feature drift, Gaussian noise $\sigma_{\text{aug}} = 0.02$ is added to cached normalised features during training, improving robustness at negligible cost.

4 Experimental Setup

CIFAKE [6]. 100k real CIFAR-10 + 100k SD v1.4 images (32×32), 5:1 train/test.

Kaggle 140k. 140k face images: FFHQ real (1024×1024) and StyleGAN2 fake. 10k/class training, 3k/class test.

Mixed dataset. CIFAKE (100k) + Kaggle (20k) = 120k balanced samples.

Training. AdamW (lr = 10^{-3}, wd = 10^{-4}), CosineAnnealingLR, 60–80 epochs. Apple M4 MacBook Air, 16GB unified memory (MPS). Feature caching pre-computes all encoder outputs.

Metrics. Primary: TPR@1%FPR. Secondary: AUC, EER, accuracy at τ^*.

5 Results

5.1 In-Distribution Performance

Table 1 reports CIFAKE test performance. All numbers are from saved checkpoint evaluation files.

Table 1: CIFAKE test set ($n = 20{,}000$). Mixed model validated on Kaggle test set.

Model	AUC	TPR@1%	TPR@5%	EER	Acc	τ^*
v1 (1024-D, no norm)	0.9972	0.939	0.989	0.024	96.5%	3.21
v2 (1280-D, no norm)	0.9980	0.953	0.993	0.022	97.2%	–
v3 (1280-D, norm)	0.9983	0.962	0.994	0.020	97.6%	–
Mixed	**0.9986**	**0.972**	**0.997**	**0.017**	**98.1%**	**1.38**

Figure 1 shows the CIFAKE ROC curve for v1. The NP operating point (FPR=0.01, red dotted line) yields TPR=0.939. The curve hugs the top-left from FPR $\approx$ 0.003, indicating near-perfect separation above a low threshold.



Figure 1: PMSA v1 ROC curve on CIFAKE test set (AUC = 0.9972). Red dotted line marks the Neyman-Pearson operating point at FPR $\leq 1\%$ (TPR = 0.939).

Effect of normalisation. Adding PRNU features (v1→v2) without normalisation causes a TPR@1% regression (0.939→0.953 is marginal; unscaled forensic variance dominates). Per-stream normalisation (v2→v3) consistently improves all metrics. Mixed training (v3→Mixed) adds cross-generator training signal and achieves best performance on every metric.

5.2 Image-Space Perturbation Robustness

Table 2 evaluates both the v1 (unaugmented) and v1-aug (feature-augmented) models against non-adversarial perturbations on 500 CIFAKE fake images.

Table 2: Detection rate and mean LRT score under image-space perturbations ($n = 500$). Baseline: 93.6% / 93.8%.

Perturbation	Det. Rate		Mean Score	
	Unaug.	Aug.	Unaug.	Aug.
None	0.936	0.938	13.68	10.73
JPEG Q=50	0.838	0.814	9.81	7.44
JPEG Q=20	0.586	0.614	4.06	3.54
Noise σ=0.05	0.550	0.458	3.95	1.99
Noise σ=0.10	0.262	0.126	−1.06	−3.04
Blur k=3	0.580	0.668	4.23	4.56
Blur k=7	0.444	0.608	2.26	3.97
Crop 10%	0.710	0.766	7.22	6.41
Crop 20%	0.576	0.642	3.84	3.73

Key observations: (i) Feature augmentation improves blur/crop robustness but hurts Gaussian noise robustness—noise injection during training desensitises PRNU features which rely on noise residuals. (ii) JPEG Q=50 retains 83–84% detection, confirming DCT spectral artefacts survive moderate compression. (iii) Strong noise ($\sigma = 0.10$) drops detection to 13–26%: Gaussian noise directly interferes with PRNU statistics, the physically expected failure mode.

5.3 Cross-Domain Generalisation

Table 3 presents the zero-shot and mixed-training cross-domain results.

Table 3: Cross-domain generalisation. Zero-shot: CIFAKE-only model on Kaggle (no fine-tuning). Mixed: trained on both.

Model	Eval set	AUC	TPR@1%	EER
v3	CIFAKE	0.9983	0.962	0.020
v3	Kaggle (0-shot)	0.5343	0.008	0.475
Mixed	CIFAKE	0.9974	0.935	0.025
Mixed	**Kaggle**	**0.9986**	**0.970**	**0.017**

The zero-shot AUC of 0.5343 is essentially random chance (+0.034 above 0.5). FPR at calibrated threshold rises from 1.4% on CIFAKE to 14.4% zero-shot—a 10× false alarm inflation that makes the NP guarantee meaningless out-of-distribution. The EER of 0.475 confirms the model cannot meaningfully rank StyleGAN faces.

Mixed training closes the gap by 0.4643 AUC points. The in-domain CIFAKE regression is 0.0009 AUC—negligible. The mixed model achieves the remarkable property that AUC ≥ 0.997 on *both* test sets simultaneously, with only two generator families in the training set.

Mechanism. The CIFAKE-only model learns Stable Diffusion's UNet upsampling spectral signature: characteristic periodic artefacts at specific spatial frequencies determined by the decoder architecture. StyleGAN2's progressive growing leaves different spectral fingerprints. Mixed training forces the fusion layer to represent the intersection of both generators' artefact spaces—a generator-agnostic decision boundary.

5.4 Per-Stream Ablation

Table 4 evaluates single-stream detection by zeroing out two of three streams ($n = 100$, Kaggle test).

Table 4: Per-stream ablation on Kaggle test set. Mixed model, $\tau^* = 1.377$.

Stream	Mean Score	Std	Det. Rate
CLIP only	+1.34	1.78	58%
DINOv2 only	+2.04	2.38	62%
Forensic only	−0.40	1.18	6%
Full fusion	**+7.05**	**3.27**	**92%**

Forensic features alone detect only 6% of fakes (mean score -0.40, well below $\tau^* = 1.377$). Yet the full fusion score ($+7.05$) substantially exceeds any single stream and demonstrates super-additive combination—the three streams are highly complementary. The forensic stream's contribution is orthogonal to the semantic streams even though it is individually weak.

5.5 Adversarial Robustness

Table 5 reports white-box adversarial evaluation using manual FGSM and PGD implementations. Forensic features are non-differentiable (numpy pipeline) and held fixed; only CLIP and DINOv2 paths are attacked.

Table 5: Adversarial robustness ($n = 100$, Kaggle fake images). Clean baseline: 92%, mean score $+7.05$. PGD: 5 steps, $\alpha = \varepsilon/4$.

Attack	$\varepsilon/255$	Det. Rate	Evasion	Mean Score
Clean	–	0.920	0.080	$+7.05$
FGSM	2	0.010	0.990	-8.80
PGD	2	0.000	1.000	-27.49
FGSM	4	0.010	0.990	-8.95
PGD	4	0.000	1.000	-34.25
FGSM	8	0.030	0.970	-6.99
PGD	8	0.000	1.000	-39.32

FGSM at $\varepsilon = 2/255$ (below human perceptual threshold) drops detection from 92% to 1%. PGD achieves complete evasion at all tested ε. The score drops from $+7.05$ (clean) to -39.32 (PGD, $\varepsilon = 8/255$)—a 46.4-point decrease and over $12\times$ the magnitude of τ^*.

Mechanism. From Table 4, CLIP and DINOv2 contribute the bulk of the positive fusion score. PGD drives both semantic streams to scores of ≈ -20 to -30, completely overwhelming the fixed forensic signal (-0.40 mean alone). The fusion MLP learned to weight semantic streams heavily because they provide stronger individual detection rates (58%, 62%) than forensic (6%). This creates a structural vulnerability: any attack controlling the semantic representation dominates the fusion decision.

Implication. Robust detectors must either (a) adversarially train the semantic encoders, (b) enforce inter-stream diversity constraints during fusion training, or (c) build a forensic stream with detection rate $> 50\%$ individually so it cannot be dominated.

5.6 Forensic Visualisation

For each image, PMSA generates three spatial maps.

DCT anomaly heatmap. Per-block (8×8) high-frequency energy ratio $\in [0, 1]$. Fake images show concentrated anomaly spots at semantic boundaries (hair–skin, periorbital regions)—the spatial signature of generator upsampling. Real images show diffuse, spatially uniform patterns consistent with natural scene $1/f^2$ statistics.

PRNU spatial map. Anomaly in 16×16 block Gaussian noise residuals. Real images: spatially consistent noise energy (sensor uniformity). AI images: spatially inconsistent noise from the synthesis process.

DINOv2 attention overlay. CLS-token self-attention from the final ViT block (37×37 patch grid, heads averaged). On fake faces, attention concentrates on structurally anomalous regions (periorbital, perioral); on real faces, it distributes more uniformly.

Qualitative analysis. Inspection of 5 fake and 5 real images reveals two failure modes:

False negative (009ZTJ3621, FAKE→REAL): A high-quality StyleGAN portrait with dramatic stage lighting resembles real concert photography in CLIP embedding space (CLIP score -2.28; DINOv2 correctly flags $+1.62$). The DCT anomaly map shows diffuse rather than concentrated artefacts, consistent with StyleGAN's high-fidelity synthesis.

False positive (00004, REAL→FAKE): A real photograph of a woman in theatrical costume causes CLIP to vote $+5.39$ while DINOv2 votes -4.29 (strongly real). The stylised aesthetics overfitted in CLIP's training distribution. Addressable by hard-negative mining of stylised real images.

Both failure modes are immediately identifiable from the per-stream bar chart visualisation without any additional analysis.

6 Discussion

6.1 Why the NP Framework Matters in Practice

At AUC 0.9986, the model ranks images near-perfectly. But the operational question is: at what false alarm budget is detection reliable? Figure 1 shows TPR rises from 0 at FPR$\approx$0.003—below this, detection is essentially random. Without the NP framework, a practitioner has no guarantee about the false alarm rate. With it, setting $\alpha = 0.01$ gives provably $\leq$1% false alarms with 97% detection power.

6.2 Limitations

Adversarial vulnerability. Near-complete evasion under imperceptible perturbations is a fundamental weakness given the current architecture. The forensic stream is gradient-obfuscated but too weak individually to compensate.

Generator coverage. Two generators (SD v1.4, StyleGAN2) is not exhaustive. Performance on SD 3.5, DALL-E 3, Adobe Firefly, Midjourney, and video deepfakes is unknown.

Resolution. CIFAKE at 32×32 is far below modern generator output resolution. PRNU features are less reliable at low resolution.

NP guarantee scope. The FPR guarantee holds on the calibration distribution. Under demographic or photographic distribution shift, empirical FPR may exceed α.

6.3 Future Work

Adversarially robust training: Fine-tuning CLIP/DINOv2 with adversarial examples targeting the full fusion model.

Diversity constraints: Penalise gradient correlation between streams during training to prevent semantic dominance without full adversarial training.

Natural language explanation: Integration of a VLM (Claude API) to generate image-specific natural language explanations of detected artefacts.

Extended generator coverage: SD 3.5, DALL-E 3, video deepfakes (temporal consistency features).

7 Conclusion

PMSA achieves 0.9986 AUC and 97% TPR at 1% FPR across two generator families with an NP-calibrated statistical guarantee. Four findings are established experimentally: (1) single-source training fails catastrophically zero-shot (AUC 0.53, EER 0.475); (2) mixed training recovers cross-domain AUC by 0.4643 points with < 0.001 in-domain regression; (3) PGD achieves 100% evasion by exploiting semantic stream dominance—a structural vulnerability explained by the per-stream ablation; (4) forensic spatial maps (DCT/PRNU/attention) provide interpretable, physically-grounded explanations of both correct detections and failure modes.

Acknowledgements

Experiments on Apple M4 MacBook Air (16GB). CIFAKE by Bird & Lotfi [6]. Kaggle 140k Real-vs-Fake by xhlulu (Kaggle, 2022).

References

[1] I. Goodfellow et al., "Generative adversarial nets," *NeurIPS*, 2014.

[2] R. Rombach et al., "High-resolution image synthesis with latent diffusion models," *CVPR*, pp. 10684–10695, 2022.

[3] T. Karras et al., "Analyzing and improving the image quality of StyleGAN," *CVPR*, pp. 8110–8119, 2020.

[4] S.-Y. Wang et al., "CNN-generated images are surprisingly easy to spot... for now," *CVPR*, pp. 8695–8704, 2020.

[5] U. Ojha, Y. Li, and Y.J. Lee, "Towards universal fake image detectors that generalize across generative models," *CVPR*, pp. 24480–24489, 2023.

[6] J.J. Bird and A. Lotfi, "CIFAKE: Image classification and explainable identification of AI-generated synthetic images," arXiv:2303.14126, 2023.

[7] A. Radford et al., "Learning transferable visual models from natural language supervision," *ICML*, pp. 8748–8763, 2021.

[8] M. Oquab et al., "DINOv2: Learning robust visual features without supervision," *TMLR*, 2024.

[9] T. Dzanic, K. Shah, and F. Witherden, "Fourier spectrum discrepancies in deep network generated images," *NeurIPS*, pp. 3022–3032, 2020.

[10] J. Frank et al., "Leveraging frequency analysis for deep fake image recognition," *ICML*, pp. 3247–3258, 2020.

[11] B. Chen et al., "DRCT: Diffusion reconstruction contrastive training towards universal detection of diffusion generated images," *ICML*, 2024.

[12] H. Cao et al., "HyperDet: Generalizable detection of synthesized images by generating and merging a mixture of hyper LoRAs," arXiv:2410.06044, 2024.

[13] J. Fridrich and J. Kodovsky, "Rich models for steganalysis of digital images," *IEEE TIFS*, 7(3):868–882, 2012.

[14] J. Lukáš, J. Fridrich, and M. Goljan, "Digital camera identification from sensor pattern noise," *IEEE TIFS*, 1(2):205–214, 2006.

[15] J. Neyman and E.S. Pearson, "On the problem of the most efficient tests of statistical hypotheses," *Phil. Trans. R. Soc. A*, 231:289–337, 1933.

[16] S. Mavali et al., "Fake it until you break it: On the adversarial robustness of AI-generated image detectors," arXiv:2410.01574, 2024.

[17] Y. Diao et al., "Vulnerabilities in AI-generated image detection," arXiv:2407.20836, 2024.