

```

---
title: "Final project data"
format: html
editor: visual
---

```{r}
hair<-read.csv("C:/users/yosol/Downloads/Untitled form.csv",
 header = TRUE, stringsAsFactors = TRUE)
hair$age <- as.factor(hair$Age.Group.)
```

```{r}
head(hair)
```

```{r}
names(hair)<-
c('time','age','race','styled','styletype','hair1','hair2','hair3','hair4','hair5','hair6','hair7'
)
head(hair)
```

```{r}
converting categorical data into numerical likert scale
hair[] <- lapply(hair, gsub, pattern = "Neither Disagree nor Agree", replacement = 3, fixed =
TRUE)
hair[] <- lapply(hair, gsub, pattern = "Strongly Disagree", replacement = 1, fixed = TRUE)
hair[] <- lapply(hair, gsub, pattern = "Disagree", replacement = 2, fixed = TRUE)
hair[] <- lapply(hair, gsub, pattern = "Strongly Agree", replacement = 5, fixed = TRUE)
hair[] <- lapply(hair, gsub, pattern = "Agree", replacement = 4, fixed = TRUE)
head(hair)
tail(hair)

```

```{r}
#remove timestamp
hair<-hair[,-1]
hair
```

```{r}
#convert strings to numeric data
cols <- 5:11 # first number STARTS your likert scale; last number ENDS the scale
hair[,cols] <- sapply(hair[,cols], as.numeric)
hair
```

```{r}
hist(hair$hair7)
```

```{r}
nrow(hair)
```

```{r}
hair<-hair[-c(16,7),]
```

```{r}
hair[1:20,]
```

```{r}
hair$age <- as.factor(hair$age)
levels(hair$age)<-c('13-27', '28+', '28+')
```

```

```

```{r}
library(psych)
library(gplots)

plot(hair$age, main='Age')
summary(hair$age)

...

```{r}
hair.df<-with(hair, data.frame(hair1, hair2, hair3, hair4, hair5, hair6, hair7))
hair$hairemote<-rowMeans(hair.df, na.rm=T)
hist(hair$hairemote, xlim=c(1,5),main='Histogram of Hair emotions', xlab='Hair Depression Score'
)
describe(hair$hairemote)
summary(hair$hairemote)

...

```{r}
library(gplots)
hair$styled <- as.factor(hair$styled)
plot(hair$styled, main='Styled?')
summary(hair$styled)

...

```{r}
mod1<-lm(hairemote~age, data=hair)
plotmeans(hairemote~age, data=hair, main='Emotions Based on Age')
summary(mod1)
coef(mod1)

...

```{r}
mod2<-lm(hairemote~styled, data=hair)
plot<-plotmeans(hairemote~styled, data=hair, main='Emotions Based on Style Choice')
coef(mod2)
summary(mod2)
confint(mod2)

...

```{r}
mod3<-lm(hairemote~age+styled, data=hair)
plot(hairemote~age+styled, data=hair)
summary(mod3)
confint(mod3)

...

```{r}
confint(mod1)
confint(mod2)
alpha(hair.df)

...

```{r}
d <- hair #yuo will need to change your dataset to be called d

bucket <- array() #don't change
for(i in 1:1000){
  boot.sample <- d[ sample(1:nrow(d), nrow(d), replace=TRUE), ] #don't change this
  boot.mod <- lm(hairemote ~ age, data = boot.sample) # CHANGE DV AND IV
  bucket[i] <- coef(boot.mod)[2] #don't change this
}

...

```{r}
boot.mod <- lm(hairemote ~ styled, data = boot.sample) # CHANGE DV AND IV

```

```
bucket[i] <- coef(boot.mod)[2]
,,,
```