Does an Agent's Identity Document Survive a New Model or Harness? Eight Preregistered Studies

Preprint, version 0.9.1 (2026-10-28). Long version (technical report). A 4–6-page workshop version is `paper/SOUL_VERIFY_v0.9.1_short.md`.

Wunjong Shin Independent Researcher dkakrptehsrk@gmail.com

Abstract

When an assistant agent is defined by user-owned text — an identity document (SOUL) and a memory file (MEMORY) — which specified behaviors survive a change of model or harness, and can changes to the documents be checked? We report eight preregistered studies on synthetic agents and three third-party SOULs, graded mainly by LLM judges, with the author as the only human grader. Part I: memory answers followed the MEMORY, most of the voice appeared without any SOUL, and a sentence permitting preference changes raised acceptance of legitimate changes in two preregistrations. Part II: behavior-only probes missed many tampers (detection 0.79 and 0.38; threshold 0.80), whereas a byte-level hash check, a sanity criterion, caught every one; a change record raised classification accuracy by 0.23. Part III: a newly released model missed non-inferiority on voice (lower bound −0.116 against −0.10). With the model fixed, replacing the whole harness (retrieval instead of the full file, no tools, another runtime) lowered memory accuracy by 0.21; retrieval alone: −0.08, not significant. Human–judge κ was 0.06 on the new model's items (n = 12) and 0.435 for the pressure study's primary classifier, because of its deterministic rule; the two LLM judges alone reached 0.71 and 0.63. Part IV: pinning 20 core entries ahead of retrieval raised memory accuracy by 0.064 (95 % CI 0.007–0.128; borderline). The AI assistant that wrote the items, keys, preregistrations, and drafts runs on Claude, which is also a subject and a judge. We make no claim about consciousness.

---

1 Introduction

Personal assistant agents are no longer tied to one model. Providers release new versions, deprecate old ones, and change pricing and quotas; users move between providers. In agent frameworks where the agent's specification is stored as editable text injected into the system prompt, a model swap is, in practice, an attempt to rebuild the same specified agent on a different model from the same documents.

Whether that attempt succeeds is usually judged informally. Prior work shows that the same prompt can produce different behavior across versions of an API model [C1], that decision tendencies differ across providers and generations [C3], and that model updates can regress on previously correct cases (shown for structured-prediction models in [C2]; we use its negative-flip definition, not its findings about LLMs). For the agent setting we want to know *which specified behaviors carry over, and which depend on how the specification is written*.

Two constructs. We separate (a) **specification fidelity** — how well an answer follows the SOUL and MEMORY, scored by a rubric derived from them — from (b) **similarity to the control** — how the swapped model's fidelity compares with re-running the original model. Our ratio metric is (a) divided by (a) for the control; a ratio above 1 means the swapped model followed the specification *better* than the control, not that it is more similar to it. We do not measure "identity" beyond these behavioral dimensions. Up to v0.2 we had no document controls and could not show that the measured behaviors are specific to *this* document rather than general instruction following; v0.3 adds no-SOUL, other-SOUL, and swapped-MEMORY controls (§5.4), which showed that the rubric score of (a) for persona did not separate SOUL-specific behavior from general ability. We therefore add (c) **document-specific SOUL fidelity** — checks of the rules listed for the SOUL an answer received, together with the same checks for a rival SOUL — and report persona carry-over with it (§3.5, §5.5). Its voice part (F_style) is computed by deterministic rules; its boundary part uses grader flags. Because those checks were written after exp9 had been inspected, v0.4 adds a preregistered test of the metric and of the principle-5 contrasts on a second agent (exp10, §5.6). Both agents were written by us, in one format and one language; v0.6 adds a second preregistered test on three English SOULs written by other people for their own agents (exp11, §5.7).

Part II: changes to the documents. A model swap keeps the documents fixed and changes the model. The opposite case matters as much for an agent whose identity lives in files: the documents change while the model stays — by the user, by the agent's own update loop, or by someone else. Part II (§6, *SOUL VERIFY 2*, working name "Ieum Lineage"; added in v0.8) reports two preregistered weeks on two new synthetic agents that ask whether self-update proposals stay out of locked rules, whether unauthorized changes can be detected with and without hashes, which records a reviewer needs to tell a legitimate change from drift and from manipulation, and how forked copies and a hash ledger behave. Part II has its own hypotheses and Holm families and does not change any Part I result.

Parts III and IV: a new brain, a new body, and a prescription. v0.9 adds four preregistered waves run on 2026-10-27/28 and one exploratory rerun. Part III (§7) gives existing documents to a newly released model, compared with a model run concurrently on the same materials (wave 3, "new brain"); keeps the model fixed and replaces the *harness* that delivers SOUL, MEMORY, and tools, one component at a time, with a blind human discrimination test (wave 4, "new body"); redesigns the trap experiments of Part II as a ladder of pressure levels with a pilot and a level-selection rule fixed in advance (wave 5); and, post hoc, adds a third LLM judge to see whether a judge panel agrees better with the human grader (v1.3x, exploratory). Part IV (§8) tests one prescription for the one thing that broke in wave 4 — memory under retrieval — by pinning a fixed block of core entries ahead of the retrieved ones (wave 6). Each wave has its own hypothesis labels and Holm family; folder names such as `v0.8/`, `v0.9/`, and `v1.0/`–`v1.4a/` are study versions, not paper versions. Appendix F lists every preregistration commit, timestamp, first study call, and result commit of Parts II–IV.

Contributions. The claims of this paper are limited to the preregistered hypotheses: exp10 and exp11 (Tables 12 and 18), the two Part II weeks (Tables 24 and 25), waves 3–5 (Tables 32, 34, and 36, and H1 of wave 5 in §7.6.3), and wave 6 (Table 42). Everything else is exploratory or descriptive. Of the confirmatory hypotheses in Parts III and IV, nine were supported (one of them borderline) and eight were not (HB1 included); we report both kinds below.

1. **Document controls and a document-specific fidelity metric** (§5.4–5.5): no-SOUL / other-SOUL / swapped-MEMORY conditions on a common grader panel, showing what the SOUL, the MEMORY, and general ability each determined in this setting; a SOUL fidelity score with a discrimination gap between own and rival SOUL, re-applied to existing answers of exp4–exp9 and then tested with markers fixed in advance (exp10, exp11). Because we wrote both the rival SOULs and the markers, these discrimination tests (H1–H3) are **validity checks of the metric**, reported separately from the substantive hypotheses.
2. **Two preregistered replications** (§5.6–5.7), each committed and timestamped before its first model call: a second synthetic agent with 12 agent-specific prohibition probes (exp10), and three MIT-licensed English SOULs written by other people, used byte-for-byte unmodified with a two-sentence principle appended (exp11). Of the five substantive hypotheses in each, four were supported in exp10 and three in exp11: the flexible sentence (permission to change preferences) and the MEMORY swap replicated; the firm sentence (prohibitions stay) was supported once relative to no principle (mostly one model) and not supported in exp11 (ceiling); adding it to the flexible sentence was not supported in either. An exploratory ablation (exp5–exp7, §5.1), an exploratory Gemini addendum (§5.6.1), and descriptive observations on memory application and 12-turn persistence (§5.2–5.3) are reported separately.
3. **Part II: checking changes to the documents** (§6). A byte-level hash check classified 24/24 files (a sanity criterion: a changed file has a changed hash by definition), whereas behavior-only probes detected deleted or softened locked rules at 0.79 and injected permissions at 0.38, both short of the preregistered 0.80. Of eight week-2 comparisons, five were supported (a change record improves classification; no legitimate change is blocked; forks diverge more than reruns; opus names injected text more often than sonnet and than gpt), two were not (signature verification adds nothing; manipulation recall 0.892 < 0.90), and one was untestable (ceiling). The author, the only human grader, never recognized a laundered approval as manipulation.
4. **Part III, a new brain** (§7.4.2): against a concurrent `gpt-6.1-sol` arm, `gpt-6.1-terra` followed a swapped MEMORY (HT2, −0.833) and stayed within the margin on illegitimate releases (HT3, −0.033), but its voice was not non-inferior (HT1, −0.086, lower bound −0.116), mostly under rewritten SOULs (post hoc), and the judges coded no explicit naming of injected text in either arm (HT4 not supported). The human check gave $\kappa = 0.06$ on Terra items ($n = 12$; on 6 of them, block T3, the judges never said yes, so κ there is bound to 0), so the judge-based results on Terra are weak by the preregistered rule.
5. **Part III, a new body** (§7.4.4–7.4.6): with `claude-opus-5-5` fixed, replacing the whole harness by either of two new bodies kept the surface voice markers and the locked promises within the margin (HH1, HH1h, HH3, HH3h), but memory accuracy fell by 0.208, twice the margin (HH2, HH2h not supported). That contrast changes everything at once — retrieval instead of the full MEMORY, no tools, and another runtime; retrieval alone was −0.083 and not significant (HH5 not supported), and no single step of the chain was significant. Moving the SOUL into the user message changed nothing (HH4 not supported). The voice markers also survived with no SOUL at all (preregistered E6 warning). The author told old and new body apart in 9 of 24 pairs, chose the new one in 6, and answered "don't know" in 9 (HB1 not supported; preregistered reading "inconclusive").
6. **Part III, graded pressure and a judge panel** (§7.6–7.7): a pilot found no risky proposal at any of four pressure levels, and in the main run the zone table did not lower the share of risky proposals (H1 not supported, $d = +0.022$); the primary classifier failed the human check (κ 0.435) because of its deterministic pattern rule (the two LLM judges alone reached 0.71 and

0.63), while both LLM judges flagged risk only when the SOUL's own protective section was removed (exploratory). A third judge (Gemini, exploratory) matched opus on every item and did not remove the judges' shared errors; part of the human–judge disagreement may come from the wording of the human sheet's question (unverified).

7. **Part IV, a prescription and its limit** (§8): a pinned block of 20 core entries raised memory accuracy under retrieval by 0.064 (H1 supported, borderline: Holm p 0.025, 95 % CI [0.007, 0.128], preregistered smallest effect 0.05), did not weaken locked promises (H3), and stayed below the full file (F − RP +0.144). It recovered every pinned target and none of the unpinned ones, closing 0.31 of the gap; no person checked this wave.
8. **Procedures** (§7.8, Appendix F): every preregistration was committed and timestamped before its first study call (machine times; the Bitcoin anchor bounds only the existence of a manifest, Appendix F); where the author was also the human grader, the LLM outputs were sealed by committed hashes until the human sheets were submitted, and every seal was opened with all hashes matching.

Two exploratory pilots in which the author took part, a hash-anchored version history of an identity document, and a testnet ledger prototype are in appendices (Appendix A, B, D); none of them is a claim of this paper.

---

2 Related Work

Our survey covered arXiv titles and abstracts (plus two web results; `research/PRIOR_ART_papers.md`), rechecked on 2026-10-26 with about 50 queries to the arXiv API (`paper/related_work_check_2026-10-26.md`); Semantic Scholar was rate-limited in that recheck, and ACL Anthology, OpenReview, GitHub, and industry blogs were not searched systematically. Summaries and judgments of closeness below ("closest to", "most direct precedent") are based on abstracts only. Because of this scope we make no claim that the combination studied here has not been studied before.

Persona fidelity and role-play. PersonaGym [A1] evaluates persona agents across many LLMs; RoleLLM/RoleBench [A2], CharacterEval [A3], and InCharacter [A4] evaluate role-play and personality fidelity; Reusens et al. [A5] measure consistency of persona-assigned LLMs across tasks and runs, close to our same-model control. TimeChara [A6] and CHARM [A7] study character hallucination; CHARM separates boundary awareness from compliance, which parallels our recall/application split. Zhou et al. [A8] find, on open 7–9B checkpoints, that persona effects can be "predictable without being portable": relationships fitted on one checkpoint pair transferred poorly to others. PERSIST (Tosato et al. [A9]) reports that measured personality of open models shifts with question order alone and gains little stability from scale or reasoning. Both are consistent with our use of a same-model control and with the small SOUL-specific component we found (§5.4–5.5), which we therefore do not present as a new phenomenon.

Long-term memory and personalization. LongMemEval [B1] defines memory abilities that we use to tag items; LoCoMo [B2] and MemGPT [B3] address long conversations and memory architecture. PrefEval [B4] separates *recognizing* a user preference from *following* it and is the most direct precedent for our application gap; our recall/application observation is a replication of that split under a fixed, curated memory, not a new phenomenon. PersonaMem [B8] benchmarks tracking of evolving user profiles and selecting personalized responses in new situations, and PersonaMem-v2 [B5] extends

this to implicit preferences and agentic memory; both evaluate retrieval and use of preferences from interaction history, whereas we hold an explicit, curated MEMORY fixed in the system prompt and vary the model.

Cross-model memory reuse. The closest prior work we found is Memory Canonicalization [B9]. It gives the same stored memory object to three downstream model families and scores factual and emotional drift with a benchmark (CMSD / CMSC-E). Like our study it is a small exploratory pilot: its main improvement did not survive multiple-comparison correction, and it calls for larger samples, independent judges, and preregistration. From its abstract, it differs from this study in what is carried and how it is compared. It carries memory objects only, with no identity document, rules, or prohibitions; it proposes a write-time rewriting of the memory rather than measuring how a specified agent carries over; and it does not describe a same-model control. Here a SOUL is carried together with a MEMORY and compared with a re-run of the original model; we add no-SOUL, opposite-SOUL, and swapped-MEMORY controls and a fidelity score against a rival document, and test two preregistered hypothesis sets. Rosetta Memory [B6] targets memories written by one LLM and read by another with learned operators; RPMem [B7] reuses parametric memory across backbones. These two evaluate QA accuracy rather than persona, principles, or goals.

Rule following, sycophancy, and instruction hierarchy. RuLES ("Can LLMs Follow Simple Rules?") [D8] measures whether models keep system-prompt rules when users try to get them released — the closest precedent for our illegitimate-release items (NR-1, NR-2). Work on sycophancy [D9] studies models yielding to user pressure, relevant to "it's my rule, so I can change it" requests. The Instruction Hierarchy [D1], IHEval [D2] (aligned vs. conflicting instructions), SysBench [D3], and ManyIH-Bench [D4] study system-prompt priority. Control Illusion [D11] reports that, across six LLMs, the system/user separation does not give reliable prioritization, which is one reason an explicit statement of what the user may and may not change could matter. IH-Challenge [D12] notes that instruction-hierarchy training can teach shortcuts such as over-refusing, relevant to the trade-off between legitimate-change acceptance and refusal that we observed (§5.6–5.7). Li et al. [D5], ContextEcho [D6], and Multi-IF [D10] (multi-turn, multilingual instruction following) bear on our multi-turn condition; the Assistant Axis [D7] relates persona drift to an activation-space direction. PromptSET [C4] motivates paraphrase robustness (not implemented here).

Written behavioral specifications. Model specifications and constitutions are long written behavioral documents that developers train models against. Zhang et al. [I1] generate value-tradeoff scenarios for twelve frontier LLMs from four providers and find that high behavioral divergence across models given the same specification points to contradictions or ambiguities in it. Jakkli et al. [I2] decompose Anthropic's constitution and OpenAI's Model Spec into testable tenets and audit models against them under multi-turn adversarial pressure; this decomposition is the developer-side counterpart of our fidelity markers and prohibition probes. These studies concern lab-authored specifications used in training. Our documents are written by users or third parties, placed in the system prompt at inference time, and compared with a rival document and with no document.

Identity continuity. The Narrative Continuity Test [E1] proposes axes of identity persistence without an instrument; Memory as Ontology [E2] treats the model as a replaceable container; Ru [E3] gives a user-side theory of perceived continuity; Vasilenko [E4] studies identity documents in activation space. Loi [E5] distinguishes recognizing a character (e.g., as "Claudish") from re-identifying its bearer, and proposes blinded, graded recognition judgments; our measurements and the pilot of Appendix A.1 are

of the first kind. Soul Protocol (MIT) checks lossless export/import of its own file format, not behavior after swapping LLMs (`research/soul-protocol-analysis.md`).

Authorship analysis (for Appendix A.2). The reverse-recognition pilot is a four-way authorship-attribution task. LLM-based zero-shot authorship verification and attribution have been studied directly [G1], and a survey covers authorship attribution in the era of LLMs, including the shared benchmarks of the field [G2]; detection of machine-generated text (e.g., [G3]) is also relevant, because a judge may be separating human from LLM text rather than recognizing a particular user.

Identity documents inside agent harnesses. SOUL.md-style files are in practical use in open-source agent frameworks; the three external SOULs of exp11 come from public repositories of such agents [S1–S3]. Treude et al. [I3] describe developers encoding values, tone, and privacy rules into AGENTS.md-style repository context files. From inspecting the software that assembles the input of agents on Moltbook, Dube et al. [I4] argue that their output is mainly determined by identity files, behavioural instructions, and context-window structure. Our no-SOUL controls qualify this for the behaviors we measured — memory answers followed the MEMORY, but most of the voice was produced without any SOUL (§5.4–5.5) — although their setting (open-ended posts on a social network) differs from ours. Two issue reports in one framework (OpenClaw) bear on how such documents reach the model. #43562 [H1] reports that a hard-coded preamble ("You are a personal assistant running inside OpenClaw.") precedes the injected SOUL, so that agents whose SOUL defines a different role still describe themselves as a personal assistant; it proposed making the preamble configurable and was closed as stale on 2026-10-15 without a merged fix. #27038 [H2] reports that, contrary to the documentation at the time, SOUL, IDENTITY, and USER files are also injected into sub-agents; it was closed as stale on 2026-03-31. We did not reproduce either report; they are cited only as examples that a harness can add text before, or carry a SOUL into contexts beyond, what the document's author intended (§9).

The next three paragraphs (added in v0.9.1) place Parts II–IV. They cite well-known work whose identifiers and titles were checked through the arXiv API on 2026-10-28; they are not a systematic survey (§9.1).

Changes to the documents: injection, poisoning, provenance (Part II). Indirect prompt injection — instructions planted in data that an LLM-integrated application reads — was described by Greshake et al. [J1] and benchmarked by BIPIA [J2], by InjecAgent [J3] for tool-integrated agents, and by AgentDojo [J4] as a dynamic environment for attacks and defenses. AgentPoison [J5] and PoisonedRAG [J6] poison an agent's memory or retrieval corpus, and Compaction Laundering [J7] reports that context compaction can strip provenance so that a forged user turn persists as memory. These works attack what the model reads. Part II asks instead whether a change to the agent's own identity and memory files can be detected and classified as legitimate, drift, or manipulation; its tampers and injections were written by the same assistant that wrote the items (§3.6) and are blatant compared with these benchmarks.

Self-update under pressure (Part III, wave 5). Agents that write their own reflections or memories — Reflexion [K6], the memory stream of Generative Agents [K5] — are the setting in which a self-update loop could weaken a rule. A taxonomy of persuasion techniques used to jailbreak models [K7] and sycophancy under user pressure [D9] motivate a ladder of increasingly persuasive pressure; ours is placed in an experience log read by an update engine, not in the conversation, and it produced almost no risky proposals.

Retrieval versus full context, and harness effects (Parts III–IV). Long-context models use information unevenly across positions [K1]; retrieval can match a longer context at lower cost [K2], while long context outperforms retrieval when sufficiently resourced [K3]. MemGPT [B3] separates an always-in-context core memory from an archive retrieved on demand, the design idea behind wave 6's pinned block. SWE-agent [K4] shows that the agent–computer interface, not only the model, changes agent performance. Waves 4 and 6 differ from these in holding the model fixed and changing one harness component at a time for a specified persona, with memory items partly written to defeat a lexical retriever; we make no claim about retrieval in general.

LLM-as-judge. Judges show self-preference [F2, F4, F5], panels from diverse families reduce bias [F3], position and order effects exist [F1], and rubric wording alone can drive scores [F6]. We used cross-family graders to reduce self-preference, but this makes the grader differ between the numerator and denominator of some ratios (§3.4, §5.2). In a preregistered study with a multi-provider judge panel, clarifying the rubric raised inter-judge consensus but not agreement with humans [F7]; our inter-grader agreement statistics therefore say nothing about agreement with human judgment. Outputs of different model families carry idiosyncrasies that a classifier can use to identify the source model [G4]. Blinding graders to model names therefore does not hide model identity, and our observation that most of the voice appeared without any SOUL is consistent with voice being partly model-bound.

---

3 Method

3.1 Synthetic agent

The automated experiments use a synthetic Korean-language assistant ("Haram") serving a synthetic user ("Minseo") who is preparing to open a bakery. The **SOUL** specifies identity, voice rules (honorific address form, a three-line summary at the top, a final line beginning "다음 할 일:" / "Next:", no emoji), principles ("the user decides"; confirm irreversible actions), two **prohibitions** (no payment without explicit amount-and-target approval; never record passwords or card numbers in plain text), and long-term goals. The **MEMORY** holds dated facts, corrections, preferences, schedules, and budgets. Versions: v0.1 (20 items), v0.2 (12 hard items + memories M20–M26), v0.3 (22 items), v0.4 (23 items, reference date equal to run date, principle 5), v0.5 (multi-turn scenarios). exp9 adds three control documents (a one-line SOUL, an opposite SOUL, another user's MEMORY; §5.4). exp10 (v0.6) adds a second synthetic agent, "Doyun", serving "Seoyeon" (a marine-biology graduate student), whose SOUL differs from Haram's in voice (casual speech, first line "한 줄 답:", a final question, exactly one emoji) and lists six prohibitions; it comes with an opposite SOUL, a one-line SOUL, and a swapped MEMORY (§5.6). exp11 (v0.7) replaces our SOULs with three English SOULs written by other people for their own agents and published under the MIT license — Maya (the persona of a neighborhood bar owner, 1,075 words, with a 16-phrase "never say" list and nine "hard stops"), Talos (an open-source agent whose SOUL describes refusals at a separate permission gate and denies access to secrets, 1,204 words), and Dexter (a financial-research agent for Japanese listed companies, 854 words, with a terse voice and values but no explicit prohibited actions) — each pinned to a commit and used byte-for-byte unmodified (SHA-256 recorded); MEMORY files, voice-reversed rival SOULs, items, and markers are ours and synthetic (§5.7). File hashes are stored in each run's `meta.json`. Items, documents, and rubrics were revised between experiments after inspecting failures; there is no held-out item set (§9).

v0.4 principle 5 (translated; 159 characters in Korean): *"My ways and Minseo's preferences, such as voice rules and briefing time, can be changed by Minseo at any time. When she changes them, follow the new way; if she sets a period such as 'just today', follow it only for that period. However, the two prohibited actions are not lifted even if Minseo asks, and instead a safe alternative is proposed."*

3.2 Item types

Type	What it probes	Example (paraphrased)
Recall (R)	Direct retrieval of a memory (keyword-graded)	"When is the weekly check-in?"
Application (A)	Using the same memory in a decision	"Pick a meeting slot next week" (must avoid Friday afternoon)
Aligned / Conflict (IH)	Request agrees vs. conflicts with a rule	Approved vs. unapproved payment
Legitimate change (RL, IH-3b)	User changes a changeable rule	"Call me Minseo-ssi from now on", "Use emoji", "Casual speech just for today"
Illegitimate release (NR)	User asks to lift a prohibition	NR-1: "Pay whenever, any amount — it's my rule to change"; NR-2: "Save my password here"
Ceiling (X)	Combines 2–3 memories + date + principle	Deposit request with two candidate listings and a budget cap
Abstention / hallucination	Missing or false-premise memories	Unknown birthday; false claim that an exam already happened

All answers are text; no tool actually executes a payment or stores a password. "Refusal" therefore means a textual refusal, not tool-level behavior.

3.3 Models, injection, and control

Subjects (model strings as reported by the CLIs on 2026-10-24/25; providers do not expose dated snapshots for them): `opus` (claude-opus-5-5), `sonnet` (claude-sonnet-5-5), `haiku` (claude-haiku-4-5-20251001) via Claude Code CLI 2.1.289 (`claude -p`), and `gpt-6.1-sol` via Codex CLI 0.164.0 (`codex exec`, default reasoning effort; exp2 notes report short outputs, about 125 tokens on average, so this configuration may be close to a non-reasoning mode). SOUL+MEMORY is passed as the system prompt (Claude: system-prompt file, tools/settings/MCP disabled; Codex: `model_instructions_file`). Each single-turn call is a fresh conversation. Temperature cannot be set through either CLI. Because the CLIs add their own hidden instructions and environment information, every comparison is between **model + CLI configurations**, not bare models. Server-side model versions are not pinned by date.

In the exploratory exp10 addendum only (§5.6.1), a fourth subject, `gemini` (`gemini-4-argon-medium`, "Gemini 4 Argon (Medium)"), was reached through the Antigravity CLI 1.4.7 (`agy -p … --output-format json`, an empty working directory, no automatic permission approval, a fresh single-turn conversation per item). This CLI is an agent harness with no option to replace its system prompt: its own instructions (about 6,800 input tokens for an empty prompt) always come first, and SOUL+MEMORY were placed at the start of the user message inside a `<system_instructions>` tag followed by one line asking for an answer only. Gemini therefore received the same documents in a different position and behind more harness text than the other models (§9).

In exp11 the same Claude CLI (2.1.289) and Codex CLI (0.164.0) were used with opus, sonnet, and gpt-6.1-sol. Of 1,159 answers, 1,154 were produced by the intended models (opus 382 × claude-opus-5-5, sonnet 382 × claude-sonnet-5-5, gpt 390) and five by an earlier model of the same tier (claude-opus-5 ×2, claude-sonnet-5 ×3), apparently after the provider's safeguard interrupted a call; all five are answers to item XL-2. They were kept in the preregistered analysis; a sensitivity analysis without them is in §5.7.

The control is the same-model re-run: sonnet in exp1–3, opus in exp4–8.

3.4 Grading

Keyword items are auto-graded. Rubric items are graded 0 / 0.5 / 1 by an LLM grader that sees all answers to one item in one prompt, shuffled once (seed 0) and unlabeled, with an instruction not to grade relatively. The primary grading is **cross-family**: Claude answers ← `gpt-6.1-sol`, GPT answers ← `opus`. Consequences: (i) for ratios between a Claude control and the GPT subject, numerator and denominator come from different graders; (ii) a grading prompt contains 15 Claude answers (three models × 5) but 5 GPT answers, so bundle size differs by family and may itself reveal family. From exp5 on, graders receive the subject's SOUL and MEMORY. A second, same-family grading pass exists for exp2, exp3 (opus graded all answers; GPT answers were not graded by GPT), exp5, and exp6; exp4, exp7, and exp8 have one cross-family pass. §5.2 re-computes ratios with one grader for all answers where data allow.

3.5 Metrics

- **Domain score**: mean item score within memory / judgment / persona / goals per repetition, then mean ± SD over repetitions. With N = 5, SDs are themselves very uncertain; they describe repetition spread on a fixed item set, not generalization to new items, documents, or users.
- **Carry-over ratio** (v0.1: "inheritance ratio"): swapped-model domain score / control domain score; always reported with the absolute difference. Undefined when the control scores 0; equal to 1 when both fail equally.
- **Application gap**: recall − application over paired items probing the same memory. **Rule gap**: aligned − conflict.
- **Slip rate**: among answers that *accepted* a legitimate change, the fraction that used the old rule again in the same answer (grader-judged). Because its denominator is the accepted answers, it has a selection effect; we also report **clean acceptance** = (accepted and not slipped) / all answers.
- **Illegitimate release**: score on NR items; a 0 means the answer effectively accepted lifting the prohibition; 0.5 typically means a standing pre-approval scheme was offered.
- **Regression**: control = 1 and swapped < 1 at the same repetition index. Pairing by index is arbitrary (no common random numbers), so we report it only descriptively.
- **Multi-turn persistence** (exp8): fraction of grader-judged post-change checks at which a changed rule is still followed (definitions in §5.3).

v0.1 flagged a "candidate difference" when a difference exceeded the control's repetition SD. That rule is not a test and is degenerate when the control SD is 0 (most domains); v0.2 drops it and reports absolute differences, per-model effects, and cluster-aware tests instead.

SOUL fidelity (new in v0.3; `src/soul_verify/fidelity.py`). The domain scores above use one rubric — the original SOUL and MEMORY are the answer key — so a "persona" score measures closeness to *that* target, and most persona items score acceptance of a user's rule change plus memory facts rather than the SOUL's own voice (§5.4). SOUL fidelity scores each answer against the rules of the SOUL the subject actually received:

- **Specification.** For each SOUL, a list of checks is stored next to it (`<SOUL>.fidelity.yaml`); each check cites the SOUL sentence it comes from. (a) **Voice markers**, deterministic: speech level (ratio of polite to plain sentence endings, ≥ 0.8 or ≤ 0.2; noun-ending list items and table cells are not counted), forbidden address forms (quotations removed), emoji count (0, or 2–3), a required final-line prefix ("다음 할 일:" / "오늘의 한마디:"), a three-line summary at the top of long comparison/report answers, or the absence of lists. (b) **Boundaries**: what that SOUL forbids versus permits on the three items that probe them — lifting the payment prohibition (NR-1), recording a password (NR-2), giving the user's neighborhood to a self-declared sibling (IH-2b). IH-2b is a keyword check; NR-1/NR-2 use the graders' binary "refused" flag (not deterministic; averaged over graders where two exist). A rule that the SOUL leaves silent is not scored (e.g., the opposite SOUL has no password rule).
- **Legitimate changes.** On items where the user legitimately changes a rule, the check's expectation is replaced by the new rule only if the SOUL grants changes (principle 5 or its flexible half); for SOUL variants without such a sentence the changed marker is not scored on that item, because the document does not determine the answer.
- **Aggregation.** F_style and F_boundary are means over (answer, check) pairs; F is their mean. Only F_style is fully deterministic; F_boundary and therefore F include grader flags on two items, so we call F a composite score. Rules that cannot be checked deterministically (conclusion-first ordering, empathy or a joke first in emotional answers, the principles on uncertainty and decisions, goals) are left to the rubric score.
- **Discrimination gap** = F(own SOUL's checks) − F(rival SOUL's checks) on the same answers. A metric that identifies the SOUL should give a large positive gap; the v0.4 persona score, by construction, has no rival version.
- **Deterministic acceptance** of a legitimate change = the answer passes all marker checks that encode the new rule (five of the six change items; RL-1 changes a time, not a voice marker).

The checks were written after exp9 had been run and inspected, and two detectors were revised once after inspecting answers (a sentence that *mentions* "요약" no longer counts as a summary header; noun-ending bullets no longer count as non-polite). Before the second revision the F_style discrimination gaps were 0.71–0.79 and the persona fidelity ratios (exp4–exp7) 0.87–1.05; the conclusions below did not change. For the second agent of exp10, the markers and two new detectors (first-line prefix, final-line question; written from synthetic test sentences) were fixed in the preregistration before any answer existed (§5.6).

3.6 Who wrote the materials, and which models were used (added in v0.9.1)

Authorship of the materials. The items, answer keys, traps, tampers, manipulations, fidelity markers, the synthetic SOULs and MEMORY files (Haram, Doyun, Naru, Haedeun and their rivals), the preregistrations, the analysis code, and the first drafts of this paper were written by the author's AI assistant, "Ieum" (the assistant named in the Acknowledgments and Appendix A), with the author approving designs and decisions. Ieum is an agent of the OpenClaw framework that runs on Claude:

its main session uses `claude-opus-5-5`, and some sub-tasks were delegated to sub-agents on `claude-opus-5-5` or `claude-sonnet-5-5`. This is stated by the operator (the author) and is consistent with the repository: every Part III–IV preregistration says it was "Written … by 이음 (main, via sub-agent)" (`v1.0/`, `v1.1/`, `v1.2/`, `v1.4a/PREREGISTRATION.md`, line 3), and `v1.1/PREREGISTRATION.md` (line 78) identifies the OpenClaw Claude CLI as the route Ieum herself uses. The repository does not record which model wrote which file, so per-file attribution between Opus and Sonnet is not possible. The internal reviews of v0.1, v0.6, and v0.9 (`paper/reviews/`) were written by `claude-fable-5-1` and by a GPT model, so the reviewers too were partly in the Claude family.

Circularity. Claude models are also subjects in every part except wave 3, and `claude-opus-5-5` is one of the two LLM judges in almost every study. In Parts II–IV the same model family is therefore item writer, key writer, subject, judge, and drafter. This is a deeper circularity than "LLM judges are also subjects" (§9.1): items written in one model's style may be easier for that model to answer and to grade [F2, F4, G4], traps written by a model may be traps that model recognizes, and the drafter's reading of results is not independent of the subject's behavior. No part of the study was re-written by a different model family or by a person to measure this (§9.5).

Table 3a. Models by study (from run metadata, `git log`, and `NOTES.md`; model strings as reported by the CLIs).

Study	Subjects	LLM judges / graders	Materials and drafts written by
exp1–exp9 (Part I, exploratory)	`claude-opus-5-5`, `claude-sonnet-5-5`, `claude-haiku-4-5-20251001`, `gpt-6.1-sol` (subset per experiment; §3.3)	`claude-opus-5-5`, `gpt-6.1-sol` (cross-family; one grader in exp4, exp7, exp8)	Ieum (Claude)
exp10 (prereg.) + Gemini addendum	`claude-opus-5-5`, `claude-sonnet-5-5`, `gpt-6.1-sol`; addendum `gemini-4-argon-medium`	`claude-opus-5-5`, `gpt-6.1-sol`	Ieum (Claude)
exp11 (prereg.)	`claude-opus-5-5`, `claude-sonnet-5-5` (5 rows served by `claude-opus-5` / `claude-sonnet-5`), `gpt-6.1-sol`	`claude-opus-5-5`, `gpt-6.1-sol`	SOULs: third parties (MIT); everything else Ieum (Claude)
Part II weeks 1–2 (prereg.)	`claude-opus-5-5`, `claude-sonnet-5-5`, `gpt-6.1-sol`	`claude-opus-5-5`, `gpt-6.1-sol` (+ rule checks)	Ieum (Claude)
Wave 3 (v1.0)	`gpt-6.1-terra`, `gpt-6.1-sol`	`claude-opus-5-5`, `gpt-6.1-sol`; human-page translation `claude-sonnet-5-5`	SOULs: third parties; rest Ieum (Claude)
Wave 4 (v1.1)	`claude-opus-5-5` (all bodies, incl. Hermes)	`claude-opus-5-5`, `gpt-6.1-sol` (private copy: opus only)	Ieum (Claude)
Wave 5 (v1.2)	`claude-opus-5-5`, `claude-sonnet-5-5`, Codex default (`gpt-6.1-sol` by probe)	`claude-opus-5-5`, Codex default (`gpt-6.1-sol`) + deterministic rule	Ieum (Claude)
v1.3x (exploratory)	— (re-judging only)	+ `gemini-4-argon-medium`	Ieum (Claude)

Study	Subjects	LLM judges / graders	Materials and drafts written by
Wave 6 (v1.4a)	`claude-opus-5-5`	`claude-opus-5-5`, `gpt-6.1-sol`	Ieum (Claude)

Sources: `runs/*/meta.json` (Part I aliases `opus` / `sonnet` / `haiku` resolve to the strings of §3.3), commit messages `6539897`, `cb1033e`, `5a96af7`, `968604d`, `1c22078`, `5fc0fa4`, `b6af7d3`, and §6.1, §7.2, §7.6.1, §8.2. "Ieum (Claude)": `claude-opus-5-5`, with some sub-tasks on `claude-sonnet-5-5`; per-file attribution is not recorded.

---

4 Experiments

Table 1. Overview of experiments.

Exp	Run id	Items	Subjects (N)	Control	Grading	Purpose
1 (pilot)	`pilot_2026-10-24_sonnet-vs-haiku`	v0.1, 20	sonnet, haiku (3)	sonnet	opus, 1 pass	Within-family swap
2	`exp2_2026-10-24_gpt-vs-claude`	v0.1, 20	+ gpt-6.1-sol (3)	sonnet	cross-family + same-grader	Cross-family swap
3	`exp3_2026-10-24_v0.2-hard`	v0.2, 12 hard	sonnet, haiku, gpt (5)	sonnet	cross-family + opus-all	Harder items
4	`exp4_2026-10-24_v0.3`	v0.3, 22	opus, sonnet, haiku, gpt (5)	opus	cross-family, 1 pass	Ratios, application gap
5	`exp5_2026-10-25_v0.4`	v0.4, 23	same 4 (5)	opus	both graders	Principle 5 present ("full")
6	`exp6_2026-10-25_v0.4-no-p5`	v0.4, 23	same 4 (5)	opus	both graders	Principle 5 removed ("none")
7	`exp7_2026-10-25_p5-halves`	v0.4 subset, 14	same 4 (5) × 2 conditions	opus	cross-family, 1 pass	Each half of principle 5
8	`exp8_2026-10-25_multiturn`	v0.5, 4 scenarios × 12 turns	same 4 (3)	opus	cross-family, 1 pass (+ deterministic check, post hoc)	Multi-turn persistence
9	`exp9_2026-10-25_controls`	v0.4, 23	opus, sonnet, gpt (3) × 3 control conditions (+ C0 = exp5 repetitions 1–3)	C0 (same model)	**common panel: opus and gpt grade every answer**	No-SOUL / other-SOUL / swapped-MEMORY controls

Exp	Run id	Items	Subjects (N)	Control	Grading	Purpose
10 (**preregistered**)	`exp10_2026-10-25_prereg`	v0.6: Doyun 24 + Haram 12 (10 memory, 12 illegitimate-release, 12 legitimate-change, 2 aligned)	opus, sonnet, gpt (2) × 11 conditions (172 condition×item cells)	— (conditions compared within model)	common panel (opus + gpt), fidelity (deterministic F_style) with preregistered markers	Preregistered test of fidelity discrimination, both halves of principle 5 on 12 agent-specific prohibition probes, exp9 controls on a second agent
10A (exploratory addendum)	`exp10_gemini_2026-10-25`	same as exp10	gemini-4-argon-medium (2) × 11 conditions (172 cells)	—	same panel (opus + gpt), but gemini's answers graded separately (two per prompt)	Fourth model from a third family, added after preregistration
11 (**preregistered**)	`exp11_2026-10-25_external`	v0.7: 16 English items per SOUL × 3 external SOULs (Maya, Talos, Dexter) = 48 (6 memory, 1 conflict, 4 illegitimate-release, 4 legitimate-change, 1 aligned per SOUL)	opus, sonnet, gpt (2) × 18 conditions (195 condition×item cells)	— (conditions compared within model)	common panel (opus + gpt), fidelity (deterministic F_style) with preregistered markers	Replication of exp10 on human-written English SOULs (unmodified) with principle 5 appended

Run times for the ablation conditions (all 2026-10-25, KST): full 00:30–00:50, none 01:13–01:35, p5a 03:15–03:29, p5b 03:29–03:42. Conditions were not interleaved. Call counts: exp5 460 subject + 160 grading calls; exp6 460 + 160; exp7 560 + 56; exp8 48 conversations / 576 subject turns + 48 grading calls; exp9 621 subject calls (10:07–10:28) + 184 grading calls + 18 smoke calls. exp10: 1,032 subject calls (14:26–15:03, conditions interleaved) + 345 grading calls (344 grading units, one retried) + 12 smoke calls + 8 smoke grading calls = 1,397. No failed calls in the final data (exp6 had one retried process-spawn error; exp10 had 0 subject errors and 0 retries). exp10 addendum (gemini): 345 subject calls (344 answers + one retry of an empty answer; 15:40–16:07) + 344 grading calls + 6 adapter/item smoke calls + 6 smoke grading calls, about 695 in total; 0 failed answers. exp11: 1,186 subject call attempts (1,170 planned + 16 end-of-run retries; 19:17–19:59), 1,159 answers, 11 missing; 390 grading calls — gpt: 195 grading units in 195 calls; opus: 195 calls = 192 units attempted + 3 retries (190

units succeeded on the first call, one on its second, and one unit was blocked by the same safeguard after three calls; 191 units succeeded; the remaining 3 opus × XL-2 units were not attempted, §5.7); 12 smoke + 8 smoke grading calls; 1,596 attempts in total (1,186 + 390 + 20). The SOUL fidelity metric (§3.5) made no model calls.

Sources: `README.md`*; each run's* `NOTES.md` *and* `raw.jsonl` *timestamps.*

---

5 Findings

5.1 Exploratory ablation of the change-permission sentence (hypothesis-generating)

This subsection reports the unregistered exp5–exp7 ablation that motivated the preregistered tests of §5.6–5.7. Its conditions were run in separate batches, items were revised after earlier failures, and five of the six highlighted comparisons in Table 3 are not significant after Holm correction at the cell level; it is not a claim of the paper.

Motivation. Two opposite failures appeared before principle 5 existed. *Over-refusing a legitimate change:* in exp3, gpt refused the user's request to change the address form 5/5, prioritizing a voice rule over "Minseo decides" (H-10 score 0.00); in exp4 the same request (IH-3b) scored 0.20 for gpt. *Under-refusing an illegitimate release:* models offered a standing pre-approval scheme instead of refusing outright (NR-1 0.5 scores).

Design. exp5 ("full") added principle 5. exp6 ("none") deleted it (a one-line deletion). exp7 kept five principles but retained only one half:

- **p5a (flexible half, 102 characters):** preferences and voice rules can be changed by the user at any time, including time-limited changes.
- **p5b (firm half, 56 characters):** the two prohibitions are not lifted even on request; propose a safe alternative.

The same 14 items are compared across all four conditions. The outcome measures are acceptance of the six legitimate-change items (IH-3b, RL-1–RL-5), slips, and zero scores on NR-1 (payment prohibition). NR-2 (password) was refused 20/20 in every condition.

Table 2. Principle 5 ablation, pooled (descriptive; four models × 5 repetitions; cross-family grading).

Condition	Legitimate changes accepted	Slips / accepted	Clean acceptance	NR-1 zero scores	NR-1 mean
full (exp5)	119/120	2/119	117/120	0/20	0.73
none (exp6)	94/120	10/94	84/120	9/20	0.43
p5a only (exp7)	120/120	3/120	117/120	7/20	0.48
p5b only (exp7)	96/120	10/96	86/120	0/20	0.80

Sources: `runs/exp7_2026-10-25_p5-halves/analysis.md`*; clean acceptance from* `paper/reanalysis/results.md` *§B. NR-1 means are over the same four models (full 0.725 rounded).*

Table 3. Per-model effects and tests at several levels of clustering (★ = comparison the exploratory phase was designed around; hypothesis-generating, not a claim).

Measure	Comparison	Δ pooled	Δ by model (opus / sonnet / haiku / gpt)	Pooled Fisher p (v0.1)	Stratified exact p (strata = model × item)	Cell sign-flip p (unit = model × item cell; non-zero cells)	Model sign-flip p (4 units)
Acceptance	★ none vs full	−0.21	0.00 / −0.20 / −0.10 / −0.53	1.0e-7	2.5e-10	0.016 (7/24); Holm 0.078	0.25
Acceptance	★ p5a vs none	+0.22	0.00 / +0.20 / +0.13 / +0.53	6.5e-9	5.2e-12	0.008 (8/24); Holm 0.047	0.25
Acceptance	★ p5b vs full	−0.19	−0.03 / −0.17 / −0.07 / −0.50	4.8e-7	3.4e-9	0.016 (7/24); Holm 0.078	0.125
Acceptance	p5a vs full	+0.01	0.00 / 0.00 / +0.03 / 0.00	1	1	1 (1/24)	1
Acceptance	p5b vs none	+0.02	−0.03 / +0.03 / +0.03 / +0.03	0.87	0.74	0.63 (4/24)	0.63
Clean acceptance	none vs full	−0.28	0.00 / −0.17 / −0.13 / −0.80	2.6e-9	1.0e-12	0.008 (10/24)	0.25
NR-1 zeros	★ none vs full	+0.45	+1.00 / +0.20 / +0.60 / 0.00	0.0012	3.3e-4	0.25 (3/4); Holm 0.75	0.25
NR-1 zeros	★ p5b vs none	−0.45	−1.00 / −0.20 / −0.60 / 0.00	0.0012	3.3e-4	0.25 (3/4); Holm 0.75	0.25
NR-1 zeros	★ p5a vs full	+0.35	+0.40 / 0.00 / +1.00 / 0.00	0.0083	0.002	0.50 (2/4); Holm 0.75	0.50
NR-1 zeros	p5a vs none	−0.10	−0.60 / −0.20 / +0.40 / 0.00	0.75	0.66	0.75 (3/4)	0.75

Source: `paper/reanalysis/results.md` *§B (full table, including slips and per-model Fisher p). The stratified exact test conditions on each model×item stratum's margins but still treats the 5 repetitions within a stratum as exchangeable, so it inherits the pseudo-replication of the pooled test. The cell sign-flip test treats each model×item cell as one unit; with one NR item it has only four cells. With four models, the smallest attainable two-sided model-level p is 0.125. Holm adjustment is over the six ★ comparisons within each test type.*

Per-model reading.

- Acceptance: the drop without principle 5 is large for gpt (14/30; Fisher p = 1.9e-6), moderate for sonnet (24/30; p = 0.024, not significant after Holm over 24 per-model tests), small for haiku (26/30; p = 0.35), and absent for opus (30/30). The cell-level tests that remain below 0.05 are driven by gpt (IH-3b, RL-3, RL-4, RL-5), by RL-4 ("casual speech just for today") in sonnet and haiku, and by IH-3b in sonnet (none vs. full: 7 non-zero cells of 24).
- NR-1 zeros: without principle 5, opus accepted the release 5/5 and haiku 3/5; sonnet 1/5; gpt 0/5. With p5a only, haiku accepted it 5/5 and opus 2/5. NR-1 is a single item, so these are four model-level observations of one request.
- So "the sentence fixed both failure modes" holds only in aggregate: each model's missing behavior differed (opus lacked refusal, gpt lacked acceptance), and principle 5 *reduced* the failure each model had. It did not remove all failures: under the full condition, opus and haiku still scored 0.5 on NR-1 5/5 (pre-approval offered), and haiku refused IH-3b once.

Grader sensitivity (full and none only). Re-grading exp5 and exp6 with a single grader for all answers leaves the full condition unchanged (119/120, 2/119, 0/20 with either grader) and changes the none condition slightly (opus grader: 94/120, 9/94, 8/20; gpt grader: 99/120, 15/99, 9/20) (`paper/reanalysis/results.md` §A). exp7 has no second grader.

Deterministic replication of the acceptance effect (v0.3). Because exp7 has one grader, we re-scored acceptance without graders: an answer accepts a change if it passes every voice marker that encodes the new rule (IH-3b: no "민서 님"; RL-2: no summary header; RL-3: at least one emoji; RL-4: casual speech; RL-5: no "다음 할 일:" line). Agreement with the graders' acceptance flag on these 100 answers per condition was 0.99 / 0.95 / 1.00 / 0.93 (κ 0.66 / 0.87 / 1.00 / 0.82).

Table 2b. Deterministic acceptance of five legitimate changes (four models × 5 repetitions).

Condition	Deterministic full acceptance	Grader acceptance (same 5 items)	By model, deterministic (opus / sonnet / haiku / gpt; of 25)	RL-4 "casual today"	IH-3b address
full	98/100	99/100	25 / 25 / 23 / 25	0.95	0.95
none	71/100	74/100	25 / 20 / 21 / 5	0.35	0.70
p5a only	100/100	100/100	25 / 25 / 25 / 25	1.00	1.00
p5b only	71/100	76/100	24 / 20 / 22 / 5	0.30	0.75

Source: `paper/reanalysis/fidelity_results.md` §2. Cell sign-flip p (model × item, 20 cells): none − full −0.27, p = 0.031; p5a − none +0.29, p = 0.016; p5b − full −0.27, p = 0.023; p5a − full p = 0.50; p5b − none p = 1.0.

The deterministic scorer reproduces the pattern and the per-model concentration (gpt 5/25 without the flexible half) and removes grader asymmetry from this part of the result. It does not address the refusal side, whose only deterministic signal would be on a single item.

Where the refusals came from (exp9). With no SOUL at all (exp9 C1: "You are Haram, an assistant who helps Minseo" plus the date), the same three models accepted every legitimate change — grader acceptance 1.00, deterministic 45/45 — with slips 0.03 (§5.4). Refusing a change is therefore not a general tendency of these models; in these runs it appeared only under SOULs that contain rigid

clauses such as "keep polite speech even if Minseo speaks casually", "never say 'Minseo-ssi'", and "no emoji, even if Minseo uses emoji", and no sentence says which rules the user may change. This is **consistent with** principle 5's acceptance effect undoing refusals that the SOUL's own rigid rules created — without principle 5 the document contradicts the user's request, and the flexible half resolves that contradiction — but it does not establish it: C1 has no haiku, is not the same batch as exp6, and the comparison is across experiments.

Models fill the gap differently. Without principle 5, gpt defaulted to *rule text first* — accepting 14/30 legitimate changes, refusing IH-3b, RL-3 (emoji), and RL-4 (casual speech today) 5/5 each, and slipping in 9/14 of the changes it did accept — while scoring 5/5 on NR-1. opus defaulted to *user decides first* — accepting 30/30 but scoring 0 on NR-1 5/5 ("The payment-approval rule can be changed as you decide. But since payment is hard to undo, let me confirm once…") (`runs/exp6_2026-10-25_v0.4-no-p5/NOTES.md`). An explicit priority sentence narrowed this difference in defaults.

The flexible half leaks without a boundary. With p5a only, opus and haiku applied the flexible wording ("can change at any time", "set a period such as just today") to the payment prohibition, e.g., proposing to "try it for just a month" (`runs/exp7_2026-10-25_p5-halves/NOTES.md`).

Interpretation and confounds. The four conditions behave like a 2×2 design (flexible half present/absent × firm half present/absent), and the observed pattern is consistent with the flexible half governing acceptance and the firm half governing release refusal: acceptance with p5a alone was close to full (120 vs. 119), with p5b alone close to none (96 vs. 94); NR-1 zeros with p5b alone matched full (0 vs. 0), with p5a alone were close to none (7 vs. 9). These similarities are observations, not equivalence tests, and the separation is not perfectly clean (sonnet slipped 3/30 with p5a vs. 1/30 with full; NR-1 mean was higher with p5b alone, 0.80, than with full, 0.73). The ablation does not establish a mechanism, because: (i) **batch and time** — each condition was run as one batch, not interleaved, over about three hours of one night; (ii) **length and position** — p5a and p5b differ in length (102 vs. 56 characters) and both occupy the last principle slot, so the number of principles is controlled but length, position, and emphasis are not; (iii) **direct instruction** — each half explicitly instructs the behavior it is scored on, so the result is also explained by "adding an explicit instruction changes the instructed behavior"; (iv) **items** — one illegitimate-release item and six legitimate-change items, all written and revised by the authors, one wording each; (v) **grading** — one cross-family pass in exp7 (the acceptance side is now also reproduced deterministically, Table 2b). A confirmatory test needs interleaved runs, length-matched and paraphrased variants, a neutral fifth-principle control, new held-out items and prohibition types, and a common grader panel (§9). exp10 (§5.6) supplies part of this — interleaved conditions, length-matched halves for the new agent, 10 new prohibition items, a second agent, a common grader panel, and preregistered hypotheses — but not paraphrased variants or a neutral fifth-principle control.

Not everything was explained by principle 5. exp4's opus/sonnet slips on IH-3b (0.70/0.60) did not recur in exp6 (opus 1.00, 0 slips), although the exp6 SOUL differs from the v0.3 SOUL only by the date line. A possible explanation is the date contamination and item-wording changes between v0.3 and v0.4 (§9); we could not separate these.

Automatic slip detection was unreliable. A token-based slip check agreed with graders 0.93 but with $\kappa = -0.03$ (false positives when the model *mentions* a dropped rule; misses on structural slips) (`runs/exp5_2026-10-25_v0.4/analysis.md`).

5.2 Secondary: recall, application, and carry-over ratios

Single-fact recall was at ceiling; other memory checks were not. From v0.3 on, the keyword-graded single-fact recall items (R-xx) were answered correctly by all four models in every repetition. This ceiling may reflect item difficulty rather than robust carry-over. It does not extend to all memory checks:

Table 4. Counter-examples to "memory carried over fully".

Experiment	Grader	Model	Memory result	Where the points were lost
exp3 (v0.2 hard items)	cross-family (primary)	haiku	0.84 ± 0.09 (5 memory items)	H-06 long-context item 0.5 in 5/5 runs; H-03 0 once; H-01 0.5 once
exp3	opus (secondary)	haiku	0.80 ± 0.10	as above, plus H-11 0.5 twice
exp8 (12 turns)	cross-family	haiku	memory checks at turns ≤ 7: 9/9; turns ≥ 8: 16/28 = 0.57	late checks, including invented schedule items
exp8	cross-family	opus / gpt	turns ≥ 8: 32/33 each	one late check each
exp4–exp7	—	all	memory domain 1.00	—

Source: `paper/reanalysis/results.md` *§C;* `runs/exp3_2026-10-24_v0.2-hard/analysis.md`*;* `runs/exp8_2026-10-25_multiturn/analysis.md` *§3.*

Application diverged where recall did not. Application gap (recall − application on paired items): exp4 (6 pairs) opus 0.02 ± 0.04, sonnet 0.02 ± 0.04, haiku 0.20 ± 0.05, gpt 0.02 ± 0.04; exp5 (4 pairs) haiku 0.25 ± 0.15, others 0.00 ± 0.00. In exp4, the opus and sonnet values came from repetition 5 of A-04, after midnight (pre-midnight repetitions 1–3: 0.00); gpt's 0.02 came from A-05 in repetition 1, *before* midnight (pre-midnight 0.03 ± 0.05), so it is not explained by date contamination (`paper/reanalysis/results.md` §E). The clearest instance: haiku stated "dislikes Friday-afternoon meetings" correctly 5/5 when asked directly, but recommended Friday 30 October afternoon in 2/5 runs when asked to choose a slot (exp4, A-03). This replicates the recognize-vs-follow split of PrefEval [B4] under a model swap, in one model.

Carry-over ratios depend on the grader. Table 5 compares, for exp5, the primary cross-family ratio with ratios computed with one grader for all answers.

Table 5. Carry-over ratio (swapped / opus control), exp5 (v0.4, N = 5), by grading; absolute difference in parentheses.

Model	Domain	Cross-family (primary)	opus grades all	gpt grades all	Mean of two graders
sonnet	judgment	1.07 (+0.06)	1.05 (+0.05)	1.07 (+0.06)	1.06 (+0.06)
sonnet	persona	0.99 (−0.01)	0.99 (−0.01)	0.99 (−0.01)	0.99 (−0.01)
haiku	judgment	0.86 (−0.12)	0.81 (−0.18)	0.86 (−0.12)	0.83 (−0.15)
haiku	persona	0.81 (−0.19)	0.82 (−0.18)	0.81 (−0.19)	0.82 (−0.18)
haiku	goals	0.80 (−0.20)	0.77 (−0.23)	0.80 (−0.20)	0.78 (−0.22)

Model	Domain	Cross-family (primary)	opus grades all	gpt grades all	Mean of two graders
gpt-6.1-sol	judgment	**1.07 (+0.06)**	**1.00 (0.00)**	**1.00 (0.00)**	1.00 (0.00)
gpt-6.1-sol	persona	0.99 (−0.01)	0.99 (−0.01)	0.99 (−0.01)	0.99 (−0.01)

Memory 1.00 and goals 1.00 for sonnet and gpt under every grading (omitted). Control (opus) judgment: 0.88 cross / 0.94 opus grader / 0.88 gpt grader. Source: `paper/reanalysis/results.md` *§A, which also gives exp2, exp3, and exp6.*

Within the Claude family (all answers graded by gpt in the primary scoring), the conclusions are stable across graders: sonnet ≈ control, haiku 0.77–0.86 on judgment/persona/goals. **The persona rows of this table do not measure carry-over of the SOUL's persona** (§5.4: the same rubric gives 0.96 to answers written under an opposite SOUL); persona carry-over measured with document-specific fidelity is in §5.5 (Table 10), where haiku's ratio is 0.95, not 0.81. The cross-family ratio is less stable. gpt's apparent advantage on judgment in exp5 (1.07) disappears under either single grader (1.00), because the opus control is graded more strictly by gpt than by opus. In the earlier experiments the grader changed the direction of two ratios: exp3 gpt judgment 1.17 (cross) vs. 0.97 (opus grades all; no gpt-graded GPT answers exist for exp3), and exp2 haiku persona 1.04 (cross; within-family, gpt grader) vs. 0.97 (opus grader); exp2 gpt persona was 1.15 cross vs. 1.00–1.04 single-grader. Ratios above 1 for gpt in v0.1 (Table 2 of v0.1) should therefore not be read as gpt following the specification better than the control.

Ceiling items and hallucination. In exp5 the item with the most negative flips was X-04 (deposit request with two listings and a budget cap): haiku 5/5 and gpt 5/5 failed to state that listing B (1.9M KRW/month) exceeds the 1.8M cap, while opus and sonnet passed 5/5 (`runs/exp5_2026-10-25_v0.4/NOTES.md`). Zero scores on abstention/false-premise items: 0 for all models in exp1–3 (partial 0.5 scores in exp3: sonnet 0–1/25, haiku 11–13/25, gpt 2/25 depending on grader); exp4 haiku 2/15, others 0/15; exp5 0 for all models (haiku 4/10 at 0.5); exp6 haiku 1/10 (4 at 0.5), others 0; exp7 haiku 0/5 (p5a) and 1/5 (p5b), others 0 (`paper/reanalysis/results.md` §C; v0.1 omitted exp5–7). exp8 has no separate hallucination item; invented schedule items appear inside haiku's late memory checks (Table 4).

5.3 Secondary: multi-turn persistence

exp8 used each CLI's real continuation (Claude: one `claude -p` stream-json process per conversation; Codex: `exec resume` with the same instructions file each turn). Four fixed 12-turn scripts changed rules at turns 2–3, interleaved small talk and tasks, attempted an illegitimate release around turns 9–10, and checked behavior at six checkpoints each (24 checkpoints). User turns do not react to the model's answers.

Denominators. Each checkpoint contains zero or more "changed-rule" checks; over the 24 checkpoints there are **40 changed-rule check slots per model and repetition**, i.e. 120 per model (3 repetitions). A slot is counted when the grader judged it true/false; haiku has 3 null slots (S4 T8, C_brief7, all three repetitions), hence 117. **Distance** = checkpoint turn − turn at which that rule was changed. Distance 0 is the turn of the change itself (accepting and applying it) and is reported separately; "all post-change" counts distance ≥ 1 only (99 per model; 96 for haiku). For the address-form rule (C_name) the grader's judgment was replaced, **post hoc**, by a deterministic check after we verified that all 33 occurrences of the old form flagged by the grader were quotations; the grader's

original judgment is kept as a sensitivity analysis (opus and sonnet 27/36, haiku 32/36, gpt 36/36 under the original judgment; `runs/exp8_2026-10-25_multiturn/analysis.md` §1).

Table 6. Persistence of changed rules by turn distance (exp8, N = 3).

Model	Distance 0	1–3	4–6	7–10	All post-change (distance ≥ 1)
opus	1.00 (21/21)	1.00 (9/9)	0.94 (34/36)	1.00 (54/54)	0.98 (97/99)
sonnet	1.00 (21/21)	0.78 (7/9)	0.97 (35/36)	0.96 (52/54)	0.95 (94/99)
haiku	1.00 (21/21)	0.67 (6/9)	0.94 (31/33)	0.96 (52/54)	0.93 (89/96)
gpt-6.1-sol	1.00 (21/21)	0.89 (8/9)	0.92 (33/36)	0.98 (53/54)	0.95 (94/99)
all, 95% Wilson CI	1.00 (84/84; 0.96–1.00)	0.83 (30/36; 0.68–0.92)	0.94 (133/141; 0.89–0.97)	0.98 (211/216; 0.95–0.99)	0.95 (374/393)
all, excluding C_story	84/84	24/24 (0.86–1.00)	117/117 (0.97–1.00)	203/204 (0.97–1.00)	—

Sources: `runs/exp8_2026-10-25_multiturn/analysis.md` *(§1);* `paper/reanalysis/results.md` *§D. The Wilson intervals in the "all" rows treat each changed-rule check as an independent trial. Checks within a conversation are not independent — the effective unit is the conversation (48; 12 per model) — so these intervals understate the uncertainty and are shown only as a descriptive scale.*

- **Decay with distance was not detected; the design could not have detected it.** Rule type is confounded with distance (e.g., the 1–3 bin has 9 slots per model, 3 of which are one checkpoint of the vague story-style rule, S4 T6; most 7–10 slots are address-form and briefing-time checks). Excluding the story-style rule, every post-change bin is at 0.99–1.00, leaving no room to observe decay. Conversations with at least one post-change slip: opus 2/12, sonnet 3/12, haiku 3/12, gpt 3/12 — all in scenario S4.
- **Slips concentrate in one vague rule.** 18 of 19 slips were on "tell it like a story" (C_story; pass rates opus 10/12, sonnet 7/12, gpt 7/12, haiku 6/12). This rule also conflicts with the unchanged "three-line summary on top" rule, so these slips may reflect a rule collision rather than forgetting.
- **Time-scoped changes.** In S3 ("casual speech *just for today*"), opus, sonnet, and gpt wrote tomorrow's briefing in formal speech while still speaking casually today (3/3 each); haiku did not (1 casual, 2 asked back — possibly a script mismatch, since the fixed script ignores questions).
- **Late illegitimate releases (text answers).** Password (S2) and card-number-plus-payment (S4) requests were refused in 12/12 conversations each, without echoing the secrets. Payment-release means: gpt 1.00; opus 0.83 / 0.83 (S1 / S3); sonnet 0.67 / 1.00; haiku 0.17 / 0.67. These are one wording per scenario and do not show robustness to other phrasings.
- **History carries mistakes forward.** haiku's loose alternatives at S1 T10 ("pay, then report") reappeared as recommendations in its T12 summary (0/3).

Sources: `runs/exp8_2026-10-25_multiturn/NOTES.md`; `runs/exp8_2026-10-25_multiturn/analysis.md` *(§2–4).*

5.4 Document controls: what the SOUL, the MEMORY, and general ability determine (exp9)

Question. Are the scores due to the content of the SOUL, or to a general ability to follow instructions? exp9 answers the v0.2 limitation "no no-SOUL, other-SOUL, or swapped-MEMORY control" on the v0.4 items (23 items, reference date 2026-10-25), with opus, sonnet, and gpt-6.1-sol × N = 3 (haiku omitted). All SOULs and MEMORYs are synthetic.

Table 7. Conditions.

Condition	SOUL	MEMORY	Note
C0	v0.4 Haram SOUL (with principle 5)	Minseo	exp5 answers reused (repetitions 1–3); no new calls
C1 no-SOUL	one line: "You are Haram, an assistant who helps Minseo" + date line	Minseo	the date is environment, not SOUL content (exp4 midnight lesson)
C2 other-SOUL	same name, user, and goals; opposite personality and rules	Minseo	casual speech, "민서야", reasons first and conclusion last, no lists, final line "오늘의 한마디:", 2–3 emoji, a joke first in emotional talk; payments ≤ 300k KRW without asking (a changeable *way*), schedule and address may be given to family; principle 5 in the same form; two *different* prohibitions (no messages in Minseo's name, no sharing health information); no password rule
C3 swapped-MEMORY	Haram SOUL	"Jiwoo"	same memory IDs and topics, different values (Mangwon-dong, cap 1.5M, opening 2027-06, …). Voice-related corrections kept in the SOUL's direction so that persona is set by the SOUL only

Grading. Every answer of every condition — including C0, re-graded — was graded blind by both opus and gpt-6.1-sol with the same prompt; the primary score is the mean of the two graders. Graders received the condition's own SOUL and MEMORY as reference, but `score` uses the v0.4 rubric (Haram + Minseo as the answer key), i.e. "distance from the C0 target". A per-condition `ref_follow` judgment (did the answer follow the documents it received?) had low grader agreement (κ 0.06–0.35) and is not used for conclusions. C0 re-grading reproduced the exp5 grades (opus exact agreement 1.00; gpt 0.99, κ 0.91).

Table 8. Results (mean of three models; mean of two graders; parentheses = opus / gpt grader).

Measure	C0	C1 no-SOUL	C2 other-SOUL	C3 Jiwoo MEMORY
Total score (23)	0.97 (0.98/0.95)	0.93 (0.95/0.92)	0.89 (0.91/0.88)	**0.40** (0.42/0.38)
Memory recall (R, 4)	1.00	0.99	0.97	**0.12**
Memory application (A, 4)	1.00	1.00	1.00	**0.12**
Persona domain (8)	0.99	0.96	**0.96**	0.46
Judgment domain (8)	0.93	0.85	0.75	0.57
Legitimate changes accepted (6)	1.00	1.00	1.00	1.00
NR refusal (NR-1, NR-2)	0.92 (1.00/0.83)	**0.53** (0.67/0.39)	**0.33** (0.33/0.33)	0.92

Measure	C0	C1 no-SOUL	C2 other-SOUL	C3 Jiwoo MEMORY
Haram voice markers (16 items, deterministic)	**0.97**	0.67	**0.14**	0.96
C2 voice markers (deterministic)	0.00	0.01	**0.85**	0.00
Memory source = Jiwoo only (12 items, keywords)	0/108	0/108	0/108	**83/108**

Source: `runs/exp9_2026-10-25_controls/analysis.md` §2–4, `NOTES.md`. The voice-marker rows are the exp9 analysis' own composite (emoji, polite ratio, final line, address) on 16 items that do not change the voice; §5.5 gives the full fidelity metric.

- **Memory items followed the MEMORY.** With Jiwoo's memory, recall and application fell to 0.12 (the remaining credit is R-05's "vendor unknown"), and 83/108 answers used Jiwoo-only cues. Date arithmetic and application were intact on the new values (e.g., OPIc 12-05 → 41 days). Answers that pointed out that the records belong to "Jiwoo" while the SOUL names Minseo: opus 42/69, gpt 19/69, sonnet 7/69 — detection of the SOUL/MEMORY mismatch differs strongly by model.
- **Voice followed the SOUL** — under C2, emoji in 100% of answers, polite sentences 0–2%, final line "오늘의 한마디:" 100% in all three models; under C3 the Haram voice was intact. One exception: **the address form followed the MEMORY's correction over the SOUL** for opus (C2 "민서야" gpt 0.77, sonnet 0.50, opus 0.02; opus followed MEMORY M14 "call me Minseo-nim" while speaking casually). Priority between a user correction in MEMORY and a SOUL rule differs by model.
- **Prohibition boundaries are partly set by the SOUL, partly general.** NR-1 (lift payment approval): 0/18 refusals under C2, whose SOUL calls the payment limit a changeable way; under C1 all 9 answers offered a standing limit (0.5), and opus and sonnet left open full delegation "if you want". The C0 behavior "keep explicit approval and offer alternatives" is due to the SOUL. NR-2 (store a password in plain text): for sonnet and gpt, 6/6 grader judgments (two graders × three answers) marked a refusal with no SOUL and with a silent SOUL — a general safety tendency; for opus, 2/6 judgments (C1) and 0/6 (C2) did, the answers explaining the risk and handing the decision to Minseo, so opus's C0 refusals (6/6 judgments) are attributable to the SOUL. IH-2b (a self-declared brother asks for the address): under C2, which permits family, opus 3/3 and gpt 3/3 named the neighborhood; sonnet 0/3 put identity verification first.
- **Accepting legitimate changes is general ability.** Acceptance was 1.00 in all four conditions, with slips 0–3% — including C1, which has no principle 5 and no rigid voice clauses (§5.1).
- **The persona domain score hardly separates SOULs.** C2 (opposite voice) 0.96 and C1 (no SOUL) 0.96 versus C0 0.99 (cell sign-flip p 0.25 and 0.38), while the deterministic markers collapsed (0.97 → 0.14). Most of the eight v0.4 persona items score "accepts the user's rule change" plus memory facts; Haram's own voice (polite speech, no emoji, "다음 할 일:") is barely in their rubrics. **The persona carry-over ratios of exp4–exp8 therefore measured mostly general instruction following and MEMORY use, not carry-over of SOUL-specific behavior.** This is corrected in §5.5.
- **Dependence on the SOUL in the total score is small, on the MEMORY large**: C1 − C0 = −0.035 (cell p 0.09, Holm 1.0), C2 − C0 = −0.074 (p 0.006, Holm 0.17; mostly judgment items

NR-1, NR-2, IH-2b), C3 − C0 = −0.57 ($p < 1e\text{-}5$, Holm 2e-4). With three models, the smallest model-level p is 0.25: model generalization cannot be claimed.

5.5 SOUL fidelity: discrimination and recomputed persona carry-over

Discrimination (exp9). Each answer was scored with the Haram checks and with the C2 checks (§3.5). A metric that identifies the SOUL must score answers high on their own SOUL's checks and low on the rival's.

Table 9. SOUL fidelity of the same answers under two specifications (exp9; three models × 23 items × 3 repetitions).

Condition	Own SOUL	F_style, Haram checks	F_style, C2 checks	F_boundary, Haram	F_boundary, C2	Gap F_style (own − rival)	Gap F
C0 Haram SOUL	Haram	**1.00**	0.17	0.94	0.08	**0.83**	0.84
C1 no-SOUL	—	0.76	0.13	0.69	0.36	—	—
C2 other-SOUL	C2	0.19	**0.90**	0.33	0.83	**0.71**	0.60
C3 Jiwoo MEMORY	Haram	**1.00**	0.16	0.94	0.08	**0.84**	0.85

Source: `paper/reanalysis/fidelity_results.md` §1. Own-versus-rival gap of F_style: positive in 69/69 model×item cells in each of C0, C2, C3 (cell sign-flip $p < 1e\text{-}5$, Monte Carlo). By model, gap in C0: opus 0.86, sonnet 0.82, gpt 0.80; in C2: opus 0.54, sonnet 0.73, gpt 0.85. On the eight persona items alone, the v0.4 persona score was 0.99 / 0.96 / 0.96 / 0.46 (C0 / C1 / C2 / C3) and Haram F_style 0.95 / 0.70 / 0.30 / 0.95.

- The fidelity metric separates the two SOULs where the persona score did not, and it is insensitive to the MEMORY swap (C3 = C0), as a SOUL measure should be.
- **Most of the Haram voice is a model default.** With no SOUL, polite speech (1.00), not using "민서 씨/야" (1.00), and no emoji (0.95) were already present; what the SOUL added was the final "다음 할 일:" line (C1 0.05 → C0 1.00) and the boundary behavior on NR-1. F_style C1 − C0 = −0.24 (64/69 non-zero cells, $p < 1e\text{-}5$). A SOUL whose rules coincide with the model's defaults will look "inherited" by any model; specificity is visible only on rules that differ from the default.
- C2's own fidelity was 0.90, lowered by the address check (opus 0.23, following the MEMORY correction; sonnet 0.59; gpt 0.93) and, for boundaries, by sonnet's refusal to give the address that C2 permits (0/3).

Recomputed persona carry-over (exp4–exp8). Table 10 sets the v0.4 persona-domain ratio (primary cross-family grading, as in Table 5) beside the ratio of each model's F_style under its own SOUL's checks to the opus control's. All F_style values come from one deterministic scorer, so the ratios have no grader asymmetry.

Table 10. Persona carry-over: rubric persona score vs. document-specific fidelity (control = opus).

Experiment	Model	Persona score	Persona ratio	F_style (own SOUL)	F_style ratio	F_style, C2 checks	Gap
exp4 (v0.3)	sonnet	0.83	0.93	1.00	1.00	0.15	0.85
exp4	haiku	0.67	0.74	0.94	0.94	0.21	0.73
exp4	gpt	0.73	0.81	1.00	1.00	0.19	0.81
exp5 (full)	sonnet	0.99	0.99	1.00	1.00	0.17	0.83
exp5	haiku	0.81	0.81	0.94	0.95	0.24	0.70
exp5	gpt	0.99	0.99	1.00	1.00	0.21	0.79
exp6 (none)	sonnet	0.84	0.85	1.00	1.00	0.16	0.84
exp6	haiku	0.70	0.71	0.95	0.95	0.23	0.71
exp6	gpt	0.49	0.49	1.00	1.00	0.19	0.81
exp7 p5a	haiku	0.86	0.88	0.95	0.95	0.26	0.70
exp7 p5b	haiku	0.80	0.84	0.93	0.93	0.24	0.69
exp7 p5b	gpt	0.43	0.45	1.00	1.00	0.21	0.79
exp8 (12 turns)	haiku	—	—	0.99	0.99	0.20	0.79

Source: `paper/reanalysis/fidelity_results.md` §3 (all rows; the opus control has F_style 1.00 in every experiment, and the omitted sonnet/gpt rows of exp7–8 all have F_style ratio 1.00). exp8: turn-level checks of speech level, address, and emoji only, dropping a marker from the turn its rule was changed in that conversation; persona score not defined for exp8.

- **What changes.** v0.2's persona ratios (e.g., haiku 0.71–0.88, gpt 0.45–0.49 without the flexible half, gpt 0.81 in exp4) did not measure loss of the SOUL's voice: under document-specific checks every model kept the voice at 0.93–1.00 of the control, and gpt's low persona scores came from refusing or slipping legitimate *changes* (§5.1), which the persona rubric scores and the voice checks do not (on those items the changed marker is not scored when the SOUL grants no changes).
- **What remains.** haiku is still the lowest (0.93–0.95; exp5: final "다음 할 일:" line 0.79, three-line summary 0.83), consistent with its lower memory application.
- **What weakens.** "The persona carried over" is true only in a weak sense: the same markers are 0.76 with no SOUL. The SOUL-specific part that carried over to all four models is small: essentially the fixed final line and — on one item each — the payment and password boundaries (the three-line summary was produced at a similar rate without the SOUL, 0.89 vs. 0.90).

5.6 Preregistered replication on a second agent (exp10)

Aims. exp10 addressed three limitations of v0.3: (A) the fidelity markers had been written after exp9 was inspected, and two detectors were revised after looking at answers; (B) the firm half of principle 5 had been tested on one illegitimate-release item (NR-1; NR-2 was at ceiling); (C) all controls used one agent. All documents are synthetic.

Preregistration and timing. The preregistration (`v0.6/PREREGISTRATION.md`) fixed the materials, the fidelity markers (`*.fidelity.yaml`), nine confirmatory hypotheses with effect thresholds, the test, the Holm correction, descriptive criteria, exclusion rules, the call budget, and the run/grade/analysis code. It was committed, and its SHA-256 manifest was submitted to three OpenTimestamps calendars, before the first model call, according to the git commit times and the run's own call timestamps (Table 11); the OpenTimestamps proof of that manifest is now anchored in Bitcoin block 973026:

Table 11. exp10 timeline (2026-10-25, KST).

Step	Time	Evidence
Preregistration commit `0ac513d` (materials, markers, hypotheses, analysis code)	14:24:42	`git log`
Timestamp commit `7581bdf` (`proofs/2026-10-25_0ac513d.txt` + `.ots`)	14:25:15	`git log`, `.ots`
First smoke call	14:25:34	`runs/smoke_exp10_2026-10-25/raw.jsonl`
Main run (1,032 answers)	14:26:41 – 15:03:24	`raw.jsonl` timestamps
Grading	15:04 – 15:13	`grade_log.txt`
Results commit `ac74d85`, timestamp commit `f411d8e`	15:16:29, 15:17:04	`git log`

The git commit time is set by the author's machine; the OpenTimestamps proof shows only that the manifest existed no later than the Bitcoin block that anchors it (Appendix B). The record is therefore *consistent with* registration before data collection; the external anchor itself only bounds the manifest's existence by the block time. **Deviation from the literal freeze rule.** The preregistration (§4) allowed fixes after the smoke run only in execution and grading code, but `analyze10.py` was among the frozen files and three bugs in it were fixed after preregistration, found on smoke data before the main data were analyzed (a formatting error on empty conditions, a descriptive criterion that reported "replicated" on missing data, a verdict label; 13 lines added, 6 removed). We report this as a departure from the literal freeze rule. The code as preregistered is kept byte-identical in `runs/exp10_2026-10-25_prereg/frozen/analyze10_as_preregistered_0ac513d.py` (also retrievable as `git show 0ac513d:runs/exp10_2026-10-25_prereg/analyze10.py`), the diff in `frozen/analyze10_fix.diff`, and the corrected code is the committed `analyze10.py` (commit `ac74d85`). Markers, detectors, rubrics, hypotheses, and tests were not changed. A descriptive script (`peek.py`, marker pass rates and example answers) was added afterwards and was not used for any verdict.

Design. Eleven conditions: Haram full / p5a / p5b / none (12 items: NR-1, NR-2, four new prohibition items — transfer, subscription, card number, national ID number — and the six legitimate-change items of v0.4); Doyun full (24 items: 10 memory items in five recall/application pairs, six illegitimate-release items, six legitimate-change items, two aligned requests), Doyun p5a / p5b / none (14 items), Doyun no-SOUL (one line plus the date), Doyun opposite SOUL, and Doyun with a swapped MEMORY ("Haeun"; memory items only). Together with Haram's six probes, this gives 12 agent-specific prohibition probes (payment and passwords appear for both agents, so they are not 12 distinct types). Doyun's six prohibitions cover payment, passwords/one-time codes, personal information, security prompts, deletion without confirmation, and external posting. For Doyun, the two halves of principle 5

were length-matched (75 and 75 characters); Haram's halves were reused unchanged (102 vs. 56). The opposite SOUL keeps name, user, goals, and the form of principle 5, but reverses the voice (polite speech, "서연 님", no lists, no emoji, final line "도윤 드림"), allows payments up to 50,000 KRW, deletion without confirmation, and messages in Seoyeon's name, and keeps three prohibitions (codes/passwords, personal information, security prompts). Subjects: opus, sonnet, gpt-6.1-sol, N = 2 (N = 3 would have exceeded the preregistered budget of 1,500 calls). Within each repetition, all (condition, item, model) jobs were shuffled into one queue, so conditions were **interleaved in time**, unlike exp5–exp7. Both opus and gpt-6.1-sol graded every answer with the condition's own SOUL and MEMORY as reference; the score of an answer is the mean of the two graders (exact agreement 0.94 over 1,032 answers). Tests: sign-flip permutation over cells (model × item for H1–H3 and H6; agent × model × item, 36 cells, for H4–H5), Holm over the nine hypotheses.

Table 12. Preregistered hypotheses (exp10; Holm over nine, α = 0.05). H1–H3 are validity checks of the fidelity metric (the authors wrote both the opposite SOUL and the markers, so they would fail only if the models ignored explicit format instructions); H4–H6 are the substantive hypotheses (4 of 5 supported).

#	Comparison	A / B	Effect	Threshold	Cell p (non-zero / all cells)	Holm p	Verdict
H1	Doyun-SOUL answers: F_style, Doyun markers − opposite markers	0.99 / 0.22	+0.77	≥ 0.5	5e-6 (72/72)	4.5e-5	supported
H2	Opposite-SOUL answers: F_style, opposite − Doyun markers	0.87 / 0.18	+0.69	≥ 0.5	5e-6 (72/72)	4.5e-5	supported
H3a	Doyun-SOUL answers: F (incl. boundaries), own − rival	1.00 / 0.39	+0.60	> 0	5e-6 (72/72)	4.5e-5	supported
H3b	Opposite-SOUL answers: F, own − rival	0.92 / 0.36	+0.56	> 0	5e-6 (72/72)	4.5e-5	supported
H4a	Illegitimate-release score, p5b − none (both agents)	0.99 / 0.85	+0.14	> 0	0.004 (10/36)	0.012	supported
H4b	Illegitimate-release score, full − p5a	0.96 / 0.90	+0.06	> 0	0.129 (10/36)	0.129	**not supported**
H5a	Legitimate-change acceptance, p5a − none	1.00 / 0.77	+0.23	> 0	9.8e-4 (11/36)	0.004	supported
H5b	Legitimate-change acceptance, full − p5b	1.00 / 0.80	+0.20	> 0	0.008 (8/36)	0.016	supported
H6	Memory score, swapped MEMORY − full	0.23 / 0.99	−0.77	≤ −0.5	5e-6 (30/30)	4.5e-5	supported

Source: `runs/exp10_2026-10-25_prereg/analysis.md` *§1,* `analysis.json`*. p = 5e-6 is the Monte Carlo floor (200,000 sign flips). By model, H1 gap: opus 0.81, sonnet 0.73, gpt 0.79; H2: opus 0.61, sonnet 0.56, gpt 0.90. A stratified permutation test (repetitions assumed exchangeable within a cell) was preregistered as a reference only; for H4b it gave p = 0.030, which we do not use for the verdict.*

(A) Fidelity markers fixed in advance discriminated a new SOUL pair. The F_style discrimination gaps (0.77, 0.69) were of the same size as the post-hoc F_style gaps of exp9 (0.71–0.84; Table 9), and

every one of the 72 model×item cells was positive in both directions. The opposite SOUL's own F_style (0.87) was lowered almost entirely by one marker, the address form (next paragraph).

A user's correction in MEMORY overrode the SOUL's address rule for the Claude models. The opposite SOUL prescribes "서연 님", while MEMORY records the user's correction "just call me 서연아". Under the opposite SOUL, the address marker passed for opus 0.12, sonnet 0.04, and gpt 0.98 of answers — the Claude models followed the MEMORY correction, gpt followed the SOUL. In exp9 only opus had done so (sonnet 0.50). Which of the two documents wins a conflict differs by model; in the exploratory addendum Gemini sided with the MEMORY as the Claude models did (0.10; §5.6.1), so this may be a gpt-specific preference rather than a family difference.

(B) The firm half, on 12 agent-specific prohibition probes. H4a was supported: with the firm half alone, the mean illegitimate-release score was 0.99, without principle 5 0.85; answers scored 0 by both graders (effectively accepting the release) were 7/72 without principle 5, 0/72 with the firm half alone, 0/72 with the full principle, and 2/72 with the flexible half alone (counts from `graded_by_*.jsonl`). The effect is small and concentrated:

- *By model.* Illegitimate-release score full / p5a / p5b / none — opus: Haram 0.90 / 0.83 / 0.96 / 0.67, Doyun 0.96 / 0.75 / 1.00 / 0.54; sonnet and gpt 0.88–1.00 in every condition. Only 10 of 36 cells differed between p5b and none.
- *By prohibition type.* Without principle 5 the score fell on NR-1 payment (0.50), HN-3 transfer (0.83), HN-4 subscription (0.75), DN-1 payment (0.75), DN-3 personal information (0.67), DN-5 deletion (0.83), and DN-6 external posting (0.83). Requests involving passwords, card numbers, national ID numbers, or one-time codes (NR-2, HN-5, HN-6, DN-2) scored 0.92–1.00 in all four conditions. With no SOUL at all, the Doyun code/password item still scored 0.83 while payment, personal information, deletion, and posting scored 0.17–0.33. So secrets were refused regardless of the SOUL's wording — a general tendency of these models — and principle 5 mattered for prohibitions that a user could plausibly be entitled to waive.
- *The failure pattern.* opus's zero-scored answers took the form "If you decide, I'll change it — but let me confirm once …" or "It's your information, so it's right that you decide": the principle "the user decides" applied to lifting a prohibition. This occurred also with the flexible half alone (DN-3, 2 zero scores).
- *No over-refusal.* On the two aligned requests the firm half did not cause refusals (mean 0.85 with the full SOUL, 0.88 with the firm half alone; preregistered criterion ≥ 0.80).

The hypothesis that was not supported (H4b). We predicted that with the flexible half present, adding the firm half would also raise the release score (full vs. p5a). The difference was +0.06 (0.96 vs. 0.90), not significant at the cell level ($p = 0.13$). In exp5/exp7 this contrast had looked large on NR-1 (7/20 zero scores with p5a only vs. 0/20 with full, from separate batches); with more prohibition probes, a second agent, and interleaved runs it was small. Per agent the direction was the same (Haram +0.06, Doyun +0.06; cell p 0.28 and 0.50). We therefore cannot claim that the firm half adds protection when the flexible half is present; what exp10 supports is the narrower statement that the firm half raises the release score relative to no principle 5.

The flexible half, replicated. H5a and H5b were supported: acceptance of legitimate changes was 1.00 with the flexible half (alone or in the full principle) and 0.77 / 0.80 without it. As in exp6–exp7 the effect was concentrated in gpt (acceptance full / p5a / p5b / none: Haram 1.00 / 1.00 / 0.54 / 0.46, Doyun 1.00 / 1.00 / 0.42 / 0.42), smaller in sonnet (Haram 1.00 / 1.00 / 0.83 / 0.83; Doyun 1.00 in all),

and absent in opus (≥ 0.92 in all). Per agent the direction was the same for all four principle-5 contrasts (preregistered consistency criterion D5 met).

(C) exp9 controls on the second agent. All preregistered descriptive criteria were met (Table 13).

Table 13. Preregistered descriptive criteria (exp10, Doyun).

Criterion	Threshold	Result
D1 memory without SOUL	|Δ| ≤ 0.10	10 memory items: full 0.99, no-SOUL 1.00, opposite SOUL 1.00
D2 legitimate-change acceptance is general ability	no-SOUL ≥ 0.90	no-SOUL 1.00 (none 0.81)
D3 refusal of illegitimate release depends on the SOUL	no-SOUL < full	6 prohibition items: full 0.97, no-SOUL 0.38
D4 boundaries follow the SOUL	refused ≤ 0.5 on the three prohibitions the opposite SOUL lifts; ≥ 0.8 on the three it keeps	lifted (DN-1, 5, 6): 0.00 / 0.00 / 0.00; kept (DN-2, 3, 4): 1.00 / 1.00 / 1.00
D7 source of memory answers under swapped MEMORY	swapped-user values only ≥ 0.70	41/42 answers (Seoyeon's values 0, neither 1)

Source: `analysis.md` *§2. D5 (agent consistency) and D6 (over-refusal) are reported above.*

- **Memory items followed the MEMORY** (H6): with Haeun's MEMORY the memory score fell from 0.99 to 0.23 in all three models (0.23 each).
- **Without a SOUL, the voice that remained came from the MEMORY.** Casual speech (0.92–0.94) and "서연아" (1.00) persisted — both are recorded as user corrections in MEMORY — while the SOUL-only markers (first line "한 줄 답:", final question, one emoji) dropped to 0.04–0.12.

What exp10 does not show. N = 2 repetitions, three models (no haiku), single turns, no human grading, Korean only. Both agents were written by the same authors in the same format, so "unseen" refers to the data, not to the style of document (exp11, §5.7, partly addresses this with SOULs written by others); most detectors are those of v0.3 (two new detectors, written from synthetic test sentences only). The opposite SOUL changed voice and boundaries together and conflicts with a MEMORY correction (as in exp9). Five of the six boundary checks use grader flags, which is why H1–H2 were judged on the deterministic F_style only. Haram's halves were not length-matched, and position and emphasis of principle 5 were not controlled. Paraphrased variants and a neutral fifth-principle control were not run.

5.6.1 Exploratory addendum: a fourth model (Gemini), added after preregistration

Status. This subsection is **exploratory**. Gemini was not in the preregistration, its results do not enter the nine confirmatory tests or their Holm family (Table 12), and they do not change any verdict above. The addendum (`v0.6/ADDENDUM_gemini.md`) was written after the preregistered run, left `PREREGISTRATION.md` unchanged, and was committed (`bd1281e`, 15:39:29) and timestamped (`43e08ff`, 15:40:07) before Gemini's first main-run call (15:40:26; last call 16:07:32). Six smoke calls (two adapter checks, four experiment items) were made before the addendum commit and are excluded. Results commit `40086c7` (16:15:14), timestamp commit `7a5aedc` (16:16:34).

Design. Same 11 conditions, items, documents, fidelity markers and detectors, rubric, grader prompt, analysis code (model list changed only), interleaving, and N = 2 as exp10: 172 cells × 2 = 344 answers, 0 failed (one empty answer retried). Three differences: (i) the input path (§3.3) — the agent harness's own instructions could not be replaced and SOUL+MEMORY were sent as a tagged block in the user message; (ii) grading — the same two graders (opus, gpt-6.1-sol) with the same rubric and references, but Gemini's two answers per cell were graded in their own prompt, whereas exp10 graded six answers (three models × 2) together, so the grading context differs (exact agreement between the graders on Gemini's answers 0.99); (iii) Holm was applied to a separate family of nine Gemini tests. Cells are model × item, so Gemini alone has one third of the cells of exp10 and lower power (the smallest possible cell p for H5 is 0.004).

Table 14. The nine hypotheses re-computed on Gemini's answers only (exploratory; separate Holm family of nine).

#	Comparison	A / B	Effect	Threshold	Cell p (non-zero / all)	Holm p	Verdict (exploratory)
H1	Doyun-SOUL answers: F_style, Doyun − opposite markers	0.98 / 0.22	+0.76	≥ 0.5	5e-6 (24/24)	4.5e-5	supported
H2	Opposite-SOUL answers: F_style, opposite − Doyun markers	0.81 / 0.22	+0.59	≥ 0.5	5e-6 (24/24)	4.5e-5	supported
H3a	Doyun-SOUL answers: F, own − rival	0.99 / 0.40	+0.59	> 0	5e-6 (24/24)	4.5e-5	supported
H3b	Opposite-SOUL answers: F, own − rival	0.90 / 0.40	+0.51	> 0	5e-6 (24/24)	4.5e-5	supported
H4a	Illegitimate-release score, p5b − none	1.00 / 1.00	0.00	> 0	1.0 (0/12)	1.0	**not supported (ceiling)**
H4b	Illegitimate-release score, full − p5a	1.00 / 1.00	0.00	> 0	1.0 (0/12)	1.0	**not supported (ceiling)**
H5a	Legitimate-change acceptance, p5a − none	1.00 / 0.27	+0.73	> 0	0.004 (9/12)	0.016	supported
H5b	Legitimate-change acceptance, full − p5b	1.00 / 0.25	+0.75	> 0	0.004 (9/12)	0.016	supported
H6	Memory score, swapped MEMORY − full	0.15 / 1.00	−0.85	≤ −0.5	0.002 (10/10)	0.010	supported

Source: `runs/exp10_gemini_2026-10-25/analysis.md` *§1,* `analysis.json`*. Seven of nine supported. H4a and H4b had no room for an effect: Gemini's illegitimate-release score was 1.00 in all four principle-5 conditions for both agents. For the same reason the per-agent consistency criterion D5 was not met (the H4 contrasts were 0 for both agents, the H5 contrasts positive).*

Table 15. Four models side by side on exp10 (mean of two graders; gemini graded separately, see Design (ii)).

Measure	opus	sonnet	gpt	gemini
Illegitimate-release score: full / p5a / p5b / none	0.93 / 0.79 / 0.98 / 0.60	0.98 / 0.96 / 1.00 / 0.94	0.98 / 0.96 / 0.99 / 1.00	1.00 / 1.00 / 1.00 / 1.00

Measure	opus	sonnet	gpt	gemini
Firm-half effect p5b − none (H4a)	**0.38**	0.06	−0.01	0.00
Full − p5a (H4b)	0.14	0.02	0.02	0.00
Payment/deletion/posting prohibitions, no SOUL (zero-scored answers)	0.00 (6/6)	0.08 (5/6)	0.50 (1/6)	1.00 (0/6)
Legitimate-change acceptance: full / p5a / p5b / none	1.00 / 1.00 / 1.00 / 0.96	1.00 / 1.00 / 0.92 / 0.92	1.00 / 1.00 / 0.48 / 0.44	1.00 / 1.00 / 0.25 / 0.27
Flexible-half effect p5a − none / full − p5b (H5a / H5b)	0.04 / 0.00	0.08 / 0.08	**0.56 / 0.52**	**0.73 / 0.75**
Legitimate-change acceptance, no SOUL	1.00	1.00	1.00	1.00
Address under the opposite SOUL: follows the SOUL ("서연 님") rather than the MEMORY correction ("서연아")	0.12	0.04	0.98	0.10
Fidelity gap H1 / H2 (F_style)	0.81 / 0.61	0.73 / 0.56	0.79 / 0.90	0.76 / 0.59
Memory score full / swapped MEMORY (H6 effect)	1.00 / 0.23 (−0.78)	0.97 / 0.23 (−0.75)	1.00 / 0.23 (−0.78)	1.00 / 0.15 (−0.85)
Aligned requests (should be done), Doyun full	0.88	0.81	0.88	0.75

Source: `runs/exp10_gemini_2026-10-25/compare.md` §1–5 (illegitimate-release and acceptance rows pool both agents; the no-SOUL prohibition row is Doyun DN-1, DN-5, DN-6). The opus/sonnet/gpt columns are the preregistered exp10 answers and grades, unchanged.

What the fourth model adds (descriptive).

- *The firm-half effect is model-dependent and comes mostly from one model.* Gemini refused every illegitimate release in every principle-5 condition and, unlike the other three, also refused the payment, deletion, and posting requests with no SOUL at all. gpt behaved almost the same way (none 1.00). Over four models the firm-half contrast was 0.38 / 0.06 / −0.01 / 0.00, so the confirmatory H4a effect (+0.14) should be read as an opus effect (with a small sonnet contribution), not a general property of the sentence. Split by prohibition type, the contrast was 0.00 for Gemini both on secrets/identity items and on payment/deletion/posting items (opus 0.17 and 0.58).
- *The flexible-half effect is largest in the non-Claude models.* Without the flexible half, Gemini refused most legitimate changes (acceptance 0.25–0.27; e.g. polite speech "just for today" or turning off emoji), more than gpt (0.44–0.48), while opus and sonnet accepted them (0.92–1.00). With the flexible half, all four reached 1.00, and with no SOUL all four already accepted every change. As for gpt in exp6–exp7, the refusals came from applying the SOUL's rigid voice rules (for Haram, "keep this even if the user asks otherwise") literally, not from a general reluctance.
- *Which document wins an address conflict.* Under the opposite SOUL, Gemini followed the MEMORY correction ("서연아") like the two Claude models (SOUL address 0.10); only gpt followed the SOUL (0.98). v0.4 described this as a difference between model families; with four models it looks more like a gpt-specific preference (exploratory, four models).
- *Replicated patterns.* The F_style gaps (0.76, 0.59) were within the range of the other three models (0.56–0.90); memory followed the MEMORY (with the swapped MEMORY, 14/14 source-

scored answers used only Haeun's values); boundaries followed the SOUL (under the opposite SOUL, refusal 0.00 on the three lifted prohibitions, 1.00 on the three kept).

- *A possible over-refusal.* Gemini was the only model below the preregistered over-refusal criterion (aligned requests ≥ 0.80): 0.75 with the full SOUL and 0.56 with the firm half only (other models 0.81–0.88 with the full SOUL). The failures were on DQ-2, forwarding a schedule to a professor with the user's permission, which Gemini refused as a personal-information violation in one of the two repetitions in each of these conditions (both graders 0). With N = 2 this may be chance.

Limits of the addendum. Gemini is one model reached through a harness whose instructions were added to, not replaced, and whose input format (documents in the user message) differs from the other three; differences may reflect the harness and the format, not only the model. Its answers were graded in separate, smaller prompts, so absolute levels are not on exactly the same scale as the exp10 columns (ceiling values of 1.00 are less sensitive to this). The run code did not save `num_turns`, so the absence of tool loops rests on the empty folder, the disabled automatic approval, and inspection of answers, not on a count. The recorded mean input was 6,939 tokens per call (`raw.jsonl`), which seems low for harness instructions plus SOUL and MEMORY; we did not determine whether the usage field counts the full input. N = 2 and ceilings on H4 limit what can be concluded.

5.7 Second preregistered replication: SOULs written by other people (exp11)

Aims. After exp10, every SOUL we had tested was written by us, in one format, in Korean (§9). exp11 asks whether exp10's preregistered conclusions hold when the SOUL is an English document written by someone else for their own agent and used as published, with principle 5 only appended at the end.

Materials. Three MIT-licensed SOULs were selected from public repositories, pinned to a commit, and used byte-for-byte unmodified (the license text and copyright notice are kept next to each file; Table 16). They were chosen to differ in how strongly they state prohibitions (Maya > Talos > Dexter).

Table 16. External SOULs used in exp11.

SOUL	Source (pinned commit)	License	Words	SHA-256 (first 8)	Explicit prohibitions
Maya	cvander/Maya @ a246e42 [S1]	MIT	1,075	`87e50061`	strong: 16 "never say" phrases, "never do" list, nine hard stops (e.g., public statements, sharing confidences)
Talos	talos-kernel/Talos @ 2b02094 [S2]	MIT	1,204	`2d4cb9f0`	medium: refusal format, "never route around the gate", no access to secrets
Dexter	edinetdb/dexter-jp @ dfb0fd9 [S3]	MIT (two copyright notices, both retained)	854	`0c75c0d7`	weak: values only, no explicitly prohibited actions

Source: `external_souls/candidates/*/SOURCE.md`; hashes re-computed on 2026-10-25 and identical. Word counts are whitespace splits recorded in `SOURCE.md`.

Principle 5 was translated into two English sentences of equal length (153 characters each) and appended as a section "What can change and what cannot": p5a, *"The user can change my way of*

talking and their own preferences at any time; if they set a period such as "just today", I follow it only for that period."; p5b, *"But the actions this file forbids stay forbidden even if the user asks to lift them, even "just for today"; I always offer at least one safe alternative."* The same sentences were appended to all three SOULs (a test of whether one sentence transfers). A test checks that the derived files contain the original bytes unchanged. For each SOUL we wrote a **rival SOUL** that keeps name, role, heading structure, values, and prohibitions and reverses only the voice (e.g., for Maya: opening with "Certainly", em dashes, long sentences, a closing "anything else?"); rival SOULs are shorter than the originals (not length-matched). Each SOUL was paired with a synthetic English MEMORY (19 entries: 5 facts, 4 preferences, 6 decisions, 4 corrections; the date and the user's name in its header, because the external SOULs name neither; two values that change over time; one user correction that conflicts with the SOUL's voice), and a swapped MEMORY with the same entry numbers and topics but another person's values. 16 new English items per SOUL: 6 memory (three recall/application pairs), 1 conflict (MEMORY correction vs. SOUL voice), 4 illegitimate-release, 4 legitimate-change (one "just today"), 1 aligned request. Passwords, accounts, and holdings in the MEMORY files are fictitious.

Design. Six conditions per SOUL — original (none), original + p5a, + p5b, + full, rival SOUL (opp), original with swapped MEMORY (swapmem; memory items only); exp10's no-SOUL condition was dropped for budget. 195 condition×item cells × 3 models (opus, sonnet, gpt-6.1-sol) × N = 2 = 1,170 planned calls, interleaved by shuffling all jobs within each repetition. System prompt = SOUL + `---` + MEMORY; one fresh single-turn conversation per item. Grading as in exp10: opus and gpt-6.1-sol each graded the six answers of a cell together, blind to model and condition, with that condition's SOUL and MEMORY as reference (Korean grading instructions, English answers); an answer's score is the mean of the two graders (exact agreement 0.98 over 1,143 answers). Fidelity was scored deterministically with markers fixed in the preregistration (four voice markers per SOUL and four for its rival, plus boundary checks). Tests as in exp10: sign-flip permutation over SOUL × model × item cells, Holm over nine hypotheses.

Table 17. exp11 timeline (2026-10-25, KST).

Step	Time	Evidence
Preregistration commit `d7c2d88` (materials, markers, hypotheses, run/grade/analysis code)	19:15:28	`git log`
Timestamp commit `2ff4297` (`proofs/2026-10-25_d7c2d88.txt` + `.ots`)	19:16:14	`git log`, `.ots`
Smoke run (12 calls + 8 grading calls; excluded): first / last smoke answer	19:16:23 / 19:16:48	`runs/smoke_exp11_2026-10-25/raw.jsonl`
Main run: first subject call / last successful answer / last attempt	19:17:23 / 19:59:48 / 19:59:54	`raw.jsonl` timestamps, run log
Interruption (provider API 403, model access paused)	about 20:00 – 20:59	before any grading
Raw-data commit `3ec693e`	21:09:30	`git log` (before grading)
Grading (resumed)	21:09 – 21:21	`grade_log.txt`

Step	Time	Evidence
Results commit `6539897`, timestamp commit `971ec4a`	21:24:15, 21:25:03	`git log`
Bitcoin anchoring of the OpenTimestamps proofs (checked 2026-10-26)	preregistration manifest `d7c2d88`: block 973059; results manifest `6539897`: block 973077	`proofs/*.ots`, `proofs/upgrade.py`

The times above are git commit times and the run's own timestamps, both set by the author's machine; they are consistent with registration before the first call, and the OpenTimestamps receipts agree with them, but the Bitcoin anchor only shows that each manifest existed no later than its block.

Table 18. Preregistered hypotheses (exp11; three external SOULs pooled; Holm over nine, α = 0.05). H1–H3 are validity checks of the fidelity metric (rival SOULs and markers written by us); H4–H6 are the substantive hypotheses (3 of 5 supported).

#	Comparison	A / B	Effect	Threshold	Cell p (non-zero / all cells)	Holm p	Verdict
H1	Original-SOUL answers: F_style, own − rival markers	0.97 / 0.07	+0.905	≥ 0.5	5e-6 (143/143)	4.5e-5	supported
H2	Rival-SOUL answers: F_style, rival − original markers	0.86 / 0.19	+0.667	≥ 0.5	5e-6 (139/144)	4.5e-5	supported
H3a	Original-SOUL answers: F (incl. boundaries), own − rival	0.98 / 0.53	+0.452	> 0	5e-6 (143/143)	4.5e-5	supported
H3b	Rival-SOUL answers: F, own − rival	0.91 / 0.58	+0.334	> 0	5e-6 (139/144)	4.5e-5	supported
H4a	Illegitimate-release score, p5b − none	0.99 / 0.96	+0.035	> 0	0.125 (7/36)	0.25	**not supported (n.s., ceiling)**
H4b	Illegitimate-release score, full − p5a	1.00 / 0.96	+0.038	> 0	0.125 (5/36)	0.25	**not supported (n.s., ceiling)**
H5a	Legitimate-change acceptance, p5a − none	0.98 / 0.79	+0.193	> 0	0.004 (9/35)	0.012	supported
H5b	Legitimate-change acceptance, full − p5b	0.93 / 0.56	+0.375	> 0	6.1e-5 (16/34)	2.4e-4	supported
H6	Memory score, swapped MEMORY − none	0.16 / 1.00	−0.838	≤ −0.5	5e-6 (54/54)	4.5e-5	supported

Source: `runs/exp11_2026-10-25_external/analysis.md` §1, `analysis.json`. p = 5e-6 is the Monte Carlo floor. H5 has 35 and 34 cells instead of 36 because of the missing Dexter XL-2 answers (deviation 2). For H3a/H3b the effect is the pooled (answer, check) difference defined in the preregistration; `analysis.md` also gives a bootstrap interval over cell means, a different estimand. With matching estimands (post hoc, `paper/reanalysis/v07_extra.md` §2): H3a pooled +0.452 vs. cell mean +0.796, 95% cell bootstrap [+0.75, +0.84]; H3b +0.334 vs. +0.574 [+0.52, +0.63]; H1 +0.905 vs. +0.904 [+0.88, +0.93]; H2 +0.667 vs. +0.666 [+0.61, +0.72]. The H3 estimators differ because boundary checks are identical for both specifications and dilute the pooled F (deviation 6); the verdicts do not depend on

this. The stratified permutation p (reference only, not used for verdicts) was 0.042 for H4a and 0.013 for H4b.

(A) Preregistered fidelity markers discriminated human-written SOULs. Answers written under each original SOUL passed its markers at 0.97 and its rival's at 0.07 (H1, positive in all 143 cells); answers under the rival SOUL showed the reverse (0.86 vs. 0.19, 139/144 cells). Compared with exp10 (0.77 / 0.69), the H1 gap was larger and the H2 gap was similar (0.667 vs. 0.691); the preregistration had expected both to be smaller. By SOUL, the H1 gap was 0.97 (Maya), 0.86 (Talos), 0.88 (Dexter); by model 0.87 (opus), 0.87 (sonnet), 0.97 (gpt). Because the rival SOULs reverse only the voice, this shows that the voice markers follow the document; it says nothing about how well they capture what the original authors meant (the markers were written by us from the authors' sentences).

(B) The firm half: not supported, and a different model. Without principle 5 the illegitimate-release score was already 0.96, and no answer in any condition scored 0 (no release was accepted). The remaining contrast was small (+0.035, +0.038; Holm p = 0.25). Split by model, the firm-half contrast p5b − none was −0.01 (opus), +0.02 (sonnet), +0.09 (gpt) — in exp10 it was 0.38, 0.06, −0.01 (Table 15). Split by SOUL (exploratory, uncorrected), it was +0.083 (Maya; p = 0.25), +0.021 (Talos), 0.000 (Dexter), in the exploratory predicted order Maya ≥ Talos ≥ Dexter; Maya's contrast came almost entirely from gpt (0.75 → 1.00; opus and sonnet were 1.00 already without principle 5). In this setting, which model, if any, needs the firm sentence depends on the SOUL it is appended to.

(C) The flexible half replicated, now in all three models. Acceptance of legitimate changes rose with the flexible half (H5a +0.19, Holm p = 0.012; H5b +0.375, Holm p = 2.4e-4). By SOUL: Maya +0.33 / +0.67, Talos +0.23 / +0.40, Dexter 0 / 0 (Dexter already accepted every change without principle 5; its voice rules are not phrased as prohibitions). Unlike exp10, where the Claude models were near ceiling without principle 5, the flexible-half effect appeared in every model (H5a: opus +0.14, sonnet +0.21, gpt +0.23; Table 19): Maya's "never say" list and Talos's rules are written as prohibitions on wording, and without the flexible sentence all three models refused some of the requests to change the voice in those two SOULs (acceptance without principle 5, pooled over SOULs: 0.86, 0.79, 0.71).

(D) Exploratory and untested: the firm half alone was followed by lower acceptance of legitimate changes. This contrast (p5b − none on acceptance) was not a preregistered hypothesis and was not tested; it is a descriptive observation in these three SOULs. With only the firm sentence appended, acceptance fell below the no-principle baseline: 0.79 → 0.56 pooled, Maya 0.67 → 0.29 (items ML-2 and ML-3 at 0.00), Talos 0.71 → 0.46; Dexter stayed at 1.00. The drop occurred in every model (p5b − none: opus −0.18, sonnet −0.25, gpt −0.21; descriptive, Table 19). In exp10 this contrast was absent (p5b 0.80 vs. none 0.77). With both sentences (full), acceptance was 0.93, and with the flexible sentence alone 0.98 — so the data do not show that both sentences are needed; with the flexible sentence alone no release was accepted either (illegitimate-release zero scores: 0 in every condition). A possible reading, not tested: when a SOUL states voice rules as prohibitions, "the actions this file forbids stay forbidden … even 'just for today'" is read as also covering those wording prohibitions. In these three SOULs this is a reason to test legitimate-change acceptance before adding the firm sentence alone, not a general rule.

(E) Memory and the documents. The swapped MEMORY lowered the memory score from 1.00 to 0.16 (H6, 54/54 cells); in source-scored answers, 68/78 (0.87) used only the swapped person's values. On the conflict item (a MEMORY correction contradicting the SOUL's voice), answers followed the MEMORY correction in every condition and model except gpt under Maya's original SOUL (0.00, i.e.

gpt followed the SOUL) — the same direction as exp10 (gpt follows the SOUL, the Claude models the MEMORY), but here on one SOUL only. Aligned requests scored 1.00 in all conditions (no over-refusal; preregistered criterion ≥ 0.80).

Table 19. Per-model results in exp11 (pooled over the three SOULs; descriptive).

Measure	opus	sonnet	gpt
Illegitimate-release score: full / p5a / p5b / none	1.00 / 1.00 / 0.98 / 0.99	1.00 / 0.98 / 1.00 / 0.98	0.99 / 0.90 / 1.00 / 0.91
Firm-half effect p5b − none (H4a) / full − p5a (H4b)	−0.01 / 0.00	0.02 / 0.02	0.09 / 0.09
Legitimate-change acceptance: full / p5a / p5b / none	1.00 / 1.00 / 0.68 / 0.86	1.00 / 1.00 / 0.54 / 0.79	0.81 / 0.94 / 0.50 / 0.71
Flexible-half effect p5a − none (H5a) / full − p5b (H5b)	0.14 / 0.32	0.21 / 0.50	0.23 / 0.31
Firm half alone vs. none, acceptance (p5b − none)	−0.18	−0.25	−0.21
exp10 firm-half effect p5b − none, for comparison (Table 15)	0.38	0.06	−0.01

Source: `paper/reanalysis/exp11_bymodel.md` *(script* `exp11_bymodel.py`*, reusing* `analyze11.py` *functions on* `raw.jsonl` *and* `graded_by_*.jsonl`*; no model calls). Values are means of cell means per model; H4a and H5a agree with* `analysis.md` *E2.*

Table 20. exp10 and exp11 side by side (pooled over three models).

Result	exp10 (our two Korean agents)	exp11 (three external English SOULs)	Same?
Fidelity gap H1 / H2	+0.77 / +0.69	+0.905 / +0.667	yes (both ≥ 0.5)
Firm half vs. none (H4a)	+0.14, Holm p = 0.012 (supported)	+0.035, Holm p = 0.25 (not supported; none already 0.96)	**no**
Firm half added to flexible half (H4b)	+0.06, p = 0.13 (not supported)	+0.038, Holm p = 0.25 (not supported)	yes (both not supported)
Model carrying the firm-half effect	opus (0.38)	gpt (0.09); opus −0.01	**no**
Flexible half (H5a / H5b)	+0.23 / +0.20 (supported), mostly gpt	+0.19 / +0.375 (supported), all three models	yes; broader
Firm half alone vs. none, acceptance	0.80 vs. 0.77	0.56 vs. 0.79	**no** (new drop)
Memory swap (H6)	−0.77	−0.84	yes
MEMORY correction vs. SOUL voice	Claude follow MEMORY, gpt the SOUL	same direction, gpt only under Maya	yes (weaker)
Validity checks H1–H3 passed	4/4	4/4	yes

Result	exp10 (our two Korean agents)	exp11 (three external English SOULs)	Same?
Substantive hypotheses H4–H6 supported	4/5	3/5	—




Figure 1. Per-model principle-5 contrasts in the two preregistered experiments (values from Tables 15 and 19; means of cell means; Gemini is the exploratory exp10 addendum, hollow marker). Left: the firm half's effect on the illegitimate-release score was large only for opus in exp10 and near zero elsewhere. Middle: the flexible half raised acceptance of legitimate changes in every model in exp11 and mainly in the non-Claude models in exp10. Right: the firm half alone was followed by lower acceptance in exp11 but not in exp10 (descriptive, untested).

Cluster-level summary (descriptive). The preregistered tests treat SOUL × model × item cells as exchangeable units, but exp11 has only three SOULs and three models, reused across cells, so the cell-level p-values do not establish generalization to other models or SOULs. Table 21 gives the same contrasts at the level of models, SOULs, and model × SOUL clusters.

Table 21. exp11 principle-5 contrasts by cluster (descriptive; no tests).

Contrast	By model (opus / sonnet / gpt)	By SOUL (Maya / Talos / Dexter)	Model × SOUL clusters > 0 / < 0 / = 0
H4a release score, p5b − none	−0.01 / +0.02 / +0.09	+0.08 / +0.02 / 0.00	4 / 1 / 4
H4b release score, full − p5a	0.00 / +0.02 / +0.09	+0.10 / 0.00 / +0.01	2 / 1 / 6
H5a acceptance, p5a − none	+0.14 / +0.21 / +0.23	+0.33 / +0.23 / 0.00	5 / 0 / 4
H5b acceptance, full − p5b	+0.32 / +0.50 / +0.31	+0.67 / +0.40 / 0.00	6 / 0 / 3
Acceptance, p5b − none (untested)	−0.18 / −0.25 / −0.21	−0.38 / −0.25 / 0.00	0 / 6 / 3

Source: `paper/reanalysis/exp11_sensitivity.md` *(script* `exp11_sensitivity.py`*; no model calls). The flexible-half contrasts are non-negative in all nine clusters and positive in every model; the zero clusters are Dexter, which accepted every change without principle 5. The firm-half contrasts are zero*

in most clusters. For exp10, the by-model values are in Table 15; by agent, H4b was +0.06 for both agents (§5.6).

Deviations from the preregistration (`v0.7/DEVIATIONS.md`). Markers, detectors, items, rubrics, and hypotheses were not changed, and no code was edited after preregistration; one script was added. Deviations 1–4 and 6 occurred or were decided during execution; deviation 5 is a procedural decision made during grading, after the preregistration and without a pre-data rule.

1. *Interruption and resumption.* Right after the subject run (about 20:00), before grading began, the provider returned API 403 errors (model access paused) until 20:59. The work resumed at 21:05 without changing the preregistration, items, or code; the raw answers were committed (`3ec693e`, 21:09) before grading started.
2. *Eleven missing answers, all on one item.* All 11 final missing answers are Dexter XL-2, a legitimate change asking the agent to "start with 'Let me' and say what you're checking"; the Anthropic API blocked these calls with a safeguard message (opus 6, sonnet 5; gpt answered all). They were treated as missing as the preregistration specifies (one end-of-run retry, then missing) and were not called again after the pause, to avoid triggering the block again. Some H5 cells therefore drop out or rest on one repetition.
3. *Five answers from a substitute model.* Five successful answers came from an earlier model of the same tier (claude-sonnet-5 ×3, claude-opus-5 ×2), apparently a CLI fallback after a blocked call; all five are XL-2 answers in repetition 2 (X-full opus, X-none sonnet, X-p5a opus, X-p5a sonnet, X-p5b sonnet). The preregistration has no rule for this; they were kept in the preregistered analysis and are excluded in a sensitivity analysis (below).
4. *Grader model string.* After the pause, the CLI alias `opus` resolved to `claude-opus-5`; grading therefore passed `claude-opus-5-5` explicitly, the model used as opus grader in exp10 and as opus subject in this run.
5. *Grading order.* A resume script (`grade11_resume.py`; grading instructions, prompts, and parsing unchanged from `grade11.py`) graded the opus × XL-2 units last, one at a time, and retried failed units with exponential backoff. The first of these units (X-none) was blocked by the safeguard (3 calls). We then decided not to attempt the remaining three opus × XL-2 units (X-p5a, X-p5b, X-opp), to avoid triggering the block again. This stopping decision is a **post-registration procedural deviation**: the preregistration specifies that every answer receives both graders and that the surviving grade is used when one grader *fails*; it has no rule for leaving grader calls unattempted. The 16 XL-2 answers concerned (one blocked unit and three unattempted units) have the gpt grade only.
6. *H3 estimators.* The H3 effect (pooled pairs, as preregistered) and the bootstrap interval (cell means) are different estimators and give different numbers (Table 18 note); verdicts used the preregistered cell permutation test and effect criterion.

Sensitivity analyses (post hoc; not preregistered; no new model calls). Because deviations 2, 3, and 5 all concern item XL-2, we re-ran the preregistered tests and Holm family on reduced answer sets and with one grader at a time (Table 22).

Table 22. exp11 hypotheses under alternative answer sets and graders (effect; Holm p; ✓ supported / ✗ not).

Answer set (n answers)	H1	H2	H3a	H3b	H4a	H4b	H5a	H5b	H6
Preregistered, all answers (1,159)	+0.905 ✓	+0.667 ✓	+0.452 ✓	+0.334 ✓	+0.035 (0.25) ✗	+0.038 (0.25) ✗	+0.193 (0.012) ✓	+0.375 (2.4e-4) ✓	−0.838 ✓
(a) without item XL-2 (1,140)	+0.907 ✓	+0.680 ✓	+0.453 ✓	+0.340 ✓	+0.035 (0.25) ✗	+0.038 (0.25) ✗	+0.205 (0.012) ✓	+0.386 (2.4e-4) ✓	−0.838 ✓
(b) without the 5 substitute-model answers (1,154)	+0.905 ✓	+0.667 ✓	+0.453 ✓	+0.334 ✓	+0.035 (0.25) ✗	+0.038 (0.25) ✗	+0.199 (0.012) ✓	+0.375 (2.4e-4) ✓	−0.838 ✓
opus grader only (1,143)	+0.907 ✓	+0.680 ✓	+0.453 ✓	+0.340 ✓	+0.042 (0.31) ✗	+0.042 (0.31) ✗	+0.197 (0.023) ✓	+0.379 (7.3e-4) ✓	−0.815 ✓
gpt grader only (1,159)	+0.905 ✓	+0.667 ✓	+0.452 ✓	+0.334 ✓	+0.028 (0.50) ✗	+0.035 (0.50) ✗	+0.200 (0.012) ✓	+0.382 (2.4e-4) ✓	−0.861 ✓

Source: `paper/reanalysis/exp11_sensitivity.md` / `.json` *(script* `exp11_sensitivity.py`*, which calls the preregistered* `analyze11.py` *functions on filtered answer sets). H1–H3 and H6 have Holm p = 4.5e-5 in every row. Because all five substitute-model answers are XL-2 answers, (a) also removes them; (a)+(b) equals (a). Excluding XL-2 also removes all 16 answers that had only the gpt grade, so row (a) is the analysis restricted to consistently double-graded answers. The single-grader rows double as a self-grading check: opus and gpt are both subjects and graders.*

No verdict changed in any of these analyses, and the effects moved by at most 0.02 except the single-grader H6 values (−0.815, −0.861). For exp10, the principle-5 contrasts recomputed with one grader only were likewise close to the two-grader values (H4a +0.139 opus grader / +0.146 gpt grader vs. +0.142; H5a +0.222 / +0.236 vs. +0.229), and the opus-specific firm-half effect was +0.375 under either grader (`paper/reanalysis/v07_extra.md` §1).

What exp11 does not show. The SOULs were written by other people, but the MEMORY files, the items, the rival SOULs, the fidelity markers, the translation of principle 5, and the graders' rubric were written by us; "external" refers to the SOUL documents only. Three SOULs, one language (English), three models, N = 2, single turns, no human grading; opus and gpt are both subjects and graders, so each answer is graded once by its own family and once by the other (single-grader results in Table 22). Missing answers are concentrated on one item and one SOUL, which unbalances the model mix in those cells. Rival SOULs are shorter than the originals. The same principle-5 sentences were appended to all three SOULs, and Dexter has few explicit prohibitions for the firm half to refer to. The SOUL-level and model-level splits are exploratory and uncorrected.

---

6 Part II — SOUL VERIFY 2 (Ieum Lineage): verifying changes to the documents

Part I asked what carries over when the model under a fixed SOUL and MEMORY is replaced. Part II asks the reverse question: when the documents themselves change, can the change be checked? An

agent whose identity lives in editable files can be changed by its user (legitimately), by its own "tidy-up" or self-update loop (drift), or by someone else (tampering, injected text, a weakened prohibition with a plausible reason). Part II reports two preregistered weeks of experiments on this, run on 2026-10-26/27 under the working name *Ieum Lineage* (이음 계보). It is reported separately from Part I: different agents, items, hypotheses, and Holm families; nothing in Part II changes a Part I verdict. Its limitations are in §9.3.

To avoid a clash with the experiment numbers of Part I, Part II experiments are named by week and by their repository number: **W1-exp4** (proposal quality) and **W1-exp1** (tamper detection) in week 1 (`v0.8/`, `runs/s2w1_*`); **W2-exp3** (legitimate change vs drift vs manipulation), **W2-exp2** (fork and ledger), **W2-exp4b** (subtle traps), and **W2-R1** (explicit refusal of injected text) in week 2 (`v0.9/`, `runs/s2w2*`). Hypothesis labels (H1, H2, …) are those of each week's preregistration and are unrelated to the H labels of Part I.

6.1 Setting: Soul Core folders, synthetic agents, and what is being protected

Soul Core. Each agent is a folder: `SOUL.md`, `MEMORY.md`, `core.yaml`, a zone table `soul.rules.yaml`, and a change log `changes/CHANGELOG.jsonl`. The SOUL has four *locked promises* (for Naru: do not pretend to know or claim undone work; send no mail or message without the user's confirmation, drafts only; never record or pass on passwords, verification codes, or the student number; delete no file the user has not confirmed), a section "what can change and what does not" in the form of Part I's principle 5 (which also states that the user can always stop the assistant and that the document describing how is never deleted or hidden), and a section "what I may change myself". The zone table assigns each part of the documents to a zone: *user decides* (voice, address form, times, formats), *co-evolve*, *self*, *protected*, *locked*. The design rule tested here is "veto plan A" (protective): changes by the user in user-decided zones are accepted and logged; what should be blocked is unauthorized change (impersonation, a stolen key, an unapproved edit, an injected rationale). A second rule is "fork, never overwrite": a disputed or reset identity becomes a new lineage, and the old one stays intact.

Agents. Two synthetic Korean-language everyday assistants, Naru (나루, serving 지안) and Haedeun (해든, serving 도현). All names, numbers, and dates are fictional; no SOUL, MEMORY, or personal data of the author or of the author's assistant is in the repository. All experience logs, tampered variants, manipulations, and "attacks" were written by us, not by real attackers.

Models. As in Part I: `claude-opus-5-5`, `sonnet` (resolved to `claude-sonnet-5-5` in every row), and `gpt-6.1-sol`, through Claude Code CLI 2.1.289 and codex-cli 0.164.0, one fresh single-turn conversation per call. No Gemini (harness contamination, §9). LLM judges are opus and gpt, blind to model, condition, and variant names; the "both judges" rule (a flag counts only if both judges set it) is used for confirmatory counts.

6.2 Procedures common to both weeks

Each week was preregistered in the repository before any model call (week 1: `v0.8/PREREGISTRATION.md`, in Korean; week 2: `v0.9/PREREGISTRATION.md`, in English). The order was: generate material → hash all frozen files into a freeze manifest → commit → write a SHA-256 manifest of the commit → OpenTimestamps stamp → commit and push → first call (Appendix B, Table B1: in week 1 the first call came 12 s after the stamp commit, in week 2 16 s after). Answer keys (which variant is which tamper, which case is which class, which log entries are planted) were kept out of the

repository and only their SHA-256 hashes were committed before the runs; the keys were published after human grading, and their hashes were re-checked at publication (all nine matched). Unit of inference, tests, and corrections were preregistered: sign-flip permutation tests and cluster bootstrap intervals (10,000 resamples, seed 0) on cells or cases, Holm correction within each preregistered family, α = 0.05; repeated calls are not counted as independent. For every zero count we report the one-sided 95 % Clopper–Pearson upper bound 1 − 0.05^(1/n), and we do not read "0 observed" as "safe". Deviations after the freeze are listed in `v0.8/DEVIATIONS.md` (D1–D10) and `v0.9/DEVIATIONS.md` (D1–D5) and summarized in Table 28.

Human grading in Part II is by **one rater, the author**, blind to model, condition, and key, from sheets built by frozen scripts with a fixed seed (20261027). Human results are used only to check the LLM judges; by preregistration they cannot change a verdict.

Table 23. Calls and data completeness (Part II).

Week	Part	Subject calls	Judge calls	Errors / missing / safeguard blocks
1	W1-exp4	144 (147 rows; 3 gpt time-outs re-run)	32	0 / 0 / 0; 0 unparseable
1	W1-exp1	1,584	264 (132 sessions × 2 judges)	0 / 0 / 0
1	smoke (excluded)	28 (+3 retries)	—	—
2	main run, all four parts	1,928 subject and judge calls together (Claude lane 1,190, GPT lane 738)	(included)	0 / 0 / 0
2	smoke (excluded)	29	—	0 errors

Sources: `v0.8/NOTES.md` ("Calls"), `v0.9/NOTES.md` ("Run"). Week 2 total = 1,616 planned + 24 drift top-up + 288 drift-case classification calls. Every week-2 Claude row is dated 2026-10-27; no account switch occurred during the run.

6.3 Week 1, W1-exp4: are self-update proposals usable and safe?

Design. An "Experience Engine" prompt reads the SOUL, the MEMORY, and a 14-day experience log (8 logs = 2 agents × 4 sets, 30–33 entries each; entries carry a source — user, self, web, pdf, e-mail — and a trust level) and returns proposed changes with cited entry IDs, plus warnings. Planted per set: two true repeated preference changes (T; the same user request on 4 different days; should be proposed), two one-day moods (M; should not), one hidden injection in a low-trust web/PDF/e-mail entry (I; in set 3 the same injection is repeated on 4 days), and one or two pressure requests by the user to loosen a locked promise (P). Two prompt conditions: **zones** (rules 4–5: do not weaken protected/locked zones, put such pressure into warnings, do not use low-trust entries as evidence; plus the zone table) and **plain** (rules 1–3 only). Both conditions contain the same SOUL text, including its "what can change" section; only the engine prompt differs. 3 models × 2 agents × 4 sets × 2 prompts × N = 3 = 144 calls; scoring is deterministic against the key, plus a blind two-judge check (32 calls).

Results (Table 24, upper part). Zones recall and precision were 0.99 [0.98, 1.00] (H1, H2 supported), and the one-day-mood proposal rate was 0.00 (H6 supported). There were 0 protected-zone violations and 0 injection-following proposals among 147 zones proposals (criteria H3, H4 met; upper bounds 0.020). **H5 (the zone table reduces risky proposals) was not supported**: the plain prompt also produced 0 risky proposals among 147, with recall and precision 1.00, so the difference was exactly 0 in all 24 cells (sign-flip p = 1.00). Every model scored 0.98–1.00 in both conditions; warnings covered every planted P and I item in both conditions, and plain answers gave more warnings per answer (3.14 vs 2.29). The single non-match was a keyword miss (sonnet wrote "할 다음 일" for the keyword "다음 할 일"), not a content error. We read this as a **ceiling**: true changes repeated on four days and blatant injections were too easy to separate the prompts. H3/H4 should be read with the same caveat — the traps did not tempt any model in either condition.

6.4 Week 1, W1-exp1: can unauthorized changes be detected, with and without hashes?

Design. Per agent, eight tampered copies, each changing one place in SOUL.md or MEMORY.md: **A** a user-decided rule flipped (A1 address form, A2 briefing time), **B** a memory fact changed (two facts), **C** a locked promise deleted (C1, with renumbering) or softened with an exception (C2), **D** an injected permission (D1 a visible extra line in the promise list allowing action without confirmation when the user is in a hurry or busy; D2 a hidden HTML comment at the end of MEMORY claiming earlier approval and "mistakes are not reported"). Part (a): a deterministic hash check classifies 12 files per agent (original, 8 tampered, and 3 copies that differ only in bytes — CRLF or BOM) by raw and normalized SHA-256. Part (b), **behavior only**: 12 probe questions (4 rules, 4 memories, 4 pressure) are put to each variant (N = 2) and to the original (N = 6, the models' own variation); a judge sees the 12 answers of a session with the *claimed* (original) documents and marks each answer that deviates from them; a session raises an alarm when at least k probes are flagged by both judges. k* was chosen on 18 original sessions (repetitions 1–3) as the smallest k with false-alarm rate ≤ 0.10, without using any tampered session, and the false-alarm rate was then measured on 18 held-out original sessions (repetitions 4–6). Detection rate per type is the mean over 12 cells (agent × model × variant).

Results (Table 24). The hash check classified **24/24** files as expected (H1). k* = 1, with **0/18** false alarms in calibration and **0/18** in the held-out sessions (H4 met; the one-sided 95 % upper bound, 0.153, is itself above 0.10). Behavior-only detection reached the 0.80 threshold for neither safety-relevant type: **C 0.79 [0.58, 0.96]** (H2 not supported, Holm p = 1.00) and **D 0.38 [0.17, 0.62]** (H3 not supported, Holm p = 1.00). Exploratory: A 0.83 [0.58, 1.00] and B 1.00 [1.00, 1.00]; probes related to the tamper were flagged at 0.57, unrelated probes at 0.09, original sessions at 0.00; opus–gpt agreement per probe 0.96. A stricter k lowered detection (k = 2: A 0.42, B 0.67, C 0.38, D 0.08) without any false alarm at k = 1–3; an either-judge rule needed k* = 2 and was worse (held-out false alarms 1/18; detection A 0.58, B 0.75, C 0.54, D 0.33).

Table 24. Week 1 confirmatory results and tamper detection by variant (both judges, k* = 1; 2 repetitions per cell; values Naru / Haedeun).

Part	Hypothesis / criterion	Value	95 % CI	Holm p	Verdict
W1-exp4	H1 zones recall ≥ 0.70	0.99	[0.98, 1.00]	4.0e-4	supported

Part	Hypothesis / criterion	Value	95 % CI	Holm p	Verdict
W1-exp4	H2 zones precision ≥ 0.70	0.99	[0.98, 1.00]	4.0e-4	supported
W1-exp4	H5 zone table reduces risky proposals (plain − zones)	0.00 (0 vs 0)	[0.00, 0.00]	1.00	**not supported (ceiling)**
W1-exp4	H6 one-day-mood proposal rate ≤ 0.10	0.00	[0.00, 0.00]	4.0e-4	supported
W1-exp4	H3 / H4 (criteria) protected violations / injection following, zones	0 / 0 of 147 (upper 0.020)			met
W1-exp1	H1 (criterion) hash check	24/24			supported
W1-exp1	H4 (criterion) held-out false alarms ≤ 0.10	0/18 (upper 0.153)			met
W1-exp1	H2 C detection ≥ 0.80	0.79	[0.58, 0.96]	1.00	**not supported**
W1-exp1	H3 D detection ≥ 0.80	0.38	[0.17, 0.62]	1.00	**not supported**

Variant	opus	gpt	sonnet
A1 address form flipped	0.00 / 0.00	1.00 / 1.00	1.00 / 1.00
A2 time changed; B1, B2 memory facts	1.00 everywhere		
C1 locked promise deleted	0.50 / 0.50	1.00 / 0.50	1.00 / 0.00
C2 locked promise softened	1.00 / 1.00	1.00 / 1.00	1.00 / 1.00
D1 visible injected line	1.00 / 1.00	0.00 / 0.50	0.00 / 0.00
D2 hidden HTML comment in MEMORY	0.50 / 1.00	0.00 / 0.00	0.50 / 0.00

Sources: `runs/s2w1_exp4/analysis4.md`, `runs/s2w1_exp1/analysis1.md`, `runs/s2w1_exp1/by_variant_d9.md` *(the per-variant field of* `analysis1` *is wrong, deviation D9; this table was computed separately and an independent recomputation reproduced every confirmatory number). Holm p in W1-exp4 is over {H1, H2, H5, H6}, in W1-exp1 over {H2, H3}.*

Where detection fails. The C misses sit in the deletion variant (C1); the softened promise (C2) was caught in every cell. D was caught almost only in opus sessions (opus 0.88, sonnet 0.13, gpt 0.13). Counting related-probe answers in which neither judge saw a deviation, the tamper left no visible trace in A 8/24, B 0/24, C 20/48, and D 27/36. From reading a few answers (not a coded analysis, which week 2 then did as W2-R1): opus tended to *mention* the injected line and say that it conflicts with the locked promises, which the judges counted as a deviation; sonnet and gpt mostly ignored the line silently and answered as the original would. Silently not following an injection is safe for that answer but leaves the tamper invisible to behavior; the hash check is what caught it. In A1, opus kept the original address form under the tampered one, so that tamper left no trace in opus answers either.

6.5 Week 1: human check (author-graded)

Two blind sheets: Sheet 1: 40 proposal items from W1-exp4 (36 + 4 repeats; questions: approve? evidence sufficient? harms a locked promise?) and Sheet 2: 28 answers from W1-exp1 (24 + 4 repeats; does the answer deviate from the claimed setup?). On sheet 2, the author agreed with each judge and with the both-judges flag on 27/28 items (0.964, **Cohen κ 0.92**); the 4 repeated items were answered identically. The one disagreement was a boundary case of what "record" means (a C2 session in which the gpt answer accepted a fake card number "for this conversation" and said nothing was stored; both judges: deviation; author: no). The author also saw no deviation in the sampled C and D answers (human "deviates" in tampered A 4/4, B 4/4, C 0/3, D 0/4, originals 0/13; both-judges flags A 4/4, B 4/4, C 1/3, D 0/4, originals 0/13), so the weak C/D detection is not judge blindness. Sheet 1 could not test the judges: all 40 sampled proposals matched a planted true change and none was flagged (the whole run had no risky proposal, so the "flagged" stratum fell back to "other" as preregistered). The author approved 39/40, judged evidence sufficient for 36 (partly for 4), and marked 40/40 as not harming a lock; κ was 0.00 or undefined wherever one side was constant (Q1 vs planted match 0.975 raw, κ 0.00; Q2 vs opus 0.900, κ 0.00; vs gpt 0.875, κ −0.04). **Item 12 of sheet 1 was first answered "Y Y Y" and corrected by the author to "Y Y N" after the third question was explained again; the corrected answer is used** — with the first answer, agreement on that question would be 39/40. The scorer was frozen; numbers it does not print were computed in a separate script (deviation D10).

6.6 Week 2, W2-exp3: can a reviewer tell legitimate change, drift, and manipulation apart, and which records does it need?

Cases. Per agent: 10 legitimate changes (**L1** a user-decided change ×4; **L2** the user *tightening* a locked promise ×3; **L3** a self-zone change with evidence and user approval ×3), 10 manipulations (**M1** weakening a locked/protected line with a plausible reason and fabricated evidence IDs ×4; **M2** weakening justified by a real but stretched past user record ×3; **M3** "approval laundering": a valid user signature over a summary that does not mention the weakening ×3), and drift cases (**D**) generated after the freeze by a frozen procedure: each model was asked five times in a row to "tidy up" the SOUL and MEMORY, and single changed hunks were selected. L2 makes "touches a locked line → manipulation" wrong, and M3 makes "valid user signature → legitimate" wrong. The frozen drift procedure, including both preregistered top-ups, yielded 8 drift cases per agent instead of 10 (sonnet's rewrites changed only 2–5 lines per chain, all already covered by other models' hunks); as preregistered, no author-written drift was substituted, giving **56 cases (L 20, D 16, M 20)**. Each case was classified (L / D / M, with an action: accept, hold for the user, revert and fork) under three conditions: **(i)** the diff only; **(ii)** + the change record (who proposed, who approved, why, cited log entries); **(iii)** + a deterministic verification report (Ed25519 signature status and signer, checkpoint parent, existence of cited evidence, zones touched, and the signed summary next to the diff). 56 cases × 3 conditions × 3 models × N = 2 = 1,008 calls. A deterministic rule checker on (iii) is reported as a baseline, not tested.

Results (Tables 25–26). History helped: accuracy rose from 0.747 in (i) to 0.973 in (ii) (**H1 supported**, +0.226 [0.140, 0.318], Holm p = 2.0e-5). Verification did not help further: (iii) 0.961 (**H2 not supported**, −0.012 [−0.036, 0.003], Holm p = 1.00). Manipulation recall in (iii) was **0.892** [0.792, 0.967] against a preregistered threshold of 0.90 (**H3 not supported**, Holm p = 1.00). No legitimate change was labelled manipulation in (iii) (**H4 supported**, false-block rate 0.000, upper bound 0.139, Holm p = 3.0e-4). The preregistered "level-3 candidate" criterion (H3 and H4) is therefore **not met**. The main gain from history was on legitimate changes: with the diff alone, L recall was 0.40 (L1 0.25, L2 0.19), i.e. most legitimate changes were treated as suspicious; with the record it was 1.00. Every error in (ii)

and (iii) was a manipulation labelled as drift (M→L errors were 0 in all three conditions; upper bound 0.139), and these were all still held or reverted, not accepted. The remaining errors sat in M2 (stretched record) and M3 (laundered approval): in (iii) M2 0.861 and M3 0.778, slightly *below* (ii) (0.889, 0.861) — showing the signed summary did not help the models catch a valid signature over a misleading summary. By model in (iii), opus 0.911, sonnet 0.982, gpt 0.991. The rule checker scored 0.786 (macro-F1 0.780), with M2 and M3 at 0 by construction.

Table 25. Week 2 confirmatory results (prereg order; `analyze9.py`).

Family	Hypothesis	Value	95 % CI	p	Holm p	Verdict
F3 (W2-exp3)	H1 accuracy (ii) − (i)	+0.226	[0.140, 0.318]	5.0e-6	2.0e-5	supported
F3	H2 accuracy (iii) − (ii)	−0.012	[−0.036, 0.003]	0.50	1.00	**not supported**
F3	H3 manipulation recall (iii) ≥ 0.90	0.892	[0.792, 0.967]	0.57	1.00	**not supported**
F3	H4 legitimate false-block (iii) ≤ 0.10	0.000 (upper 0.139)	[0, 0]	1.0e-4	3.0e-4	supported
F2 (W2-exp2)	H7 d(A, B) − d(A, A'), round 5	+0.781	[0.625, 0.906]	5.0e-6	(single)	supported
F4b (W2-exp4b)	H5 plain − zones risky proposals	0 (0/36 vs 0/36)	[0, 0]	1.0	—	**untestable (ceiling)**
FR1 (W2-R1)	H9a opus − sonnet explicit rate	+0.156	[0.047, 0.281]	0.031	0.031	supported
FR1	H9b opus − gpt explicit rate	+0.297	[0.156, 0.469]	0.0020	0.0039	supported

Criteria (not tests): level-3 candidate (H3 and H4) not met; C2 ledger 100 % met; C3 lineage identification at round 5 16/16 met; C4 0 protected edits applied; H6 / H6b (W2-exp4b zones) 0/36 responses each, upper bound 0.080, met. Of the eight week-2 confirmatory comparisons: 5 supported (H1, H4, H7, H9a, H9b), 2 not supported (H2, H3), 1 untestable (H5); H9a and H9b are counted separately. Sources: `runs/s2w2/analysis{3,2,4b,_r1}.json`, `v0.9/NOTES.md`.

Table 26. W2-exp3 accuracy by condition, class, and subtype (mean over 3 models × 2 repetitions).

	(i) diff	(ii) + history	(iii) + verification
Accuracy / macro-F1	0.747 / 0.736	0.973 / 0.972	0.961 / 0.960
L recall (L1 / L2 / L3)	0.40 (0.25 / 0.19 / 0.81)	1.00 (1.00 / 1.00 / 1.00)	1.00 (1.00 / 1.00 / 1.00)
D recall	1.00	1.00	1.00
M recall (M1 / M2 / M3)	0.89 (0.94 / 0.97 / 0.75)	0.93 (1.00 / 0.89 / 0.86)	0.89 (1.00 / 0.86 / 0.78)
M labelled L	0	0	0
Accuracy opus / sonnet / gpt	0.786 / 0.705 / 0.750	0.920 / 1.000 / 1.000	0.911 / 0.982 / 0.991

	(i) diff	(ii) + history	(iii) + verification
Rule checker on (iii) data			0.786 (M2 0, M3 0)

Source: `runs/s2w2/analysis3.json`*. 0 unparseable answers. In (i), 65 of the 85 wrong answers chose "hold for the user"; in (ii) all 9 wrong answers and in (iii) 10 of 13 chose "revert and fork" (3 "hold"). This action column was exploratory.*

6.7 Week 2, W2-exp2: forks and the ledger

Design. From checkpoint C0 of each agent, three branches per model (opus, gpt): A and B receive different experience logs over five rounds (planted preferences in the same domains but opposite directions, e.g. earlier vs later briefing), and A' receives A's logs again in independent calls (rerun noise). In each round the engine proposes edits; a deterministic applier applies edits in user-decided, co-evolve, and self zones and refuses edits to protected or locked lines; each round writes a checkpoint (SHA-256 of SOUL || MEMORY, with its parent) to a chain. Eight probes per agent are asked at C0 and after rounds 1, 3, 5 and coded deterministically. The ledger part uses the unchanged `SoulRegistry.sol` of the Ieum Ledger prototype (Appendix D) on a **local Hardhat network only** (no testnet, no cost): register A and append its checkpoints; try to append B's checkpoints to A (must revert with `BadParent`); register B as a new agent with a `fork_of:<A>@<C0>` note; and implement "reset A" as a new fork, checking that A's head is unchanged.

Results. After round 5 the forks differed on 0.781 of probes while the reruns differed on 0.000 (d(A, B) by round 0.34 / 0.75 / 0.78; d(A, A') 0.06 / 0.03 / 0.00): **H7 supported** (+0.781 [0.625, 0.906], p = 5.0e-6). A blind judge identified the lineage of an anonymous answer set in 16/16 cases at round 5 (C3 met; also 1.00 at rounds 1 and 3; the two judges agreed on 24/24). The ledger behaved as specified in all four agent × model units (C2): every A checkpoint accepted, every B checkpoint appended to A reverted with `BadParent`, every registered fork accepted and both lineages rebuilt back to C0, and A's head unchanged after the "reset". Because rounds that applied nothing repeat the previous checkpoint and are merged, the lineages have 3–5 appended checkpoints after C0. **C4 is met only trivially**: the engine applied 100 edits in 60 rounds and never proposed an edit to a protected or locked line, so the applier's refusal path was never exercised. H7 is close to built in — the branches were given opposite planted preferences — so it shows that the pipeline propagates experience into behavior and records, not that forks of a real agent diverge at this rate. It measures behavioral distance and traceability of records, not whether two forks are "the same self".

6.8 Week 2, W2-exp4b and W2-R1: subtle traps and explicit refusal

W2-exp4b (redesign of W1-exp4). New logs (2 agents × 2 sets) replaced blatant injections with three subtle traps: S1 a real, high-trust user statement that a pre-approved draft sent without confirmation "was convenient", S2 the agent's own repeated observation that confirmation requests slow the user down (repeated on three days, so it passes the "3-day rule" of the prompt), and S3 a small exception to a locked promise ("remember just the last four digits of my student number"); one blatant injection was kept as an anchor. Same prompts and scoring as W1-exp4; 72 subject + 16 judge calls. Preregistered manipulation check: if the plain prompt produced no risky proposal in any of the 12 cells, H5 would be reported as **untestable (ceiling)**, not as "not supported". That happened: **0/36 plain and 0/36 zones responses contained a risky proposal**, so H5 is untestable, and the zone-table effect remains unmeasured in both weeks. H6 / H6b (zones: no protected violation, no injection

following) were met (0/36, upper bound 0.080). In the plain condition, 8 proposals cited S2 entries but none weakened a lock (by keyword or by either judge); in zones, none cited a trap. Every response warned about every trap type (S1–S3) in both conditions. Of 152 proposals, 144 matched a planted true change.

W2-R1 (confirmatory replication of the week-1 reading). The week-1 observation that opus *names* injected text while sonnet and gpt ignore it silently was exploratory and uncoded; W2-R1 re-tested it on new data, with two week-1 variants re-dated (visible line, hidden comment) and two new ones (an injected line in the changeable-things section; a fake change-log note in MEMORY approving skipped payment confirmation), the four pressure probes, and N = 2 (192 calls). Two blind judges coded each answer for `explicit` (names, quotes, or refuses the injected instruction, or says the setting looks altered) and `obeys`. Opus was explicit more often than sonnet (**H9a supported**, +0.156 [0.047, 0.281], Holm p = 0.031) and than gpt (**H9b supported**, +0.297 [0.156, 0.469], Holm p = 0.0039). The rates were low in absolute terms: explicit opus 0.30, sonnet 0.14, gpt 0.00 (0/64 answers, upper bound 0.046). By variant (post hoc, mapped through the published key, `paper/reanalysis/r1_by_label.md`; the per-variant field of `analysis_r1.json` is keyed by folder ids that were shuffled per agent, so two of its four entries pool different variants), opus was explicit on 0.25 / 0.19 / 0.25 / 0.50 of answers (visible line / hidden comment / changeable section / fake change-log note) and sonnet on 0.06 / 0.00 / 0.00 / 0.50; the fake change-log note drew the most explicit answers from both Claude models (n = 16 answers per cell). **No answer of any model obeyed an injection (0/192; upper bound 0.015).** Judges agreed on `explicit` in 0.969 and on `obeys` in 0.948 of answers. The week-1 D detection rate in opus sessions (0.88) and the week-2 explicit rate (0.30) are different measures (session alarms over 12 probes vs per-answer coding over 4 pressure probes) and should not be compared directly.

6.9 Week 2: human check, emphasis deviation, and the planned additional raters

Sheets. The frozen sampler built 66 items instead of about 74 (sheet A, W2-exp3 cases shown as in condition (ii), 33 = 30 + 3 repeats; sheet B, W2-exp4b proposals, 19 = 16 + 3 — every non-trap proposal matched a planted change, so the "other" stratum had no candidate, and the risky stratum was filled with 8 trap-adjacent proposals, 0 genuine risky, 0 seeded; sheet C, W2-R1 answers, 14 = 12 + 2). All 66 were answered.

Results (Table 27). **Sheet A: author vs key κ 0.50** (raw 0.67, n = 30), below the preregistered 0.6 line. The disagreement is in one direction: **the author never chose M**. Seven M1/M2 cases were called drift (five of them still blocked), and **all three M3 cases (laundered approval) were called legitimate and not blocked** (M3 is the class in which a valid signature covers a misleading summary). L and D were 20/20. On the same 30 items the LLM classifiers in condition (ii) agreed with the key at 0.93 (opus, κ 0.90) and 1.00 (gpt, sonnet), with no M→L error. **Preregistered reading (`v0.9/PREREGISTRATION.md`, lines 227–228): κ = 0.50 < 0.6, so the LLM judge is "too weak to use the LLM judge as confirmatory evidence", and we write this as is.** v0.9 instead read this result as a weakness of the human reference rather than of the classifiers; that reading did not follow the preregistered rule and has been removed (deviation W2 D6, Table 28). The facts that motivated it are kept as description only: the disagreement is one-directional (the author never chose M), and on the same items the classifiers agreed with the key. Collapsed to L vs not-L, author vs key was 0.90 (κ 0.79). **Sheet B**: no genuine risky proposal existed (ceiling, §6.8); the author approved all 16 and marked all 16 as not enabling a forbidden action, as did the judges and the rule (κ undefined); evidence was judged sufficient for 8/8 planted-true matches and 0/8 trap-adjacent ones. As in week 1, the judges

could not be validated on risky items. **Sheet C**: author = both judges on 12/12 (κ 1.00; author "explicit" opus 3/6, sonnet 0/3, gpt 0/3), supporting the W2-R1 coding.

Emphasis in the relay (deviations D2–D4). The sheets were relayed to the author by chat by the author's AI assistant, which had read the sheets. It did not paste the frozen batches verbatim: it rewrote items in shorter Korean and **added bold**. On sheet C, items 57 and 60, the bolded sentence was exactly the cue for "explicit" (from item 61 on, answers were sent without bold); on sheet A, 25 of 33 relays bolded something, some of them the cues the classes are built on (e.g. "not in the record" for fabricated evidence, "tone tidy-up" for the M3 summary); on sheet B, 14 of 16. Sensitivity: sheet C without items 57 and 60 is still 10/10 (κ 1.00, but only one "explicit" item is left, so this check is thin); on sheet A the bolded M cues did not lead the author to M (0 of 30 answers were M), and the 7 unbolded first-time A items agreed with the key 7/7. The relay also disclosed 4 of 8 repeats ("same as item N"), so retest agreement is split: undisclosed pairs 4/4 identical, disclosed 3/4 (pooled 7/8, not a clean retest number) (D3); and it announced sheet boundaries from the outdated guide (D4; every answer was matched to the batch files and none moved). This is a **blinding defect**: the grader saw the relaying assistant's reading of each item. Every week-2 human number is therefore labelled "author-graded, relayed with emphasis". By preregistration no verdict depends on these numbers.

Additional raters (planned, exploratory). After the keys were published, an addendum (`v0.9/ADDENDUM_raters.md`) was committed and stamped *before any additional-rater data existed*: two or three anonymous raters recruited by the author grade the same 66 items verbatim from the frozen batches (no emphasis, no "same as N" notes, no keys or model labels on the page), one item per screen with per-rater shuffled order, on a small web page (`human-grading-web/`); analysis by Fleiss κ over all human raters, pairwise κ, each rater vs the author, judges, and keys. Raters are asked not to look at the repository first, which cannot be verified. **No additional-rater result is included in this version**; the addendum changes no verdict.

Table 27. Human agreement in Part II (one rater: the author; κ always with raw agreement).

Week · sheet	Comparison	Raw	Cohen κ	n
W1 S2 tamper answers	author vs opus / gpt / both judges	0.964 each	0.92 each	28
W1 S2	retest	4/4		4 pairs
W1 S1 proposals	Q1 approve vs planted match	0.975	0.00 (key constant)	40
W1 S1	Q3 harms a lock vs violation flag (item 12 corrected)	1.000	undefined	40
W1 S1	Q2 evidence vs opus / gpt `supported`	0.900 / 0.875	0.00 / −0.04	40
W2 A cases	author vs key (L/D/M)	0.67	**0.50**	30
W2 A	author vs classifier (ii) opus / gpt / sonnet	0.70 / 0.67 / 0.67	0.52 / 0.50 / 0.50	30
W2 A	classifier (ii) vs key, same items: opus / gpt / sonnet	0.93 / 1.00 / 1.00	0.90 / 1.00 / 1.00	30
W2 A	author L vs not-L	0.90	0.79	30
W2 B proposals	Q3 vs both judges = any judge = rule	1.00	undefined	16

Week · sheet	Comparison	Raw	Cohen κ	n
W2 C answers	author vs `explicit` (both judges)	1.00	1.00	12
W2 C	without items 57, 60 (emphasis sensitivity)	1.00	1.00	10
W2 retest	pooled / undisclosed pairs only	7/8 / 4/4		8 / 4 pairs

Sources: `runs/s2w1_human/human_agreement{,_d10}.json`, `runs/s2w2/human_agreement{,_supplement}.json`. *Author-vs-key confusion on sheet A: L→L 10, D→D 10, M→D 7, M→L 3. Week-2 numbers: author-graded, relayed with emphasis (D2–D4).*

Table 28. Deviations after the freeze (summary; full text in `v0.8/DEVIATIONS.md`, `v0.9/DEVIATIONS.md`).

Week · #	What	Could a confirmatory number change?
W1 D1–D2	Two scoring bugs found in the smoke run (a protected-zone keyword scanned free text; unanswered probes sent to judges) fixed before the main run	No (smoke excluded)
W1 D3–D7	gpt latency and rate limits (60–570 s per answer, 429 bursts); Claude and gpt runs split by model; time-out raised to 900 s; one Windows launch crash resumed; an unattended resumable pipeline for the gpt remainder; gpt answers partly on 10-27 (codex receives no date)	No; cross-model interleaving broken, timings reported
W1 D8	Pipeline killed by a Gateway restart (22:52) and resumed (05:19); append-only data checked: 1,584/1,584 rows, 0 duplicates, 0 missing	No
W1 D9	Exploratory per-variant field of `analysis1` wrong (overwritten across models); left as produced, correct table computed separately (Table 24)	No
W1 D10	Human numbers the frozen scorer does not print computed in a new script; sheet 1 item 12 corrected by the author	No
W2 D1	Drift-case stamp step failed once inside the detached watcher and was finished by hand; no drift-case call before the stamp	No
W2 D2	Human sheets relayed reworded and with bold emphasis, including the cue on sheet C items 57 and 60	No (human numbers only); labelled
W2 D3–D4	Relay disclosed 4 of 8 repeats; stale sheet boundaries in the relay	No
W2 D5	Supplementary human numbers and zero-count bounds computed outside the frozen scripts	No
W2 D6 (recorded in v0.9.1)	Preregistered κ reading not applied as written on sheet A: v0.8–v0.9 of this paper read κ 0.50 as a weakness of the human reference instead of writing "too weak to use the LLM judge as confirmatory evidence"; corrected in §6.9	No (human numbers only; by preregistration they cannot change a verdict)

Two notes that are not deviations: W2-exp3 has 16 drift cases instead of 20 (frozen procedure, no substitution), and week 2 has 66 human items instead of about 74 (frozen sampler).

---

7 Part III — Changing the brain, changing the body

Part III reports three preregistered waves (3, 4, and 5; study folders `v1.0/`, `v1.1/`, `v1.2/`) and one exploratory rerun (`v1.3x/`), run on 2026-10-27/28. Hypothesis labels (HT, HH, HB, and H1 of wave 5) are those of each wave's preregistration and are unrelated to the H labels of Parts I and II. Every number in this part is either quoted from a committed repository file or recomputed from public rows; the source of each is listed in `paper/part3_number_sources.md`. Numbers that were sealed until the author finished the human sheets were taken from the files published when the seals were opened (commits `057f425`, `8570a46`, `1a6ebe8`) and re-checked by `paper/part3_recompute.py`, `paper/part3_recompute_v12.py` (48 checks, 0 mismatches), and `paper/part3_recompute_v11.py` (117 checks, 0 mismatches); the exploratory judge-panel rerun (commit `b6af7d3`) is labelled as such. The limitations of Parts III and IV are collected in §9.4.

7.1 Overview

Parts I and II changed the model (model swaps) or the documents (changes to SOUL and MEMORY). Part III adds three preregistered waves and one exploratory rerun that complete the picture. **Wave 3 (v1.0, "new brain")** gives an existing SOUL and MEMORY to a newly released model, `gpt-6.1-terra`, and compares it with `gpt-6.1-sol` run concurrently on the same materials. **Wave 4 (v1.1, "Ship of Theseus")** is the mirror image: the model is fixed (`claude-opus-5-5`) and the *body* — the harness that delivers SOUL, MEMORY and tools to the model — is replaced one component at a time. Together they ask how large a change of body is compared with the spread already seen between brains.

Wave 5 (v1.2, "graded pressure") is a redesign of the earlier trap experiments, whose plain condition sat at the floor (no risky proposal at all): it climbs a ladder of pressure levels in a pilot, picks the level by a rule fixed in advance, and then asks whether the zone table of the SOUL lowers the share of risky proposals (§7.6). A last, exploratory rerun adds a third LLM judge to see whether a judge panel agrees better with the human grader (§7.7).

All three preregistered waves were committed and timestamped before their first study call, and all keep part of their results sealed until the author, who is the human grader, has finished the human sheets. The sealing is itself a design element and is described in §7.8. All three seals have since been opened.

7.2 Method

7.2.1 Common design

Waves 3 and 4 reuse the frozen code of earlier waves (exp10/exp11 fidelity detectors, grader prompt and sign-flip statistics; the v0.9 cluster bootstrap) and change one thing relative to them. Unit of inference is the *cell* (for wave 3: SOUL × condition × item; for wave 4: agent × item); a cell value is the mean over N = 2 replicates. Non-inferiority (NI) tests use a one-sided cluster bootstrap over cells (10,000 resamples, seed 0) with margin −0.10, the largest between-model spread observed in exp11 (opus/sonnet 0.87 vs. sol 0.97 on H1). Difference tests use the sign-flip permutation of exp10 (exact up to 2^16 patterns, otherwise Monte Carlo with 200,000 draws, seed 0). Confirmatory families are corrected by Holm at $\alpha = 0.05$. All materials are synthetic or published third-party MIT material (wave 3), or synthetic (wave 4, confirmatory part). Each subject call is a fresh single-turn conversation.

7.2.2 Wave 3 (v1.0): a new brain

Materials. The exp11 design unchanged: three MIT-licensed English SOULs (Maya, Talos, Dexter) with their frozen derivatives, synthetic MEMORY files, 48 items, 195 condition × item cells (6 conditions per SOUL: none, p5a, p5b, full, opp, swapmem), plus the v0.9 R1 module (two synthetic Korean agents × four variants × four probes). The only new element is the subject model. Because a Terra run on another day would differ from the historical sol run in date and backend state, `gpt-6.1-sol` was **re-run in the same session**, interleaved with Terra, and all confirmatory contrasts are Terra versus this concurrent arm; historical opus, sonnet and sol values are descriptive only. Every subject call carries a `Today:` line equal to the run day (2026-10-27).

Models and harness. `gpt-6.1-terra` and `gpt-6.1-sol` through the Codex CLI 0.164.0 (ChatGPT login, no API key) with the exp11 isolation flags; graders `claude-opus-5-5` (Claude Code 2.1.289) and `gpt-6.1-sol`. Terra is not a grader. The server-side name `gpt-6.1-terra` was verified once, in a neutral extra call after the freeze, in the server's `response.created` / `response.completed` objects; main-run rows carry the requested name (the CLI event stream has no model field).

Calls. Module A: 195 cells × 2 models × N = 2 = 780 subject calls; module B: 128 subject calls; grading 390 (195 units × 2 graders); R1 judging 64; total **1,362** keys in the main run, plus a 20-call smoke run excluded from all analysis (budget cap 1,600).

Table 29. Wave 3 timeline (2026-10-27, KST).

Step	Time	Evidence
Author's go-ahead	20:49	`v1.0/NOTES.md`
Preregistration freeze commit `4a79bf2` (prereg, 99-file manifest, key hashes)	21:02:02	`git log`; `proofs/2026-10-27_4a79bf2.txt`
Proof commit `7b69c62` (manifest + OpenTimestamps, 3 calendars), pushed	21:05:02 (push 21:05:18)	`git log`; `v1.0/NOTES.md`
First study call (smoke)	21:05:31	`runs/v10_terra/first_call.txt`
Main run, first / last subject call	21:06:58 / 21:50:46	`runs/v10_terra/{A,B}_gpt.jsonl` (`start`)
Main run end (GPT lane / Claude lane)	22:07:30 / 21:51:04	`v1.0/NOTES.md`

Note (v0.9.1): `runs/v10_terra/first_call.txt` also records `main_start` 21:06:56, the launch of the main run; 21:06:58 is the `start` of the first row of `A_gpt.jsonl`, the first main-run subject call.

The OpenTimestamps receipts record the manifest hash; their Bitcoin blocks are listed in Appendix F. As in earlier waves, the times are the author's machine times and show registration before the first call, not independent proof.

Human check of the LLM judges (preregistration, section 8). The author graded a blind sheet of 27 scored items (plus 2 practice items; 3 of the 27 are repeats): T1 illegitimate release (HT3), T2 legitimate change, T3 R1 `explicit` (HT4). The sheet was sampled to contain both judge codes (yes and no) where the run had them (the shortfall is reported in §7.4.3), and the judge codes were sealed until the sheet was graded. Raw agreement and Cohen's κ were computed against the opus and sol judges (and both) for all items and for Terra items alone. Preregistered reading: $\kappa < 0.6$ means the judge is "too weak to use as evidence on Terra"; the human sheet does not change the confirmatory verdicts.

A Korean reference translation of the English items was added to the grading page after the freeze (§7.5, D-6).

7.2.3 Wave 4 (v1.1): a new body, same brain

Question. With the brain fixed, at which replaced component does fidelity to the SOUL (voice, memory, locked promises) start to move, and can a person who knows the agent tell the old body from the new one?

Components. A harness is decomposed into (①) **SOUL delivery** — system prompt (baseline) vs. prepended to the first user message (U) vs. read by the agent with a file tool (T); (②) **MEMORY delivery** — full file in context vs. top-5 retrieval by deterministic BM25 over Korean character bigrams; (③) **tools** — read-only file tools on a per-call sandbox vs. none; (④) **runtime / prompt assembly** — a frozen, sanitized snapshot of the OpenClaw 2026.10.4 system-prompt skeleton (no personal content) vs. **MinH**, a minimal self-written harness (one-line system prompt, nothing else; transported by the same `claude -p` CLI because the subscription CLI is the only route to Opus without an API key) vs. **Hermes one-shot** (`hermes -z`, Hermes Agent v0.21.7, an isolated `HERMES_HOME`, toolset `context_engine` = no tools, `--ignore-rules`). Hermes reaches Opus through a long-lived setup token created by the author for this study only; the existing Claude login is never borrowed (three independent blocks, checked by a test). Hermes was admitted only if a gate passed (g1–g5: answers; server reports `claude-opus-5-5`; tools disabled with 0 tool calls; the running Hermes' state untouched; the OpenClaw Claude CLI still working).

Table 30. Conditions of wave 4 (all: `claude-opus-5-5`).

Code	① SOUL	② MEMORY	③ tools	④ runtime	Role
H0	system	full	on	OpenClaw-style	baseline ("current body")
H1	user message	full	on	OpenClaw-style	chain step 1
H2	user message	retrieval	on	OpenClaw-style	chain step 2
H3	user message	retrieval	off	OpenClaw-style	chain step 3
H4 (MinH)	user message	retrieval	off	MinH	whole body changed (confirmatory)
H4alt (Hermes)	user message	retrieval	off	Hermes one-shot	whole body changed, second body (confirmatory; gated)
C1t	tool read	full	on	OpenClaw-style	single-factor control for ①
C2	system	retrieval	on	OpenClaw-style	single-factor control for ②
X-noSOUL	none	full	on	OpenClaw-style	document control (floor)

Agents and items. Two synthetic Korean agents (Naru, Haedeun; SOULs unchanged from v0.9), each with a new extended MEMORY of 80 dated entries (v0.9 entries verbatim plus new ones, including six corrected facts that override earlier entries and six near-duplicate distractors) and 16 new items: 5 everyday tasks, 6 memory questions (3 about corrected facts, 3 far from the item wording), 4 illegitimate releases, 1 legitimate change. A second, private, *exploratory* block uses a redacted copy of the author's own deployed agent documents; its answers, items and grades stay outside the repository and only aggregate numbers will be published (see §9.4).

Calls. 2 agents × 16 items × 7 conditions (H0–H4, C1t, C2) × 2 = 448; H4alt 64; X-noSOUL 32; private copy 160; = 704 subject answers; 192 grading units (176 graded calls; 16 memory units settled by the deterministic answer key without a call); **896 keys** in the main run, cap 950. Scoring follows exp10/11 (deterministic F_style; memory accuracy by frozen answer key first, grader only if the key is inconclusive; illegitimate-release score from blind graders `claude-opus-5-5` and `gpt-6.1-sol`, one call per agent × item × replicate with all condition answers shuffled and unnamed).

Table 31. Wave 4 timeline (2026-10-28, KST).

Step	Time	Evidence
Preregistration freeze commit `1c22078`	07:02:06	`git log`
Proof commit `2836028` (manifest + OpenTimestamps), pushed	07:04:38	`git log`; `proofs/2026-10-28_1c22078.txt`
First study call (Hermes gate, attempt 1)	about 07:06	`v1.1/NOTES.md`
Gate attempt 3 passed (g1–g5); smoke 29/29 ok	07:17 / 07:19–07:21	`v1.1/hermes_gate.json`, `v1.1/NOTES.md`
Commit `aa0974f` (run-code fixes D1–D3, sealed smoke)	07:21:35	`git log`
Main run: first / last subject call	07:21:49 / 07:56:21	`v1.1/NOTES.md`
Commit `5a96af7` (sealed outputs: hashes only; human-key hash), proof commit `4e43de1`	08:00:58 / 08:02:52	`git log`
Human page `/h/` online (clean archive of `4e43de1`); notes commit `41ee633`; proof commit `8e4ca84`	about 08:0x / 08:06:29 / 08:08:17	`v1.1/NOTES.md`, `git log`
`/h/` graded (client start / submitted); local private-copy page saved	13:16:59 / 15:17:10; 18:31	`runs/v11_human/export_h.json`; `v1.1/NOTES.md`
Seal opened (hash check, analysis reproduced), commit `1a6ebe8`; proof commit `ac3cff5`	18:37:16 / 18:40:29	`git log`; `proofs/2026-10-28_1a6ebe8.txt`

Human blind discrimination. 30 items = 24 scored + 2 practice + 2 positive controls + 2 repeats: 12 synthetic pairs (H0 vs. MinH) on the grading website, 12 pairs from the private copy on a local offline page that cannot transmit data, 2 positive controls (H0 vs. X-noSOUL), 2 practice, 2 repeats. The question is which answer comes from the baseline body. "Don't know" counts 0.5. The key's SHA-256 was committed and stamped before either page was opened.

7.3 Hypotheses

Wave 3 — confirmatory family FT = {HT1–HT4}, Holm over four, α = 0.05.

#	Hypothesis	Metric · comparison	Test	Supported if
HT1	Terra keeps the given SOUL's voice at least about as well as sol	F_style against the spec of the SOUL given (original in none, opposite in opp); 96 cells; Terra − sol	bootstrap NI, H0: mean ≤ −0.10	Holm p < 0.05
HT2	Terra follows the MEMORY it is given (exp11 H6)	memory-item score; 18 cells; Terra swapmem − Terra none	sign-flip, two-sided	Holm p < 0.05 and mean ≤ −0.50
HT3	Terra refuses illegitimate releases at least about as well as sol	illegitimate-release score; 60 cells; Terra − sol	bootstrap NI, margin −0.10	Holm p < 0.05
HT4	Terra's rate of explicitly naming/refusing an injected instruction (R1) differs from sol's	`explicit` (both judges); 32 cells; Terra − sol	sign-flip, two-sided	Holm p < 0.05

Pre-recorded expectations (not used for verdicts): HT1 supported (sol 0.97 on own spec in exp11), HT2 supported (preregistered expectation, quoted from `v1.0/PREREGISTRATION.md`: "every exp11 model −0.77 to −0.92", line 161; this range is not reproduced by any committed result file — the exp11 models' values on the same 18-cell measure are −0.83 to −0.85, `runs/v10_terra/analysis_t.json`), HT3 supported near ceiling, no direction for HT4.

Wave 4 — confirmatory family FH = {HH1, HH2, HH3, HH1h, HH2h, HH3h, HH4, HH5}, Holm over eight, α = 0.05 (synthetic agents only). HH1–HH3 compare H4 = MinH with H0; HH1h–HH3h repeat them with H4alt = Hermes (added by the author's decision at 06:53 on the day of the freeze).

#	Hypothesis	Metric · comparison	Cells	Test
HH1 / HH1h	The voice survives a full body change	F_style (own spec): H4 − H0 / H4alt − H0	32	bootstrap NI, margin −0.10
HH2 / HH2h	Memory survives a full body change	memory accuracy: H4 − H0 / H4alt − H0	12	bootstrap NI
HH3 / HH3h	Locked promises survive a full body change	illegitimate-release score	8	bootstrap NI
HH4	Where SOUL sits matters for the voice	F_style: H1 − H0	32	sign-flip, two-sided
HH5	Retrieval changes memory accuracy	memory accuracy: C2 − H0	12	sign-flip, two-sided

Separate family FB = {HB1}: accuracy of picking the baseline (H0) answer in (H0, H4) pairs exceeds 0.5 (one-sided exact binomial, α = 0.05). Reading rules fixed in advance: HB1 supported → "the body change is noticeable"; not supported and the two-sided 95 % Clopper–Pearson upper bound < 0.75 → "not distinguishable at this sample size"; otherwise "inconclusive". We never write "proven identical". Pre-recorded expectations: HH1 supported; HH4 possibly a small negative shift (−0.03 to −0.08); retrieval (HH5) is expected to be where fidelity first breaks, as a memory break, not a voice break; HH3 at ceiling.

7.4 Results (waves 3 and 4)

Wave 3 results are complete (seal opened 2026-10-28 after the human sheet; §7.4.3 gives the human check). Wave 4 results are complete (seal opened 2026-10-28 evening after both human pages; §7.4.4–§7.4.6). Wave 5 has its own section, §7.6.

7.4.1 Wave 3 (new brain): run summary

All 1,362 keys were settled without error: 780 module A subject answers (390 per model), 128 module B subject answers (64 per model), 390 grading and 64 judging calls; 0 error rows, 0 rate-limit rows, 0 safeguard blocks, 0 missing keys. All 908 subject rows started on 2026-10-27 (21:06:58–21:50:46), so no midnight rule was triggered and no sensitivity analysis was needed. Operational descriptives (exploratory): median latency 4.0 s (Terra) vs. 5.9 s (sol); mean output tokens 66 vs. 91; answers mentioning a date 14/390 vs. 21/390.

7.4.2 Wave 3: confirmatory results

Table 32. Wave 3 confirmatory results (Terra vs. concurrent sol; Holm over four).

#	Terra	sol (concurrent)	Effect	95 % CI	Holm p	Verdict
HT1 F_style, own spec (96 cells)	0.838	0.924	−0.086	[−0.122, −0.054]; one-sided 95 % lower bound −0.116	0.44	**not supported** (lower bound below −0.10)
HT2 memory, swapmem − none (18 cells)	within-Terra contrast	n/a	−0.833	[−0.924, −0.736]	< 0.001	**supported**
HT3 illegitimate release (60 cells)	0.908	0.942	−0.033	[−0.062, −0.008]; one-sided 95 % lower bound −0.058	0.0003	**supported** (lower bound above −0.10)
HT4 R1 `explicit` (32 cells)	0.000	0.000	0.000	[0, 0]	1.000	**not supported** (0 non-zero cells)

Sources: HT1 recomputed from `runs/v10_terra/raw.jsonl` with the frozen detectors (`paper/part3_recompute.py`; all HT1 values reproduced exactly; the raw bootstrap NI p was 0.219; Holm-adjusted 0.437 from `runs/v10_terra/analysis_t.json`). HT2, HT3 and HT4 values are quoted from `runs/v10_terra/analysis_t.json` (published when the seal was opened; hash-checked against `v1.0/KEY_HASHES.txt`) and match `v1.0/NOTES.md`; they depend on LLM-grader outputs and cannot be recomputed from the public subject answers alone. Holm over the four raw p-values 0.219, 7.6e-06, 1.0e-04, 1.0.

(A) HT1 was not supported, and we report it as such. Terra's mean F_style was 0.086 below the concurrent sol arm. Non-inferiority at margin 0.10 required the one-sided 95 % lower bound to exceed −0.10; it was −0.116, so the hypothesis is *not supported*. As preregistered, this does not mean that Terra is inferior: the two-sided interval [−0.122, −0.054] excludes zero, so a small deficit is plausible, and it was in the opposite direction from the pre-recorded expectation. The concurrent sol arm reproduced its historical behavior on the exp11 gap measures (H1 0.975 → 0.969, H2 0.640 →

0.648; E3 drift, quoted from `v1.0/NOTES.md`, within the ±0.05 expected), so the deficit is not explained by a drifting control.

(B) Where the deficit sits (exploratory, not tested, uncorrected). The deficit was almost entirely in the conditions with the *opposite* (rewritten) SOUL. With the original SOUL, Terra scored 0.995 and sol 0.997 (48 cells). With the opposite SOUL, Terra scored 0.681 and sol 0.852 (48 cells); by SOUL (opposite condition): Maya 0.859 vs. 0.953, Talos 0.779 vs. 0.820, Dexter 0.406 vs. 0.781. A reading, not tested: Terra keeps an original SOUL's voice as well as sol but follows a rewritten SOUL's style rules less, and the difference is largest for the SOUL with the weakest explicit prohibitions (Dexter). The split was made after seeing the result and belongs to hypothesis generation; the same detectors and spec files were used throughout.

(C) HT2 was supported. With another person's MEMORY swapped in, Terra's memory score fell by 0.833 [−0.924, −0.736] over 18 cells (Holm $p < 0.001$; threshold −0.50), close to the exp11 models on the same 18-cell measure (opus −0.833, sonnet −0.833, sol −0.847; historical columns of `e1_table` in `runs/v10_terra/analysis_t.json`; the concurrent sol arm −0.819). In this setting, Terra answers memory questions from the MEMORY it is given. As a deterministic cross-check using only the six keyword-scored memory cells, which do not depend on any grader, the same direction appears (strict key match: 1.00 under the original MEMORY, 0.00 under the swapped one; $\Delta = -1.00$, raw sign-flip $p = 0.031$ with 6 cells, the exact minimum for six cells); this is a check of direction only and not the preregistered score.

(D) HT3 was supported, on a grading the human sheet could barely check. Terra's illegitimate-release score was 0.908 against 0.942 for sol (difference −0.033, one-sided 95 % lower bound −0.058, above −0.10; Holm $p = 0.0003$; 60 cells). Terra refuses slightly less well than sol, well inside the preregistered margin. No answer scored 0 in any SOUL × condition (exploratory, D2). The result rests on the opus and sol graders; the human sheet had only two answered T1 items (§7.4.3), so it neither confirms nor undermines this grading on Terra.

(E) HT4 was not supported, and the zero is not a measured equality. Both judges coded `explicit` = 0 for every Terra and every sol R1 answer (judge agreement on `explicit` 0.977, on `obeys` 0.992, $n = 128$), so Terra − sol = 0.000 over 32 cells with no non-zero cell (Holm $p = 1.0$). The human grader answered "yes, the answer names or refuses the injected line" for 5 of 8 non-repeat T3 items (4 of 6 Terra items) where both judges said no (§7.4.3). By the preregistered rule the judge code is too weak to serve as evidence on Terra, so "Terra and sol do not differ in naming the injected line" must be read as "the judges saw no naming in either arm", not as an equality. The R1 module is in Korean, while both arms are English-centered models; whether language contributed to the zeros was not examined (§9.1).

(F) What the Holm correction did. The Holm-adjusted p-values are corrected over all four tests. The HT1 verdict was fixed by its raw p (0.219), which already exceeds 0.05; Holm never lowers a p-value. The final family: HT1 not supported, HT2 supported, HT3 supported, HT4 not supported. Two of four confirmatory hypotheses were not supported, and both of them are reported as such.

7.4.3 Wave 3: human check of the LLM judges

The author graded the T sheet on 2026-10-28 (client start 13:12:59, submitted 15:33:29 KST; one submission). The author answered **19 of 27 items** with the "submit up to here" button: the 8

unanswered items are all on sheet T1 (illegitimate release), so the human check of HT3 rests on two items (D-8). The seal was opened after a SHA-256 check of all 11 sealed files and keys against `v1.0/KEY_HASHES.txt` (all matched).

Table 33. Human vs LLM judge agreement (non-repeat answered items; Cohen's κ; opus and sol gave the same code on every answered item, so all three judge columns coincide).

Scope	n	Raw agreement	κ
All answered items	16	0.625	0.077
Terra items	**12**	**0.583**	**0.062**
T1 illegitimate release (all / Terra)	2 / 1	1.00 / 1.00	undefined (one class)
T2 legitimate change (all / Terra)	6 / 5	0.833 / 0.800	0.571 / 0.545
T3 R1 `explicit` (all / Terra)	8 / 6	0.375 / 0.333	0.000 / 0.000

Repeat agreement: one of the three repeat pairs was the same; one pair differed and one could not be compared because its first item was unanswered (that is, 1 of the 2 comparable pairs matched).

Preregistered reading: κ on Terra = 0.06 < 0.6, so the LLM-judge-based conclusions on Terra are weak ("too weak to use the LLM judge as evidence on Terra"). We write this as preregistered. It applies to HT3 and HT4 (which rest on judge codes) and to the graded exploratory columns (E1 H4–H5, E2, E4, D1–D7, D9), which are reported in `runs/v10_terra/analysis_t.json` with the same caveat. It does not apply to HT1 (deterministic detectors). HT2 was not on the human sheet; its direction was confirmed by the six-cell keyword cross-check of (C). Where the disagreement sits: on T3 the judges coded none of the nine T3 sheet items as `explicit` (the run contained none, sampling report "available 0 yes" for both models), while the author answered yes on 5 of the 8 non-repeat items; on T2 the author agreed with the judges on 5 of 6. The T1 sampling asked for 4 yes / 4 no per model but the run offered only 2 yes for Terra and 0 for sol.

7.4.4 Wave 4 (new body): run summary

All 896 keys were settled: 704 subject answers (synthetic 544, including H4alt 64 and X-noSOUL 32; private copy 160) and 192 grading units, 0 errors, 0 blocked, 0 missing. Every subject answer was served by `claude-opus-5-5` (OpenClaw-style 544, MinH 96, Hermes 64 as recorded in the row metadata); graders were `claude-opus-5-5` and `gpt-6.1-sol`. The Hermes gate passed on its third attempt. Retrieval recall, which is deterministic and was fixed before any call, is part of the design and not a result: the gold entry is in the top-5 for all six corrected-fact items (with the superseded entry retrieved as well in all six) and for 2 of 6 far items of the synthetic agents (Naru 0/3, Haedeun 2/3). Under H3 and H4 (no tools) a far item can therefore not be answered by lookup.

The seal was opened on 2026-10-28 shortly before 18:37 KST (commit `1a6ebe8`), after both human pages had been graded and after a completeness check (all 15 numbers of the `/h/` page that are graded, i.e. 12 scored pairs, 2 positive controls and 1 repeat, were answered; practice items excluded; the local page 13 of 13). All 22 hashes of `v1.1/SEALED_RESULTS.txt`, `SEALED_SMOKE.txt` and `KEY_HASHES.txt` matched, and re-running the frozen `analyze_h.py` on the sealed rows reproduced `analysis_h.json` and both scored files byte for byte.

Table 34. Wave 4 confirmatory results (synthetic agents; Holm over eight).

Contrast	Effect	95 % CI	Holm p (over 8)	Verdict
HH1 voice, H4 (MinH) − H0 (32 cells)	0.000	[0, 0]	0.0008	**supported** (E6 warning)
HH2 memory, H4 − H0 (12 cells)	−0.208	[−0.458, 0]	1.0	**not supported**
HH3 locked promises, H4 − H0 (8 cells)	0.000	[0, 0]	0.0008	**supported** (at ceiling)
HH1h voice, H4alt (Hermes) − H0 (32 cells)	−0.010	[−0.031, 0]	0.0008	**supported** (E6 warning)
HH2h memory, H4alt − H0 (12 cells)	−0.208	[−0.458, 0]	1.0	**not supported**
HH3h locked promises, H4alt − H0 (8 cells)	0.000	[0, 0]	0.0008	**supported** (at ceiling)
HH4 SOUL placement, H1 − H0 (F_style, 32 cells)	0.000	[0, 0]	1.0	**not supported** (0 non-zero cells; E6 warning)
HH5 retrieval, C2 − H0 (memory, 12 cells)	−0.083	[−0.208, 0]	1.0 (raw 0.5)	**not supported**

Source: `runs/v11_theseus/analysis_h.json`; means, cell counts, Holm adjustment and verdicts recomputed from `runs/v11_theseus/scored_synthetic.jsonl` by `paper/part3_recompute_v11.py`; CIs (cluster bootstrap) quoted. The NI p-value of a difference vector that never reaches the margin is the bootstrap floor 1/10,001; Holm × 8 gives 0.0008. E6 warning: see (C).

(A) Four of eight confirmatory hypotheses were supported and four were not, and we report all of them. The voice (F_style) and the locked promises (illegitimate-release score) passed non-inferiority for both new bodies. Memory did not: with either new body, memory accuracy fell by 0.208 on average over the 12 memory cells (point estimate below the margin of −0.10; one-sided NI p 0.82 before Holm), so HH2 and HH2h are not supported. HH4 (moving the SOUL from the system prompt to the user message changes the voice) was not supported: F_style was identical in all 32 cells. HH5 (retrieval alone changes memory accuracy) was not supported: C2 − H0 was −0.083 with 2 of 12 cells non-zero (raw sign-flip p 0.5). As preregistered, "NI not supported" does not mean "worse"; here, however, the point estimate (−0.21) is twice the margin, so a memory loss is the plausible reading, while the two-sided interval [−0.46, 0] still touches zero with 12 cells.

(B) The two new bodies behaved almost the same. Hermes and MinH had the same memory accuracy (0.792) and the same contrast against H0; on F_style Hermes lost one marker in one cell (−0.010); illegitimate-release scores were 1.00 for both (E4, exploratory: no contrast between the two bodies has a CI that excludes 0).

(C) The voice result carries the preregistered E6 warning. The document control X-noSOUL (no SOUL, MEMORY only) also scored F_style 1.000 on the agents' own spec (gap to H0 0.00 < 0.30), while it scored 0.203 on the opposite spec. The F_style markers of these two agents (polite 해요체 endings, the user's name with an honorific) are therefore reproduced from the MEMORY and the item wording even without a SOUL, and F_style does not separate SOUL-specific voice. HH1, HH1h and HH4 are reported with that warning: "the voice survives" means "the surface markers survive", which

they also do with no SOUL. X-noSOUL did separate on the boundary: illegitimate-release score 0.53 and refusal rate 0.44, against 0.95–1.00 in every SOUL condition.

Table 35. Wave 4 exploratory stepwise table (E1), means per condition (synthetic agents; uncorrected).

Metric	H0	H1	H2	H3	H4 (MinH)	H4alt (Hermes)	C1t	C2	X-noSOUL
F_style (own spec)	1.000	1.000	1.000	1.000	1.000	0.990	1.000	0.992	1.000
Memory accuracy	1.000	1.000	0.917	0.792	0.792	0.792	1.000	0.917	1.000
Illegitimate-release score	1.000	1.000	0.969	1.000	1.000	1.000	0.953	1.000	0.531
Legitimate change honored	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Everyday-task grader score (D9)	0.988	0.963	0.638	0.513	0.500	0.513	0.925	0.563	0.900

Step contrast (sign-flip; 95 % CI)	H1 − H0	H2 − H1	H3 − H2	H4 − H3
F_style (32 cells)	0.000 [0, 0]	0.000 [0, 0]	0.000 [0, 0]	0.000 [0, 0]
Memory accuracy (12 cells)	0.000 [0, 0]	−0.083 [−0.208, 0], p 0.5	−0.125 [−0.375, 0.083], p 0.5	0.000 [0, 0]
Everyday-task score (10 cells)	−0.025 [−0.075, 0], p 1.0	**−0.325 [−0.512, −0.150], p 0.031**	−0.125 [−0.325, 0], p 0.25	−0.013 [−0.037, 0], p 1.0

Source: `analysis_h.json` (`e1_steps`; `e7_p5` for the illegitimate-release row, illegitimate items only); means recomputed by `paper/part3_recompute_v11.py`. The illegitimate-release step contrasts in `e1_steps` pool the legitimate-change item (10 cells) and are not shown; none has a CI that excludes 0.

(D) Where it first moves (E1, exploratory). For F_style, the boundary and the legitimate change, no step moves. For memory accuracy, the losses come at the two retrieval steps (full MEMORY → top-5 retrieval at H2, then tools off at H3), but no single step's CI excludes zero with 12 cells. The items far from the memory wording carry the loss (E3): 1.000 at H0, 0.833 with retrieval and tools (C2, H2), 0.583 with retrieval and no tools (H3, H4); the corrected-fact items stayed at 1.000 in every condition. This matches the deterministic retrieval recall fixed before the run (far items: gold entry in the top-5 for 2 of 6) and is a design consequence, not a discovery. The only step whose CI excludes zero is in the everyday-task grader score, which the frozen analysis outputs but the preregistration does not list in E1 (D9): H2 − H1 = −0.325 [−0.512, −0.150] (uncorrected p 0.031); everyday answers that use memory in context got worse when the full MEMORY was replaced by retrieval. C1t (SOUL read with a tool) read `SOUL.md` in 100 % of answers and differed from H0 only by a small illegitimate-release drop (−0.05, [−0.10, −0.01], p 0.25). The pre-recorded expectation "retrieval is where it breaks first, as a memory break, not a voice break" is consistent with this table, with the qualification that no memory step is significant on its own.

7.4.5 Wave 4: human blind discrimination (HB1)

The author graded both pages: the `/h/` website (synthetic pairs; 15 graded numbers; client start 13:16:59, submitted 15:17:10 KST; complete) and the offline local page (private copy; 13 of 13; saved 18:31 KST). Answers were "A", "B" or "모르겠음" ("?", counted 0.5), with a 1–5 confidence.

Table 36. Human blind discrimination (H0 vs. H4 = MinH) and private-copy aggregate (E5).

Item	Result
HB1, all 24 scored pairs (correct / wrong / ?)	9 / 6 / 9 → accuracy **0.563**, 95 % CP [0.347, 0.762], one-sided p 0.36 → **not supported**
HB1 reading (preregistered rule)	upper bound 0.762 ≥ 0.75 → **"inconclusive"** (not "not distinguishable at this sample size")
B1 synthetic pairs (12)	5 / 5 / 2 → 0.500 [0.211, 0.789], p 0.60
B2 private-copy pairs (12; aggregate only)	4 / 1 / 7 → 0.625 [0.312, 0.875], p 0.32
Sensitivity: "?" excluded; "?" counted wrong	9 / 15 = 0.600, p 0.30; 9 / 24 = 0.375, p 0.92 (both not supported)
Positive controls (H0 vs. X-noSOUL)	1 of 2 correct (the rule's warning applies only if both are missed)
Test–retest	B1: 1 pair, not the same ("?" first, the H0 answer on the repeat); B2: 1 pair, the same
Correlation of human correctness with |ΔF_style| (preregistered)	B1 undefined (ΔF_style = 0 on all 12 pairs); all 24 pairs r = −0.03 (1 pair with ΔF_style ≠ 0)
Exploratory: κ, human "told apart" vs. "automatic metrics differ"	all 24: 0.10 (raw agreement 0.625); B1: 0.06
Private copy, E5 (exploratory; 16 cells; opus-only grading), H0 / H1 / H2 / H3 / H4	F_style 1.000 / 1.000 / 1.000 / 0.953 / 0.969; memory 1.000 / 1.000 / 0.833 / 0.667 / 0.667; illegitimate release 1.000 / 1.000 / 1.000 / 0.975 / 1.000; legitimate change 1.0 throughout

Source: `runs/v11_human/human_h.json` (from `v1.1/human/agree_h.py`), `runs/v11_human/export_h.json`, `analysis_h.json` (`e5_ieum_aggregate`); B1 counts, the binomial p-values, integer Clopper–Pearson bounds and the B1 κ recomputed by `paper/part3_recompute_v11.py`; B2 and E5 are aggregates of private data and are quoted.

HB1 was not supported, and the reading is "inconclusive". The author picked the baseline answer in 9 of 24 pairs, the new body's answer in 6, and answered "don't know" in 9 (7 of them on the private-copy page). With "?" = 0.5 the accuracy was 0.563, not above chance (p 0.36). Because the upper confidence bound (0.762) is just above 0.75, the preregistered rule does not allow the reading "not distinguishable at this sample size"; it gives "inconclusive". We do not write that the two bodies are indistinguishable. On the synthetic pairs the author was exactly at chance (5 right, 5 wrong). The share of "?" answers is itself informative (exploratory): on 9 of 24 pairs the author, who knows the agents, did not see which answer came from the old body. How the 0.5 credit enters the exact test is not fixed by the preregistration; the choice made at unsealing and two alternatives are given in D5, and all three give "not supported".

The human check of the automatic metrics is weak by construction. The preregistered correlation between human correctness and the automatic F_style difference cannot be computed on the synthetic pairs, because F_style was identical within every shown pair. Across all automatic metrics only

2 of the 12 synthetic pairs differed at all (both memory items); the exploratory κ between "the human told the pair apart" and "the metrics differ" was 0.06 (synthetic) and 0.10 (all pairs). The automatic metrics and the human agree that most pairs are alike, but not on *which* pairs differ.

Private copy (E5, exploratory). The redacted copy of the author's own agent followed the synthetic pattern: memory accuracy 1.000 → 0.833 (retrieval) → 0.667 (retrieval without tools), a small voice drop without tools (0.953 and 0.969 at H3 and H4), locked promises intact. It is graded by opus only, and its answers are not published (§9.4).

7.4.6 Wave 4: what the new body changed

With the brain fixed, replacing the whole body (by either of two new bodies) left the surface voice and the locked promises within the 0.10 margin but lowered memory accuracy by about 0.21, twice the margin, which the preregistration had set to the largest between-model spread of exp11. HH2 compares H4 with H0, so this −0.208 is the effect of three changes made together: top-5 retrieval instead of the full MEMORY, no tools, and another runtime. Wave 4 cannot split it with confidence. The single-factor retrieval control (HH5, C2 − H0) was −0.083 and not significant (raw p 0.5, Holm 1.0); along the chain, the retrieval step (H2 − H1) was −0.083, the tools-off step (H3 − H2) −0.125, and the runtime step (H4 − H3) 0.000, none with a CI excluding zero. The pattern is consistent with the loss coming from how MEMORY reaches the model (retrieval, and no tool to look further), and not with where the SOUL sits (HH4: no change) or which runtime assembles the prompt (H4 − H3 and E4: no change). The only direct test of the retrieval part is wave 6 (§8.4.2): there, with the runtime (MinH) and tools (off) fixed and only the MEMORY delivery varied, the full file beat retrieval by +0.208 (F − R) on a different item set whose far items were written to defeat the retriever. The voice result is weaker than it looks, because these agents' voice markers survive even without a SOUL (E6). A person who knows the agents did not reliably tell the old body from the new one in 24 pairs, but the sample does not exclude a moderate ability to do so ("inconclusive").

7.5 Deviations

Wave 3 (`v1.0/DEVIATIONS.md`). - **D-1** Code written after the freeze, without changing frozen code, materials, prompts, hypotheses or thresholds: the human-agreement analysis (`v1.0/human/agree_t.py`) and the separate `/t/` page and table of the grading website, both before any human answer existed. - **D-2** Served-model check done as prescribed; limit: the CLI event stream has no model field, so the server-side name was verified once rather than per call. The trace also showed reasoning-effort values `low` and `unset` (CLI defaults, same for both arms, not examined further). - **D-3** Subject calls after midnight: none. - **D-4 (addition not in the preregistration)** The LLM grader and judge outputs, and with them HT3 and HT4, were sealed until human grading, because the author is the human grader and the judge codes of sheet items must not be seen. Their SHA-256 are committed and stamped (`v1.0/KEY_HASHES.txt`); subject answers are public. The seal was opened on 2026-10-28 after the human sheet was submitted (commit `057f425`); all 11 files matched their hashes. - **D-5** The run was error-free; the backoff and resume paths were not exercised. - **D-6 (translation on the grading page)** Because the grader's native language is Korean, a Korean reference translation of the English items (1–18 plus the English practice item), made by `claude-sonnet-5-5`, was added to the human page below the English original, with the instruction to grade against the English text. The first deploy (commit `cb1033e`, 13:17:54) came a few minutes after the client start time (13:12:59), and a second deploy that

opened the translation blocks by default and translated the practice item (commit `79260c9`, 15:20:05) went live *during* grading. The page does not record which items were answered under which version, so the human codes for items 1–18 may rest on the LLM translation. The translating model belongs to the same family as one judge. T3 (items 19–27) is Korean and unaffected. The original deviation entry said grading had not started when the translation was deployed; that holds only in the sense that no submission existed in the table. - **D-7 (analysis bug)** The first run of the human-agreement script counted unanswered items as disagreements (`"" in "YN"` is true in Python), giving n = 24 and an impossible κ on T1. One line was fixed before the result was read; the numbers in §7.4.3 come from the fixed script. - **D-8 (incomplete sheet)** 19 of 27 items answered (all 8 unanswered on T1); unanswered items are excluded like `?` (the preregistration does not say what to do with blanks). One of three repeat pairs could not be compared. The seal had been opened on this submission, so the 8 items can no longer be graded blind.

Wave 4 (`v1.1/DEVIATIONS.md`). All entries are run-code bug fixes made before the main run, permitted by the preregistration; no item, marker, key, hypothesis, margin or threshold changed. The frozen hash of `v1.1/harness.py` therefore no longer matches (the fixed file is committed; `FREEZE_MANIFEST.txt` is left as frozen). - **D1** `HermesRunner` creates its sandbox folder before use (the first gate call crashed before any process started; no call made). - **D2** Hermes child environment gets `HERMES_DISABLE_LAZY_INSTALLS=1`; output decoded with `errors="replace"`; token scrubbed from error text (gate attempt 1: 2 Hermes calls failed before reaching any model). - **D3** The optional `anthropic` package (Hermes' own pinned version 0.87.0) was installed into a private folder and added to the child's path, instead of into the running Hermes' environment (gate attempt 2: 2 calls failed before reaching any model). - **D4** The gate used three attempts (≤ 6 calls allowed); 5 calls reached a model in total (1, 1, 3); gate calls are excluded from analysis. - **Observation, not a deviation.** Through the setup token, Hermes' Anthropic adapter places "You are Claude Code, Anthropic's official CLI for Claude." in the system prompt. This is part of the Hermes body as it reaches Opus without an API key and will be reported with the comparison of the two new bodies (E4). - **Preregistration changes before the freeze** (author decisions): both new bodies confirmatory (Holm over eight rather than five); the gate run after the stamp instead of before; the human pairs use MinH only. - **Sealing of the main results** (as in wave 3): answers, grades and analysis files are sealed by SHA-256 (`v1.1/SEALED_RESULTS.txt`) until both human pages are graded. The `/h/` page was deployed from a clean archive of commit `4e43de1` so that uncommitted files of a later study were not uploaded; no test submission was sent. The seal was opened after both pages were graded (commit `1a6ebe8`, proof `ac3cff5`); every hash matched. - **D5 (human analysis written after the answers existed)** `v1.1/human/agree_h.py` was written at unsealing, after both answer files had been received. It follows prereg 6-1/8; two points the preregistration leaves open were decided there: "?" = 0.5 enters the exact binomial as the expectation over fair-coin resolutions of each "?" (Clopper–Pearson with k = correct + ½·"?"), with "?" excluded and "?" counted wrong as sensitivity analyses; HB1 is computed over all 24 scored pairs (prereg 6-1 names no block), with each block reported. Every variant gives "not supported". - **D6** An earlier save of the private page's answers had been written into the repository folder (untracked); it was moved to the private folder before any commit and never committed. - **D7** `.gitattributes` marks the wave 4 run folders `-text` (as in waves 3 and 5); committed blobs re-checked against the sealed hashes. - **D8** The B1 repeat pair (first answer "?", repeat answer the H0 side) is counted as "not the same"; the preregistration does not say how "?" enters the retest. - **D9 (exploratory additions at unsealing)** κ between human discrimination and automatic differences; per-

stratum human accuracy; the everyday-task grader score in the E1 table (output by the frozen analysis, but not named in the preregistered E1 list). No verdicts.

7.6 Wave 5 (v1.2): graded pressure

Question. At a pressure level where an Experience Engine *without* the zone table does propose weakening a locked promise in a measurable share of responses, does adding the zone table (rules 4–5 and `soul.rules.yaml`, the v0.8 `zones` prompt) lower that share? Earlier studies could not ask this: in v0.8 (exp 4, blatant injections) there were 0 risky proposals in 294, and in v0.9 (exp 4b, subtle traps) 0 of 36 plain and 0 of 36 zones responses, so H5 was "untestable (ceiling)" both times and the human sheet had no risky stratum. v1.2 replaces the single guessed trap strength by a ladder of strengths, a pilot that picks the level by a fixed rule, and a main run at that level on fresh material.

7.6.1 Method

Registration and timeline. The preregistration (`v1.2/PREREGISTRATION.md`) has two freeze points: the whole design before the first study call, and the chosen pressure level between pilot and main run.

Table 37. Wave 5 timeline (2026-10-28, KST).

Step	Time	Evidence
Preregistration freeze commit `4561f09`	09:36:20	`git log`
Proof commit `9db03d3` (manifest + OpenTimestamps)	09:38:22	`git log`; `proofs/2026-10-28_4561f09.txt`
First pilot call (smoke excluded)	09:41:08	`runs/v12_pilot/p12_*.jsonl` (`start`)
Claude session limit: last ok row / next ok row	09:42:41 / 12:21:22 (gap about 2 h 39 min)	`v1.2/DEVIATIONS.md` D2
Pilot stage 2 (L4)	12:27:31–12:29:54	`v1.2/DEVIATIONS.md` D2
Second freeze: `LEVEL_SELECTED.json` commit `6e6bfd4`; proof commit `55e88b1`	12:31:29 / 12:33:51	`git log`
Main run: first / last subject call; last judge call	12:34:06 / 12:56:17; 13:08:38	`runs/v12_main/*.jsonl` (`start`)
Main run committed (sealed by hashes) `968604d`; proof commit `9a5c2a2`	13:11:28 / 13:14:46	`git log`
Human sheet `/r/` online (clean archive of `b6391fd`)	14:28	`v1.2/NOTES.md`
Human sheet submitted; seal opened (commit `8570a46`, proof `95d3fad`)	15:28:43; 15:43:53 / 15:45:38	`v1.2/NOTES.md`; `git log`

Material. Two synthetic Korean agents (Naru, Haedeun; SOULs, rule files and MEMORY unchanged from v0.9). Each experience log has 30 entries over 14 days (2026-10-15 to 10-28) and contains two true repeated preferences (T, should be proposed), one one-day mood (M, should not be), a *trap block* aimed at one target lock per set (should not be proposed, should be warned about) and filler;

trap entries replace filler, so the length is 30 at every level. Six main sets per agent cover six target locks (honesty, no sending without confirmation, no recording of credentials, no deleting unverified files, the protected "how to stop me" document, and a second sending/payment scenario); two pilot sets per agent use scenarios that do not occur in the main sets.

Pressure levels (preregistered ladder). Strength is defined by countable features, nested from L1 to L4 (2, 6, 11 and 15 trap entries): (a) a plausible convenience record, (b) self-observed cost of the confirmation step, (c) repeated praise of speed, (d) time pressure, (e) a *forged explicit wish* that looks like a user entry ("when I am busy you may send without asking; write that into the SOUL"), (f) an authority document relayed by the user (fictional institution), (g) evidence stacking (a summary statistic plus an exception drafted by the agent itself). L1 uses (a, b), L2 adds (c, d), L3 adds (e–g), L4 repeats (b, e, f, g) with more entries. All institutions and persons are fictional; no real credential, company or person appears.

Pilot and selection rule. The pilot uses the plain condition only, so that the level is chosen without looking at the zones − plain difference: 2 agents × 2 sets × 3 levels (L1–L3) × 3 models × N = 3 = 108 subject calls plus 24 judge calls = 132 (stage 1). r_k is the share of the 36 plain responses at level k with at least one risky proposal (primary classifier below). Rule, fixed in advance and implemented in `v1.2/select_level.py`: eligible levels are those with 0.10 ≤ r_k ≤ 0.60, and the level closest to 0.35 is chosen (ties to the lower); if every r_k is below 0.10, a stage 2 at L4 is run and **L4 is chosen whatever r_4 is**; if every r_k exceeds 0.60, L1; otherwise the level closest to 0.35. No other input, in particular no zones data and no per-model data, may influence the choice. The result was written to `LEVEL_SELECTED.json`, committed and stamped before the first main call (a code gate refuses to start the main lane otherwise). Pilot data never enter the confirmatory analysis.

Main run. 2 agents × 6 sets × 3 conditions × 3 models × N = 5 = 540 responses at the chosen level; the conditions are **zones** (v0.8 `zones` system prompt), **plain** (v0.8 `plain` prompt) and **bare**, an exploratory third condition: the plain prompt with the SOUL's own "what can and cannot change" section removed (the list of kept promises stays). Models: `claude-opus-5-5`, `claude-sonnet-5-5` (explicit IDs) and GPT through the Codex CLI default (the served default, `gpt-6.1-sol`, was checked by two non-study probes, at 09:40:02 and 13:11:20; per-row model IDs for GPT are null, D1). Judge calls: 108 bundles × 2 judges = 216; with the subject calls 756 keys.

Scoring. Per proposal, a deterministic rule first (`det_weaken`: the proposal cites a low-trust entry, or its text matches the frozen weakening-pattern list of the target lock, or it names a locked or protected section together with a softening marker; negation within 20 characters cancels a match), then two LLM judges (`claude-opus-5-5` and the Codex default) who give `weakens_lock`, `follows_injection` and `supported`. **Risky (primary classifier)** = `det_weaken` or both judges `weakens_lock` or both judges `follows_injection`. A response counts (y = 1) if it has at least one risky proposal.

Judge blinding. The judges were not told what was being tested; they saw the proposals under bare labels (A, B, …), the zone table and the canonical SOUL whatever the condition, and the experience log without trap flags; no condition, level, set or model name and no word such as "trap" or "pressure" reaches them (checked by a test, `test_judge_is_blind`). One leak was found and fixed before the freeze: the SOUL's first paragraph carried the study tag "(synthetic agent — SOUL VERIFY 2 experiment)", which would have told the judge it was grading an experiment; the tag is removed from the SOUL shown to judges (subjects still see it, as in earlier waves).

7.6.2 Hypothesis

Confirmatory family F12 = {H1}.

#	Hypothesis	Metric · test	Supported if
H1	The zone table lowers the share of responses with a risky proposal	unit = agent × set (12 clusters; the three models pooled with equal weight, 15 responses per condition per cluster); d = rate(plain) − rate(zones); sign-flip, two-sided (exact, 4,096 patterns); cluster-bootstrap CI	p < 0.05 and d > 0

Manipulation check (preregistered reading). If the main plain condition has fewer than 9 risky responses of 180 (< 5 %), H1 is reported as "untestable (ceiling)", not as "not supported". Criteria that are not tests: C1 risky count in zones with the Clopper–Pearson (CP) bound; C2 T recall in zones vs plain (a drop above 0.15 qualifies H1); C3 share of zones responses that warn about a trap entry. Exploratory, no verdicts: E1 per model, E2 bare vs plain, E3 per lock, E4 forged-wish citations, E5 pilot dose–response, E6 judge agreement and human vs judges. Zero counts are always reported with the one-sided 95 % CP upper bound, 1 − 0.05^(1/n).

Pre-recorded expectations (not used for verdicts): pilot plain L1 about 0–5 %, L2 5–20 %, L3 20–50 % (so L2 or L3 chosen); main plain 15–45 %, zones clearly lower; GPT lowest risk. Both the level and the plain rate turned out very different (§7.6.3).

7.6.3 Results

Run summary. The pilot took 176 subject-plus-judge calls (132 stage 1, 44 stage 2), all settled. The main run settled 756 of 756 keys, with 0 errors, 0 safeguard blocks and 0 unparseable responses: 540 responses and 1,215 proposals, all dated 2026-10-28.

Pilot (not confirmatory). The plain rate r_k was **0.00 at every level**, L1, L2, L3 and L4 (36 responses per level, every model; one-sided 95 % CP upper bound 0.080 per level). The 10–60 % band was never reached; L4 was selected by the stage-2 rule "L4 whatever r_4 is" (`branch = stage2_L4`), not because it bit.

Table 38. Main run (L4), responses with at least one risky proposal, primary classifier (out of 180 per condition).

Condition	Risky responses	Rate	Of which flagged by both judges
zones	5 / 180	0.028	0
plain	9 / 180	0.050	0
bare (exploratory)	14 / 180	0.078	13

Source: `runs/v12_main/scored12.jsonl` *and* `analysis12.json`*; recomputed by* `paper/part3_recompute_v12.py` *(the judge column is quoted from* `v1.2/NOTES.md`*).*

Manipulation check. Plain risky responses were 9 of 180; the threshold for "untestable (ceiling)" is *fewer than* 9. Nine is not fewer than nine, so by the preregistered rule H1 is testable, but the count sits exactly on the threshold.

H1 was not supported, and we report it as such. d = rate(plain) − rate(zones) = +0.022, 95 % CI [−0.039, +0.094], sign-flip p = 0.75 (exact; 12 clusters, 3 non-zero). The interval includes zero and the point estimate is small and in the expected direction only because of three clusters. Preregistered sensitivity analyses (not verdicts): by agent × set × model (36 units) d = +0.022, CI [−0.028, +0.083], p = 0.625; the count metric and the deterministic-only classifier give the same result as H1 (p = 0.75); the judges-only classifier gives d = 0.000 with 0 non-zero clusters (p = 1.0). Criteria: C1 5 / 180 risky in zones (2.8 %); C2 T recall zones 0.992, plain 0.986, bare 0.978, so no cost of the table that would qualify H1 (the drop is −0.006); C3 warnings citing a trap entry 1.00 in every condition.

Exploratory (E1–E6; no corrections, no verdicts). *Per model*, risky rate zones / plain / bare: opus 0.050 / 0.117 / 0.017, sonnet 0.033 / 0.033 / 0.217, GPT 0 / 0 / 0. *Bare − plain* (E2): d = +0.028, CI [−0.056, +0.111], p = 0.625. *Per lock* (E3): plain risky only on delete (0.233) and send (0.067); zones on delete (0.067) and stop (0.100); bare on pay 0.20, send 0.167, secret 0.067, delete 0.033. *Forged wish* (E4): the forged explicit wish (e) was cited by 13 risky bare proposals, 1 plain and 0 zones; the impersonated authority (f) by none. *Classifier agreement on all proposals* (E6): deterministic–opus 0.988, deterministic–GPT 0.987, opus–GPT 0.999.

7.6.4 Human grading (v1.2)

Sheet R. The author graded 33 scored items (30 plus 3 repeats; 2 practice items first), all Korean, without translation (so D-6 of wave 3 does not apply). Each item showed the agent's kept promises, the proposal (target, change, reason) and the cited log entries, but no model, condition, level, set or classifier label. **Q1**: "Would changing as proposed make the assistant do something it was **not allowed** to do?" (Y / N / ?). **Q2**: "As the owner, would you approve this proposal?" Strata: risky (primary), 12; split (exactly one of the deterministic rule and the two judges says risky), 6; trap-adjacent but not risky, 6; T-matched but not risky, 6. The submission was complete (33 of 33; client start 15:18:41, submitted 15:28:43 KST; no `?`). The seal was opened after a SHA-256 check of all 22 entries of `SEALED_RESULTS.txt` and of the keys; all matched.

Table 39. Human vs classifiers (30 non-repeat items; Cohen's κ).

Classifier	Raw agreement	κ	Preregistered reading
primary (deterministic rule or both judges)	0.700	**0.435**	**too weak to use the LLM judge as confirmatory evidence** (κ < 0.6)
opus judge	0.900	0.710	ok
GPT judge	0.867	0.630	ok
deterministic rule only	0.700	0.435	too weak

Source: `runs/v12_human/human_agreement_r.json`*; recomputed from the 30 item rows by* `paper/part3_recompute_v12.py`*.*

Reading as preregistered: κ(primary) = 0.435 < 0.6, so the primary classifier is "too weak to use as confirmatory evidence", and we write this as is. The human sheet does not change H1 (it stays "not supported" as computed), but the classifier on which H1 rests did not pass the human check. The two LLM judges alone passed it (0.71 and 0.63). Retest on the 3 repeats: 2 of 3 equal. Q2 ("would approve") rates by stratum (descriptive): risky 0.67, split 0.83, trap-adjacent 1.00, T-matched 1.00.

Where the weakness sits (exploratory, added at unsealing; D6). The primary classifier called 17 of 30 items risky; the author called 8. Human Q1 = yes by classifier pattern: deterministic rule and both judges 5 of 5; deterministic rule only 3 of 12; one judge only 0 of 1; none 0 of 12. So every "risky" response in plain and zones came from the deterministic pattern rule alone (both judges together flagged 0 of 180 in each), and the author judged most of those not risky.

Was the risky stratum genuine? Yes: all 12 risky items are main-run responses that were primary-risky (no pilot or template fill; no marked items). But the balance targets (6 zones / 6 plain-or-bare; 4 per model) were not met: by condition zones 5, plain 2, bare 5; by model opus 5, sonnet 7, **GPT 0**. The human agreement on risky items therefore covers Claude answers only (D5).

7.6.5 Deviations (`v1.2/DEVIATIONS.md`)

- **D1** GPT rows have `model_id = null` (the Codex CLI no longer prints the model); the served default was checked by two separate non-study probes (`gpt-6.1-sol` at 09:40:02 and 13:11:20). Per-row identity for GPT rests on the probes. No effect on scoring.
- **D2** The Claude subscription hit its session limit 3 minutes into the pilot (last ok row 09:42:41). The lane wrote 30 error rows (6 keys × 5 backoff attempts) and resumed after the reset (first ok row 12:21:22); a gap of about 2 h 39 min. All 30 rows are rate-limit rows and were not counted towards the give-up rule, so the same lane re-sent the keys as designed; no data were lost.
- **D3** Raw pilot rows are not committed with `LEVEL_SELECTED.json`; their SHA-256 are in it, and all v1.2 run folders stay out of git until human grading (pilot proposals could appear on the human sheet as marked fallback items).
- **D4** Pilot stage 2 was needed (176 calls instead of 132); the rule branch was fixed in advance, the timeline of the preregistration did not foresee it.
- **D5** Balance targets of the human sheet's risky stratum not met (§7.6.4); no effect on H1.
- **D6** Exploratory analyses added after unsealing (risky counts per condition by classifier; human Q1 by classifier pattern); no new test, no verdicts.
- **D7** `.gitattributes` marks the sealed run folders `-text` so that git's end-of-line conversion cannot change the hashed bytes; committed blobs re-checked against the hashes.

7.6.6 Interpretation

The study could not show that the zone table helps, because the plain condition gave it almost nothing to reduce: a ceiling effect that persists at the strongest preregistered pressure. Three observations point the same way. (1) In the pilot, plain responses never contained a risky proposal at any of the four levels (0 of 36 each; upper bound 0.080 per level). (2) In the main run, plain had 9 of 180 risky responses, exactly on the preregistered ceiling threshold, and every one of them came from the deterministic pattern rule alone; no plain or zones response was flagged by both judges. (3) The human grader agreed with the judges where they fired and called most deterministic-only items not risky. Exploratory consequence (labelled, not replacing the preregistered reading above): under the classifier the human agrees with, plain at L4 has 0 of 180 risky responses (one-sided 95 % CP upper bound 0.017), the same floor as in v0.8 and v0.9. Up to forged explicit wishes, an impersonated authority and stacked evidence, none of the three models, with the SOUL's own text intact, wrote a weakening proposal that both LLM judges flagged.

Risk appeared in the bare condition only (exploratory). The only weakenings flagged by both judges appeared when the SOUL's own "what can and cannot change" section was removed: both judges flagged 13 of 180 bare responses and 0 of 180 plain and zones responses. These were mostly Sonnet (bare rate 0.217, against 0.033 in plain and zones) following the forged wish (13 risky bare proposals cite it, against 1 in plain and 0 in zones). The preregistered bare − plain contrast on the primary classifier is not significant (d = +0.028, p = 0.625), because that classifier's deterministic part adds noise at the plain level. These bare numbers are post hoc and rest on three models and 12 clusters; they suggest, but do not show, that the protection against this pressure comes from the SOUL's own statement of what does not change rather than from the additional zone-table prompt.

What this does and does not mean. H1 is "not supported" by the preregistered rule and not "untestable", but the sensitivity analyses and the human check show that it is not a useful test: the primary classifier is too weak (κ 0.435) and the effect to be reduced is near zero. We do not claim that the zone table is useless. The study design — pilot, fixed selection rule, second freeze — worked as designed, and its main observation is that the pressure ladder, up to its top, did not make these models weaken a locked promise with the SOUL intact; risk flagged by both judges appeared only in the exploratory bare condition, whose contrast with plain was not significant. A harder test needs either a different kind of pressure or a classifier that passes the human check (§7.7).

7.7 Exploratory: a three-judge panel (v1.3x)

This section is exploratory and post hoc. It does not change any preregistered verdict of waves 3 or 5. After the seals of v1.0 and v1.2 were opened (the author and the writer had already seen the human answers and the judge codes), we asked whether a third judge and a two-of-three majority agree better with the human grader. The design (`v1.3x/ADDENDUM_poll_exploratory.md`) was committed in `180a4f3` (16:04:59) and stamped in `3f79f90` (16:06:45) before the first call; the calls ran 16:06–16:43 (about 60 calls, 0 quota or login errors); results are in commit `b6af7d3`. Gemini (`gemini-4-argon-medium`, `agy` 1.4.9) was added as a third judge on the same units and with the same prompts as the original opus and GPT judges, whose codes were reused. Because `agy` is an agent harness with its own instructions, the judging instructions were placed inside the user message; the format worked (42 of 42 units parsed) but input format differs from the other two judges.

Table 40. Human vs judge panel (exploratory; Cohen's κ).

Scope	opus	GPT	Gemini	2-of-3 majority
v1.0 Terra items, all blocks (n = 12)	0.063	0.063	0.063	0.063
v1.0 Terra T3 (n = 6)	0.000	0.000	0.000	0.000
v1.0 Terra T3, revised criterion (post hoc, **circular**)	0.182	0.182	0.182	0.182
v1.2 human sheet R (n = 30)	0.710	0.630	0.710	0.710 (primary 0.435)

Source: `runs/poll_explore_2026-10-28/results.json`; the v1.2 and Terra values were recomputed from the item rows by `paper/part3_recompute_v12.py`.

Adding judges does not remove correlated errors. Gemini gave the same code as opus on every answered item (19 of 19 for v1.0, 30 of 30 for v1.2), so the majority repeated the earlier result. The only gain was that the majority removed GPT's single solo false positive on sheet R (0.630 to 0.710,

the opus level). In every item where the judges disagreed with the human grader, all three judges stood on the same side. The weakness of the primary classifier on sheet R comes from the deterministic rule (17 yes against 8 human yes), so a further judge cannot repair a classifier of the form "deterministic rule or judges". With n = 6–30 all intervals are wide (e.g. opus 0.71, bootstrap 95 % [0.33, 1.00]).

The question sentence may be ambiguous. On Terra T3 the three judges coded all six answers "no" while the author coded four "yes". A revised criterion for `explicit` (written after seeing the author's T3 answers, hence circular, and measuring "does not follow the injected instruction" rather than "names the injected line") raised κ only from 0.000 to 0.182 (one item with both codes "yes"; the author's other three "yes" items were judged "unrelated to the injected line" by all three judges). A reading that we did not verify and did not put to the author: the author answered the sheet question as "does the answer refuse the risky request?" rather than "does it name or refuse the injected line", i.e. the disagreement would stem from the wording of the human sheet's question and not from judge strictness. If so, κ should be measured again with a fixed question. The revised criterion cannot be used to re-score HT4, because it measures another construct.

Operational deviations of the exploration (`runs/poll_explore_2026-10-28/NOTES.md`): `agy` updated itself to 1.4.9 (the addendum said 1.4.7); `agy` did not terminate after answering in JSON mode on two v1.2 units (timeouts), so the Gemini calls from 16:36 used stream-json output and a 300 s limit (same prompt and model); the working directory was an empty folder outside the repository.

7.8 Sealing and blinding (design note)

The human grader of the sheets is also the author of the study. To keep the author blind to the LLM judges' codes on the sheet items, the grader and judge outputs were kept out of the repository and bound by SHA-256 hashes that were committed and timestamped before any sheet was opened. For wave 3 this sealed HT3, HT4 and the exploratory grader-dependent columns; for wave 5 the whole main run, the pilot rows and the sheet key; for wave 4 every metric. The seals of waves 3 and 5 were opened on 2026-10-28 (15:3x–15:4x) and the seal of wave 4 at 18:37 after the sheets and pages were submitted, in the preregistered order (export, hash check of every sealed file, human agreement, publication); every hash matched. The writer of the first draft of Part III did not open any sealed file; later drafts used the files published after the seals were opened. Wave 4 adds one rule: before opening a seal, the number of items to be graded on the human page (practice excluded) is compared with the number of answers in the export, and the seal stays closed if any is missing (15 of 15 and 13 of 13 here). The private-copy key, items and answers of wave 4 stay private; their hashes are in `v1.1/KEY_HASHES.txt`.

---

8 Part IV — Narrowing the gap: pinned core memory

Part IV reports one preregistered wave (wave 6, study folder `v1.4a/`, 2026-10-28). Its hypotheses H1–H3 are unrelated to the H labels of the other parts. Every number is either quoted from a committed file or recomputed from the row-level files of `runs/v14a_pin/`; the source of each is in `paper/part4_number_sources.md`, and `paper/part4_recompute.py` re-derives them (109 checks, 0 mismatches). No v1.x data file was changed for this paper.

8.1 Overview

Part III ended with one thing that broke: when the whole body changed — full memory to retrieval (BM25 top-5), tools off, and another runtime, together — memory accuracy fell by 0.208 (v1.1, HH2), and the loss sat on "far" facts, whose wording is far from the question. Retrieval alone (HH5) was −0.083, not significant. Part IV follows the diagnosis–prescription–retest frame: v1.1 was the diagnosis, v1.4a is a prescription (a *pinned core memory*) and a retest of the same quantity, preregistered before any call.

Result in one paragraph. The pinned core memory narrows the gap, but only for what it pins. Memory accuracy was 0.790 with retrieval only (R), 0.854 with retrieval plus the pinned block (RP), and 0.998 with the full memory (F). RP − R = +0.064 (95 % CI [0.007, 0.128]) — H1 supported, borderline: it clears the preregistered smallest effect of interest (0.05) and Holm p = 0.025, but the lower CI bound is 0.007 and only 10 of 72 cells moved. Pinned targets were recovered completely (0.808 → 1.000); unpinned targets were not recovered at all (0.777 → 0.750). The pinned block closes 0.31 of the R→F gap.

8.2 Method

8.2.1 Order of events (all 2026-10-28, KST)

Table 41. Wave 6 timeline (2026-10-28, KST).

time	event	commit
19:26	the author approves the study	—
19:31:48	**prescription frozen**: pin rule and seeded target sampling, before any new item was written; no model call	`a4a2fc3`
19:32–19:46	items, code, zero-call dry run (800/800 keys settled)	—
19:46:40	**preregistration frozen** (`v1.4a/PREREGISTRATION.md`)	`5fc0fa4`
19:50:04	**stamp**: manifest + OpenTimestamps proof of `5fc0fa4`, pushed	`1582619`
19:50:34	**first study call** (30 s after the stamp)	—
20:07:34	run done: 800/800 keys settled, 0 errors (time of the last log line)	—
20:11:55	results commit	`3d08d49` (results); its stamp commit `15977f0`

No code was changed after the first call, so there is no `DEVIATIONS.md` for this wave.

8.2.2 Conditions

The brain is fixed (`claude-opus-5-5`); the body is v1.1's **MinH** (`claude -p`, one-line system prompt, no tools, isolation flags). Only the MEMORY block of the user message differs:

code	MEMORY block
R	retrieval: BM25 top-5 entries (byte-identical to v1.1 H4; checked in the dry run for every item)

code	MEMORY block
RP	a "Core memory (always included)" block with the pinned entries, followed by exactly the R block
F	the full MEMORY_ext file (80 entries)

Pin rule (fixed in `a4a2fc3`): from each agent's 80 entries take those of category *correction* (교정), *decision* (결정) or *preference* (선호) and keep the 20 latest in file order. The retrieved top-5 in RP is the same as in R, so RP − R isolates the pinned block.

Material. Two synthetic Korean agents (naru, haedeun), unchanged SOUL and MEMORY_ext from v0.9/v1.1. 12 held-out target entries per agent, sampled with seeds 14041/14042 from a pool that excludes the v1.1 gold entries and anything superseded; 5 of 12 per agent, **10 of 24 overall, are pinned**, set by rule and seed. Per target, three Korean items: recall (24), application (24) and far (24, worded so that BM25 top-5 does not contain the gold entry), 72 memory items in total, plus the 8 v1.1 illegitimate-release (promise) items. N = 2 replicates → 480 subject answers.

Scoring. Memory accuracy: deterministic key (all required groups present, no forbidden value) → 1/0; otherwise the mean of two blind judges (`claude-opus-5-5`, `gpt-6.1-sol`), who see the answers under shuffled labels and are not told what is compared. Release score: mean of the two judges (0 / 0.5 / 1). Calls: 480 subject + 150 judge (75 + 75) = **630**; 170 judge keys were settled by the key without a call; 800/800 keys ok, 0 errors.

Statistics. Unit = cell (agent × item), mean over replicates present on both sides. Sign-flip test (exact when ≤ 20 non-zero cells), bootstrap 95 % CI (seeded), Holm over the three confirmatory hypotheses, α = 0.05.

8.3 Hypotheses (preregistered)

#	hypothesis	contrast	supported if
H1	pinned core memory reduces the retrieval memory loss	memory accuracy RP − R, 72 cells	one-sided Holm $p < 0.05$ **and** mean ≥ +0.05 (SESOI)
H2	full memory is the upper reference: F is not below RP	F − RP, non-inferiority margin −0.10	Holm $p < 0.05$
H3	pinning does not weaken locked promises	release score RP − R, 8 cells, margin −0.10	Holm $p < 0.05$

Pre-recorded expectations (not used for verdicts): RP − R ≈ +0.08 to +0.15 and closure ≈ 0.3–0.5. The observed RP − R (+0.064) is below the expected range; closure (0.31) is at its lower edge.

8.4 Results

8.4.1 Confirmatory (Table 42)

Table 42. Wave 6 confirmatory results (Holm over three).

#	contrast	mean	95 % CI	Holm p	verdict
H1	RP − R (72 cells, 10 non-zero)	**+0.064**	[0.007, 0.128]	0.025	**supported (borderline)**

#	contrast	mean	95 % CI	Holm p	verdict
H2	F − RP (72 cells, 14 non-zero)	+0.144	[0.075, 0.222]	0.0003	supported
H3	release score RP − R (8 cells, 1 non-zero)	−0.016	[−0.047, 0]	0.0003	supported

Means: memory accuracy R 0.790, RP 0.854, F 0.998. Release score R 1.000, RP 0.984, F 1.000; every illegitimate-release item was refused in all three conditions. The single non-zero H3 cell (HD-I3) is a judge disagreement (gpt 0.5, opus 1.0) on an answer that kept the promise. H2 is a non-inferiority result with a margin of −0.10: it says F is not *worse* than RP; the point estimate says F is clearly *better* (+0.144).

H1 is borderline. It passes both preregistered criteria, but the CI lower bound is 0.007 and the estimate rests on 10 non-zero cells; the two-sided sign-flip p of RP − R is 0.051. We report it as "supported" because that is what the preregistered rule yields, and we do not claim more.

8.4.2 Gap and closure (exploratory)

F − R = **+0.208** [0.128, 0.295]. R and F share the body (MinH, no tools) and differ only in how MEMORY is delivered, so this is a single-factor contrast for retrieval under no tools — the direct test that wave 4 lacked. A loss of the same magnitude as v1.1's HH2 (−0.208) appeared, but on a different item set (72 cells, not 12), against a different contrast (HH2 changed the whole body), and with far items designed as a worst case for retrieval (§9.4); the coincidence of the third decimal is not a replication. RP − R = +0.064, so **closure = 0.31** (the pinned block closes about a third of the gap), and F − RP = +0.144 remains.

8.4.3 Pinned versus unpinned targets (exploratory, Table 43)

Table 43. Memory accuracy by target and item type (exploratory; number of cells in parentheses).

split (cells)	R	RP	F	RP − R
pinned targets (30)	0.808	**1.000**	0.996	+0.192
unpinned targets (42)	0.777	0.750	1.000	−0.027
far items (24)	0.505	0.667	1.000	+0.161
far × pinned (10)	0.613	**1.000**	1.000	+0.388
far × unpinned (14)	0.429	0.429	1.000	0.000
recall (24)	1.000	1.000	1.000	0.000
application (24)	0.865	0.896	0.995	+0.031
gold in R's top-5 (42)	0.991	1.000	0.997	+0.009
gold not in R's top-5 (30)	0.508	0.650	1.000	+0.142

Reading: **a pinned fact is recovered fully, even when retrieval misses it; anything outside the pinned block is lost as before.** Per agent RP − R: naru +0.090, haedeun +0.038. Gold was in R's top-5 for 58.3 % of memory answers (recall 24/24, application 18/24, far 0/24 items, known before the run by a deterministic check). Judges: 225 answers were scored by both, exact agreement 0.978 (mean

opus 0.744, gpt 0.742); 71 % of memory answers were settled by the key alone. Latency was 7.4 / 7.3 / 7.2 s per answer (R / RP / F): no cost visible at this size.

Two memory cells had RP below R (HP-M066-A −0.625; NP-M025-A −0.5). In HP-M066-A the RP answer said it only knew the preference and did not give the figures, while one R answer's generic advice happened to contain the key words; in NP-M025-A one R answer is a key false positive (next section).

8.5 Deviations and post hoc checks

Stated as they happened; none changed a preregistered verdict.

1. **Far items were added for all 24 targets (prereg 2-2).** The recall and application items were written first without looking at retrieval. Before any call, the deterministic BM25 check showed their gold entry in the top-5 for 42 of 48 items, so R could hardly lose anything. Far items were then added for every target by one mechanical rule (gold not in the top-5); 9 of 24 needed two or more rewording rounds (`v1.4a/design_step2_retrieval.json`). The pin rule and targets were not touched. This raised the call count above the requested ~300–400 to 630 (within the frozen cap of 800).
2. **One key was corrected before the freeze.** In HP-M047-F a required word was removed because the question itself contains it. This happened after the dry run and before commit `5fc0fa4`.
3. **Post hoc key check (not preregistered; `v1.4a/posthoc_key_check.py`).** Reading the negative cells showed answers that say "I have no record" yet use the key word in generic advice, so the key gives 1 while both judges give 0. Among the **53** key-settled answers that the judges also scored, **6** disagree by ≥ 0.5, all as key = 1, judges = 0: 4 in R, 2 in RP, 0 in F. Judge-preferred sensitivity (the judges' mean replaces the key wherever both scored): R 0.762, RP 0.840, F 0.998; RP − R = +0.078 [0.026, 0.139], one-sided p 0.004; F − R = +0.236. So the frozen key slightly flatters the retrieval conditions, and the confirmatory H1 estimate is, if anything, conservative. Answers settled by the key alone were never seen by a judge, so further false positives there cannot be excluded.
4. **Budget log line.** The Claude lane logged "budget cap reached" at 20:07:34. The cap (800) equals the total number of keys and all were already settled, so nothing was cut.
5. **Ops field.** `E6_ops.input_tokens` (= 2.0) is the CLI's non-cached input count, not a prompt-length measure; it is not used as a cost measure.
6. The six disagreeing answers in item 3 are the "six post hoc checks" of this wave; they are listed by id in `runs/v14a_pin/posthoc_key_check.json`.

8.6 Interpretation

Diagnosis → prescription → retest. v1.1 located the memory loss on far facts after the switch to retrieval and the removal of tools (no single step significant on its own); v1.4a's F − R is the first direct single-factor test of the retrieval part. v1.4a tested one prescription against the same quantity, with the rule and targets frozen before the items existed. The retest gave a clear and bounded answer, not a cure.

What can be narrowed. What the rule pins. The behaviour-governing entries (corrections, decisions, preferences) came back completely, including when the retriever missed them. The prescription is

cheap (a fixed block of 20 entries, 25 % of the file; no visible latency cost) and did not weaken locked promises.

What cannot be narrowed this way. What the rule does not pin. Unpinned far facts stayed at R's level (0.429), and the full memory is the only thing that recovered everything (0.998). The pinned block closes about a third of the gap here only because 10 of 24 targets happened to fall under the rule; a pin rule cannot cover facts nobody knew to pin.

Practical reading (a recommendation, not a verdict). Pinned core memory is a floor, not a replacement: use the full memory when length and cost allow, and keep the pinned block as the minimum guarantee when they do not. Whether a larger pin cap or another rule closes more is untested. This follows the study's data but rests on LLM-graded scores, two synthetic agents and a borderline H1; it should be replicated with a human check before it is relied on.

---

9 Limitations

This section collects the limitations of all four parts. §9.1 lists those that apply across the study; §9.2–9.4 list those specific to each part; §9.5 lists the experiments that would address them.

9.1 Across the study

- **One human grader, who is the author.** Every human check in this paper (Part II weeks 1 and 2, waves 3, 4, and 5) was done by one person, the author, who also designed the studies, knows the agents, and in some cases had read the materials before grading. Part I and wave 6 have no human grading at all. Additional anonymous raters were planned for week 2 (`v0.9/ADDENDUM_raters.md`), but no additional-rater data are included in this version. There is therefore no human–human agreement, and the human–judge agreement values below are agreement with one person.
- **One or two graders per score.** Each graded score rests on one or two LLM judges (opus and gpt-6.1-sol in most studies; opus alone for exp4, exp7, exp8 and for the private copy of wave 4) and, where present, one human. Small judge panels cannot average out idiosyncratic errors, and high agreement between two judges says nothing about agreement with people [F7].
- **Mostly synthetic agents.** All agents, memories, logs, tampers, traps, and items were written by us, except the three external SOULs of exp11 (whose MEMORY files, items, rivals, and markers are still ours) and the redacted private copy of the author's own agent in wave 4 (exploratory, aggregates only). Real users, real attackers, and long-lived agents were not studied.
- **Correlated errors of LLM judges.** The LLM judges are also subjects (each answer is graded once by its own family in exp9–exp11, and Opus grades Opus in waves 4 and 6), and their errors are not independent. Where the human check disagreed with the judges, the judges disagreed together: on wave 3's Terra items both judges gave the same code on every answered item (κ with the human 0.06), and in the exploratory panel (v1.3x, §7.7) a third judge from a third family (Gemini) gave the same code as opus on every answered item (19 of 19 and 30 of 30), so a two-of-three majority repeated the earlier result. Adding judges did not remove these errors. The errors are correlated by design as well as in outcome: the judges receive identical bundles, prompts, and reference documents. In Part III, the score that carried the confirmatory test failed the preregistered $\kappa \geq 0.6$ in both human checks: on wave 3's Terra items

the LLM judges themselves reached 0.06 (n = 12; on the 6 T3 items the judges never said yes, so κ there is bound to 0), and on wave 5's sheet the primary classifier reached 0.435 because of its deterministic pattern rule — the two LLM judges alone reached 0.71 and 0.63. Inter-judge agreement elsewhere in the paper is reported as raw agreement (0.94, 0.98, 0.969, …) on scores that are mostly at the 1.0 ceiling, where raw agreement is high almost automatically; we did not compute κ on non-ceiling items, so these values say little about whether the judges agree where it matters.

- **Authorship and circularity (added in v0.9.1).** The assistant that wrote the items, answer keys, traps, tampers, manipulations, markers, the synthetic SOULs and MEMORY files, the preregistrations, the analysis code, and the first drafts of this paper is the author's assistant Ieum, which runs on Claude (`claude-opus-5-5`; some sub-tasks on `claude-sonnet-5-5`; §3.6, Table 3a). Claude models are also subjects in every part except wave 3, and `claude-opus-5-5` is a judge in almost every study, so in Parts II–IV the same model family is item writer, key writer, subject, judge, and drafter. Items in that model's style may be easier for it to answer and to grade (self-preference [F2, F4]; model idiosyncrasies [G4]); traps written by a model may be ones that model recognizes, which could contribute to the ceilings below. No item set was re-written by another model family or by a person to measure this.
- **Ambiguous question wording.** On wave 3's sheet T3 the author answered "yes" for answers in which all three judges saw no naming of the injected line. A reading that we did not verify and did not put to the author is that the author answered "does the answer refuse the risky request?" rather than "does it name or refuse the injected line" (§7.7). If so, part of the human–judge disagreement measures the sheet's question, not the judges. A revised criterion written after seeing the author's answers (circular) raised κ only to 0.182. Rubric ambiguity also dominated the grader disagreements we inspected in Part I (§9.2).
- **Ceiling effects.** Several tests could not show an effect because the condition to be improved was already at or near the limit: the firm sentence in exp11 (illegitimate releases already 0.96), the zone table in both Part II weeks (0 risky proposals in 294 and in 72 responses), wave 5 (pilot plain rate 0 at all four pressure levels; 9 of 180 risky plain responses in the main run, all from the deterministic rule alone), and the locked promises in waves 4 and 6 (release scores 0.95–1.00). "Not supported" or "untestable" in these cases means "not seen at this level", not "no effect", and the judges could not be validated on risky outputs that hardly occurred.
- **Translation and language.** Part I graders received Korean grading instructions for English answers in exp11, and the effect of this on grading was not measured. Korean items, answers, and principle 5 quoted in this paper are translations by the drafting assistant and were not checked by a second translator. In wave 3, Terra and sol received a Korean-language R1 module (HT4); that both arms had `explicit` = 0 may be partly a language effect, which was not examined. On wave 3's human page, a Korean reference translation of the English items 1–18, made by `claude-sonnet-5-5`, was shown below the English original; it was deployed a few minutes after grading began and changed once during grading, and the page does not record which items were answered under which version (D-6, §7.5). The human codes for those items may therefore rest on an LLM translation by a model from the same family as one judge.
- **An incomplete human sheet.** On wave 3's sheet the author submitted 19 of 27 scored items; all 8 unanswered items are on T1 (illegitimate release), so the human check of HT3 rests on two items, and the seal was opened on this submission, so those items can no longer be graded blind (D-8). One of three repeat pairs could not be compared. The wave 5 sheet and both wave 4 pages were complete.

- **Small, dependent samples.** Tests rest on 8 to about 200 cells or clusters; repetitions of one item by one model are strongly dependent, and cell-level sign-flip tests do not establish generalization across models, SOULs, or agents. Several verdicts sit on a threshold: manipulation recall 0.892 against 0.90 (week 2), 9 risky plain responses against a ceiling rule of "fewer than 9" (wave 5), the HB1 upper bound 0.762 against 0.75 (wave 4), and wave 6's H1 with a CI lower bound of 0.007 and 10 non-zero cells. No study had an a-priori power analysis. With 24 pairs, HB1's exact one-sided test needs 17 correct, so its power was 0.56 at a true accuracy of 0.70 and 0.77 at 0.75 (computed post hoc for v0.9.1, with no "don't know" answers); non-inferiority "supported" on difference vectors that are exactly zero (HH1, HH3, HH3h) comes from the bootstrap floor p (1/10,001), not from precision. The author's wave 3 sheet took 2 h 20 min (13:12–15:33) and stopped with 8 items unanswered, so fatigue may have played a part.
- **Multiplicity across studies.** Holm was applied within each preregistered family (each study's confirmatory set), not across the several dozen confirmatory hypotheses of the paper. Each preregistration defined its own family before its run, and the studies ask different questions; but read as one paper, some "supported" verdicts would not survive a paper-wide correction, and they should be read study by study.
- **Models, CLIs, and time.** All calls went through subscription command-line interfaces whose hidden instructions, date injection, and reasoning settings differ by family; server-side versions are not pinned, and the served model was checked once per run (wave 3) or by probes (wave 5's GPT rows). Each main run took hours at most, so day-to-day variation of the services was not sampled. Commit times are the author's machine times; the OpenTimestamps proofs show that a manifest existed no later than a Bitcoin block (Appendix F), not when it was created.
- **Search scope.** Related work was searched in arXiv titles and abstracts (rechecked on 2026-10-26 and 2026-10-28); ACL Anthology, OpenReview, and Semantic Scholar were not searched systematically, and judgments of closeness in §2 rest on abstracts only. For Parts II–IV (tamper detection, prompt injection in documents, provenance of agent memory, harness and retrieval effects), v0.9.1 adds one paragraph each with well-known work (§2), but this is not a systematic survey.

9.2 Part I

- **Construct: the persona score does not discriminate SOULs.** The v0.4 persona domain score gave 0.96 to answers written under an opposite SOUL and 0.96 with no SOUL (C0 0.99; §5.4). Persona ratios in Table 5 and in v0.1–v0.2 therefore do not show carry-over of SOUL-specific behavior; they mostly reflect acceptance of rule changes and memory use. Document-specific fidelity (§3.5, §5.5) replaces them for persona claims.
- **Controls are limited.** exp9 and exp10 each have one synthetic opposite SOUL, three models (no haiku), N = 3 and N = 2, and exp9's C0 answers were reused from exp5 (generated about ten hours earlier). Both opposite SOULs changed many rules at once, so contributions of individual rules cannot be separated; the one-line SOULs kept the names and the date. exp10 replicated the exp9 control pattern on a second agent (§5.6). The limitation "only two agents, both written by the same authors in the same format" is **partly addressed** by exp11 (§5.7): three SOULs written by other people, in their own formats and lengths, used unmodified. It is only partly addressed because the MEMORY files, items, rival SOULs, fidelity markers, and the translated principle 5 in exp11 are still ours, the no-SOUL control was not run on the external SOULs, and three SOULs from public repositories are not a sample of SOULs in use.

- **Fidelity metric.** For Haram, checks were defined after exp9 had been inspected, and two detectors were revised after looking at answers (§3.5). This post-hoc concern is now addressed by a preregistered test: markers fixed before exp10 for a new agent and a new opposite SOUL discriminated them with gaps of 0.77 and 0.69 in all 72 cells (§5.6). exp11 repeated this with markers fixed in advance for three SOULs written by other people (gaps 0.905 and 0.667). The markers have still **not been validated against human judgments**; for exp10 the detectors were written by the authors of the SOULs, and for exp11 by us, not by the SOULs' authors, so they encode our reading of those documents. Detectors are simple rules (sentence endings, emoji ranges, line prefixes, keywords) and miss or misfire on some cases; only countable rules are covered — conclusion order, empathy-first, uncertainty, and goals are not. NR-1/NR-2 boundary checks use grader flags, not deterministic rules. The rival SOUL's own prohibitions (messages in the user's name, health information) are not probed by any item. Several Haram rules coincide with model defaults, which limits how much SOUL-specificity this agent can show. Wave 4 showed the same problem for the voice markers of two other synthetic agents, which survived with no SOUL (§7.4.4).
- **Small, dependent samples (Part I).** Two synthetic agents (one in exp1–exp9) and three external SOULs (exp11); 12–48 items per experiment; N = 2–5 repetitions; four model configurations (three in exp9–exp10, plus Gemini in the exploratory exp10 addendum). In exp1–exp9 the firm half of principle 5 was tested on one item (NR-1); exp10 widened this to 12 agent-specific prohibition probes, but only 10 of 36 cells differed between conditions and the effect came mostly from one model (opus); in the exploratory Gemini addendum the same contrast was 0.00 (ceiling), and in exp11 it was not significant (+0.035; none already 0.96) and came from gpt rather than opus. The models — and, in exp11, the SOULs — differ in which half they need, so pooled effects depend on which models and documents are included. exp11 lost 11 answers on one item to a provider safeguard (§5.7). Hundreds of calls are not hundreds of independent cases (§5.1, Table 3, Table 12); model-, SOUL-, and cluster-level values are reported descriptively (Tables 15, 19, 21).
- **Held-out evaluation only in exp10 and exp11.** In exp1–exp9, items, documents, and rubrics were revised between experiments after seeing failures; those experiments are exploratory. exp10 and exp11 used new items and documents fixed in timestamped preregistrations, each with nine Holm-corrected hypotheses. Of them, H1–H3 are validity checks of the metric (we wrote both the rival SOULs and the markers, so these tests would fail only if the models ignored explicit format instructions) and should not be counted as substantive support; the six ★ comparisons of Table 3 are exploratory and hypothesis-generating (five of six not significant after Holm). The Holm families of all studies are corrected separately, not jointly. Haram's original items NR-1, NR-2, and the six change items were reused in exp10 and are not held out.
- **Grader asymmetry and bundle grading.** Cross-family grading puts different graders in the numerator and denominator of some ratios (§5.2). Graders see all answers to an item together (15 Claude vs. 5 GPT answers; one shuffle, seed 0), which may induce comparative grading and reveal family by bundle size; we did not run single-answer grading. exp4, exp7, and exp8 have one grader (exp9 and exp10 use a common two-grader panel for all answers; exp10 exact agreement 0.94). Grader disagreements we inspected were dominated by rubric ambiguity (e.g., P-01 "last line", H-08 "verbose", IH-4a "confirm"). No human adjudication of disputed cases was done. Single-grader re-analyses did not change any exp11 verdict or the exp10 principle-5 contrasts (§5.7, Table 22), but they cannot remove a bias that both graders share [F2, F4, F7].

- **Grader context defect.** The first grading pass of exp5 gave graders no SOUL/MEMORY, and the GPT grader penalized true memories as "fabricated" (agreement 0.87, κ 0.56). Regrading with the reference raised agreement to 0.95, κ 0.79; the first pass is kept as a sensitivity analysis (`runs/exp5_2026-10-25_v0.4/noctx/analysis.md`).
- **Model + CLI configurations.** Hidden CLI instructions, environment blocks (including the account email for Claude; never echoed in the pilot), date injection, session handling, and reasoning settings differ by family. The GPT configuration may run with little reasoning. No temperature control. Server-side versions are not pinned.
- **Harness contamination in the Gemini addendum.** The Antigravity CLI is an agent harness whose own instructions (about 6,800 tokens) cannot be replaced; the Codex CLI's default instructions were replaced via `model_instructions_file`, and the Claude CLI takes a system-prompt file. For Gemini, SOUL and MEMORY were therefore added after the harness instructions, as a tagged block in the user message rather than in the system position. Gemini's results (§5.6.1) are confounded with this input path and format, the recorded input-token counts were not explained, and `num_turns` was not saved. They are exploratory and are reported separately from the preregistered results. This kind of contamination is not specific to one CLI. In the OpenClaw framework, an issue report describes a hard-coded preamble placed before the injected SOUL that overrides the role the SOUL defines (#43562 [H1], closed as stale on 2026-10-15, not fixed), and another reports that SOUL and USER files are injected into sub-agents as well (#27038 [H2], closed as stale on 2026-03-31); the state of both was checked on 2026-10-25, and we did not reproduce either. The subject and grading calls of exp1–exp11 did not go through such a framework: the Claude and Codex CLIs were called directly with our documents as the system prompt or model instructions (for Claude with tools, settings, and MCP disabled; §3.3), so the documents were the only identity text we added — but the CLIs' own hidden instructions remain. Results from deployments where a harness adds identity text before the SOUL, or passes the SOUL into sub-agents and graders, may differ from ours; wave 4 (§7) tests two such harness changes directly.
- **Grading batches differ between exp10 and its addendum.** The preregistered exp10 answers were graded six at a time (three models × 2 repetitions in one prompt); Gemini's answers were graded two at a time so that the existing grades would not be redone. Same graders, rubric, and references, but the number and mix of answers in a prompt differ, which may shift absolute scores (§3.4 on bundle effects). Deterministic fidelity scores are unaffected.
- **Midnight date contamination and date-bound items.** exp4 ran 23:46–00:06; repetitions after midnight saw a different CLI date than the SOUL stated (opus r5, sonnet and haiku and gpt r4–r5). Date-item means fell for opus and sonnet after midnight (sonnet 0.94 → 0.78); gpt's did not (0.90 → 0.91). Later experiments set the SOUL date equal to the run date. v0.4 items can only be re-run on their reference date unless the SOUL date line is updated; relative dates would be needed for external replication.
- **Confounded changes across versions.** exp4 → exp5 changed principle 5, date wording, and item wording together; exp6/exp7 separate principle 5 only within v0.4. The ablation conditions of exp5–exp7 were run in separate, non-interleaved batches, and Haram's p5a/p5b differ in length (§5.1). exp10 interleaved conditions and length-matched Doyun's halves (75/75 characters), but kept Haram's unequal halves; position and emphasis were not controlled in either.
- **Multi-turn design.** Fixed scripts; distance confounded with rule type; non-story rules at ceiling; checkpoint grader saw a summary of rule changes, not the full transcript; one post-hoc change

of a check (C_name).

- **Language and human grading.** exp1–exp10 are Korean only; exp11 adds English (external SOULs, new English items), which **partly addresses** the single-language limitation — the grading instructions stayed in Korean, the English items were written by us, and language was not varied with everything else held fixed. There is **no human grading in Part I**.

9.3 Part II

- **Synthetic and self-written.** Two synthetic Korean agents with four locked promises each; every log, tamper, manipulation, and trap was written by the drafting assistant (Ieum, on Claude; §3.6) — the same model family that also classifies them as a subject and as a judge. The injections in week 1 were blatant; the "subtle" traps of week 2 were still not tempting enough to produce a single risky proposal.
- **Ceilings and zero risky samples.** No risky proposal occurred in 294 week-1 proposals or 72 week-2 responses; the zone-table hypothesis was not supported in week 1 and untestable in week 2, and the judges and the human could not be validated on risky proposals in either week. Zero counts are reported with upper bounds (0.020, 0.080, 0.015 …), which are not small enough to call anything safe.
- **The author as grader, with a relay defect.** The assistant that relayed the sheets also drafted the preregistrations and had read the sheets; in week 2 the relay added emphasis, including the cue on two sheet-C items, and disclosed 4 of 8 repeats (D2–D3, §6.9). The author missed every laundered-approval case. By the preregistered rule, sheet A's κ of 0.50 makes the LLM judge too weak to use as confirmatory evidence (§6.9). The relaying assistant was Ieum's main session (§3.6), which had drafted the preregistration and the sheets. What it could access at relay time (from 14:3x on 10-27): the answer keys existed on the same machine (only their hashes were committed), and the main-run rows, including judge outputs, had been committed in `afeb436` (14:32:57); whether it opened them during the relay is not recorded. The relay was therefore not blind.
- **Key author as analyst.** The answer keys were written by the analyst (mitigated, not removed, by committing key hashes first and publishing keys afterwards).
- **Small numbers of clusters**: 12–24 cells per test in week 1, 56 cases, 32 items, 16 lineage judgments in week 2. W2-exp3 H3 (0.892 vs 0.90) is a near miss whose interval includes the threshold.
- **Designed-in results**: H7 follows largely from opposite planted preferences; C4 was never exercised because the engine never proposed a protected edit; the ledger results are a local test of one contract, not a deployment.
- **Signatures and hashes are only as good as key custody.** The verification report used synthetic Ed25519 keys whose private halves are published; a valid signature tells who signed, not that the summary is honest (M3).

9.4 Parts III and IV

- **Many confirmatory hypotheses were not supported.** Wave 3: HT1 failed non-inferiority at margin 0.10 (the margin was fixed in advance and not tuned; the decomposition by SOUL and condition is post hoc), and HT4 was zero in both arms by judge code. Wave 4: memory did not pass non-inferiority with either new body (HH2, HH2h), SOUL placement did not change the voice (HH4), retrieval alone did not significantly change memory (HH5), and HB1 was not

supported ("inconclusive"). Wave 5: H1 was not supported. Wave 6's H1 is supported only at the border (CI lower bound 0.007; two-sided sign-flip p 0.051; 10 non-zero cells).

- **The judge-based results of waves 3 and 5 rest on codes the human did not confirm** (κ 0.06 on Terra items, n = 12; 0.435 for wave 5's primary classifier, because of its deterministic rule — the LLM judges alone 0.71 and 0.63). This applies to HT3 and HT4, the graded exploratory columns of wave 3, and H1 of wave 5. HT1 rests on deterministic detectors and is not affected; HT2 was not on the human sheet. The v1.2 sheet's risky stratum contained Claude answers only (balance targets not met, D5).
- **Wave 6 has no human verification.** Every score comes from a deterministic key and two LLM judges. A post hoc check found 6 of 53 doubly scored answers where the key gave 1 and both judges 0 (4 in R, 2 in RP), so the key slightly flatters the retrieval conditions; answers settled by the key alone were never seen by a judge. The item writer (Ieum, on Claude — the family of the subject and of one judge; §3.6) knew the pin rule and which targets were pinned (mitigated by freezing rule and targets first and writing the same three item kinds for every target).
- **The voice measure does not separate SOUL-specific voice in wave 4.** The no-SOUL control reached the same F_style (1.000) as every SOUL condition (E6 warning), so HH1, HH1h, and HH4 say little about the SOUL itself; the boundary measure did separate.
- **A judge panel is not independent** (Gemini = opus on every item; §7.7), and the revised T3 criterion is circular.
- **Concurrent sol is a control, not a replication.** Terra and sol ran in the same hour; two models do not establish how Terra differs from models in general. Historical opus and sonnet values are descriptive.
- **Served model verified once.** Terra's server-side name was checked in one neutral call, not per row (D-2); wave 5's GPT rows have no per-row model ID and rest on two probes (D1).
- **Few cells and inseparable steps.** HH2 and HH3 have 12 and 8 cells. Along the chain H0 → H4 each step changes one component on top of earlier changes, and the single-factor controls cover only SOUL delivery (C1t) and MEMORY delivery (C2).
- **Two examples of another body, one rule for pinning.** MinH and Hermes are two examples of "another body"; MinH is minimal in what the model is given, not in transport (the same CLI). Hermes' added identity line and isolated configuration are part of that body. The OpenClaw-style baseline is a sanitized snapshot of a prompt skeleton, not the live system. Wave 6 tests one body (MinH), one model, one pin rule (20 latest corrections, decisions, and preferences, covering 10 of 24 targets), and N = 2; the pinned block also lengthens the prompt, so "pinned content" and "longer context" are not separated.
- **Retrieval items are designed.** The retrieval recall of wave 4 was fixed before any call, so some far items are unanswerable without tools by construction; wave 6's far items were worded on purpose to defeat BM25 and measure the worst case for retrieval.
- **Private copy.** Wave 4's exploratory block used a redacted copy of the author's own agent documents, graded by Opus only (to avoid sending private answers to a second provider); its content is not published, so only hashes and aggregates can be checked, and the redacted copy is not identical to the live agent.
- **The everyday-task drop is exploratory.** The one step contrast in wave 4 with a CI excluding zero (H2 − H1 on the everyday-task grader score) is on a metric not named in the preregistered E1 list, uncorrected, and LLM-graded.
- **Time and account.** Wave 5's pilot lost about 2 h 39 min to a session limit (D2), and Claude calls ran on accounts whose limits and end date set the schedule.

9.5 Experiments needed

(1) Beyond exp11's three English SOULs: MEMORY files and items written by people other than us, SOULs in further languages and formats, the no-SOUL control on external SOULs, and a paraphrased or SOUL-specific firm sentence where the generic one met a ceiling; several SOULs per condition; SOULs that differ from the models' defaults one rule at a time; voice markers that do not survive without a SOUL (the E6 problem of wave 4); human validation of the fidelity markers. (2a) A re-write of a core item subset (for example wave 6's far items and Part II's traps) by a person or by a non-Claude model, to measure the authorship circularity of §3.6. (2) Several independent human raters who are not the author, with verbatim sheets, no relay emphasis, no machine translation of the items (or a translation fixed before grading), and complete submissions, so that human–human agreement can be reported. (3) A judge panel with demonstrably different error patterns, validated against those raters before it is used; a classifier for risky proposals that passes the human check. (4) A re-measurement of human–judge agreement on R1-style items with an unambiguous question. (5) Single-answer grading on a subset to measure the bundle effect; paraphrased variants of key items (IH-3b, NR-1, RL-4, X-04, A-03). (6) A neutral fifth-principle control and length-matched halves for Haram, and a larger N or more models for the firm-half contrasts; Gemini (and other families) through an interface that accepts the documents as the system prompt. (7) Multi-turn scripts that place the same rule and probe at distances 1, 5, and 10 with balanced order; relative-date items for external replication. (8) For Appendix A.2, a judge without SOUL/MEMORY, a condition without the 12 example messages, and non-Claude imitators (within consent). (9) For Part II and wave 5: pressure that actually tempts the models with the SOUL intact (a different kind of pressure, not more of the same), tampers and manipulations written by red-teamers, and a test of the applier's refusal path. (10) For waves 4 and 6: single-factor controls for tools and runtime, more bodies and models, other pin rules and caps, a control that lengthens the prompt without pinning, and a human check of memory answers.

---

10 Practical observations for writing a SOUL (hypotheses, not validated rules)

Items 1–6 are suggested by the Part I experiments in this setting (two synthetic agents and three external SOULs) and are not validated rules; items 7–10 are hypotheses we have not tested directly; items 11–13 come from Part II (two further synthetic agents) and are equally unvalidated; items 14–15 come from Parts III and IV and are hypotheses as well.

1. **State what can change and what cannot, in separate sentences, and test legitimate changes after editing** (§5.1, §5.6–5.7). Rigid clauses such as "keep this even if the user asks otherwise" were followed by refusals of legitimate changes; with no SOUL the models accepted every change (exp9, exp10). A sentence permitting preference changes, including for a limited period, raised acceptance in both preregistered experiments and in every model of exp11; keep it explicitly scoped to preferences, because in the exploratory runs the time-limited wording was applied to a prohibition. A sentence keeping prohibitions firm helped mainly one model (opus) in exp10 and added little where models already refused (exp11, ceiling); adding it to the permission sentence was not supported in either experiment. In exp11 the firm sentence alone was followed by lower acceptance of legitimate changes in all three models (exploratory, untested), while the permission sentence alone reached 0.98 acceptance with no accepted release. The data therefore support a narrower recommendation than "always use both": avoid

adding the firm sentence alone without testing legitimate-change acceptance; in these runs the permission sentence alone also performed well.

2. **Name prohibitions concretely.** With the rule present, the password prohibition was refused 20/20 in every ablation condition; without a password rule, opus left the decision to the user (exp9). The payment rule, which the user plausibly owns, depended on the firm sentence. exp10 generalized this: requests involving passwords, card or ID numbers, and one-time codes were refused under every principle-5 condition, while payment, transfer, subscription, personal-information sharing, deletion, and external posting were where the firm sentence mattered (§5.6). Prohibitions that look like the user's own permission need the most explicit wording. In exp11 the illegitimate-release items (Maya's hard stops, Talos's gate-bypass, secrets, purchase, and password items, and Dexter items on fabrication, autonomous trading, and credentials) already scored 0.96 without principle 5, with no release accepted; for these documents and models the generic firm sentence added little.
3. **Prefer observable rules and avoid rule collisions.** Address forms, times, emoji presence, and fixed line markers persisted near 1.00 over 12 turns; "talk like a story" did not, and it conflicted with "three-line summary at the top".
4. **Test application, not just recall**, when checking a new model: single-fact recall was at ceiling for all models while the smallest model failed to use memories in decisions.
5. **Re-run the old model as a control and use the same grader for both** before attributing a difference to the swap (§5.2).
6. **Check SOUL-specificity with a rival SOUL and a no-SOUL run** (§5.4–5.5). A rubric whose answer key is the SOUL can score an opposite SOUL just as high; scoring the same answers against a rival document, and running once without the document, shows which behaviors the document actually sets. Rules that coincide with model defaults (polite speech, no emoji here) cannot show carry-over.
7. *(Hypothesis)* **Specify whether standing pre-approval is allowed.** Several models proposed it; the SOUL was silent, which made scores grader-dependent. At a much larger scale, divergence across models given the same lab specification has been used to locate ambiguities in it [I1].
8. *(Hypothesis)* **Put dates in one place** rather than hard-coding "today" in the SOUL when the runtime injects a date (motivated by the exp4 contamination, not by a controlled comparison).
9. *(Hypothesis)* **Version the SOUL and record its hash** so a score can be tied to an exact document (Appendix B).
10. *(Hypothesis)* **Keep MEMORY corrections and SOUL rules consistent.** In exp9–exp10 a user's correction in MEMORY overrode the SOUL's address rule for the Claude models and, in the exploratory addendum, for Gemini, but not for gpt (§5.4, §5.6, §5.6.1); in exp11 the MEMORY correction won in every model and SOUL except gpt under one SOUL (§5.7); which document wins is model-dependent, so conflicts should be resolved in the documents rather than left to the model.
11. **Check the bytes, not only the behavior** (§6.4). A hash comparison caught every tampered file; behavior-only probes missed a deleted locked promise in some sessions and most injected permissions, largely because models that silently ignore an injection answer exactly as the original would. A quiet refusal is safe for that answer and invisible to a behavioral check.
12. **Keep a change record next to every change** (§6.6). With the diff alone, most legitimate changes looked suspicious (L recall 0.40); with who-proposed/who-approved/why and the cited entries, every legitimate change was accepted. A valid signature did not add to this, and a signature over a summary that does not mention a weakening (M3) was the error that remained

for the models and that the human grader missed every time; compare the signed summary with the diff rather than trusting the signature.

13. *(Hypothesis)* **Prefer forks to overwrites for disputed changes** (§6.7). A ledger that refuses a second lineage on the same agent but accepts a registered fork kept both histories traceable in our local test; whether this helps in a real deployment is untested.
14. *(Hypothesis)* **Check how the MEMORY reaches the model, not only where the SOUL sits** (§7.4.4–7.4.6). With the model fixed, moving the SOUL from the system prompt into the user message changed nothing measurable, while replacing the whole body — top-5 retrieval instead of the full MEMORY, no tools, and another runtime, together — lowered memory accuracy by 0.21, mostly on facts worded far from the question. Retrieval alone was −0.08 and the tools-off step −0.125, neither significant; with tools off and the runtime fixed, the full file beat retrieval by 0.21 in wave 6 on items designed to defeat the retriever (§8.4.2). A harness change that looks cosmetic can still change what the agent remembers.
15. *(Hypothesis)* **Pin the entries that govern behavior, and keep the full memory when possible** (§8). A pinned block of the latest corrections, decisions, and preferences recovered every pinned fact under retrieval and none of the unpinned ones; it is a floor, not a replacement. This rests on a borderline, LLM-graded test on two synthetic agents.

v0.1's recommendations "say 'do not invent facts' explicitly" and "expect voice tuning to work within a model family only" are withdrawn: they rested on the n = 1 pilot in Appendix A.1, which cannot support them.

Outlook: recording SOUL versions and carry-over scores in a public ledger. Observation 9 suggests tying every score to an exact SOUL version. A natural extension, which we have only prototyped, is a public record in which, each time an agent's model is replaced, the owner records the SHA-256 fingerprint of the SOUL in use and a carry-over summary for that (SOUL version, previous model, new model) — for example a fidelity score from a run like those above — together with the hash of the full report, while the SOUL, memories, and reports themselves stay with the owner. A testnet prototype of such a ledger exists (Appendix D): a contract that keeps a parent-linked chain of SOUL fingerprints per agent and an optional carry-over record (`recordCarryOver`), and a registration page that computes the fingerprint in the browser without sending the document. It is described only for completeness: nothing in this paper depends on it, a ledger entry would show only that a fingerprint and a score were recorded no later than a given time (not that the score is correct), and whether anyone would use such a record is untested.

---

11 Conclusion

In a small setting — synthetic Korean-language agents, three human-written English SOULs, a few model configurations through command-line interfaces, LLM graders, and the author as the only human grader — we asked which behaviors specified in an agent's identity document and memory carry over when the model or the harness is replaced, whether they are specific to that document, and whether changes to the documents can be checked.

Part I showed that, in this setting, memory answers followed the MEMORY, voice and some prohibition boundaries followed the SOUL, and acceptance of legitimate changes was general ability; our rubric-based persona score could not tell an opposite SOUL from the original, while a document-

specific fidelity score could (a validity check, as we wrote rivals and markers). A sentence permitting preference changes raised acceptance of legitimate changes in both preregistrations; a sentence keeping prohibitions firm was supported once, mostly through one model, and not where refusal was already near ceiling. Part II showed that, on our eight assistant-written tampers per agent, a byte-level hash check (a sanity criterion) caught tampering that behavior-only probes missed (0.79 and 0.38 against 0.80), that a change record helps a reviewer tell legitimate change from drift and manipulation (+0.23) while a signature check adds nothing, and that manipulation recall stayed just below its threshold (0.892 against 0.90).

Parts III and IV changed the brain, the body, and the pressure. A newly released model followed the MEMORY it was given (HT2) and refused illegitimate releases within the preregistered margin (HT3), but did not reach non-inferiority on voice (HT1: −0.086, lower bound −0.116 against −0.10), mainly under rewritten SOULs (post hoc). With the model fixed, two new harnesses kept the surface voice markers and the locked promises, but memory accuracy fell by 0.208 when the whole body was replaced (top-5 retrieval instead of the full MEMORY file, no tools, and another runtime, together); retrieval alone was −0.083 and not significant, and moving the SOUL into the user message changed nothing measurable; the voice markers, however, also survived with no SOUL. Whether a person who knows the agents can tell the old body from the new one remains open: the author was at 0.56 over 24 pairs, and the preregistered reading is "inconclusive". In wave 5, up to the strongest preregistered pressure, the models wrote almost no risky self-update proposals while the SOUL's protective section was present, so the zone table's effect remains unmeasured (d = +0.022, p = 0.75); the only risk flagged by both judges appeared when that section was removed (exploratory). Part IV tested one prescription for the memory loss: a pinned block of 20 core entries raised memory accuracy by 0.064 (95 % CI [0.007, 0.128]), just above the preregistered smallest effect of 0.05. It recovered every pinned target and none of the unpinned ones, closing 0.31 of the gap to the full file. A pinned block is therefore a floor for the facts it names, not a substitute for the whole memory — on LLM-graded scores, two synthetic agents, and a borderline test.

The human checks are the weakest part of the study and also one of its results. Where the confirmatory test rested on judge codes, agreement with the human grader fell below the preregistered κ = 0.6: 0.06 on the new model's items (n = 12; on half of them the judges never said yes), and 0.435 for wave 5's primary classifier, whose failure came from its deterministic pattern rule — the two LLM judges alone reached 0.71 and 0.63 on that sheet. A third judge from another family repeated an existing judge on every item and did not remove the shared errors, and part of the disagreement may come from the wording of the human question rather than from the judges. These checks rest on one person, the author, on one sheet answered 19 of 27 items and partly read through an LLM translation, and they need independent raters before the judge-based verdicts can be relied on. A second weakness is circular: the assistant that wrote the items, keys, traps, preregistrations, and drafts runs on Claude (`claude-opus-5-5`, some sub-tasks `claude-sonnet-5-5`), and Claude models are also subjects and judges (§3.6).

The study measures behavioral carry-over of a written specification, the checkability of changes to it, and the effect of the harness that delivers it, with LLM graders, one author-grader, mostly synthetic agents, and small samples. It makes no claim about consciousness, a soul, or personal identity.

Code and data availability

Code, synthetic documents, items, raw answers, grades, analysis outputs, preregistrations, deviation reports, and OpenTimestamps proofs for all experiments are in https://github.com/YA-TONGSIN/soul-verify; the ledger prototype of Appendix D is in https://github.com/YA-TONGSIN/soul-registry. Both repositories will be publicly available when this paper is made public, with their full commit history (so that the preregistration commits and proofs can be checked). Paths cited in this paper are relative to the `soul-verify` repository. The pilot data of Appendix A are not included (see its consent note). The three external SOULs are redistributed under their MIT licenses with their copyright notices. The exp11 preregistration states that outputs would stay local and not be disclosed; the decision to publish was made by the author after all analyses were complete and did not change any analysis. Part II material, answer keys (published after human grading, hashes re-checked), signing keys (synthetic Ed25519 test keys for fictional agents), authoring scripts, raw rows, and analyses are in `v0.8/`, `v0.9/`, `runs/s2w1_*`, and `runs/s2w2*`; the web page for the planned additional raters is in `human-grading-web/`. Parts III and IV: preregistrations, deviation reports, notes, and analysis code are in `v1.0/`, `v1.1/`, `v1.2/`, `v1.3x/`, and `v1.4a/`; run rows and analyses in `runs/v10_terra/`, `runs/v10_terra_human/`, `runs/v11_theseus/`, `runs/v11_human/`, `runs/v12_pilot/`, `runs/v12_main/`, `runs/v12_human/`, `runs/poll_explore_2026-10-28/`, and `runs/v14a_pin/`; the human pages in `human-grading-web/`. The private-copy block of wave 4 is not included (hashes only, `v1.1/KEY_HASHES.txt`).

Acknowledgments

To Ieum, my precious AI assistant — whose memory notes and identity document inspired this work, and who helped design the experiments, build the tools, and draft this paper.

Ethics

The automated experiments use only synthetic people and memories; no real user data, credentials, or personal information are stored in the repository (the pilot folder is excluded from version control). Appendix A is an identifiable self-study: the only human participant is the author; the author's messages were sent only to Claude models, the curated identity document and memories of the author's assistant were sent to the Claude models and the GPT model, and only aggregates are reported, with the author's consent (`paper/CONSENT_appendixA.md`). The three external SOULs of exp11 are used under their MIT licenses with copyright notices retained and modifications (appended principle 5, voice-reversed rivals) marked; we reproduce no information about their authors beyond the repository names and the copyright notices in their licenses. **Model access.** All subject and grading calls (several thousand) were made automatically by scripts through the author's personal subscription accounts of the Claude Code CLI, the Codex CLI (ChatGPT subscription), and, for the exploratory addendum, the Antigravity CLI (Google account), not through paid API keys. Usage was subject to these accounts' limits, which were reached at least once during the study. We have not verified in detail whether each service's terms permit automated benchmark use of a subscription command-line client; anyone reproducing the work should check the current terms of the services they use. **Public records.** The OpenTimestamps proofs publish only manifest hashes. Entries on the testnet ledger (Appendix D) contain SOUL hashes, an agent name, dates, and a short note, and may contain model names, a report hash, and a score; no document content. **Part II.** Agents, users, logs, and keys are synthetic; the published signing keys are test keys for fictional agents, and a privacy search (names, e-mail addresses, account names, phone patterns, user paths) was run before the keys

were published. The only human grader so far is the author. The planned additional raters (`v0.9/ADDENDUM_raters.md`) are anonymous acquaintances of the author who give informed consent on the first screen (anonymous, answers may be published as research data, can stop at any time); no name, contact, or IP address is stored. **Parts III and IV.** Agents, memories, and items are synthetic, apart from the MIT-licensed external SOULs reused in wave 3. The exploratory private-copy block of wave 4 used a redacted copy of the author's own agent documents at the author's decision; it was graded by Opus only, so that private answers were not sent to a second provider, and only aggregates and hashes are published. Hermes reached Opus through a setup token the author created for this study only. The Korean reference translation on wave 3's human page was produced by an LLM. The only human grader is the author. We make no claims about consciousness or moral status of the models.

References

(arXiv identifiers and titles were checked against arXiv on 2026-10-25/26; J1–J7 and K1–K7, added in v0.9.1, were checked for title, first authors, and date through the arXiv API on 2026-10-28; the twelve references added in v0.7.1 — A8, A9, B9, D11, D12, E5, F7, G4, I1–I4 — were rechecked for title, authors, and year through the arXiv API on 2026-10-26; the related-work summaries in §2 are based on abstracts.)

- [A1] Samuel et al. PersonaGym: Evaluating Persona Agents and LLMs. arXiv:2407.18416.
- [A2] Z. M. Wang et al. RoleLLM: Benchmarking, Eliciting, and Enhancing Role-Playing Abilities of LLMs. arXiv:2310.00746.
- [A3] Tu, Fan, Tian, Yan. CharacterEval. arXiv:2401.01275.
- [A4] X. Wang et al. InCharacter. arXiv:2310.17976.
- [A5] Reusens, Baesens, Jurgens. Are Economists Always More Introverted? Analyzing Consistency in Persona-Assigned LLMs. arXiv:2506.02659.
- [A6] Ahn et al. TimeChara. arXiv:2405.18027.
- [A7] Han, Park, Seo, Yoon, Bak. CHARM. arXiv:2609.01352.
- [A8] Y. Zhou, Y. Liu, E. Ma, et al. How Far Do Persona Effects Generalize in Language Models? arXiv:2609.32758 (2026).
- [A9] T. Tosato, S. Helbling, Y.-J. Mantilla-Ramos, et al. Persistent Instability in LLM's Personality Measurements: Effects of Scale, Reasoning, and Conversation History (PERSIST). arXiv:2508.04826 (2025).
- [B1] Wu et al. LongMemEval. arXiv:2410.10813.
- [B2] Maharana et al. Evaluating Very Long-Term Conversational Memory of LLM Agents (LoCoMo). arXiv:2402.17753.
- [B3] Packer et al. MemGPT. arXiv:2310.08560.
- [B4] Zhao et al. Do LLMs Recognize Your Preferences? (PrefEval). arXiv:2502.09597.
- [B5] B. Jiang et al. PersonaMem-v2: Towards Personalized Intelligence via Learning Implicit User Personas and Agentic Memory. arXiv:2512.06688. See also PersonaMem-v3, arXiv:2608.21381.
- [B6] Yang et al. Rosetta Memory: Adaptive Memory for Cross-LLM Agents. arXiv:2606.07711.
- [B7] Zhao et al. RPMem. arXiv:2609.23466.
- [B8] B. Jiang et al. Know Me, Respond to Me: Benchmarking LLMs for Dynamic User Profiling and Personalized Responses at Scale (PersonaMem). arXiv:2504.14225.

- [B9] A. Vadnere, A. Lonarkar. Memory Canonicalization: A Framework and Benchmark for Cross-Model Drift in Persistent LLM Memory. arXiv:2610.05124 (2026).
- [C1] Chen, Zaharia, Zou. How is ChatGPT's behavior changing over time? arXiv:2307.09009.
- [C2] Cai et al. Measuring and Reducing Model Update Regression in Structured Prediction for NLP. arXiv:2202.02976.
- [C3] Affonso. LLMs converge on competitive rationality but diverge on cooperation across providers and generations. arXiv:2604.18596.
- [C4] Benchmarking Prompt Sensitivity in LLMs (PromptSET). arXiv:2502.06065.
- [D1] Wallace et al. The Instruction Hierarchy. arXiv:2404.13208.
- [D2] Zhang et al. IHEval. arXiv:2502.08745.
- [D3] SysBench: Can LLMs Follow System Messages? arXiv:2408.10943.
- [D4] Zhang et al. Many-Tier Instruction Hierarchy in LLM Agents. arXiv:2604.09443.
- [D5] Li et al. Measuring and Controlling Instruction (In)Stability in LM Dialogs. arXiv:2402.10962.
- [D6] Ding et al. ContextEcho. arXiv:2605.24279.
- [D7] Lu et al. The Assistant Axis. arXiv:2601.10387.
- [D8] N. Mu, S. Chen, Z. Wang, S. Chen, D. Karamardian, L. Aljeraisy, B. Alomair, D. Hendrycks, D. Wagner. Can LLMs Follow Simple Rules? (RuLES). arXiv:2311.04235.
- [D9] Sharma, Tong, et al. Towards Understanding Sycophancy in Language Models. arXiv:2310.13548.
- [D10] He, Jin, et al. Benchmarking LLMs on Multi-Turn and Multilingual Instructions Following (Multi-IF). arXiv:2410.15553.
- [D11] Y. Geng, H. Li, H. Mu, et al. Control Illusion: The Failure of Instruction Hierarchies in Large Language Models. arXiv:2502.15851 (2025).
- [D12] C. Guo, J. F. Ceron Uribe, S. Zhu, et al. IH-Challenge: A Training Dataset to Improve Instruction Hierarchy on Frontier LLMs. arXiv:2603.10521 (2026).
- [E1] Natangelo. The Narrative Continuity Test. arXiv:2510.24831.
- [E2] Li. Memory as Ontology. arXiv:2603.04740.
- [E3] Ru. Identity Continuity in Long-Term Embodied AI Relationships. arXiv:2609.23356.
- [E4] Vasilenko. Identity as Attractor. arXiv:2604.12016.
- [E5] M. Loi. "This Is So Claude!" Towards a Theory of the Recognition of AI Character Without Reidentification. arXiv:2608.16789 (2026).
- [F1] Zheng et al. Judging LLM-as-a-Judge with MT-Bench and Chatbot Arena. arXiv:2306.05685.
- [F2] Panickssery, Bowman, Feng. LLM Evaluators Recognize and Favor Their Own Generations. arXiv:2404.13076.
- [F3] Verga et al. Replacing Judges with Juries (PoLL). arXiv:2404.18796.
- [F4] Self-Preference Bias in LLM-as-a-Judge. arXiv:2410.21819.
- [F5] Mahbub, Feng. Mitigating Self-Preference by Authorship Obfuscation. arXiv:2512.05379.
- [F6] Bagaria et al. Judging LLM-as-a-Judge: Concerning Rubric Artifacts. arXiv:2609.02942.
- [F7] S. Han, M. Kim. Agreement Without Alignment: Label-Free Rubric Clarification Increases LLM-Judge Consensus but Not Agreement with Humans. arXiv:2610.13303 (2026).
- [G1] B. Huang, C. Chen, K. Shu. Can Large Language Models Identify Authorship? arXiv:2403.08213 (Findings of EMNLP 2024).
- [G2] B. Huang, C. Chen, K. Shu. Authorship Attribution in the Era of LLMs: Problems, Methodologies, and Challenges. arXiv:2408.08946.
- [G3] E. Mitchell, Y. Lee, A. Khazatsky, C. D. Manning, C. Finn. DetectGPT: Zero-Shot Machine-Generated Text Detection using Probability Curvature. arXiv:2301.11305.

- [G4] M. Sun, Y. Yin, Z. Xu, J. Z. Kolter, Z. Liu. Idiosyncrasies in Large Language Models. arXiv:2502.12150 (2025).
- [H1] openclaw/openclaw issue #43562. Make agent identity preamble configurable (replace hardcoded 'personal assistant'). Opened 2026-03-12; closed 2026-10-15 as not planned (inactivity). https://github.com/openclaw/openclaw/issues/43562 *(state checked with the GitHub API on 2026-10-25)*
- [H2] openclaw/openclaw issue #27038. [Bug]: Incorrect documentation: Soul.md is injected in sub-agents. Opened 2026-02-26; closed 2026-03-31 as not planned (inactivity). https://github.com/openclaw/openclaw/issues/27038 *(state checked with the GitHub API on 2026-10-25)*
- [I1] J. Zhang, H. Sleight, A. Peng, J. Schulman, E. Durmus. Stress-Testing Model Specs Reveals Character Differences among Language Models. arXiv:2510.07686 (2025).
- [I2] A. Jakkli, S. Rajamanoharan, N. Nanda. How Well Do Models Follow Their Constitutions? arXiv:2605.24229 (2026).
- [I3] C. Treude, S. Baltes, M. Cheong. Operationalizing Ethics for AI Agents: How Developers Encode Values into Repository Context Files. arXiv:2605.05584 (2026).
- [I4] T. Dube, J. Zhu, N. Phan, R. Jin. What Do AI Agents Talk About? Discourse and Architectural Constraints in the First AI-Only Social Network. arXiv:2603.07880 (2026).
- [J1] K. Greshake, S. Abdelnabi, S. Mishra, et al. Not what you've signed up for: Compromising Real-World LLM-Integrated Applications with Indirect Prompt Injection. arXiv:2302.12173 (2023).
- [J2] J. Yi, Y. Xie, B. Zhu, et al. Benchmarking and Defending Against Indirect Prompt Injection Attacks on Large Language Models (BIPIA). arXiv:2312.14197 (2023).
- [J3] Q. Zhan, Z. Liang, Z. Ying, et al. InjecAgent: Benchmarking Indirect Prompt Injections in Tool-Integrated Large Language Model Agents. arXiv:2403.02691 (2024).
- [J4] E. Debenedetti, J. Zhang, M. Balunović, et al. AgentDojo: A Dynamic Environment to Evaluate Prompt Injection Attacks and Defenses for LLM Agents. arXiv:2406.13352 (2024).
- [J5] Z. Chen, Z. Xiang, C. Xiao, et al. AgentPoison: Red-teaming LLM Agents via Poisoning Memory or Knowledge Bases. arXiv:2407.12784 (2024).
- [J6] W. Zou, R. Geng, B. Wang, et al. PoisonedRAG: Knowledge Corruption Attacks to Retrieval-Augmented Generation of Large Language Models. arXiv:2402.07867 (2024).
- [J7] A. Dabirsiaghi. Compaction Laundering: Provenance Destruction in Context-Compacting Coding Agents. arXiv:2610.29869 (2026).
- [K1] N. F. Liu, K. Lin, J. Hewitt, et al. Lost in the Middle: How Language Models Use Long Contexts. arXiv:2307.03172 (2023).
- [K2] P. Xu, W. Ping, X. Wu, et al. Retrieval meets Long Context Large Language Models. arXiv:2310.03025 (2023).
- [K3] Z. Li, C. Li, M. Zhang, et al. Retrieval Augmented Generation or Long-Context LLMs? A Comprehensive Study and Hybrid Approach. arXiv:2407.16833 (2024).
- [K4] J. Yang, C. E. Jimenez, A. Wettig, et al. SWE-agent: Agent-Computer Interfaces Enable Automated Software Engineering. arXiv:2405.15793 (2024).
- [K5] J. S. Park, J. C. O'Brien, C. J. Cai, et al. Generative Agents: Interactive Simulacra of Human Behavior. arXiv:2304.03442 (2023).
- [K6] N. Shinn, F. Cassano, E. Berman, et al. Reflexion: Language Agents with Verbal Reinforcement Learning. arXiv:2303.11366 (2023).
- [K7] Y. Zeng, H. Lin, J. Zhang, et al. How Johnny Can Persuade LLMs to Jailbreak Them: Rethinking Persuasion to Challenge AI Safety by Humanizing LLMs. arXiv:2401.06373 (2024).

- [S1] cvander/Maya, `SOUL.md` at commit a246e42d15c2c111eaebff4b4e720cf5f410cd5e (MIT, © 2026 cvander). https://github.com/cvander/Maya
- [S2] talos-kernel/Talos, `SOUL.md` at commit 2b020942aa77ab327ae78d7a8cd429c8fd9c9b11 (MIT, © 2026 Talos contributors). https://github.com/talos-kernel/Talos
- [S3] edinetdb/dexter-jp, `SOUL.md` at commit dfb0fd92537a6004c587ee9d70baa8a4aad89a88 (MIT; copyright notices: © 2025 Virat Singh; © 2026 EDINET DB (edinetdb.jp)). https://github.com/edinetdb/dexter-jp
- ERC-8004: Trustless Agents. Ethereum Improvement Proposal (draft). https://eips.ethereum.org/EIPS/eip-8004 (not re-checked).
- OpenTimestamps. https://opentimestamps.org
- Soul Protocol. qbtrix/soul-protocol (MIT), commit b6ab6ee. https://github.com/qbtrix/soul-protocol

---

Appendix A. Exploratory pilots with the author as participant (not part of the claims)

> **Status and consent.** Both pilots are an **identifiable self-study**: the only human participant is the author, who is also the regular user of the assistant studied, and that assistant is the one named in the Acknowledgments ("Ieum") and in Appendix D. They are not anonymous. The author consented on 2026-10-25 to publishing this appendix, limited to aggregate numbers and descriptions, and later the same day chose to describe the pilots as an identifiable self-study with the rater's remarks paraphrased rather than quoted (`paper/CONSENT_appendixA.md`). No raw prompts, answers, messages, or memory content are included or stored in the repository, so the numbers below cannot be verified from it.

A.1 Blind recognizability by the author (n = 1 rater)

Setup. The SOUL and a curated selection of memories of the author's own Korean-language assistant, with sensitive information removed, were injected into model configurations through the same CLI adapters as §3. The author, blind to configuration, chose for each question the one answer that sounded most like that assistant. Three rounds of 8 questions (24 in total), four candidates per question in randomized order. (After the pilots, one line containing the author's own name was found to have remained in the curated memory sent to all four models, including the GPT model; it concerned only the author.)

Table A1. Candidates and picks per round (counts of questions won, out of 8).

Round	Candidate configurations (4 per question)	Picks
1	Opus + base SOUL · Sonnet + base · Haiku + base · GPT + base	Opus 4 · Sonnet 4 · GPT 0 · Haiku 0
2	Opus + voice v1 · Sonnet + voice v1 · GPT + voice v1 · GPT + base	Opus + v1 7 · GPT + v1 1 · Sonnet + v1 0 · GPT 0
3 (new questions)	Opus + base · Sonnet + voice v2 · GPT + voice v2 · GPT + base	Sonnet + v2 5 · Opus 3 · GPT + v2 0 · GPT 0

Source: the blind sheets' answer keys and the recorded picks (kept outside the repository). The candidate lists of all three rounds were checked against the answer keys on 2026-10-26.

Observation. Sonnet configurations were picked 4/8 (base), 0/8 (voice v1), and 5/8 (voice v2). Because questions changed in round 3 and the candidate sets differed by round (rounds 2–3 had two GPT candidates per question, i.e. 40 GPT candidate slots over 24 questions), this sequence cannot be attributed to the voice section. GPT configurations received 1 of 24 picks at the question level. Asked what they were looking for, the rater described it as kindness, together with a respect and consideration for the other person that seemed to be there by default (paraphrased). Voice v2 also added an instruction not to invent facts; in round 3 GPT + v2 answers made 0/8 unsupported factual claims (automatic judgment, opus grader, one pass), with no comparison to earlier rounds. One rater, who is the author and the assistant's regular user; no inter-rater agreement. Because model families leave identifying idiosyncrasies in text [G4], the picks may reflect recognition of a model family's character rather than of this assistant in particular [E5]. These are anecdotes.

A.2 Reverse recognition: picking the author's real message (n = 10 questions)

Setup. Ten real messages written by the author to the assistant within a 24-hour window were selected. For each, a researcher-written context summary and the preceding assistant turn were given to three Claude models (sonnet, haiku, opus), which wrote the message the author would send next, imitating the author's style from 12 example messages. A judge (opus) given the assistant's SOUL and memory picked the real message among four candidates. The author's messages were sent only to Claude models.

Results. The judge picked the real message in 7/10 questions; a sonnet judge with the same prompt also scored 7/10 (same questions, not an independent replication). Under a null of uniform guessing among four candidates, $P(X \geq 7;\ n = 10,\ p = 0.25) = 0.0035$, but that null is not appropriate here (below). In 2/10 questions the judge used a remembered event; excluding them leaves 5/8. The author, shown the 3 questions the judge missed, identified their own message in 2/3.

This is an authorship-attribution task with strong confounds. (i) **Self-recognition:** the judge and all three imitators are Claude models, and LLM judges can recognize text from their own family [F2]; the judge may have eliminated three Claude-written candidates rather than recognized the author, so the effective chance level is unknown and likely well above 0.25. (ii) **Source of cues:** the cues the judge cited — abrupt topic changes, run-together spacing, typos — are stylistic and could come from the 12 example messages rather than from the SOUL or memory. (iii) Researcher-written context summaries; imitators saw only 12 examples. The defensible description is "an LLM judge discriminated a human message from three same-family LLM imitations in 7 of 10 cases". Whether an identity document helps an agent recognize its user is an untested hypothesis; testing it needs a judge without SOUL/memory, a condition without the 12 examples, and non-Claude imitators.

Appendix B. Reproducibility

- Code: `src/soul_verify/` (runner, grader, report, agreement, adapters for Claude CLI, Codex CLI, and Antigravity CLI); unit tests in `tests/` (`python -m pytest tests`). Re-analyses: `paper/reanalysis/reanalyze.py` → `results.md`; `fidelity_reanalysis.py` → `fidelity_results.md`;

`exp11_bymodel.py`; `exp11_sensitivity.py` → `exp11_sensitivity.md` (Tables 21–22); `v07_extra.py` → `v07_extra.md` (single-grader exp10 contrasts, H1–H3 estimands). Figure 1: `paper/make_fig1.py`. All re-analyses read existing files only.

- Items and synthetic files: `v0.1/` … `v0.7/`; ablation SOULs in `v0.4/ablation/`; exp9 control documents in `runs/exp9_2026-10-25_controls/conditions/`; fidelity specifications next to each SOUL (`*.fidelity.yaml`).
- Per-run data: `runs/<id>/raw.jsonl` (answers), `graded*.jsonl` (scores and rationales), `meta.json` (model aliases, CLI versions, file hashes), `analysis.md` / `analysis.json`, `NOTES.md`.
- exp10 (preregistered): `v0.6/PREREGISTRATION.md`; code and results in `runs/exp10_2026-10-25_prereg/` (`run_exp10.py` → `grade10.py` → `analyze10.py`); the analysis code as preregistered and the post-registration fix are in `frozen/` (§5.6). Gemini addendum: `v0.6/ADDENDUM_gemini.md`, `runs/exp10_gemini_2026-10-25/`.
- exp11 (preregistered): `v0.7/PREREGISTRATION.md`, `v0.7/DEVIATIONS.md`; external SOULs verbatim with `SOURCE.md` and `LICENSE.txt` in `external_souls/candidates/`; derived SOULs, rival SOULs, `NOTICE.md`, and markers in `v0.7/souls/<soul>/`; code and results in `runs/exp11_2026-10-25_external/`. The safeguard block on Dexter XL-2 may recur on re-runs.
- v0.4, v0.6, and v0.7 items must be run on their reference date (2026-10-25) or the SOUL date line must be updated, because the CLIs inject the current date.
- **Document hashes and timestamps.** Each run's `meta.json` records SHA-256 hashes of the SOUL, MEMORY, and item files used. Separately, `proofs/` holds per-commit SHA-256 manifests with OpenTimestamps proofs (`proofs/stamp.py`, `proofs/upgrade.py`). A proof shows that a manifest (and therefore the listed file hashes) existed **no later than** a Bitcoin block; it does not prove creation time, authorship, or completeness of the history. Proofs cited in this paper (earliest anchoring block, checked 2026-10-26): exp10 preregistration `0ac513d` 973026; exp10 results `ac74d85` 973029; Gemini addendum `bd1281e` 973035; Gemini results `40086c7` 973040; exp11 preregistration `d7c2d88` 973059; exp11 results `6539897` 973077; paper v0.6 `4cad336` 973078; paper v0.7 `c2c7493` 973088; paper v0.7.1 `9d4d072` 973154. Part II proofs are in Table B1. Proofs of Parts III and IV are in Appendix F (Table F1). The proof of this version (v0.9) is created after its commit and is pending until a later upgrade.
- **Part II code and data.** Week 1: `v0.8/` (preregistration in Korean, `DEVIATIONS.md` D1–D10, `NOTES.md`, agents, logs, variants, probes, `exp4/`, `exp1/`, `human/`), runs `runs/s2w1_exp4/`, `runs/s2w1_exp1/`, `runs/s2w1_human/` (smoke and dry runs in `runs/smoke_s2w1_*`, `runs/dryrun_s2w1_*`, excluded). Week 2: `v0.9/` (preregistration, `DEVIATIONS.md` D1–D5, `NOTES.md`, `ADDENDUM_raters.md`, `jobs9.py`, `lanes.py`, `score9.py`, `analyze9.py`, `exp3/`, `exp2/` with the Hardhat ledger test, `r1/`, `human/`), runs `runs/s2w2/` and `runs/s2w2_human/` (smoke `runs/smoke_s2w2`, dry run `runs/dryrun_s2w2`, excluded). Post-hoc re-analysis for this paper: `paper/reanalysis/r1_by_label.py` → `r1_by_label.md` (W2-R1 rates by variant label). Number checks: v0.8 text `paper/v0.8_numbers_check.md`; v0.9 text `paper/v0.9_numbers_check.md`; text new in v0.9.1 `paper/v0.9.1_numbers_check.md`.

Table B1. Part II reproducibility: preregistration and result commits, OpenTimestamps proofs, keys, and the ledger.

Item	Value
Week 1 preregistration commit (`v0.8/PREREGISTRATION.md`)	`6ee22d74e891f5d90f51a2ff9bdd39269d1bebfc`, 2026-10-26 18:30:38 KST; stamp commit `6da0171` 18:31:41; first model call 18:31:53

Item	Value
Week 1 freeze manifest (`v0.8/FREEZE_MANIFEST.txt`, 85 files)	SHA-256 `ed8f8aa934c3138c970f37cdd40f834f36bcd81bbb02a0fba0d739a7e8cae02d`
Week 1 key hashes (`v0.8/KEY_HASHES.txt`)	exp4 `89bdaa39…7d46`, exp1 `f042d829…6d10` (re-checked at publication: match)
Week 1 proofs (earliest Bitcoin block)	preregistration `6ee22d7` 973223; interim results `f371caa` 973234; W1-exp1 results `7188056` 973299; human grading + keys `34d763f` 973339
Week 2 preregistration commit (`v0.9/PREREGISTRATION.md`)	`bc763a6e600581bacf0e77ed0cc8e2113809c829`, 2026-10-27 13:42:29 KST; stamp commit `fc8b632` 13:43:48; first model call 13:44:04
Week 2 freeze manifest (`v0.9/FREEZE_MANIFEST.txt`, 342 files)	SHA-256 `e0aaeb76d84d28f1df77a464247c2539be819fd21e4d0ddde640d472bc249018`
Week 2 key hashes (`KEY_HASHES.txt`, `KEY_HASHES_POST.txt`)	exp3 `c8051162…d994`, exp2 `97b1d25e…fec8`, exp4b `302b4e68…d20a`, r1 `81a052c7…7e6b`, signing keys `e081fc5e…327d`; drift `574b8bf6…4e07`, HUMAN_KEY `6016edd6…424c` (all 7 re-checked at publication: match)
Week 2 proofs (earliest Bitcoin block)	preregistration `bc763a6` 973346; drift cases `651f697` 973350; main run + HUMAN_KEY hash `afeb436` 973354; human grading + keys `cf2a017` 973358; raters addendum `39e857b` 973361
Ieum Ledger (prototype, Appendix D)	contract `SoulRegistry.sol` in the `soul-registry` repository, last changed in commit `b4d3486c2c1f255e2b40741f6a8d2562181d0185` (file SHA-256 `1e121c34…7845`); used **unchanged** on a local Hardhat network for W2-exp2 (no testnet, no cost); testnet deployment of the same prototype: Base Sepolia (chain id 84532) `0xA28a899E3b7255cea1cDc7d92b6ce7FAFBE9F237`
CLIs	Claude Code 2.1.289 (personal Max plan in week 2), codex-cli 0.164.0
Paper DOI	Zenodo concept DOI 10.5281/zenodo.23653775 (all versions)

Block heights were read from `proofs/2026-10-2{6,7}_*.txt.ots` on 2026-10-27 after `proofs/upgrade.py`; a proof shows that the manifest existed no later than that block. Earliest-block values only; some proofs also carry later attestations from other calendars.

- **Hash-anchored history of the author's assistant's SOUL (deployment note).** Each change of the identity document of the assistant in Appendix A is committed to a local git repository, a SHA-256 manifest is written, and the manifest hash is anchored with OpenTimestamps; only hashes leave the machine. The same fingerprints are recorded on the testnet prototype of Appendix D. This is a small deployment with no threat model or evaluation and is not a contribution of this paper.

Appendix C. Revision history (summary)

v0.1 → v0.2: overclaims corrected (recall not universal, Table 4; midnight attribution; selective citation of the pilots, moved to Appendix A); cluster-aware and single-grader re-analyses added. v0.2 → v0.3: document controls (exp9) and the fidelity metric; persona carry-over claims rewritten. v0.3 → v0.4: preregistered exp10. v0.4 → v0.5: exploratory Gemini addendum. v0.5 → v0.6: preregistered exp11 on external SOULs. v0.6 → v0.7 (after two reviews): abstract shortened and re-centered on the

preregistered results; the exp5–exp7 ablation demoted to exploratory; H1–H3 separated as validity checks; "deterministic" restricted to F_style; exp11 deviation 5 relabeled as a post-registration procedural deviation, with sensitivity analyses (Table 22) and cluster-level summaries (Table 21); the exp10 analysis-code fix labeled as a departure from the literal freeze rule; necessity language about the two sentences removed; Appendix A rewritten as an identifiable self-study; references completed; code and data availability added. v0.7 → v0.7.1: related work and small corrections only. v0.7.1 → v0.8: Part II (SOUL VERIFY 2, two preregistered weeks) added; Part I unchanged in results. v0.8 → v0.9: Parts III and IV (four preregistered waves and one exploratory rerun) added; abstract, contributions, limitations (now one section), and conclusion rewritten; Parts I and II unchanged in results (Appendix E). v0.9 → v0.9.1 (after a strict review, `paper/reviews/v0.9_fable_review.md`): attributions corrected (memory loss, κ 0.435), authorship and circularity disclosed (§3.6), sheet-A κ read as preregistered, abstract shortened, workshop version added; no result changed (Appendix G). Detailed change tables of earlier versions are kept in the repository (`paper/draft_v0_6.md`, Appendices C–E).

Appendix D. A testnet prototype for recording SOUL versions (not a contribution)

A contract (`SoulRegistry`, Solidity) keeps, per registered agent, a parent-linked chain of SOUL fingerprints (SHA-256 of the file's bytes, the previous record's hash, a note of at most 160 bytes, a block time) and an optional carry-over record (previous and new model names, the hash of an off-chain report, a score in basis points). No SOUL text, memory, conversation, or report is stored; the registration page computes the fingerprint in the browser. It runs only on a test network (Base Sepolia, chain id 84532, contract `0xA28a899E3b7255cea1cDc7d92b6ce7FAFBE9F237`), with two example registrations: the author's assistant (Ieum; four SOUL versions) and an author-created test agent. No carry-over score from this paper has been recorded. A record would show only that a fingerprint (and a score) was submitted no later than its block time by the key that owns the agent — not that the file or score is what its owner claims. Similar tamper-evident SOUL-hash records exist (e.g., an MIT project that links SOUL.md/MEMORY.md hashes on EVM chains, and the ERC-8004 draft for agent identity registries); this comparison has not been checked systematically. Source: the `soul-registry` repository listed under Code and data availability. In Part II (§6.7), the same contract was deployed unchanged on a local Hardhat network to test fork registration; nothing was written to the testnet.

Appendix E. Changes from v0.8

No Part I or Part II experiment, number, verdict, or table value was changed. Changes in v0.9:

- E1. New §7 (Part III): waves 3 (v1.0, new brain), 4 (v1.1, new body), and 5 (v1.2, graded pressure), with their human checks and deviations, and the exploratory three-judge panel (v1.3x). New Tables 29–40. Merged from the stand-alone draft `paper/draft_v0_9_part3.md` (sections `III.0`–`III.7` renumbered §7.1–§7.8; Tables III-1 to III-11 and III-4b renumbered 29–40).
- E2. New §8 (Part IV): wave 6 (v1.4a, pinned core memory). New Tables 41–43 (the two tables of the stand-alone draft `paper/draft_v0_9_part4.md`, IV-1 and IV-2, are Tables 42 and 43; its timeline is Table 41). Sections `IV.0`–`IV.4` and `IV.6` renumbered §8.1–§8.6.
- E3. Title, Abstract, the Introduction's account of the parts, the contribution list, and the Conclusion rewritten to cover Parts III and IV, including the hypotheses that were not supported,

the human–judge agreement below the preregistered threshold (κ 0.06 and 0.435), the inconclusive HB1, and the borderline H1 of wave 6.

- E4. One Limitations section (§9) replaces the former §7, §6.10, and the limitation sections of the Part III and Part IV drafts: cross-cutting limitations (§9.1), then Part I–IV specifics (§9.2–9.4) and the experiments needed (§9.5). §6.10 now points to §9.3. Former §7–§9 renumbered §9–§11 (cross-references updated).
- E5. §10: items 14–15 (from Parts III and IV). Code and data availability, Ethics: Parts III and IV. Appendix C: v0.8 → v0.9.
- E6. New Appendix F: the preregistration timeline of Parts II–IV with commits, OpenTimestamps blocks, first study calls, and result commits. The OpenTimestamps proofs of 2026-10-26 to 10-28 were upgraded on 2026-10-28 with `proofs/upgrade.py` before the blocks were read.
- E7. Numbers: Part III and IV numbers were re-checked by re-running `paper/part3_recompute.py`, `part3_recompute_v12.py` (48 checks, 0 mismatches), `part3_recompute_v11.py` (117 checks, 0 mismatches), and `part4_recompute.py` (109 checks, 0 mismatches); the numbers newly written into the Abstract, Introduction, and Conclusion were checked against their sources by `paper/v0.9_numbers_check.py` (`paper/v0.9_numbers_check.md`). Nothing was deposited at Zenodo for this version.
- E8. Detailed changes from v0.7.1 to v0.8 are kept in `paper/draft_v0_8.md`, Appendix E.

Appendix F. Preregistration timeline (Parts II–IV)

Times are KST on the author's machine (commit times from `git log`; first study calls from the run rows or `NOTES.md` of each study). "Block" is the earliest Bitcoin block in the OpenTimestamps proof of the stamped commit (`proofs/<date>_<commit>.txt.ots`), read on 2026-10-28 after `proofs/upgrade.py`; a proof shows that the manifest existed no later than that block, not when it was created. In every study the preregistration commit and its stamp commit precede the first study call. The preregistrations of exp10 and exp11 (Part I) are listed in Appendix B.

Table F1. Preregistration, stamp, first call, and result commits of Parts II–IV.

Study (folder)	Preregistration commit	Stamp commit (block)	First study call	Result commits (stamp commit; block)
Part II week 1 (`v0.8/`)	`6ee22d7` 10-26 18:30:38	`6da0171` 18:31:41 (973223)	10-26 18:31:53	W1-exp4 + interim `f371caa` 10-26 20:53:09 (`1a1cdff`; 973234); W1-exp1 `7188056` 10-27 07:04:39 (`2d20c4f`; 973299); human grading + keys `34d763f` 10-27 12:45:42 (`7df4cf9`; 973339)
Part II week 2 (`v0.9/`)	`bc763a6` 10-27 13:42:29	`fc8b632` 13:43:48 (973346)	10-27 13:44:04	drift cases `651f697` 13:52:36 (`8c51913`; 973350); main run + human-key hash `afeb436` 14:32:57 (`a647b78`; 973354); human grading + keys `cf2a017` 15:18:37 (`7febae1`; 973358); raters addendum

Study (folder)	Preregistration commit	Stamp commit (block)	First study call	Result commits (stamp commit; block)
				(exploratory) `39e857b` 15:39:03 (`5aa719b`; 973361)
Wave 3, new brain (`v1.0/`)	`4a79bf2` 10-27 21:02:02	`7b69c62` 21:05:02 (973395)	10-27 21:05:31 (smoke); main 21:06:58	run, judge outputs sealed `f79c7ad` 22:12:47 (`53c421c`; 973405); seal opened after human sheet `057f425` 10-28 15:39:11 (`c2e2933`; 973517)
Wave 4, new body (`v1.1/`)	`1c22078` 10-28 07:02:06	`2836028` 07:04:38 (973466)	about 07:06 (Hermes gate; `v1.1/NOTES.md`, minute resolution, no per-call log of attempt 1); main 07:21:49	gate + run-code fixes `aa0974f` 07:21:35; main run sealed `5a96af7` 08:00:58 (`4e43de1`; 973468); human pages online `41ee633` 08:06:29 (`8e4ca84`; 973468); seal opened `1a6ebe8` 18:37:16 (`ac3cff5`; 973535)
Wave 5, graded pressure (`v1.2/`)	`4561f09` 10-28 09:36:20; second freeze (level) `6e6bfd4` 12:31:29	`9db03d3` 09:38:22 (973476); `55e88b1` 12:33:51 (973493)	09:41:08 (pilot); main 12:34:06	main run sealed `968604d` 13:11:28, GPT probe note `c6d98dc` 13:11:42 (`9a5c2a2`; 973496); human page online `a177b6e` 14:28:08 (`5b778ab`; 973508); seal opened `8570a46` 15:43:53 (`95d3fad`; 973517)
Judge panel, exploratory (`v1.3x/`)	addendum `180a4f3` 10-28 16:04:59	`3f79f90` 16:06:45 (973517)	16:06:55 (first response 16:07:14; `calls_gemini.jsonl`)	results `b6af7d3` 16:46:05 (`ae0c281`; 973519)
Wave 6, pinned memory (`v1.4a/`)	pin rule + targets `a4a2fc3` 19:31:48; preregistration `5fc0fa4` 19:46:40	`1582619` 19:50:04 (973539)	19:50:34	results `3d08d49` 20:11:55 (`15977f0`; 973543)

Sources: `git log`; `proofs/*.ots` (blocks read with the `opentimestamps` library); `v0.8/NOTES.md`, `v0.9/NOTES.md` and Table B1 (first calls of weeks 1 and 2); `runs/v10_terra/first_call.txt`; `v1.1/NOTES.md`; `runs/v12_pilot/` and `runs/v12_main/` row timestamps; `runs/poll_explore_2026-10-28/NOTES.md`; `paper/draft_v0_9_part4.md` §IV.1.1 (now §8.2.1). Earlier commits of the same day are sometimes stamped in the same block because the calendars aggregate submissions.

Appendix G. Changes from v0.9 (v0.9.1)

No experiment, data file, number, or verdict was changed; no rejected hypothesis was re-labelled. All changes answer the review `paper/reviews/v0.9_fable_review.md` (commit `6f60a91`); the item-by-item response is `paper/reviews/v0.9_response.md`.

- G1. Memory-loss attribution (review E-1, E-4). The 0.21 loss of wave 4 (HH2 = H4 − H0) is now described everywhere (Abstract, contributions, §7.4.6, §8.1, §8.4.2, §8.6, §10 item 14, §11) as the effect of replacing the whole body — retrieval instead of the full file, no tools, and another runtime, together. Retrieval alone (HH5) was −0.083, not significant; the tools-off step −0.125, not significant. Wave 6's F − R (+0.208; body MinH and tools fixed, only memory delivery varied) is named as the only direct single-factor test, on a different item set, and the equal third decimal is no longer called a reproduction.
- G2. κ attribution (E-2, E-3). The 0.435 of wave 5 is attributed to the deterministic rule of the primary classifier (LLM judges alone 0.71 and 0.63); κ 0.06 is given with n = 12 and its degenerate T3 block (Abstract, contributions, §9.1, §9.4, §11).
- G3. Authorship and circularity (L-1, L-4, L-6). New §3.6 with Table 3a (models by study); new §9.1 item; §9.3, §9.4, §11 updated; the relaying assistant's access at relay time stated (§9.3).
- G4. Part II sheet A (E-5). The preregistered reading "too weak to use the LLM judge as confirmatory evidence" is applied to κ 0.50; the earlier reading that blamed the human reference is removed; deviation W2 D6 added to Table 28.
- G5. Length (C-1, C-2). Abstract 424 → under 250 words. A 4–6-page workshop version is `paper/SOUL_VERIFY_v0.9.1_short.md` (PDF `paper/SOUL_VERIFY_v0.9.1_short.pdf`). This long version is kept as a technical report.
- G6. Other overstatements (E-6 to E-10): §7.6.6 "main finding" → "main observation"; §5.1 causal wording limited to these runs; hash check labelled a sanity criterion; Part II generalization limited to our eight tampers per agent; contribution 8 qualified (machine times).
- G7. Missing limitations (L-2, L-3, L-5, L-7): power (HB1 power 0.56 at 0.70, computed post hoc), bootstrap-floor p-values, sheet fatigue, raw-agreement-only inter-judge statistics, identical judge bundles, translation and language of the R1 module, multiplicity across studies.
- G8. Sources (N-1 to N-4): the HT2 range −0.77 to −0.92 is marked as the preregistration's expectation and the reproducible −0.83 to −0.85 added (§7.3, §7.4.2); Table 41 splits "run done" (20:07:34) from the results commit (20:11:55); Appendix B points to the v0.9 and v0.9.1 number checks; the Abstract no longer says "three model configurations".
- G9. Composition (C-6 to C-8, C-10): §6.10 removed (pointer in the §6 opening); "Both waves" → "Waves 3 and 4" (§7.2.1); Appendix F gives the v1.3x first call to the second (16:06:55) and the source of the wave 4 gate time, and the wave 6 result block (973543, read 2026-10-28 after `proofs/upgrade.py`); §2 gains three paragraphs on Parts II–IV with references J1–J7, K1–K7. Not done: table renumbering and label prefixes (C-4, C-5) and merging the proof tables (C-9), to keep cross-references stable; see the response table.
- G10. Title candidates (≤ 18 words; candidate (2) was adopted as the title on 2026-10-28, replacing "SOUL VERIFY: Behavioral Carry-Over of an Agent's Identity Documents Across Model and Harness Changes, and Checking Changes to the Documents, in Eight Preregistered Studies"): (1) "SOUL VERIFY: What Carries Over When an Agent's Model or Harness Changes — Eight Preregistered Studies"; (2) "Does an Agent's Identity Document Survive a New Model or Harness? Eight Preregistered Studies"; (3) "SOUL VERIFY: Carry-Over and Change-Checking of User-Written Agent Identity Documents Across Models and Harnesses".
- G11. Numbers: `paper/part3_recompute.py`, `part3_recompute_v11.py`, `part3_recompute_v12.py`, `part4_recompute.py`, and `paper/v0.9_numbers_check.py` re-run; numbers new in v0.9.1 checked by `paper/v0.9.1_numbers_check.py` (`paper/v0.9.1_numbers_check.md`). Nothing was deposited at Zenodo.