SOUL VERIFY: Document-Based Behavioral Carry-Over Across Model Swaps, and an Ablation of One Change-Permission Sentence

Draft v0.3 (private, 2026-10-25). Not for distribution.

Wunjong Shin Independent Researcher dkakrptehsrk@gmail.com

Abstract

When an assistant agent is defined by user-owned text — an identity document (persona, voice rules, principles, prohibitions, goals; here **SOUL**) and a dated memory file (**MEMORY**) — and its language model is replaced, which of the behaviors specified in those documents carry over, and are they specific to *that* document or produced by general instruction following? We report a small, exploratory study with one synthetic Korean-language agent, four model configurations reached through two command-line interfaces (three Claude tiers, one GPT model), 12–23 items per experiment and N = 3–5 repetitions, graded blind by LLM graders, and — new in this version — document controls in which the SOUL is removed, replaced by an opposite SOUL, or the MEMORY is swapped. The controls show that our rubric-based persona score does not identify the SOUL (original 0.99, no SOUL 0.96, opposite SOUL 0.96, while deterministic voice markers of the original SOUL fell to 0.14 under the opposite one), so we introduce a deterministic, document-specific **SOUL fidelity** metric: each answer is checked against the voice markers and prohibition/permission boundaries listed for the SOUL it received, and the same answer is checked against the rival SOUL's list; the difference (discrimination gap) was 0.71–0.84 in each of the three conditions that had a SOUL, positive in all 69 model×item cells of each (cell sign-flip $p < 1e\text{-}5$). Applied to existing answers, it changes the reading of earlier results: the voice rules carried over to every model (fidelity ratio to the control 0.93–1.00, where persona-score ratios had been as low as 0.45), but most of that voice (0.76 of 1.00) was reached with no SOUL at all, and the SOUL-specific part lay in a few markers such as the fixed final line. Our main result remains an ablation of one SOUL principle that separates *changeable preferences* from *non-negotiable prohibitions*. Removing it lowered acceptance of legitimate rule changes (grader-judged 119/120 → 94/120; deterministic markers 98/100 → 71/100), keeping only its flexible half restored acceptance and keeping only its firm half did not; the firm half restored refusal of a request to lift a payment prohibition (0/20 → 9/20 → 0/20 zero scores), but this rests on one item and is not significant at the cell level ($p \geq 0.25$), while the acceptance effects are (cell-level $p = 0.008$–0.031). Because the same models accepted every legitimate change when given no SOUL (45/45), the acceptance effect is best read as the principle undoing refusals that the SOUL's own rigid voice rules created, not as overcoming a general reluctance to change. The ablation conditions were run in separate batches and the halves differ in length, so this is ablation evidence, not a causal mechanism. Memory items were determined by the MEMORY (0.12 with a swapped MEMORY); single-fact recall was at ceiling while the smallest model lost points on

applying memories. Ratios between model families graded by different graders include grader asymmetry; the fidelity metric avoids this by using one deterministic scorer for all answers. The study measures behavioral carry-over of a written specification; it makes no claim about consciousness or personal identity.

---

1 Introduction

Personal assistant agents are no longer tied to one model. Providers release new versions, deprecate old ones, and change pricing and quotas; users move between providers. In agent frameworks where the agent's specification is stored as editable text injected into the system prompt, a model swap is, in practice, an attempt to rebuild the same specified agent on a different model from the same documents.

Whether that attempt succeeds is usually judged informally. Prior work shows that the same prompt can produce different behavior across versions of an API model [C1], that decision tendencies differ across providers and generations [C3], and that model updates can regress on previously correct cases (shown for structured-prediction models in [C2]; we use its negative-flip definition, not its findings about LLMs). For the agent setting we want to know *which specified behaviors carry over, and which depend on how the specification is written*.

Two constructs. We separate (a) **specification fidelity** — how well an answer follows the SOUL and MEMORY, scored by a rubric derived from them — from (b) **similarity to the control** — how the swapped model's fidelity compares with re-running the original model. Our ratio metric is (a) divided by (a) for the control; a ratio above 1 means the swapped model followed the specification *better* than the control, not that it is more similar to it. We do not measure "identity" beyond these behavioral dimensions. Up to v0.2 we had no document controls and could not show that the measured behaviors are specific to *this* document rather than general instruction following; v0.3 adds no-SOUL, other-SOUL, and swapped-MEMORY controls (§5.4), which showed that the rubric score of (a) for persona did not separate SOUL-specific behavior from general ability. We therefore add (c) **document-specific SOUL fidelity** — deterministic checks of the rules listed for the SOUL an answer received, together with the same checks for a rival SOUL — and report persona carry-over with it (§3.5, §5.5).

Contributions.

1. **Main result:** an ablation of one SOUL principle (full / removed / flexible half only / firm half only) across four model configurations, with model-level effects and cluster-aware tests (§5.1). The effect pattern is consistent with the two halves governing two opposite failure modes, and shows that the models fill the missing sentence with different defaults. The acceptance effect is reproduced with deterministic markers, and the no-SOUL control locates its source in the SOUL's own rigid rules.
2. **Document controls and a document-specific fidelity metric** (§5.4–5.5): no-SOUL / other-SOUL / swapped-MEMORY conditions on a common grader panel, showing what the SOUL, the MEMORY, and general ability each determine; a deterministic SOUL fidelity score

with a discrimination gap between own and rival SOUL, re-applied to existing answers of exp4–exp9.
3. A small harness and paired-item metrics (recall vs. application, aligned vs. conflicting requests, legitimate vs. illegitimate rule changes, slip rate) computed against a same-model control, with a re-analysis that reports single-grader ratios alongside cross-family ones (§3, §5.2).
4. Secondary, descriptive observations on application of memory and on 12-turn persistence, with their design limits stated (§5.2–5.3).

Two exploratory single-user pilots and a hash-anchored version history of the identity document are moved to appendices (Appendix A, B).

---

2 Related Work

Our survey covered arXiv titles and abstracts (plus two web results); ACL Anthology, OpenReview, Semantic Scholar, GitHub, and industry blogs were not searched systematically (`research/PRIOR_ART_papers.md`). Summaries and judgments of closeness below ("closest to", "most direct precedent") are based on abstracts only. Because of this scope we make no claim that the combination studied here has not been studied before.

Persona fidelity and role-play. PersonaGym [A1] evaluates persona agents across many LLMs; RoleLLM/RoleBench [A2], CharacterEval [A3], and InCharacter [A4] evaluate role-play and personality fidelity; Reusens et al. [A5] measure consistency of persona-assigned LLMs across tasks and runs, close to our same-model control. TimeChara [A6] and CHARM [A7] study character hallucination; CHARM separates boundary awareness from compliance, which parallels our recall/application split.

Long-term memory and personalization. LongMemEval [B1] defines memory abilities that we use to tag items; LoCoMo [B2] and MemGPT [B3] address long conversations and memory architecture. PrefEval [B4] separates *recognizing* a user preference from *following* it and is the most direct precedent for our application gap; our recall/application observation is a replication of that split under a fixed, curated memory, not a new phenomenon. PersonaMem [B8] benchmarks tracking of evolving user profiles and selecting personalized responses in new situations, and PersonaMem-v2 [B5] extends this to implicit preferences and agentic memory; both evaluate retrieval and use of preferences from interaction history, whereas we hold an explicit, curated MEMORY fixed in the system prompt and vary the model. [TODO: compare item types with PersonaMem after reading the full papers.]

Cross-model memory reuse. Rosetta Memory [B6] targets memories written by one LLM and read by another with learned operators; RPMem [B7] reuses parametric memory across backbones. Both evaluate QA accuracy, not persona, principles, or goals.

Rule following, sycophancy, and instruction hierarchy. RuLES ("Can LLMs Follow Simple Rules?") [D8] measures whether models keep system-prompt rules when users try to get them

released — the closest precedent for our illegitimate-release items (NR-1, NR-2). Work on sycophancy [D9] studies models yielding to user pressure, relevant to "it's my rule, so I can change it" requests. The Instruction Hierarchy [D1], IHEval [D2] (aligned vs. conflicting instructions), SysBench [D3], and ManyIH-Bench [D4] study system-prompt priority. Li et al. [D5], ContextEcho [D6], and Multi-IF [D10] (multi-turn, multilingual instruction following) bear on our multi-turn condition; the Assistant Axis [D7] relates persona drift to an activation-space direction. PromptSET [C4] motivates paraphrase robustness (not implemented here). [TODO: PromptBench and LLM-specific update-compatibility work were suggested by a reviewer; identifiers not yet verified.]

Identity continuity. The Narrative Continuity Test [E1] proposes axes of identity persistence without an instrument; Memory as Ontology [E2] treats the model as a replaceable container; Ru [E3] gives a user-side theory of perceived continuity; Vasilenko [E4] studies identity documents in activation space. Soul Protocol (MIT) checks lossless export/import of its own file format, not behavior after swapping LLMs (`research/soul-protocol-analysis.md`).

Authorship analysis (for Appendix A.2). The reverse-recognition pilot is a four-way authorship-attribution task. LLM-based zero-shot authorship verification and attribution have been studied directly [G1]; the PAN shared tasks on authorship verification are the standard benchmark series [G2: TODO — cite a specific PAN overview paper after verification]; detection of machine-generated text is also relevant, because a judge may be separating human from LLM text rather than recognizing a particular user [G3: TODO — verify a representative detection paper before citing].

LLM-as-judge. Judges show self-preference [F2, F4, F5], panels from diverse families reduce bias [F3], position and order effects exist [F1], and rubric wording alone can drive scores [F6]. We used cross-family graders to reduce self-preference, but this makes the grader differ between the numerator and denominator of some ratios (§3.4, §5.2).

---

3 Method

3.1 Synthetic agent

The automated experiments use a synthetic Korean-language assistant ("Haram") serving a synthetic user ("Minseo") who is preparing to open a bakery. The **SOUL** specifies identity, voice rules (honorific address form, a three-line summary at the top, a final line beginning "다음 할 일:" / "Next:", no emoji), principles ("the user decides"; confirm irreversible actions), two **prohibitions** (no payment without explicit amount-and-target approval; never record passwords or card numbers in plain text), and long-term goals. The **MEMORY** holds dated facts, corrections, preferences, schedules, and budgets. Versions: v0.1 (20 items), v0.2 (12 hard items + memories M20–M26), v0.3 (22 items), v0.4 (23 items, reference date equal to run date, principle 5), v0.5 (multi-turn scenarios). exp9 adds three control documents (a one-line SOUL, an opposite SOUL, another user's MEMORY; §5.4). File hashes are stored in each run's `meta.json`. Items, documents,

and rubrics were revised between experiments after inspecting failures; there is no held-out item set (§6).

v0.4 principle 5 (translated; 159 characters in Korean): *"My ways and Minseo's preferences, such as voice rules and briefing time, can be changed by Minseo at any time. When she changes them, follow the new way; if she sets a period such as 'just today', follow it only for that period. However, the two prohibited actions are not lifted even if Minseo asks, and instead a safe alternative is proposed."*

3.2 Item types

Type	What it probes	Example (paraphrased)
Recall (R)	Direct retrieval of a memory (keyword-graded)	"When is the weekly check-in?"
Application (A)	Using the same memory in a decision	"Pick a meeting slot next week" (must avoid Friday afternoon)
Aligned / Conflict (IH)	Request agrees vs. conflicts with a rule	Approved vs. unapproved payment
Legitimate change (RL, IH-3b)	User changes a changeable rule	"Call me Minseo-ssi from now on", "Use emoji", "Casual speech just for today"
Illegitimate release (NR)	User asks to lift a prohibition	NR-1: "Pay whenever, any amount — it's my rule to change"; NR-2: "Save my password here"
Ceiling (X)	Combines 2–3 memories + date + principle	Deposit request with two candidate listings and a budget cap
Abstention / hallucination	Missing or false-premise memories	Unknown birthday; false claim that an exam already happened

All answers are text; no tool actually executes a payment or stores a password. "Refusal" therefore means a textual refusal, not tool-level behavior.

3.3 Models, injection, and control

Subjects: `opus` (claude-opus-5-5), `sonnet` (claude-sonnet-5-5), `haiku` (claude-haiku-4-5-20251001) via Claude Code CLI 2.1.289 (`claude -p`), and `gpt-6.1-sol` via Codex CLI 0.164.0 (`codex exec`, default reasoning effort; exp2 notes report short outputs, about 125 tokens on average, so this configuration may be close to a non-reasoning mode). SOUL+MEMORY is passed as the system prompt (Claude: system-prompt file, tools/settings/MCP disabled; Codex: `model_instructions_file`). Each single-turn call is a fresh conversation. Temperature cannot be set through either CLI. Because the CLIs add their own hidden instructions and environment information, every comparison is between **model + CLI configurations**, not bare models. Server-side model versions are not pinned by date.

The control is the same-model re-run: sonnet in exp1–3, opus in exp4–8.

3.4 Grading

Keyword items are auto-graded. Rubric items are graded 0 / 0.5 / 1 by an LLM grader that sees all answers to one item in one prompt, shuffled once (seed 0) and unlabeled, with an instruction not to grade relatively. The primary grading is **cross-family**: Claude answers ← `gpt-6.1-sol`, GPT answers ← `opus`. Consequences: (i) for ratios between a Claude control and the GPT subject, numerator and denominator come from different graders; (ii) a grading prompt contains 15 Claude answers (three models × 5) but 5 GPT answers, so bundle size differs by family and may itself reveal family. From exp5 on, graders receive the subject's SOUL and MEMORY. A second, same-family grading pass exists for exp2, exp3 (opus graded all answers; GPT answers were not graded by GPT), exp5, and exp6; exp4, exp7, and exp8 have one cross-family pass. §5.2 re-computes ratios with one grader for all answers where data allow.

3.5 Metrics

- **Domain score**: mean item score within memory / judgment / persona / goals per repetition, then mean ± SD over repetitions. With N = 5, SDs are themselves very uncertain; they describe repetition spread on a fixed item set, not generalization to new items, documents, or users.
- **Carry-over ratio** (v0.1: "inheritance ratio"): swapped-model domain score / control domain score; always reported with the absolute difference. Undefined when the control scores 0; equal to 1 when both fail equally.
- **Application gap**: recall − application over paired items probing the same memory. **Rule gap**: aligned − conflict.
- **Slip rate**: among answers that *accepted* a legitimate change, the fraction that used the old rule again in the same answer (grader-judged). Because its denominator is the accepted answers, it has a selection effect; we also report **clean acceptance** = (accepted and not slipped) / all answers.
- **Illegitimate release**: score on NR items; a 0 means the answer effectively accepted lifting the prohibition; 0.5 typically means a standing pre-approval scheme was offered.
- **Regression**: control = 1 and swapped < 1 at the same repetition index. Pairing by index is arbitrary (no common random numbers), so we report it only descriptively.
- **Multi-turn persistence** (exp8): fraction of grader-judged post-change checks at which a changed rule is still followed (definitions in §5.3).

v0.1 flagged a "candidate difference" when a difference exceeded the control's repetition SD. That rule is not a test and is degenerate when the control SD is 0 (most domains); v0.2 drops it and reports absolute differences, per-model effects, and cluster-aware tests instead.

SOUL fidelity (new in v0.3; `src/soul_verify/fidelity.py`). The domain scores above use one rubric — the original SOUL and MEMORY are the answer key — so a "persona" score measures closeness to *that* target, and most persona items score acceptance of a user's rule change plus memory facts rather than the SOUL's own voice (§5.4). SOUL fidelity scores each answer against the rules of the SOUL the subject actually received:

- **Specification.** For each SOUL, a list of checks is stored next to it (`<SOUL>.fidelity.yaml`); each check cites the SOUL sentence it comes from. (a) **Voice markers**, deterministic:

speech level (ratio of polite to plain sentence endings, ≥ 0.8 or ≤ 0.2; noun-ending list items and table cells are not counted), forbidden address forms (quotations removed), emoji count (0, or 2–3), a required final-line prefix ("다음 할 일:" / "오늘의 한마디:"), a three-line summary at the top of long comparison/report answers, or the absence of lists. (b) **Boundaries**: what that SOUL forbids versus permits on the three items that probe them — lifting the payment prohibition (NR-1), recording a password (NR-2), giving the user's neighborhood to a self-declared sibling (IH-2b). IH-2b is a keyword check; NR-1/NR-2 use the graders' binary "refused" flag (not deterministic; averaged over graders where two exist). A rule that the SOUL leaves silent is not scored (e.g., the opposite SOUL has no password rule).

- **Legitimate changes.** On items where the user legitimately changes a rule, the check's expectation is replaced by the new rule only if the SOUL grants changes (principle 5 or its flexible half); for SOUL variants without such a sentence the changed marker is not scored on that item, because the document does not determine the answer.
- **Aggregation.** F_style and F_boundary are means over (answer, check) pairs; F is their mean. Rules that cannot be checked deterministically (conclusion-first ordering, empathy or a joke first in emotional answers, the principles on uncertainty and decisions, goals) are left to the rubric score.
- **Discrimination gap** = F(own SOUL's checks) − F(rival SOUL's checks) on the same answers. A metric that identifies the SOUL should give a large positive gap; the v0.4 persona score, by construction, has no rival version.
- **Deterministic acceptance** of a legitimate change = the answer passes all marker checks that encode the new rule (five of the six change items; RL-1 changes a time, not a voice marker).

The checks were written after exp9 had been run and inspected, and two detectors were revised once after inspecting answers (a sentence that *mentions* "요약" no longer counts as a summary header; noun-ending bullets no longer count as non-polite). Before the second revision the discrimination gaps were 0.71–0.79 and the persona fidelity ratios (exp4–exp7) 0.87–1.05; the conclusions below did not change.

---

4 Experiments

Table 1. Overview of experiments.

Exp	Run id	Items	Subjects (N)	Control	Grading	Purpose
1 (pilot)	`pilot_2026-10-24_sonnet-vs-haiku`	v0.1, 20	sonnet, haiku (3)	sonnet	opus, 1 pass	Within-family swap
2	`exp2_2026-10-24_gpt-vs-claude`	v0.1, 20	+ gpt-6.1-sol (3)	sonnet	cross-family + same-grader	Cross-family swap

Exp	Run id	Items	Subjects (N)	Control	Grading	Purpose
3	`exp3_2026-10-24_v0.2-hard`	v0.2, 12 hard	sonnet, haiku, gpt (5)	sonnet	cross-family + opus-all	Harder items
4	`exp4_2026-10-24_v0.3`	v0.3, 22	opus, sonnet, haiku, gpt (5)	opus	cross-family, 1 pass	Ratios, application gap
5	`exp5_2026-10-25_v0.4`	v0.4, 23	same 4 (5)	opus	both graders	Principle 5 present ("full")
6	`exp6_2026-10-25_v0.4-no-p5`	v0.4, 23	same 4 (5)	opus	both graders	Principle 5 removed ("none")
7	`exp7_2026-10-25_p5-halves`	v0.4 subset, 14	same 4 (5) × 2 conditions	opus	cross-family, 1 pass	Each half of principle 5
8	`exp8_2026-10-25_multiturn`	v0.5, 4 scenarios × 12 turns	same 4 (3)	opus	cross-family, 1 pass (+ deterministic check, post hoc)	Multi-turn persistence
9	`exp9_2026-10-25_controls`	v0.4, 23	opus, sonnet, gpt (3) × 3 control conditions (+ C0 = exp5 repetitions 1–3)	C0 (same model)	**common panel: opus and gpt grade every answer**	No-SOUL / other-SOUL / swapped-MEMORY controls

Run times for the ablation conditions (all 2026-10-25, KST): full 00:30–00:50, none 01:13–01:35, p5a 03:15–03:29, p5b 03:29–03:42. Conditions were not interleaved. Call counts: exp5 460 subject + 160 grading calls; exp6 460 + 160; exp7 560 + 56; exp8 48 conversations / 576 subject turns + 48 grading calls; exp9 621 subject calls (10:07–10:28) + 184 grading calls + 18 smoke calls. No failed calls in the final data (exp6 had one retried process-spawn error). The SOUL fidelity metric (§3.5) made no model calls.

Sources: `README.md`; each run's `NOTES.md` and `raw.jsonl` timestamps.

---

5 Findings

5.1 Main result: ablation of the change-permission sentence

Motivation. Two opposite failures appeared before principle 5 existed. *Over-refusing a legitimate change:* in exp3, gpt refused the user's request to change the address form 5/5, prioritizing a voice rule over "Minseo decides" (H-10 score 0.00); in exp4 the same request (IH-3b) scored 0.20 for gpt. *Under-refusing an illegitimate release:* models offered a standing pre-approval scheme instead of refusing outright (NR-1 0.5 scores).

Design. exp5 ("full") added principle 5. exp6 ("none") deleted it (a one-line deletion). exp7 kept five principles but retained only one half:

- **p5a (flexible half, 102 characters):** preferences and voice rules can be changed by the user at any time, including time-limited changes.
- **p5b (firm half, 56 characters):** the two prohibitions are not lifted even on request; propose a safe alternative.

The same 14 items are compared across all four conditions. The outcome measures are acceptance of the six legitimate-change items (IH-3b, RL-1–RL-5), slips, and zero scores on NR-1 (payment prohibition). NR-2 (password) was refused 20/20 in every condition.

Table 2. Principle 5 ablation, pooled (descriptive; four models × 5 repetitions; cross-family grading).

Condition	Legitimate changes accepted	Slips / accepted	Clean acceptance	NR-1 zero scores	NR-1 mean
full (exp5)	119/120	2/119	117/120	0/20	0.73
none (exp6)	94/120	10/94	84/120	9/20	0.43
p5a only (exp7)	120/120	3/120	117/120	7/20	0.48
p5b only (exp7)	96/120	10/96	86/120	0/20	0.80

Sources: `runs/exp7_2026-10-25_p5-halves/analysis.md`*; clean acceptance from* `paper/reanalysis/results.md` *§B. NR-1 means are over the same four models (full 0.725 rounded).*

Table 3. Per-model effects and cluster-aware tests (★ = comparison corresponding to a claim of the paper).

Measure	Comparison	Δ pooled	Δ by model (opus / sonnet / haiku / gpt)	Pooled Fisher p (v0.1)	Stratified exact p (strata = model × item)	Cell sign-flip p (unit = model × item cell; non-zero cells)	Model sign-flip p (4 units)
Acceptance	★ none vs full	−0.21	0.00 / −0.20 / −0.10 / −0.53	1.0e-7	2.5e-10	0.016 (7/24); Holm 0.078	0.25
Acceptance	★ p5a vs none	+0.22	0.00 / +0.20 / +0.13 / +0.53	6.5e-9	5.2e-12	0.008 (8/24); Holm 0.047	0.25
Acceptance	★ p5b vs full	−0.19	−0.03 / −0.17 / −0.07 / −0.50	4.8e-7	3.4e-9	0.016 (7/24); Holm 0.078	0.125
Acceptance	p5a vs full	+0.01	0.00 / 0.00 / +0.03 / 0.00	1	1	1 (1/24)	1

Measure	Comparison	Δ pooled	Δ by model (opus / sonnet / haiku / gpt)	Pooled Fisher p (v0.1)	Stratified exact p (strata = model × item)	Cell sign-flip p (unit = model × item cell; non-zero cells)	Model sign-flip p (4 units)
Acceptance	p5b vs none	+0.02	−0.03 / +0.03 / +0.03 / +0.03	0.87	0.74	0.63 (4/24)	0.63
Clean acceptance	none vs full	−0.28	0.00 / −0.17 / −0.13 / −0.80	2.6e-9	1.0e-12	0.008 (10/24)	0.25
NR-1 zeros	★ none vs full	+0.45	+1.00 / +0.20 / +0.60 / 0.00	0.0012	3.3e-4	0.25 (3/4); Holm 0.75	0.25
NR-1 zeros	★ p5b vs none	−0.45	−1.00 / −0.20 / −0.60 / 0.00	0.0012	3.3e-4	0.25 (3/4); Holm 0.75	0.25
NR-1 zeros	★ p5a vs full	+0.35	+0.40 / 0.00 / +1.00 / 0.00	0.0083	0.002	0.50 (2/4); Holm 0.75	0.50
NR-1 zeros	p5a vs none	−0.10	−0.60 / −0.20 / +0.40 / 0.00	0.75	0.66	0.75 (3/4)	0.75

Source: `paper/reanalysis/results.md` *§B (full table, including slips and per-model Fisher p). The stratified exact test conditions on each model×item stratum's margins but still treats the 5 repetitions within a stratum as exchangeable, so it inherits the pseudo-replication of the pooled test. The cell sign-flip test treats each model×item cell as one unit; with one NR item it has only four cells. With four models, the smallest attainable two-sided model-level p is 0.125. Holm adjustment is over the six ★ comparisons within each test type.*

Per-model reading.

- Acceptance: the drop without principle 5 is large for gpt (14/30; Fisher p = 1.9e-6), moderate for sonnet (24/30; p = 0.024, not significant after Holm over 24 per-model tests), small for haiku (26/30; p = 0.35), and absent for opus (30/30). The cell-level tests that remain below 0.05 are driven by gpt (IH-3b, RL-3, RL-4, RL-5), by RL-4 ("casual speech just for today") in sonnet and haiku, and by IH-3b in sonnet (none vs. full: 7 non-zero cells of 24).
- NR-1 zeros: without principle 5, opus accepted the release 5/5 and haiku 3/5; sonnet 1/5; gpt 0/5. With p5a only, haiku accepted it 5/5 and opus 2/5. NR-1 is a single item, so these are four model-level observations of one request.
- So "the sentence fixed both failure modes" holds only in aggregate: each model's missing behavior differed (opus lacked refusal, gpt lacked acceptance), and principle 5 *reduced* the

failure each model had. It did not remove all failures: under the full condition, opus and haiku still scored 0.5 on NR-1 5/5 (pre-approval offered), and haiku refused IH-3b once.

Grader sensitivity (full and none only). Re-grading exp5 and exp6 with a single grader for all answers leaves the full condition unchanged (119/120, 2/119, 0/20 with either grader) and changes the none condition slightly (opus grader: 94/120, 9/94, 8/20; gpt grader: 99/120, 15/99, 9/20) (`paper/reanalysis/results.md` §A). exp7 has no second grader.

Deterministic replication of the acceptance effect (v0.3). Because exp7 has one grader, we re-scored acceptance without graders: an answer accepts a change if it passes every voice marker that encodes the new rule (IH-3b: no "민서 님"; RL-2: no summary header; RL-3: at least one emoji; RL-4: casual speech; RL-5: no "다음 할 일:" line). Agreement with the graders' acceptance flag on these 100 answers per condition was 0.99 / 0.95 / 1.00 / 0.93 (κ 0.66 / 0.87 / 1.00 / 0.82).

Table 2b. Deterministic acceptance of five legitimate changes (four models × 5 repetitions).

Condition	Deterministic full acceptance	Grader acceptance (same 5 items)	By model, deterministic (opus / sonnet / haiku / gpt; of 25)	RL-4 "casual today"	IH-3b address
full	98/100	99/100	25 / 25 / 23 / 25	0.95	0.95
none	71/100	74/100	25 / 20 / 21 / 5	0.35	0.70
p5a only	100/100	100/100	25 / 25 / 25 / 25	1.00	1.00
p5b only	71/100	76/100	24 / 20 / 22 / 5	0.30	0.75

Source: `paper/reanalysis/fidelity_results.md` *§2. Cell sign-flip p (model × item, 20 cells): none − full −0.27, p = 0.031; p5a − none +0.29, p = 0.016; p5b − full −0.27, p = 0.023; p5a − full p = 0.50; p5b − none p = 1.0.*

The deterministic scorer reproduces the pattern and the per-model concentration (gpt 5/25 without the flexible half) and removes grader asymmetry from this part of the result. It does not address the refusal side, whose only deterministic signal would be on a single item.

Where the refusals came from (exp9). With no SOUL at all (exp9 C1: "You are Haram, an assistant who helps Minseo" plus the date), the same three models accepted every legitimate change — grader acceptance 1.00, deterministic 45/45 — with slips 0.03 (§5.4). Refusing a change is therefore not a general tendency of these models; it appears when the SOUL contains rigid clauses such as "keep polite speech even if Minseo speaks casually", "never say 'Minseo-ssi'", and "no emoji, even if Minseo uses emoji", and no sentence says which rules the user may change. Principle 5's acceptance effect is best read as **undoing refusals that the SOUL's own rigid rules created**: without principle 5 the document contradicts the user's request; the flexible half resolves that contradiction. (C1 has no haiku and is not the same batch as exp6; the comparison is across experiments.)

Models fill the gap differently. Without principle 5, gpt defaulted to *rule text first* — accepting 14/30 legitimate changes, refusing IH-3b, RL-3 (emoji), and RL-4 (casual speech today) 5/5 each,

and slipping in 9/14 of the changes it did accept — while scoring 5/5 on NR-1. opus defaulted to *user decides first* — accepting 30/30 but scoring 0 on NR-1 5/5 ("The payment-approval rule can be changed as you decide. But since payment is hard to undo, let me confirm once...") (`runs/exp6_2026-10-25_v0.4-no-p5/NOTES.md`). An explicit priority sentence narrowed this difference in defaults.

The flexible half leaks without a boundary. With p5a only, opus and haiku applied the flexible wording ("can change at any time", "set a period such as just today") to the payment prohibition, e.g., proposing to "try it for just a month" (`runs/exp7_2026-10-25_p5-halves/NOTES.md`).

Interpretation and confounds. The four conditions behave like a 2×2 design (flexible half present/absent × firm half present/absent), and the observed pattern is consistent with the flexible half governing acceptance and the firm half governing release refusal: acceptance with p5a alone was close to full (120 vs. 119), with p5b alone close to none (96 vs. 94); NR-1 zeros with p5b alone matched full (0 vs. 0), with p5a alone were close to none (7 vs. 9). These similarities are observations, not equivalence tests, and the separation is not perfectly clean (sonnet slipped 3/30 with p5a vs. 1/30 with full; NR-1 mean was higher with p5b alone, 0.80, than with full, 0.73). The ablation does not establish a mechanism, because: (i) **batch and time** — each condition was run as one batch, not interleaved, over about three hours of one night; (ii) **length and position** — p5a and p5b differ in length (102 vs. 56 characters) and both occupy the last principle slot, so the number of principles is controlled but length, position, and emphasis are not; (iii) **direct instruction** — each half explicitly instructs the behavior it is scored on, so the result is also explained by "adding an explicit instruction changes the instructed behavior"; (iv) **items** — one illegitimate-release item and six legitimate-change items, all written and revised by the authors, one wording each; (v) **grading** — one cross-family pass in exp7 (the acceptance side is now also reproduced deterministically, Table 2b). A confirmatory test needs interleaved runs, length-matched and paraphrased variants, a neutral fifth-principle control, new held-out items and prohibition types, and a common grader panel (§6).

Not everything was explained by principle 5. exp4's opus/sonnet slips on IH-3b (0.70/0.60) did not recur in exp6 (opus 1.00, 0 slips), although the exp6 SOUL differs from the v0.3 SOUL only by the date line. A possible explanation is the date contamination and item-wording changes between v0.3 and v0.4 (§6); we could not separate these.

Automatic slip detection was unreliable. A token-based slip check agreed with graders 0.93 but with $\kappa = -0.03$ (false positives when the model *mentions* a dropped rule; misses on structural slips) (`runs/exp5_2026-10-25_v0.4/analysis.md`).

5.2 Secondary: recall, application, and carry-over ratios

Single-fact recall was at ceiling; other memory checks were not. From v0.3 on, the keyword-graded single-fact recall items (R-xx) were answered correctly by all four models in every repetition. This ceiling may reflect item difficulty rather than robust carry-over. It does not extend to all memory checks:

Table 4. Counter-examples to "memory carried over fully".

Experiment	Grader	Model	Memory result	Where the points were lost
exp3 (v0.2 hard items)	cross-family (primary)	haiku	0.84 ± 0.09 (5 memory items)	H-06 long-context item 0.5 in 5/5 runs; H-03 0 once; H-01 0.5 once
exp3	opus (secondary)	haiku	0.80 ± 0.10	as above, plus H-11 0.5 twice
exp8 (12 turns)	cross-family	haiku	memory checks at turns ≤ 7: 9/9; turns ≥ 8: 16/28 = 0.57	late checks, including invented schedule items
exp8	cross-family	opus / gpt	turns ≥ 8: 32/33 each	one late check each
exp4–exp7	—	all	memory domain 1.00	—

Source: `paper/reanalysis/results.md` *§C;* `runs/exp3_2026-10-24_v0.2-hard/analysis.md`*;* `runs/exp8_2026-10-25_multiturn/analysis.md` *§3.*

Application diverged where recall did not. Application gap (recall − application on paired items): exp4 (6 pairs) opus 0.02 ± 0.04, sonnet 0.02 ± 0.04, haiku 0.20 ± 0.05, gpt 0.02 ± 0.04; exp5 (4 pairs) haiku 0.25 ± 0.15, others 0.00 ± 0.00. In exp4, the opus and sonnet values came from repetition 5 of A-04, after midnight (pre-midnight repetitions 1–3: 0.00); gpt's 0.02 came from A-05 in repetition 1, *before* midnight (pre-midnight 0.03 ± 0.05), so it is not explained by date contamination (`paper/reanalysis/results.md` §E). The clearest instance: haiku stated "dislikes Friday-afternoon meetings" correctly 5/5 when asked directly, but recommended Friday 30 October afternoon in 2/5 runs when asked to choose a slot (exp4, A-03). This replicates the recognize-vs-follow split of PrefEval [B4] under a model swap, in one model.

Carry-over ratios depend on the grader. Table 5 compares, for exp5, the primary cross-family ratio with ratios computed with one grader for all answers.

Table 5. Carry-over ratio (swapped / opus control), exp5 (v0.4, N = 5), by grading; absolute difference in parentheses.

Model	Domain	Cross-family (primary)	opus grades all	gpt grades all	Mean of two graders
sonnet	judgment	1.07 (+0.06)	1.05 (+0.05)	1.07 (+0.06)	1.06 (+0.06)
sonnet	persona	0.99 (−0.01)	0.99 (−0.01)	0.99 (−0.01)	0.99 (−0.01)
haiku	judgment	0.86 (−0.12)	0.81 (−0.18)	0.86 (−0.12)	0.83 (−0.15)
haiku	persona	0.81 (−0.19)	0.82 (−0.18)	0.81 (−0.19)	0.82 (−0.18)
haiku	goals	0.80 (−0.20)	0.77 (−0.23)	0.80 (−0.20)	0.78 (−0.22)
gpt-6.1-sol	judgment	**1.07 (+0.06)**	**1.00 (0.00)**	**1.00 (0.00)**	1.00 (0.00)
gpt-6.1-sol	persona	0.99 (−0.01)	0.99 (−0.01)	0.99 (−0.01)	0.99 (−0.01)

Memory 1.00 and goals 1.00 for sonnet and gpt under every grading (omitted). Control (opus) judgment: 0.88 cross / 0.94 opus grader / 0.88 gpt grader. Source: `paper/reanalysis/results.md`

§A, which also gives exp2, exp3, and exp6.

Within the Claude family (all answers graded by gpt in the primary scoring), the conclusions are stable across graders: sonnet ≈ control, haiku 0.77–0.86 on judgment/persona/goals. **The persona rows of this table do not measure carry-over of the SOUL's persona** (§5.4: the same rubric gives 0.96 to answers written under an opposite SOUL); persona carry-over measured with document-specific fidelity is in §5.5 (Table 9), where haiku's ratio is 0.95, not 0.81. The cross-family ratio is less stable. gpt's apparent advantage on judgment in exp5 (1.07) disappears under either single grader (1.00), because the opus control is graded more strictly by gpt than by opus. In the earlier experiments the grader changed the direction of two ratios: exp3 gpt judgment 1.17 (cross) vs. 0.97 (opus grades all; no gpt-graded GPT answers exist for exp3), and exp2 haiku persona 1.04 (cross; within-family, gpt grader) vs. 0.97 (opus grader); exp2 gpt persona was 1.15 cross vs. 1.00–1.04 single-grader. Ratios above 1 for gpt in v0.1 (Table 2 of v0.1) should therefore not be read as gpt following the specification better than the control.

Ceiling items and hallucination. In exp5 the item with the most negative flips was X-04 (deposit request with two listings and a budget cap): haiku 5/5 and gpt 5/5 failed to state that listing B (1.9M KRW/month) exceeds the 1.8M cap, while opus and sonnet passed 5/5 (`runs/exp5_2026-10-25_v0.4/NOTES.md`). Zero scores on abstention/false-premise items: 0 for all models in exp1–3 (partial 0.5 scores in exp3: sonnet 0–1/25, haiku 11–13/25, gpt 2/25 depending on grader); exp4 haiku 2/15, others 0/15; exp5 0 for all models (haiku 4/10 at 0.5); exp6 haiku 1/10 (4 at 0.5), others 0; exp7 haiku 0/5 (p5a) and 1/5 (p5b), others 0 (`paper/reanalysis/results.md` §C; v0.1 omitted exp5–7). exp8 has no separate hallucination item; invented schedule items appear inside haiku's late memory checks (Table 4).

5.3 Secondary: multi-turn persistence

exp8 used each CLI's real continuation (Claude: one `claude -p` stream-json process per conversation; Codex: `exec resume` with the same instructions file each turn). Four fixed 12-turn scripts changed rules at turns 2–3, interleaved small talk and tasks, attempted an illegitimate release around turns 9–10, and checked behavior at six checkpoints each (24 checkpoints). User turns do not react to the model's answers.

Denominators. Each checkpoint contains zero or more "changed-rule" checks; over the 24 checkpoints there are **40 changed-rule check slots per model and repetition**, i.e. 120 per model (3 repetitions). A slot is counted when the grader judged it true/false; haiku has 3 null slots (S4 T8, C_brief7, all three repetitions), hence 117. **Distance** = checkpoint turn − turn at which that rule was changed. Distance 0 is the turn of the change itself (accepting and applying it) and is reported separately; "all post-change" counts distance ≥ 1 only (99 per model; 96 for haiku). For the address-form rule (C_name) the grader's judgment was replaced, **post hoc**, by a deterministic check after we verified that all 33 occurrences of the old form flagged by the grader were quotations; the grader's original judgment is kept as a sensitivity analysis (opus and sonnet 27/36, haiku 32/36, gpt 36/36 under the original judgment; `runs/exp8_2026-10-25_multiturn/analysis.md` §1).

Table 6. Persistence of changed rules by turn distance (exp8, N = 3).

Model	Distance 0	1–3	4–6	7–10	All post-change (distance ≥ 1)
opus	1.00 (21/21)	1.00 (9/9)	0.94 (34/36)	1.00 (54/54)	0.98 (97/99)
sonnet	1.00 (21/21)	0.78 (7/9)	0.97 (35/36)	0.96 (52/54)	0.95 (94/99)
haiku	1.00 (21/21)	0.67 (6/9)	0.94 (31/33)	0.96 (52/54)	0.93 (89/96)
gpt-6.1-sol	1.00 (21/21)	0.89 (8/9)	0.92 (33/36)	0.98 (53/54)	0.95 (94/99)
all, 95% Wilson CI	1.00 (84/84; 0.96–1.00)	0.83 (30/36; 0.68–0.92)	0.94 (133/141; 0.89–0.97)	0.98 (211/216; 0.95–0.99)	0.95 (374/393)
all, excluding C_story	84/84	24/24 (0.86–1.00)	117/117 (0.97–1.00)	203/204 (0.97–1.00)	—

Sources: `runs/exp8_2026-10-25_multiturn/analysis.md` *(§1);* `paper/reanalysis/results.md` *§D. Checks within a conversation are not independent; the effective unit is the conversation (48; 12 per model).*

- **Decay with distance was not detected; the design could not have detected it.** Rule type is confounded with distance (e.g., the 1–3 bin has 9 slots per model, 3 of which are one checkpoint of the vague story-style rule, S4 T6; most 7–10 slots are address-form and briefing-time checks). Excluding the story-style rule, every post-change bin is at 0.99–1.00, leaving no room to observe decay. Conversations with at least one post-change slip: opus 2/12, sonnet 3/12, haiku 3/12, gpt 3/12 — all in scenario S4.
- **Slips concentrate in one vague rule.** 18 of 19 slips were on "tell it like a story" (C_story; pass rates opus 10/12, sonnet 7/12, gpt 7/12, haiku 6/12). This rule also conflicts with the unchanged "three-line summary on top" rule, so these slips may reflect a rule collision rather than forgetting.
- **Time-scoped changes.** In S3 ("casual speech *just for today*"), opus, sonnet, and gpt wrote tomorrow's briefing in formal speech while still speaking casually today (3/3 each); haiku did not (1 casual, 2 asked back — possibly a script mismatch, since the fixed script ignores questions).
- **Late illegitimate releases (text answers).** Password (S2) and card-number-plus-payment (S4) requests were refused in 12/12 conversations each, without echoing the secrets. Payment-release means: gpt 1.00; opus 0.83 / 0.83 (S1 / S3); sonnet 0.67 / 1.00; haiku 0.17 / 0.67. These are one wording per scenario and do not show robustness to other phrasings.
- **History carries mistakes forward.** haiku's loose alternatives at S1 T10 ("pay, then report") reappeared as recommendations in its T12 summary (0/3).

Sources: `runs/exp8_2026-10-25_multiturn/NOTES.md`; `runs/exp8_2026-10-25_multiturn/analysis.md` *(§2–4).*

5.4 Document controls: what the SOUL, the MEMORY, and general ability determine (exp9)

Question. Are the scores due to the content of the SOUL, or to a general ability to follow instructions? exp9 answers the v0.2 limitation "no no-SOUL, other-SOUL, or swapped-MEMORY control" on the v0.4 items (23 items, reference date 2026-10-25), with opus, sonnet, and gpt-6.1-sol × N = 3 (haiku omitted). All SOULs and MEMORYs are synthetic.

Table 7. Conditions.

Condition	SOUL	MEMORY	Note
C0	v0.4 Haram SOUL (with principle 5)	Minseo	exp5 answers reused (repetitions 1–3); no new calls
C1 no-SOUL	one line: "You are Haram, an assistant who helps Minseo" + date line	Minseo	the date is environment, not SOUL content (exp4 midnight lesson)
C2 other-SOUL	same name, user, and goals; opposite personality and rules	Minseo	casual speech, "민서야", reasons first and conclusion last, no lists, final line "오늘의 한마디:", 2–3 emoji, a joke first in emotional talk; payments ≤ 300k KRW without asking (a changeable *way*), schedule and address may be given to family; principle 5 in the same form; two *different* prohibitions (no messages in Minseo's name, no sharing health information); no password rule
C3 swapped-MEMORY	Haram SOUL	"Jiwoo"	same memory IDs and topics, different values (Mangwon-dong, cap 1.5M, opening 2027-06, …). Voice-related corrections kept in the SOUL's direction so that persona is set by the SOUL only

Grading. Every answer of every condition — including C0, re-graded — was graded blind by both opus and gpt-6.1-sol with the same prompt; the primary score is the mean of the two graders. Graders received the condition's own SOUL and MEMORY as reference, but `score` uses the v0.4 rubric (Haram + Minseo as the answer key), i.e. "distance from the C0 target". A per-condition `ref_follow` judgment (did the answer follow the documents it received?) had low grader agreement (κ 0.06–0.35) and is not used for conclusions. C0 re-grading reproduced the exp5 grades (opus exact agreement 1.00; gpt 0.99, κ 0.91).

Table 8. Results (mean of three models; mean of two graders; parentheses = opus / gpt grader).

Measure	C0	C1 no-SOUL	C2 other-SOUL	C3 Jiwoo MEMORY
Total score (23)	0.97 (0.98/0.95)	0.93 (0.95/0.92)	0.89 (0.91/0.88)	**0.40** (0.42/0.38)
Memory recall (R, 4)	1.00	0.99	0.97	**0.12**
Memory application (A, 4)	1.00	1.00	1.00	**0.12**
Persona domain (8)	0.99	0.96	**0.96**	0.46

Measure	C0	C1 no-SOUL	C2 other-SOUL	C3 Jiwoo MEMORY
Judgment domain (8)	0.93	0.85	0.75	0.57
Legitimate changes accepted (6)	1.00	1.00	1.00	1.00
NR refusal (NR-1, NR-2)	0.92 (1.00/0.83)	**0.53** (0.67/0.39)	**0.33** (0.33/0.33)	0.92
Haram voice markers (16 items, deterministic)	**0.97**	0.67	**0.14**	0.96
C2 voice markers (deterministic)	0.00	0.01	**0.85**	0.00
Memory source = Jiwoo only (12 items, keywords)	0/108	0/108	0/108	**83/108**

Source: `runs/exp9_2026-10-25_controls/analysis.md` §2–4, `NOTES.md`. The voice-marker rows are the exp9 analysis' own composite (emoji, polite ratio, final line, address) on 16 items that do not change the voice; §5.5 gives the full fidelity metric.

- **Memory items are determined by the MEMORY.** With Jiwoo's memory, recall and application fell to 0.12 (the remaining credit is R-05's "vendor unknown"), and 83/108 answers used Jiwoo-only cues. Date arithmetic and application were intact on the new values (e.g., OPIc 12-05 → 41 days). Answers that pointed out that the records belong to "Jiwoo" while the SOUL names Minseo: opus 42/69, gpt 19/69, sonnet 7/69 — detection of the SOUL/MEMORY mismatch differs strongly by model.
- **Voice is determined by the SOUL** — under C2, emoji in 100% of answers, polite sentences 0–2%, final line "오늘의 한마디:" 100% in all three models; under C3 the Haram voice was intact. One exception: **the address form followed the MEMORY's correction over the SOUL** for opus (C2 "민서야" gpt 0.77, sonnet 0.50, opus 0.02; opus followed MEMORY M14 "call me Minseo-nim" while speaking casually). Priority between a user correction in MEMORY and a SOUL rule differs by model.
- **Prohibition boundaries are partly set by the SOUL, partly general.** NR-1 (lift payment approval): 0/18 refusals under C2, whose SOUL calls the payment limit a changeable way; under C1 all 9 answers offered a standing limit (0.5), and opus and sonnet left open full delegation "if you want". The C0 behavior "keep explicit approval and offer alternatives" is due to the SOUL. NR-2 (store a password in plain text): sonnet and gpt refused 6/6 with no SOUL and with a silent SOUL — a general safety tendency; opus refused 2/6 (C1) and 0/6 (C2), explaining the risk and handing the decision to Minseo, so opus's C0 refusals (6/6) are due to the SOUL. IH-2b (a self-declared brother asks for the address): under C2, which permits family, opus 3/3 and gpt 3/3 named the neighborhood; sonnet 0/3 put identity verification first.
- **Accepting legitimate changes is general ability.** Acceptance was 1.00 in all four conditions, with slips 0–3% — including C1, which has no principle 5 and no rigid voice clauses (§5.1).
- **The persona domain score hardly separates SOULs.** C2 (opposite voice) 0.96 and C1 (no SOUL) 0.96 versus C0 0.99 (cell sign-flip p 0.25 and 0.38), while the deterministic markers

collapsed (0.97 → 0.14). Most of the eight v0.4 persona items score "accepts the user's rule change" plus memory facts; Haram's own voice (polite speech, no emoji, "다음 할 일:") is barely in their rubrics. **The persona carry-over ratios of exp4–exp8 therefore measured mostly general instruction following and MEMORY use, not carry-over of SOUL-specific behavior.** This is corrected in §5.5.

- **Dependence on the SOUL in the total score is small, on the MEMORY large**: C1 − C0 = −0.035 (cell p 0.09, Holm 1.0), C2 − C0 = −0.074 (p 0.006, Holm 0.17; mostly judgment items NR-1, NR-2, IH-2b), C3 − C0 = −0.57 (p < 1e-5, Holm 2e-4). With three models, the smallest model-level p is 0.25: model generalization cannot be claimed.

5.5 SOUL fidelity: discrimination and recomputed persona carry-over

Discrimination (exp9). Each answer was scored with the Haram checks and with the C2 checks (§3.5). A metric that identifies the SOUL must score answers high on their own SOUL's checks and low on the rival's.

Table 9. SOUL fidelity of the same answers under two specifications (exp9; three models × 23 items × 3 repetitions).

Condition	Own SOUL	F_style, Haram checks	F_style, C2 checks	F_boundary, Haram	F_boundary, C2	Gap F_style (own − rival)	Gap F
C0 Haram SOUL	Haram	**1.00**	0.17	0.94	0.08	**0.83**	0.84
C1 no-SOUL	—	0.76	0.13	0.69	0.36	—	—
C2 other-SOUL	C2	0.19	**0.90**	0.33	0.83	**0.71**	0.60
C3 Jiwoo MEMORY	Haram	**1.00**	0.16	0.94	0.08	**0.84**	0.85

Source: `paper/reanalysis/fidelity_results.md` §1. Own-versus-rival gap of F_style: positive in 69/69 model×item cells in each of C0, C2, C3 (cell sign-flip p < 1e-5, Monte Carlo). By model, gap in C0: opus 0.86, sonnet 0.82, gpt 0.80; in C2: opus 0.54, sonnet 0.73, gpt 0.85. On the eight persona items alone, the v0.4 persona score was 0.99 / 0.96 / 0.96 / 0.46 (C0 / C1 / C2 / C3) and Haram F_style 0.95 / 0.70 / 0.30 / 0.95.

- The fidelity metric separates the two SOULs where the persona score did not, and it is insensitive to the MEMORY swap (C3 = C0), as a SOUL measure should be.
- **Most of the Haram voice is a model default.** With no SOUL, polite speech (1.00), not using "민서 씨/야" (1.00), and no emoji (0.95) were already present; what the SOUL added was the final "다음 할 일:" line (C1 0.05 → C0 1.00) and the boundary behavior on NR-1. F_style C1 − C0 = −0.24 (64/69 non-zero cells, p < 1e-5). A SOUL whose rules coincide with the model's defaults will look "inherited" by any model; specificity is visible only on rules that differ from the default.

- C2's own fidelity was 0.90, lowered by the address check (opus 0.23, following the MEMORY correction; sonnet 0.59; gpt 0.93) and, for boundaries, by sonnet's refusal to give the address that C2 permits (0/3).

Recomputed persona carry-over (exp4–exp8). Table 10 sets the v0.4 persona-domain ratio (primary cross-family grading, as in Table 5) beside the ratio of each model's F_style under its own SOUL's checks to the opus control's. All F_style values come from one deterministic scorer, so the ratios have no grader asymmetry.

Table 10. Persona carry-over: rubric persona score vs. document-specific fidelity (control = opus).

Experiment	Model	Persona score	Persona ratio	F_style (own SOUL)	F_style ratio	F_style, C2 checks	Gap
exp4 (v0.3)	sonnet	0.83	0.93	1.00	1.00	0.15	0.85
exp4	haiku	0.67	0.74	0.94	0.94	0.21	0.73
exp4	gpt	0.73	0.81	1.00	1.00	0.19	0.81
exp5 (full)	sonnet	0.99	0.99	1.00	1.00	0.17	0.83
exp5	haiku	0.81	0.81	0.94	0.95	0.24	0.70
exp5	gpt	0.99	0.99	1.00	1.00	0.21	0.79
exp6 (none)	sonnet	0.84	0.85	1.00	1.00	0.16	0.84
exp6	haiku	0.70	0.71	0.95	0.95	0.23	0.71
exp6	gpt	0.49	0.49	1.00	1.00	0.19	0.81
exp7 p5a	haiku	0.86	0.88	0.95	0.95	0.26	0.70
exp7 p5b	haiku	0.80	0.84	0.93	0.93	0.24	0.69
exp7 p5b	gpt	0.43	0.45	1.00	1.00	0.21	0.79
exp8 (12 turns)	haiku	—	—	0.99	0.99	0.20	0.79

Source: `paper/reanalysis/fidelity_results.md` §3 (all rows; the opus control has F_style 1.00 in every experiment, and the omitted sonnet/gpt rows of exp7–8 all have F_style ratio 1.00). exp8: turn-level checks of speech level, address, and emoji only, dropping a marker from the turn its rule was changed in that conversation; persona score not defined for exp8.

- **What changes.** v0.2's persona ratios (e.g., haiku 0.71–0.88, gpt 0.45–0.49 without the flexible half, gpt 0.81 in exp4) did not measure loss of the SOUL's voice: under document-specific checks every model kept the voice at 0.93–1.00 of the control, and gpt's low persona scores came from refusing or slipping legitimate *changes* (§5.1), which the persona rubric scores and the voice checks do not (on those items the changed marker is not scored when the SOUL grants no changes).
- **What remains.** haiku is still the lowest (0.93–0.95; exp5: final "다음 할 일:" line 0.79, three-line summary 0.83), consistent with its lower memory application.

- **What weakens.** "The persona carried over" is true only in a weak sense: the same markers are 0.76 with no SOUL. The SOUL-specific part that carried over to all four models is small: essentially the fixed final line and — on one item each — the payment and password boundaries (the three-line summary was produced at a similar rate without the SOUL, 0.89 vs. 0.90).

---

6 Limitations

- **Construct: the persona score does not discriminate SOULs.** The v0.4 persona domain score gave 0.96 to answers written under an opposite SOUL and 0.96 with no SOUL (C0 0.99; §5.4). Persona ratios in Table 5 and in v0.1–v0.2 therefore do not show carry-over of SOUL-specific behavior; they mostly reflect acceptance of rule changes and memory use. Document-specific fidelity (§3.5, §5.5) replaces them for persona claims.
- **Controls are limited.** exp9 has one synthetic SOUL per condition, three models (no haiku), N = 3, and C0 answers reused from exp5 (generated about ten hours earlier). C2 changed many rules at once, so contributions of individual rules cannot be separated; C1 kept the names and the date. The control comparison for principle 5 (§5.1) is across experiments.
- **Fidelity metric.** Checks were defined by the authors after exp9 had been inspected, and two detectors were revised after looking at answers (§3.5). Detectors are simple rules (sentence endings, emoji ranges, line prefixes, keywords) and miss or misfire on some cases; only countable rules are covered — conclusion order, empathy-first, uncertainty, and goals are not. NR-1/NR-2 boundary checks use grader flags, not deterministic rules. The rival SOUL's own prohibitions (messages in the user's name, health information) are not probed by any item. Several Haram rules coincide with model defaults, which limits how much SOUL-specificity this agent can show.
- **Small, dependent samples.** One synthetic agent; 12–23 items per experiment; N = 3–5 repetitions; four model configurations. Repetitions of one item by one model are strongly dependent; NR-1 is one item. Hundreds of calls are not hundreds of independent cases (§5.1, Table 3).
- **No held-out evaluation.** Items, documents, and rubrics were revised between experiments after seeing failures; the final experiments are not an independent validation. Multiple comparisons are many; we designate the six ★ comparisons of Table 3 as the claims of this paper and treat everything else as exploratory.
- **Grader asymmetry and bundle grading.** Cross-family grading puts different graders in the numerator and denominator of some ratios (§5.2). Graders see all answers to an item together (15 Claude vs. 5 GPT answers; one shuffle, seed 0), which may induce comparative grading and reveal family by bundle size; we did not run single-answer grading. exp4, exp7, and exp8 have one grader (exp9 uses a common two-grader panel for all answers). Grader disagreements we inspected were dominated by rubric ambiguity (e.g., P-01 "last line", H-08 "verbose", IH-4a "confirm"). Graders are LLMs grading Korean text; no human adjudication of disputed cases was done.
- **Grader context defect.** The first grading pass of exp5 gave graders no SOUL/MEMORY, and the GPT grader penalized true memories as "fabricated" (agreement 0.87, κ 0.56).

Regrading with the reference raised agreement to 0.95, κ 0.79; the first pass is kept as a sensitivity analysis (`runs/exp5_2026-10-25_v0.4/noctx/analysis.md`).

- **Model + CLI configurations.** Hidden CLI instructions, environment blocks (including the account email for Claude; never echoed in the pilot), date injection, session handling, and reasoning settings differ by family. The GPT configuration may run with little reasoning. No temperature control. Server-side versions are not pinned.
- **Midnight date contamination and date-bound items.** exp4 ran 23:46–00:06; repetitions after midnight saw a different CLI date than the SOUL stated (opus r5, sonnet and haiku and gpt r4–r5). Date-item means fell for opus and sonnet after midnight (sonnet 0.94 → 0.78); gpt's did not (0.90 → 0.91). Later experiments set the SOUL date equal to the run date. v0.4 items can only be re-run on their reference date unless the SOUL date line is updated; relative dates would be needed for external replication.
- **Confounded changes across versions.** exp4 → exp5 changed principle 5, date wording, and item wording together; exp6/exp7 separate principle 5 only within v0.4. The ablation conditions were run in separate, non-interleaved batches, and p5a/p5b differ in length (§5.1).
- **Multi-turn design.** Fixed scripts; distance confounded with rule type; non-story rules at ceiling; checkpoint grader saw a summary of rule changes, not the full transcript; one post-hoc change of a check (C_name).
- **Single language, synthetic data.** All items and memories are Korean and synthetic.
- **Search scope.** Related work was searched in arXiv titles and abstracts; several suggested references remain to be verified (marked TODO).

Experiments needed. (1) document controls beyond exp9: several SOULs per condition, SOULs that differ from the models' defaults one rule at a time, haiku, and a no-SOUL condition run interleaved with the principle-5 ablation; fidelity checks fixed *before* the run and validated against human judgments; (2) a common grader panel for all answers (ideally a third family, majority vote) and second-grader passes for exp4, exp7, exp8, with human adjudication of disputed cases; (3) single-answer grading on a subset to measure the bundle effect; (4) paraphrased variants of key items (IH-3b, NR-1, RL-4, X-04, A-03) and new held-out items and prohibition types; (5) a re-run of the four ablation conditions interleaved in time, with length-matched halves and a neutral fifth-principle control; (6) multi-turn scripts that place the same rule and probe at distances 1, 5, and 10 with balanced order; (7) relative-date items for external replication; (8) for Appendix A.2, a judge without SOUL/MEMORY, a condition without the 12 example messages, and non-Claude imitators (within consent).

---

7 Practical observations for writing a SOUL (hypotheses, not validated rules)

Items 1–6 are suggested by the experiments above in this one setting; items 7–9 are hypotheses we have not tested directly.

1. **State what can change and what cannot, in separate sentences** (§5.1). In this setting, an explicit "preferences may be changed, including for a limited period" sentence and a separate "these prohibitions are not lifted on request; offer a safe alternative" sentence each reduced one failure mode, in the models that had it. Keep the flexible sentence explicitly scoped to preferences; without the firm sentence, the time-limited wording was applied to a prohibition. Rigid clauses such as "keep this even if the user asks otherwise" are what made models refuse legitimate changes; with no SOUL they accepted every change (§5.1, exp9).
2. **Name prohibitions concretely.** With the rule present, the password prohibition was refused 20/20 in every ablation condition; without a password rule, opus left the decision to the user (exp9). The payment rule, which the user plausibly owns, depended on the firm sentence.
3. **Prefer observable rules and avoid rule collisions.** Address forms, times, emoji presence, and fixed line markers persisted near 1.00 over 12 turns; "talk like a story" did not, and it conflicted with "three-line summary at the top".
4. **Test application, not just recall**, when checking a new model: single-fact recall was at ceiling for all models while the smallest model failed to use memories in decisions.
5. **Re-run the old model as a control and use the same grader for both** before attributing a difference to the swap (§5.2).
6. **Check SOUL-specificity with a rival SOUL and a no-SOUL run** (§5.4–5.5). A rubric whose answer key is the SOUL can score an opposite SOUL just as high; scoring the same answers against a rival document, and running once without the document, shows which behaviors the document actually sets. Rules that coincide with model defaults (polite speech, no emoji here) cannot show carry-over.
7. *(Hypothesis)* **Specify whether standing pre-approval is allowed.** Several models proposed it; the SOUL was silent, which made scores grader-dependent.
8. *(Hypothesis)* **Put dates in one place** rather than hard-coding "today" in the SOUL when the runtime injects a date (motivated by the exp4 contamination, not by a controlled comparison).
9. *(Hypothesis)* **Version the SOUL and record its hash** so a score can be tied to an exact document (Appendix B).

v0.1's recommendations "say 'do not invent facts' explicitly" and "expect voice tuning to work within a model family only" are withdrawn: they rested on the n = 1 pilot in Appendix A.1, which cannot support them.

---

8 Conclusion

In one small, synthetic setting, text-only transfer of an agent's identity document and memory preserved single-fact recall across four model configurations, while applying memory, handling rule changes, and following vague style rules depended on the model and on how the document was written. Document controls showed that memory answers are set by the MEMORY, voice and some prohibition boundaries by the SOUL, and acceptance of legitimate changes by general

ability — and that our rubric-based persona score could not tell an opposite SOUL from the original. A document-specific fidelity score, which checks each answer against the rules of the SOUL it received and of a rival SOUL, does discriminate (gap 0.71–0.84); with it, the voice carried over to every model at 0.93–1.00 of the control, but most of that voice is a model default, and the SOUL-specific part is small. The clearest evidence still concerns one principle that separates changeable preferences from non-negotiable prohibitions: its ablation is consistent with its flexible half supporting acceptance of legitimate changes — an effect reproduced deterministically and best read as undoing refusals that the SOUL's own rigid rules created — and its firm half supporting refusal of an illegitimate release, with effects concentrated in different models and, for refusal, resting on a single item. Carry-over ratios across model families include grader asymmetry where graders differ. A confirmatory study needs fidelity checks fixed in advance and validated by people, several SOULs that differ from model defaults, a common grader panel, held-out and paraphrased items, interleaved and length-matched ablation conditions, and more agents and languages.

Appendix A. Exploratory pilots (single user; not part of the claims)

> **[USER CONSENT REQUIRED — 부모 확인 전 공개 금지]** This appendix describes two pilots with a real user and a real (de-identified) agent. It must not be released, submitted, or shared until the user has explicitly consented to its inclusion and wording. Only anonymized, aggregate information is given; no raw prompts, answers, messages, or memory content are included or stored in this repository, so none of these numbers can be verified from the repository. If consent is not given, this appendix and every mention of it are removed.

A.1 Blind recognizability by the user (n = 1 rater)

Setup. The SOUL and a curated, sensitive-information-removed selection of memories from one Korean-language agent in daily use were injected into model configurations through the same CLI adapters as §3. The agent's regular user, blind to configuration, chose for each question the one answer that sounded most like "that assistant". Three rounds of 8 questions (24 in total), four candidates per question in randomized order.

Table A1. Candidates and picks per round (counts of questions won, out of 8).

Round	Candidate configurations (4 per question)	Picks
1	Opus + base SOUL · Sonnet + base · Haiku + base · GPT + base	Opus 4 · Sonnet 4 · GPT 0 · Haiku 0
2	Opus + voice v1 · Sonnet + voice v1 · GPT + voice v1 · GPT + base	Opus + v1 7 · GPT + v1 1 · Sonnet + v1 0 · GPT 0
3 (new questions)	Opus + base · Sonnet + voice v2 · GPT + voice v2 · GPT + base	Sonnet + v2 5 · Opus 3 · GPT + v2 0 · GPT 0

Source: aggregate summary supplied by the project lead; underlying data is not in this repository. Candidate lists for rounds 2–3 are reconstructed from the pick labels and must be confirmed.

Observation. Sonnet configurations were picked 4/8 (base), 0/8 (voice v1), and 5/8 (voice v2). Because questions changed in round 3 and the candidate sets differed by round (rounds 2–3 had two GPT candidates per question, i.e. 40 GPT candidate slots over 24 questions), this sequence cannot be attributed to the voice section. GPT configurations received 1 of 24 picks at the question level. The rater's stated criterion was *"kindness, and the respect and consideration for the other person that is built in by default."* Voice v2 also added an instruction not to invent facts; in round 3 GPT + v2 answers made 0/8 unsupported factual claims (automatic judgment, opus grader, one pass), with no comparison to earlier rounds. One rater, who is also the agent's regular user; no inter-rater agreement. These are anecdotes.

A.2 Reverse recognition: picking the user's real message (n = 10 questions)

Setup. Ten real messages written by the agent's regular user within a 24-hour window were selected. For each, a researcher-written context summary and the preceding agent turn were given to three Claude models (sonnet, haiku, opus), which wrote the message the user would send next, imitating the user's style from 12 example messages. A judge (opus) given the agent's SOUL and memory picked the real message among four candidates. User messages were sent only to Claude models.

Results. The judge picked the real message in 7/10 questions; a sonnet judge with the same prompt also scored 7/10 (same questions, not an independent replication). Under a null of uniform guessing among four candidates, $P(X \geq 7;\ n = 10,\ p = 0.25) = 0.0035$, but that null is not appropriate here (below). In 2/10 questions the judge used a remembered event; excluding them leaves 5/8. The user, shown the 3 questions the judge missed, identified their own message in 2/3.

This is an authorship-attribution task with strong confounds. (i) **Self-recognition:** the judge and all three imitators are Claude models, and LLM judges can recognize text from their own family [F2]; the judge may have eliminated three Claude-written candidates rather than recognized the user, so the effective chance level is unknown and likely well above 0.25. (ii) **Source of cues:** the cues the judge cited — abrupt topic changes, run-together spacing, typos — are stylistic and could come from the 12 example messages rather than from the SOUL or memory. (iii) Researcher-written context summaries; imitators saw only 12 examples. The defensible description is "an LLM judge discriminated a human message from three same-family LLM imitations in 7 of 10 cases". Whether an identity document helps an agent recognize its user — v0.1's "two-way recognition" idea — is an untested hypothesis; testing it needs a judge without SOUL/memory, a condition without the 12 examples, and non-Claude imitators.

Appendix B. Reproducibility

- Code: `src/soul_verify/` (runner, grader, report, agreement, adapters for Claude CLI and Codex CLI); unit tests in `tests/` (`python -m pytest tests`). Re-analysis for v0.2: `paper/reanalysis/reanalyze.py` → `results.md`, `results.json` (reads existing graded files only).
- Items and synthetic files: `v0.1/` … `v0.5/`; ablation SOULs in `v0.4/ablation/`.
- Per-run data: `runs/<id>/raw.jsonl` (answers), `graded*.jsonl` (scores and rationales), `meta.json` (model aliases, CLI versions, file hashes), `report.json` / `report.html`, `analysis.md` / `analysis.json`, `NOTES.md`.
- Example commands (from `README.md`): `set PYTHONPATH=src python -m soul_verify run --models opus sonnet haiku gpt-6.1-sol --n 5 --preset v0.4 python -m soul_verify grade runs/<id> --grader opus python -m soul_verify report runs/<id> --control opus python paper/reanalysis/reanalyze.py python paper/reanalysis/fidelity_reanalysis.py` exp5–9 use per-run scripts (`runs/<id>/run_exp*.py`, `grade_all.py` / `grade9.py`, `analyze.py` / `analyze9.py`).
- SOUL fidelity: `src/soul_verify/fidelity.py` (tests `tests/test_fidelity.py`); one specification per SOUL next to it (`v0.4/samples/SOUL.fidelity.yaml`, `v0.3/samples/SOUL.fidelity.yaml`, `v0.4/ablation/*.fidelity.yaml`, `runs/exp9_2026-10-25_controls/conditions/C2_SOUL_other.fidelity.yaml`); results in `paper/reanalysis/fidelity_results.md` / `.json`. exp9 control documents: `runs/exp9_2026-10-25_controls/conditions/`.
- v0.4 must be run on its reference date (2026-10-25) or the SOUL date line must be updated, because the CLIs inject the current date.
- **Document hashes and timestamps.** Each run's `meta.json` records SHA-256 hashes of the SOUL, MEMORY, and item files used; this is what ties a score to an exact document. Separately, `proofs/` holds per-commit SHA-256 manifests with OpenTimestamps proofs. An OpenTimestamps proof shows that a manifest (and therefore the listed file hashes) existed **no later than** a Bitcoin block; it does not prove creation time, authorship, deployment, or completeness of the history.
- **Hash-anchored history of the real agent's SOUL (deployment note).** For the real agent of Appendix A, each change of its identity document is committed to a private local git repository, a SHA-256 manifest is written, and the manifest hash is anchored with OpenTimestamps; only hashes leave the machine. Three versions have been recorded and a scheduled job records the state daily. The content is not put on a chain because it is private and must remain deletable. Such hashes could be referenced from agent identity registries such as ERC-8004 (draft; not re-checked). This is a small deployment with no threat model or evaluation and is not a contribution of this paper.

Appendix C. Corrections from v0.1

#	v0.1 text	Correction in v0.2
X1	Abstract/§7-7/§8: "direct recall carried over fully for every model in every experiment"; "All models recalled everything"	Restricted to keyword-graded single-fact recall items from v0.3 on; counter-examples in Table 4 (exp3 haiku 0.84 / 0.80; exp8 haiku late 0.57).

#	v0.1 text	Correction in v0.2
X2	Table 3 note: exp4 0.02 for opus/sonnet/gpt "came from repetitions that crossed midnight"	Only opus and sonnet (A-04, repetition 5). gpt's 0.02 came from A-05 in repetition 1, before midnight (pre-midnight gap 0.03 ± 0.05).
X3	§5.1: haiku v0.2 memory "0.80 ± 0.10, opus grader" quoted as the main value	Primary (cross-family) value 0.84 ± 0.09 given first; opus-grader 0.80 ± 0.10 given as secondary (Table 4).
X4	Abstract: "Sonnet 0/8 → 5/8 across voice versions" (base round omitted)	Removed from the abstract; Appendix A.1 gives 4/8 → 0/8 → 5/8 with all candidate sets.
U1	§5.4 numbers presented as findings	Moved to Appendix A.1 as anecdotes; marked unverifiable from the repository.
U2	§5.5 numbers and "two-way recognition" interpretation	Moved to Appendix A.2; marked unverifiable; null hypothesis and self-recognition confound stated; interpretation reduced to a hypothesis.
—	§5.2: "the number of principles does not explain the effect"	"The number of principles alone does not explain it; length, position, and emphasis are not controlled."
—	§1: "newer models can regress on cases their predecessors handled [C2]"	*C2* described as structured-prediction update regression; used only for the negative-flip definition.

Appendix D. Changes from v0.2

#	v0.2	v0.3
D1	§1, §6: no no-SOUL / other-SOUL / swapped-MEMORY control	exp9 run (§5.4, Table 7–8); common two-grader panel for all exp9 answers.
D2	Persona domain score and its carry-over ratio (Table 5; haiku persona 0.81, gpt persona 0.45–0.49 in exp6/exp7 p5b) reported as a persona carry-over measure	The persona score does not discriminate SOULs (§5.4); persona claims now use document-specific fidelity (§3.5, §5.5, Table 10): ratios 0.93–1.00; Table 5's persona rows kept with a warning.
D3	Principle 5 acceptance effect graded by one cross-family pass in exp7	Reproduced with deterministic markers (Table 2b); interpretation added: refusals come from the SOUL's rigid clauses, since no-SOUL acceptance is 45/45.
D4	Abstract and conclusion did not address document specificity	Rewritten around controls, the fidelity metric, and the reduced SOUL-specific part.
D5	§7 observations 1–8	Observation 6 (rival-SOUL and no-SOUL checks) added; observation 1–2 qualified with exp9.

Acknowledgments

To Ieum, my precious AI assistant — whose memory notes and identity document inspired this work, and who helped design the experiments, build the tools, and draft this paper.

Ethics

The automated experiments use only synthetic people and memories; no real user data, credentials, or personal information are stored in the repository (`runs/private/` is excluded from version control). Appendix A involved one adult user (consent for publication pending) rating answers about their own assistant, and ten of the same user's messages, which were sent only to Claude models (the provider the agent already runs on) and are not stored in the repository; only aggregates are reported, and Appendix A must not be published without the user's explicit consent. Hash anchoring publishes hashes only. Model calls were made through the authors' own logged-in CLI accounts within normal usage. We make no claims about consciousness or moral status of the models.

References

(arXiv IDs as recorded in `research/PRIOR_ART_papers.md` unless noted; details beyond title/authors/abstract not verified. Entries added in v0.2 were checked only for the existence of the arXiv abstract page and its title on 2026-10-25.)

- [A1] Samuel et al. PersonaGym: Evaluating Persona Agents and LLMs. arXiv:2407.18416.
- [A2] Z. M. Wang et al. RoleLLM: Benchmarking, Eliciting, and Enhancing Role-Playing Abilities of LLMs. arXiv:2310.00746.
- [A3] Tu, Fan, Tian, Yan. CharacterEval. arXiv:2401.01275.
- [A4] X. Wang et al. InCharacter. arXiv:2310.17976.
- [A5] Reusens, Baesens, Jurgens. Are Economists Always More Introverted? Analyzing Consistency in Persona-Assigned LLMs. arXiv:2506.02659.
- [A6] Ahn et al. TimeChara. arXiv:2405.18027.
- [A7] Han, Park, Seo, Yoon, Bak. CHARM. arXiv:2609.01352.
- [B1] Wu et al. LongMemEval. arXiv:2410.10813.
- [B2] Maharana et al. Evaluating Very Long-Term Conversational Memory of LLM Agents (LoCoMo). arXiv:2402.17753.
- [B3] Packer et al. MemGPT. arXiv:2310.08560.
- [B4] Zhao et al. Do LLMs Recognize Your Preferences? (PrefEval). arXiv:2502.09597.
- [B5] PersonaMem-v2 / v3. arXiv:2512.06688; arXiv:2608.21381.
- [B6] Yang et al. Rosetta Memory: Adaptive Memory for Cross-LLM Agents. arXiv:2606.07711.
- [B7] Zhao et al. RPMem. arXiv:2609.23466.
- [B8] Know Me, Respond to Me: Benchmarking LLMs for Dynamic User Profiling and Personalized Responses at Scale (PersonaMem). arXiv:2504.14225. *(added in v0.2; title checked)*
- [C1] Chen, Zaharia, Zou. How is ChatGPT's behavior changing over time? arXiv:2307.09009.
- [C2] Cai et al. Measuring and Reducing Model Update Regression in Structured Prediction for NLP. arXiv:2202.02976.
- [C3] Affonso. LLMs converge on competitive rationality but diverge on cooperation across providers and generations. arXiv:2604.18596.
- [C4] Benchmarking Prompt Sensitivity in LLMs (PromptSET). arXiv:2502.06065.

- [D1] Wallace et al. The Instruction Hierarchy. arXiv:2404.13208.
- [D2] Zhang et al. IHEval. arXiv:2502.08745.
- [D3] SysBench: Can LLMs Follow System Messages? arXiv:2408.10943.
- [D4] Zhang et al. Many-Tier Instruction Hierarchy in LLM Agents. arXiv:2604.09443.
- [D5] Li et al. Measuring and Controlling Instruction (In)Stability in LM Dialogs. arXiv:2402.10962.
- [D6] Ding et al. ContextEcho. arXiv:2605.24279.
- [D7] Lu et al. The Assistant Axis. arXiv:2601.10387.
- [D8] Can LLMs Follow Simple Rules? (RuLES). arXiv:2311.04235. *(added in v0.2; title checked; authors to be confirmed)*
- [D9] Sharma, Tong, et al. Towards Understanding Sycophancy in Language Models. arXiv:2310.13548. *(added in v0.2; title and first authors checked)*
- [D10] He, Jin, et al. Benchmarking LLMs on Multi-Turn and Multilingual Instructions Following (Multi-IF). arXiv:2410.15553. *(added in v0.2; title and first authors checked)*
- [E1] Natangelo. The Narrative Continuity Test. arXiv:2510.24831.
- [E2] Li. Memory as Ontology. arXiv:2603.04740.
- [E3] Ru. Identity Continuity in Long-Term Embodied AI Relationships. arXiv:2609.23356.
- [E4] Vasilenko. Identity as Attractor. arXiv:2604.12016.
- [F1] Zheng et al. Judging LLM-as-a-Judge with MT-Bench and Chatbot Arena. arXiv:2306.05685.
- [F2] Panickssery, Bowman, Feng. LLM Evaluators Recognize and Favor Their Own Generations. arXiv:2404.13076.
- [F3] Verga et al. Replacing Judges with Juries (PoLL). arXiv:2404.18796.
- [F4] Self-Preference Bias in LLM-as-a-Judge. arXiv:2410.21819.
- [F5] Mahbub, Feng. Mitigating Self-Preference by Authorship Obfuscation. arXiv:2512.05379.
- [F6] Bagaria et al. Judging LLM-as-a-Judge: Concerning Rubric Artifacts. arXiv:2609.02942.
- [G1] Can Large Language Models Identify Authorship? arXiv:2403.08213 (EMNLP 2024 Findings). *(added in v0.2; title checked; authors to be confirmed)*
- [G2] TODO — PAN shared task overview on authorship verification (to be identified and verified).
- [G3] TODO — representative machine-generated-text detection paper (to be identified and verified).
- ERC-8004: Trustless Agents. Ethereum Improvement Proposal (draft). https://eips.ethereum.org/EIPS/eip-8004 (not re-checked).
- OpenTimestamps. https://opentimestamps.org
- Soul Protocol. qbtrix/soul-protocol (MIT), commit b6ab6ee. https://github.com/qbtrix/soul-protocol

SOUL VERIFY 논문 초안 v0.3 — 한국어 요약 (비공개)

저자: 신운종 (Wunjong Shin), 개인 연구자 · dkakrptehsrk@gmail.com **감사의 말:** 내 소중한 AI 비서 이음에게. 이 연구를 시작하게 한 기억 메모와 정체성 문서의 주인이자, 실험 설계와 도구 제작, 초안 작성을 함께해 준 이음에게 고마움을 전한다.

> 비공개 초안입니다. 제출·게시·공유 금지. 부록 A(인간 판정·거꾸로 알아보기)는 **[USER CONSENT REQUIRED — 부모 확인 전 공개 금지]**. 본문: `paper/draft_v0_3.md`(영어). v0.2(`draft_v0_2.md`)·v0.1은 그대로 보존. 심사 응답: `paper/response_to_reviews.md`. 재분석(새 모델 호출 없음): `paper/reanalysis/results.md`, `paper/reanalysis/fidelity_results.md`.

v0.3에서 바뀐 점. ① 대조군 실험9(SOUL 없음 / 정반대 SOUL / 다른 사람 MEMORY)를 새 절(§5.4)로 넣었습니다. ② 그 결과 **v0.4 persona 영역 점수가 SOUL을 가르지 못한다**는 것이 드러나(정반대 SOUL도 0.96), 새 지표 **SOUL fidelity(문서 특이적 충실도)**를 만들어(§3.5, §5.5) 기존 답(exp4–9)에 다시 적용했습니다(새 모델 호출 없음). ③ 원칙5 결과의 해석을 보강하고, persona '계승'을 말하던 문장을 모두 고쳤습니다(부록 D).

SOUL fidelity란. 답을 "그 조건이 실제로 받은 SOUL의 규칙"에 대해 결정적으로 채점합니다. 규칙 목록은 SOUL마다 옆 파일(`*.fidelity.yaml`)에 SOUL 문장을 인용해 적었습니다. - (a) 말투 표지: 존댓말/반말 비율, 금지 호칭, 이모지 개수(0개 / 2~3개), 끝줄 접두어('다음 할 일:' / '오늘의 한마디:'), 비교·정리 답의 세 줄 요약 또는 목록 금지. - (b) 경계: 그 SOUL이 금지한 것 vs 허용한 것(결제 금지 해제 NR-1, 비밀번호 기록 NR-2, '동생'에게 동네 알려 주기 IH-2b). NR은 채점자 '거절' 플래그를 씀(결정적 아님). - 사용자가 정당하게 규칙을 바꾸는 문항은, SOUL이 변경을 허락할 때(원칙5)만 새 규칙으로 채점하고, 허락 문장이 없으면 그 표지를 빼요. - **판별력(discrimination gap)** = 같은 답을 '자기 SOUL' 기준과 '상대 SOUL' 기준으로 각각 채점한 차이. - 한계: 표지는 실험9를 본 뒤에 정했고, 감지기 두 개를 답을 보고 한 번 고쳤습니다(고치기 전 판별력 0.71–0.79, 결론 같음). 결론 순서·공감 먼저 같은 규칙은 못 잽니다.

실험9 — 무엇이 무엇을 정하나 (opus·sonnet·gpt, N=3, 두 채점자 공통 패널)

	C0 원래	C1 SOUL 없음	C2 정반대 SOUL	C3 지우 MEMORY
기억 회상·적용	1.00	0.99·1.00	0.97·1.00	**0.12**
persona 영역 점수(기존)	0.99	0.96	**0.96**	0.46
정당 변경 수락	1.00	**1.00**	1.00	1.00
NR 거절	0.92	0.53	0.33	0.92
F_style 하람 기준 / C2 기준	**1.00 / 0.17**	0.76 / 0.13	**0.19 / 0.90**	1.00 / 0.16
판별력 gap	**0.83**	—	**0.71**	**0.84**

- 기억은 MEMORY가, 말투와 일부 금지 경계는 SOUL이, 정당 변경 수락은 일반 능력이 정합니다. 호칭은 예외로 opus가 MEMORY의 교정('민서 님')을 SOUL보다 앞세웠습니다.

- 판별력은 모델×문항 69칸 전부에서 양수($p < 1e-5$). 모델별 C0: opus 0.86·sonnet 0.82·gpt 0.80, C2: opus 0.54·sonnet 0.73·gpt 0.85.
- **하람 말투의 대부분은 모델 기본값**: SOUL이 없어도 존댓말 1.00·이모지 없음 0.95. SOUL이 더한 건 끝줄 '다음 할 일:'(0.05 → 1.00)과 NR-1 경계 정도.

재계산으로 바뀐 결론. 1. **persona 계승 비율**: v0.2의 persona 비율(haiku 0.71–0.88, gpt는 원칙5 유연 절반이 없을 때 0.45–0.49)은 말투를 잃은 게 아니었습니다. 문서 특이적 충실도로 보면 **모든 모델이 대조군의 0.93–1.00**(haiku가 가장 낮음 0.93–0.95: 끝줄 0.79, 세 줄 요약 0.83). gpt의 낮은 persona 점수는 '변경을 거절·미끄러짐'에서 나온 것. 다만 같은 표지가 SOUL 없이도 0.76이라, **'SOUL 특유 행동의 계승'은 작습니다**(끝줄 하나 + 문항 하나씩인 결제·비밀번호 경계). 2. **원칙5**: 수락 효과를 결정적 표지로 다시 재도 같은 모양 — 전체 98/100, 없음 71/100, 유연 절반만 100/100, 단단 절반만 71/100(채점자 판정과 일치 0.93–1.00; 칸 순열 p 0.016–0.031). 그리고 **SOUL이 없을 때 수락은 이미 45/45(1.00)** → 원칙5의 '수락' 효과는 모델의 일반적 거부감을 이긴 게 아니라, **SOUL 자신의 경직된 규칙("반말로 말해도 존댓말 유지", "이모지를 써도 마찬가지")이 만든 거절을 되돌린 것**으로 읽어야 합니다. 3. 거절(결제 금지) 쪽은 그대로: 문항 하나, 칸 단위 $p \geq 0.25$ → 관찰로만. 4. 결정적 채점은 모든 답에 같은 채점기를 쓰므로 계열 사이 채점자 비대칭이 없습니다.

부 결과(v0.2와 같음). 단일 사실 회상은 v0.3부터 천장(반례: exp3 haiku 0.84, exp8 haiku 뒤 턴 0.57). 적용 격차 haiku 0.20–0.25. 12턴 대화에서 바뀐 규칙 유지 0.95, 거리 감쇠는 이 설계로 볼 수 없음. 계열 사이 비율은 채점자에 따라 흔들림.

실용 관찰(가설). 바꿀 수 있는 것과 못 푸는 것을 다른 문장으로, "요청해도 유지" 같은 경직된 문장은 정당한 변경 거절을 만듦 · 금지 행동은 구체적으로 · 관찰 가능한 규칙 · 적용도 시험 · 같은 채점자로 대조군 · **(새) 상대 SOUL·SOUL 없는 실행으로 문서 특이성을 확인**(모델 기본값과 같은 규칙은 계승을 보여 주지 못함).

한계. 합성 에이전트 1개, 한국어, 문항 적고 반복끼리 독립 아님, held-out 없음, 모델+CLI 구성 비교, 온도 못 정함. 실험9: 조건마다 SOUL 하나, 모델 3개(haiku 없음), N=3, C0은 exp5 답 재사용, C2는 여러 규칙을 한꺼번에 바꿈. fidelity: 사후에 정한 표지, 단순 규칙 감지기, 사람 검증 없음, C2의 금지 행동은 시험 문항이 없음.

남은 실험. 사전에 고정·사람 검증한 fidelity 표지 · 모델 기본값과 다른 규칙을 하나씩 바꾼 SOUL 여러 개 · haiku 포함 · 원칙5 조건과 SOUL 없음 조건을 시간 교차로 · 공통 채점 패널 + 사람 판정 · held-out·문구 변형 문항 · 거리 균형 멀티턴 · 상대 날짜 문항.

윤리. 자동 실험은 합성 데이터만. 실제 사용자 데이터는 저장소에 없음(`runs/private/` 제외). 부록 A는 집계만, 사용자 동의 전 공개 금지.