PhonePe

Api Reference

Payment Gateway
GETTING STARTED
Introduction
PG STANDARD CHECKOUT APIS
UI Flow
Merchant Checklist
API Details
Authorization
Create Payment
Initiate Payment
Order Status
Refund
Refund Status
Handling Webhooks
PG Ecommerce Plugins
UAT and Prod Details
ANDROID PG SDK (STANDARD)
Introduction
SDK Setup
API Details
UAT and Prod Details
IOS PG SDK (STANDARD)
Introduction
SDK Setup
API Details
UAT and Prod Details
PG HYBRID SDK (STANDARD)
React Native SDK Integration
Flutter SDK Integration
Ionic SDK Integration
UAT and Prod Details
PG BACKEND SDK
Java SDK (Standard)
Python SDK (Standard)
Nodejs SDK (Standard)
PHP SDK (Standard)
AUTOPAY
Introduction
API Details
UAT and Prod Details
AUTOPAY BACKEND SDK
Java SDK (Autopay)

Authorization

Postman Collection

Click here to fork the PhonePe APIs Postman collection and start testing instantly.

Fetch Auth Token API

Merchant backend should call this API to get an auth token, which will be used to authorize the subsequent API calls between the Merchant & PhonePe backend.

- The generated token can be used to make multiple API calls until it expires.
- Merchant can save the token and rely on the "expires_at" field for the expiry of the token, within which the token should be refreshed by using the same API.

Host Details

Environment	Value
`UAT`	https://api-preprod.phonepe.com/apis/pg-sandbox
`PROD`	https://api.phonepe.com/apis/identity-manager

Endpoint

/v1/oauth/token – Endpoint is common for UAT and Production.

Complete Host Details

Environment	Http Method	Value
`UAT`	POST	https://api-preprod.phonepe.com/apis/pg-sandbox/v1/oauth/token
`PROD`	POST	https://api.phonepe.com/apis/identity-manager/v1/oauth/token

Request Details

Request Headers

Header Name	Header Value
`Content-Type`	application/x-www-form-urlencoded

Request Parameters

Parameter Name	Description
`client_id`	Client ID shared by PhonePe
`client_version`	In case of UAT, client_version value should be 1. In case of PROD, use the value as received in credentials email.
`client_secret`	Client secret shared by PhonePe
`grant_type`	Value will be "client_credentials"

PhonePe

```
curl --location 'https://api-preprod.phonepe.com/apis/pg-sandbox/v1/oauth/token' \
--header 'Content-Type: application/x-www-form-urlencoded' \
--data-urlencode 'client_id=CLIENT_ID' \
--data-urlencode 'client_version=1' \
--data-urlencode 'client_secret=CLIENT_SECRET' \
--data-urlencode 'grant_type=client_credentials'
```

NOTE : Above CURL has the UAT Host URL and the dummy data for **client_id** and **client_secret**. Ensure to replace with the appropriate values.

Response Body


```
{
    "access_token": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJleHBpcmVzT24iOjE3MjA2MzUzMjE5OTYsIm1lcm
    "encrypted_access_token": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJleHBpcmVzT24iOjE3MjA2MzUzMjE5
    "expires_in": null,
    "issued_at": 1706073005,
    "expires_at": 1706697605,
    "session_expires_at": 1706697605,
    "token_type": "O-Bearer"
}
```


Response Parameters

Parameter Name	Data Type	Description
access_token	String	Token generated at PhonePe, Generated token will remain valid for a specific time and this can be checked by referring to the "expires_at" field. After expiry, the token must be refreshed using the same API.
issued_at	DateTime	Token generated timestamp in epoch **(in seconds)**
expires_at	DateTime	Token expiry timestamp in epoch **(in seconds)**
token_type	String	Type will be "O-Bearer".

Note: Merchants should rely on the following response parameters.

- *access_token* – The TOKEN that has to be used in the API calls with PhonePe.
- *expires_at* – The validity of the TOKEN **(in seconds)**

Updated on Jul 04, 2024