PhonePe

Api Reference

Create Payment

This API is used to create the payment.

Postman Collection

Click here to fork the PhonePe APIs Postman collection and start testing instantly.

Quick Links

- Sample Request
- Request Parameters
- Sample CURL Request
- Sample Response
- How to Initiate Payment

Note:

To avoid transaction blocking in production, kindly check the below points:

1. If you are using a personalised Chrome tab within their Android app, hindering URL retrieval. Please use SDK integration to resolve this issue.
2. If you are launching PayPage in a new window or tab, resulting in the absence of a referrer, then either redirect or employ an iFrame for PayPage is essential.
3. If you have implemented a no-referrer-policy then it leads to blank merchant URLs captured at our end. Please refrain from using it on the checkout page.

Host Details

Environment	Http Method	Value
UAT	POST	https://api-preprod.phonepe.com/apis/pg-sandbox
PROD	POST	https://api.phonepe.com/apis/pg

Endpoint

/checkout/v2/pay – Endpoint is common for UAT and Production.

Complete Host Details

Environment	Http Method	Value
UAT	POST	https://api-preprod.phonepe.com/apis/pg-sandbox/checkout/v2/pay
PROD	POST	https://api.phonepe.com/apis/pg/checkout/v2/pay

Note: Before initiating the payment, install the PhonePe Test App and make sure to Configure Template. Otherwise, you will get HTTP Error Code: 500.

Request Details

Request Headers

PhonePe

Authorization	O-Bearer <access_token>	Pass *access_token* received in Authorization call

Sample Request

```
{
    "merchantOrderId": "TX123456",
    "amount": 1000,
    "expireAfter": 1200,
    "metaInfo": {
        "udf1": "additional-information-1",
        "udf2": "additional-information-2",
        "udf3": "additional-information-3",
        "udf4": "additional-information-4",
        "udf5": "additional-information-5"
    },
    "paymentFlow": {
        "type": "PG_CHECKOUT",
        "message": "Payment message used for collect requests",
        "merchantUrls": {
            "redirectUrl": ""
        }
    }
}
```

Sample Request with Selected Instrument

```
{
    "merchantOrderId": "TX123456",
    "amount": 1000,
    "expireAfter": 1200,
    "metaInfo": {
        "udf1": "<additional-information-1>",
        "udf2": "<additional-information-2>",
        "udf3": "<additional-information-3>",
        "udf4": "<additional-information-4>",
        "udf5": "<additional-information-5>"
    },
    "paymentFlow": {
        "type": "PG_CHECKOUT",
        "message": "Payment message used for collect requests",
        "merchantUrls": {
            "redirectUrl": ""
        },
        "paymentModeConfig": {
            "enabledPaymentModes": [
                {
                    "type": "UPI_INTENT"
                },
                {
                    "type": "UPI_COLLECT"
                },
                {
                    "type": "UPI_QR"
                },
                {
                    "type": "NET_BANKING"
                },
                {
                    "type": "CARD",
                    "cardTypes": [
                        "DEBIT_CARD",
                        "CREDIT_CARD"
                    ]
                }
            ],
            "disabledPaymentModes": [
                {
                    "type": "UPI_INTENT"
                },
                {
                    "type": "UPI_COLLECT"
                },
                {
```

PhonePe

```
                    },
                    {
                        "type": "CARD",
                        "cardTypes": [
                            "DEBIT_CARD",
                            "CREDIT_CARD"
                        ]
                    }
                ]
            }
        }
    }
```

Important Notes:

- Merchants should pass "paymentModeConfig" block only if the merchant wants to manage the instrument to be displayed on the checkout page. Otherwise, the "paymentModeConfig" block should be ignored which will show the default instruments enabled at PhonePe's end.
- Either enabledPaymentModes or disabledPaymentModes is required, if both are present API will throw error.
- paymentModeConfig.enabledPaymentModes:
  This will ensure the list of Instruments passed within the "enabledPaymentModes" block will only be shown on the Checkout Page while all other enabled instruments at PhonePe end won't be displayed.
- paymentModeConfig.disabledPaymentModes:
  This will ensure the list of Instruments passed within the "disabledPaymentModes" block will not be shown on the Checkout Page while all other enabled instruments at PhonePe end will be displayed.
- Special Case for the CARD instrument
  Ensure to pass the cardTypes as well along with type.
  - If "enabledPaymentModes.type" = "CARD" but "enabledPaymentModes.cardTypes" is not passed, then the Card option will be displayed based on the instrument enabled at PhonePe's end [CreditCard (and/or) Debit Card].
  - If "enabledPaymentModes.type" = "CARD" and "enabledPaymentModes.cardTypes" = ["DEBIT_CARD"] is passed, then the Debit Card option only will be allowed on the PhonePe checkout.
  - If "disabledPaymentModes.type" = "CARD" but "disabledPaymentModes.cardTypes" is not passed, then the Card option won't be disabled and user will be displayed based on the instrument enabled at PhonePe's end [CreditCard (and/or) Debit Card].
  - If "disabledPaymentModes.type" = "CARD" and "disabledPaymentModes.cardTypes" = ["DEBIT_CARD"] is passed, then the Debit Card option alone will be disabled on the PhonePe checkout.
  - If "disabledPaymentModes.type" = "CARD" and "disabledPaymentModes.cardTypes" = ["DEBIT_CARD", "CREDIT_CARD"] is passed, only then both Debit Card and Credit Card will be disabled on the PhonePe checkout.

Request Parameters ⚓

Parameter Name	Data Type	Description	Mandatory (Yes/No)	Constraints
merchantOrderId	STRING	Unique merchant order id generated by merchant	Yes	Max Length = 6: charactersNo Specia characters allowe except underscore "_ and hyphen "-"
expireAfter	LONG	Order expiry in seconds. If not passed, default value will be used.	No	Min Value = 300, Ma Value = 3600 (i Seconds) Default Value = 120 Secs (20 Mins)

PhonePe

metaInfo	OBJECT	Merchant defined meta info to store additional information.same data will be returned in status and callback response	No	
metaInfo.udf1-4	STRING	Merchant defined additional information	No	Max length = 25(characters
paymentFlow	OBJECT	Additional details required by this flow	Yes	
paymentFlow.type	STRING	Type of payment flow	Yes	Valued Allowed : [PG_CHECKOUT]
paymentFlow.message	STRING	Payment message used for collect requests	No	
paymentFlow.merchantUrls	OBJECT	Object to store different merchant Urls	Yes	
paymentFlow.merchantUrls.redirectUrl	STRING	Url where user will be redirected after success/failed payment.	Yes	
paymentModeConfig	OBJECT	Additional details to display only the selected instruments	Optional	Either enabledPaymentModes or disabledPaymentMode is required, if both ar present API will throv error.

Sample CURL Request

```
curl --location 'https://api-preprod.phonepe.com/apis/pg-sandbox/checkout/v2/pay' \
--header 'Content-Type: application/json' \
--header 'Authorization: O-Bearer eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJleHBpcmVzT24iOjE3MTIyNTM2M
--data '{
  "merchantOrderId": "TX123rrty34432456",
  "amount": 1000,
  "paymentFlow": {
    "type": "PG_CHECKOUT",
    "message": "Payment message used for collect requests",
    "merchantUrls": {
      "redirectUrl": "https://www.xyz.com/PGIntegration/"
    }
```

PhonePe

Sample Response

Response Headers:

Header Name	Header Value
Content-Type	application/json

Response Payload:

Case 1: Order created successfully

Http Response Code: 200

```
{
    "orderId": "OMO123456789",
    "state": "PENDING",
    "expireAt": 1703756259307,
    "redirectUrl": "https://mercury-uat.phonepe.com/transact/uat_v2?token=eyJhbGciOiJIUzI1NiIsInR5cC
}
```

How to Initiate Payment

The JS Checkout bundle will handle the opening of pay page on the merchant's page. Merchants can either opt for IFrame or Redirect mode.

- Invoke PayPage on Checkout Page
  - In IFrame [Most Recommended]
  - In Redirect Mode

```
<script src="https://mercury.phonepe.com/web/bundle/checkout.js"></script>
```

After including this script,

- the `PhonePeCheckout` object will be available to merchants, which they can use to invoke PayPage using the 'transact' function.
- They can also use the `closePage` function to explicitly close the PayPage iFrame if invoked in iFrame mode.

Merchants must ensure to call the appropriate function and pass the necessary parameters to handle the PayPage flow on their checkout page.

Case 2: Order with same merchant order id is already present and not in CREATED state

Http Response Code: 400

```
{
    "code": "BAD_REQUEST",
    "message": "Please check the inputs you have provided."
}
```

Case 3: Internal Server Error

Http Response code: 500

```
{
    "code": "INTERNAL_SERVER_ERROR",
```

PhonePe

Response Parameters

Field Name	Data Type	Description
`orderId`	String	PG generated internal order id
`state`	String	State of the order created, Expected value is CREATED
`expiryAt`	Long	Order expiry date in epoch (in milliseconds)
`redirectUrl`	String	Url where merchant is supposed to redirect user to complete payment

Updated on May 22, 2024