PhonePe

Api Reference

Payment Gateway
GETTING STARTED
Introduction
PG STANDARD CHECKOUT APIS
UI Flow
Merchant Checklist
API Details
Authorization
Create Payment
Initiate Payment
Order Status
Refund
Refund Status
Handling Webhooks
PG Ecommerce Plugins
UAT and Prod Details
ANDROID PG SDK (STANDARD)
Introduction
SDK Setup
API Details
UAT and Prod Details
IOS PG SDK (STANDARD)
Introduction
SDK Setup
API Details
UAT and Prod Details
PG HYBRID SDK (STANDARD)
React Native SDK Integration
Flutter SDK Integration
Ionic SDK Integration
UAT and Prod Details
PG BACKEND SDK
Java SDK (Standard)
Python SDK (Standard)
Nodejs SDK (Standard)
PHP SDK (Standard)
AUTOPAY
Introduction
API Details
UAT and Prod Details
AUTOPAY BACKEND SDK
Java SDK (Autopay)

Initiate Payment

Invoke PayPage on Checkout Page

To Invoke PayPage on the checkout page, merchants need to include the `checkout.js` script provided by PhonePe:

```
<script src="https://mercury.phonepe.com/web/bundle/checkout.js"></script>
```

This script will append the `PhonePeCheckout` object in the `window` object.

`PhonePeCheckout` object will have the following two functions exposed, which merchants can use as per their use case:

`PhonePeCheckout.transact`
`PhonePeCheckout.closePage`

The `transact` function is used to invoke PayPage either in iFrame or redirect mode, as explained earlier.

The `closePage` function is used to explicitly close the PayPage iFrame (if invoked in iFrame mode), as explained earlier.

Merchants must use these functions appropriately in their checkout flow to enable PayPage payment processing.

Invoking PayPage in Redirect Mode

To invoke PayPage in redirect mode, merchants need to call the `transact()` function provided by the `window.PhonePeCheckout` object:

```
window.PhonePeCheckout.transact({ tokenUrl });
```

The `tokenUrl` parameter will contain the PayPage's URL which merchants will obtain via a server-to-server call. This URL will redirect the user to the PayPage for payment processing.

Once the payment process is completed, PayPage will redirect the user back to the merchant's website.

Merchants must ensure they have the necessary backend logic to verify the status of the payment completion from the PayPage server and update the user accordingly.

Invoking PayPage in IFrame

To invoke PayPage in an iFrame over the merchant's page, merchants need to call the `transact()` function provided by the `window.PhonePeCheckout` object.

```
window.PhonePeCheckout.transact({ tokenUrl, callback, type: "IFRAME" });
```

The `tokenUrl` parameter will contain the PayPage's URL which merchants will obtain via a server-to-server call.

PhonePe

```
function callback (response) {
  if (response === 'USER_CANCEL') {
    /* Add merchant's logic if they have any custom thing to trigger on UI after the transaction is
    return;
  } else if (response === 'CONCLUDED') {
    /* Add merchant's logic if they have any custom thing to trigger on UI after the transaction is
    return;
  }
}
```

The response parameter in the `callback` function will contain either USER_CANCEL or CONCLUDED based on whether the transaction was canceled by the user or it has reached a terminal state.

Merchants can add their custom UI logic in the if statements to trigger after the transaction is canceled or completed.

Using the closePage() Function ⚓

The `closePage()` function is used to explicitly close the iFrame on the merchant's logic. This function can be used to close the PayPage only if there are use cases where the merchant wants to close the PayPage on their logic.

Usage

To use the closePage() function, call it from the merchant's code:

```
window.PhonePeCheckout.closePage();
```

This will close the PayPage iFrame.

Note: This function should not be used in normal use cases as the iFrame will be closed anyways after the payment is complete. It should only be used if the merchant has specific use cases where they want to close the PayPage on their logic.

To integrate PhonePe Checkout features into your Flutter web project, follow these steps:

- Add the PhonePe Checkout JavaScript package to your project by adding the following

  ```
  <script src="https://mercury-stg.phonepe.com/web/bundle/checkout.js" defer></script>
  ```

  This will load the PhonePe Checkout package into your project.

- Define a JavaScript function to call the PhonePe Checkout transact function with a callback. The function should take three parameters: tokenUrl, type, and callback. Here's an example:

  ```
  window.checkout = (tokenUrl, type, callback) => {
    if(window && window.PhonePeCheckout && window.PhonePeCheckout.transact) {
       window.PhonePeCheckout.transact({tokenUrl, callback, type});
    }
  }
  ```

  This code defines a checkout function that calls the PhonePeCheckout.transact() function with the provided parameters.

- In your Dart code, define a callback function that will be triggered when a transaction is concluded or canceled. Here's an example:

PhonePe

```
        // Add merchant's logic if they have any custom thing to trigger on UI after the transact
        return;
      } else if (response === 'CONCLUDED') {
        // Add merchant's logic if they have any custom thing to trigger on UI after the transact
        return;
      }
    }
```

This callback function takes a response parameter that represents the status of the transaction. In this example, the function checks if the transaction was canceled by the user or concluded successfully, and then adds any custom UI logic if needed.

- In the function that handles the pay page invocation or redirection, you can check if the checkout function is defined and then call it using the parameters tokenUrl, type, and js.allowInterop(callback). Here's an example:

```
import 'dart:js' as js;
void handlePayPage() {
   if(js.context.hasProperty('checkout')) {
      // The package is loaded
      const tokenUrl = "PayPage Generated URL";
      const type = "IFRAME";
      js.context.callMethod('checkout', [tokenUrl, type, js.allowInterop(callback)]);
   }
}
```

Updated on Dec 21, 2023