

COLD SPRING HARBOR, NEW YORK—How many genes does an organism need to survive? Last week at the genome meeting here,* two genome researchers with radically different approaches presented complementary views of the basic genes needed for life. One research team, using computer analyses to compare known genomes, concluded that today's organisms can be sustained just 250 genes, and that the *Escherichia coli* genome required a mere 128 genes. The other researcher mapped genes in a simple parasite and estimated that for this organism, 800 genes are plenty to do the job—but that anything short of 100 wouldn't be enough.

Although the numbers don't match precisely, those predictions

"are not all that far apart," especially in comparison to the 75,000 genes in the human genome, notes Siv Andersson of Uppsala University in Sweden, who arrived at the 800 number. But coming up with a consensus answer may be more than just a genetic numbers game, particularly as more and more genomes are completely mapped and

sequenced. "It may be a way of organizing the genome," explains

Arcady Mushegian, a computational mo-

lecular biologist at the National Center

of Biotechnology Information (NCBI)


in Bethesda, Maryland. Comparing an

S&DS 265 / 565 Introductory Machine Learning

Topic Models



November 8



* Genome Mapping and Sequencing, Cold Spring Harbor, New York, May 8 to 12.

Stripping down. Computer analysis yields an estimate of the minimum modern and ancient gene sets.

Yale

Checkpoint

- Assignment 4 (LMs and embeddings) due Thursday
- Assignment 5 posted Thursday (topic models and NNs)
- Quiz 4 last week; Quiz 5 next Thursday

Probabilistic modeling

- ① Data are assumed to be observed from a generative probabilistic process that includes hidden variables.
 - *In text, the hidden variables are the thematic structure.*
- ② Infer the hidden structure using posterior inference
 - *What are the topics that describe this collection?*
- ③ Situate new data into the estimated model.
 - *How does a new document fit into the topic structure?*


Latent Dirichlet allocation (LDA)

Seeking Life's Bare (Genetic) Necessities

COLD SPRING HARBOR, NEW YORK—How many genes does an organism need to survive? Last week at the genome meeting here,* two genome researchers with radically different approaches presented complementary views of the basic genes needed for life. One research team, using computer analyses to compare known genomes, concluded that today's organisms can be sustained with just 250 genes, and that the earliest life forms required a mere 128 genes. The other researcher mapped genes in a simple parasite and estimated that for this organism, 800 genes are plenty to do the job—but that anything short of 100 wouldn't be enough.

Although the numbers don't match precisely, those predictions

"are not all that far apart," especially in comparison to the 75,000 genes in the human genome, notes Siv Andersson of Uppsala University in Sweden, who arrived at the 800 number. But coming up with a consensus answer may be more than just a genetic numbers game, particularly as more and more genomes are completely mapped and sequenced. "It may be a way of organizing any newly sequenced genome," explains Arcady Mushegian, a computational molecular biologist at the National Center for Biotechnology Information (NCBI) in Bethesda, Maryland. Comparing an




ADAPTED FROM NCBI

Stripping down. Computer analysis yields an estimate of the minimum modern and ancient genomes.


Simple intuition: Documents exhibit multiple topics.

Generative model for LDA




- Each **topic** is a distribution over words
- Each **document** is a mixture of corpus-wide topics
- Each **word** is drawn from one of those topics

The posterior distribution




- In reality, we only observe the documents
- The other structure are **hidden variables**

The posterior distribution




- Our goal is to **infer** the hidden variables
 - I.e., compute their distribution conditioned on the documents
- $$p(\text{topics, proportions, assignments} \mid \text{documents})$$

LDA as a graphical model




- Encodes our assumptions about the data
- Connects to algorithms for computing with data
- See *Pattern Recognition and Machine Learning* (Bishop, 2006).

LDA as a graphical model




- Nodes are random variables; edges indicate dependence.
- Shaded nodes are observed.
- Plates indicate replicated variables.

LDA as a graphical model




$$\prod_{i=1}^K p(\beta_i | \eta) \prod_{d=1}^D p(\theta_d | \alpha) \left(\prod_{n=1}^N p(z_{d,n} | \theta_d) p(w_{d,n} | \beta_{1:K}, z_{d,n}) \right)$$

LDA



- This joint defines a posterior.
- From a collection of documents, infer
 - Per-word topic assignment $Z_{d,n}$
 - Per-document topic proportions θ_d
 - Per-corpus topic distributions β_k
- Then use posterior expectations to perform the task at hand, e.g., information retrieval, document similarity, exploration, ...

Example inference



- **Data:** The OCR'ed collection of *Science* from 1990–2000
 - 17K documents
 - 11M words
 - 20K unique terms (stop words and rare words removed)
- **Model:** 100-topic LDA model using variational inference.


Example inference

Seeking Life's Bare (Genetic) Necessities

COLD SPRING HARBOR, NEW YORK—How many genes does an organism need to survive? Last week at the genome meeting here,⁶ two genome researchers with radically different approaches presented complementary views of the basic genes needed for life. One research team, using computer analyses to compare known genomes, concluded that today's organisms can be sustained with just 250 genes, and that the earliest life forms required a mere 128 genes. The other researcher mapped genes in a simple parasite and estimated that for this organism, 800 genes are plenty to do the job—but that anything short of 100 wouldn't be enough.


Although the numbers don't match precisely, those predictions

"are not all that far apart," especially in comparison to the 75,000 genes in the human genome, notes Siv Andersson of Uppsala University in Sweden, who arrived at the 800 number. But coming up with a consensus answer may be more than just a genetic numbers game, particularly as more and more genomes are completely mapped and sequenced. "It may be a way of organizing any newly sequenced genome," explains Arcady Mushegian, a computational molecular biologist at the National Center for Biotechnology Information (NCBI) in Bethesda, Maryland. Comparing an



* Genome Mapping and Sequencing, Cold Spring Harbor, New York, May 8 to 12.

Stripping down. Computer analysis yields an estimate of the minimum modern and ancient genomes.



Example inference

human	evolution	disease	computer
genome	evolutionary	host	models
dna	species	bacteria	information
genetic	organisms	diseases	data
genes	life	resistance	computers
sequence	origin	bacterial	system
gene	biology	new	network
molecular	groups	strains	systems
sequencing	phylogenetic	control	model
map	living	infectious	parallel
information	diversity	malaria	methods
genetics	group	parasite	networks
mapping	new	parasites	software
project	two	united	new
sequences	common	tuberculosis	simulations

Example inference (II)

Chaotic Beetles

Charles Godfray and Michael Hassell

Ecologists have known since the pioneering work of May in the mid-1970s (1) that the population dynamics of animals and plants can be exceedingly complex. This complexity arises from two sources: The tangled web of interactions that constitute any natural community provide a myriad of different pathways for species to interact, both directly and indirectly. And even in isolated populations the nonlinear feedback processes present in all natural populations can result in complex dynamic behavior. Natural populations can show persistent oscillatory dynamics and chaos, the latter characterized by extreme sensitivity to initial conditions. If such chaotic dynamics were common in nature, then this would have important ramifications for the management and conservation of natural resources. On page 389 of this issue, Costantino *et al.* (2) provide the most

convincing evidence to date of complex dynamics and chaos in a biological population—of the flour beetle, *Tribolium castaneum* (see figure).

It has proven extremely difficult to demonstrate complex dynamics in populations in the field. By its very nature, a chaotically fluctuating population will superficially resemble a stable or cyclic population buffeted by the normal random perturbations experienced by all species. Given a long enough time series, diagnostic tools from nonlinear mathematics can be used to identify the telltale signatures of chaos. In phase space, chaotic trajectories come to lie on “strange attractors,” curious geometric objects with fractal structure and hence noninteger dimension. As they

move over the surface of the attractor, sets of adjacent trajectories are pulled apart, then stretched and folded, so that it becomes impossible to predict exact population densities into the future. The strength of the mixing that gives rise to the extreme sensitivity to initial conditions can be measured mathematically estimating the Liapunov exponent, which is positive for chaotic dynamics and nonpositive otherwise. There have been many attempts to estimate attractor dimension and Liapunov exponents from time series data, and some candidate chaotic population have been identified (some insects, rodents, and most convincingly, human childhood diseases), but the statistical difficulties preclude any broad generalization (3).

An alternative approach is to parameterize population models with data from natural populations and then compare their predictions with the dynamics in the field. This technique has been gaining popularity in recent years, helped by statistical advances in parameter estimation. Good ex-




Cannibalism and chaos.
The flour beetle, *Tribolium castaneum*, exhibits chaotic population dynamics when the amount of cannibalism is altered in a mathematical model.

The authors are in the Department of Biology, Imperial College at Silwood Park, Ascot, Berks, SL5 7PZ UK. E-mail: m.hassell@ic.ac.uk

Example inference (II)

problem	model	selection	species
problems	rate	male	forest
mathematical	constant	males	ecology
number	distribution	females	fish
new	time	sex	ecological
mathematics	number	species	conservation
university	size	female	diversity
two	values	evolution	population
first	value	populations	natural
numbers	average	population	ecosystems
work	rates	sexual	populations
time	data	behavior	endangered
mathematicians	density	evolutionary	tropical
chaos	measured	genetic	forests
chaotic	models	reproductive	ecosystem

Posterior inference for LDA



- There is a large literature on approximating the posterior.
- We will focus on
 - Gibbs sampling
 - Mean-field variational methods (batch and online)



Markov chain Monte Carlo

- Construct a **Markov chain** on the hidden variables, whose limiting distribution is the posterior.
- Collect **independent samples** from that distribution; approximate the posterior with them
- In **Gibbs sampling** the chain is defined by the conditional distribution of each hidden variable given observations and the current setting of the other hidden variables.

Approximate inference

- We'll talk a bit about Gibbs sampling
- Variational inference saved for Intermediate Machine Learning (S&DS 365, IML)

Idea behind Gibbs sampling

- Only the assignments $Z_{n,d}$ are needed
- From these we can infer the proportions θ_d (per document)
- And the topics β_k (per corpus)
- The following slides indicate how in a toy example

Idea behind Gibbs sampling

At each time step in the algorithm, we have an assignment $Z_{n,d}$ of a topic to each word $w_{n,d}$ in every document d

Repeat forever:

- Select a word $w_{n,d}$
- Holding all of the other assignments $Z_{n',d'}$ fixed, calculate the probability distribution over $Z_{n,d}$ for that word
- Sample from that distribution to get a (potentially new) assignment $Z_{n,d}$

Toy example: 3 topics, 3 docs

w	z	w	z	w	z
meth	2	drug	3	inning	1
father	1	baseball	2	mother	3
divorce	3	hit	1	son	1
drug	1	inning	2	hit	2
illegal	1	steroids	1	baseball	3

Toy example: 3 topics, 3 docs

w	z	w	z	w	z
meth	1	drug	1	inning	1
father	2	baseball	2	mother	1
divorce	2	hit	2	son	2
drug	1	inning	3	hit	3
illegal	3	steroids	1	baseball	2

Toy example: 3 topics, 3 docs

w	z	w	z	w	z
meth	1	drug	1	inning	2
father	3	baseball	2	mother	3
divorce	3	hit	2	son	3
drug	1	inning	2	hit	2
illegal	1	steroids	1	baseball	2

For Assn6, we'll have you calculate the distribution of θ_d and β_k for this toy example

Extensions

Modeling richer assumptions

- Correlated topic model
- Dynamic topic model


Shortcoming of the Dirichlet

- Dirichlet for topic proportions:

$$p(\theta | \alpha) \propto \prod_{j=1}^k \theta_j^{\alpha_j - 1}$$


- Near independence of components makes it an unrealistic model
 - ▶ An article about *fossil fuels* is more likely to also be about *geology* than about *genetics*

Correlated topic model




- Draw topic proportions from a logistic normal.
- Useful for:
 - ▶ providing a “map” of topics and how they are related;
 - ▶ better prediction via correlated topics.
- Sacrifice conjugacy: Posterior over θ does not have same form

Topic graphs



Topic graphs



Modeling Evolution of Topics

- In LDA, document order doesn't matter
- The topics should *evolve* over time
 - ▶ “Cleaning Birds” (1883)
 - ▶ “Interspecific Brood Parasitism in Blackbirds (Icterinae): A Phylogenetic Perspective” (1992)
- Many document collections have such dynamics: emails, query logs, news articles, etc.

Science 1893 ⇒ Science 1976


Administration	Limnology	Astronomy	Psychology
association	water	observatory	mind
meeting	lake	observations	nature
american	sea	stars	say
committee	waters	time	science
congress	lakes	made	psychology
members	gulf	astronomical	work
held	great	comet	knowledge
international	depth	star	truth
meetings	river	observed	religion
section	stream	telescope	human

Administration	Limnology	Astronomy	Psychology
house	water	mass	human
congress	concentrations	radio	attempts
science	mercury	objects	theory
bill	fish	astronomy	learning
nsf	samples	xray	ideas
president	soil	stars	new
budget	lake	astronomical	memory
office	ppm	sources	psychology
committee	concentration	observations	behavior
new	waters	observatory	complex

Time series topic model

1. Allow topics evolve between time slices
3. For each document in the current time slice:
 - a. Select a distribution over topics;
 - b. Generate the words from the resulting topic mixture.

Dynamic topic models



Topics drifting in time

Time-corrected document similarity

The Brain of the Orang (1880)

300

EXTRACT

There is one query, which may be submitted to the author in his day of leisure, but for convenience or brevity :—no objection being made we present him with it. The author has written us as follows :—
"I am sorry to inform you that I have been unable to verify what the author of the article under review has said in his article. We therefore request our reader to consider the whole subject again."—

George F. Barker, Frederick D. C. Ward and Priscilla J. M. Blagden are preparing more elaborate and detailed versions of their important papers, and we presume these will be ready in time.

In the *Crang*, the parrot-oculo-sinus does not measure the calcarus, being separated from it by the *anulus pulvinatus* of *Crang*, or "uræna" of *Crang*. This has been mentioned in a number of recent papers.

According to Blandford, this disposition obtains in *Gorilla*, and we believe, also, in the *chimpanzee*.

On the other hand, however, as the author did not find the parrot-oculo-sinus passing into the nasal cavity, he has placed the *anulus pulvinatus* as a transverse fold extending across the nasal cavity, and separating the nasal from the oral cavity by the factors of *Bateson*, and *Ward*.

THE MEAN OF THE CHANNEL



1


the brain of the Ceylon Chalcides, and ours are the same; there are certain minor differences, however, in the arrangement of all three. The sense of Rhythm in the Ovary ring is due to the fact that it contains only a single bipinnately branched dendrite, the anterior one being the largest. In the Ovary ring of the male, quite a surprise, is, however, offered by the presence of an anterior lobe which is much more advanced forward than that in man. It differentiates the Ovary ring from the testis. The anterior lobe of the Ovary ring is well marked, bordered anteriorly by the testis. The epiphysis dorsalis descended normally on the median side of the anterior lobe.



6

acoustico-occipital fissure; externally it is continuous with the occipital lobe, as the fine occipital gyrus, although it is separated from the posterior central convolution more completely than is usual, by a fissure which runs parallel with the visual radiations. There is in the Ozong, also, a transverse sulcus which divides the parietal lobe into upper and lower portions. The parietal, or the upper, on the one side of the parietal lobe between the parieto-occipital

* *Proceedings of the Academy of Natural Sciences, Phil., etc.*



Time-corrected document similarity

Representation of the Visual Field on the Medial Wall of Occipital-Parietal Cortex in the Owl Monkey (1976)

present by recording responses of the medial occipital cortex were plotted with描记technique using techniques in five owl monkeys (2). The monkeys were anesthetized, killed, and prepared for recording. Tissue and pterygomastoid incisions were used to expose the medial occipital cortex or occasionally from single resections it was possible to expose the parietal cortex. The surface of exposed parietal cortex, that is, the surface of the medial occipital cortex, was covered with a thin layer of a translucent plastic hemisphere centered in front of the contralateral eye. A circular white disk was projected onto the plane hemispherical screen with the method of Fernald and Chase (5). The preferred eye usually was

covered with a opaque shield. Electrode tracks and recording sites were extracted from histological sections and photographs of the intact brain.

In all experiments, this form of our most complete mapping of the visual field area, has obtained in the other four experiments, was used to map the visual field organization. Tungsten penetrations were made at an angle of approximately 45° to the surface of the exposed medial occipital cortex in a distance of approximately 1 mm from the center of the receptive field. In all experiments, we found that the receptive fields recorded adjacent to the medial area were more elongated and oriented near the lower quadrant near the vertical meridian about 30° to 40° from the center (6). Thus, as is shown in Fig. 1, and





Fig. 1. Microelectrode recording penetrations and receptive field data for the medial visual area in owl monkey 72-415. The diagram on the lower left is a medial view of the left hemisphere of the left hemisphere with the brainstem and cerebellum removed. An arrow is used to denote the direction of depth in the diagram. Microelectrode tracks are shown in the medial wall of the right hemisphere. The scatter plot of receptive fields are shown in the left medial wall on the right. The upper-left is a polar map of the visuospatial organization of the medial visual area. The horizontal axis is the azimuth of the visual field, the vertical field, the elongated shape of the receptive fields near the vertical meridian and the peripheral portions of the lower visual quadrant. Dots, the medial area is adjusted by poles.



Exploring the UN General Debates with Dynamic Topic Models



Luke Lefebvre [Follow](#)
Oct 17, 2018 · 11 min read



Credit: [Vladislav Klapin](#) on [Unsplash](#)


<https://towardsdatascience.com/>

exploring-the-un-general-debates-with-dynamic-topic-models-72dc0e307696

Human rights

	1970	1980	1990	2000	2010
0	right	right	right	right	right
1	human	human	human	human	human
2	people	people	freedom	law	law
3	international	freedom	people	democracy	woman
4	principle	international	democracy	respect	freedom
5	justice	political	respect	international	respect
6	freedom	principle	law	people	people
7	law	respect	international	freedom	democracy
8	state	justice	principle	principle	rule
9	must	social	state	must	international


Human rights



Apartheid

	1970	1980	1990	2000	2010
0	africa	africa	africa	african	african
1	african	south	south	peace	country
2	south	african	african	africa	government
3	colonial	namibia	apartheid	country	africa
4	people	people	people	government	people
5	regime	regime	government	community	peace
6	southern	independence	country	democratic	political
7	government	apartheid	namibia	international	community
8	territory	racist	community	republic	democratic
9	apartheid	southern	process	effort	national


Apartheid



Arab-Israeli conflict

	1970	1980	1990	2000	2010
0	arab	palestinian	peace	peace	peace
1	israel	israel	east	east	state
2	east	right	middle	resolution	palestinian
3	middle	east	arab	palestinian	solution
4	peace	people	people	middle	east
5	territory	arab	palestinian	security	international
6	resolution	middle	international	people	israel
7	1967	peace	israel	israel	middle
8	palestinian	territory	kuwait	state	arab
9	israeli	state	right	international	people


Arab-Israeli conflict



Nuclear arms

	1970	1980	1990	2000	2010
0	nuclear	nuclear	nuclear	weapon	nuclear
1	disarmament	disarmament	weapon	nuclear	weapon
2	weapon	weapon	disarmament	convention	non
3	soviet	arm	treaty	arm	proliferation
4	arm	state	arm	treaty	arm
5	treaty	race	state	disarmament	treaty
6	union	military	chemical	proliferation	international
7	agreement	treaty	agreement	international	disarmament
8	power	soviet	proliferation	non	convention
9	state	power	soviet	destruction	state

Nuclear arms



Tutorials

<https://medium.com/@lettier/how-does-lda-work-ill-explain-using-emoji-108abf40fa7d>

<https://towardsdatascience.com/>

[latent-dirichlet-allocation-intuition-math-implementation-and-visualisation-63ccb616e094](https://towardsdatascience.com/latent-dirichlet-allocation-intuition-math-implementation-and-visualisation-63ccb616e094)

Summary

- Topic models automatically extract “semantic themes” from large document collections
- Use mixtures and latent variables
- Estimating Bayesian posterior done with Gibbs sampling
- Many extensions are possible