S&DS 265 / 565 Introductory Machine Learning

# **Trees**

October 4

#### Plan for this and next week

- Notes on assignments: select pages in Gradescope, rerun notebook, limit length of output, line wrap
- Assn 2 is out decision tree problem
- Quiz 3 Thursday; classification, SGD, bias-variance, trees
- Midterm exam: Tuesday October 18 (in class); practice exams posted to Canvas
- Questions?

#### You are here

4	Sept 20, 22	Stochastic gradient descent	CO SGD examples	Sept 20: Classification (continued) Sept 22: Stochastic gradient descent	ISL Section 6.2.2 ISL Section 10.7.2	Thu: Quiz 2
5	Sept 27, 29	Bias and variance, cross-validation	CO Bias- variance tradeoff CO Covid trends (revisited) CO California housing	Sept 27: Bias and variance Sept 29: Cross-validation	ISL Section 2.2 ISL Section 5.1	Thu: Assn 1 in
6	Oct 4, 6	Tree-based methods	Trees and forests Visualizing trees	Oct 4: Trees Oct 6: Forests	ISL Sections 8.1, 8.2	Thu: Quiz 3
7	Oct 11, 13	PCA and dimension reduction	CO PCA examples CO PCA revisited CO Used for regression	Oct 11: PCA Oct 13: PCA and review	ISL Section 12.2	Thu: Assn 2 in CO Assn3 out
8	Oct 18	Midterm exam (in class)			On Canvas: Practice midterms / Sample solns Midterm / Sample	

Trees provide ways of modeling nonlinear relationships by carving out *rectangular regions* in the feature space.

Trees provide ways of modeling nonlinear relationships by carving out *rectangular regions* in the feature space.

Response variables can be categorical or quantitative

Trees provide ways of modeling nonlinear relationships by carving out *rectangular regions* in the feature space.

- Response variables can be categorical or quantitative
- Yields a set of interpretable decision rules

Trees provide ways of modeling nonlinear relationships by carving out *rectangular regions* in the feature space.

- Response variables can be categorical or quantitative
- Yields a set of interpretable decision rules
- Predictive ability is mediocre, but can be improved by combining multiple trees (resampling, ensemble methods)

#### Titanic data



#### Titanic data

- Survived: Outcome of survival (0 = No; 1 = Yes)
- Pclass: Socio-economic class (1 = Upper class; 2 = Middle class; 3 = Lower class)
- · Name: Name of passenger
- · Sex: Sex of the passenger
- Age: Age of the passenger (Some entries contain NaN)
- . SibSp: Number of siblings and spouses of the passenger aboard
- · Parch: Number of parents and children of the passenger aboard
- · Ticket: Ticket number of the passenger
- · Fare: Fare paid by the passenger
- . Cabin Cabin number of the passenger (Some entries contain NaN)
- Embarked: Port of embarkation of the passenger (C = Cherbourg; Q = Queenstown; S = Southampton)

#### **Trees**




#### **Trees**




#### **Trees**



#### Modeling Titanic survival:




**Internal nodes** are points where the predictor space is split.




The internal node at the top is the **root** of the tree.

**Terminal nodes** (or **leaves**) are the ends of the tree where no further splitting occurs.




**Terminal nodes** (or **leaves**) are the ends of the tree where no further splitting occurs.



Denote these *J* regions as  $R_1, \ldots, R_J$ .

R



```
• R_1 = \{i : \text{sex}_i = \text{male} \cap \text{age}_i \ge 9.5\}

• R_2 = \{i : \text{sex}_i = \text{male} \cap \text{age}_i < 9.5 \cap \text{sibsp}_i \ge 2.5\}

• R_3 = \{i : \text{sex}_i = \text{male} \cap \text{age}_i < 9.5 \cap \text{sibsp}_i < 2.5\}

• R_4 = \{i : \text{sex}_i \ne \text{male}\}
```

# Let's go to the Titanic demo

#### Runs batted in (RBI)






2022 ✓ REGULAR SEASON ✓


PLAYERS	G	PA	AB	Н	R	28	3B	HR	RBI ▼	SB	
P. Alonso NYM	158	678	592	159	94	27	0	40	131	5	1
2 A. Judge NYY	155	689	563	175	131	28	0	61	130	16	3
3 J. Ramírez CLE	155	676	592	163	88	42	5	29	122	20	7

#### Regression tree example


Baseball hitter salaries (in \$1,000s — old data!):



### Regression tree example



### **Regression tree example**



Trace each test observation into a leaf  $R_j$  based on the sequence of conditions. Predict  $\hat{y}_{R_i}$  for all observations in  $R_j$ .

Trace each test observation into a leaf  $R_j$  based on the sequence of conditions. Predict  $\hat{y}_{R_i}$  for all observations in  $R_i$ .

 $\hat{y}_{R_j}$  is a function of all training observations *i* in  $R_j$ .

Trace each test observation into a leaf  $R_j$  based on the sequence of conditions. Predict  $\hat{y}_{R_i}$  for all observations in  $R_i$ .

 $\hat{y}_{R_i}$  is a function of all training observations *i* in  $R_j$ .

• Regression:  $\hat{y}_{R_j} = \bar{y}_{i:i \in R_j}$ 

Trace each test observation into a leaf  $R_j$  based on the sequence of conditions. Predict  $\hat{y}_{R_i}$  for all observations in  $R_i$ .

 $\hat{y}_{R_i}$  is a function of all training observations i in  $R_j$ .

- Regression:  $\hat{y}_{R_j} = \bar{y}_{i:i \in R_j}$
- Classification:  $\widehat{y}_{R_j} = \text{most frequently occurring class } y_i \text{ for } i \in R_j$

Trace each test observation into a leaf  $R_j$  based on the sequence of conditions. Predict  $\hat{y}_{R_i}$  for all observations in  $R_i$ .

 $\hat{y}_{R_i}$  is a function of all training observations i in  $R_j$ .

- Regression:  $\hat{y}_{R_j} = \bar{y}_{i:i \in R_j}$
- Classification:  $\widehat{y}_{R_j} = \text{most frequently occurring class } y_i \text{ for } i \in R_j$

Trace each test observation into a leaf  $R_j$  based on the sequence of conditions. Predict  $\hat{y}_{R_i}$  for all observations in  $R_i$ .

 $\hat{y}_{R_i}$  is a function of all training observations i in  $R_j$ .

- Regression:  $\hat{y}_{R_j} = \bar{y}_{i:i \in R_j}$
- Classification:  $\hat{y}_{R_j} = \text{most frequently occurring class } y_i \text{ for } i \in R_j$

Fitting a tree boils down to identifying the appropriate set of regions  $R_1, \ldots, R_J$  that "best" describes the relationship between X and y.

#### Tree building

We want to choose  $R_1, \ldots, R_J$  to minimize error:

$$\textit{RSS} = \sum_{j=1}^J \sum_{i \in R_j} (y_i - \bar{y}_{R_j})^2$$


### Tree building

We want to choose  $R_1, \ldots, R_J$  to minimize error:


$$RSS = \sum_{j=1}^{J} \sum_{i \in R_j} (y_i - \bar{y}_{R_j})^2$$


Tree building takes a *greedy* approach.


- Grow the tree by recursive binary splitting
- Prune back the tree





Where can we draw a horizontal or vertical line that best splits the data into two homogeneous parts?














## **Tree growth (Regression)**

① Cycle through predictors  $X_k$  for k = 1, ..., p. For each  $X_k$ ,

### **Tree growth (Regression)**

- ① Cycle through predictors  $X_k$  for k = 1, ..., p. For each  $X_k$ ,
  - (Quantitative  $X_k$ ) Consider cutpoints s (unique values of  $X_k$ ) that divide up the region into two parts:

$$R_1(k, s) = \{i | X_{ik} < s\}$$
 and  $R_2(k, s) = \{i | X_{ik} \ge s\}$ 

### **Tree growth (Regression)**


- ① Cycle through predictors  $X_k$  for k = 1, ..., p. For each  $X_k$ ,
  - (Quantitative  $X_k$ ) Consider cutpoints s (unique values of  $X_k$ ) that divide up the region into two parts:

$$R_1(k,s) = \{i | X_{ik} < s\}$$
 and  $R_2(k,s) = \{i | X_{ik} \ge s\}$ 


Evaluate (for regression trees):


$$Q_k(s) = \sum_{i:i \in R_1(k,s)} (y_i - \bar{y}_{R_1})^2 + \sum_{i:i \in R_2(k,s)} (y_i - \bar{y}_{R_2})^2$$

$$Q_k(s) = \sum_{i:i \in R_1(k,s)} (y_i - ar{y}_{R_1})^2 + \sum_{i:i \in R_2(k,s)} (y_i - ar{y}_{R_2})^2$$



$$Q_k(s) = \sum_{i:i \in R_1(k,s)} (y_i - ar{y}_{R_1})^2 + \sum_{i:i \in R_2(k,s)} (y_i - ar{y}_{R_2})^2$$






• 
$$R_1(RBI, 50)$$
:  $\bar{y}_{R_1} = 359$ 

• 
$$R_2(RBI, 50)$$
:  $\bar{y}_{R_2} = 753$ 

$$Q_{RBI}(50) = \sum_{i:i \in R_1} (y_i - 359)^2 + \sum_{i:i \in R_2} (y_i - 753)^2$$
$$= 13015000 + 30186039$$
$$= 43201039$$

25



- $R_1(RBI, 60)$ :  $\bar{y}_{R_1} = 405$
- $R_2(RBI, 60)$ :  $\bar{y}_{R_2} = 802$

$$Q_{RBI}(60) = \sum_{i:i \in R_1} (y_i - 405)^2 + \sum_{i:i \in R_2} (y_i - 805)^2$$
$$= 19186489 + 24943383$$
$$= 44129872$$

Compute  $Q_{RBI}(s)$  for all distinct values of RBI s.

### **Categorical predictors**

If a predictor  $X_k$  is categorical, then cut points are modified.

### **Categorical predictors**

If a predictor  $X_k$  is categorical, then cut points are modified.

Suppose  $X_k$  has unique values in  $\{A, B, C, D, E\}$ . Then, the possible splits include:

- {*D*} vs. {*A*, *B*, *C*, *E*}
- {*D*, *B*} vs. {*A*, *C*, *E*}
- ..

## **Categorical predictors**

If a predictor  $X_k$  is categorical, then cut points are modified.

Suppose  $X_k$  has unique values in  $\{A, B, C, D, E\}$ . Then, the possible splits include:

- {*D*} vs. {*A*, *B*, *C*, *E*}
- {*D*, *B*} vs. {*A*, *C*, *E*}
- ..

Every possible partition of the set of unique values into 2 subsets is considered, and again we identify the split producing the lowest resulting RSS.

- **1** Cycle through predictors  $X_k$  for k = 1, ..., p. For each  $X_k$ :
  - (Quantitative  $X_k$ ) Consider cutpoints s (unique values of  $X_k$ ) that divide up the region into two parts:

$$R_1(k,s) = \{i | X_{ik} < s\}$$
 and  $R_2(k,s) = \{i | X_{ik} \ge s\}$ 

Evaluate (for regression trees):

$$Q_k(s) = \sum_{i:i \in R_1(k,s)} (y_i - \bar{y}_{R_1})^2 + \sum_{i:i \in R_2(k,s)} (y_i - \bar{y}_{R_2})^2$$

▶ Find the value of s that minimizes  $Q_k(s)$ . Call this  $s_k$ .


- **①** Cycle through predictors  $X_k$  for k = 1, ..., p. For each  $X_k$ :
  - (Quantitative  $X_k$ ) Consider cutpoints s (unique values of  $X_k$ ) that divide up the region into two parts:


$$R_1(k,s) = \{i | X_{ik} < s\}$$
 and  $R_2(k,s) = \{i | X_{ik} \ge s\}$ 

Evaluate (for regression trees):

$$Q_k(s) = \sum_{i:i \in R_1(k,s)} (y_i - \bar{y}_{R_1})^2 + \sum_{i:i \in R_2(k,s)} (y_i - \bar{y}_{R_2})^2$$

- ▶ Find the value of s that minimizes  $Q_k(s)$ . Call this  $s_k$ .
- ② Find the predictor  $X_k$  with the minimum  $Q_1(s_1), Q_2(s_2), \ldots, Q_p(s_p)$ . Make the first binary partition along predictor  $X_k$  at cut point  $s_k$ .





Repeat the previous 2 steps on each of the resulting regions separately, iteratively. (Hence **recursive** binary partitioning.)

### **Bias-variance**

#### **Bias-variance**

- As tree is grown deeper, bias decreases
- But the variance increases
- How to choose the right size of tree?

Once we stop, we relabel the terminal nodes to be  $R_1, \ldots, R_J$  and compute  $\bar{y}_{R_i}$  (means within each region) to serve as  $\hat{y}$  values.

But when do we stop?

Once we stop, we relabel the terminal nodes to be  $R_1, \ldots, R_J$  and compute  $\bar{y}_{R_i}$  (means within each region) to serve as  $\hat{y}$  values.

But when do we stop?

Some possibilities:

number of observations in a node has reached a minimum

Once we stop, we relabel the terminal nodes to be  $R_1, \ldots, R_J$  and compute  $\bar{y}_{R_i}$  (means within each region) to serve as  $\hat{y}$  values.

But when do we stop?

#### Some possibilities:

- number of observations in a node has reached a minimum
- depth of tree has reached a maximum

Once we stop, we relabel the terminal nodes to be  $R_1, \ldots, R_J$  and compute  $\bar{y}_{R_i}$  (means within each region) to serve as  $\hat{y}$  values.

But when do we stop?

#### Some possibilities:

- number of observations in a node has reached a minimum
- depth of tree has reached a maximum
- grow until no further splits can reduce RSS by some amount

Once we stop, we relabel the terminal nodes to be  $R_1, \ldots, R_J$  and compute  $\bar{y}_{R_i}$  (means within each region) to serve as  $\hat{y}$  values.

But when do we stop?

#### Some possibilities:

- number of observations in a node has reached a minimum
- depth of tree has reached a maximum
- grow until no further splits can reduce RSS by some amount

Once we stop, we relabel the terminal nodes to be  $R_1, \ldots, R_J$  and compute  $\bar{y}_{R_i}$  (means within each region) to serve as  $\hat{y}$  values.

#### But when do we stop?

#### Some possibilities:

- number of observations in a node has reached a minimum
- depth of tree has reached a maximum
- grow until no further splits can reduce RSS by some amount

Many options – resulting in tuning parameters that are hard to deal with.


Another way to get around the overfitting problem is to grow a large tree and then **prune** it back.

Another way to get around the overfitting problem is to grow a large tree and then **prune** it back.

Typically, pruning involves looking at subtrees of the fully-grown tree, and comparing how well the subtrees perform.

Another way to get around the overfitting problem is to grow a large tree and then **prune** it back.

Typically, pruning involves looking at subtrees of the fully-grown tree, and comparing how well the subtrees perform.



How do we prune?

How do we prune?

cross validation

How do we prune?

- cross validation
- cost-complexity pruning

$$C(T) = \sum_{m=1}^{|T|} \sum_{i \in R_m} (y_i - \widehat{y}_{R_m})^2 + \alpha |T|$$

 $\alpha$  is a tuning parameter that controls for the complexity of the model.

$$C(T) = \sum_{m=1}^{|T|} \sum_{i \in R_m} (y_i - \widehat{y}_{R_m})^2 + \alpha |T|$$

 $\alpha$  is a tuning parameter that controls for the complexity of the model.

•  $\alpha = 0$  implies the full tree

$$C(T) = \sum_{m=1}^{|T|} \sum_{i \in R_m} (y_i - \widehat{y}_{R_m})^2 + \alpha |T|$$

 $\alpha$  is a tuning parameter that controls for the complexity of the model.

- $\alpha =$  0 implies the full tree
- Larger  $\alpha$  implies higher penalty for complexity of model

$$C(T) = \sum_{m=1}^{|T|} \sum_{i \in R_m} (y_i - \widehat{y}_{R_m})^2 + \alpha |T|$$

 $\alpha$  is a tuning parameter that controls for the complexity of the model.

- $\alpha =$  0 implies the full tree
- Larger  $\alpha$  implies higher penalty for complexity of model

$$C(T) = \sum_{m=1}^{|T|} \sum_{i \in R_m} (y_i - \widehat{y}_{R_m})^2 + \alpha |T|$$

 $\alpha$  is a tuning parameter that controls for the complexity of the model.

- $\alpha =$  0 implies the full tree
- Larger  $\alpha$  implies higher penalty for complexity of model

It is possible to efficiently identify a sequence of nested subtrees that are optimal for a sequence of increasing  $\alpha$ .

- Grow a big tree on a training set.
- ② Obtain a nested set of subtrees T<sub>L</sub> ⊂ · · · ⊂ T<sub>2</sub> ⊂ T<sub>1</sub> ⊂ T<sub>0</sub> corresponding to a sequence of α values.
- 3 Use K-fold cross-validation to identify the subtree/ $\alpha$  that does best.

#### Issues with trees

- Instability. Trees can have high variance. As data change, tree topology can change dramatically, making interpretation difficult
- Lack of smoothness. The splits lead to a "jagged" decision boundary. More of a problem for regression than classification
- Difficulty capturing additive structure, where the regression function is a sum of terms
- Predictive power is...meh

We'll talk about ways of addressing some of these next time

#### **Demos**

#### Some nice demonstrations of decision trees:

```
http://www.r2d3.us/
visual-intro-to-machine-learning-part-1/
http://www.r2d3.us/
visual-intro-to-machine-learning-part-2
```

### **Summary from today**

- Trees give interpretable, nonlinear prediction rules
- Deep trees have low bias, high variance
- Shallow trees have high bias, low variance
- Deep trees are pruned back using cross-validation to find best bias/variance tradeoff.