


S&DS 365 / 665

Intermediate Machine Learning

Deep Reinforcement Learning

November 4

Yale

Version of 2026/11/08 at 17:16

Reminders

- Assignment 3 due tomorrow
- Assignment 4 out today (GNNs and Deep RL)
- Quiz 4 next week (Wednesday, in class)
- Project proposals due next week (Thursday)
- Exam 1 sample solutions posted to Canvas

Outline

- Quick recap
  - *Q*-learning
  - Bellman equation
- Deep reinforcement learning
- Policy gradient methods

Main reference: “Reinforcement Learning: An Introduction” (Second Edition), Richard S. Sutton and Andrew G. Barto

Reinforcement learning: Formalization


- The environment is in state s at a given time
- The agent takes action a
- The environment transitions to state $s' = \text{next}(s, a)$
- The agent receives reward $r = \text{reward}(s, a)$

Reinforcement learning: Formalization

- The environment is in state s at a given time
- The agent takes action a
- The environment transitions to state $s' = \text{next}(s, a)$
- The agent receives reward $r = \text{reward}(s, a)$

This is said to be a *Markov decision process*. It's "Markov" because the next state only depends on the current state and the action selected. It's a "decision process" because the agent is making choices of actions in a sequential manner.


Keep in mind the basic setup




"Reinforcement Learning: An Introduction" (Second Edition), Richard S. Sutton and Andrew G. Barto

Recall: Taxi problem

A taxicab drives around the environment, picking up and delivering a passenger at four locations




```
+---------+
|R: | : :G|
| : | : :▄|
| : : : : |
| | : | : |
|Y| : |B: |
+---------+
  (East)
```



Question


For a fixed passenger location and destination, the value function $v(\texttt{row}, \texttt{col})$ assigns a value to each of the $25 = 5 \times 5$ grid points.



Is the passenger waiting, or in the taxi?

Question

For a fixed passenger location and destination, the value function $v(\texttt{row}, \texttt{col})$ assigns a value to each of the $25 = 5 \times 5$ grid points.



Is the passenger waiting, or in the taxi?

Bellman equation



The optimal value function is the largest expected discounted long term reward starting from that state.

---

https://en.wikipedia.org/wiki/Richard_E._Bellman

Bellman equation: Deterministic case

The optimality condition for the value function v_* is

$$v_*(s) = \max_a \Big\{ \text{reward}(s, a) + \gamma v_*(\text{next}(s, a)) \Big\}$$

Bellman equation: Deterministic case

The optimality condition for the Q-function is

$$Q_*(s,a) = \text{reward}(s,a) + \gamma \max_{a'} Q_*(\text{next}(s,a), a')$$

and then $v_*(s) = \max_{a'} Q_*(s,a')$

Q-learning update

Note how this makes sense in terms of the update rule:

$$Q(s,a) \longleftarrow Q(s,a) + \alpha\Big(\text{reward}(s,a) + \gamma \max_{a'} Q(\text{next}(s,a), a') - Q(s,a)\Big)$$

Bellman equation: Deterministic case

If we know Q_*, we know v_*:

Bellman equation: Deterministic case

If we know Q_*, we know v_*:

$$
\begin{aligned}
v_*(s) &= \max_a Q_*(s,a) \\
&= \max_a \left\{ \text{reward}(s,a) + \gamma \max_{a'} Q_*(\text{next}(s,a), a') \right\} \\
&= \max_a \left\{ \text{reward}(s,a) + \gamma v_*(\text{next}(s,a)) \right\}
\end{aligned}
$$

which is the Bellman equation

Bellman equation: Random environments

Value function optimality

$$v_*(s) = \max_a \mathbb{E}\Big[R_{t+1} + \gamma v_*(S_{t+1}) \mid S_t = s, A_t = a\Big]$$

Bellman equation: Random environments

Q-function optimality

$$Q_*(s,a) = \mathbb{E}\Big[R_{t+1} + \gamma \max_{a'} Q_*(S_{t+1}, a') \mid S_t = s, A_t = a\Big]$$

Deep reinforcement learning: Motivation

- Direct implementation of Q-learning only possible for small state and action spaces
- For large state spaces we need to map states to “features”
- Deep RL uses a multilayer neural network to learn these features and the Q-function

Starting point: Bellman equation

$$Q(s, a; \theta) = \mathbb{E}\left[R_{t+1} + \gamma \max_{a'} Q(S_{t+1}, a'; \theta) \mid S_t = s, A_t = a\right]$$

- The parameters θ are weights in a neural network
- The state S_{t+1} is the input to the network
- Each possible action a is assigned a value by the network

How do we solve this implicit equation for the network parameters?

Strategy: Regression

Objective:

$$Q(s, a; \theta) = \mathbb{E}\Big[R_{t+1} + \gamma \max_{a'} Q(S_{t+1}, a'; \theta) \mid S_t = s, A_t = a\Big]$$

Let y_t be a sample from this conditional distribution:

$$y_t = R_{t+1} + \gamma \max_{a'} Q(S_{t+1}, a'; \theta_{\text{current}})$$

Adjust the parameters θ to make the squared error small (SGD):

$$(y_t - Q(s, a; \theta))^2$$

Strategy

Adjust the parameters θ to make the squared error small

$$(y_t - Q(s, a; \theta))^2$$

How? Carry out SGD

$$\theta \longleftarrow \theta + \eta \left(y_t - Q(s, a; \theta)\right) \nabla_\theta Q(s, a; \theta)$$

using backpropagation!

When does learning take place?


Recall from Bellman equation that y_t is an expectation.

Learning takes place when expectations are violated. The receipt of the reward itself does not cause changes.

Space Invaders




Space Invaders: Q-learning framework



Space Invaders: Q-learning framework



(multiple frames)



Early DeepMind work

- Images cropped to 84 $\times$ 84 pixels; 128 color palette; input sequence of 4 frames; reward is score
- 3-layer convolutional neural network, ReLU nonlinearity, final layer fully connected, 256 neurons
- *Q*-learning carried out over minibatches of playing sequences that are "remembered and replayed"

"Playing Atari with Deep Reinforcement Learning," Mnih et al., DeepMind Technologies, 2013.
Larger versions reached human level performance on 29/49 games.
https://patentimages.storage.googleapis.com/71/91/4a/c5cf4ffa56f705/US20150100530A1.pdf
Google acquired DeepMind and used Deep *Q*-learning to save energy (and money) in data centers.

Early DeepMind work

Role of replay buffer (inspired by neuroscience, “dreaming”)

- Prevent “forgetting” how to play early parts of a game
- Remove correlations between nearby state transitions
- Prevent cycling behavior, due to target changing

“Playing Atari with Deep Reinforcement Learning,” Mnih et al., DeepMind Technologies, 2013.
Larger versions reached human level performance on 29/49 games.
https://patentimages.storage.googleapis.com/71/91/4a/c5cf4ffa56f705/US20150100530A1.pdf
Google acquired DeepMind and used Deep *Q*-learning to save energy (and money) in data centers.

Early DeepMind work

- Identical architecture used for seven games (Beam Rider, Breakout, Enduro, Pong, Q*bert, Seaquest, Space Invaders)
- Each game trained for 100 epochs (50,000 minibatch weight updates / epoch), about 50 hours
- Surpasses human expert on three of seven games

"Playing Atari with Deep Reinforcement Learning," Mnih et al., DeepMind Technologies, 2013.
Larger versions reached human level performance on 29/49 games.
https://patentimages.storage.googleapis.com/71/91/4a/c5cf4ffa56f705/US20150100530A1.pdf
Google acquired DeepMind and used Deep *Q*-learning to save energy (and money) in data centers.

Payoff

SUSTAINABILITY


DeepMind AI reduces energy used for cooling Google data centers by 40%

Jul 20, 2016 · 4 min read

R Rich Evans
Research Engineer, DeepMind


 Jim Gao
Data Center Engineer, Google

Share




Payoff

We tested our model by deploying on a live data center. The graph below shows a typical day of testing, including when we turned the machine learning recommendations on, and when we turned them off.




Google DeepMind graph showing results of machine learning test on power usage effectiveness in Google data centers

Second generation DQN



https://storage.googleapis.com/deepmind-data/assets/papers/DeepMindNature14236Paper.pdf

Second generation DQN: Interpretation




t-SNE represenations of last layer for Space Invaders, color-coded for v_*.

Further examples

BLOG POST
RESEARCH

17 JUN 2016

Deep Reinforcement Learning



SHARE


AUTHORS

DS David Silver

Humans excel at solving a wide variety of challenging problems, from low-level motor control through to high-level cognitive tasks. Our goal at DeepMind is to create artificial agents that can achieve a similar level of performance and generality. Like a human, our agents learn for themselves to achieve successful strategies that lead to the greatest long-term rewards. This paradigm of learning by trial-and-error, solely from rewards or punishments, is known as reinforcement learning (RL). Also like a human, our agents construct and learn their own knowledge directly from raw inputs, such as vision, without any hand-engineered features or domain heuristics. This is achieved by deep learning of neural

https://deepmind.com/blog/article/deep-reinforcement-learning

Assignment 4: FlapPy bird



Summary: Deep Q-learning

- For large state spaces, can't estimate Q-function directly
- Deep Q-learning: Using a (deep) neural network with state as input, value assigned to each possible action
- Success at games (Backgammon, Atari, Go)
- Close connection to neuroscience of behavior and reward