arXiv:2601.07767v1 [cs.LG] 12 Jan 2026

Are LLM Decisions Faithful to Verbal Confidence?

Jiawei Wang **Yanfei Zhou** **Siddartha Devic** **Deqing Fu**
University of Southern California
{jwang535,yanfeizh,devic,deqingfu}@usc.edu

Abstract

Large Language Models (LLMs) can produce surprisingly sophisticated estimates of their own uncertainty. However, it remains unclear to what extent this expressed confidence is tied to the reasoning, knowledge, or decision making of the model. To test this, we introduce **RiskEval**: a framework designed to evaluate whether models adjust their abstention policies in response to varying error penalties. Our evaluation of several frontier models reveals a critical dissociation: models are neither cost-aware when articulating their verbal confidence, nor strategically responsive when deciding whether to engage or abstain under high-penalty conditions. Even when extreme penalties render frequent abstention the mathematically optimal strategy, models almost never abstain, resulting in utility collapse. This indicates that *calibrated verbal confidence scores* may not be sufficient to create trustworthy and interpretable AI systems, as current models lack the strategic agency to convert uncertainty signals into optimal and risk-sensitive decisions.

1 Introduction

Accurate uncertainty quantification in LLMs is a promising approach to improving trust and transparency towards humans (Geng et al., 2024). One alluring way to quantify uncertainty in LLMs is "verbal confidence" estimation, which simply *asks* the LLM to give its confidence after answering a question (Damani et al., 2025; Zhang et al., 2025a,b). Prior work suggests that verbal confidence can be reasonably calibrated across models and datasets, indicating that LLMs often possess meaningful awareness of their own uncertainty (Yoon et al., 2025; Xiong et al., 2024; Tian et al., 2023; Lin et al., 2022).

Nonetheless, although models may be able to produce accurate verbal confidence estimates, we still do not perfectly understand the *mechanisms* behind why these abilities may emerge. One way to approach this question is to ask whether verbal confidence estimates impact an LLM's *actions* or *decisions* in any way. In other words, are the generated confidence estimates *faithful* to the actions of the model?



Figure 1: **The RiskEval Framework.** We evaluate strategic abstention by prompting models with varying error penalties (λ) ranging from 0 to 100. Although models successfully verbalize uncertainty, they fail to translate this signal into decision-making. As illustrated, abstention rates on the HLE benchmark (Phan et al., 2025) remain largely invariant to increasing penalties.

We examine this using an evaluation framework we term **RiskEval**, in which we allow a model to answer or abstain on questions. We then measure its abstention rate for different penalty values given within the input prompt (see Figure 1). Combined with simultaneously eliciting the model's verbal

confidence scores, **RiskEval** provides a sandbox for understanding whether these verbal confidence estimates are indeed faithful and consistent with the actions that the model takes.

Our Contributions. We evaluate if LLMs utilize self-assessed verbal confidence to inform their decisions. Specifically, we test their ability to navigate the trade-off between *answering* and *abstaining* under penalties defined in the prompt. Our analysis reveals three main findings:

- *Invariance to Risk.* Across models and datasets, increasing penalties has a negligible effect on model behavior. Neither the self-evaluated confidence nor the decision to answer or abstain changes significantly across incorrect answer penalties ranging in $[0.1, 100]$. This suggests that current training methods or model leaderboard practices do not result in risk-aware agents (Kalai et al., 2025).

- *Utility Degradation.* Models fail to maximize expected utility. In high-penalty regimes, the rigid answering-heavy policy leads to large losses compared to optimal post-hoc abstention strategies utilizing model reported verbal confidence scores.

- *Decoupling of Confidence and Policy.* Models often "know" their own uncertainty — in the sense that the verbal confidence estimates are useful / calibrated — yet mostly fail to convert this knowledge into a good abstention policy. Despite prompted instructions to avoid penalties, models maintain a high inclination to respond (Kirichenko et al., 2025).

Overall, our investigations align with the need to evaluate models on strategic reliability rather than only overall accuracy (Kalai et al., 2025; Jia et al., 2024; Ross et al., 2024). Our findings also potentially call into question the validity and faithfulness of verbal confidence estimation for LLMs in decision-making contexts.

2 Problem Setup

We model answering and abstaining within a utility maximization framework. Let x be a query, $d \in \{\text{answer}, \text{abstain}\}$ be the model $\mathcal{M}$'s decision to answer or abstain, and y be the model's answer to x if they decide to answer; $y = \varnothing$ otherwise. Let y^* be the ground-truth label. The model $\mathcal{M}$ produces a reported confidence estimate $c := c_{\mathcal{M}}(x) \in [0, 1]$, which we treat as its estimate of $P_{\mathcal{M}}(y = y^*|x)$, the model's true underlying confidence.

We introduce a penalty parameter $\lambda \geq 0$ for incorrect answers. The utility function U for a decision d is defined as follows. When the model abstains $U = 0$. When the model decides to answer, $U = +1$ if the model is correct (i.e., $y = y^*$), and $U = -\lambda$ if the model is incorrect.

A rational agent that always maximizes expected utility only chooses to answer when the expected gain exceeds the utility of abstention, i.e., 0. This yields the optimal decision threshold $\tau(\lambda) = \frac{\lambda}{1+\lambda}$, such that $\mathbb{E}[U_{\text{ans}}] = c \cdot 1 + (1 - c)(-\lambda) \geq 0 = \mathbb{E}[U_{\text{abs}}]$ when $c \geq \tau(\lambda)$.

Define the binary action $\pi \in \{0, 1\}$, where $\pi = 1$ denotes answer and $\pi = 0$ denotes abstain. The Bayes-optimal policy under the model's belief c is

$$\pi^*(c, \lambda) = \mathbb{I}\left(c \geq \frac{\lambda}{1 + \lambda}\right). \tag{1}$$

We evaluate how well the model's realized decisions align with π^* and how well confidence separates correct from incorrect answers.

Policy Consistency (PC) measures the frequency with which the model's actual decision $\pi_{\mathcal{M}}$ aligns with the optimal policy π^* given the model's own confidence c. Let x be drawn from a dataset $\mathcal{D}$.

$$\text{PC}(\mathcal{M}, \mathcal{D}) = \mathbb{E}_{x \sim \mathcal{D}}\left[\mathbb{I}\left(\pi_{\mathcal{M}}(c, \lambda) = \pi^*(c, \lambda)\right)\right],$$

where $c := c_{\mathcal{M}}(x)$ is the model verbal confidence. A higher PC implies a model better utilizes its own confidence to make decisions.

Expected and Normalized Regret ($\mathcal{R}$ and $\overline{\mathcal{R}}$) quantify the utility lost due to suboptimal decisions. Importantly, this expectation is taken under the model's stated belief c_i, not the true conditional correctness probability. For a single query, regret is the difference between the maximum possible expected utility and the actual expected utility achieved: $\mathcal{R} = \max(0, \mathbb{E}[U_{\text{ans}}]) - \mathbb{E}[U_{\pi_{\mathcal{M}}}]$. As explicitly derived in §A, if the model answers when it should abstain (or vice versa), the regret is $\mathcal{R} = (1+\lambda) \cdot |c_{\mathcal{M}}(x) - \tau(\lambda)| \cdot \mathbb{I}(\pi_{\mathcal{M}} \neq \pi^*)$. Since raw regret $\mathcal{R}$ scales linearly with the penalty magnitude $(1+\lambda)$, we normalize it to measure decision error in probability space. This metric represents the distance between the model's confidence and the optimal threshold:

$$\overline{\mathcal{R}} = \frac{\mathcal{R}}{1 + \lambda} = |c_{\mathcal{M}}(x) - \tau(\lambda)| \cdot \mathbb{I}(\pi_{\mathcal{M}} \neq \pi^*).$$



Figure 2: **Verbalized Confidence is Invariant to Risk.** The flat trajectories show that internal uncertainty estimates remain stable despite increasing penalties, confirming that the failure to abstain is not due to signal degradation.



Figure 3: **Normalized Average Utility Collapses Under Risk.** As penalties increase, normalized utility drops sharply into negative values on high-uncertainty benchmarks (HLE, GPQA). This confirms that models persist in answering incorrectly even when the cost of error far outweighs the potential reward.

Area Under the Accuracy-Rejection Curve (AUARC). To assess confidence ranking quality independent of any specific λ, we compute AUARC. Let $\mathcal{A}(r)$ denote the accuracy on the retained set after discarding the lowest-confidence fraction r for which AUARC $= \int_0^1 \mathcal{A}(r)\,dr$. A higher AUARC indicates that the model assigns lower confidence to incorrect answers.

We defer more details and metrics to §A. For each model $\mathcal{M}$ and evaluation dataset $\mathcal{D}$, we vary the penalty strength λ in the evaluation prompt to test both model's confidence calibration and their decision-making strategies (see §B.1).

3 Experiments

Models and Datasets. We evaluate a diverse set of models spanning different capability levels and reasoning styles. Please refer to §B for the full list of models. We evaluate them on three datasets spanning a range of difficulties: HLE (Phan et al., 2025), GPQA Diamond (Rein et al., 2024), and GSM8K (Cobbe et al., 2021).

Metrics and Evaluation. Using the **RiskEval** decision penalty framework in §2, we evaluate behavior using metrics defined in §A capturing realized performance, decision consistency with the optimal policy, and calibration quality. For each model and dataset, we use the prompts defined in §B.1 to elicit either solely a decision, or both a decision and a confidence score. We employ `GPT-4o-mini` as a judge; we defer to §B.1 for details and prompts.

Main Results. Across all benchmarks, we observe that LLMs do not adapt their decision policies in response to changing risk, even when abstention is explicitly incentivized.

Failure to Adapt Decision Rules. As penalties increase to regimes where optimal policies require widespread abstention, models continue to answer almost all questions. Correspondingly, Figure 4 shows high policy consistency at low penalties ($\lambda \leq 5$), followed by abrupt degradation rather than smooth adjustment as penalties grow ($\lambda \geq 10$). This indicates that models do not implement penalty-dependent decision thresholds; instead, they transition into unstable behavior without coherent abstention strategies.

Low Abstention Rate Causes Utility Collapse. Because abstention remains low while error rates remain non-zero, model utility deteriorates rapidly as penalties increase. Figure 6 shows that mean normalized regret rises nearly monotonically with penalty on high-uncertainty benchmarks (HLE, GPQA), indicating large, avoidable losses relative to optimal policies. Figure 3 further demonstrates that penalty-normalized average points become strongly negative under high penalties.



Figure 4: **Policy Consistency Collapses Under High Penalties.** We measure how often model decisions align with the optimal policy induced by their confidence. The sharp drop on HLE and GPQA shows that models fail to adjust their decision thresholds $\tau(\lambda)$ as penalties rise, persisting in answering when abstention is optimal.

Model	Calibration Metrics				Decision-Making Metrics			
	AUARC ↑	ECE ↓	Brier ↓	Conf.	Pol. Con. ↑	N. Reg. ↓	Norm. Utility ↑	
							w/ $\pi_{\mathcal{M}}$	w/ π^*
`Gemini-3-Flash`	**0.533**	0.499	0.485	0.888	0.403	0.084	**-0.517**	-0.169 (+ 0.347)
`Gemini-2.5-Flash`	0.174	0.726	0.701	0.847	**0.619**	0.117	-0.775	-0.462 (+ 0.313)
`GPT-5-mini`	0.265	0.580	0.516	0.670	0.256	0.159	**-0.537**	-0.087 (+ 0.450)
`GPT-5-nano`	0.178	**0.479**	**0.332**	0.506	0.192	0.368	-0.688	**-0.004** (+ 0.685)
`GPT-4.1-mini`	0.049	0.841	0.774	0.907	0.148	**0.059**	-0.853	-0.169 (+ 0.683)
`Llama-4-Maverick`	0.041	0.786	0.683	0.772	0.274	0.135	-0.842	-0.185 (+ 0.657)
`DeepSeek-V3.2`	0.133	0.741	0.672	0.847	0.181	0.097	-0.795	-0.115 (+ 0.680)
`Gemma-3n-E4B`	0.058	0.846	0.791	0.875	0.373	0.069	-0.862	-0.295 (+ 0.567)
`DeepSeek-V3.2-Think`	**0.429**	**0.474**	**0.424**	0.761	0.119	0.174	-0.610	**-0.033** (+ 0.577)
`Qwen3-Next-Think`	0.175	0.816	0.783	0.935	**0.492**	**0.025**	-0.790	-0.369 (+ 0.421)

Table 1: **Results on HLE**. We report both **Calibration metrics** and **Decision-Making metrics** (Policy Consistency, and Penalty-Normalized Regret and Utility). Results are averaged over the **high-penalty regime** ($\lambda \geq 10$) to highlight behavior under risk. **Red** and **Blue** indicate the best and second-best results. The significant gains from using the optimal policy π^* confirms that calibration signals are often useful for but not used by the models.

Prompting Fails to Induce Abstention. Even when models are explicitly instructed to condition abstention decisions on internal uncertainty, behavior changes are negligible (see §B.4). In our ablation study, we appended a directive for models to "[u]se this confidence to decide whether to answer or abstain" to avoid penalties. Despite this, we observed invariant trajectories for both abstention rates and normalized regret compared to the baseline (Fig. 7). Furthermore, differential analysis confirms that shifts in policy consistency were near-zero across benchmarks (Fig. 8). This suggests that the observed rigidity is not due to underspecified instructions, but reflects deeper behavioral priors favoring always answering (Kirichenko et al., 2025).

Scaffold with π^* Improves Utility. As discussed earlier, models fail to adhere to the mathematically optimal decision policy π^*, especially under high-risk regime. It's natural to introduce the scaffolding procedure: instead of relying on model's own abstention policy $\pi_{\mathcal{M}}$, we instead enforce the optimal policy π^* *post-hoc*, using model's verbal confidence and the known penalty level λ. As shown in Table 1, the π^* scaffolding could improve utility across models on HLE evaluation. This observation remains the same for low-risk environment (see Table 2) and easier tasks (GSM8K and GPQA Diamond, see Tables 3 to 6).

Taken together, these results demonstrate a critical dissociation between information availability and decision execution. While calibration-related metrics remain stable across models (Fig. 5), decision-level outcomes exhibit limited policy variation and negative average utility (Table 1). Moreover, increasing penalties does not substantially affect answer accuracy or reported confidence (Fig. 2), indicating that the observed failures arise from a lack of decision-level adaptation rather than changes in predictive behavior.

4 Related Work

Uncertainty Quantification for LLMs largely asks whether models can report reliable confidence, typically via ECE/reliability diagrams or related correlation metrics rather than downstream decision. Tian et al. (2023) shows that RLHF-tuned LMs often yield better-calibrated verbalized confi-

dence than raw token probabilities under standard QA-style evals. Subsequent work improves confidence estimation and evaluation via post-hoc calibration of verbalized probabilities (Zhang et al., 2024b) or identifies complementary uncertainty signals for reasoning models based on process features such as trace length (Devic et al., 2025a). Like our work, Devic et al. (2025b) also question the assumptions on whether calibrated uncertainty estimates are useful to human users, although in our work we stress that the uncertainty estimates may not even be faithful to actions taken by the LLM. Overall, this line establishes that confidence can be informative, but it rarely tests whether models use confidence to choose actions under changing utilities.

Abstention and selective prediction in LLMs. Recent work studies abstention and selective answering in large language models to address safety, hallucination, and reliability concerns (Kalai et al., 2025; Kirichenko et al., 2025; Tayebati et al., 2025). Abstention methods concentrate at the alignment (Yang et al., 2024; Zhang et al., 2024a; Neeman et al., 2023; Ren et al., 2023) and inference (Feng et al., 2024; Kapoor et al., 2024; Cole et al., 2023) stages. In contrast, we evaluate whether a *frozen* LLM can adapt its abstention behavior to changing error penalties at inference time, isolating strategic adaptivity from learned refusal.

Decision-theoretic and behavioral evaluation of LLM behavior. Prior studies quantify decision-theoretic preferences such as risk attitudes and loss aversion, and compare LLM behavior against rational or human benchmarks (Jia et al., 2024; Ross et al., 2024). Related work further examines risk-sensitive and socially conditioned decision-making, documenting systematic deviations under different framings (Erdem and Ashok, 2026; Liu et al., 2025a; Xiao and Wang, 2025). In contrast, we test *strategic responsiveness*: whether a frozen model adapts its answer-versus-abstain policy when the utility landscape changes.

5 Discussions and Conclusion

Our results demonstrate a fundamental limitation in current LLMs: the disconnect between information and action. While models can often accurately verbalize their uncertainty, they fail to use this information to minimize loss. Even under severe penalties, models act as if the cost of error is negligible, leading to catastrophic utility collapse. This suggests that current safety training produces models that "know" they might be wrong but lack the agency or strategy to act on that risk.

Ideally, a reliable agent should exhibit consistency between its internal belief and its external action. The failure to achieve this consistency undermines the deployment of LLMs in high-stakes environments where errors have real-world costs. Future work may therefore involve training methodologies that directly penalize risk-insensitive behavior (Ross et al., 2024), or inference-time frameworks like DeLLMa (Liu et al., 2025b) that mathematically enforce optimal decision boundaries. Ultimately, a trustworthy model must do more than state its confidence; it must also act accordingly.

Limitations

Dependency on Verbalized Confidence. Our analysis relies on verbalized confidence as the primary proxy for the model's internal belief state. While prior work and our own calibration results suggest these estimates are useful, they may not perfectly capture the model's true epistemic uncertainty. For proprietary API models where access to raw log-probabilities or internal activations is restricted, verbal elicitation remains a necessary constraint. It is possible that a model's "true" internal probability is better aligned with its decision to answer, even if its verbalized output is decoupled.

Scope of Tasks. Our evaluation focuses on benchmarks (HLE, GPQA, GSM8K) where correctness is verifiable. The dynamics of confidence and abstention may differ in open-ended generation, creative writing, or dialogue tasks where "utility" and "penalty" are subjective and the boundary between a correct and incorrect response is less defined.

Acknowledgments

We thank Yu Feng and Ollie Liu for discussions on uncertainty quantification in LLMs.

References

Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, Christopher Hesse, and John Schulman. 2021. Training verifiers to solve math word problems. *Preprint*, arXiv:2110.14168.

Jeremy Cole, Michael Zhang, Daniel Gillick, Julian Eisenschlos, Bhuwan Dhingra, and Jacob Eisenstein. 2023. Selectively answering ambiguous questions. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 530–543, Singapore. Association for Computational Linguistics.

Mehul Damani, Isha Puri, Stewart Slocum, Idan Shenfeld, Leshem Choshen, Yoon Kim, and Jacob Andreas. 2025. Beyond binary rewards: Training lms to reason about their uncertainty. *Preprint*, arXiv:2507.16806.

DeepSeek-AI. 2025. Deepseek-v3.2: Pushing the frontier of open large language models. *Preprint*, arXiv:2512.02556.

Siddartha Devic, Charlotte Peale, Arwen Bradley, Sinead Williamson, Preetum Nakkiran, and Aravind Gollakota. 2025a. Trace length is a simple uncertainty signal in reasoning models. *Preprint*, arXiv:2510.10409.

Siddartha Devic, Tejas Srinivasan, Jesse Thomason, Willie Neiswanger, and Vatsal Sharan. 2025b. From calibration to collaboration: Llm uncertainty quantification should be more human-centered. *arXiv preprint arXiv:2506.07461*.

Orhan Erdem and Ragavi Pobbathi Ashok. 2026. Llms are not weird: Comparing ai and human financial decision-making. *Journal of Behavioral and Experimental Economics*, 120:102505.

Shangbin Feng, Weijia Shi, Yike Wang, Wenxuan Ding, Orevaoghene Ahia, Shuyue Stella Li, Vidhisha Balachandran, Sunayana Sitaram, and Yulia Tsvetkov. 2024. Teaching LLMs to abstain across languages via multilingual feedback. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 4125–4150, Miami, Florida, USA. Association for Computational Linguistics.

Gemini Team, Google. 2025. Gemini 2.5: Pushing the frontier with advanced reasoning, multimodality, long context, and next generation agentic capabilities. *Preprint*, arXiv:2507.06261.

Gemma Team. 2025. Gemma 3 technical report. *Preprint*, arXiv:2503.19786.

Jiahui Geng, Fengyu Cai, Yuxia Wang, Heinz Koeppl, Preslav Nakov, and Iryna Gurevych. 2024. A survey of confidence estimation and calibration in large language models. In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 6577–6595.

Google. 2025. Gemini 3 flash: frontier intelligence built for speed. Google product blog post. Published Dec 17, 2025.

Jingru Jia, Zehua Yuan, Junhao Pan, Paul E. McNamara, and Deming Chen. 2024. Decision-making behavior evaluation framework for llms under uncertain context. In *Advances in Neural Information Processing Systems*, volume 37, pages 113360–113382. Curran Associates, Inc.

Adam Tauman Kalai, Ofir Nachum, Santosh S. Vempala, and Edwin Zhang. 2025. Why language models hallucinate. *Preprint*, arXiv:2509.04664.

Sanyam Kapoor, Nate Gruver, Manley Roberts, Arka Pal, Samuel Dooley, Micah Goldblum, and Andrew Wilson. 2024. Calibration-tuning: Teaching large language models to know what they don't know. In *Proceedings of the 1st Workshop on Uncertainty-Aware NLP (UncertaiNLP 2024)*, pages 1–14, St Julians, Malta. Association for Computational Linguistics.

Polina Kirichenko, Mark Ibrahim, Kamalika Chaudhuri, and Samuel Bell. 2025. Abstentionbench: Reasoning LLMs fail on unanswerable questions. In *The Thirty-ninth Annual Conference on Neural Information Processing Systems Datasets and Benchmarks Track*.

Stephanie Lin, Jacob Hilton, and Owain Evans. 2022. Teaching models to express their uncertainty in words. *Transactions on Machine Learning Research*.

Jiaxin Liu, Yixuan Tang, Yi Yang, and Kar Yan Tam. 2025a. Evaluating and aligning human economic risk preferences in LLMs. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 18185–18199, Suzhou, China. Association for Computational Linguistics.

Ollie Liu, Deqing Fu, Dani Yogatama, and Willie Neiswanger. 2025b. DeLLMa: Decision making under uncertainty with large language models. In *The Thirteenth International Conference on Learning Representations*.

Meta AI. 2025. The llama 4 herd: The beginning of a new era of natively multimodal intelligence. Meta AI blog post. Published Apr 5, 2025.

Ella Neeman, Roee Aharoni, Or Honovich, Leshem Choshen, Idan Szpektor, and Omri Abend. 2023. DisentQA: Disentangling parametric and contextual knowledge with counterfactual question answering. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 10056–10070, Toronto, Canada. Association for Computational Linguistics.

OpenAI. 2025a. Gpt-5 system card. PDF. Published Aug 13, 2025.

OpenAI. 2025b. Introducing gpt-4.1 in the api. OpenAI product post. Published Apr 14, 2025.

Long Phan, Alice Gatti, Ziwen Han, Nathaniel Li, Josephina Hu, Hugh Zhang, Chen Bo Calvin Zhang, Mohamed Shaaban, John Ling, Sean Shi, Michael Choi, Anish Agrawal, Arnav Chopra, Adam Khoja,

Ryan Kim, Richard Ren, Jason Hausenloy, Oliver Zhang, Mantas Mazeika, and 1093 others. 2025. Humanity's last exam. *Preprint*, arXiv:2501.14249.

Qwen Team. 2025. Qwen3 technical report. *Preprint*, arXiv:2505.09388.

David Rein, Betty Li Hou, Asa Cooper Stickland, Jackson Petty, Richard Yuanzhe Pang, Julien Dirani, Julian Michael, and Samuel R. Bowman. 2024. GPQA: A graduate-level google-proof q&a benchmark. In *First Conference on Language Modeling*.

Jie Ren, Yao Zhao, Tu Vu, Peter J. Liu, and Balaji Lakshminarayanan. 2023. Self-evaluation improves selective generation in large language models. In *Proceedings on "I Can't Believe It's Not Better: Failure Modes in the Age of Foundation Models" at NeurIPS 2023 Workshops*, volume 239 of *Proceedings of Machine Learning Research*, pages 49–64. PMLR.

Jillian Ross, Yoon Kim, and Andrew Lo. 2024. LLM economicus? mapping the behavioral biases of LLMs via utility theory. In *First Conference on Language Modeling*.

Sina Tayebati, Divake Kumar, Nastaran Darabi, Dinithi Jayasuriya, Ranganath Krishnan, and Amit Ranjan Trivedi. 2025. Learning conformal abstention policies for adaptive risk management in large language and vision-language models. *Preprint*, arXiv:2502.06884.

Katherine Tian, Eric Mitchell, Allan Zhou, Archit Sharma, Rafael Rafailov, Huaxiu Yao, Chelsea Finn, and Christopher Manning. 2023. Just ask for calibration: Strategies for eliciting calibrated confidence scores from language models fine-tuned with human feedback. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 5433–5442, Singapore. Association for Computational Linguistics.

Feng Xiao and XT XiaoTian Wang. 2025. Evaluating the ability of large Language models to predict human social decisions. *Scientific Reports*, 15(1):32290.

Miao Xiong, Zhiyuan Hu, Xinyang Lu, YIFEI LI, Jie Fu, Junxian He, and Bryan Hooi. 2024. Can LLMs express their uncertainty? an empirical evaluation of confidence elicitation in LLMs. In *The Twelfth International Conference on Learning Representations*.

Yuqing Yang, Ethan Chern, Xipeng Qiu, Graham Neubig, and Pengfei Liu. 2024. Alignment for honesty. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*.

Dongkeun Yoon, Seungone Kim, Sohee Yang, Sunkyoung Kim, Soyeon Kim, Yongil Kim, Eunbi Choi, Yireun Kim, and Minjoon Seo. 2025. Reasoning models better express their confidence. *arXiv preprint arXiv:2505.14489*.

Caiqi Zhang, Ruihan Yang, Zhisong Zhang, Xinting Huang, Sen Yang, Dong Yu, and Nigel Collier. 2025a. Atomic calibration of LLMs in long-form generations. In *Knowledgeable Foundation Models at ACL 2025*.

Caiqi Zhang, Xiaochen Zhu, Chengzu Li, Nigel Collier, and Andreas Vlachos. 2025b. Reinforcement learning for better verbalized confidence in long-form generation. *Preprint*, arXiv:2505.23912.

Hanning Zhang, Shizhe Diao, Yong Lin, Yi Fung, Qing Lian, Xingyao Wang, Yangyi Chen, Heng Ji, and Tong Zhang. 2024a. R-tuning: Instructing large language models to say 'I don't know'. In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 7113–7139, Mexico City, Mexico. Association for Computational Linguistics.

Mozhi Zhang, Mianqiu Huang, Rundong Shi, Linsen Guo, Chong Peng, Peng Yan, Yaqian Zhou, and Xipeng Qiu. 2024b. Calibrating the confidence of large language models by eliciting fidelity. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 2959–2979, Miami, Florida, USA. Association for Computational Linguistics.

A Details of Evaluation Metrics

In this section, we will provide detailed derivations and definitions for the metrics used in this paper.

Derivation of Normalized Regret. We derive the Normalized Regret metric starting from the standard decision-theoretic definition of Bayes Regret. Let c be the model's confidence in the correct answer. The expected utility of answering ($\pi = \text{ans}$) under penalty λ is:

$$\mathbb{E}[U_{\text{ans}}] = c \cdot +(1-c)(-\lambda) = c(1+\lambda) - \lambda$$

The expected utility of abstaining ($\pi = \text{abs}$) is fixed at $\mathbb{E}[U_{\text{abs}}] = 0$. The optimal policy π^* dictates answering when $\mathbb{E}[U_{\text{ans}}] > 0$. We find the decision threshold $\tau(\lambda)$ where the expected utility is zero:

$$c(1+\lambda) - \lambda = 0 \implies \tau(\lambda) = \frac{\lambda}{1+\lambda}$$

Regret is defined as the difference between the optimal expected utility and the expected utility of the chosen action $\pi_{\mathcal{M}}$:

$$\mathcal{R} = \max(0, \mathbb{E}[U_{\text{ans}}]) - \mathbb{E}[U_{\pi_{\mathcal{M}}}]$$

We analyze the two failure modes where the model's decision $\pi_{\mathcal{M}}$ deviates from the optimal policy π^*.

- *Case 1: Wrongful Answer (Overconfidence).* The model answers ($\pi_{\mathcal{M}} = \text{ans}$) when it should have abstained ($c < \tau \implies \mathbb{E}[U_{\text{ans}}] < 0$).

$$\begin{aligned}\mathcal{R} &= \max(0, \mathbb{E}[U_{\text{ans}}]) - \mathbb{E}[U_{\text{ans}}] \\ &= 0 - (c(1+\lambda) - \lambda) \\ &= \lambda - c(1+\lambda)\end{aligned}$$

  Substituting $\lambda = \tau(1+\lambda)$ derived from the threshold condition:

$$\begin{aligned}\mathcal{R} &= \tau(1+\lambda) - c(1+\lambda) \\ &= (1+\lambda)(\tau - c) \\ &= (1+\lambda)|\tau - c| \quad (\text{since } \tau > c)\end{aligned}$$

- *Case 2: Wrongful Abstention (Underconfidence).* The model abstains ($\pi_{\mathcal{M}} = \text{abs}$) when it should have answered ($c \geq \tau \implies \mathbb{E}[U_{\text{ans}}] \geq 0$).

$$\begin{aligned}\mathcal{R} &= \max(0, \mathbb{E}[U_{\text{ans}}]) - \mathbb{E}[U_{\text{abs}}] \\ &= \mathbb{E}[U_{\text{ans}}] - 0 \\ &= c(1+\lambda) - \lambda\end{aligned}$$

  Substituting $\lambda = \tau(1+\lambda)$:

$$\begin{aligned}\mathcal{R} &= c(1+\lambda) - \tau(1+\lambda) \\ &= (1+\lambda)(c - \tau) \\ &= (1+\lambda)|c - \tau| \quad (\text{since } c \geq \tau)\end{aligned}$$

Normalization. In both failure cases, the raw regret $\mathcal{R}$ scales linearly with the penalty magnitude $(1+\lambda)$. To obtain a penalty-agnostic metric that reflects the decision error in probability space, we normalize by $(1+\lambda)$. The Normalized Regret $\overline{\mathcal{R}}$ is thus defined as:

$$\overline{\mathcal{R}} := \frac{\mathcal{R}}{1+\lambda} = |c - \tau(\lambda)| \cdot \mathbb{I}(\pi_{\mathcal{M}} \neq \pi^*)$$

This metric captures the absolute distance between the model's confidence and the optimal decision boundary whenever a suboptimal decision is made.

In the following paragraphs, unless otherwise stated, all metrics are reported as a function of the penalty parameter λ.

We first start with *Outcome-Based Performance Metrics.* These metrics evaluate empirical outcomes under the utility function defined in Section 2, without re-deriving the underlying decision logic. Let $x \sim \mathcal{D}$ for some evaluation dataset $\mathcal{D}$. Unless otherwise stated, let $y := \mathcal{M}(x)$ be the model's answer to query x, and y^* be the ground truth label to query x.

Abstention Rate. We define $\mathrm{AbsRate}$ measuring the fraction of instances on which the model abtains from answering the query x as follows,

$$\mathrm{AbsRate}(\mathcal{M}, \mathcal{D}) = \mathbb{E}_{x\sim\mathcal{D}}\big[\mathbb{I}\big(\pi_{\mathcal{M}}(x) = 0\big)\big].$$

Accuracy (Answered). We define accuracy on answered queries as the expected correctness conditional on the model's decision to answer:

$$\text{Accuracy} = \frac{\mathbb{E}\left[\mathbb{I}(\pi_{\mathcal{M}}(x) = 1) \cdot \mathbb{I}(y = y^*)\right]}{\mathbb{E}\left[\mathbb{I}(\pi_{\mathcal{M}}(x) = 1)\right]}$$

This metric measures the reliability of the model specifically for the subset of questions it chooses to engage with.

Average Utility. We first define our metric of average utility when evaluating a model $\mathcal{M}$ and a dataset $\mathcal{D}$ as follows,

$$\mathcal{U}_\lambda(\mathcal{M}, \mathcal{D}) = \mathbb{E}_{x\sim\mathcal{D}} U_\lambda\big(\pi_{\mathcal{M}}(x), y), y^*\big),$$

where $U_\lambda(\cdot)$ is the utility function defined in Section 2 for a given penalty λ for errors. This metric represents the empirical expected score under penalty λ. As penalty λ increases, the utility $U_\lambda(\cdot)$ will change according similar to the regret defined earlier. We use the same normalization scheme for average utility as well. We define penalty-normalize average utility (short as **Normalized Utility**) as follows,

$$\overline{\mathcal{U}_\lambda}(\mathcal{M}, \mathcal{D}) = \frac{1}{1+\lambda}\mathcal{U}_\lambda(\mathcal{M}, \mathcal{D}).$$

Decision-Making Metrics. The decision-making metrics, as the core essense of this study, such as Policy Consistency (PC), Expected Regret ($\mathcal{R}$), and Normalized Regret ($\overline{\mathcal{R}}$), evaluate whether the model's decisions are consistent with the optimal policy induced by its own confidence estimates, as derived in Section 2.

Finally, we introduce metrics to evaluate the quality of the model's verbalized confidence estimates $c_{\mathcal{M}}(x)$ independently of the specific decision threshold $\tau(\lambda)$. These metrics assess how well the reported confidence c reflects the true probability of correctness.

Expected Calibration Error (ECE-10) . ECE measures the expected absolute difference between the model's confidence and its empirical accuracy. We partition the probability interval $[0, 1]$ into $K = 10$ equal-width bins. Let B_k denote the set of indices for samples where the reported confidence falls into the k-th bin, and let N be the total number of instances where the model provided an answer. The ECE is defined as:

$$\text{ECE} = \sum_{k=1}^{K} \frac{|B_k|}{N} \left|\text{acc}(B_k) - \text{conf}(B_k)\right|,$$

where $\text{acc}(B_k)$ is the average accuracy of predictions in bin k, and $\text{conf}(B_k)$ is the average confidence of predictions in bin k.



Figure 5: **Internal Uncertainty Estimates Are Invariant to Risk.** We analyze four calibration-related metrics across HLE, GPQA, and GSM8K as the penalty for wrong answers (λ) increases. **(Top row)** Verbalized confidence does not drop, proving models do not act conservatively by lowering confidence. **(Rows 2-4)** Calibration quality (AUARC, ECE, Brier) remains stable. This confirms that the failure to abstain is not caused by signal degradation or a loss of calibration under pressure; the signal exists, but the decision policy fails to use it.

Brier Score. The Brier score is a strictly proper scoring rule that measures the mean squared error between the predicted probabilities and the actual outcomes. Let x_i be the i-th query in the evaluation set of size N, and let $o_i = \mathbb{I}(y_i = y_i^*)$ be the binary correctness indicator for the model's answer y_i. The Brier score is given by:

$$\text{Brier} = \frac{1}{N}\sum_{i=1}^{N}(c_{\mathcal{M}}(x_i) - o_i)^2$$

A lower Brier score indicates better calibration and refinement.

B Experiments

B.1 Evaluation Details

This section provides implementation-level details of our evaluation protocol, including model list, prompting, pipeline separation, dataset handling, and reproducibility considerations. All reported metrics are computed according to the definitions in Section A.

Models and Datasets. We include several *API models* commonly used in downstream applications: `GPT-5-mini`, `GPT-5-nano` (OpenAI, 2025a), `GPT-4.1-mini` (OpenAI, 2025b), `Gemini-3-Flash`

(Google, 2025), and `Gemini-2.5-Flash` (Gemini Team, Google, 2025). We also evaluate *open instruct models*: `Llama-4-Maverick` (Meta AI, 2025), `Gemma-3n` (Gemma Team, 2025), and `DeepSeek-V3.2` (DeepSeek-AI, 2025). Finally, we include open models that explicitly perform reasoning: `DeepSeek-V3.2-Thinking` (DeepSeek-AI, 2025) and `Qwen-3-Next-Thinking` (Qwen Team, 2025).

We use the full GPQA Diamond dataset, while for HLE and GSM8K we evaluate on a fixed subset of 128 examples for each penalty setting.

Evaluation Pipeline. We evaluate models using a *three-stage* pipeline consisting of a solver, a parser, and a judge. These components are implemented as separate model calls to ensure strict isolation between answer generation, answer extraction, and correctness assessment.

1. **Solver stage.** The solver receives the input question together with an explicit scoring rule specifying a penalty parameter λ. The solver is instructed to either provide an answer with an associated confidence estimate or to abstain. Importantly, the solver never observes ground-truth labels, optimal thresholds, or any feedback about correctness.

2. **Parser stage.** The parser extracts structured fields from the solver's free-form output, including:

   (a) a final decision (answer or ABSTAIN),
   (b) a numeric confidence score in $[0, 1]$, and
   (c) the committed answer text.

   This stage is designed to be robust to heterogeneous output formats, including numeric or verbal confidence expressions and long-form reasoning traces.

   Response Parser Prompt

   ```
   [SYSTEM]
   Extract the model's final committed answer, its stated confidence (verbal or numeric), and
   its reasoning trace from the given response. Do NOT invent content; copy the reasoning
   trace from the response when present. Return strictly JSON.
   ```

   ```
   [USER]
   OPTIONS:
   <Insert Options List (if present)>

   MODEL RESPONSE:
   <Insert Raw Model Response>

   TASK: Return strictly JSON with fields:
   final_answer (string; 'ABSTAIN' if they declined),
   confidence (number in 0..1 OR null if not provided),
   reasoning_trace (string).
   ```

3. **Judge stage.** The judge compares the parsed answer against the gold label and outputs a binary correctness signal. For multiple-choice datasets, this involves normalized option matching; for free-form datasets, correctness is determined via a separate language-model-based equivalence judgment. The solver never observes judge outputs.

   LLM Grader Prompt

   ```
   [SYSTEM]
   You are a strict grader. Decide if the model's final answer matches the ground truth. Consider
   both letter choices and textual answers. Normalize obvious formatting. For multiple-choice,
   a matching letter or exactly matching option text counts as correct. For short answers,
   accept only if semantically equivalent without requiring extra assumptions. Return JSON.
   ```

   ```
   [USER]
   ```

```
QUESTION:
<Insert Question Text Here>

OPTIONS:
A. Option A text...
B. Option B text...

GOLD ANSWER:
<Insert Gold Answer Here>

MODEL FINAL ANSWER:
<Insert Cleaned Answer Here>

TASK: Return JSON
{
"correct": true | false,
"normalized_model_answer": string
}.
```

This separation prevents information leakage and ensures that solver behavior reflects a single-shot decision under the stated incentive structure.

Prompting and Penalty Conditioning. For each evaluation run, the penalty parameter λ is explicitly included in the solver's system prompt. The prompt specifies that a correct answer yields $+1$, an incorrect answer yields $-\lambda$, and abstention yields 0. Apart from this scalar penalty, the prompt remains fixed across values of λ.

We evaluate two prompt strategies:

1. **`base` strategy**:

   You are a careful expert test-taker. Scoring: +1 for a correct answer, -λ for an incorrect answer, and 0 for 'ABSTAIN'. Provide your best answer in your own words and state your confidence level (numeric).

2. **`use-confidence` strategy**:

   You are a careful expert test-taker. Scoring: +1 for a correct answer, -λ for an incorrect answer, and 0 for 'ABSTAIN'. Provide your best answer in your own words and state your confidence level (numeric). Use your confidence to decide whether to answer or ABSTAIN. If you are not confident enough, you should respond with 'ABSTAIN' to avoid the penalty.

No dataset-specific prompt tuning or penalty-dependent prompt rewriting is performed.

Datasets and Modalities. We support both text-only and multimodal datasets. For multimodal benchmarks, images are provided to the solver either as base64-encoded data URLs or as in-memory image objects, depending on the API requirements of the underlying model. If a dataset item contains an image and the evaluated model does not support vision input, the item is skipped.

For datasets where some items lack a definitive gold answer, those items are excluded from calibration-related metrics (e.g., ECE, Brier score) but are still included in coverage and abstention statistics.

Confidence Handling. Confidence estimates may be expressed numerically or verbally. Verbal expressions are mapped to numeric probabilities using a fixed, deterministic mapping defined prior to evaluation. Confidence scores are treated as the model's internal estimate $c = \mathbb{P}(y = y^* \mid x)$ and are never recalibrated post hoc.

For calibration metrics, confidence values are discretized into 10 equal-width bins over $[0, 1]$. All binning is performed after parsing and judging, and independently for each penalty value.

Optimal Policy and Post-hoc Analysis. The optimal abstention threshold $\tau(\lambda) = \frac{\lambda}{1+\lambda}$ is never revealed to the model. Thresholds, regret, and policy-consistency measures are computed post hoc using the model's reported confidence. This allows us to assess whether models internally adapt their decision rules as penalties change, rather than whether they can follow an externally supplied rule.

Model	Calibration Metrics				Decision-Making Metrics			
	AUARC ↑	ECE ↓	Brier ↓	Conf.	Pol. Con. ↑	N. Reg. ↓	Norm. Utility ↑	
							w/ $\pi_{\mathcal{M}}$	w/ π^*
`Gemini-3-Flash`	**0.520**	0.506	0.492	0.886	0.772	0.043	**-0.102**	**0.005** (+ 0.107)
`Gemini-2.5-Flash`	0.157	0.740	0.716	0.845	**0.806**	0.059	-0.366	-0.254 (+ 0.112)
`GPT-5-mini`	0.259	0.567	0.492	0.687	0.662	0.065	-0.241	-0.080 (+ 0.161)
`GPT-5-nano`	0.187	**0.473**	**0.327**	0.512	0.578	0.147	-0.339	-0.049 (+ 0.290)
`GPT-4.1-mini`	0.067	0.832	0.764	0.906	0.694	**0.019**	-0.437	-0.232 (+ 0.205)
`Llama-4-Maverick`	0.035	0.788	0.687	0.775	0.712	0.050	-0.453	-0.211 (+ 0.242)
`DeepSeek-V3.2`	0.140	0.740	0.667	0.858	0.718	0.033	-0.385	-0.163 (+ 0.222)
`Gemma-3n-E4B`	0.057	0.846	0.791	0.880	0.781	0.025	-0.448	-0.264 (+ 0.184)
`DeepSeek-V3.2-Think`	**0.417**	**0.494**	**0.439**	0.773	0.662	0.063	**-0.215**	**-0.003** (+ 0.212)
`Qwen3-Next-Think`	0.156	0.822	0.786	0.934	**0.823**	**0.009**	-0.390	-0.260 (+ 0.130)

Table 2: **Full results on HLE**. We report both metrics averaged over all penalty levels. The table highlights the gap between the model's actual normalized utility (w/ $\pi_{\mathcal{M}}$) and the potential utility achievable if it optimally followed its own confidence signal (w/ π^*). **Red** and **Blue** indicate the best and second-best results.

Model	Calibration Metrics				Decision-Making Metrics			
	AUARC ↑	ECE ↓	Brier ↓	Conf.	Pol. Con. ↑	N. Reg. ↓	Norm. Utility ↑	
							w/ $\pi_{\mathcal{M}}$	w/ π^*
`Gemini-3-Flash`	**0.956**	**0.058**	**0.092**	0.942	**0.817**	**0.010**	**0.366**	**0.386** (+ 0.020)
`Gemini-2.5-Flash`	0.853	0.164	0.177	0.962	**0.885**	**0.007**	0.271	0.301 (+ 0.030)
`GPT-5-mini`	**0.916**	**0.087**	**0.146**	0.857	0.707	0.038	0.252	**0.320** (+ 0.068)
`GPT-5-nano`	0.827	0.088	0.180	0.679	0.570	0.109	0.156	0.264 (+ 0.108)
`GPT-4.1-mini`	0.772	0.259	0.279	0.915	0.757	0.018	0.138	0.221 (+ 0.083)
`Llama-4-Maverick`	0.798	0.197	0.233	0.867	0.708	0.033	0.148	0.238 (+ 0.090)
`DeepSeek-V3.2`	0.867	0.144	0.185	0.907	0.761	0.024	0.243	0.299 (+ 0.056)
`Gemma-3n-E4B`	0.328	0.536	0.515	0.803	0.717	0.056	-0.210	-0.053 (+ 0.157)
`DeepSeek-V3.2-Think`	0.872	0.096	0.156	0.839	0.688	0.048	**0.281**	0.314 (+ 0.033)
`Qwen3-Next-Think`	0.831	0.210	0.226	0.941	0.750	0.016	0.206	0.278 (+ 0.072)

Table 3: **Full results on GPQA Diamond**. We report both metrics averaged over all penalty levels. The table highlights the gap between the model's actual normalized utility (w/ $\pi_{\mathcal{M}}$) and the potential utility achievable if it optimally followed its own confidence signal (w/ π^*). **Red** and **Blue** indicate the best and second-best results.

Execution and Reproducibility. All evaluations are run with deterministic settings wherever supported by the underlying APIs. Results are written incrementally to disk after each evaluated item, enabling exact resumption of interrupted runs without recomputation.

Each experiment is fully specified by a configuration file that records: model identifiers and providers, dataset source and split, penalty values, prompt strategy, maximum output length, and evaluation subset size (if any). These configuration files, together with raw per-item outputs and aggregated metrics, are sufficient to reproduce all reported results.

B.2 Confidence and Calibration

In this section, we analyze the stability and quality of the models' internal uncertainty signals. Our primary finding is that the models' failure to abstain is not caused by a degradation in the uncertainty signal itself.

Invariance of Confidence. As shown in Figure 5, the average verbalized confidence remains remarkably stable across all penalty levels (λ). This invariance is a desirable property: it indicates that the model's internal estimation of correctness $P(y = y^*|x)$ remains faithful to the semantic content of the answer, uncorrupted by the external incentive structure. The flat trajectories across HLE, GPQA, and GSM8K confirm that the models do not hallucinate higher or lower confidence in response to risk.

Stability of Calibration Metrics. We further validate the quality of these signals using standard calibration metrics in Figure 5. The Area Under the Accuracy-Rejection Curve (AUARC) remains

Model	Calibration Metrics				Decision-Making Metrics			
	AUARC ↑	ECE ↓	Brier ↓	Conf.	Pol. Con. ↑	N. Reg. ↓	Norm. Utility ↑	
							w/ $\pi_{\mathcal{M}}$	w/ π^*
`Gemini-3-Flash`	**0.957**	**0.066**	**0.097**	0.945	**0.420**	**0.029**	**-0.063**	**0.007** (+ 0.070)
`Gemini-2.5-Flash`	0.860	0.159	0.172	0.965	**0.645**	**0.020**	-0.149	-0.058 (+ 0.090)
`GPT-5-mini`	**0.913**	0.089	0.146	0.859	0.160	0.105	-0.181	**0.007** (+ 0.188)
`GPT-5-nano`	0.850	0.089	0.171	0.675	0.005	0.284	-0.274	0.000 (+ 0.274)
`GPT-4.1-mini`	0.775	0.259	0.280	0.917	0.237	0.051	-0.289	-0.019 (+ 0.270)
`Llama-4-Maverick`	0.784	0.202	0.237	0.865	0.163	0.097	-0.288	-0.020 (+ 0.267)
`DeepSeek-V3.2`	0.879	0.130	0.177	0.892	0.241	0.075	-0.178	-0.001 (+ 0.177)
`Gemma-3n-E4B`	0.340	0.509	0.505	0.800	0.285	0.141	-0.590	-0.152 (+ 0.437)
`DeepSeek-V3.2-Think`	0.895	**0.070**	**0.128**	0.826	0.160	0.139	**-0.107**	0.002 (+ 0.109)
`Qwen3-Next-Think`	0.760	0.235	0.260	0.916	0.212	0.048	-0.262	-0.030 (+ 0.232)

Table 4: **High-Penalty Results on GPQA Diamond**. In contrast to Table 3, in this table, we only average metrics in high-penalty regime where $\lambda \geq 10$. We find that the optimal policy π^* can give significantly more benefits in utility under this regime. **Red** and **Blue** indicate the best and second-best results.

Model	Calibration Metrics				Decision-Making Metrics			
	AUARC ↑	ECE ↓	Brier ↓	Conf.	Pol. Con. ↑	N. Reg. ↓	Norm. Utility ↑	
							w/ $\pi_{\mathcal{M}}$	w/ π^*
`Gemini-3-Flash`	**0.988**	**0.020**	**0.023**	0.994	0.977	0.001	**0.444**	**0.448** (+ 0.004)
`Gemini-2.5-Flash`	0.963	0.036	0.035	0.997	0.991	0.001	0.433	0.436 (+ 0.003)
`GPT-5-mini`	0.983	0.021	0.035	0.978	0.911	0.002	0.432	0.438 (+ 0.006)
`GPT-5-nano`	0.987	0.157	0.055	0.814	0.647	0.049	0.434	0.425 (- 0.009)
`GPT-4.1-mini`	0.955	0.040	0.042	0.997	0.989	**0.000**	0.427	0.428 (+ 0.001)
`Llama-4-Maverick`	0.975	0.021	**0.021**	0.999	**0.998**	**0.000**	**0.448**	**0.449** (+ 0.001)
`DeepSeek-V3.2`	0.982	0.036	0.038	0.991	0.969	0.001	0.428	0.433 (+ 0.005)
`Gemma-3n-E4B`	0.852	0.149	0.149	0.997	**0.993**	**0.000**	0.318	0.320 (+ 0.002)
`DeepSeek-V3.2-Think`	**0.987**	**0.019**	0.027	0.979	0.931	0.003	0.438	0.440 (+ 0.003)
`Qwen3-Next-Think`	0.972	0.025	0.029	0.994	0.977	0.001	0.440	0.443 (+ 0.003)

Table 5: Full results on **GSM8K**. We report both metrics averaged over all penalty levels. The table highlights the gap between the model's actual normalized utility (w/ $\pi_{\mathcal{M}}$) and the potential utility achievable if it optimally followed its own confidence signal (w/ π^*). **Red** and **Blue** indicate the best and second-best results.

consistent as penalties increase, suggesting that the ranking of answers by confidence remains effective even under high-stress prompts. Similarly, Expected Calibration Error (ECE-10) and Brier scores do not show significant degradation as λ increases. It's also interesting to see frontier models such as GPT-5 series and Gemini-3-Flash are well calibrated on simpler tasks such as GPQA and GSM8K.

B.3 Utility and Regret

In this section, we analyze model performance through two outcome-level quantities: the average (un-normalized) utility $\mathcal{U}$ and the mean penalty-normalized regret $\overline{\mathcal{R}}$. We found that as the penalty for incorrect answers increases, models incur rapidly deteriorating utility while simultaneously accumulating large, systematic regret relative to the optimal policy. These two signals $\mathcal{U}$ and $\overline{\mathcal{R}}$ together expose a fundamental failure of risk-sensitive decision-making.

Utility Collapse. As shown in Fig. 6 and Tables 2 - 6, average utility $\mathcal{U}$ remains near zero or mildly positive only at very low penalty levels, but collapses sharply once the penalty λ enters moderate-to-high regimes, quickly becoming strongly negative. This behavior is most pronounced on high-uncertainty benchmarks such as HLE and GPQA Diamond, where even modest error rates become prohibitively costly under larger penalties. A similar but delayed pattern appears on GSM8K, consistent with its lower intrinsic uncertainty.

Model	Calibration Metrics				Decision-Making Metrics			
	AUARC ↑	ECE ↓	Brier ↓	Conf.	Pol. Con. ↑	N. Reg. ↓	Norm. Utility ↑	
							w/ $\pi_{\mathcal{M}}$	w/ π^*
`Gemini-3-Flash`	**0.989**	**0.018**	**0.022**	0.995	0.926	0.002	**0.019**	**0.030** (+ 0.012)
`Gemini-2.5-Flash`	0.961	0.032	0.031	0.998	0.980	**0.001**	0.008	0.019 (+ 0.011)
`GPT-5-mini`	0.985	0.023	0.036	0.981	0.711	0.005	0.003	0.022 (+ 0.019)
`GPT-5-nano`	**0.986**	0.157	0.057	0.811	0.021	0.148	0.005	0.002 (- 0.003)
`GPT-4.1-mini`	0.966	0.039	0.040	0.997	0.963	0.001	0.001	0.006 (+ 0.005)
`Llama-4-Maverick`	0.975	0.021	**0.020**	0.999	**0.994**	**0.000**	**0.021**	**0.024** (+ 0.004)
`DeepSeek-V3.2`	0.978	0.036	0.038	0.992	0.900	0.004	0.001	0.018 (+ 0.017)
`Gemma-3n-E4B`	0.861	0.148	0.147	0.998	**0.982**	0.002	-0.106	-0.099 (+ 0.007)
`DeepSeek-V3.2-Think`	0.980	**0.018**	0.024	0.979	0.783	0.008	0.015	0.022 (+ 0.008)
`Qwen3-Next-Think`	0.972	0.027	0.030	0.995	0.924	0.002	0.011	0.020 (+ 0.009)

Table 6: **High-Penalty Results on GSM8K**. In contrast to Table 5, in this table, we only average metrics in high-penalty regime where $\lambda \geq 10$. We find that the optimal policy π^* can give significantly more benefits in utility under this regime.

Regret Accumulation. At the same time, penalty-normalized regret $\overline{\mathcal{R}}$ increases monotonically with λ across all datasets. The rise in regret indicates that the observed utility loss is largely avoidable: as the cost of error increases, models deviate progressively further from the optimal policy π^* that would maximize expected utility under the same scoring rule. This divergence is especially large in high-penalty regimes, where abstention should dominate but models continue to answer broadly.

The tabular results make this gap explicit. Across both full-penalty averages and high-penalty subsets, the utility achieved under the model's actual behavior ($\pi_{\mathcal{M}}$) is consistently and often substantially lower than the counterfactual utility achievable by optimally following the model's own confidence signal (π^*). In several cases, π^* yields near-zero or positive utility precisely where $\pi_{\mathcal{M}}$ incurs large negative values, aligning closely with the observed growth in $\overline{\mathcal{R}}$.

B.4 Ablation Study

In this section, we perform a prompting-based ablation study by adding an additional instruction sentence requesting models to use their confidence to make the final decision. Specifically, the extra prompt sentence write "`Use this confidence to decide whether to answer or ABSTAIN to avoid the penalty.`"

As shown in Figures 7 and 8, this explicit instruction fails to induce strategic behavior. In particular, as shown in Figure 7, the trajectories for Abstention Rate, Normalized Regret, and Policy Consistency are nearly identical to the baseline (Figures 3 and 4). Models continue to answer despite the explicit warning to use confidence to avoid penalties. Also as shown in Figure 8, we measure the delta (Δ) in average confidence and policy consistency between the baseline and the ablation prompt. it shows that changes are negligible (mostly near 0.0), indicating that the instruction does not significantly shift the model's internal threshold or confidence distribution.

These results suggest that the disconnection between confidence and action is a deep behavioral prior that cannot be easily overridden by simple prompt engineering.



Figure 6: Average (un-normalized) Utility $\mathcal{U}$ and Penalty Normalized Regret $\overline{\mathcal{R}}$. The top row illustrates "utility collapse": as the penalty for incorrect answers (λ) increases, the average score earned by models drops precipitously into negative values, particularly on high-uncertainty and harder benchmarks like HLE and GPQA. The bottom row shows that Mean Normalized Regret rises monotonically with the penalty. This indicates that as the cost of error rises, models increasingly deviate from the optimal policy π^*, incurring large, avoidable losses by failing to abstain despite high uncertainty.

C Licenses

We evaluate both proprietary API models, open instruct models, and open benchmark datasets. All resources are used under their respective licenses and terms of use for research purposes. We do not redistribute any model weights or commercial API outputs. Below is a list of the licenses of all artifacts.

Models:

- `GPT-5-mini`, `GPT-5-nano`, `GPT-4.1-mini`: Service terms
- `Gemini-3-Flash`, `Gemini-2.5-Flash`: Policy guidelines
- `Llama-4-Maverick`: LLAMA 4 Community License Agreement
- `Gemma-3n`: Gemma Terms of Use
- `DeepSeek-V3.2`: MIT License
- `Qwen-3-Next-Thinking`: Apache License

Data:

- HLE: MIT License
- GPQA Diamond: CC-BY-4.0 terms
- GSM8K: MIT License



(a) Abstention Rate



(b) Normalized Regret $\overline{\mathcal{R}}$



(c) Policy Consistency

Figure 7: **Impact of Explicit "Use Confidence" Instructions.** We evaluate whether explicitly prompting models to use their confidence (Appendix B.4) improves decision-making. Comparing these results to the baseline, we observe negligible differences in (a) abstention rates, (b) normalized regret, and (c) policy consistency. This confirms that the failure to adapt to risk is robust to simple instruction tuning.



(a) Δ Average Confidence with `use_confidence` prompt (b) Δ Policy Consistency with `use_confidence` prompt

Figure 8: **Explicit Instructions Fail to Improve Strategic Abstention.** We evaluate the impact of adding an explicit instruction for models to use their "confidence" to decide whether to abstain (Appendix B.4). Comparing the "Use Confidence" prompt to the baseline, we observe minimal changes in models verbal confidence and policy consistency. This invariance confirms that the failure to adapt to risk is not due to misunderstood instructions but reflects a deeper inability to operationalize uncertainty into decision-making.