REVEAL: Agentic In-Hand Manipulation for Language-Guided Target Presentation

Anonymous CVPR submission




Figure 1. **REVEAL overview.** New visual evidence guides semantic decisions as the hand inspects and presents a requested object face. This staged simulation illustration is not a recorded rollout or physical-robot result.

Abstract

How can a robot find and present a requested object face when it is initially hidden or blocked by the fingers? We present REVEAL, a framework for agentic in-hand manipulation that connects visual search to continuous motor control. The agent chooses inspection actions, links the requested face to a motor goal, and directs its presentation. A recurrent motor policy follows this goal, while teacher-supervised local controllers adjust joint commands during agent inference and action execution. We evaluate six object-specific systems in simulation and test English and Chinese instructions on three objects. Under changed target-to-skill mappings, REVEAL achieves 65.8% success averaged across objects, exceeding the strongest evaluated baseline by 40.4 percentage points. Paired cube experiments show that fresh images enable additional correct target bindings, increasing success from 9/40 to 32/40. A separate controller ablation supports joint correction during inference.

1. Introduction

A command such as "present the face marked T" tells the robot what to show. The robot still has to find T, choose a motor goal that exposes it, and move the object without dropping it. The target may initially face away from the camera or be blocked by the fingers. Moving the object can reveal the target, but also changes the grasp. The robot therefore needs to decide both what to look at next and how to keep controlling the object.

Vision-language agents can interpret the instruction and inspect camera images, but each response takes time. Meanwhile, the hand and object continue to move. Repeating the previous command may lose the grasp or leave the target hidden. Slowing down limits motion but cannot change the direction of the joint command. A local controller must therefore respond to new measurements while the agent is still reasoning.

REVEAL lets the agent and motor policy run at different rates while sharing the same motor goals. The agent chooses inspection actions from the current image and action history.

Once it identifies the requested face, it links that face to a motor goal, a step we call *target binding*. A recurrent student uses this goal, measured pose and proprioception to propose joint commands. For the cube, two local controllers adjust these commands during agent inference and action execution. Both learn from teacher actions in simulation. The hand can thus respond to its current state before the next agent reply arrives.

We adapt a ViserDex-style policy [4] that estimates pose from RGB and uses recurrent control. Its new goal input accepts vectors from a fixed goal bank. The agent selects these vectors through explicit tool arguments. For comparison, a fine-tuned Qwen3-VL [2] predicts a goal vector directly, and a rule-based VLM returns a color and a readability decision. These systems share a motor student within each object, but differ in inspection, history, local control and stopping. We therefore compare complete systems and use separate cube experiments to study individual components.

Across 1,440 simulation trials on six objects, REVEAL achieves 70.4% success with the original target-to-skill mappings and 65.8% after the mappings change. These equal-object averages exceed the strongest baseline by 26.2 and 40.4 percentage points, respectively. Each object has its own policy and perception setup. A separate 2,160-trial English/Chinese study favors REVEAL over fine-tuning in all eight duck and hedgehog conditions after correction for multiple comparisons; cube differences remain inconclusive.

Paired cube studies examine how the agent acquires target evidence. Fresh images enable 25 additional correct bindings after the first call, with 23 leading to success; repeating the first image enables none. A new comparison tests adaptive against fixed inspection while keeping the model and controllers unchanged. Its 17.5-point observed success gain remains statistically unresolved. A separate three-seed study supports joint correction during agent inference.

Our contributions are threefold. First, we study language-guided target presentation through visual search, target binding and continuous in-hand control. Second, we connect an agent to a recurrent motor policy through explicit goal selection and teacher-supervised local controllers. Third, we evaluate six object-specific systems and two languages, with cube studies testing continued feedback, fresh images, inspection choices and waiting-time control.

2. Related Work

RL for dexterous in-hand manipulation. RL policies trained in simulation can reorient objects with a physical hand using domain randomization [1] and handle diverse object shapes [7]. Rapid motor adaptation handles changing object properties [15]. RotateIt combines vision, touch and proprioception through teacher–student distillation [16], while AnyRotate supports different rotation axes and hand orientations [21]. REVEAL builds on these motor capabilities to find and present a target specified by language, even when the robot must first move the object to see it.

Visual and goal-conditioned dexterity. ViserDex combines monocular pose estimation with recurrent control [4]. We adapt its released Revo3 policy to accept semantic goals. GoalDex uses current and goal images, selects goals from language with a VLM, and studies multi-object sim-to-real transfer and visual-processing delays [3]. REVEAL focuses on finding a requested face through new observations while hand control continues. ManipTrans uses residual learning for dexterous bimanual transfer [12]. Our local corrections support the agent's inspection and presentation actions.

Agentic reasoning and embodied feedback. SayCan selects language-guided skills using robotic affordances [11], and Inner Monologue uses environmental feedback to update plans [9]. Code as Policies connects perception and control APIs [14]. VoxPoser and ReKep translate language into spatial value maps and keypoint constraints [8, 10]. Magma connects multimodal representations to actions [20], while VERA includes language-guided dexterous reorientation from visual plans [13]. REVEAL studies this interaction for a target held in the hand: inspection reveals new evidence, binding selects a motor goal, and local control continues during reasoning. Separate image and inspection-policy interventions test the value of new observations and agent-selected views. Our contribution concerns their interaction with continuous in-hand control.

Asynchronous robot policies. Prior work handles inference delay through real-time action-chunk execution [5], online VLA corrections [18], latency-aware RL [22], and temporal counterfactual preferences [23]. LiMA combines sparse semantic decisions with asynchronous dexterous action generation [6]. REVEAL trains small local controllers around a motor policy and an agent with explicit tool actions. We study how observation, target binding and control work together. Asynchronous execution and residual actions alone are not new, and our ablations do not isolate the benefit of explicit controller-goal input.

3. Task and Evaluation

Semantic target. Q1 evaluates six objects in simulation: a marked cube, a wooden die, a duck, a hedgehog, a pig, and a milk carton. Q2 and Q3 use only the marked cube. Instructions request one of six surface letters, or one through six dots on the die. The cube letters are $\{T, E, R, L, S, H\}$. Each target has a fixed reference orientation $Q(g)$ that places the requested face upward. Scoring compares the full quaternion, including rotation about the face normal. Thus, showing the correct face alone is insufficient: the scorer also

requires a particular twist that the language instruction does not specify. This rule is shared by all methods.

At step t, the agent receives an RGB image I_t and instruction ℓ. The motor policy receives proprioception x_t and measured pose $\hat{p}_t$. Cube pose is estimated from RGB. Other objects use simulator pose with added noise. True pose p_t and teacher actions are used only for training and independent evaluation. During deployment, the controller cannot use a future agent reply. We denote the active goal vector by g_t, the recurrent state by h_t, and a pending request by $m_t = 1$.

Timing. Only one agent request can be pending at a time. Cube episodes allow up to six model calls and 3,600 control steps at 30 Hz. Other objects use 20 Hz over the same 120 seconds of simulated time. For the cube, a call taking L wall-clock seconds can affect control only after it completes and at least $\lceil 30L \rceil$ steps have passed since the request. Physics continues while the agent reasons. The simulator runs slower than real time, so this models inference delay but does not demonstrate a 30 Hz hardware system.

Autonomous completion. All cube systems use the same stopping check at 3 Hz. The agent must have bound the requested symbol to a goal, with no request pending and no inspection underway. Measured orientation error must be at most $\epsilon = 0.16$ radians. This check can stop the system without an explicit stop action from the agent. On other objects, REVEAL uses calibrated completion correction, while the baselines use a measured-pose check. Their stopping rules are detailed in the supplement, and all are scored with the same true-pose tolerance. At stop time τ, success is

$$S = \mathbf{1}\left[\hat{b}_\tau = b^*(\ell),\ d(q_\tau, Q(b^*)) \le \epsilon,\ \neg D_{0:\tau}\right], \quad (1)$$

where $\hat{b}_\tau$ is the declared target binding, q_τ is true orientation, $D_{0:\tau}$ indicates an earlier terminal drop, and $d(q, Q) = 2\arccos(|\langle q, Q\rangle|)$ for normalized quaternions. The target must be correct at the stop time, not merely reached earlier. We do not require an additional hold after stopping. A wrong binding or an incorrect final pose counts as failure even if the object remains in the hand. A drop terminates the trial when the object is at least 0.24 metres from its nominal grasp position.

Paired trials and service failures. Unless stated otherwise, each condition uses 40 trials: 20 per seed under two seeds. Compared methods share the same initial physical states and scored targets. Control and feedback experiments also share instructions. In the mapping experiment, the requested letter changes with the layout so that the physical target stays the same. A service error or a model call taking more than 120 seconds excludes that trial from the service-eligible comparison. We remove the same trial from every compared method, retain all raw results, and do not replace excluded trials. Each reported rate uses the denominator for its own comparison. Service failures are reported separately from control failures.

4. Method

REVEAL connects the agent to continuous motor control through a shared goal bank (Fig. 2). We first adapt a pretrained student with frozen-teacher supervision, then train local controllers around that student. At deployment, the agent selects inspection or presentation goals from new observations. We describe the cube system below; other objects use their own students, noisy pose feedback and maintenance controllers.

4.1. Visual pose estimation and motor policy

A frozen CNN takes a 120×120 RGB crop and predicts image coordinates and depth for the object center and eight keypoints. Camera calibration and rigid fitting recover object position, XYZW orientation and a fitting error. The rendered cube images include hand occlusion. The deployed policy receives this estimated pose, without ground-truth pose.

We start from a pretrained student that takes geometric goals. A learned projection replaces these goal inputs with $g_t \in \mathbb{R}^{768}$:

$$z_t = \tanh(W_g g_t + b_g) \in \mathbb{R}^{64}, \quad (2)$$

$$(u_t, h_{t+1}) = \pi_\theta([x_t, z_t], \hat{p}_t, h_t). \quad (3)$$

Here $x_t \in \mathbb{R}^{109}$ contains proprioception and history without the target pose, and $u_t \in \mathbb{R}^{21}$ contains proposed joint targets in normalized coordinates. We reuse compatible encoders, recurrent and actor weights, and normalization statistics from the released policy. The adapted student receives neither the target quaternion nor the relative-goal quaternion.

We train the goal projection and adapt the recurrent policy using actions from a frozen teacher in a DAgger-style procedure [17]. Teacher states and actions are available only during training. At deployment, the cube student uses the frozen RGB pose estimator. The supplement describes the policy and perception setup for each other object.

4.2. From observations to motor goals

The cube has a bank of six normalized goal vectors $B = \{g_1, \ldots, g_6\}$, computed from cached SigLIP2 text features [19]. Each vector represents a color skill and its reference object orientation.

Semantic agent interface. Given the instruction and current image, the hosted agent returns an explicit action: inspect, reorient, verify, stop, or abstain. We validate the action




Figure 2. **REVEAL training and deployment.** Teacher supervision trains a student to follow goal-bank vectors. During deployment, the agent selects skills and local controllers adjust the hand commands. Dashed slots are reserved for future physical-hand images.

before use. Its color argument selects a goal vector from B. An inspection can move the object toward a new view without declaring that the requested target has been found. The agent chooses inspection and reorientation durations of 10–90 steps, separately from inference latency. It uses new images and the recorded action history for later decisions. Tool arguments select the student goal through a fixed lookup, without hidden agent features.

4.3. Control while the agent is reasoning

The hand needs updated commands while an agent request is pending. The waiting controller receives a feature vector s_t containing proprioception, measured pose, the student's recurrent state and proposed action, fitting error, binding status and request status. It also receives the pose and command recorded when the request began, which we call the *request anchor*, and the elapsed waiting time. The active goal g_t is encoded separately. Before target binding, this goal represents the startup or inspection skill. The controller does not know the target that a future reply may select.

A fusion layer combines the outputs of a sensor encoder and a goal encoder. The waiting actor predicts a speed logit r_t and correction values $v_t \in \mathbb{R}^{21}$. Let $\bar{q}_t$ denote normalized current joint positions and $\bar{u}_t$ the clipped student proposal.




Figure 3. **Visual target search.** The agent observes, inspects candidate faces, binds the requested target, and issues a presentation command. The reference crops are simulated; real-hand frames are pending.




Figure 4. **Local control.** The controller combines sensor and goal features to adjust the speed and direction of the student's joint command. Empty photo slots are reserved for physical-hand results.

The applied command is

$$\alpha_t = \mathrm{sigmoid}(4r_t + \mathrm{logit}(0.15)), \tag{4}$$

$$b_t = \begin{cases} \bar{q}_t + \alpha_t(\bar{u}_t - \bar{q}_t), & m_t = 1, \\ \bar{u}_t, & m_t = 0, \end{cases} \tag{5}$$

$$a_t = \mathrm{clip}\big(b_t + 0.35\tanh(v_t), -1, 1\big). \tag{6}$$

Zero actor outputs give fixed slowing with coefficient 0.15 while a request is pending. The environment keeps the same joint mapping and smoothing. Unlike scalar slowing, the joint correction can change the command direction as well as its size.

During training, the frozen teacher provides holding actions for the request anchor. At deployment, the actor uses only measured inputs and the active goal, without the pending reply. Writing the correction as $\delta_\phi = 0.35\tanh(v_t)$, we train it to match the teacher action while keeping this correction small:

$$\mathcal{L}_{\text{control}} = \mathbb{E}_{(s,g,a^*)\sim\mathcal{D}}\left[\|a_\phi(s,g) - a^*\|_2^2 + 0.01\|\delta_\phi(s,g)\|_2^2\right]. \tag{7}$$

The waiting-actor update changes only control during pending requests. The student, pose estimator, execution controller and stopping rule remain fixed. Training details are in the supplement.

4.4. Learning execution after a decision

When no request is pending ($m_t = 0$), a separate execution actor supplies v_t in Eq. 6. It learns from teacher actions to add a bounded correction to the student's proposal. The actor also receives the active goal, although our experiments do not isolate the benefit of this extra goal input.

4.5. Closed-loop execution

At each control step, REVEAL updates the pose estimate, runs the recurrent student, selects the waiting or execution actor, and sends the resulting joint targets to the hand. Only a valid agent reply can change the active skill or target binding. The next image shows the object after the motion that occurred during inference. A separate stopping check determines whether to end the trial. Invalid replies cannot select the true target through an oracle fallback.

We evaluate student adaptation separately from controller learning because a new student also changes the recurrent features and action proposals seen by the controllers.

5. Experiments

Q1 compares complete systems, Q2 studies control during inference, and Q3 studies active target search. Q2 and Q3 use only the marked cube. Q4 describes the pending hardware evaluation.

Q1. How do complete systems compare across objects, mappings and instruction variants?
Q2. How should the hand move while the agent is reasoning?
Q3. How do new observations and inspection choices help find the target?
Q4. Does the system work on physical objects?

5.1. Setup and reporting

We use Revo3 assets in Isaac Lab 3.0/Newton. Unless specified otherwise, each condition has 40 trials across two evaluation seeds, paired by physical task. Cube systems share the frozen RGB pose estimator, goal bank, student, stopping rule and 0.16-radian tolerance. Other objects use separate students and noisy simulator pose. REVEAL additionally uses calibrated completion correction on these objects. The VLM baselines omit the extra control actors and follow a fixed inspection schedule when the target is unreadable. REVEAL chooses its inspection actions. These differences and measured inference delays are part of the complete-system comparison.

The current cube system updates only the waiting actor. Q1 and Q3 compare methods on the same service-eligible trials. Q2 reports all 120 trials per method. Q1 and Q2 use different trial sets and answer different questions, so their absolute success rates need not match. Controller gains are measured within Q2. Its three-seed table reports descriptive results. The supplement gives the paired tests and corrections for multiple comparisons used in each study.

5.2. Q1: Systems across objects and mappings

We compare the original and changed target-to-skill mappings on six objects. Earlier native-image studies are reported separately in the supplement. Neither found a significant REVEAL–fine-tuned difference (cube $p = 0.267$, die $p = 0.4545$).

Aggregate system performance. Across 1,440 scheduled trials, mean success is 70.4% with original mappings and 65.8% with changed mappings. The strongest baseline averages are 44.2% for fine-tuning and 25.4% for rules, respectively. REVEAL improves on them by 26.2 and 40.4 percentage points. These post-hoc averages weight each object's service-eligible rate equally. They do not pool trials or provide an additional significance test.

Four additional objects. Duck, hedgehog, pig and milk carton contribute 960 trials across two mappings. REVEAL has the highest observed rate in each condition (Table 1), with a separate policy for each object. Three service failures exclude matching trials from all methods. The milk carton still drops in 15/40 original-mapping and 20/40 changed-mapping REVEAL trials. Thus, higher completion does not guarantee a stable grasp. Reset checks and sensitivity analyses are in the supplement.

Visual-semantic intervention. We change only the image sent to the agent, keeping pose-estimator input and lighting fixed. Each method uses 40 matched states under three conditions: original letters, cyclically reassigned letters, and hidden letters. All three use reconstructed face images. After reassignment, REVEAL remains at 32/40 successes, fine-tuning falls from 30/40 to 16/40 (Holm $p = 0.0130$, six comparisons), and rules remain at 23/40. Hiding letters yields 0/39, 3/40 and 0/40, respectively. Nine of eleven fine-tuned wrong bindings after reassignment follow the old mapping. This suggests learned shortcuts, although it does not prove memorization as the sole cause. One reassignment cannot establish broad generalization or equivalence.

Dice layout transfer. A separate 240-trial study changes the die's visible layout by rotating its visual mesh. Collision geometry, inertia and the prompt separating dot counts from motor-skill IDs stay fixed. Each condition has 40 matched trials with no exclusions. Under the changed layout, exploratory paired tests give $p = 2.98 \times 10^{-8}$ against fine-tuning and $p = 5.96 \times 10^{-8}$ against rules. REVEAL's own layout difference is not significant ($p = 0.688$), which does not prove equivalence. REVEAL also uses inspection, history and noisy feedback, so the result compares complete systems.

Language and wording coverage. We test standard and rewritten instructions in English and Chinese on three objects: 60 trials per condition across three seeds, totaling 2,160 trials. Table 2 compares the same service-eligible trials for all methods. We keep weights, mappings and scoring fixed, without retraining for Chinese. The rule baseline also translates its task/output instructions. This tests language coverage of the deployed systems. The supplement retains all raw outcomes, including service failures.

REVEAL reaches 67.8–76.7% on duck and 73.3–76.7% on hedgehog. It outperforms fine-tuning in all eight conditions (Holm-adjusted paired $p \leq 0.0258$ across 36 method comparisons). Six of eight differences against rules remain significant after correction. On cube, REVEAL leads numerically in three conditions, while fine-tuning leads for rewritten Chinese instructions (81.1% versus 67.9%). None of these four differences is significant (all adjusted $p = 1.0$). Requiring exact state and image matching preserves these significance decisions. No language or wording comparison is significant after its separate 36-test correction, which does not prove equivalence.

5.3. Q2: Controller ablations on the cube

We compare four ways to control the hand while the agent is reasoning: continue the student's command, slow it by a fixed coefficient of 0.15, learn the slowing coefficient, or learn slowing together with a bounded joint correction. All four use the same execution controller when no request is pending. Each method has 120 trials, with 40 per seed across three seeds.

Learned slowing with joint correction achieves 104/120 successes (86.7%), compared with 88/120 (73.3%) for fixed slowing, a gain of 13.3 percentage points. Waiting drops decrease from 13 to five, and execution drops from eight to four. Learning speed alone gives 82/120 successes (68.3%), below fixed slowing. The results favor learning speed and joint correction together. Drop stages tell us when failure occurs, but do not identify its cause. Seed settings and outcome breakdowns are in the supplement.

5.4. Q3: Active Target Search and Visual Feedback

Three separate paired experiments examine the search process (Table 4): continuing to observe and decide, receiving new images, and choosing where and how long to inspect. Each comparison uses its own trial set.

(a) Does continued feedback help find the target? The initial plan selects up to six bounded actions from one image and measured feedback. Full feedback allows up to six calls with new images and history. Both use the same local controllers, stopping rule and time limit. Success rises from 6/39 to 33/39 eligible trials: 27 pairs succeed only with feedback and none only with the initial plan (exact $p =$

Object	Motor pose	$n_{\text{orig}}/n_{\text{changed}}$	Original mapping			Changed mapping		
			Rule	Fine-tuned	REVEAL	Rule	Fine-tuned	REVEAL
Cube	RGB pose	40 / 40	57.5	75.0	**80.0**	57.5	40.0	**80.0**
Die	Noisy pose	40 / 40	32.5	57.5	**70.0**	2.5	0.0	**65.0**
Duck	Noisy pose	38 / 40	39.5	36.8	**65.8**	22.5	5.0	**60.0**
Hedgehog	Noisy pose	39 / 40	43.6	33.3	**71.8**	25.0	5.0	**80.0**
Pig	Noisy pose	40 / 40	52.5	40.0	**92.5**	37.5	7.5	**82.5**
Milk carton	Noisy pose	40 / 40	32.5	22.5	**42.5**	7.5	2.5	**27.5**
Mean	Object-specific	–	43.0	44.2	**70.4**	25.4	10.0	**65.8**

Table 1. **Q1: six objects and two semantic mappings.** Completion (%) uses common service-eligible trials; each cell has 40 scheduled trials. Mean weights six objects equally. Bold denotes the highest observed rate, not significance. Object-specific weights remain fixed across mappings; bare baselines omit added control modules. Cube uses reconstructed upper images and RGB pose; die rotates its visual mesh; other objects permute surface letters with noisy simulator pose. Native-image and language cohorts remain separate.




Figure 5. **Recorded inspection before binding.** Unretouched model-input frames from a recorded simulated trial. The initial plan abstains; feedback reveals T, then REVEAL binds T to red and completes at step 420 (true error 0.0812 radians). Both arms start from identical state and image. This selected example illustrates evidence acquisition, not wrong-binding correction or hardware performance.

1.49×10^{-8}). One service failure excludes a matched pair. Of 28 initial-plan abstentions, 22 succeed with feedback; 32 feedback trials first bind after inspection. Figure 5 illustrates this search process. This comparison also changes the call budget.

(b) Does the next image provide useful evidence? Both conditions allow six calls with the same request rule, live numeric feedback, history and local control. Only the agent's RGB input changes: the current image versus the exact first frame on every call. Success is 32/40 versus 9/40, with all 23 pairs with different outcomes favoring fresh images (exact $p = 2.38 \times 10^{-7}$). Correct terminal bindings number 34 versus nine. Both conditions first bind correctly on call one in the same nine trials. Fresh images enable 25 additional correct bindings later, of which 23 lead to success; repeated first frames enable none. Drops differ by only one. These records connect new observations to target binding and completion. They measure declared bindings, not initial visibility or first visual recognition.

(c) Does choosing the next view help? Forty new pairs compare agent-selected inspection directions and durations with a fixed color sweep of 90-step actions. Both use the same model, controllers, fresh images, history format and stopping rule. Feedback reports the action actually executed. The model still decides whether to inspect, bind or abstain in both conditions. Adaptive inspection achieves 38/40 successes (95.0%), compared with 31/40 (77.5%) for the fixed sweep. Nine pairs favor adaptive and two favor fixed inspec-

System	English Standard	English Rewrite	Chinese Standard	Chinese Rewrite
Cube (n)	56	59	57	53
Rule VLM	48.2	45.8	31.6	32.1
Fine-tuned VLM	71.4	72.9	75.4	**81.1**
REVEAL	**75.0**	**79.7**	**84.2**	67.9
Duck (n)	60	59	60	60
Rule VLM	50.0	25.4	33.3	31.7
Fine-tuned VLM	38.3	30.5	31.7	35.0
REVEAL	**68.3**	**67.8**	**68.3**	**76.7**
Hedgehog (n)	60	60	52	60
Rule VLM	46.7	38.3	36.5	36.7
Fine-tuned VLM	38.3	31.7	34.6	25.0
REVEAL	**73.3**	**76.7**	**75.0**	**76.7**

Table 2. **Q1: language and wording coverage.** Completion (%) on common service-eligible trials. Methods share the listed n of 60 scheduled slots. Bold denotes the highest observed rate, not significance. Raw counts and paired analyses are in the supplement.

Waiting policy	Success	%	Wait drops	Exec. drops	Other
Continue student	73/120	60.8	24	14	9
Fixed slowing	88/120	73.3	13	8	11
Learned slowing	82/120	68.3	7	14	17
Slowing + correction	**104/120**	**86.7**	**5**	**4**	**7**

Table 3. **Q2: controller ablation on the cube.** Each method has 120 trials across three seeds. Wait and execution drops denote failure stages; Other contains the remaining failures. Outcome counts sum to 120 in each row.

Condition	Success	%	Drops	Calls
(a) Continued feedback: one vs. up to six calls				
One initial plan	6/39	15.4	0	40
Full feedback	33/39	84.6	5	120
(b) Fresh visual evidence: same six-call cap				
Current image	32/40	80.0	3	112
Repeated first frame	9/40	22.5	4	98
(c) Inspection policy: same model and controllers				
Fixed sweep	31/40	77.5	1	126
Adaptive inspection	38/40	95.0	0	117

Table 4. **Q3: active target search on the cube.** Each panel has 40 scheduled trials per condition. (a) excludes one service-affected pair and reuses Q2's initial full-feedback subset. (b) changes only the agent's RGB input. (c) changes inspection direction and duration. (b,c) have no exclusions. Drops/calls include all trials; actual inference cost differs.

tion, giving a 17.5-point observed gain (exact $p = 0.0654$). Correct terminal bindings are 39 versus 32, with zero versus one drop. This suggests a benefit from choosing inspection actions, but the success difference is not significant at $\alpha = 0.05$ and tests only one fixed sweep.

5.5. Q4: Multi-object hardware evaluation

Hardware protocol. **[TODO: Complete the multi-object physical-hand evaluation.]** No hardware outcomes are available yet. The planned comparison uses REVEAL and two baselines per object, reporting completion, drops, false stops and inference cost. The supplement details calibration, resets, independent scoring and synchronized videos.

6. Discussion and Limitations

Search and control. Fresh images help the agent bind targets that it does not bind from the first view. The inspection-policy comparison shows a favorable but statistically unresolved trend. Together with the controller ablation, these studies examine evidence gathering and control during inference. Q1 compares complete systems and cannot separate all model, inspection, controller and stopping effects. Q2/Q3 mechanisms are tested only on the cube.

Evaluation limits. Two Q2 seeds are available only as combined counts, preventing seed-level variability estimates and paired tests. We have not isolated the benefit of controller-goal input or compared with a generic time-aware residual controller. Equal call limits do not ensure equal inference cost. We test one changed mapping per object and limited English/Chinese templates. Success checks binding and pose at termination, without an independent visibility check or a post-stop hold. It also requires a twist not specified by the instruction.

Deployment scope. Each object uses separate weights. Cube pose comes from rendered RGB; other objects use noisy simulator pose. Real-camera performance, transfer to new objects and hardware execution remain untested. Hosted models may change over time, limiting reproducibility. Rates excluding service failures do not measure end-to-end availability.

7. Conclusion

REVEAL connects active visual search and target binding to continuous in-hand control. Across six object-specific systems, mean success is 70.4% with original mappings and 65.8% with changed mappings. Cube studies show how fresh observations support target binding and how joint correction helps during inference. Adaptive inspection offers a promising but statistically unresolved gain over a fixed sweep. Physical-hand tests remain necessary to assess deployment.

LLM Usage Statement

OpenAI Codex assisted with research discussion, implementation, experiment orchestration, literature retrieval, statistical analysis, figure-layout code, and drafting and editing throughout the manuscript. A hosted vision-language model and Qwen3-VL are evaluated system components. Numerical claims are grounded in recorded experiments; unfinished work is identified explicitly. The authors are responsible for verifying the text, references, code, figures, and results before submission.

References

[1] Marcin Andrychowicz, Bowen Baker, Maciek Chociej, Rafal Józefowicz, Bob McGrew, Jakub Pachocki, Arthur Petron, Matthias Plappert, Glenn Powell, Alex Ray, Jonas Schneider, Szymon Sidor, Josh Tobin, Peter Welinder, Lilian Weng, and Wojciech Zaremba. Learning dexterous in-hand manipulation. *The International Journal of Robotics Research*, 39(1):3–20, 2020. 2

[2] Shuai Bai, Yuxuan Cai, Ruizhe Chen, Keqin Chen, Xionghui Chen, Zesen Cheng, Lianghao Deng, Wei Ding, Chang Gao, Chunjiang Ge, Wenbin Ge, Zhifang Guo, Qidong Huang, Jie Huang, Fei Huang, Binyuan Hui, Shutong Jiang, Zhaohai Li, Mingsheng Li, Mei Li, Kaixin Li, Zicheng Lin, Junyang Lin, Xuejing Liu, Jiawei Liu, Chenglong Liu, Yang Liu, Dayiheng Liu, Shixuan Liu, Dunjie Lu, Ruilin Luo, Chenxu Lv, Rui Men, Lingchen Meng, Xuancheng Ren, Xingzhang Ren, Sibo Song, Yuchong Sun, Jun Tang, Jianhong Tu, Jianqiang Wan, Peng Wang, Pengfei Wang, Qiuyue Wang, Yuxuan Wang, Tianbao Xie, Yiheng Xu, Haiyang Xu, Jin Xu, Zhibo Yang, Mingkun Yang, Jianxin Yang, An Yang, Bowen Yu, Fei Zhang, Hang Zhang, Xi Zhang, Bo Zheng, Humen Zhong, Jingren Zhou, Fan Zhou, Jing Zhou, Yuanzhi Zhu, and Ke Zhu. Qwen3-VL technical report. *arXiv preprint arXiv:2511.21631*, 2025. 2

[3] Arjun Bhardwaj, Mayank Mittal, Maximum Wilder-Smith, Vaishakh Patil, and Marco Hutter. GoalDex: Learning image-goal-conditioned policies for dexterous in-hand manipulation. *arXiv preprint arXiv:2611.02171*, 2026. 2

[4] Arjun Bhardwaj, Maximum Wilder-Smith, Mayank Mittal, Vaishakh Patil, and Marco Hutter. ViserDex: Visual sim-to-real for robust dexterous in-hand reorientation. *arXiv preprint arXiv:2604.11138*, 2026. 2

[5] Kevin Black, Manuel Galliker, and Sergey Levine. Real-time execution of action chunking flow policies. In *Advances in Neural Information Processing Systems*, pages 33383–33407, 2025. 2

[6] Ning Chen, Yankai Fu, Junkai Zhao, Qianpu Sun, Guocai Yao, Pengwei Wang, Zhongyuan Wang, and Shanghang Zhang. LiMA: Bridging long-term imagination to real-time dexterous manipulation via asynchronous diffusion. *arXiv preprint arXiv:2609.28431*, 2026. 2

[7] Tao Chen, Jie Xu, and Pulkit Agrawal. A system for general in-hand object re-orientation. In *Proceedings of the 5th Conference on Robot Learning*, pages 297–307, 2022. 2

[8] Wenlong Huang, Chen Wang, Ruohan Zhang, Yunzhu Li, Jiajun Wu, and Li Fei-Fei. VoxPoser: Composable 3D value maps for robotic manipulation with language models. In *Proceedings of the 7th Conference on Robot Learning*, pages 540–562, 2023. 2

[9] Wenlong Huang, Fei Xia, Ted Xiao, Harris Chan, Jacky Liang, Pete Florence, Andy Zeng, Jonathan Tompson, Igor Mordatch, Yevgen Chebotar, Pierre Sermanet, Tomas Jackson, Noah Brown, Linda Luu, Sergey Levine, Karol Hausman, and Brian Ichter. Inner monologue: Embodied reasoning through planning with language models. In *Proceedings of the 6th Conference on Robot Learning*, pages 1769–1782, 2023. 2

[10] Wenlong Huang, Chen Wang, Yunzhu Li, Ruohan Zhang, and Li Fei-Fei. ReKep: Spatio-temporal reasoning of relational keypoint constraints for robotic manipulation. In *Proceedings of the 8th Conference on Robot Learning*, pages 4573–4602, 2025. 2

[11] Brian Ichter, Anthony Brohan, Yevgen Chebotar, Chelsea Finn, Karol Hausman, Alexander Herzog, Daniel Ho, Julian Ibarz, Alex Irpan, Eric Jang, Ryan Julian, Dmitry Kalashnikov, Sergey Levine, Yao Lu, Carolina Parada, Kanishka Rao, Pierre Sermanet, Alexander T. Toshev, Vincent Vanhoucke, Fei Xia, Ted Xiao, Peng Xu, Mengyuan Yan, Noah Brown, Michael Ahn, Omar Cortes, Nicolas Sievers, Clayton Tan, Sichun Xu, Diego Reyes, Jarek Rettinghouse, Jornell Quiambao, Peter Pastor, Linda Luu, Kuang-Huei Lee, Yuheng Kuang, Sally Jesmonth, Nikhil J. Joshi, Kyle Jeffrey, Rosario Jauregui Ruano, Jasmine Hsu, Keerthana Gopalakrishnan, Byron David, Andy Zeng, and Chuyuan Kelly Fu. Do as i can, not as i say: Grounding language in robotic affordances. In *Proceedings of the 6th Conference on Robot Learning*, pages 287–318, 2023. 2

[12] Kailin Li, Puhao Li, Tengyu Liu, Yuyang Li, and Siyuan Huang. ManipTrans: Efficient dexterous bimanual manipulation transfer via residual learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 6991–7003, 2025. 2

[13] Sizhe Lester Li, Evan Kim, Xingjian Bai, Tong Zhao, Tao Pang, Max Simchowitz, and Vincent Sitzmann. Turning video models into generalist robot policies. *arXiv preprint arXiv:2605.27817*, 2026. 2

[14] Jacky Liang, Wenlong Huang, Fei Xia, Peng Xu, Karol Hausman, Brian Ichter, Pete Florence, and Andy Zeng. Code as policies: Language model programs for embodied control. In *Proceedings of the IEEE International Conference on Robotics and Automation*, pages 9493–9500, 2023. 2

[15] Haozhi Qi, Ashish Kumar, Roberto Calandra, Yi Ma, and Jitendra Malik. In-hand object rotation via rapid motor adaptation. In *Proceedings of the 6th Conference on Robot Learning*, pages 1722–1732, 2023. 2

[16] Haozhi Qi, Brent Yi, Sudharshan Suresh, Mike Lambeta, Yi Ma, Roberto Calandra, and Jitendra Malik. General in-hand object rotation with vision and touch. In *Proceedings of the 7th Conference on Robot Learning*, pages 2549–2564, 2023. 2

[17] Stephane Ross, Geoffrey Gordon, and Drew Bagnell. A reduction of imitation learning and structured prediction to no-regret online learning. In *Proceedings of the Fourteenth*

International Conference on Artificial Intelligence and Statistics, pages 627–635, 2011. 3

[18] Kohei Sendai, Maxime Alvarez, Tatsuya Matsushima, Yutaka Matsuo, and Yusuke Iwasawa. Leave no observation behind: Real-time correction for VLA action chunks. *arXiv preprint arXiv:2509.23224*, 2025. 2

[19] Michael Tschannen, Alexey Gritsenko, Xiao Wang, Muhammad Ferjad Naeem, Ibrahim Alabdulmohsin, Nikhil Parthasarathy, Talfan Evans, Lucas Beyer, Ye Xia, Basil Mustafa, Olivier Hénaff, Jeremiah Harmsen, Andreas Steiner, and Xiaohua Zhai. SigLIP 2: Multilingual vision-language encoders with improved semantic understanding, localization, and dense features. *arXiv preprint arXiv:2502.14786*, 2025. 3

[20] Jianwei Yang, Reuben Tan, Qianhui Wu, Ruijie Zheng, Baolin Peng, Yongyuan Liang, Yu Gu, Mu Cai, Seonghyeon Ye, Joel Jang, Yuquan Deng, and Jianfeng Gao. Magma: A foundation model for multimodal AI agents. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 14203–14214, 2025. 2

[21] Max Yang, Chenghua Lu, Alex Church, Yijiong Lin, Christopher J. Ford, Haoran Li, Efi Psomopoulou, David A. W. Barton, and Nathan F. Lepora. AnyRotate: Gravity-invariant in-hand object rotation with sim-to-real touch. In *Proceedings of the 8th Conference on Robot Learning*, pages 4727–4747, 2025. 2

[22] Brian Zhu, Momen Khalil, E Harrison, Emanuele Poggi, Philipp Schmitt, Bernd Kast, Philine Meister, Pranav Atreya, Qiyang Li, Finn Ferchau, Cesar Colmenero, Yash Shahapurkar, Gokul Narayanan, Melih Erdogan, Kai Wurm, Georg von Wichert, Oier Mees, Eugen Solowjow, Andrew Wagenmaker, and Sergey Levine. Learning to act while waiting: RL finetuning of generalist robot policies under inference latency. *arXiv preprint arXiv:2608.23831*, 2026. 2

[23] Yixiang Zhu, Yonghao Chen, Jiaxiang Zou, Yusong Hu, and Xinyu Chen. DEFLECT: Temporal counterfactual preference learning for delay-robust asynchronous VLAs. *arXiv preprint arXiv:2605.19294*, 2026. 2