AgenticRotation: Learning Local Control for Asynchronous Visual Agents in Semantic In-Hand Reorientation

Anonymous CVPR submission

Abstract

A visual agent can identify the object face requested by a user, but a dexterous hand must maintain contact while that decision is being computed. We study semantic in-hand reorientation with asynchronous visual reasoning and continuous physical execution. AgenticRotation connects a visual agent to a pose-conditioned recurrent student through a common semantic goal representation. Lightweight local controllers adapt joint targets using measured state and public request history, supervised by a privileged teacher during training. On a marked cube with 40 matched trials per system, the full Astra system achieves 87.5% autonomous semantic success, compared with 75.0% for a bare fine-tuned VLM and 42.5% for a bare rule VLM. A separate waiting ablation gives 62.5% for continued execution and 85.0% for learned slowing with joint correction. The Astra–fine-tuned difference and the three adjacent waiting contrasts remain statistically unresolved. With the same motor controllers, continued feedback raises completion from 6/39 with one initial plan to 33/39 with up to six calls. Under a controlled letter–color remapping, Astra retains 32/40 successes while the fine-tuned model falls from 30/40 to 16/40. These results support continued visual feedback while exposing limits of the current control and grounding modules. ***[TODO: Add multi-object, improved-predictor, and physical-hand results.]***

1. Introduction

A command such as "turn the face marked T upward" specifies a visual relation, not a sequence of joint targets. A robot must locate the mark, associate it with a controllable orientation, and move the object without losing it. The requested face may initially be hidden by the object itself or by the fingers. Moving to obtain evidence changes both visibility and contact. This coupling makes in-hand reorientation a useful setting for studying visual agents that act through physical feedback.

Large visual models provide a flexible interface between an instruction and an action. Their inference time introduces another problem. The hand cannot assume that the object remains in place while an external model reasons. Continuing the current skill can expose useful evidence or destabilize the grasp. Slowing every action can reduce movement without supplying the corrective motion needed to recover. A suitable local controller must act on the current contact state even when the next semantic decision is unavailable.

We investigate the following question: *how should a dexterous controller execute a visual agent's current intention while a new decision is pending, and resume useful motion after it arrives?* Our system separates the semantic decision rate from the motor control rate. An asynchronous agent requests inspection, binds a visible target, and updates its command from feedback. A recurrent student maps a goal representation and measured object pose to joint targets. Two compact learned controllers adapt those targets during pending requests and ordinary execution. This design permits a local policy to react without a second expensive reasoning call.

The visual and control interfaces are explicit. We adapt a ViserDex-style RGB-to-pose policy [1] to a continuous semantic goal input while reusing compatible recurrent weights. A fine-tuned local VLM directly predicts a goal vector. The Astra implementation instead emits validated public tool arguments that are mapped to the same goal space. Thus the controller consumes a common representation, but the Astra branch does not expose hidden model embeddings. The distinction makes it possible to compare a strong external agent with a compact learned grounding model without changing the deployed motor interface.

We freeze the task mapping, checkpoints, stopping path, and physical success rule before evaluation. Each system retains 40 raw trials, with service exclusions applied symmetrically within a comparison. Physical reach is reported separately from correct semantic binding and autonomous completion.

Our latest cube evaluation gives 35/40 successes for the complete system, 30/40 for the bare fine-tuned VLM, and 17/40 for the bare rule VLM. A new matched study compares continued execution, fixed slowing, learned slowing, and learned slowing with joint correction while keeping non-pending execution fixed. Two complementary interventions examine the agent: removing subsequent feedback




Figure 1. **Continuous control around asynchronous semantic decisions.** The visual agent selects an inspection or target skill. Its validated public command determines a semantic goal vector. A frozen RGB pose estimator and recurrent student run underneath this interface. Separate learned actors adapt joint targets while a request is pending and during execution. The hand continues moving during inference. A common measured-pose gate decides when to stop, and an independent evaluator checks true task completion. The fine-tuned VLM baseline predicts its vector directly and uses the same student without the added actors.

sharply reduces completion, and changing the letter–color association exposes a weakness of the fine-tuned grounding baseline. These studies test different mechanisms and are reported as separate cohorts. Earlier results and unsuccessful controller variants remain part of the evidence.

This work develops three contributions: (1) a semantic control interface that connects asynchronous visual decisions to a recurrent dexterous student, (2) teacher-supervised local adaptation that maintains physical execution during reasoning and resumes goal-directed motion afterward, and (3) matched feedback and visual-semantic interventions that separate useful observation, contact failure, and service availability. Current results support continued feedback and give a favorable estimate for joint correction. They do not establish the three adjacent waiting gains, an explicit controller-goal benefit, or a stable advantage over the fine-tuned model. Multi-object and hardware validation remain necessary.

2. Related Work

Visual dexterous manipulation. ViserDex uses monocular visual pose estimation and recurrent control for dexterous reorientation, with Gaussian representations supporting visual training [1]. We reuse this division between perception and control and adapt a released Revo3 policy to semantic goals. ManipTrans studies residual learning for dexterous bimanual transfer [4]. These works motivate a reusable motor policy and residual adaptation. Our residual parameterization alone is not a novelty claim. The question here is how a local policy should condition its behavior on the phase and intention of an asynchronous semantic agent.

Language and visual agents. Magma connects multimodal representations to agent actions [10]. VERA translates visual plans into robot actions and includes language-conditioned dexterous in-hand reorientation [5]. Its hand experiments include directional rotation prompts. Consequently, language-guided in-hand rotation is not an unoccupied task category. Our setting emphasizes identifying a requested marked face under occlusion, maintaining contact during external reasoning, and checking a canonical target at autonomous stopping. Those distinctions require direct evidence, rather than a claim of being the first language-controlled hand.

Asynchronous robot policies. Real-time chunk execution [2], online corrections for VLA chunks [8], and latency-aware RL [11] address inference delays through different execution and learning designs. DEFLECT studies delay-robust asynchronous VLAs through temporal counterfactual preferences [12]. LiMA combines sparse semantic intention and asynchronous action generation for dexterous manipulation [3]. These are close methodological references. Our current implementation learns small teacher-supervised controllers around a separate recurrent policy and public semantic tools. A controlled comparison with a generic time-aware residual policy is still needed to show that the active semantic goal and request anchor add value beyond reactive correction.

3. Task and Evaluation Contract

Semantic target. The current object is a cube with six marked faces. An instruction identifies one letter from $\{T, E, R, L, S, H\}$. Each face has a fixed color and a canonical world orientation $Q(g)$ that places its normal upward. The environment scores the full canonical quaternion, including its fixed twist, rather than accepting every orientation with the correct normal. The language prompt is therefore less specific than the scoring convention. This convention is disclosed and held constant for all methods. A face-normal-only score can be reported as an additional diagnostic without replacing the primary metric.

At step t, the agent observes RGB evidence I_t and the instruction ℓ. The motor system observes proprioception x_t and measured pose $\hat{p}_t$. True pose p_t, teacher actions, and future semantic responses are unavailable to online control. The simulator exposes them only for training labels and independent scoring. We denote the active goal vector by g_t, recurrent state by h_t, and the pending-request flag by m_t.

Physical time. One request may be pending at a time. The default protocol allows six model calls per episode and 3,600 logical control steps at 30 Hz. If a call starts at k and takes L wall-clock seconds, its response becomes usable only after the call completes and at least $\lceil 30L \rceil$ control steps have elapsed. Physics continues throughout this interval. The simulator currently runs slower than real time. This protocol represents inference delay in simulated physical time, but does not demonstrate a 30 Hz hardware pipeline.

Autonomous completion. All systems share a measured-pose stopping gate, evaluated at 3 Hz. It requires a declared binding for the requested symbol, no pending request, a non-inspection state, and measured full-orientation error at most $\epsilon = 0.16$ radians. The gate may stop independently of an agent's native stop suggestion. At stop time τ, the independent success variable is

$$S = \mathbf{1}\left[\hat{b}_\tau = b^*(\ell),\ d(q_\tau, Q(b^*)) \le \epsilon,\ \neg D_{0:\tau}\right], \quad (1)$$

where $\hat{b}_\tau$ is the declared face binding, q_τ is true orientation, $D_{0:\tau}$ indicates an earlier terminal drop, and $d(q, Q) = 2\arccos(|\langle q, Q\rangle|)$ for normalized quaternions. Merely passing through a target does not count. No extra hold duration is added after stopping. A pose false stop and a semantically wrong binding are failures even if the hand retains the object. The frozen drop rule is distance of at least 0.24 metres from the nominal object grasp position.

Matched reporting. Every arm uses 40 raw trials from two seeds, with 20 trials per seed and matching initial physical states and scored physical targets. Instructions also match within the control and feedback studies. In the remapping study, the requested letter changes with the mapping to preserve the physical target. A service error or measured model latency above 120 seconds is recorded as a service exclusion. For a panel of methods $\mathcal{C}$, the eligible set removes the union of excluded trial identifiers across $\mathcal{C}$. We report both raw and eligible outcomes, never replace an excluded trial, and never mix denominators from different panels. Long service delays remain visible without being interpreted as controller failures.

4. Method

Figure 1 summarizes AgenticRotation. The system has a semantic interface, a visual motor policy, and local adaptation. The semantic interface changes the active intention. The local controllers change how that intention is executed using current measurements.

4.1. Reusing a visual pose-conditioned student

A frozen CNN predicts the image coordinates and depth of the object center and eight keypoints from a 120×120 RGB image. Calibration, unprojection, and rigid fitting recover $\hat{p}_t \in \mathbb{R}^7$, comprising position and an XYZW quaternion. The fit residual accompanies the measurement. The current rendering uses the object's Gaussian representation with live black hand occlusion. It is not a full-scene image or a real-camera observation, and no ground-truth pose fallback is used at deployment.

The inherited student expects geometric goals. We replace its goal channels with a learned projection of $g_t \in \mathbb{R}^{768}$:

$$z_t = \tanh(W_g g_t + b_g) \in \mathbb{R}^{64}, \quad (2)$$

$$(u_t, h_{t+1}) = \pi_\theta([x_t, z_t], \hat{p}_t, h_t). \quad (3)$$

Here $x_t \in \mathbb{R}^{109}$ contains target-free proprioceptive features and history, while $u_t \in \mathbb{R}^{21}$ gives normalized joint-target proposals. Compatible encoders, recurrent weights, actor weights, and normalization statistics are initialized from the released policy. Neither target quaternion nor relative-goal quaternion is an input to the migrated student.

The first training stage fits the new interface while preserving inherited coefficients. A second stage adapts the recurrent core using actions labeled by the frozen privileged teacher. Teacher and student rollouts are mixed in a DAgger-style procedure [7]. The frozen release uses 200 interface updates and 400 adaptation updates, each with 128 environments and 45 rollout steps, totaling 3,456,000 transitions. These stages use simulated pose noise. All reported closed-loop trials instead obtain pose from the frozen CNN. We separately measure the loss introduced by this transfer rather than assuming that initialization preserves the teacher's performance.

4.2. Semantic grounding and public actions

We maintain six normalized goal vectors $B = \{g_1, \ldots, g_6\}$ from cached SigLIP2 text features [9]. Each vector denotes a color skill and is bound to a canonical orientation in the audited asset. The goal bank is fixed for the cube release.

Astra interface. Astra receives the requested letter and visual observations. It emits a validated public action from `inspect_face`, `reorient_target`, `verify_target`, `stop`, or `abstain`. A color argument selects a vector from B. Inspection can change the motor goal without declaring that the requested letter has been found. Inspection actions can request between 10 and 90 control steps. Subsequent visual evidence and public action history support another decision. We use the name Astra for the hosted route `gpt-6-astra` recorded in our experiment, not for a model trained here. Its exact reproducible provider version is a release requirement.

The vector delivered to the student is a local encoding of a public command. We do not access Astra's internal features, train Astra weights, or describe this pathway as end-to-end language-to-action learning. This explicit interface also enables fixed-public-plan diagnostics in which the motor system is evaluated under recorded decisions and delays.

Fine-tuned VLM. The compact baseline uses Qwen3-VL-4B-Instruct [6] with low-rank adaptation and a goal head. The head predicts a normalized continuous vector in the centered five-dimensional span of B, together with a readability probability. The continuous vector enters Eq. 3 directly. Its nearest canonical vector determines the declared binding and the orientation used by the shared stopping gate. This interface is not unrestricted open-vocabulary motor generation.

Let y indicate whether the requested mark is readable, k its skill index, and $\hat{g}$ the predicted goal. Training combines readability binary cross-entropy with positive-example goal classification and cosine alignment:

$$\mathcal{L}_{\text{ground}} = \text{BCE}(\hat{y}, y) + \mathbf{1}[y = 1]\big(\text{CE}(\hat{k}, k) + 1 - \cos(\hat{g}, g_k)\big). \tag{4}$$

The implementation averages positive terms over readable examples. Readability supervision uses geometric visibility and an image-signal filter, not human judgments. Training first uses teacher-view data and then includes observations from student trajectories. The current objective does not include an action-consistency loss.

Rule VLM. The rule baseline parses a color and readability decision from the local VLM and maps accepted colors to B. Both local baselines use the same fixed inspection sequence when a view is not accepted. They use the migrated student directly, with no learned waiting actor, execution actor, or learned completion correction. This is the primary complete-system comparison. A separate auxiliary comparison adds the same control actors to each provider to examine the control contribution.

4.3. Learning control while a request is pending

An outstanding query does not determine whether the current movement is still safe. We construct a deployable feature vector s_t from proprioception, measured pose, student belief, proposed action, pose-fit residual, semantic binding status, and request status. It also includes the measured pose and command at the request anchor and elapsed pending time. The active goal g_t is encoded separately. Before a binding is established it denotes the startup or inspection skill, not the unavailable future target.

A 192-dimensional sensor encoder and 64-dimensional goal encoder feed a 128-dimensional fusion layer. A waiting actor produces one speed logit r_t and a residual $v_t \in \mathbb{R}^{21}$. Let $\bar{q}_t$ be normalized current joint position and $\bar{u}_t$ the clipped student proposal. The applied command is

$$\alpha_t = \text{sigmoid}(4r_t + \text{logit}(0.15)), \tag{5}$$

$$b_t = \begin{cases} \bar{q}_t + \alpha_t(\bar{u}_t - \bar{q}_t), & m_t = 1, \\ \bar{u}_t, & m_t = 0, \end{cases} \tag{6}$$

$$a_t = \text{clip}\big(b_t + 0.35\tanh(v_t), -1, 1\big). \tag{7}$$

Zero outputs reproduce fixed slowing with a coefficient of 0.15 during a pending query. The coefficient scales the proposed joint-position displacement while simulation time and the control loop continue to advance. The environment applies its original joint mapping and smoothing. Scalar slowing restricts the command to the segment between current joint position and the student proposal. The joint residual can change the command outside that segment, which permits contact adjustments that a speed coefficient alone cannot express.

Waiting targets are generated by the frozen teacher with the request anchor as the holding objective. This supervision is available in simulation. The deployed actor receives measurements and the active goal only. It never receives the answer being computed. The objective fits the applied action to the teacher label and penalizes residual magnitude:

$$\mathcal{L}_{\text{control}} = \mathbb{E}_{(s,g,a^*)\sim\mathcal{D}}\left[\|a_\phi(s,g) - a^*\|_2^2 + 0.01\|\delta_\phi(s,g)\|_2^2\right]. \tag{8}$$

Refitting the waiting policy. The waiting actor is refitted for 2,400 updates on separately collected measured-state trajectories. Each actor batch contains one half pending states and one quarter each unbound and bound execution

states. A separate fixed-plan development gate selects uniform pending sampling over a startup-balanced candidate. Only pending-request outputs are deployed. Execution, student, predictor, and stopping remain fixed. The supplement records selection and fresh live confirmation. Neither uses the subsequent three-system or Q2/Q3 test outcomes.

4.4. Learning execution after a decision

A second actor with the same architecture serves non-pending execution. It uses the student proposal as its base, with no speed attenuation, and learns the bounded correction in Eq. 7. Its target is the teacher action for the active goal. It can remain active throughout execution, including inspection, rather than only during a short handover interval.

Paired training examples reuse a physical state and recurrent history with different valid goals. Features and teacher labels are reconstructed for each goal. The motivation is that a generic holding action can preserve contact without moving toward the requested orientation. Goal-dependent labels give the actor a reason to retain directional information. This data construction does not itself demonstrate that the deployed network uses semantics. We test this mechanism with a matched no-explicit-goal actor, shuffled-goal evaluation, and restored-state interventions. The completed tests do not establish a benefit from the explicit actor-goal pathway (Sec. 5).

Training also includes states collected under recorded public action and delay schedules, matching the controller's pending and execution phases more closely to deployment. The selected execution actor is the v6 candidate from development. The same weights are retained throughout the frozen evaluation. The original development selection was informed by observed development outcomes, not a blind preregistration. Reserved evaluation results did not select the checkpoint. Learned completion heads were explored during development but are not active in the reported release.

4.5. Closed-loop execution

At each control step, the system updates visual pose, advances the recurrent student, chooses the waiting or execution actor, and applies the resulting joint targets. A completed semantic response is validated before it changes the active skill or declared binding. The next image reflects the motion that occurred while the previous response was pending. The common stopping gate is checked separately from semantic action generation. Invalid model output cannot supply ground-truth information or silently select the requested target.

Student adaptation and controller learning are evaluated separately. A new student changes the belief and proposal distribution seen by the controllers. Their checkpoint-bound weights therefore require compatibility validation before transfer.

5. Experiments

We organize evaluation around four questions: **Q1** How do complete systems compare under original and changed semantic mappings? **Q2** How should the hand move while the agent is thinking? **Q3** Is an initial plan sufficient, or does continued visual feedback help? **Q4** How do perception and control transfer to a physical hand? Cube system comparisons and the 200-trial matched waiting/feedback cohort are complete. Additional objects, predictor improvements, and hardware results remain TODO.

5.1. Setup and reporting

Experiments use Revo3 cube assets in Isaac Lab 3.0/Newton with validated contact capacities. Each condition has two seeds and 40 scheduled trials. Initial physical states are matched within each study. All systems use the same frozen pose estimator, goal bank, latent student, 0.16-radian success threshold, and measured-pose stopping gate. The primary fine-tuned and rule VLM baselines omit the added waiting and execution actors. Astra uses adaptive inspection, whereas the local baselines use a fixed unreadable-view schedule. This is a comparison of complete systems, with natural model latencies, rather than an isolated test of model weights.

The latest Astra system replaces only its waiting actor. Earlier release cohorts, module interventions, and fixed-public-plan development tests are kept separate. Table percentages use common service-eligible trials within the stated comparison. All raw records are retained, and no failed or excluded slot is replaced. Wilson intervals describe individual rates. The new waiting contrasts and six registered visual contrasts use Holm correction within their respective families. Historical paired tests remain exploratory and unadjusted.

5.2. Q1: Complete systems and object coverage

The latest full Astra system succeeds in 35/40 trials (87.5%), compared with 30/40 (75.0%) for the bare fine-tuned VLM and 17/40 (42.5%) for the bare rule VLM (Table 1). Astra has nine exclusive successes against four for the fine-tuned VLM, giving exact paired $p = 0.267$. The 12.5-point difference is therefore a favorable estimate, not established superiority. Against the rule VLM, the corresponding counts are twenty and two ($p = 0.000121$).

Earlier cohorts are retained. Earlier Astra/fine-tuned/rule cohorts give 29/39, 26/39, 13/39 and 26/37, 27/37, 21/37. Neither establishes Astra superiority over fine-tuning. The latest cohort changes both seeds and

System	Successes	Rate (%)	95% Wilson interval	Drops	Model calls
Astra full	35/40	87.5	[73.9, 94.5]	3	101
Fine-tuned VLM, bare	30/40	75.0	[59.8, 85.8]	9	117
Rule VLM, bare	17/40	42.5	[28.5, 57.8]	12	126

Table 1. **Q1: latest native-image cube comparison.** Each system has 40 matched trials, with no service exclusions. Astra uses refitted waiting control and the original execution actor. The two VLM baselines use the shared student without these actors. Model calls total all 40 trials. This evaluation uses the original object/hand RGB pipeline, not the reconstructed images used for the separate semantic intervention.

Simulation object	Rule	Fine-tuned	Full
Cube, latest release	17/40	30/40	35/40
Object 2	TODO	TODO	TODO
Object 3	TODO	TODO	TODO
Object 4	TODO	TODO	TODO
Object 5	TODO	TODO	TODO

Table 2. **Q1: object coverage.** Only the cube row is measured. Further objects require recorded geometry, calibration, policy, goal definitions, and 40 matched trials per method. Object-specific students do not imply zero-shot transfer. No average is computed over unfinished rows.

System	Identity	Permuted	Masked
Astra full	32/40	32/40	0/39
Fine-tuned VLM, bare	30/40	16/40	3/40
Rule VLM, bare	23/40	23/40	0/40

Table 3. **Q1: sensitivity to semantic mapping.** Identity and permutation retain all 40 trials. Astra masking has one service exclusion. Its paired masking contrast uses 31/39 identity successes versus 0/39 masked successes. The local methods have no exclusions. This study uses the original Astra actors.

waiting weights, so Q2 provides the dedicated control comparison. The supplement retains the earlier factorial and shared-controller studies without pooling versions.

Remaining failures. All three latest Astra drops occur during unbound inspection, outside pending requests. One further trial binds the requested letter to the wrong color and stops, and one abstains before binding. No waiting-stage drop occurs in this native-image cohort. Pending-request drops do occur in the dedicated Q2 cohort. The three inspection failures motivate contact-stable evidence acquisition. Their proximity to an inspection command does not establish its causal role. Success among trials that reach correct binding is not an unconditional measure of student reliability.

The bare fine-tuned VLM has nine execution drops and one horizon failure. The bare rule VLM has twelve drops, ten false stops, and one horizon failure. Median call latencies are 4.35 seconds for Astra, 0.099 seconds for fine-tuning, and 1.10 seconds for the rule baseline. The timing audit verifies continued control through pending intervals and delayed application of replies. It does not establish real-time simulator throughput.

Visual-semantic intervention. We keep predictor input and lighting fixed while changing the upper-level image. Identity, one cyclic letter–color permutation, and letter masking are evaluated on 40 matched states per method. All three conditions use geometry-consistent reconstructed face images, including identity. Consequently, this is a controlled image benchmark rather than the untouched RGB main comparison.

Astra retains 32/40 successes after permutation, while fine-tuned success falls from 30/40 to 16/40 (Holm-adjusted $p = 0.0130$ across six planned contrasts). Rule success remains 23/40. Equal aggregate rates do not establish equivalence or identical trajectories. Masking removes almost all completion, supporting dependence on visible semantic evidence. Nine of eleven fine-tuned wrong-binding trials after permutation select the original letter–color association. This is consistent with reliance on learned associations, but does not identify an exclusive memorization mechanism. One cube and one permutation do not establish broad semantic generalization.

5.3. Q2: Control during agent deliberation

We compare four ways of acting while a semantic request is pending: continue the student proposal, interpolate toward it with fixed speed 0.15, learn that speed, and learn both speed and a bounded joint correction. Every condition uses the same frozen execution actor outside pending intervals. Astra, the student, visual pose predictor, stopping gate, and physical horizon are fixed.

The speed-only actor is trained with its waiting residual constrained to zero throughout fitting. It uses the same data, warm-start parameters, optimizer, sampling, and 2,400 updates as the full actor. Reproducing the full training run gives tensor-identical deployed weights, and the auxiliary evidence weights match across the two runs. Evidence heads from this fitting procedure are not deployed. Tests

Waiting policy	Success	%	Drops	Wait drops
Continue student	25/40	62.5	12	7
Fixed slowdown	30/40	75.0	4	4
Learned slowdown	28/40	70.0	8	1
Learned slowdown + correction	34/40	85.0	5	4

Table 4. **Q2: how should the hand act while Astra is thinking?** Each condition has 40 scheduled trials. All arms use the same frozen controller outside pending requests. Successes and drops use the common service-eligible panel. Wait drops combine startup and later pending intervals. All 40 trials per arm are service-eligible.

on held-out measured states verify identical non-pending actions across all conditions and exactly zero waiting residual for the speed-only model.

Continued execution succeeds in 25/40 trials, fixed slowing in 30/40, learned slowing in 28/40, and learned slowing with joint correction in 34/40 (Table 4). There are no service exclusions. The full actor has the highest observed success, but learning only the speed does not improve on fixed slowing. Holm-adjusted exact paired p-values for the three registered adjacent contrasts are 0.604, 0.804, and 0.539. This cohort does not resolve those component gains.

Total drops are twelve, four, eight, and five. The full actor reduces total drops relative to continued execution and learned slowing, but has four later-pending drops versus one for learned slowing. Fixed slowing has four startup drops and no later drops. Thus the best completion count does not coincide with the fewest drops or the fewest pending-stage failures. The supplement separates startup, later waiting, and execution outcomes. Non-pending weights are fixed, but the states and subsequent agent decisions reached after waiting can differ.

Trials use seeds 185501 and 185502 with reversed condition order for the second seed. Checkpoints are fixed before these outcomes. Historical training-version comparisons remain separate from this structural ablation.

Other component evidence. Earlier waiting–execution factorial tests do not establish a reliable interaction. Explicit controller-goal interventions also do not establish a benefit, and a separate learned execution-residual gate fails its development admission rule. These negative results and the matched-state diagnostic are retained in the supplement. The new waiting study changes neither the execution actor nor its goal input.

5.4. Q3: Initial planning and visual feedback

We compare the same Astra under two observation protocols. One receives the initial RGB observation and measured feedback, then commits to a complete plan containing one to six bounded actions. It receives no later semantic observation. Its last non-abstain skill can continue until the shared stopping gate or horizon terminates the trial. The other can use up to six calls with updated observations and history. Both retain continuous pose feedback to the student, the same full waiting and execution actors, and the same stopping rule.

Protocol	Success	%	Drops	Calls
One initial plan	6/39	15.4	0	40
Full feedback	33/39	84.6	5	120

Table 5. **Q3: initial plan versus continued feedback.** Each arm has 40 scheduled trials. The full-feedback condition is shared with Q2, rather than counted as another 40 raw trials. Calls include all raw episodes. One service-affected slot is excluded symmetrically. Different inference budgets are part of the protocol comparison.

The initial plan succeeds in 6/39 eligible trials, compared with 33/39 for continued feedback. Twenty-seven paired trials succeed only with feedback and none only with the initial plan (exact $p = 1.49 \times 10^{-8}$). Raw success is 6/40 versus 34/40. One initial-plan HTTP 503 timeout is excluded from both arms without replacement. Actual calls total 40 and 120.

The initial plan abstains in 28 eligible trials, of which 22 succeed with feedback. Among the 39 eligible feedback trials, 36 contain inspection, 32 first bind a target after inspection, and 31 successes use multiple calls. No executed wrong-to-correct binding transition is observed. These traces support the benefit of the full observation protocol, especially obtaining evidence before binding. They do not establish that every initial target was hidden or isolate fresh images from additional inference compute. Zero initial-plan drops accompany frequent abstention and do not imply a superior completing policy. A recorded example and the earlier original-controller cohort are retained in the supplement.

5.5. Q4: From simulation to a physical hand

Pose estimation and task completion. With the same frozen CNN, the released pose-goal policy reaches before dropping in 39/40 diagnostic trials, versus 35/40 for the latent student. These measure physical reach, not autonomous semantic success. A separate 160-trial student-adaptation study is retained in the supplement. It changes neither the predictor nor the student used in the main comparison.

[TODO: Insert the colleague-provided predictor study.] Compare independent translation and rotation errors, then 40 matched closed-loop trials per predictor with the student, agent, and controllers fixed. Any subsequent policy adaptation is a separate stage. An oracle-pose diagnostic can estimate remaining motor limitations but is




Figure 2. **Matched waiting and feedback studies.** Bars show autonomous semantic success and individual 95% Wilson intervals. Q2 has 40 eligible trials per condition. Q3 has 39 after one symmetric service exclusion. Its full-feedback arm reuses the same 40 raw trials as the full waiting controller, with one successful slot removed for the paired Q3 analysis. There are 200 unique raw trials, not 240. The feedback protocols have different inference budgets.

not deployable. Existing student training cannot establish a predictor improvement or a hardware advantage over ViserDex.

Physical-hand evaluation. **[TODO: Add hardware setup, object dimensions and masses, calibration, control frequency, per-object success, timing, and failures.]** Plan 40 trials per system and object across two sessions, with matched setup and independent orientation scoring. Synchronized video and request/action logs must retain failures. A hardware waiting-control comparison will test whether the simulated completion and contact trade-offs transfer.

6. Discussion and Limitations

The strongest evidence concerns continued semantic feedback. With the same motor controllers, later observations and decisions complete 33/39 eligible trials, compared with 6/39 for an initial plan. Many initial-plan abstentions become feedback successes. The measured effect belongs to the full protocol with more calls, not an equal-compute test of visual information alone.

The waiting ablation gives 34/40 successes for learned slowing with joint correction, compared with 25/40 for continued execution, 30/40 for fixed slowing, and 28/40 for learned slowing alone. The three registered adjacent contrasts remain unresolved. The full actor also has more later-pending drops than the speed-only actor. Lower teacher-action error and fewer total drops do not certify uniformly better contact stability. Outcomes depend on the states reached during waiting and subsequent semantic decisions.

Explicit controller-goal conditioning does not improve the matched goal intervention or restored-state diagnostic. A learned execution gate fails its development criterion and is not deployed. The latest native three-system cohort favors full Astra at 35/40, but its difference from fine-tuning remains unresolved. Earlier cohorts do not support a universal provider ranking. We retain these results and distinguish the native comparison from the new controller cohort.

The visual intervention uses reconstructed faces, one permutation, and a single cube. The native pipeline renders a Gaussian object with hand occlusion. Neither establishes real-camera robustness. The main baselines differ in controller access and inspection scheduling. Hosted model revisions introduce further replication limits. More objects, independent predictor measurements, and physical-hand trials remain open.

7. Conclusion

We presented a pose-mediated semantic reorientation system with continuous local control around asynchronous visual decisions. Completed cube experiments support continued feedback, expose sensitivity to visual-semantic remapping, and separate the roles of slowing and joint correction during inference. The waiting results show a favorable completion estimate together with unresolved component gains and distinct failure stages. Negative goal and execution ablations are preserved. Multi-object, predictor, and hardware studies will test how far these findings transfer.

References

[1] Arjun Bhardwaj, Maximum Wilder-Smith, Mayank Mittal, Vaishakh Patil, and Marco Hutter. ViserDex: Visual sim-to-real for robust dexterous in-hand reorientation. *arXiv preprint arXiv:2604.11138*, 2026. 1, 2

[2] Kevin Black, Manuel Y. Galliker, and Sergey Levine. Real-time execution of action chunking flow policies. *arXiv preprint arXiv:2506.07339*, 2025. 2

[3] Ning Chen, Yankai Fu, Junkai Zhao, Qianpu Sun, Guocai Yao, Pengwei Wang, Zhongyuan Wang, and Shanghang Zhang. LiMA: Bridging long-term imagination to real-time dexterous manipulation via asynchronous diffusion. *arXiv preprint arXiv:2609.28431*, 2026. 2

[4] Kailin Li, Puhao Li, Tengyu Liu, Yuyang Li, and Siyuan Huang. ManipTrans: Efficient dexterous bimanual manipulation transfer via residual learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 6991–7003, 2025. 2

[5] Sizhe Lester Li, Evan Kim, Xingjian Bai, Tong Zhao, Tao Pang, Max Simchowitz, and Vincent Sitzmann. Turning video models into generalist robot policies. *arXiv preprint arXiv:2605.27817*, 2026. 2

[6] Qwen Team. Qwen3-VL-4B-Instruct model card. `https://huggingface.co/Qwen/Qwen3-VL-4B-Instruct`, 2025. 4

[7] Stephane Ross, Geoffrey Gordon, and Drew Bagnell. A reduction of imitation learning and structured prediction to no-regret online learning. In *Proceedings of the Fourteenth International Conference on Artificial Intelligence and Statistics*, pages 627–635, 2011. 3

[8] Kohei Sendai, Maxime Alvarez, Tatsuya Matsushima, Yutaka Matsuo, and Yusuke Iwasawa. Leave no observation behind: Real-time correction for VLA action chunks. *arXiv preprint arXiv:2509.23224*, 2025. 2

[9] Michael Tschannen, Alexey Gritsenko, Xiao Wang, Muhammad Ferjad Naeem, Ibrahim Alabdulmohsin, Nikhil Parthasarathy, Talfan Evans, Lucas Beyer, Ye Xia, Basil Mustafa, Olivier Hénaff, Jeremiah Harmsen, Andreas Steiner, and Xiaohua Zhai. SigLIP 2: Multilingual vision-language encoders with improved semantic understanding, localization, and dense features. *arXiv preprint arXiv:2502.14786*, 2025. 4

[10] Jianwei Yang, Reuben Tan, Qianhui Wu, Ruijie Zheng, Baolin Peng, Yongyuan Liang, Yu Gu, Mu Cai, Seonghyeon Ye, Joel Jang, Yuquan Deng, and Jianfeng Gao. Magma: A foundation model for multimodal AI agents. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 14203–14214, 2025. 2

[11] Brian Zhu, Momen Khalil, E Harrison, Emanuele Poggi, Philipp Schmitt, Bernd Kast, Philine Meister, Pranav Atreya, Qiyang Li, Finn Ferchau, Cesar Colmenero, Yash Shahapurkar, Gokul Narayanan, Melih Erdogan, Kai Wurm, Georg von Wichert, Oier Mees, Eugen Solowjow, Andrew Wagenmaker, and Sergey Levine. Learning to act while waiting: RL finetuning of generalist robot policies under inference latency. *arXiv preprint arXiv:2608.23831*, 2026. 2

[12] Yixiang Zhu, Yonghao Chen, Jiaxiang Zou, Yusong Hu, and Xinyu Chen. DEFLECT: Temporal counterfactual preference learning for delay-robust asynchronous VLAs. *arXiv preprint arXiv:2605.19294*, 2026. 2

LLM Usage Statement

Generative AI tools assisted with research discussion, implementation, experiment orchestration, literature retrieval, data analysis, and manuscript drafting. Astra and Qwen3-VL are also components evaluated in the research. Numerical results in this draft are derived from recorded experiments. Unfinished experiments are explicitly marked TODO. The authors must verify the final text, references, code, and results and remain responsible for the submitted work.