

Project Requirement Document for Network File Sharing Server and Client

Docid	Language	Author	Subject	Page
<u>Proj/WIP/B2</u>	<u>EN</u>	<u>Mahima Bhardwaj</u>	<u>Linux System Programming</u>	<u>39</u>

Contents

1. Project Overview:	5
2. Objectives:	5
3. Features:	5
User Authentication:	5
Multi Client Support:	5
File Transfer:	5
Real Time Messaging:	5

Copyright © 2024 Mahima Bhardwaj

No part of this content can be reused without exclusive written permission from
bhardwajmahima81@gmail.com

Docid	Language	Author	Subject	Page
Proj/WIP/B2	En	Mahima	Linux System Programming	3

Comprehensive logging:	5
Cross Platform Compatibility:	5
5. Functional Requirements:	5
User Authentication:.....	5
File Transfer:.....	5
Message Exchange:	6
Multi-client Handling:.....	6
Logging and Error Handling:	6
6. Non-Functional Requirements:.....	6
Security:.....	6
Usability:	6
Reliability:	6
Performance:	6
Maintainability:.....	6
7. Technologies Used:	6
C++ Programming Language:.....	6
POSIX Sockets API:	6
Multi-threading:	6
Networking Protocols:.....	6
Standard Libraries:.....	6
Linux/Unix System Calls:.....	6
8. Project Phases:.....	7
Phase 1: Requirements Gathering and Analysis	7
Phase 2: System Design	7
Phase 3: Implementation	7
Phase 4: Testing	
Phase 5 Deployment.....	7
Phase 6: Maintenance and Support	7
Phase7: Documentation and Training.....	7
9. System Design:	8
a. Overview of the components.....	8

Docid	Language	Author	Subject	Page
Proj/WIP/B2	En	Mahima	Linux System Programming	3

b. Architecture Overview:	8
c. Data Flow Diagram:.....	9
d. Class Diagram:.....	9
3. Sequence Diagram:	4
Client Send Sequence:	4
File Send Sequence:.....	4
5. Server Flow Diagram:.....	5
6. Flow Diagram.....	6
7. Server Code:.....	7
8. Client Code:	8
9. :Bug Tracker	9
a. Bug 001	9
b. Bug 002:	:9
10. Main Reference:.....	10
11. Thanks Note:.....	11

Docid	Language	Author	Subject	Page
Proj/WIP/B2	En	Mahima	Linux System Programming	3

1. Project Overview:

This project implements a basic network file-sharing application using C++ with TCP sockets. The server can list available files, send files to the client, and receive files from the client. The client can request a file list, download files, and upload files to the server. Basic logging is implemented on the server side to track file transfers

2. Objectives:

Aim- Network File Sharing Over Server and Client

3. Features:

1> User authentication

The most common method where users provide a unique username and a password. The server checks these credentials against a database to verify the user.

2> Multi-Client Support

Concurrent Connections: The server can manage multiple client connections simultaneously, thanks to its multi-threaded architecture.

3>. File Transfer

Cross-Platform File Sharing: Clients can send files to the server from any supported platform. The server saves these files securely for further use.

Docid	Language	Author	Subject	Page
Proj/WIP/B2	En	Mahima	Linux System Programming	3

4> Real-Time Messaging

Instant Messaging: Clients can send real-time text messages to the server, which can be logged and reviewed later.

5> Comprehensive Logging

Timestamped Logs: All actions, including file transfers and messages, are logged with precise timestamps to ensure traceability.

6> Cross-Platform Compatibility

Operating System Independence: The project is compatible with both Windows and Linux environments, ensuring broad accessibility.

4. Functional Requirements:

1> User Authentication:

- The system should authenticate users based on a predefined username and password.
- The server verifies the credentials sent by the client and allows access only if they match the stored credentials.

2> File Transfer:

- The system should allow the client to send a file to the server. The file should be transferred in binary mode, and the server should save the received file with the correct filename.

3> Message Exchange:

- The system should allow the client to send textual messages to the server. The server should acknowledge the reception of the message.

4> Logging and Error Handling:

Copyright © 2024 Mahima Bhardwaj.
No part of this content can be reused without exclusive written permission from
bhardwajmahima81@gmail.com

Docid	Language	Author	Subject	Page
Proj/WIP/B2	En	Mahima	Linux System Programming	3

- The server should log connection attempts, file transfers, and any errors that occur during communication.

Non-Functional Requirements

1. Security:

- The system should use basic authentication to ensure that only authorized users can access the file transfer functionality. Sensitive data like usernames and passwords should ideally be encrypted, though this is not implemented in the given program.

2. Scalability:

- The server should be able to handle multiple clients simultaneously without performance degradation.

3. Reliability:

- The system should reliably handle file transfers, ensuring that data is not corrupted during transmission.

4. Performance:

- The file transfer and message exchange operations should be completed in a reasonable amount of time. The use of multi-threading ensures that the server can process multiple requests concurrently.

5. Usability:

- The client-side interface should be user-friendly, prompting the user for inputs like file paths, messages, and authentication credentials.

6. Maintainability:

- The code should be modular, with separate functions for handling file transfers, messages, and authentication. This ensures ease of maintenance and future enhancements.

Technologies Used

1. C++ Programming Language:

- The program is written in C++, utilizing features such as multi-threading, file handling, and socket programming.

2. POSIX Sockets API:

- The program uses the POSIX sockets API for creating and managing network connections, allowing communication between the server and clients.

3. Multi-threading:

Docid	Language	Author	Subject	Page
Proj/WIP/B2	En	Mahima	Linux System Programming	3

- The `std::thread` library is used for handling multiple client connections simultaneously on the server side.
- 4. **Networking Protocols:**
 - The program uses TCP/IP for reliable communication between the client and server, ensuring that all data is delivered accurately and in order.
- 5. **Standard Libraries:**
 - Libraries such as `<iostream>`, `<fstream>`, and `<cstring>` are used for input/output operations, file handling, and string manipulation.
- 6. **Linux/Unix System Calls:**
 - System calls like `socket()`, `bind()`, `listen()`, `accept()`, `recv()`, and `send()` are used to manage the network communication.

Requirement Gathering and Analysis

- **Objective:** Identify and document the functional and non-functional requirements.
- **Activities:**
 - Discuss and document the user needs (e.g., user authentication, file transfer, multi-client support).
 - Define the system's scope, goals, and objectives.
 - Identify key stakeholders and their expectations.
- **Deliverables:** Requirement Specification Document, Use Case Diagrams.

2. System Design

- **Objective:** Create a blueprint for how the system will be implemented.
- **Activities:**
 - **Architectural Design:** Define the overall architecture, including client-server communication, multi-threading, and data flow.
 - **Module Design:** Break down the system into modules (e.g., authentication module, file transfer module).
 - **Database Design:** (Optional) If the project scales, design a database schema for storing user credentials, logs, etc.
- **Deliverables:** System Architecture Diagram, Module Design Documents, Database Schema (if applicable).

3. Implementation

- **Objective:** Develop the software according to the design specifications.

Copyright © 2024 Mahima Bhardwaj.

No part of this content can be reused without exclusive written permission from
bhardwajmahima81@gmail.com

Docid	Language	Author	Subject	Page
Proj/WIP/B2	En	Mahima	Linux System Programming	3

- **Activities:**
 - Set up the development environment.
 - Code the client and server components.
 - Implement core functionalities like authentication, file transfer, and message handling.
 - Write unit tests for individual modules.
- **Deliverables:** Source Code, Unit Test Cases.

4. Testing

- **Objective:** Ensure that the system works as intended and meets the requirements.
- **Activities:**
 - **Unit Testing:** Test individual modules to ensure they work as expected.
 - **Integration Testing:** Test the interaction between different modules (e.g., authentication followed by file transfer).
 - **System Testing:** Perform end-to-end testing of the entire system, including stress testing with multiple clients.
 - **User Acceptance Testing (UAT):** Verify that the system meets user expectations.
- **Deliverables:** Test Plan, Test Cases, Bug Reports, Test Summary Report.

5. Deployment

- **Objective:** Deploy the system in a real-world environment.
- **Activities:**
 - Set up the server environment for hosting the application.
 - Install necessary software dependencies and configurations.
 - Deploy the client application to end users.
 - Ensure security measures are in place (e.g., firewall, encryption).
- **Deliverables:** Deployment Plan, Installed and Configured System, Deployment Documentation.

6. Maintenance and Support

- **Objective:** Ensure the system remains functional, secure, and up-to-date.
- **Activities:**
 - Monitor the system for performance issues or bugs.
 - Provide technical support and updates as needed.

Copyright © 2024 Mahima Bhardwaj.

No part of this content can be reused without exclusive written permission from
bhardwajmahima81@gmail.com

Docid	Language	Author	Subject	Page
Proj/WIP/B2	En	Mahima	Linux System Programming	3

- Implement patches or updates to address security vulnerabilities.
 - Gather feedback for future improvements.
- **Deliverables:** Maintenance Logs, Update Patches, User Support Documentation.

7. Documentation and Training

- **Objective:** Provide comprehensive documentation and training for users and developers.
- **Activities:**
 - Create user manuals and technical documentation.
 - Provide training sessions for end users and administrators.
 - Document code and system architecture for future reference.
- **Deliverables:** User Manuals, Technical Documentation, Training Materials.

5. System Design:

a. Overview of the components

1. Architecture Overview

- **Client-Server Model:** The system follows a client-server architecture where multiple clients can connect to a central server to upload, download, and list files.

2. Data Flow Diagram

1. Client Authentication:

- **The client sends a password to the server for authentication.**
- **The server verifies the password and responds with an acknowledgment.**

Copyright © 2024 Mahima Bhardwaj.

No part of this content can be reused without exclusive written permission from
bhardwajmahima81@gmail.com

Docid	Language	Author	Subject	Page
Proj/WIP/B2	En	Mahima	Linux System Programming	3

Low-Level Design (LLD)

1. Detailed Component Design

1. Client Application:

- **Modules:**
 - **Network Module:** Handles socket creation, connection, and communication.
 - **Authentication Module:** Manages sending and receiving authentication data.
 - **File Transfer Module:** Handles file upload and download operations.
 - **User Interface Module:** Provides command-line interface for user interaction.

2. Server Application:

- **Modules:**
 - **Network Module:** Handles socket creation, binding, listening, and accepting connections.
 - **Authentication Module:** Verifies client credentials.
 - **File Management Module:** Manages file listings, uploads, and downloads.
 - **Security Module:** Manages SSL/TLS setup and encryption.

Docid	Language	Author	Subject	Page
Proj/WIP/B2	En	Mahima	Linux System Programming	3

2. Class Diagrams

1. Client Classes:

○ Methods:

- connectToServer()
- authenticate()
- sendFile()
- sendMessage()

2. NetworkManager Class:

○ Methods:

- createSocket()
- connect()
- sendData()
- receiveData()

1. Server Class:

○ Methods:

- start()
- acceptClient()
- handleClient()
- authenticateClient()

Docid	Language	Author	Subject	Page
Proj/WIP/B2	En	Mahima	Linux System Programming	3

- **receiveFile()**

- **sendAck()**

2. NetworkManager Class:

○ Methods:

- **createSocket()**

- **bindSocket()**

- **listenForConnections()**

- **acceptConnection()**

- **sendData()**

- **receiveData()**

Sequence Diagrams:

1. Client Authentication Sequence:

- **Client -> Server: connectToServer()**
- **Client -> Server: authenticate(username, password)**
- **Server -> Client: authenticationResult()**

2. File Send Sequence:

- **Client -> Server: sendFile(filename)**
- **Server -> Client: sendAck()**

Docid	Language	Author	Subject	Page
Proj/WIP/B2	En	Mahima	Linux System Programming	3

The server application diagram is designed to represent the different modules and their interactions within the server application. Each module has a specific role in handling client requests, managing files, and ensuring secure communication.

CLIENT- This is the main class that orchestrates the operations of the client application. It utilizes other modules to establish a connection to the server, authenticate, transfer files.

Docid	Language	Author	Subject	Page
Proj/WIP/B2	En	Mahima	Linux System Programming	3


The Client class uses the NetworkManager to send authentication credentials (e.g., password) to the server.

The server verifies the credentials and responds. The NetworkManager receives this response and passes it back to the Client.

Server Flow Diagram

Docid	Language	Author	Subject	Page
Proj/WIP/B2	En	Mahima	Linux System Programming	3

Complete Server Flow Diagram:




Docid	Language	Author	Subject	Page
Proj/WIP/B2	En	Mahima	Linux System Programming	3


Flow Diagram For Client Architecture

Docid	Language	Author	Subject	Page
Proj/WIP/B2	En	Mahima	Linux System Programming	3

Complete Flow- Diagram of Client Connection:



Docid	Language	Author	Subject	Page
Proj/WIP/B2	En	Mahima	Linux System Programming	3



Docid	Language	Author	Subject	Page
Proj/WIP/B2	En	Mahima	Linux System Programming	3

Make File

Define compiler and flags

CXX = g++

CXXFLAGS = -std=c++11 -Wall -Wextra

Define targets and their dependencies

all: client server

client: client.o

\$(CXX) \$(CXXFLAGS) -o client client.o

server: server.o

\$(CXX) \$(CXXFLAGS) -o server server.o

Compile the client source file

client.o: client.cpp

\$(CXX) \$(CXXFLAGS) -c client.cpp

Compile the server source file

server.o: server.cpp

\$(CXX) \$(CXXFLAGS) -c server.cpp

Clean up build files

clean:

rm -f *.o client server

.PHONY: all clean

Copyright © 2024 Mahima Bhardwaj.

No part of this content can be reused without exclusive written permission from
bhardwajmahima81@gmail.com

Docid	Language	Author	Subject	Page
Proj/WIP/B2	En	Mahima	Linux System Programming	3

SERVER CODE

```
#include <iostream>
#include <fstream>
#include <cstring>
#include <thread>
#include <vector>
#include <sys/socket.h>
#include <netinet/in.h>
#include <arpa/inet.h>
#include <unistd.h>

const int PORT = 8086;
const int BUFFER_SIZE = 1024;
const std::string USERNAME = "admin"; // Example username
const std::string PASSWORD = "password"; // Example password

void handleClient(int clientSocket, std::string clientIP) {
    char buffer[BUFFER_SIZE];
    int bytesRead;
```

Docid	Language	Author	Subject	Page
Proj/WIP/B2	En	Mahima	Linux System Programming	3

```

// Authenticate client
std::string receivedUsername;
std::string receivedPassword;

// Receive username
bytesRead = recv(clientSocket, buffer, BUFFER_SIZE, 0);
if (bytesRead <= 0) {
    std::cerr << "[" << clientIP << "]" Error receiving
username." << std::endl;
    close(clientSocket);
    return;
}
buffer[bytesRead] = '\0';
receivedUsername = buffer;

// Receive password
bytesRead = recv(clientSocket, buffer, BUFFER_SIZE, 0);
if (bytesRead <= 0) {
    std::cerr << "[" << clientIP << "]" Error receiving
password." << std::endl;
    close(clientSocket);
    return;
}
buffer[bytesRead] = '\0';
receivedPassword = buffer;

```

Copyright © 2024 Mahima Bhardwaj.

No part of this content can be reused without exclusive written permission from
bhardwajmahima81@gmail.com

Docid	Language	Author	Subject	Page
Proj/WIP/B2	En	Mahima	Linux System Programming	3

```

// Check credentials
if (receivedUsername != USERNAME || receivedPassword
!= PASSWORD) {
    std::cerr << "[" << clientIP << "] Authentication failed." <<
std::endl;
    close(clientSocket);
    return;
}

// Notify successful authentication
send(clientSocket, "AUTH_OK", strlen("AUTH_OK"), 0);

// Receive filename
bytesRead = recv(clientSocket, buffer, BUFFER_SIZE, 0);
if (bytesRead <= 0) {
    std::cerr << "[" << clientIP << "] Error receiving filename."
<< std::endl;
    close(clientSocket);
    return;
}
buffer[bytesRead] = '\0';
std::string filename(buffer); // Store the filename received
from the client

```

Docid	Language	Author	Subject	Page
Proj/WIP/B2	En	Mahima	Linux System Programming	3

```

// Log the filename and start receiving the file
std::cout << "[" << clientIP << "]" Receiving file (" <<
filename << ") from client..." << std::endl;

while ((bytesRead = recv(clientSocket, buffer,
BUFFER_SIZE, 0)) > 0) {
    buffer[bytesRead] = '\0';

    if (strcmp(buffer, "FILE_START") == 0) {
        std::ofstream outFile(filename, std::ios::binary);
        if (!outFile) {
            std::cerr << "Error opening file for writing." <<
std::endl;
            close(clientSocket);
            return;
        }
        std::cout << "[" << clientIP << "]" Writing to file: " <<
filename << std::endl;
        while ((bytesRead = recv(clientSocket, buffer,
BUFFER_SIZE, 0)) > 0) {
            if (strcmp(buffer, "FILE_END") == 0) break;
            outFile.write(buffer, bytesRead);
        }
        outFile.close();
    }
}

```

Docid	Language	Author	Subject	Page
Proj/WIP/B2	En	Mahima	Linux System Programming	3

```

        std::cout << "[" << clientIP << "] File (" << filename <<
        ") received successfully." << std::endl;
        send(clientSocket, "ACK: File received", strlen("ACK:
        File received"), 0);
    } else {
        std::cout << "[" << clientIP << "] Message from client: "
        << buffer << std::endl;
        send(clientSocket, "ACK: Message received",
        strlen("ACK: Message received"), 0);
    }
}

if (bytesRead < 0) {
    std::cerr << "[" << clientIP << "] Error receiving data." <<
    std::endl;
}

close(clientSocket);
}

int main() {
    int serverSocket, clientSocket;
    struct sockaddr_in serverAddr, clientAddr;
    socklen_t addrSize = sizeof(clientAddr);
    std::vector<std::thread> threads;

```

Copyright © 2024 Mahima Bhardwaj.

No part of this content can be reused without exclusive written permission from
bhardwajmahima81@gmail.com

Docid	Language	Author	Subject	Page
Proj/WIP/B2	En	Mahima	Linux System Programming	3

```
// Create socket
serverSocket = socket(AF_INET, SOCK_STREAM, 0);
if (serverSocket < 0) {
    std::cerr << "Socket creation error." << std::endl;
    return -1;
}

// Bind socket
serverAddr.sin_family = AF_INET;
serverAddr.sin_addr.s_addr = INADDR_ANY;
serverAddr.sin_port = htons(PORT);
if (bind(serverSocket, (struct sockaddr*)&serverAddr,
sizeof(serverAddr)) < 0) {
    std::cerr << "Bind error." << std::endl;
    return -1;
}

// Listen for connections
if (listen(serverSocket, 5) < 0) {
    std::cerr << "Listen error." << std::endl;
    return -1;
}
```

Docid	Language	Author	Subject	Page
Proj/WIP/B2	En	Mahima	Linux System Programming	3

```

std::cout << "Server listening on port " << PORT <<
std::endl;

while (true) {
    clientSocket = accept(serverSocket, (struct
sockaddr*)&clientAddr, &addrSize);
    if (clientSocket < 0) {
        std::cerr << "Accept error." << std::endl;
        continue;
    }

    std::string clientIP = inet_ntoa(clientAddr.sin_addr);
    std::cout << "Client connected from IP: " << clientIP <<
std::endl;

    // Handle client in a new thread
    threads.emplace_back(handleClient, clientSocket,
clientIP);
}

// Join threads (this will never actually happen in this
example)
for (auto& t : threads) {
    t.join();
}

```

Copyright © 2024 Mahima Bhardwaj.

No part of this content can be reused without exclusive written permission from
bhardwajmahima81@gmail.com

Docid	Language	Author	Subject	Page
Proj/WIP/B2	En	Mahima	Linux System Programming	3

```
    close(serverSocket);  
    return 0;  
}
```

CLIENT CODE

```
#include <iostream>  
#include <fstream>  
#include <cstring>  
#include <sys/socket.h>  
#include <netinet/in.h>  
#include <arpa/inet.h>  
#include <unistd.h>  
  
const int PORT = 8086;  
const int BUFFER_SIZE = 1024;  
  
void sendFile(int socket, const std::string& filePath) {  
    std::ifstream file(filePath, std::ios::binary);  
    if (!file) {  
        std::cerr << "Error opening file." << std::endl;  
        return;  
    }  
}
```

Docid	Language	Author	Subject	Page
Proj/WIP/B2	En	Mahima	Linux System Programming	3

```

// Extract the filename from the file path
std::string filename =
filePath.substr(filePath.find_last_of("\\") + 1);

// Send the filename
send(socket, filename.c_str(), filename.size(), 0);
usleep(100); // Small delay to ensure filename is sent
before FILE_START

char buffer[BUFFER_SIZE];
// Notify server about file transfer
send(socket, "FILE_START", strlen("FILE_START"), 0);

// Send file content
while (file.read(buffer, BUFFER_SIZE)) {
    send(socket, buffer, file.gcount(), 0);
}
send(socket, buffer, file.gcount(), 0); // Send remaining
bytes

// Notify server end of file transfer
send(socket, "FILE_END", strlen("FILE_END"), 0);

// Receive acknowledgment

```

Copyright © 2024 Mahima Bhardwaj.

No part of this content can be reused without exclusive written permission from
bhardwajmahima81@gmail.com

Docid	Language	Author	Subject	Page
Proj/WIP/B2	En	Mahima	Linux System Programming	3

```

int bytesRead = recv(socket, buffer, BUFFER_SIZE, 0);
if (bytesRead > 0) {
    buffer[bytesRead] = '\0';
    std::cout << "Server: " << buffer << std::endl;
}

std::cout << "File sent successfully." << std::endl;
}

void sendMessage(int socket, const std::string& message) {
    send(socket, message.c_str(), message.size(), 0);
    std::cout << "Message sent: " << message << std::endl;

    char buffer[BUFFER_SIZE];
    int bytesRead = recv(socket, buffer, BUFFER_SIZE, 0);
    if (bytesRead > 0) {
        buffer[bytesRead] = '\0';
        std::cout << "Server: " << buffer << std::endl;
    }
}

int main() {
    int socketFd;
    struct sockaddr_in serverAddr;
    std::string input;

```

Copyright © 2024 Mahima Bhardwaj.

No part of this content can be reused without exclusive written permission from
bhardwajmahima81@gmail.com

Docid	Language	Author	Subject	Page
Proj/WIP/B2	En	Mahima	Linux System Programming	3

```

// Create socket
socketFd = socket(AF_INET, SOCK_STREAM, 0);
if (socketFd < 0) {
    std::cerr << "Socket creation error." << std::endl;
    return -1;
}

// Connect to server
serverAddr.sin_family = AF_INET;
serverAddr.sin_port = htons(PORT);
if (inet_pton(AF_INET, "127.0.0.1", &serverAddr.sin_addr)
<= 0) { // Use appropriate IP address
    std::cerr << "Invalid address/Address not supported." <<
std::endl;
    return -1;
}

if (connect(socketFd, (struct sockaddr*)&serverAddr,
sizeof(serverAddr)) < 0) {
    std::cerr << "Connection error." << std::endl;
    return -1;
}

// Authentication

```

Copyright © 2024 Mahima Bhardwaj.

No part of this content can be reused without exclusive written permission from
bhardwajmahima81@gmail.com

Docid	Language	Author	Subject	Page
Proj/WIP/B2	En	Mahima	Linux System Programming	3

```

std::string username, password;
std::cout << "Enter username: ";
std::getline(std::cin, username);
std::cout << "Enter password: ";
std::getline(std::cin, password);

// Send username and password
send(socketFd, username.c_str(), username.size(), 0);
usleep(100); // Small delay to ensure username is sent
before password
send(socketFd, password.c_str(), password.size(), 0);

// Receive authentication response
char buffer[BUFFER_SIZE];
int bytesRead = recv(socketFd, buffer, BUFFER_SIZE, 0);
if (bytesRead > 0) {
    buffer[bytesRead] = '\0';
    if (strcmp(buffer, "AUTH_OK") != 0) {
        std::cerr << "Authentication failed." << std::endl;
        close(socketFd);
        return -1;
    }
} else {
    std::cerr << "Error receiving authentication response." <<
std::endl;

```

Copyright © 2024 Mahima Bhardwaj.

No part of this content can be reused without exclusive written permission from
bhardwajmahima81@gmail.com

Docid	Language	Author	Subject	Page
Proj/WIP/B2	En	Mahima	Linux System Programming	3

```

    close(socketFd);
    return -1;
}

// Loop for sending messages or files
while (true) {
    std::cout << "Enter 'file' to send a file, 'message' to send
a message, or 'exit' to quit: ";
    std::cin >> input;
    std::cin.ignore(); // Ignore the newline character after
input

    if (input == "file") {
        std::string filePath;
        std::cout << "Enter file path: ";
        std::getline(std::cin, filePath);
        sendFile(socketFd, filePath);
    } else if (input == "message") {
        std::string message;
        std::cout << "Enter message: ";
        std::getline(std::cin, message);
        sendMessage(socketFd, message);
    } else if (input == "exit") {
        std::cout << "Exiting..." << std::endl;
        break;
    }
}

```


Docid	Language	Author	Subject	Page
Proj/WIP/B2	En	Mahima	Linux System Programming	3

```
    } else {  
        std::cerr << "Invalid option." << std::endl;  
    }  
}  
  
close(socketFd);  
return 0;  
}
```

Docid	Language	Author	Subject	Page
Proj/WIP/B2	En	Mahima	Linux System Programming	3

Bug Tracker Report

`Project: Network File Sharing Server & Client`

1. Bug Details

Bug ID: 001

Title: Bind Error: Server Fails to Bind to Port * Date: 2024-08-11 * Status: Closed * Priority: High * Severity: Critical * Assigned to: To be assigned # Description * The server application occasionally fails to bind to the specified port, resulting in a "Bind error" message. This issue prevents the server from starting and accepting connections, leading to downtime and unavailability of the network file-sharing service. Steps to Reproduce * Start the server application. * Observe the server output for a "Bind error" message. Expected Behavior * The server should bind to the specified port and start listening for incoming connections without any errors. Actual Behavior * The server sometimes fails to bind to the port, displaying a "Bind error" message and preventing the application from starting. 3 Error Log # Example error message: Bind error. # Fix Description * Port Availability Check: Implement a check to ensure the port is available before attempting to bind. * Retry Mechanism: Implement a retry mechanism that attempts to bind to the port multiple times before failing. * Error Logging: Improve error logging to provide more detailed information about the bind error, helping to diagnose the issue more effectively.

Bug ID: 002

BUG- 1.Server Delayed Response

Reported by: Mahima Bhardwaj, Diksha kumari ,Sunny * Date: [8-8-24] * Status: Open * Severity: High * Priority: High # Description: * The server sometimes takes an unexpectedly long time to respond after a file transfer is initiated by the client. This delay may affect the user experience, especially in real-time applications where quick acknowledgment is critical.

Steps to Reproduce:

- Start the server by running ./server.
- Start the client by running ./client.
- Send a file from the client to the server.
- Observe the delay before the server acknowledges the file transfer completion.
- Observe the output in the client terminal. # Expected Result:

Docid	Language	Author	Subject	Page
Proj/WIP/B2	En	Mahima	Linux System Programming	3

- The server should respond immediately after the file has been completely received.

Actual Behaviour

- The server delays its response by a few seconds, leading to potential performance issues. # Root Cause Analysis
- The cause of the delay is currently under investigation.
Solution Implemented:
- Not yet implemented.
Testing:
- No testing has been conducted as the issue is still open.
- The client only displays "Available files:" with no files listed underneath.

2. Bug Report: Server Not Exiting Properly

Bug ID: 003 * Date: [7-8-24] * Status: Open * Severity: High * Priority: High # Title: Server Not Exiting Properly Description:

- The server does not exit gracefully upon receiving termination signals or when it encounters an error. This issue can lead to resource leaks and potential instability in the system.

Steps to Reproduce:

- Start the server application.
- Attempt to terminate the server using a signal (e.g., Ctrl+C) or after a fatal error.
- Observe that the server does not exit cleanly.

Expected Behavior:

- The server should release all resources and exit gracefully upon receiving a termination signal or after encountering a critical error.

Actual Behavior:

- The server either hangs or leaves resources (like sockets) open, causing instability.
Root Cause Analysis:
- The issue appears to be related to improper handling of termination signals and resource cleanup. Solution Implemented:
- Not yet implemented. # Testing:

Copyright © 2024 Mahima Bhardwaj.

No part of this content can be reused without exclusive written permission from
bhardwajmahima81@gmail.com

Docid	Language	Author	Subject	Page
Proj/WIP/B2	En	Mahima	Linux System Programming	3

References for the Network File Sharing Server & Client Project

Special Thanks To ShweatanK sir . This Project Has Been Made Under his Guidance and Training.

- **C++ Standard Library Documentation**
- **POSIX Socket Programming**
- **Logging Library**
- **Encryption and Security**
- **Tutorials & Examples**
- **C++ Socket Programming Example**

Docid	Language	Author	Subject	Page
Proj/WIP/B2	En	Mahima	Linux System Programming	3

**Documentation Created By:-
. MAHIMA BHARDWAJ**