



# SQL (Structured Query Language)

*Day- 4*

Dimple Waghela and Dhvani Parekh

## Proprietary Information of Fractal Analytics Inc.

This document contains proprietary and confidential information of Fractal Analytics and subsidiaries (Fractal) and shall not be reproduced or transferred to other documents, disclosed to others or used for any purpose other than that for which it is furnished, without the prior written consent of Fractal. It shall be returned to Fractal upon request.



# String & Date Functions

# STRING Functions

The following functions perform an operation on a string input value and return a string or numeric value:

ASCII	NCHAR	STR
CHAR	REPLACE	SPACE
LEFT	REPLICATE	SUBSTRING
LEN	REVERSE	UPPER
LOWER	RIGHT	
LTRIM	RTRIM	

# STRING Functions

- `Select ASCII('A');`
- `Select CHAR(6);`
- `Select CHARINDEX('C','ABCD',1);`
- `Select LEFT('SQL Session',3);`
- `Select RIGHT('SQL Session',7);`
- `Select LEN('SQL Session');`
- `Select LTRIM(' SQL Session');`
- `Select RTRIM('SQL Session ');`
- `Select LOWER('SQL Session');`
- `Select UPPER('SQL Session');`
- `Select SPACE(10)+ UPPER('SQL Session');` -- Concat is using + operator
- `Select REPLACE('ABCD','BC','FG');`
- `Select REPLICATE('ABCD',2);`
- `Select REVERSE('ABCD');`
- `Select STR(65.45,2,1);`--converts float, len,decimal optional
- `Select SUBSTRING('ABCD',1,2);`

# DATE Functions

The following functions perform an operation on a string input value and return a string or numeric value:

Function	Description
GETDATE()	Returns the current date and time
DATEPART()	Returns a single part of a date/time
DATEADD()	Adds or subtracts a specified time interval from a date
DATEDIFF()	Returns the time between two dates
CONVERT()	Displays date/time data in different formats

# TOP Clause

- The SQL **TOP** clause is used to fetch a TOP N number or X percent records from a table.

## Syntax:

```
SELECT TOP number|percent column_name(s) FROM  
table_name WHERE [condition];
```

## Example:

- `SELECT TOP 3 * FROM CUSTOMERS;`

# SQL Alias

- SQL Aliases are defined for columns and tables. Basically aliases is created to make the column selected more readable.

## **Aliases is more useful when**

- There are more than one tables involved in a query,
- Functions are used in the query,
- The column names are big or not readable,
- More than one columns are combined together

# SQL Alias-Example

## Example:

```
SELECT CustomerName AS Customer, ContactName AS  
[Contact Person]  
FROM Customers;
```



# Displaying Data From Multiple Tables-Joins

# SQL Joins

- SQL Joins are used to relate information in different tables.
- A Join condition is a part of the sql query that retrieves rows from two or more tables.
- A SQL Join condition is used in the SQL WHERE Clause of select, update, delete statements.

# Types of Joins

JOINS in SQL Server can be classified as follows:

- INNER JOIN
- OUTER JOIN
- Non Eqijoins
- Self Join
- CROSS JOIN

# The Syntax for joining two tables

```
SELECT col1, col2, col3...  
FROM table_name1, table_name2  
WHERE table_name1.col2 = table_name2.col1;
```

# INNER JOIN

- Inner joins return rows only when there is at least one row from both tables that matches the join condition.
- Inner joins eliminate the rows that do not match with a row from the other table.

# INNER -Example

```
SELECT orders1.ordernumber,customers.City  
FROM Orders1  
INNER JOIN Customers  
ON  
    orders1.Customernumber=customers.Customernumber;
```

# LEFT OUTER JOIN

- Left Outer joins return all rows from the left table referenced with a left outer join and matching rows from other table.
- Unmatched records will be NULL.

# LEFT OUTER JOIN-Example

```
SELECT customers.CustomerNumber,  
       orders1.Amount,items.Description  
FROM customers  
LEFT OUTER JOIN orders1  
ON  
(customers.CustomerNumber=orders1.CustomerNumber)
```



# RIGHT OUTER JOIN

- Right Outer joins return all rows from the right table referenced with a right outer join and matching rows from other table.
- Unmatched records will be NULL.

# RIGHT OUTER JOIN-Example

```
SELECT customers.CustomerNumber, orders1.Amount  
FROM orders1  
RIGHT OUTER JOIN customers  
ON  
    customers.CustomerNumber=orders1.CustomerNumber
```

# FULL OUTER JOIN

- Full Outer joins return all rows from both the tables. Unmatched records will be NULL.

## Example:

```
SELECT customers.CustomerNumber+2, orders1.Amount  
FROM customers FULL OUTER JOIN orders1 ON  
customers.CustomerNumber+2=orders1.CustomerNumber
```

# Non Equijoins Joins

- **SQL Non equijoins:** It is a Sql join condition which makes use of some comparison operator other than the equal sign like  $>$ ,  $<$ ,  $>=$ ,  $<=$
- **SELECT** name, age  
**FROM** employee  
**WHERE** salary  $\neq$  30000

# Self Joins

## Example SQL Self Join:

```
SELECT a.sales_person_id, a.name, a.manager_id,  
       b.sales_person_id, b.name  
FROM sales_person a, sales_person b  
WHERE a.manager_id = b.sales_person_id;
```

# CROSS JOIN

- In cross joins, each row from first table joins with all the rows of another table.
- If there are  $m$  rows from Table1 and  $n$  rows from Table2, then result set of these tables will have  $m*n$  rows.

# CROSS JOIN Example

```
SELECT Zip, FirstName, amount  
FROM Orders1  
CROSS JOIN Customers
```

# Set Operators



# Set Operators

According to SQL Standard there are following

Set operator types:

- UNION
- UNION ALL
- INTERSECT
- EXCEPT (Minus in Oracle)

# UNION Operator

- The UNION operator is used to combine the result-set of two or more SELECT statements.
- Notice that each SELECT statement within the UNION must have the same number of columns.
- The columns must also have similar data types. Also, the columns in each SELECT statement must be in the same order.

# UNION Example

**Union cities from table1 and table2**

```
SELECT city FROM table1
```

```
UNION
```

```
SELECT city FROM table2;
```

# Union ALL Operator

- Union all allows all duplicate values in the output set.

## **Example:**

```
SELECT city FROM table1
```

```
UNION ALL
```

```
SELECT city FROM table2;
```

# Intersect Operator

- Intersect returns only these rows, which are in both tables.

## **Example :**

```
SELECT city FROM table1
```

```
INTERSECT
```

```
SELECT city FROM table2;
```

# Except Operator (Minus)

- Except returns unique rows that are returned by the first query but are NOT returned by the second query.

## **Example:**

```
SELECT city FROM table1
```

```
EXCEPT
```

```
SELECT city FROM table2
```

# SubQueries

# Subquery

- Subquery or Inner query or Nested query is a query in a query.
- A subquery is usually added in the WHERE Clause of the Sql statement.
- Subqueries can be used with the following sql statements along with the comparison operators like =, <, >, >=, <= etc.

SELECT,INSERT,UPDATE,DELETE



# Subquery

A subquery can be used in the places of a query are

- Within the list of columns in the SELECT statement
- With the FROM clause
- With the WHERE clause
- With the HAVING clause
- With the GROUP BY clause.

# Subquery Example

```
SELECT firstname, City  
FROM customers  
WHERE city IN ('Plano', 'Reo');
```

```
SELECT customernumber, lastname  
FROM customers  
WHERE state NOT IN ('CA');
```

# Subquery Example

```
SELECT FirstName, Zip, State  
FROM Customers  
WHERE city IN (SELECT city  
FROM Customers  
WHERE city= 'Plano');
```

# Correlated subquery

- A query is called correlated subquery when both the inner query and the outer query are interdependent.
- For every row processed by the inner query, the outer query is processed as well.
- The inner query depends on the outer query before it can be processed.

# Correlated-Example

```
SELECT zip FROM customers
WHERE customernumber =
(SELECT CustomerNumber from customers where city
='Reo')
```

# Correlated-Example

```
SELECT last_name, salary  
FROM employee  
WHERE salary > (SELECT salary FROM employee  
WHERE last_name = 'Able');
```

```
SELECT * FROM employee WHERE salary > (SELECT  
Min(salary) FROM employees)
```

# Other Database Objects

# Views

- In SQL, a view is a virtual table based on the result-set of an SQL statement.
- A view contains rows and columns, just like a real table. The fields in a view are fields from one or more real tables in the database.
- You can add SQL functions, WHERE, and JOIN statements to a view and present the data as if the data were coming from one single table.



# Types of Views -Simple View

- When we create a view on a single table, it is called simple view.
- In simple view we can insert, update, delete data. We can only insert data in simple view if we have primary key and all not null fields in the view.

# Simple View-Example

## Syntax:

```
CREATE VIEW view_name AS  
  SELECT column_name(s)  
  FROM table_name  
  WHERE condition
```

## Example :

```
CREATE VIEW mycus AS  
SELECT * FROM customers
```

# Types of Views -Complex View

- When we create a view on more than one table, it is called complex view.

## Example:

Create VIEW vw\_Employee\_Personal\_Info

As

Select e.Emp\_ID,

e.Emp\_Name,e.Emp\_Designation,p.DOB,p.Mobile

From Employee\_Test123 e INNER JOIN Personal\_Info p

On e.Emp\_Name = p. Emp\_Name;

Select \* from vw\_employee\_personal\_info

# Thank You

# Thank You

Fortune 500 companies recognize analytics as a competitive differentiator to **understand customers** and make **better decisions**.

We deliver insight, impact and innovation to them through **predictive analytics** and **visual story-telling**.

**[fractalanalytics.com](http://fractalanalytics.com)**

United States | Canada | United Kingdom | Italy | Switzerland | Singapore | UAE | India | China

