



SQL (Structured Query Language)

Day- 3

Dimple Waghela and Dhvani Parekh

Proprietary Information of Fractal Analytics Inc.

This document contains proprietary and confidential information of Fractal Analytics and subsidiaries (Fractal) and shall not be reproduced or transferred to other documents, disclosed to others or used for any purpose other than that for which it is furnished, without the prior written consent of Fractal. It shall be returned to Fractal upon request.



SQL Data Types

Data Types

- In SQL Server, each column, local variable, expression, and parameter has a related data type. A data type is an attribute that specifies the type of data that the object can hold: integer data, character data, monetary data, date and time data, binary strings, and so on.

WHERE Clause in SELECT

- The SQL **WHERE** clause is used to specify a condition while fetching the data from single table or joining with multiple table.
- The WHERE clause not only used in SELECT statement, but it is also used in UPDATE, DELETE statement etc. which we would examine in subsequent chapters.

WHERE Clause Example

Syntax:

```
SELECT column1, column2, columnN FROM table_name  
WHERE [condition]
```

Example:

```
SELECT ID, NAME, SALARY FROM CUSTOMERS  
WHERE SALARY > 2000;
```

SQL Operators

Comparison Conditions

Operator	Meaning
=	Equal to
>	Greater than
>=	Greater than or equal to
<	Less than
<=	Less than or equal to
<>	Not equal to
BETWEEN ...AND...	Between two values (inclusive)
IN (set)	Match any of a list of values
LIKE	Match a character pattern
IS NULL	Is a null value

LIKE Operator

- The SQL **LIKE** clause is used to compare a value to similar values using wildcard operators. There are two wildcards used in conjunction with the LIKE operator:
- The percent sign (%)
- The underscore (_)
- The percent sign represents zero, one, or multiple characters.
- The underscore represents a single number or character. The symbols can be used in combinations.

LIKE Operator

Syntax:

SELECT FROM table_name WHERE column LIKE
'XXXX%' (or)

SELECT FROM table_name WHERE column LIKE
'%XXXX%' (or)

SELECT FROM table_name WHERE column LIKE
'XXXX_' (or)

SELECT FROM table_name WHERE column LIKE
'_XXXX' (or)

SELECT FROM table_name WHERE column LIKE
'_XXXX_'

LIKE Operator-Example

Statement	Description
WHERE SALARY LIKE '200%'	Finds any values that start with 200
WHERE SALARY LIKE '%200%'	Finds any values that have 200 in any position
WHERE SALARY LIKE '_00%'	Finds any values that have 00 in the second and third positions
WHERE SALARY LIKE '2_%_ %'	Finds any values that start with 2 and are at least 3 characters in length
WHERE SALARY LIKE '%2'	Finds any values that end with 2
WHERE SALARY LIKE '_2%3'	Finds any values that have a 2 in the second position and end with a 3
WHERE SALARY LIKE '2___3'	Finds any values in a five-digit number that start with 2 and end with 3

BETWEEN ... AND Operator

- The operator BETWEEN and AND, are used to compare data for a range of values.

Example:

```
SELECT customer, product  
FROM orders  
WHERE quantity BETWEEN '1' AND '3';
```

IN Operator:

- The IN operator is used when you want to compare a column with more than one value. It is similar to an OR condition.

Example:

```
SELECT * FROM orders  
where quantity  
IN ('1' , '3');
```

IS Null Operator

```
SELECT ProductID, Name, Color  
FROM Production.Product  
WHERE Color IS NULL
```

Logical Conditions

Operator	Meaning
AND	Returns TRUE if <i>both</i> component conditions are true
OR	Returns TRUE if <i>either</i> component condition is true
NOT	Returns TRUE if the following condition is false

AND Operator-Example:

- `SELECT ID, NAME, SALARY FROM CUSTOMERS
WHERE SALARY > 2000 AND age < 25;`

OR Operator-Example:

- `SELECT ID, NAME, SALARY FROM CUSTOMERS
WHERE SALARY > 2000 OR age < 25;`

NOT Operator-Example

```
SELECT ID, NAME, SALARY FROM CUSTOMERS  
WHERE NOT SALARY = 2000;
```

TOP Clause

- The SQL **TOP** clause is used to fetch a TOP N number or X percent records from a table.

Syntax:

```
SELECT TOP number|percent column_name(s) FROM  
table_name WHERE [condition];
```

Example:

- `SELECT TOP 3 * FROM CUSTOMERS;`

ORDER BY Clause

- The SQL **ORDER BY** clause is used to sort the data in ascending or descending order, based on one or more columns. Some database sorts query results in ascending order by default.

Syntax:

```
SELECT column-list FROM table_name [WHERE  
condition] [ORDER BY column1, column2, .. columnN]  
[ASC | DESC];
```

ORDER BY Example

- `SELECT * FROM CUSTOMERS ORDER BY NAME, SALARY;`
- `SELECT * FROM CUSTOMERS ORDER BY NAME DESC;`

Distinct Keyword

- The SQL **DISTINCT** keyword is used in conjunction with SELECT statement to eliminate all the duplicate records and fetching only unique records.
- There may be a situation when you have multiple duplicate records in a table. While fetching such records, it makes more sense to fetch only unique records instead of fetching duplicate records.

Distinct Keyword

Syntax:

```
SELECT DISTINCT column1, column2,.....columnN FROM  
table_name WHERE [condition];
```

Example:

```
SELECT SALARY FROM CUSTOMERS ORDER BY  
SALARY;
```

```
SELECT DISTINCT SALARY FROM CUSTOMERS  
ORDER BY SALARY;
```

Aggregate Functions OR Group Functions

Types of Group Functions

- AVG
- COUNT
- MAX
- MIN
- SUM



COUNT ()-Example

- If you want the total number of employees in all the department, the query would take the form:

Example:

```
SELECT COUNT (*) FROM employee;
```

```
SELECT COUNT (*) FROM employee  
WHERE dept = 'Electronics';
```

COUNT, MAX, MIN, AVG, SUM, DISTINCT

- `SELECT MAX (salary) FROM employee;`
- `SELECT MIN (salary) FROM employee;`
- `SELECT AVG (salary) FROM employee;`
- `SELECT SUM (salary) FROM employee;`
- `SELECT COUNT (DISTINCT name) FROM employee;`
- `SELECT DISTINCT dept FROM employee;`

Group By Clause

- The SQL **GROUP BY** clause is used in collaboration with the SELECT statement to arrange identical data into groups.
- The GROUP BY clause follows the WHERE clause in a SELECT statement.

Syntax:

```
SELECT column1, column2 FROM table_name WHERE [  
conditions ] GROUP BY column1, column2
```

Group By-Example

- `SELECT NAME, SUM(SALARY) FROM CUSTOMERS
GROUP BY NAME;`
- `SELECT NAME, SUM(SALARY) FROM CUSTOMERS
GROUP BY NAME;`

HAVING Clause

- Having clause is used to filter data based on the group functions.
- This is similar to WHERE condition but is used with group functions.
- Group functions cannot be used in WHERE Clause but can be used in HAVING clause.

HAVING Example

```
SELECT dept, SUM (salary)
FROM employee
GROUP BY dept
HAVING SUM (salary) > 25000
```

Thank You

Thank You

Fortune 500 companies recognize analytics as a competitive differentiator to **understand customers** and make **better decisions**.

We deliver insight, impact and innovation to them through **predictive analytics** and **visual story-telling**.

fractalanalytics.com

United States | Canada | United Kingdom | Italy | Switzerland | Singapore | UAE | India | China

