


HTML - Tables

The HTML tables allow web authors to arrange data like text, images, links, other tables, etc. into rows and columns of cells.

The HTML tables are created using the **<table>** tag in which the **<tr>** tag is used to create table rows and **<td>** tag is used to create data cells. The elements under **<td>** are regular and left aligned by default

Example

```
<!DOCTYPE html>
<html>
  <head>
    <title>HTML Tables</title>
  </head>
  <body>
    <table border = "1">
      <tr>
        <td>Row 1, Column 1</td>
        <td>Row 1, Column 2</td>
      </tr>
      <tr>
        <td>Row 2, Column 1</td>
        <td>Row 2, Column 2</td>
      </tr>
    </table>
  </body>
</html>
```




Here, the **border** is an attribute of **<table>** tag and it is used to put a border across all the cells. If do not need a border, then can use border = "0".

Table Heading

Table heading can be defined using **<th>** tag. This tag will be put to replace **<td>** tag, which is used to represent actual data cell. Normally will put the top row as table heading as shown below, otherwise we can use **<th>** element in any row. Headings, which are defined in **<th>** tag are **centered** and **bold** by default.

Example

```
<!DOCTYPE html>
<html>
  <head>
    <title>HTML Table Header</title>
  </head>
  <body>
    <table border = "1">
      <tr>
        <th>Name</th>
        <th>Salary</th>
      </tr>
      <tr>
        <td>Ramesh Raman</td>
        <td>5000</td>
      </tr>
      <tr>
        <td>Shabbir Hussein</td>
        <td>7000</td>
      </tr>
    </table>
  </body>
</html>
```



```

        <td>Ramesh Raman</td>
        <td>5000</td>
    </tr>
    <tr>
        <td>Shabbir Hussein</td>
        <td>7000</td>
    </tr>
</table>
</body>
</html>

```

Cellpadding and Cellspacing Attributes

There are two attributes called *cellpadding* and *cellspacing* which will be used to adjust the white space in the table cells. The **cellspacing** attribute defines space between table cells, while **cellpadding** represents the distance between cell borders and the content within a cell.


Example

```

<!DOCTYPE html>
<html>
  <head>
    <title>HTML Table Cellpadding</title>
  </head>
  <body>
    <table border = "1" cellpadding = "5"
      cellspacing = "5">

      <tr>
        <th>Name</th>
        <th>Salary</th>
      </tr>
      <tr>
        <td>Ramesh Raman</td>
        <td>5000</td>
      </tr>
      <tr>
        <td>Shabbir Hussein</td>
        <td>7000</td>
      </tr>
    </table>
  </body>
</html>

```



Colspan and Rowspan Attributes:

colspan attribute is used to merge two or more columns into a single column. Similar way will use **rowspan** if we want to merge two or more rows.

Example

```


<!DOCTYPE html>
<html>
  <head>
    <title>HTML Table Colspan/Rowspan</title>
  </head>
  <body>

```

```

<table border = "1">
  <tr>
    <th>Column 1</th>
    <th>Column 2</th>
    <th>Column 3</th>
  </tr>
  <tr>
    <td rowspan = "2">Row 1 Cell 1</td>
    <td>Row 1 Cell 2</td>
    <td>Row 1 Cell 3</td>
  </tr>
  <tr>
    <td>Row 2 Cell 2</td>
    <td>Row 2 Cell 3</td>
  </tr>
  <tr>
    <td colspan = "3">Row 3 Cell 1</td>
  </tr>
</table>
</body>
</html>

```



Tables Backgrounds

to set table background using one of the following two ways –

- **bgcolor** attribute –can set background color for whole table or just for one cell.
- **background** attribute –can set background image for whole table or just for one cell.

to set border color also using **bordercolor** attribute.


Note – The *bgcolor*, *background*, and *bordercolor* attributes deprecated in HTML5. Do not use these attributes.

Example

```

<!DOCTYPE html>
<html>
  <head>
    <title>HTML Table Background</title>
  </head>
  <body>
    <table border = "1" bordercolor = "green"
      bgcolor = "yellow">
      <tr>
        <th>Column 1</th>
        <th>Column 2</th>
        <th>Column 3</th>
      </tr>
      <tr>
        <td rowspan = "2">Row 1 Cell 1</td>
        <td>Row 1 Cell 2</td>
        <td>Row 1 Cell 3</td>
      </tr>
      <tr>
        <td>Row 2 Cell 2</td>
        <td>Row 2 Cell 3</td>
      </tr>
    </table>
  </body>
</html>

```



```

</tr>
<tr>
  <td colspan = "3">Row 3 Cell 1</td>
</tr>
</table>
</body>
</html>

```

Here is an example of using **background** attribute. Here we will use an image available test.png

```

<!DOCTYPE html>
<html>
  <head>
    <title>HTML Table Background</title>
  </head>
  <body>
    <table border = "1" bordercolor = "green" background = "test.png">
      <tr>
        <th>Column 1</th>
        <th>Column 2</th>
        <th>Column 3</th>
      </tr>
      <tr>
        <td rowspan = "2">Row 1 Cell 1</td>
        <td>Row 1 Cell 2</td><td>Row 1 Cell 3</td>
      </tr>
      <tr>
        <td>Row 2 Cell 2</td>
        <td>Row 2 Cell 3</td>
      </tr>
      <tr>
        <td colspan = "3">Row 3 Cell 1</td>
      </tr>
    </table>
  </body>
</html>

```




Table Height and Width

Set table width and height using **width** and **height** attributes to specify table width or height in terms of pixels or in terms of percentage of available screen area.

Example

```

<!DOCTYPE html>
<html>
  <head><title>HTML Table Width/Height</title></head>
  <body>
    <table border = "1" width = "400" height = "150">
      <tr>
        <td>Row 1, Column 1</td>
        <td>Row 1, Column 2</td>
      </tr><tr>
        <td>Row 2, Column 1</td>
        <td>Row 2, Column 2</td>
      </tr></table></body></html>

```





Table Caption

The **caption** tag will serve as a title or explanation for the table and it shows up at the top of the table. This tag is deprecated in newer version of HTML/XHTML.

Example

```
<!DOCTYPE html>
<html>
  <head>
    <title>HTML Table Caption</title>
  </head>
  <body>
    <table border = "1" width = "100%">
    <caption>This is the caption</caption>
    <tr>
      <td>row 1, column 1</td><td>row 1, columnn 2</td>
    </tr>
    <tr>
      <td>row 2, column 1</td><td>row 2, columnn 2</td>
    </tr>
  </table>
</body>
</html>
```



The screenshot shows a web browser window with a table. Above the table, the text 'This is the caption' is displayed. The table has two rows and two columns. The first row contains 'row 1, column 1' and 'row 1, columnn 2'. The second row contains 'row 2, column 1' and 'row 2, columnn 2'.


Nested Tables

we can use one table inside another table. Not only tables can use almost all the tags inside table data tag <td>.

Example

Following is the example of using another table and other tags inside a table cell.

```
<!DOCTYPE html>
<html>
  <head>
    <title>HTML Table</title>
  </head>
  <body>
    <table border = "1" width = "100%">
    <tr> <td>
    <table border = "1" width = "100%">
      <tr>
        <th>Name</th>
        <th>Salary</th>
      </tr>
      <tr>
        <td>Ramesh Raman</td>
        <td>5000</td>
      </tr>
      <tr>
        <td>Shabbir Hussein</td>
        <td>7000</td>
      </tr>
    </table>
    </td>
  </tr>
</table>
</body>
</html>
```



The screenshot shows a web browser window with a table. The table has one row and one column. Inside the cell of the table, there is another table. The inner table has three rows and two columns. The first row contains the headers 'Name' and 'Salary'. The second row contains 'Ramesh Raman' and '5000'. The third row contains 'Shabbir Hussein' and '7000'.

HTML - Lists

HTML offers web authors three ways for specifying lists of information. All lists must contain one or more list elements. Lists may contain –


- **** – An unordered list. This will list items using plain bullets.
- **** – An ordered list. This will use different schemes of numbers to list items.
- **<dl>** – A definition list. This arranges the items in the same way as they are arranged in a dictionary.

HTML Unordered Lists

An unordered list is a collection of related items that have no special order or sequence. This list is created by using HTML **** tag. Each item in the list is marked with a bullet.

Example

```
<!DOCTYPE html>
<html>
  <head>
    <title>HTML Unordered List</title>
  </head>
  <body>
    <ul>
      <li>Beetroot</li>
      <li>Ginger</li>
      <li>Potato</li>
      <li>Radish</li>
    </ul>
  </body>
</html>
```



The type Attribute


we can use **type** attribute for **** tag to specify the type of bullet like. By default, it is a disc. Following are the possible options –

```
<ul type = "square">
<ul type = "disc">
<ul type = "circle">
```

Example

Following is an example where we used **<ul type = "square">**


```
<!DOCTYPE html>
<html>
  <head>
    <title>HTML Unordered List</title>
  </head>
  <body>
    <ul type = "square">
      <li>Beetroot</li>
      <li>Ginger</li>
      <li>Potato</li>
      <li>Radish</li>
    </ul>
  </body> </html>
```



Example

Following is an example where we used `<ul type = "disc">` –


```
<!DOCTYPE html>
<html>
  <head>
    <title>HTML Unordered List</title>
  </head>
  <body>
    <ul type = "disc">
      <li>Beetroot</li>
      <li>Ginger</li>
      <li>Potato</li>
      <li>Radish</li>
    </ul>
  </body>
</html>
```



Example

Following is an example where we used `<ul type = "circle">` –

```
<!DOCTYPE html>
<html>
  <head>
    <title>HTML Unordered List</title>
  </head>
  <body>
    <ul type = "circle">
      <li>Beetroot</li>
      <li>Ginger</li>
      <li>Potato</li>
      <li>Radish</li>
    </ul>
  </body>
</html>
```




HTML Ordered Lists

If it required to put items in a numbered list instead of bulleted, then HTML ordered list will be used. This list is created by using `<ol>` tag. The numbering starts at one and is incremented by one for each successive ordered list element tagged with `<li>`.

Example

```
<!DOCTYPE html>
<html>

  <head>
    <title>HTML Ordered List</title>
  </head>
  <body>
    <ol>
      <li>Beetroot</li>
      <li>Ginger</li>
      <li>Potato</li>
      <li>Radish</li>
    </ol>
  </body>
</html>
```



The type Attribute


we can use **type** attribute for `<ol>` tag to specify the type of numbering like. By default, it is a number. Following are the possible options –

```
<ol type = "1"> - Default-Case Numerals.  
<ol type = "I"> - Upper-Case Numerals.  
<ol type = "i"> - Lower-Case Numerals.  
<ol type = "A"> - Upper-Case Letters.  
<ol type = "a"> - Lower-Case Letters.
```

Example

Following is an example where we used `<ol type = "1">`


```
<!DOCTYPE html>  
<html>  
  <head>  
    <title>HTML Ordered List</title>  
  </head>  
  <body>  
    <ol type = "1">  
      <li>Beetroot</li>  
      <li>Ginger</li>  
      <li>Potato</li>  
      <li>Radish</li>  
    </ol>  
  </body>  
</html>
```



Example

Following is an example where we used `<ol type = "I">`


```
<!DOCTYPE html>  
<html>  
  <head>  
    <title>HTML Ordered List</title>  
  </head>  
  <body>  
    <ol type = "I">  
      <li>Beetroot</li>  
      <li>Ginger</li>  
      <li>Potato</li>  
      <li>Radish</li>  
    </ol>  
  </body>  
</html>
```



Example

Following is an example where we used `<ol type = "i">`

```
<!DOCTYPE html>  
<html>  
  <head>  
    <title>HTML Ordered List</title>  
  </head>  
  <body>
```




```

<ol type = "i">
  <li>Beetroot</li>
  <li>Ginger</li>
  <li>Potato</li>
  <li>Radish</li>
</ol>
</body>
</html>

```


Example

Following is an example where we used `<ol type = "A" >`

```

<!DOCTYPE html>
<html>
  <head>
    <title>HTML Ordered List</title>
  </head>
  <body>
    <ol type = "A">
      <li>Beetroot</li>
      <li>Ginger</li>
      <li>Potato</li>
      <li>Radish</li>
    </ol>
  </body>
</html>

```




Example

Following is an example where we used `<ol type = "a">`

```

<!DOCTYPE html>
<html>
  <head>
    <title>HTML Ordered List</title>
  </head>
  <body>
    <ol type = "a">
      <li>Beetroot</li>
      <li>Ginger</li>
      <li>Potato</li>
      <li>Radish</li>
    </ol>
  </body>
</html>

```



The start Attribute

we can use **start** attribute for `<ol>` tag to specify the starting point of numbering. Following are the possible options –

```


<ol type = "1" start = "4"> - Numerals starts with 4.
<ol type = "I" start = "4"> - Numerals starts with IV.
<ol type = "i" start = "4"> - Numerals starts with iv.
<ol type = "a" start = "4"> - Letters starts with d.
<ol type = "A" start = "4"> - Letters starts with D.

```

Example

Following is an example where we used `<ol type = "i" start = "4" >`

```
<!DOCTYPE html>
<html>
  <head>
    <title>HTML Ordered List</title>
  </head>
  <body>
    <ol type = "i" start = "4">
      <li>Beetroot</li>
      <li>Ginger</li>
      <li>Potato</li>
      <li>Radish</li>
    </ol>
  </body>
</html>
```



HTML Definition Lists

HTML and XHTML supports a list style which is called **definition lists** where entries are listed like in a dictionary or encyclopedia. The definition list is the ideal way to present a glossary, list of terms, or other name/value list.

Definition List makes use of following three tags.

- `<dl>` – Defines the start of the list
- `<dt>` – A term
- `<dd>` – Term definition
- `</dl>` – Defines the end of the list

Example

```
<!DOCTYPE html>
<html>
  <head>
    <title>HTML Definition List</title>
  </head>
  <body>
    <dl>
      <dt><b>HTML</b></dt>
      <dd>This stands for Hyper Text Markup Language</dd>
      <dt><b>HTTP</b></dt>
      <dd>This stands for Hyper Text Transfer Protocol</dd>
    </dl>
  </body>
</html>
```

